

STAN-TONE 15ET02 ORANGE

Version Number 1.6 Revision Date 05/20/2016

Page 1 of 17 Print Date 05/21/2016

SAFETY DATA SHEET

STAN-TONE 15ET02 ORANGE

Section 1. Identification

GHS product identifier STAN-TONE 15ET02 ORANGE

Chemical name Mixture **CAS** number Mixture Other means of identification FO00000654 **Product type** liquid

Relevant identified uses of the substance or mixture and uses advised against

Product use Industrial applications. Plastics.

POLYONE CORPORATION Supplier's details

1675 Navarre Road SW, Massillon,

Ohio USA 44646

1 330 837 8679

Emergency telephone number (with hours of operation)

CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).

Section 2. Hazards identification

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. After handling, always wash hands thoroughly with soap and water.

OSHA/HCS status This material is considered hazardous by the OSHA Hazard

Communication Standard (29 CFR 1910.1200).

Classification of the substance or

mixture

CARCINOGENICITY - Category 1A

GHS label elements



STAN-TONE 15ET02 ORANGE

Version Number 1.6 Page 2 of 17 Revision Date 05/20/2016 Print Date 05/21/2016

Hazard pictograms

Signal word : Danger

Hazard statements : May cause cancer.

Precautionary statements

General : Not applicable.

Prevention: Obtain special instructions before use. Do not handle until all safety

precautions have been read and understood. Use personal protective

equipment as required.

Response: IF exposed or concerned: Get medical attention.

Storage : Store in a well-ventilated place.

Disposal : Dispose of contents and container in accordance with all local,

regional, national and international regulations.

Supplemental label elements : None known. **Hazards not otherwise classified** : None known.

Section 3. Composition/information on ingredients

Substance/mixture: MixtureChemical name: MixtureOther means of identification: FO00000654

CAS number/other identifiers

Ingredient name	%	CAS number
Molybdate orange (Lead chromate pigment)	30 - 60	12656-85-8
Antimony trioxide	1 - 5	1309-64-4

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.



STAN-TONE 15ET02 ORANGE

Version Number 1.6 Revision Date 05/20/2016 Page 3 of 17 Print Date 05/21/2016

Section 4. First aid measures

Description of necessary first aid measures

Eye contact: Immediately flush eyes with plenty of water, occasionally lifting the

upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.

Inhalation : Remove victim to fresh air and keep at rest in a position comfortable

for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie,

belt or waistband.

Skin contact: Flush contaminated skin with plenty of water. Remove contaminated

clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean

shoes thoroughly before reuse.

Ingestion: Wash out mouth with water. Remove dentures if any. Remove victim

to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing

such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects

Eye contact: No known significant effects or critical hazards.Inhalation: No known significant effects or critical hazards.Skin contact: No known significant effects or critical hazards.Ingestion: No known significant effects or critical hazards.

Over-exposure signs/symptoms

Eye contact : No specific data.



STAN-TONE 15ET02 ORANGE

Version Number 1.6 Page 4 of 17 Revision Date 05/20/2016 Print Date 05/21/2016

Inhalation: No specific data.Skin contact: No specific data.Ingestion: No specific data.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : Treat symptomatically. Contact poison treatment specialist

immediately if large quantities have been ingested or inhaled.

Specific treatments : No specific treatment.

Protection of first-aiders : No action shall be taken involving any personal risk or without

suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media : In case of fire, use water spray (fog), foam, dry chemical or CO₂.

Unsuitable extinguishing media : None known.

Specific hazards arising from the: In a fire or if heated, a pressure increase will occur and the container may burst.

Hazardous thermal : Decomposition products may include the following materials: sulfur oxides metal oxide/oxides

Special protective actions for fire- : Promp

fighters

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any

personal risk or without suitable training.

Special protective equipment for fire-fighters

: Fire-fighters should wear appropriate protective equipment and selfcontained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel : No action shall be taken involving any personal risk or without



STAN-TONE 15ET02 ORANGE

Version Number 1.6 Revision Date 05/20/2016

For emergency responders

Page 5 of 17 Print Date 05/21/2016

unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

suitable training. Evacuate surrounding areas. Keep unnecessary and

If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See

also the information in "For non-emergency personnel".

Avoid dispersal of spilled material and runoff and contact with soil, **Environmental precautions**

> waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil

or air).

Methods and materials for containment and cleaning up

Small spill Stop leak if without risk. Move containers from spill area. Dilute with

> water and mop up if water-soluble. Alternatively, or if waterinsoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal

contractor.

Large spill Stop leak if without risk. Move containers from spill area. Approach

> release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with noncombustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency

contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Put on appropriate personal protective equipment (see Section 8). **Protective measures**

> Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse



STAN-TONE 15ET02 ORANGE

Version Number 1.6 Revision Date 05/20/2016 Page 6 of 17 Print Date 05/21/2016

Advice on general occupational hygiene

container.

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store in a well-ventilated place. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
Molybdate orange (Lead chromate	OSHA PEL (1993-06-30) expressed as Mo
pigment)	PEL: Permissible Exposure Level 15 mg/m3 Form: Total dust
	OSHA PEL (2006-11-27) expressed as Cr
	PEL: Permissible Exposure Level 0.005 mg/m3
	OSHA PEL Z2 (2006-11-27)
	Ceiling, is a a limit indicating the maximum concentration of a
	chemical substances in the breathing zone that should not be exceeded.
	0.001 mg/m3
	NIOSH REL (2010-09-01) expressed as Cr
	Time Weighted Average (TWA) 0.0002 mg/m3
	Time Weighted Average (TWA) 0.5 mg/m3
	OSHA PEL 1989 (1989-03-01) Calculated as CrO3
	Ceiling, is a a limit indicating the maximum concentration of a
	chemical substances in the breathing zone that should not be exceeded.
	0.1 mg/m3
	OSHA PEL 1989 (1989-03-01) expressed as Pb
	PEL: Permissible Exposure Level 0.075 mg/m3
	OSHA PEL 1989 (1989-03-01) expressed as Mo
	PEL: Permissible Exposure Level 10 mg/m3 Form: Total dust
	OSHA PEL 1989 (1989-03-01) expressed as Cr
	PEL: Permissible Exposure Level 0.5 mg/m3



STAN-TONE 15ET02 ORANGE

Version Number 1.6 Revision Date 05/20/2016

Skin protection

Hand protection

Page 7 of 17 Print Date 05/21/2016

	ACGIH TLV (1995-05-23) expressed as Pb TLV-TWA: Threshold Limit Value - Time weighted average PEL: Permissible Exposure Level 0.05 mg/m3 ACGIH TLV (2001-02-22) expressed as Mo TLV-TWA: Threshold Limit Value - Time weighted average PEL: Permissible Exposure Level 10 mg/m3 Form: Inhalable fraction TLV-TWA: Threshold Limit Value - Time weighted average PEL: Permissible Exposure Level 3 mg/m3 Form: Respirable fraction
Antimony trioxide	OSHA PEL (1993-06-30) expressed as Sb PEL: Permissible Exposure Level 0.5 mg/m3 NIOSH REL (1994-06-01) expressed as Sb Time Weighted Average (TWA) 0.5 mg/m3 OSHA PEL 1989 (1989-03-01) expressed as Sb PEL: Permissible Exposure Level 0.5 mg/m3 ACGIH TLV (1994-09-01)
Appropriate engineering controls :	enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.
Environmental exposure controls :	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
<u>Individual protection measures</u>	
Hygiene measures :	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection :	

Chemical-resistant, impervious gloves complying with an approved



STAN-TONE 15ET02 ORANGE

Version Number 1.6 Revision Date 05/20/2016 Page 8 of 17 Print Date 05/21/2016

standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Body protection: Personal protective equipment for the body should be selected based

on the task being performed and the risks involved and should be

approved by a specialist before handling this product.

Other skin protection : Appropriate footwear and any additional skin protection measures

should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this

product.

Respiratory protection : Use a properly fitted, air-purifying or air-fed respirator complying

with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits

of the selected respirator.

Section 9. Physical and chemical properties

Appearance

Physical state liquid [Paste.] Color **ORANGE** Not available. Odor **Odor threshold** Not available. Not available. Hq Not available. **Melting point** Not available. **Boiling point** Flash point Not available. **Burning time** Not available. **Burning rate** Not available. **Evaporation rate** Not available. Flammability (solid, gas) Not available.

Lower and upper explosive : Lower: Not available. (flammable) limits : Upper: Not available.

Vapor pressure

Vapor density

Relative density

Solubility

Solubility in water

Partition coefficient: n
Partition coefficient: n
Not available.

Not available.

Not available.

Not available.



STAN-TONE 15ET02 ORANGE

Version Number 1.6 Page 9 of 17 Revision Date 05/20/2016 Print Date 05/21/2016

octanol/water

Auto-ignition temperature: Not available.Decomposition temperature: Not available.SADT: Not available.

Viscosity : Dynamic: Not available.

Kinematic: Not available.

Section 10. Stability and reactivity

Reactivity: No specific test data related to reactivity available for this product or

its ingredients.

Chemical stability : Stable under recommended storage and handling conditions (see

Section 7).

Possibility of hazardous reactions: Under normal conditions of storage and use, hazardous reactions will

not occur.

Conditions to avoid : Keep away from extreme heat and oxidizing agents.

Incompatible materials : Keep away from strong acids.

Oxidizer.

Hazardous decomposition : Under normal conditions of storage and use, hazardous decomposition

products should not be produced.

Section 11. Toxicological information

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Information on toxicological effects

Acute toxicity

products

Product/ingredient name	Result	Species	Dose	Exposure
Antimony trioxide				
	LD50 Oral	Rat	34,600 mg/kg	-
	LD50 Oral	Rat	34,000 mg/kg	-

Conclusion/Summary: Mixture.Not fully tested.

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Antimony trioxide	Eyes - Mild	Rabbit			-
-	irritant				

Conclusion/Summary

Skin : Mixture.Not fully tested.



STAN-TONE 15ET02 ORANGE

Version Number 1.6 Page 10 of 17 Revision Date 05/20/2016 Print Date 05/21/2016

Eyes : Mixture.Not fully tested. **Respiratory** : Mixture.Not fully tested.

Sensitization

Conclusion/Summary

Skin: Mixture.Not fully tested.Respiratory: Mixture.Not fully tested.

Mutagenicity

Conclusion/Summary : Mixture.Not fully tested.

Carcinogenicity

Conclusion/Summary : Mixture.Not fully tested.

Classification

Product/ingredient	OSHA	IARC	NTP
name			
Molybdate orange (Lead	+	1	Known to be a human carcinogen.Reasonably
chromate pigment)			anticipated to be a human carcinogen.
Antimony trioxide		2B	

Reproductive toxicity

Conclusion/Summary: Mixture. Not fully tested.

Teratogenicity

Conclusion/Summary : Mixture.Not fully tested.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

Information on the likely routes of :

Not available.

exposure

Potential acute health effects

Eye contact : No known significant effects or critical hazards.

10/17



STAN-TONE 15ET02 ORANGE

Version Number 1.6 Page 11 of 17 Revision Date 05/20/2016 Print Date 05/21/2016

Inhalation: No known significant effects or critical hazards.Skin contact: No known significant effects or critical hazards.Ingestion: No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact: No specific data.Inhalation: No specific data.Skin contact: No specific data.Ingestion: No specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate effects : Not available.
Potential delayed effects : Not available.

Long term exposure

Potential immediate effects : Not available.
Potential delayed effects : Not available.

Potential chronic health effects

Conclusion/Summary : Mixture. Not fully tested.

General : No known significant effects or critical hazards.

Carcinogenicity: May cause cancer. Risk of cancer depends on duration and level of

exposure.

Mutagenicity: No known significant effects or critical hazards.Teratogenicity: No known significant effects or critical hazards.Developmental effects: No known significant effects or critical hazards.Fertility effects: No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Not available.

Section 12. Ecological information



STAN-TONE 15ET02 ORANGE

Version Number 1.6 Page 12 of 17 Revision Date 05/20/2016 Print Date 05/21/2016

Toxicity

Product/ingredient name	Result	Species	Exposure
Antimony trioxide			
	Acute LC50 > 530 mg/l Fresh	Fish - Fish	96 h
	water		
	Acute LC50 > 1,000,000 μg/l	Fish - Fish	96 h
	Marine water		
	Acute EC50 423,450 µg/l Fresh	Aquatic invertebrates.	48 h
	water	Daphnia	
	Acute EC50 560 mg/l Fresh water	Aquatic invertebrates.	48 h
		Crustaceans	
	Acute EC50 730 µg/l Fresh water	Aquatic plants - Algae	72 h
	Acute EC50 760 μg/l Fresh water	Aquatic plants - Algae	96 h
	Acute EC50 740 µg/l Fresh water	Aquatic plants - Algae	96 h
	Acute NOEC 200 µg/l Fresh water	Aquatic plants - Algae	4 d

Conclusion/Summary : Not available.

Persistence and degradability

Conclusion/Summary : Not available.

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
Molybdate orange (Lead		3,600.00	high
chromate pigment)			

Mobility in soil

Soil/water partition coefficient

: Not available.

(KOC)

Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the



STAN-TONE 15ET02 ORANGE

Version Number 1.6 Revision Date 05/20/2016 Page 13 of 17 Print Date 05/21/2016

requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

United States - RCRA Acute hazardous waste "P" List: Not listed

United States - RCRA Toxic hazardous waste "U" List: Not listed

Section 14. Transport information

U.S. DOT Classification : Not regulated for transportation.

ICAO/IATA : Consult mode specific transport rules

IMO/IMDG (maritime) : Consult mode specific transport rules

Section 15. Regulatory information

U.S. Federal regulations

United States - TSCA 12(b) - Chemical export notification: The following components are listed: Molybdate orange (Lead chromate pigment)

United States - TSCA 4(a) - Final Test Rules: Not listed
United States - TSCA 4(a) - ITC Priority list: Not listed
United States - TSCA 4(a) - Proposed test rules: Not listed
United States - TSCA 4(f) - Priority risk review: Not listed
United States - TSCA 5(a)2 - Final significant new use rules: Not

listed

United States - TSCA 5(a)2 - Proposed significant new use rules:

Listed Molybdate orange (Lead chromate pigment)

United States - TSCA 5(e) - Substances consent order: Not listed

United States - TSCA 6 - Final risk management: Listed

Molybdate orange (Lead chromate pigment)

United States - TSCA 6 - Proposed risk management: Not listed United States - TSCA 8(a) - Chemical risk rules: Not listed United States - TSCA 8(a) - Dioxin/Furane precusor: Not listed United States - TSCA 8(a) - Chemical Data Reporting (CDR): Not



STAN-TONE 15ET02 ORANGE

Version Number 1.6 Revision Date 05/20/2016 Page 14 of 17 Print Date 05/21/2016

determined

United States - TSCA 8(a) - Preliminary assessment report

(PAIR): Not listed

United States - TSCA 8(c) - Significant adverse reaction (SAR):

Not listed

United States - TSCA 8(d) - Health and safety studies: Not listed United States - EPA Clean water act (CWA) section 307 - Priority pollutants: Listed Molybdate orange (Lead chromate pigment)

Antimony trioxide

United States - EPA Clean water act (CWA) section 311 -

Hazardous substances: Listed

United States - EPA Clean air act (CAA) section 112 - Accidental

release prevention - Flammable substances: Not listed

United States - EPA Clean air act (CAA) section 112 - Accidental

release prevention - Toxic substances: Not listed

United States - Department of commerce - Precursor chemical:

Not listed

Clean Air Act Section 112(b)

Hazardous Air Pollutants (HAPs)

Clean Air Act Section 602 Class I

Substances

Clean Air Act Section 602 Class II

Substances

DEA List I Chemicals (Precursor

Chemicals)

DEA List II Chemicals (Essential

Chemicals)

Listed

Not listed

Not listed

Not listed

Not listed

US. EPA CERCLA Hazardous Substances (40 CFR 302)

Chemical Name	CAS-No.	RQ for component	
Antimony trioxide	1309-64-4	1,000 lb(s)	
		454 kg	

SARA 311/312

Classification : Delayed (chronic) health hazard

Composition/information on ingredients

Name	%	Classification
Molybdate orange (Lead	30 - 60	СН



STAN-TONE 15ET02 ORANGE

Version Number 1.6 Revision Date 05/20/2016

Page 15 of 17 Print Date 05/21/2016

chromate pigment)		
Antimony trioxide	1 - 5	АН, СН

SARA 313

	Product name	CAS number	%
Form R - Reporting	Molybdate orange (Lead	12656-85-8	30 - 60
requirements	chromate pigment)		
	Barium	7440-39-3	1 - 5
	Antimony trioxide	1309-64-4	1 - 5
	Aluminum oxide	1344-28-1	1 - 5
Supplier notification	Molybdate orange (Lead chromate pigment)	12656-85-8	30 - 60
	Barium	7440-39-3	1 - 5
	Antimony trioxide	1309-64-4	1 - 5
	Aluminum oxide	1344-28-1	1 - 5

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

State regulations

Massachusetts : The following components are listed:

Barium

Antimony trioxide Aluminum oxide

New York : The following components are listed:

Antimony trioxide

New Jersey : The following components are listed:

Molybdate orange (Lead chromate pigment)

Barium

Antimony trioxide Aluminum oxide

Pennsylvania : The following components are listed:

Molybdate orange (Lead chromate pigment)

Barium

Antimony trioxide



STAN-TONE 15ET02 ORANGE

Version Number 1.6 Revision Date 05/20/2016 Page 16 of 17 Print Date 05/21/2016

Aluminum oxide

California Prop. 65

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

United States inventory (TSCA 8b) : All components are listed or exempted.

Canada inventory : All components are listed or exempted.

International regulations

International lists : Australia inventory (AICS): All components are listed or exempted.

Taiwan inventory (CSNN): All components are listed or exempted.

Malaysia Inventory (EHS Register): Not determined. EINECS: All components are listed or exempted.

Japan inventory: Not determined.

China inventory (IECSC): All components are listed or exempted.

Korea inventory: All components are listed or exempted.

New Zealand Inventory of Chemicals (NZIoC): All components

are listed or exempted.

Philippines inventory (PICCS): All components are listed or

exempted.

Chemical Weapons Convention

List Schedule I Chemicals

Chemical Weapons Convention

List Schedule II Chemicals

Chemical Weapons Convention

List Schedule III Chemicals

Not listed

Not listed

: Not listed

Section 16. Other information

History

Date of printing: 05/21/2016Date of issue/Date of revision: 05/20/2016Date of previous issue: 03/31/2016Version: 1.6

Key to abbreviations : ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of

Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods



STAN-TONE 15ET02 ORANGE

Version Number 1.6 Revision Date 05/20/2016 Page 17 of 17 Print Date 05/21/2016

LogPow = logarithm of the octanol/water partition coefficient MARPOL 73/78 = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

UN = United Nations

References : Not available.

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. Particularly this information may not be valid for such material used in conjunction with any other materials or in any process, unless specified in the text.