

Dispex® CX 4230

Product description Dispex® CX 4230 is a hydrophobic dispersant for architectural paints and coatings.

- Key benefits**
- Early blister resistance even at high humidity
 - Excellent gloss development
 - Excellent color acceptance
 - Good dispersant efficiency
 - Very competitive cost performance versus other hydrophobic dispersants

Chemical nature Aqueous solution of polymer

Properties

Physical form Light yellow to amber liquid

| | | | |
|---|--------------------------------------|-----------------|-------------------------|
| Technical data (not supply specification) | Solid content | DIN EN ISO 3251 | ~ 28 % |
| | pH value | DIN 19268 | ~ 8 |
| | Brookfield viscosity at 23 °C (73°F) | DIN EN ISO 2555 | 50 - 250 mPa·s |
| | Density at 20°C (68°F) | | ~ 1.1 g/cm ³ |

Application

Dispex® CX 4230 is used to disperse titanium dioxide and extender pigments in architectural paints and coatings.

Recommended concentrations

1.0 to 3.0% based on pigment solids

Storage

Although Dispex® CX 4230 is freeze-thaw stable it should be stored at temperatures above 5°C (41°F) to allow easy handling.

Contacts worldwide

Asia
BASF East Asia Regional Headquarters Ltd
45/F, Jardine House
No. 1 Connaught Place
Central Hong Kong
China
formulation-additives-asia@basf.com

North America
BASF Corporation
11501 Steele Creek Road
Charlotte, NC 28273
USA
formulation-additives-nafta@basf.com

Europe
BASF SE
Formulation Additives
67056 Ludwigshafen
Germany
formulation-additives-europe@basf.com

South America
BASF S.A
Rochaverá - Crystal Tower
Av. das Nações Unidas, 14.171
Morumbi - São Paulo-SP
Brazil
formulation-additives-south-america@basf.com

Validity

This Technical Data Sheet is valid for all versions of the Dispex® CX 4230.

Safety

When handling this product, please comply with the advice and information given in the safety data sheet and observe protective and workplace hygiene measures adequate for handling chemicals.

Note

The data contained in this publication are based on our current knowledge and experience. In view of the many factors that may affect processing and application of our product, these data do not relieve processors from carrying out their own investigations and tests; neither do these data imply any guarantee of certain properties, nor the suitability of the product for a specific purpose. Any descriptions, drawings, photographs, data, proportions, weights, etc. given herein may change without prior information and do not constitute the agreed contractual quality of the product. The agreed contractual quality of the product results exclusively from the statements made in the product specification. It is the responsibility of the recipient of our product to ensure that any proprietary rights and existing laws and legislation are observed.

® = Registered trademark

™ = Trademark of the BASF Group, unless otherwise noted

www.basf.com/formulation-additives