

Dispex[®] Ultra PA 4580

Product description

Dispex[®] Ultra PA 4580 is a high-molecular-weight dispersing agent. It stabilizes the pigment dispersion of inorganic and organic pigments and improves the following properties:

- Strong viscosity reduction of pigment paste
- High pigment loading
- Gloss
- Improved color strength
- Flocculation stability
- Anti-flooding behavior
- Compatible with a wide range of most commonly used water-based coatings

Chemical nature

Acrylic polymer emulsion

Properties

Physical form

clear, slightly yellowish liquid

Technical data

(not supply specification)

Solvent	Water
Density at 20°C (68°F)	~1.05 g/cm ³
Solids content	~ 40 %
Amine value	~15 mg KOH/g

Application

Dispex® Ultra PA 4580 can be used exclusively as a dispersing agent to formulate resin-free pigment concentrates for VOC-free applications. Dispex® Ultra PA 4580 does not have to be neutralized. Its solubility is pH-independent.

Recommended concentrations

Calculation method for the required amount of active ingredient on pigment:

Inorganic pigments	10 % of oil absorption value
Organic pigments	25 – 50 % of BET value
Carbon blacks	20 % of DBP absorption value

Dispex® Ultra PA 4580 should be incorporated in the mill base before adding the pigments.

Storage

Dispex® Ultra PA 4580 may partially solidify when stored below 10 °C (50 °F). Heat to 35–40 °C (95–104 °F) to reliquify.

Contacts worldwide

Asia
BASF East Asia Regional Headquarters Ltd
45/F, Jardine House
No. 1 Connaught Place
Central Hong Kong
China
formulation-additives-asia@basf.com

North America
BASF Corporation
11501 Steele Creek Road
Charlotte, NC 28273
USA
formulation-additives-nafta@basf.com

Europe
BASF SE
Formulation Additives
67056 Ludwigshafen
Germany
formulation-additives-europe@basf.com

South America
BASF S.A.
Rochaverá - Crystal Tower
Av. das Nações Unidas, 14.171
Morumbi - São Paulo-SP
Brazil
formulation-additives-south-america@basf.com

Validity

This Technical Data Sheet is valid for all versions of the Dispex® Ultra PA 4580.

Safety

When handling this product, please comply with the advice and information given in the safety data sheet and observe protective and workplace hygiene measures adequate for handling chemicals.

Note

The data contained in this publication are based on our current knowledge and experience. In view of the many factors that may affect processing and application of our product, these data do not relieve processors from carrying out their own investigations and tests; neither do these data imply any guarantee of certain properties, nor the suitability of the product for a specific purpose. Any descriptions, drawings, photographs, data, proportions, weights, etc. given herein may change without prior information and do not constitute the agreed contractual quality of the product. The agreed contractual quality of the product results exclusively from the statements made in the product specification. It is the responsibility of the recipient of our product to ensure that any proprietary rights and existing laws and legislation are observed.

® = Registered trademark

™ = Trademark of the BASF Group, unless otherwise noted

www.basf.com/formulation-additives