

# Joncryl® 2990

**Product Description** 

Joncryl 2990 is a self-crosslinking, acrylic emulsion for cementitious applications. The latex can be used in clear formulations for "wet look" concrete coatings or pigmented formulations for garage floor coatings. Joncryl 2990 provides excellent chemical, hot tire pick-up, and weathering resistance. As well as, good dirt pick-up, hot tire and blush resistance.

Key Features & Benefits

- Applicable in Clear and Pigmented Paint Formulations
- Excellent early resistance to water blushing
- Excellent Chemical resistance
- Good dirt resistance
- Good adhesion to concrete
- Resistance to hot-tire pickup
- Capable of 50 g/L VOC

**Chemical Nature** 

Acrylic emulsion

#### **Properties**

Typical Properties	Appearance	translucent emulsion
i voicai Properties	Appearance	Hansiuceni emuision

Solids content, weight % ~ 46.0% pH ~7.5 Brookfield Viscosity cPs < 400

Brooklind viboodity or o

Typical CharacteristicsSpecific gravityg/cm³ca. 1.04lbs/galca. 8.68

Average Particle size  $\mu m$  ca. 0.1 MFFT °C ca.18 Freeze-thaw stable No

These typical values should not be interpreted as specifications.

## **Application**

#### Fields of application

Joncryl® 2990 is a one-component, self-crosslinking acrylic emulsion for interior and exterior clear and pigmented coatings at 50 g/L VOC with good balance of properties on cementitious substrates. When used as a clear coat, Joncryl® 2990 gives a wet-look appearance on decorative concrete, natural and artificial stone, and brick. Key uses include residential garage floors, patio, and walkway coatings.

Joncryl® 2990 is recommended for applications such as:

- Exterior and interior decorative concrete,
- · natural or artificial stone
- · brick coatings

April 2018 rev 1 page 1 of 2

#### Safety

#### General

The usual safety precautions when handling chemicals must be observed. These include the measures described in Federal, State and Local health and safety regulations, thorough ventilation of the workplace, good skin care and wearing of protective goggles.

#### Safety Data Sheet

All safety information is provided in the Safety Data Sheet for Joncryll 2990.

### **Storage**

Storage should be in accordance with the "Handling and Storage of polymer dispersions" brochure. Technical information regarding the storage of BASF polymer dispersion products is available upon request.

#### **Important**

The descriptions, designs, and data contained herein are presented for your guidance only. Because there are many factors under your control which may affect processing or application/use it is necessary for you to make appropriate tests to determine whether the product is suitable for your particular purpose prior to use. NO WARRANTIES OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, OR DATA MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, DATA OR DESIGNS PROVIDED BE PRESUMED TO BE A PART OF OUR TERMS AND CONDITIONS OF SALE. Further, you expressly understand and agree that the descriptions, designs, and data furnished by BASF hereunder are given gratis and BASF assumes no obligation or liability for same or results obtained from use thereof, all such being given to you and accepted by you at your risk.

Joncryll is a registered trademark of BASF Group.

© BASF Corporation, 2018



BASF Corporation is fully committed to the Responsible Care® initiative in the USA, Canada, and Mexico. For more information on Responsible Care® go to: U.S.: www.basf.us/responsiblecare\_usa Canada: www.basf.us/responsiblecare\_canada México: www.basf.us/responsiblecare mexico

page 2 of 2

BASF Corporation Dispersions and Resins 11501 Steele Creek Road Charlotte, North Carolina 28273 Phone: (800) 251 – 0612

Email: DispersionsPigmentsCC@basf.com

Email: edtech-info@basf.com www.basf.us/formulation-additives

April 2018 rev 1