

Product Data Sheet

BASF Durasorb® HD

BASF Durasorb[®] is a family of products developed in combination with proprietary system design software to complement each other for the purification of Natural Gas streams. Based on the long and successful history of BASF Sorbead[®] for hydrocarbon and water dewpointing, BASF Durasorb[®] products are designed to work together to provide optimum solutions for the most difficult gas processing conditions, including retrofit of existing units.

Product Applications

Durasorb® HD is a water-resistant aluminosilicate gel adsorbent with high capacity for impurities. Durasorb® HD is used as an active adsorbent layer in LNG and NGL pre-treatment applications.

Durasorb® HD is in the form of hard, spherical beads, with a very high resistance to crushing and a low attrition rate. Durasorb® HD is resistant to damage from liquid water and hydrocarbon carry-over events. These properties provide a robust material, resulting in longer bed life and reduced operating costs.

Durasorb® HD has high resistance to hydrothermal aging and low regeneration temperature, making it ideal for applications where retrograde condensation and refluxing occur duringadsorbent regeneration. Due to these unique properties, the use of Durasorb® HD increases the overall reliability of the system.

Durasorb® HD is used in combination with other products in the Durasorb® portfolio to create a custom-tailored installation that ensures most efficient removal of heavy hydrocarbons and water from natural gas.

Typical Properties	
Chemical Composition	97 wt % SiO2 3 wt % Al2O3
Equilibrium Capacity for Water Vapor at 25° C	4 wt % at 10 % R.H. 36 wt % at 80 % R.H.
Packed Bulk Density	0.67 kg/l
Crush Strength	130 N
Attrition Rate	<0.1 wt %

^{*} These indicative properties do not represent process capabilities.

Typical distribution of grain size

2.0 - 5.0 mm

Packaging

- 750 kg(1,653 lbs) Big bag
- 130 kg (287 lbs) Steel drum

About Us

BASF is a leading global manufacturer of catalysts for the chemical industry, with solutions across the chemical value chain. The business comprises chemical catalysts and adsorbents, refinery catalysts and custom catalysts. In the process catalysts business, priority is given to developing new and improved products that enable the chemical industry transformation to net-zero emissions.

The division's portfolio also includes battery materials and recycling solutions, as well as environmental catalysts and metal solutions. Customers from a variety of industries including Automotive & Transportation, Chemicals, Plastics or Energy & Resources benefit from our innovative solutions. Further information on BASF's Catalysts division is available on the Internet at www.catalysts.basf.com.

BASF - We create chemistry

Americas

BASF Corporation Phone: +1-732-205-5000

Email: catalysts-americas@basf.com

Asia Pacific

BASF (China) Company Limited Phone: +86-21-2039 2549 Email: catalysts-asia@basf.com

Europe, Middle East, Africa BASF Services Europe GmbH Phone: +49-30-20055000 Email: catalysts-europe@basf.com

Durasorb and Sorbead are trademarks of BASF.

Although all statements and information in this publication are believed to be accurate and reliable, they are presented gratis and for guidance only, and risks and liability for results obtained by use of the products or application of the suggestions described are assumed by the user. NO WARRANTIES OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH. Statements or suggestions concerning possible use of the products are made without representation or warranty that any such use is free of patent infringement and are not recommendations to infringe any patent. The user should not assume that toxicity data and safety measures are indicated or that other measures may not be required. © 2015 BASF

BASF-10496 Rev.08/25