

Safety data sheet

Page: 1/21

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.10.2025 Version: 6.0
Date / Previous version: 08.08.2025 Previous version: 5.3

Product: Kauramin® Glue 627

(ID no. 30034900/SDS_GEN_DE/EN)

Date of print 09.10.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Kauramin® Glue 627

UFI: NXCU-7FN5-N00M-PH9R

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses: Chemical

Recommended use: Chemical, for industrial and professional users

1.3. Details of the supplier of the safety data sheet

Company:
BASF SE
67056 Ludwigshafen
GERMANY
Division Monomers

Telephone: +49 621 60 42737

E-mail address: pss.monomers@basf.com

1.4. Emergency telephone number

International emergency number: Telephone: +49 180 2273-112

Date / Revised: 08.10.2025 Version: 6.0

Date / Previous version: 08.08.2025 Previous version: 5.3

Product: Kauramin® Glue 627

(ID no. 30034900/SDS_GEN_DE/EN)

Date of print 09.10.2025

SECTION 2: Hazards Identification

2.1. Classification of the substance or mixture

For the classification of the mixture the following methods have been applied: extrapolation on the concentration levels of the hazardous substances, on basis of test results and after evaluation of experts. The methodologies used are mentioned at the respective test results.

According to Regulation (EC) No 1272/2008 [CLP]

Carc. 1B H350 May cause cancer.

For the classifications not written out in full in this section the full text can be found in section 16.

2.2. Label elements

According to Regulation (EC) No 1272/2008 [CLP]

Pictogram:



Signal Word:

Danger

Hazard Statement:

H350 May cause cancer. Precautionary Statements (Prevention):

P280 Wear protective gloves, protective clothing and eye protection or face

protection.

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and

understood.

Precautionary Statements (Response):

P308 + P311 IF exposed or concerned: Call a POISON CENTER or physician.

Precautionary Statements (Storage):
P405 Store locked up.
Precautionary Statements (Disposal):

P501 Dispose of contents and container to hazardous or special waste

collection point.

Labeling of special preparations (GHS):

EUH208: May produce an allergic reaction. Contains: formaldehyde ... %

to Regulation (EC) No 1907/2006.

Date / Revised: 08.10.2025 Version: 6.0
Date / Previous version: 08.08.2025 Previous version: 5.3

Product: Kauramin® Glue 627

(ID no. 30034900/SDS_GEN_DE/EN)

Date of print 09.10.2025

2.3. Other hazards

According to Regulation (EC) No 1272/2008 [CLP]

No specific dangers known, if the regulations/notes for storage and handling are considered. If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

The product does not contain a substance above legal limits fulfilling the PBT (persistent/bioaccumulative/toxic) criteria or the vPvB (very persistent/very bioaccumulative) criteria. Product does not contain a substance above legal limits included in the list established in accordance with Article 59(1) of Regulation (EC) No 1907/2006 for having endocrine disrupting properties or is identified to have endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

SECTION 3: Composition/Information on Ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Chemical nature

This product contains (a) substance(s) included on the candidate list according to article 59 (1,10) of regulation EC No. 1907/2006 ('REACH') in a concentration equal or above 0.1% w/w:1,3,5-triazine-2,4,6-triamine

Regulatory relevant ingredients

methanol

Content (W/W): >= 0.3 % - < 1 %

CAS Number: 67-56-1 EC-Number: 200-659-6

REACH registration number: 01-

2119433307-44

INDEX-Number: 603-001-00-X

Substance with EU occupational

exposure limit

Flam. Lig. 2

Acute Tox. 3 (Inhalation - vapour)

Acute Tox. 3 (oral)
Acute Tox. 3 (dermal)

STOT SE (Central nervous system, Optic nerve)

1

H225, H301 + H311 + H331, H370

Specific concentration limit:

STOT SE 2: 3 - < 10 % STOT SE 1: >= 10 %

Acute toxicity estimate:

oral: 100 mg/kg Inhalation: 3 mg/l dermal: 300 mg/kg

2-diethylaminoethanol

to Regulation (EC) No 1907/2006.

Date / Revised: 08.10.2025 Version: 6.0
Date / Previous version: 08.08.2025 Previous version: 5.3

Product: Kauramin® Glue 627

(ID no. 30034900/SDS_GEN_DE/EN)

Date of print 09.10.2025

Content (W/W): >= 0.3 % - < 1 %

CAS Number: 100-37-8 EC-Number: 202-845-2

REACH registration number: 01-

2119488937-14

INDEX-Number: 603-048-00-6

Flam. Liq. 3

Acute Tox. 3 (Inhalation - vapour)

Acute Tox. 4 (oral) Acute Tox. 3 (dermal)

Skin Corr. 1B Eye Dam. 1

STOT SE 3 (irr. to respiratory syst.) H226, H302, H335, H314, H311 + H331

Specific concentration limit:

STOT SE 3, irr. to respiratory syst.: >= 5 %

1,3,5-triazine-2,4,6-triamine

Content (W/W): >= 0.3 % - < 1 %

CAS Number: 108-78-1 EC-Number: 203-615-4

REACH registration number: 01-

2119485947-16

INDEX-Number: 613-345-00-2

Carc. 2

Repr. 2 (fertility)

STOT RE (Urinary tract.) 2

H351, H361f, H373

Included on the candidate list according to article 59 (1,10) of regulation EC No. 1907/2006

('REACH').

formaldehyde ... %

to Regulation (EC) No 1907/2006.

Date / Revised: 08.10.2025 Version: 6.0
Date / Previous version: 08.08.2025 Previous version: 5.3

Product: Kauramin® Glue 627

(ID no. 30034900/SDS_GEN_DE/EN)

Date of print 09.10.2025

Content (W/W): >= 0,1 % - < 0,2 % Acute Tox. 2 (Inhalation - vapour)

CAS Number: 50-00-0 Acute Tox. 3 (oral) EC-Number: 200-001-8 Acute Tox. 3 (dermal)

REACH registration number: 01- Skin Corr. 1B

2119488953-20 Eye Dam. 1 INDEX-Number: 605-001-00-5 Skin Sens. 1

Muta. 2
Substance with EU occupational Carc. 1B

exposure limit

H330, H317, H350, H341, H314, H301 + H311 <u>Differing classification according to current</u> <u>knowledge and the criteria given in Annex I of</u>

Regulation (EC) No. 1272/2008

Acute Tox. 3 (dermal)

Acute Tox. 2 (Inhalation - vapour)

Acute Tox. 3 (oral) Skin Sens. 1A Muta. 2 Carc. 1B Skin Corr. 1B Eye Dam. 1

Specific concentration limit:

Eye Irrit. 2: 5 - < 25 %

STOT SE 3, irr. to respiratory syst.: >= 5 %

Skin Sens. 1: >= 0,2 % Skin Irrit. 2: 5 - < 25 % Skin Corr. 1B: >= 25 %

For the classifications not written out in full in this section, including the hazard classes and the hazard statements, the full text is listed in section 16.

SECTION 4: First-Aid Measures

4.1. Description of first aid measures

Remove contaminated clothing.

If inhaled:

If difficulties occur after vapour/aerosol has been inhaled, remove to fresh air and seek medical attention.

On skin contact:

Wash thoroughly with soap and water

On contact with eyes:

Immediately wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.

Date / Revised: 08.10.2025 Version: 6.0
Date / Previous version: 08.08.2025 Previous version: 5.3

Product: Kauramin® Glue 627

(ID no. 30034900/SDS_GEN_DE/EN)

Date of print 09.10.2025

On ingestion:

Immediately rinse mouth and then drink 200-300 ml of water, seek medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms: Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11., (Further) symptoms and / or effects are not known so far

Hazards: No hazard is expected under intended use and appropriate handling.

4.3. Indication of any immediate medical attention and special treatment needed

Treatment: Treat according to symptoms (decontamination, vital functions), no known specific antidote.

SECTION 5: Fire-Fighting Measures

5.1. Extinguishing media

Suitable extinguishing media: water spray, foam, carbon dioxide, dry powder

5.2. Special hazards arising from the substance or mixture

Endangering substances: formaldehyde ... %, methanol, carbon monoxide, Carbon dioxide, nitrogen oxides

Advice: The substances/groups of substances mentioned can be released in case of fire.

5.3. Advice for fire-fighters

Further information:

Fire debris must be disposed of in accordance with offical regulations. In case of combustion evolution of toxic gases/vapours possible. Do not allow to enter drains or waterways. Forms slippery surfaces with water.

SECTION 6: Accidental Release Measures

Forms slippery surfaces with water.

6.1. Personal precautions, protective equipment and emergency procedures

Avoid contact with the skin, eyes and clothing. Handle in accordance with good industrial hygiene and safety practice. Information regarding personal protective measures, see section 8.

to Regulation (EC) No 1907/2006.

Date / Revised: 08.10.2025 Version: 6.0
Date / Previous version: 08.08.2025 Previous version: 5.3

Product: Kauramin® Glue 627

(ID no. 30034900/SDS_GEN_DE/EN)

Date of print 09.10.2025

6.2. Environmental precautions

Do not allow to enter soil, waterways or waste water channels. Prevent entry into drains and surface waters. Ensure compliance with local regulations before discharging into effluent treatment plants.

6.3. Methods and material for containment and cleaning up

For large amounts: Sweep/shovel up.

For residues: Pick up with suitable absorbent material.

6.4. Reference to other sections

Information regarding exposure controls/personal protection and disposal considerations can be found in section 8 and 13.

SECTION 7: Handling and Storage

7.1. Precautions for safe handling

Handle in accordance with good industrial hygiene and safety practice.

Inform workers about possible hazards caused by the release of formaldehyde during processing.

Protection against fire and explosion:

No special precautions necessary.

7.2. Conditions for safe storage, including any incompatibilities

Segregate from acids and acid forming substances.

Suitable materials for containers: glass, Stainless steel 1.4301 (V2), Polyester resin, glass reinforced (Palatal A410), High density polyethylene (HDPE), Low density polyethylene (LDPE), Stainless steel 1.4401, enamelled

Unsuitable materials for containers: Paper/Fibreboard

Further information on storage conditions: Keep in a cool place.

Storage class according to TRGS 510 (originally VCI, Germany): (6.1D) Non-combustible substances of acute toxicity, category 3 / hazardous substances that are toxic or produce chronic effects

Protect from temperatures below:15 °C

The packed product must be protected from temperatures below the indicated one.

Protect from temperatures above:30 °C

The packed product must be protected against exceeding the indicated temperature.

7.3. Specific end use(s)

For the relevant identified use(s) listed in Section 1 the advice mentioned in this section 7 is to be observed.

Date / Revised: 08.10.2025 Version: 6.0
Date / Previous version: 08.08.2025 Previous version: 5.3

Product: Kauramin® Glue 627

(ID no. 30034900/SDS_GEN_DE/EN)

Date of print 09.10.2025

SECTION 8: Exposure Controls/Personal Protection

8.1. Control parameters

Components with occupational exposure limits

The surveillance of the workplace by exposure measurements may be necessary, in order to prove the efficiency of safety measures, for example ventilation or the need of respiratory protection. Since this requires a specific competency, only accredited laboratories should be contracted. Regarding suitable methods to assess inhalation exposure, the European Standards EN 482, 689 and 14042 are to be considered. In addition, the TRGS 402 has to be observed in Germany.

50-00-0: formaldehyde ... %

STEL value 0,74 mg/m3 (Directive 2004/37/EC)

TWA value 0,37 mg/m3; 0,3 ppm (Directive 2004/37/EC)

STEL value 0,6 ppm (Directive 2004/37/EC)
OEL 0,37 mg/m3; 0,3 ppm (TRGS 900 (DE))

Ceiling limit value/factor: 2

If the occupational exposure limit value (AGW) and the biological limit value (BGW) are complied with, there should be no risk of damage for the unborn child (see TRGS 900, Number 2.7)

Short Term Exposure Classification: (TRGS 900 (DE))

Category I: Substances for which the localized effect has an assigned exposure limit or for substances with a sensitizing effect in respiratory passages

HAZ_DES (TRGS 900 (DE))

Skin sensitization

HAZ_DES X (TRGS 900 (DE))

Carcinogenic substance(s) of category 1A/1B. For activities with this hazardous substance, § 10 of the Hazardous Substances Act (GefStoffV) must also be observed.

STEL value 0,4 ppm (EU SCOEL) Ceiling limit value/factor: 15 min TWA value 0,2 ppm (EU SCOEL) Ceiling limit value/factor: 8HR

TWA value 0,62 mg/m3; 0,5 ppm (Directive 2004/37/EC)

67-56-1: methanol

Skin Designation (OEL (EU))

The substance can be absorbed through the skin. TWA value 260 mg/m3; 200 ppm (OEL (EU))

indicative

Skin Designation (TRGS 900 (DE))

The substance can be absorbed through the skin. Short Term Exposure Classification: (TRGS 900 (DE))

Category II: Substances with a resorptive effect OEL 130 mg/m3; 100 ppm (TRGS 900 (DE))

Ceiling limit value/factor: 2

If the occupational exposure limit value (AGW) and the biological limit value (BGW) are complied with, there should be no risk of damage for the unborn child (see TRGS 900, Number 2.7)

to Regulation (EC) No 1907/2006.

Date / Revised: 08.10.2025 Version: 6.0 Date / Previous version: 08.08.2025 Previous version: 5.3

Product: Kauramin® Glue 627

(ID no. 30034900/SDS_GEN_DE/EN)

Date of print 09.10.2025

100-37-8: 2-diethylaminoethanol

Short Term Exposure Classification: (TRGS 900 (DE))

Category I: Substances for which the localized effect has an assigned exposure

limit or for substances with a sensitizing effect in respiratory passages

Skin Designation (TRGS 900 (DE))

The substance can be absorbed through the skin. Short Term Exposure Factor: (TRGS 900 (DE))

Ceiling limit value/factor: 1

Substance listed with exceeding factor and category of short time value.

OEL 9,7 mg/m3; 2 ppm (TRGS 900 (DE))

Ceiling limit value/factor: 2.5

If the occupational exposure limit value (AGW) and the biological limit value (BGW) are complied with, there should be no risk of damage for the unborn child (see TRGS 900, Number 2.7)

Components with biological limit values

67-56-1: methanol

TRGS 903 (DE)

Determinant: alcohols Biological Specimen: Urine

Sampling time period is for long-term exposures, at the end of the shift after several preceding ones./ Sampling time period is at end of exposure or at end of

shift.

Concentration: 15 mg/l

Components with PNEC

50-00-0: formaldehyde ... %

freshwater: 0,132 mg/l marine water: 0,132 mg/l intermittent release: 0,49 mg/l sediment (freshwater): 0,686 mg/l sediment (marine water): 0,686 mg/l

soil: 0,059 mg/l STP: 0,19 mg/l

air:

No PNEC value available.

67-56-1: methanol

freshwater:

No hazard identified.

marine water:

No hazard identified. intermittent release: No hazard identified.

STP:

No hazard identified. sediment (freshwater): No hazard identified.

to Regulation (EC) No 1907/2006.

Date / Revised: 08.10.2025 Version: 6.0
Date / Previous version: 08.08.2025 Previous version: 5.3

Product: Kauramin® Glue 627

(ID no. 30034900/SDS_GEN_DE/EN)

Date of print 09.10.2025

sediment (marine water): No hazard identified. soil:

No hazard identified.
oral (secondary poisoning):
No bioaccumulation potential.

Components with DNEL

50-00-0: formaldehyde ... %

worker: Short-term exposure - systemic and local effects, Inhalation: 0,75

mg/m3, 0,6 ppm

worker: Long-term exposure - systemic and local effects, Inhalation: 0,375

mg/m3, 0,3 ppm

worker: Long-term exposure- systemic effects, dermal: 240 mg/kg consumer: Long-term exposure- systemic effects, oral: 4,1 mg/kg consumer: Long-term exposure- systemic effects, dermal: 102 mg/kg consumer: Long-term exposure - local effects, dermal: 0,012 mg/cm2 consumer: Long-term exposure - systemic and local effects, Inhalation: 0,1

mg/m3

67-56-1: methanol

worker: Long-term exposure- systemic effects, dermal: 20 mg/kg worker: Short-term exposure - systemic effects, dermal: 20 mg/kg worker: Long- and short-term exposure - local effects, dermal No hazard identified.

worker: Long-term exposure - systemic effects, Inhalation: 130 mg/m3 worker: Short-term exposure - systemic effects, Inhalation: 130 mg/m3 worker: Long-term exposure - local effects, Inhalation: 130 mg/m3 worker: Short-term exposure - local effects, Inhalation: 130 mg/m3 consumer: Long-term exposure - systemic effects, oral: 4 mg/kg consumer: Short-term exposure - systemic effects, oral: 4 mg/kg consumer: Long-term exposure - systemic effects, dermal: 4 mg/kg consumer: Short-term exposure - systemic effects, dermal: 4 mg/kg consumer: Long- and short-term exposure - local effects, dermal No hazard identified.

consumer: Long-term exposure- systemic effects, Inhalation: 26 mg/m3 consumer: Short-term exposure - systemic effects, Inhalation: 26 mg/m3 consumer: Long-term exposure - local effects, Inhalation: 26 mg/m3 consumer: Short-term exposure - local effects, Inhalation: 26 mg/m3

8.2. Exposure controls

Personal protective equipment

Hand protection:

Chemical resistant protective gloves (EN ISO 374-1)

Eve protection:

Safety glasses with side-shields (frame goggles) (e.g. EN 166)

to Regulation (EC) No 1907/2006.

Date / Revised: 08.10.2025 Version: 6.0 Date / Previous version: 08.08.2025 Previous version: 5.3

Product: Kauramin® Glue 627

(ID no. 30034900/SDS_GEN_DE/EN)

Date of print 09.10.2025

Body protection:

Body protection must be chosen depending on activity and possible exposure, e.g. apron, protecting boots, chemical-protection suit (according to EN 14605 in case of splashes or EN ISO 13982 in case of dust).

General safety and hygiene measures

Handle in accordance with good industrial hygiene and safety practice. Do not inhale vapours or dust.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

State of matter: liquid Form: liquid

Colour: white, translucent to opaque

Odour: almost odourless

Odour threshold:

No data available.

Melting point: 0°C

(approx. 1.013 hPa)

boiling temperature: approx. 100 °C

Boiling point: 100 °C

(1.013 bar)

Flammability: not flammable (other) (ISO 2719) Flash point:

Not determinable.

Auto-ignition temperature:

Based on the water content the

product does not ignite.

No decomposition if correctly stored and handled. Thermal decomposition: pH value: 9,6 - 10(DIN ISO 976)

(20 °C)

Viscosity, kinematic:

No data available.

900 - 1.200 mPa.s Viscosity, dynamic: (DIN EN ISO 3219, Annex B)

(20 °C)

900 - 1.200 mPa.s (DIN EN ISO 3219, Annex B)

(23 °C)

Solubility in water: miscible

partly soluble

Partitioning coefficient n-octanol/water (log Kow): < 1,0

The statements are based on the

properties of the individual components.

Vapour pressure: approx. 23 mbar

> (20 °C) 19 mbar (20 °C)

to Regulation (EC) No 1907/2006.

Date / Revised: 08.10.2025 Version: 6.0 Date / Previous version: 08.08.2025 Previous version: 5.3

Product: Kauramin® Glue 627

(ID no. 30034900/SDS_GEN_DE/EN)

Date of print 09.10.2025

96 mbar (50 °C) 121 mbar (55 °C)

Relative density:

No data available.

Density: approx. 1,32 g/cm3 (ISO 2811-3)

(20 °C)

Relative vapour density (air):

not determined

Particle characteristics

Particle size distribution: The substance / product is marketed or used in a non solid or granular

form. -

9.2. Other information

Information with regard to physical hazard classes

Explosives

Explosion hazard: not explosive

Oxidizing properties

Fire promoting properties: not fire-propagating

Self-heating substances and mixtures

Self heating ability: It is not a substance capable of

spontaneous heating.

Substances and mixtures, which emit flammable gases in contact with water

Formation of flammable gases:

Forms no flammable gases in the presence of water.

Corrosion to metals

No corrosive effect on metal.

Other safety characteristics

Radioactivity:

not radioactive for transport

purposes

Miscibility with water:

(15 °C)

partially (e.g. >10% <90%)

Hygroscopy: Non-hygroscopic

Other Information: none

Evaporation rate:

Value can be approximated from Henry's Law Constant or vapor

pressure.

to Regulation (EC) No 1907/2006. Date / Revised: 08.10.2025

Version: 6.0 Previous version: 5.3

Date / Previous version: 08.08.2025 Product: **Kauramin® Glue 627**

(ID no. 30034900/SDS_GEN_DE/EN)

Date of print 09.10.2025

SECTION 10: Stability and Reactivity

10.1. Reactivity

No hazardous reactions if stored and handled as prescribed/indicated.

Corrosion to metals: No corrosive effect on metal.

Reactions with Flammable gases: no

water/air:

Toxic gases: no
Corrosive gases: no
Smoke or fog: no
Peroxides: no

Formation of Remarks: Forms no flammable gases in the

flammable gases: presence of water.

10.2. Chemical stability

The product is chemically stable.

Peroxides: The product/the substance has not a tendency towards the formation of

peroxide.

10.3. Possibility of hazardous reactions

During processing with acids, water and / or heat formaldehyde will be released, which may act as a sensitizer.

10.4. Conditions to avoid

> 30 °C

Avoid heat. Avoid freezing. See SDS section 7 - Handling and storage.

10.5. Incompatible materials

Substances to avoid:

Organic Peroxides, strong bases, strong acids, acid anhydrides

10.6. Hazardous decomposition products

formaldehyde ... %

SECTION 11: Toxicological Information

to Regulation (EC) No 1907/2006.

Date / Revised: 08.10.2025 Version: 6.0 Date / Previous version: 08.08.2025 Previous version: 5.3

Product: Kauramin® Glue 627

(ID no. 30034900/SDS_GEN_DE/EN)

Date of print 09.10.2025

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Assessment of acute toxicity:

Virtually nontoxic after a single ingestion. Inhalation-risk test (IRT): No mortality within 7 hours as shown in animal studies. The inhalation of a highly saturated vapor-air mixture represents no acute hazard. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Experimental/calculated data:

LD50 rat (oral): > 5.000 mg/kg (BASF-Test)

Irritation

Assessment of irritating effects:

Not irritating to the skin. Not irritating to the eyes. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Experimental/calculated data:

Skin corrosion/irritation

rabbit: non-irritant (OECD Guideline 404)

Serious eye damage/irritation

rabbit: non-irritant

Serious eye damage/irritation

rabbit: non-irritant (OECD Guideline 405)

Respiratory/Skin sensitization

Assessment of sensitization:

After continuous contact with the skin, sensitization cannot be excluded.

Experimental/calculated data:

Guinea pig maximization test: Non-sensitizing.

This compound containing < 1% formaldehyde has no sensitizing effect (literature data).

Germ cell mutagenicity

Assessment of mutagenicity:

Based on available data, the classification criteria are not met.

Carcinogenicity

Information on: formaldehyde ... %

Assessment of carcinogenicity:

After lifelong inhalation exposure to concentrations that were severely damaging to the nasal epithelium, nasal tumors were induced in rats; in other species these findings were not found or were considerably less pronounced. The International Agency for Research on Cancer (IARC) has classified formaldehyde as a Group 1 (known) human carcinogen based on epidemiological evidence linking formaldehyde exposure to occurrence of nasopharyngeal cancer and leukemia. No adverse health effects are anticipated if recommended personal protective equipment and industrial hygiene practices are used.

Date / Revised: 08.10.2025 Version: 6.0
Date / Previous version: 08.08.2025 Previous version: 5.3

Product: Kauramin® Glue 627

(ID no. 30034900/SDS_GEN_DE/EN)

Date of print 09.10.2025

Reproductive toxicity

Assessment of reproduction toxicity: No reproductive toxic effects reported.

Developmental toxicity

Assessment of teratogenicity:

Not a teratogen.

Specific target organ toxicity (single exposure)

Assessment of STOT single:

Based on the available information there is no specific target organ toxicity to be expected after a single exposure.

Repeated dose toxicity and Specific target organ toxicity (repeated exposure)

Information on: formaldehyde ... %
Assessment of repeated dose toxicity:

After repeated exposure the prominent effect is local irritation.

Information on: methanol

Assessment of repeated dose toxicity:

The substance may cause blindness after repeated ingestion. The substance may cause blindness

after repeated inhalation.

·

Aspiration hazard

No aspiration hazard expected.

Interactive effects

No data available.

11.2. Information on other hazards

Endocrine disrupting properties

Product does not contain a substance above legal limits included in the list established in accordance with Article 59(1) of Regulation (EC) No 1907/2006 for having endocrine disrupting properties or is identified to have endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

Other information

Other relevant toxicity information

Date / Revised: 08.10.2025 Version: 6.0
Date / Previous version: 08.08.2025 Previous version: 5.3

Product: Kauramin® Glue 627

(ID no. 30034900/SDS_GEN_DE/EN)

Date of print 09.10.2025

The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

SECTION 12: Ecological Information

12.1. Toxicity

Assessment of aquatic toxicity:

There is a high probability that the product is not acutely harmful to aquatic organisms. The inhibition of the degradation activity of activated sludge is not anticipated when introduced to biological treatment plants in appropriate low concentrations. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Toxicity to fish:

LC50 (96 h) > 100 mg/l, Brachydanio rerio (OECD Guideline 203, static) Nominal concentration.

Microorganisms/Effect on activated sludge:

EC20 (0,5 h) > 1.000 mg/l, activated sludge, domestic (DIN EN ISO 8192-OECD 209-88/302/EEC,P. C, aquatic)

The inhibition of the degradation activity of activated sludge is not anticipated when introduced to biological treatment plants in appropriate low concentrations.

12.2. Persistence and degradability

Assessment biodegradation and elimination (H2O): Moderately/partially biodegradable.

Elimination information:

No data available.

12.3. Bioaccumulative potential

Assessment bioaccumulation potential:

Based on its structural properties, the polymer is not biologically available. Accumulation in organisms is not to be expected.

12.4. Mobility in soil

Assessment transport between environmental compartments:

Volatility: The substance will not evaporate into the atmosphere from the water surface.

to Regulation (EC) No 1907/2006.

Date / Revised: 08.10.2025 Version: 6.0 Date / Previous version: 08.08.2025 Previous version: 5.3

Product: Kauramin® Glue 627

(ID no. 30034900/SDS_GEN_DE/EN)

Date of print 09.10.2025

12.5. Results of PBT and vPvB assessment

The product does not fulfill the criteria for PBT (Persistent/bioaccumulative/toxic) and vPvB (very persistent/very bioaccumulative).

12.6. Endocrine disrupting properties

Product does not contain a substance above legal limits included in the list established in accordance with Article 59(1) of Regulation (EC) No 1907/2006 for having endocrine disrupting properties or is identified to have endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

12.7. Other adverse effects

The product does not contain substances that are listed in Regulation (EC) 1005/2009 on substances that deplete the ozone layer.

Additional information

Other ecotoxicological advice:

The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

SECTION 13: Disposal Considerations

13.1. Waste treatment methods

Incinerate in suitable incineration plant, observing local authority regulations. No disposal via sewage or waste water systems.

SECTION 14: Transport Information

Land transport

ADR

Not classified as a dangerous good under transport regulations

UN number or ID number:
UN proper shipping name:
Transport hazard class(es):
Packing group:
Environmental hazards:
Special precautions for

Not applicable
Not applicable
Not applicable
Not applicable
Not applicable

user

to Regulation (EC) No 1907/2006.

Date / Revised: 08.10.2025 Version: 6.0
Date / Previous version: 08.08.2025 Previous version: 5.3

Product: Kauramin® Glue 627

(ID no. 30034900/SDS_GEN_DE/EN)

Date of print 09.10.2025

RID

Not classified as a dangerous good under transport regulations

UN number or ID number:
UN proper shipping name:
Transport hazard class(es):
Packing group:
Environmental hazards:
Special precautions for

Not applicable
Not applicable
Not applicable
Not applicable
Not applicable

user

Inland waterway transport

ADN

Not classified as a dangerous good under transport regulations

UN number or ID number:
UN proper shipping name:
Transport hazard class(es):
Packing group:
Environmental hazards:
Special precautions for

Not applicable
Not applicable
Not applicable
Not applicable
Not applicable
Not applicable

user:

Transport in inland waterway vessel

Not evaluated

Sea transport

IMDG

Not classified as a dangerous good under transport regulations

UN number or ID number:
UN proper shipping name:
Transport hazard class(es):
Packing group:
Environmental hazards:
Special precautions for

Not applicable
Not applicable
Not applicable
Not applicable
Not applicable
Not applicable

user

Air transport

IATA/ICAO

Not classified as a dangerous good under transport regulations

UN number or ID number: Not applicable UN proper shipping name: Not applicable

to Regulation (EC) No 1907/2006. Date / Revised: 08.10.2025

Version: 6.0 Previous version: 5.3

Date / Previous version: 08.08.2025 Product: **Kauramin® Glue 627**

(ID no. 30034900/SDS_GEN_DE/EN)

Date of print 09.10.2025

Transport hazard class(es): Not applicable Packing group: Not applicable Not applicable Environmental hazards: Not applicable Special precautions for None known

user

14.1. UN number or ID number

See corresponding entries for "UN number or ID number" for the respective regulations in the tables above.

14.2. UN proper shipping name

See corresponding entries for "UN proper shipping name" for the respective regulations in the tables above.

14.3. Transport hazard class(es)

See corresponding entries for "Transport hazard class(es)" for the respective regulations in the tables above.

14.4. Packing group

See corresponding entries for "Packing group" for the respective regulations in the tables above.

14.5. Environmental hazards

See corresponding entries for "Environmental hazards" for the respective regulations in the tables above.

14.6. Special precautions for user

See corresponding entries for "Special precautions for user" for the respective regulations in the tables above.

14.7. Maritime transport in bulk according to IMO instruments

Maritime transport in bulk is not intended.

SECTION 15: Regulatory Information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Prohibitions, Restrictions and Authorizations

Chemical Prohibition Ordinance (DE): Annex 2 Restriction Type: Restricted substance

Annex XVII of Regulation (EC) No 1907/2006: Number on List: 28, 75, 3, 72, 77

Hazardous Incident Ordinance (Germany):

Listed in above regulation: no

Date / Revised: 08.10.2025 Version: 6.0
Date / Previous version: 08.08.2025 Previous version: 5.3

Product: Kauramin® Glue 627

(ID no. 30034900/SDS_GEN_DE/EN)

Date of print 09.10.2025

Directive 2012/18/EU - Control of Major Accident Hazards involving dangerous substances (EU): Listed in above regulation: no

Classification according to 'TA-Luft' (Germany):

formaldehyde ... %

methanol

Water hazard class (§8/§10 AwSV (Self-classification of the mixture according to calculation method)): (1) Weakly water polluting.

If other regulatory information applies that is not already provided elsewhere in this safety data sheet, then it is described in this subsection.

15.2. Chemical Safety Assessment

Advice on product handling can be found in sections 7 and 8 of this safety data sheet.

SECTION 16: Other Information

<u>Full text of the classifications, including the hazard classes and the hazard statements, if mentioned in section 2 or 3:</u>

Carc. Carcinogenicity
Flam. Liq. Flammable liquids
Acute Tox. Acute toxicity

STOT SE Specific target organ toxicity — single exposure

Skin Corr. Skin corrosion

Eye Dam. Serious eye damage

Repr. Reproductive toxicity

STOT RE Specific target organ toxicity — repeated exposure

Skin Sens. Skin sensitization

Muta. Germ cell mutagenicity

Eye Irrit. Eye irritation
Skin Irrit. Skin irritation
H350 May cause cancer.

H225 Highly flammable liquid and vapour.

H301 + H311 + H331 Toxic if swallowed, in contact with skin or if inhaled.

H370 Causes damage to organs (Central nervous system, Optic nerve).

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H335 May cause respiratory irritation.

H314 Causes severe skin burns and eye damage. H311 + H331 Toxic in contact with skin or if inhaled.

H351 Suspected of causing cancer. H361f Suspected of damaging fertility.

H373 May cause damage to organs (Urinary tract.) through prolonged or

repeated exposure.

H330 Fatal if inhaled.

Date / Revised: 08.10.2025 Version: 6.0
Date / Previous version: 08.08.2025 Previous version: 5.3

Product: Kauramin® Glue 627

(ID no. 30034900/SDS_GEN_DE/EN)

Date of print 09.10.2025

H317 May cause an allergic skin reaction.
H341 Suspected of causing genetic defects.
H301 + H311 Toxic if swallowed or in contact with skin.

Abbreviations

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road. ADN = The European Agreement concerning the International Carriage of Dangerous Goods by Inland waterways. ATE = Acute Toxicity Estimates. CAO = Cargo Aircraft Only. CAS = Chemical Abstract Service. CLP = Classification, Labelling and Packaging of substances and mixtures. DIN = German national organization for standardization. DNEL = Derived No Effect Level. EC50 = Effective concentration median for 50% of the population. EC = European Community. EN = European Standards. IARC = International Agency for Research on Cancer. IATA = International Air Transport Association. IBC-Code = Intermediate Bulk Container code. IMDG = International Maritime Dangerous Goods Code. ISO = International Organization for Standardization. STEL = Short-Term Exposure Limit. LC50 = Lethal concentration median for 50% of the population. LD50 = Lethal dose median for 50% of the population. TLV = Threshold Limit Value. MARPOL = The International Convention for the Prevention of Pollution from Ships. NEN = Dutch Norm. NOEC = No Observed Effect Concentration. OEL = Occupational Exposure Limit. OECD = Organization for Economic Cooperation and Development. PBT = Persistent, Bioaccumulative and Toxic. PNEC = Predicted No Effect Level. PPM = Parts per million. RID = The European Agreement concerning the International Carriage of Dangerous Goods by Rail, TWA = Time Weight Average. UN-number = UN number at transport. vPvB = very Persistent and very Bioaccumulative.

The data contained in this safety data sheet are based on our current knowledge and experience and describe the product only with regard to safety requirements. This safety data sheet is neither a Certificate of Analysis (CoA) nor technical data sheet and shall not be mistaken for a specification agreement. Identified uses in this safety data sheet do neither represent an agreement on the corresponding contractual quality of the substance/mixture nor a contractually designated use. It is the responsibility of the recipient of the product to ensure any proprietary rights and existing laws and legislation are observed.

Vertical lines in the left hand margin indicate an amendment from the previous version.