

# Safety data sheet

Page: 1/14

BASF Safety data sheet

Date / Revised: 29.03.2024

Product: **Hydroxypropyl Acrylate (HPA)**

Version: 8.0

(30041308/SDS\_GEN\_TH/EN)

Date of print: 23.10.2025

## 1. Substance/preparation and manufacturer/supplier identification

### Product name:

Hydroxypropyl Acrylate (HPA)

Use: Monomer.

#### Manufacturer/supplier:

BASF (Thai) Limited

23rd Floor, Emporium Tower, 622, Sukhumvit 24 Rd.,

Klongton, Klongtoey, Bangkok 10110, THAILAND

Telephone: +66 2624-1999

Telefax number: +66 2664-9254

E-mail address: Thailand-SDS-info@basf.com

#### Emergency information:

International emergency number:

Telephone: +49 180 2273-112

## 2. Hazard identification

### Classification according to UN GHS 2009

Classification of the substance and mixture:

Acute toxicity: Cat.4 (oral)

Acute toxicity: Cat.4 (dermal)

Skin corrosion/irritation: Cat.1B

Serious eye damage/eye irritation: Cat.1

Hazardous to the aquatic environment - acute: Cat.2

Skin sensitization: Cat.1B

Hazardous to the aquatic environment - chronic: Cat.3

Label elements and precautionary statement:

Pictogram:

BASF Safety data sheet  
Date / Revised: 29.03.2024  
Product: **Hydroxypropyl Acrylate (HPA)**

Version: 8.0

(30041308/SDS\_GEN\_TH/EN)

Date of print: 23.10.2025



Signal Word:  
Danger

Hazard Statement:

H317	May cause an allergic skin reaction.
H314	Causes severe skin burns and eye damage.
H302 + H312	Harmful if swallowed or in contact with skin.
H412	Harmful to aquatic life with long lasting effects.
H401	Toxic to aquatic life.

Precautionary Statements (Prevention):

P280	Wear protective gloves, protective clothing and eye protection or face protection.
P260	Do not breathe dust/gas/mist/vapours.
P273	Avoid release to the environment.
P272	Contaminated work clothing should not be allowed out of the workplace.
P270	Do not eat, drink or smoke when using this product.
P264	Wash contaminated body parts thoroughly after handling.

Precautionary Statements (Response):

P310	Immediately call a POISON CENTER or physician.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P301 + P330 + P331	IF SWALLOWED: rinse mouth. Do NOT induce vomiting.
P361 + P364	Take off immediately all contaminated clothing and wash it before reuse.

Precautionary Statements (Storage):

P405	Store locked up.
------	------------------

Precautionary Statements (Disposal):

P501	Dispose of contents and container to hazardous or special waste collection point.
------	---

Other hazards which do not result in classification:

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.  
See section 12 - Results of PBT and vPvB assessment.

---

### 3. Composition/information on ingredients

Chemical nature

Substance nature: Substance

BASF Safety data sheet  
Date / Revised: 29.03.2024  
Product: **Hydroxypropyl Acrylate (HPA)**

Version: 8.0

(30041308/SDS\_GEN\_TH/EN)

Date of print: 23.10.2025

hydroxypropyl acrylate  
CAS Number: 25584-83-2

### **Hazardous ingredients**

hydroxypropyl acrylate

Content (W/W): 98.5 % - 100 %  
CAS Number: 25584-83-2

Acute Tox.: Cat. 4 (oral)  
Acute Tox.: Cat. 4 (dermal)  
Skin Corr./Irrit.: Cat. 1B  
Eye Dam./Irrit.: Cat. 1  
Aquatic Acute: Cat. 2  
Skin Sens.: Cat. 1B  
Aquatic Chronic: Cat. 3

acrylic acid

Content (W/W): 0.1 % - 0.5 %  
CAS Number: 79-10-7

Aquatic Acute: Cat. 1  
Flam. Liq.: Cat. 3  
Eye Dam.: Cat. 1  
Skin Corr.: Cat. 1A  
Acute Tox.: Cat. 4 (Inhalation - vapour)  
Aquatic Chronic: Cat. 2  
Acute Tox.: Cat. 4 (oral)  
M-factor acute: 1

## **4. First-Aid Measures**

General advice:

First aid personnel should pay attention to their own safety. Remove affected person from danger area. Immediately remove contaminated clothing. If the patient is likely to become unconscious, place and transport in stable sideways position (recovery position). Avoid contact with the skin, eyes and clothing.

If inhaled:

Keep patient calm, remove to fresh air, seek medical attention. Immediately administer a corticosteroid from a controlled/metered dose inhaler.

On skin contact:

Immediately wash thoroughly with soap and water, seek medical attention.

On contact with eyes:

Immediately wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.

On ingestion:

Immediately rinse mouth and then drink 200-300 ml of water, seek medical attention. Do not induce vomiting.

Note to physician:

BASF Safety data sheet  
Date / Revised: 29.03.2024  
Product: **Hydroxypropyl Acrylate (HPA)**

Version: 8.0

(30041308/SDS\_GEN\_TH/EN)

Date of print: 23.10.2025

Symptoms: Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11.

Treatment: Treat according to symptoms (decontamination, vital functions), no known specific antidote.

---

## 5. Fire-Fighting Measures

Suitable extinguishing media:  
dry powder, water spray, carbon dioxide, foam

Unsuitable extinguishing media for safety reasons:  
water jet

Additional information:  
Use extinguishing measures to suit surroundings.

Specific hazards:  
Risk of violent self-polymerization if overheated in a container. Cool endangered containers with water-spray.

Burning produces harmful and toxic fumes. Do not breathe gas/vapour.

Shut off or stop released substance/product under safe conditions. Do not release chemically contaminated water into drains, soil or surface water. Sufficient measures must be taken to retain the water used for extinguishing. Dispose of contaminated water and soil according to local regulations.

Special protective equipment:  
Wear a self-contained breathing apparatus. Special protective equipment for firefighters

Further information:  
Extend fire extinguishing measures to the surroundings. Fight fire from maximum distance. Vapours are heavier than air and may accumulate in low areas and travel a considerable distance up to the source of ignition.

Further information:  
In case of a fire in the vicinity a restabilization system should be used if the temperature in the bulk storage-tank reaches 45°C. Evacuate area of all unnecessary personnel. In case of a fire in the vicinity evacuate all personnel in a greater area if the temperature in the bulk storage-tank reaches 60°C.

Further information:  
Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

---

## 6. Accidental Release Measures

Personal precautions:

Avoid all sources of ignition: heat, sparks, open flame. Avoid contact with the skin, eyes and clothing. Ensure adequate ventilation. Breathing protection required.

BASF Safety data sheet  
Date / Revised: 29.03.2024  
Product: **Hydroxypropyl Acrylate (HPA)**

Version: 8.0

(30041308/SDS\_GEN\_TH/EN)

Date of print: 23.10.2025

Take off immediately all contaminated clothing. Keep people away and stay on the upwind side. Beware of pits and confined spaces.

Use antistatic tools. Handle in accordance with good industrial hygiene and safety practice.

Environmental precautions:

Do not discharge into drains/surface waters/groundwater. Contain contaminated water/firefighting water.

Methods for cleaning up or taking up:

For large amounts: Pump off product.

Spills should be contained, solidified, and placed in suitable containers for disposal. Dispose of absorbed material in accordance with regulations. Ensure adequate ventilation. Suppress gases/vapours/mists with water spray jet. Clean contaminated floors and objects thoroughly with water and detergents, observing environmental regulations. Cleaning operations should be carried out only while wearing breathing apparatus. Pick up with suitable appliance and dispose of.

Additional information: High risk of slipping due to leakage/spillage of product.

Release of substance/product can cause fire or explosion. Shut off or stop source of leak. Shut off or stop released substance/product under safe conditions.

Pack in tightly closed containers for disposal.

---

## 7. Handling and Storage

### Handling

The substance/ product may be handled only by appropriately trained personnel. Facility parts must be checked for polymer residues and cleaned on regular basis in order to avoid hazardous reactions.

Ensure thorough ventilation of stores and work areas. Encapsulation or exhaust ventilation required. When filling, transferring, or emptying of containers, adequate local exhaust ventilation is necessary. Vent waste air to atmosphere only through suitable separators. Check the condition of seals and connector screw threads. Do not open warm or swollen product containers. Remove persons to safety and alert fire brigade.

The temperatures which must be avoided are to be considered. Protect against heat. Protect from direct sunlight. Protect contents from the effects of light.

Because of the possible separation from the stabilizer the product should never be partially melted and taken. Ensure that there is no crystallized product in the container before use.

Ensure adequate inhibitor and dissolved oxygen level. Avoid all sources of ignition: heat, sparks, open flame.

Avoid inhalation of dusts/mists/vapours. Avoid aerosol formation. Avoid all direct contact with the substance/product.

Protection against fire and explosion:

Avoid all sources of ignition: heat, sparks, open flame. Substance/product can form explosive mixture with air. Ground all transfer equipment properly to prevent electrostatic discharge.

Containers should be grounded against electrostatic charge. It is recommended that all conductive

parts of the machinery are grounded. Explosion-proof equipment is not necessary when loading and processing of the product takes place at a minimum of 5 °C below the flash point.

Heated containers should be cooled to prevent polymerization. If exposed to fire, keep containers cool by spraying with water. Emergency cooling must be provided for the eventuality of a fire in the vicinity. Avoid influence of heat.

### Storage

Further information on storage conditions: Prior to storage ensure that the transfer equipment used and the intended storage containers do not contain other substances/products. Before transfer to stock the identity of the product must be proved to be without doubt. The entrance to storage rooms is to be granted only to appropriately trained personnel.

The stabilizer is only effective in the presence of oxygen. Maintain contact with atmosphere containing 5 - 21% oxygen. Never use tanks with inert-gas installation for storage.

Risk of polymerization. Protect against heat. Protect from direct sunlight. Protect contents from the effects of light. Avoid UV-light and other radiation with high energy. Protect against contamination. In case of bulk storage, the storage-tanks should at least be equipped with two high temperature alert devices.

Do not store product below the indicated minimum temperature, because crystallization should be absolutely avoided.

Even if the product is stored and handled as prescribed/indicated it should be used up within the indicated duration of storage.

Storage stability:

Storage temperature: < 35 °C

Storage duration: 12 Months

The stated storage temperature should be noted.

Avoid prolonged storage.

This product should be processed as soon as possible.

Ensure adequate inhibitor and dissolved oxygen level.

Do not store with less than 10 % headspace above liquid.

Storage stability is based upon ambient temperatures and conditions described.

It is recommended to keep a safe distance of +2 degrees above the crystallization range.

The product is stabilized, the shelf life should be noted.

Storage temperature: 45 °C

A restabilization system should be used if the temperature in the bulk storage-tank reaches the indicated value.

Storage temperature: 60 °C

All personnel in a greater area should be evacuated if the temperature in the bulk storage-tank reaches the indicated value.

Protect from temperatures above: 35 °C

Changes in the properties of the product may occur if substance/product is stored above indicated temperature for extended periods of time.

---

## 8. Exposure controls and personal protection

### Components with occupational exposure limits

acrylic acid, 79-10-7;

BASF Safety data sheet  
Date / Revised: 29.03.2024  
Product: **Hydroxypropyl Acrylate (HPA)**

Version: 8.0

(30041308/SDS\_GEN\_TH/EN)

Date of print: 23.10.2025

TWA value 2 ppm (ACGIHTLV)  
TWA value 2 ppm (OEL (TH))  
Skin Designation (ACGIHTLV)  
Danger of cutaneous absorption

#### Personal protective equipment

##### Respiratory protection:

Suitable respiratory protection for lower concentrations or short-term effect: Gas filter for gases/vapours of organic compounds (boiling point >65 °C, e. g. EN 14387 Type A)

##### Hand protection:

Suitable materials also with prolonged, direct contact (Recommended: Protective index 6, corresponding > 480 minutes of permeation time according to EN ISO 374-1):

fluoroelastomer (FKM) - 0.7 mm coating thickness

nitrile rubber (NBR) - 0.4 mm coating thickness

Supplementary note: The specifications are based on tests, literature data and information of glove manufacturers or are derived from similar substances by analogy. Due to many conditions (e.g. temperature) it must be considered, that the practical usage of a chemical-protective glove in practice may be much shorter than the permeation time determined through testing.

Manufacturer's directions for use should be observed because of great diversity of types.

##### Eye protection:

Tightly fitting safety goggles (splash goggles) (e.g. EN 166)

##### Body protection:

Body protection must be chosen depending on activity and possible exposure, e.g. apron, protecting boots, chemical-protection suit (according to EN 14605 in case of splashes or EN ISO 13982 in case of dust).

##### General safety and hygiene measures:

Avoid inhalation of vapour. Avoid contact with the skin, eyes and clothing. Wearing of closed work clothing is required additionally to the stated personal protection equipment. Handle in accordance with good industrial hygiene and safety practice.

---

## 9. Physical and Chemical Properties

Form:	liquid
Colour:	colourless
Odour:	acrylic-like
Odour threshold:	not determined

pH value:	(20 °C) neutral, miscible
-----------	------------------------------

Melting point:	-23.4 °C Literature data.
----------------	------------------------------

Boiling point:	198.5 °C (1,013.25 hPa) Cannot be distilled without decomposition at normal pressure.
----------------	--

BASF Safety data sheet

Date / Revised: 29.03.2024

Version: 8.0

Product: **Hydroxypropyl Acrylate (HPA)**

(30041308/SDS\_GEN\_TH/EN)

Date of print: 23.10.2025

Flash point:	99 °C	(ISO 2719, closed cup)
Evaporation rate:	Value can be approximated from Henry's Law Constant or vapor pressure.	
Flammability (solid/gas):	hardly combustible	(derived from flash point)
Lower explosion limit:	For liquids not relevant for classification and labelling., The lower explosion point may be 5 - 15 °C below the flash point.	
Upper explosion limit:	For liquids not relevant for classification and labelling.	
Ignition temperature:	308 °C	(DIN EN 14522)
Self ignition:	Temperature: 20 °C Based on its structural properties the product is not classified as self-igniting.	Test type: Spontaneous self-ignition at room-temperature.
Self heating ability:	Not tested on account of the low melting-point. It is not a substance capable of spontaneous heating.	
SADT:	Not a substance/mixture liable to self-decomposition according to GHS.	
Explosion hazard:	Based on the chemical structure there is no indication of explosive properties.	
Fire promoting properties:	Based on its structural properties the product is not classified as oxidizing.	
Vapour pressure:	0.1 hPa (20 °C) dynamic	(measured)
Density:	1.054 g/cm <sup>3</sup> (20 °C)	(ISO 2811-3)
	1.0256 g/cm <sup>3</sup> (50 °C)	(OECD Guideline 109)
Relative density:	0.1049 (25 °C) Literature data.	
Relative vapour density (air):	4.5 (20 °C) Heavier than air.	(calculated)
Solubility in water:	miscible	
Partitioning coefficient n-octanol/water (log Pow):	0.2 (25 °C)	(measured)
Adsorption/water - soil:	KOC: 1.49; log KOC: 0.17	(calculated)



BASF Safety data sheet  
Date / Revised: 29.03.2024  
Product: **Hydroxypropyl Acrylate (HPA)**

Version: 8.0

(30041308/SDS\_GEN\_TH/EN)

Date of print: 23.10.2025

Surface tension:	Based on chemical structure, surface activity is not to be expected.	
Viscosity, dynamic:	9.1 mPa.s (20 °C)	(calculated (from kinematic viscosity))
Viscosity, kinematic:	8.63 mm <sup>2</sup> /s (20 °C)	(OECD Guideline 114)
Molar mass:	130.14 g/mol	

## 10. Stability and Reactivity

### Conditions to avoid:

Avoid heat. Avoid oxygen content above the product of less than 5 %. Avoid UV-light and other radiation with high energy. Avoid direct sunlight. Avoid prolonged storage. Avoid inhibitor loss. Avoid excessive temperatures. Avoid all sources of ignition: heat, sparks, open flame. Avoid freezing. Avoid moisture. Avoid temperatures below the crystallization range.

### Substances to avoid:

radical formers, free radical initiators, peroxides, mercaptans, nitro-compounds, perborates, azides, ether, ketones, aldehydes, amines, nitrates, nitrites, oxidizing agents, reducing agents, strong bases, alkaline reactive substances, acid anhydrides, acid chlorides, concentrated mineral acids, metal salts  
Inert gas

Corrosion to metals: No corrosive effect on metal.

### Hazardous reactions:

Explosion and fire hazard exists under confined conditions. Ignitable air mixtures can form when the product is heated above the flash point and/or when sprayed or atomized. Formation of explosive gas/air mixtures.

Polymerization coupled with heat formation.

Risk of spontaneous polymerization by oxygen depletion of the liquid phase. Risk of spontaneous polymerization when heated or in the presence of UV radiation. Risk of spontaneous and violent self-polymerization if inhibitor is lost or product is exposed to excessive heat. Polymerization produces gases which may burst closed or confined containers. Reactions may cause ignition.

Radical formation can cause exothermic polymerization. Reacts with peroxides and other radical components. Risk of spontaneous polymerization in the presence of starters for radical chain reactions (e.g. peroxides). Reacts with nitric acid. Polymerizes explosively in contact with strong oxidizing agents. Risk of spontaneous polymerization in the presence of oxidizing agents.

Hazardous reactions in presence of mentioned substances to avoid.

The product is stabilized against spontaneous polymerization prior to despatch. The product is stable if stored and handled as prescribed/indicated.

### Hazardous decomposition products:

No hazardous decomposition products if stored and handled as prescribed/indicated.

### Chemical stability:

The product is stable if stored and handled as prescribed/indicated.

### Reactivity:

No hazardous reactions if stored and handled as prescribed/indicated.

## 11. Toxicological Information

### Routes of exposure

#### Acute oral toxicity

Experimental/calculated data:

LD50rat (oral): 820 mg/kg (similar to OECD guideline 401)

#### Acute inhalation toxicity

LC50 rat (by inhalation): > 0.38 mg/l 8 h (similar to OECD guideline 403)

Inhalation-risk test (IRT): No mortality within 8 hours as shown in animal studies. The inhalation of a highly saturated vapor-air mixture represents no acute hazard. The vapour was tested.

#### Acute dermal toxicity

LD50 rat (dermal): > 1,000 mg/kg (OECD Guideline 402)

No mortality was observed.

#### Acute toxicity other routes

LD50 mouse (intraperitoneal): approx. 0,45 ml/kg

#### Assessment of acute toxicity

Of moderate toxicity after single ingestion. Of moderate toxicity after short-term skin contact. The inhalation of a highly enriched/saturated vapor-air-mixture represents an unlikely acute hazard. The European Union (EU) has classified the substance as "toxic" after inhalation. The European Union (EU) has classified the substance as "toxic" after dermal exposure. The European Union (EU) has classified the substance as "toxic" after oral exposure.

#### Symptoms

Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11.

#### Irritation

Assessment of irritating effects:

Corrosive! Damages skin and eyes.

Experimental/calculated data:

Skin corrosion/irritation rabbit: Corrosive. (BASF-Test)

Serious eye damage/irritation rabbit: irreversible damage (BASF-Test)

#### Respiratory/Skin sensitization

Assessment of sensitization:

Sensitization after skin contact possible.

Experimental/calculated data:

Mouse Local Lymph Node Assay (LLNA) mouse: skin sensitizing (similar to OECD guideline 429)

#### Germ cell mutagenicity

**Assessment of mutagenicity:**

Results from a number of mutagenicity studies with microorganisms, mammalian cell culture and mammals are available. Taking into account all of the information, there is no indication that the substance is mutagenic. The product has not been fully tested. The statements have been derived in parts from products of a similar structure or composition.

**Carcinogenicity****Assessment of carcinogenicity:**

In long-term animal studies in which the substance was given by inhalation, a carcinogenic effect was not observed. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

**Reproductive toxicity****Assessment of reproduction toxicity:**

The results of animal studies gave no indication of a fertility impairing effect.

**Developmental toxicity****Assessment of teratogenicity:**

No indications of a developmental toxic / teratogenic effect were seen in animal studies. The product has not been fully tested. The statements have been derived in parts from products of a similar structure or composition.

**Experiences in humans**

Experimental/calculated data:

Danger of skin sensitization on repeated contact.

**Specific target organ toxicity (single exposure)**

Based on the available information there is no specific target organ toxicity to be expected after a single exposure.

**Repeated dose toxicity and Specific target organ toxicity (repeated exposure)****Assessment of repeated dose toxicity:**

After repeated exposure the prominent effect is local irritation. No substance-specific organotoxicity was observed after repeated administration to animals. The product has not been fully tested. The statements have been derived in parts from products of a similar structure or composition.

**Aspiration hazard**

No aspiration hazard expected.

---

**12. Ecological Information****Ecotoxicity**

BASF Safety data sheet  
Date / Revised: 29.03.2024  
Product: **Hydroxypropyl Acrylate (HPA)**

Version: 8.0

(30041308/SDS\_GEN\_TH/EN)

Date of print: 23.10.2025

**Assessment of aquatic toxicity:**

Acutely toxic for aquatic organisms. The inhibition of the degradation activity of activated sludge is not anticipated when introduced to biological treatment plants in appropriate low concentrations.

**Toxicity to fish:**

LC50 (96 h) 3.61 mg/l, Pimephales promelas (Fish test acute, Flow through.)

Literature data. The statement of the toxic effect relates to the analytically determined concentration.

**Aquatic invertebrates:**

EC50 (48 h) 24 mg/l, Daphnia magna (OECD Guideline 202, part 1, static)

The details of the toxic effect relate to the nominal concentration.

**Aquatic plants:**

EC50 (96 h) 6.98 mg/l (growth rate), Selenastrum capricornutum (OECD Guideline 201, static)

The details of the toxic effect relate to the nominal concentration.

**Microorganisms/Effect on activated sludge:**

EC20 (0.5 h) approx. 1,000 mg/l, activated sludge (DIN EN ISO 8192-OECD 209-88/302/EEC, P. C, aerobic)

**Chronic toxicity to fish:**

No data available.

**Chronic toxicity to aquatic invertebrates:**

No observed effect concentration (21 d), 0.86 mg/l, Daphnia magna (OECD Guideline 211, semistatic)

The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

**Mobility****Assessment transport between environmental compartments:**

The substance will not evaporate into the atmosphere from the water surface.

Adsorption to solid soil phase is not expected.

**Persistence and degradability****Elimination information:**

90 - 100 % DOC reduction (14 d) (OECD 301 A (new version)) (aerobic, activated sludge, domestic)

**Assessment of stability in water:**

In contact with water the substance will hydrolyse slowly.

**Information on Stability in Water (Hydrolysis):**

$t_{1/2}$  > 490 d, (28 d) (25 °C, pH value 3), (OPPTS 835.2130, other)

$t_{1/2}$  > 230 d, (28 d) (25 °C, pH value 7), (OPPTS 835.2130, pH 7)

$t_{1/2}$  12.27 d, (7 d) (25 °C, pH value 11), (OPPTS 835.2130, other)

**Sum parameter**

Chemical oxygen demand (COD): 1,705 mg/g

Biochemical oxygen demand (BOD) Incubation period 5 d: < 10 mg/g

BASF Safety data sheet  
Date / Revised: 29.03.2024  
Product: **Hydroxypropyl Acrylate (HPA)**

Version: 8.0

(30041308/SDS\_GEN\_TH/EN)

Date of print: 23.10.2025

### Bioaccumulation potential

Assessment bioaccumulation potential:

Because of the n-octanol/water distribution coefficient (log Pow) accumulation in organisms is not to be expected.

Bioaccumulation potential:

No data available.

### Additional information

Other ecotoxicological advice:

Do not release untreated into natural waters.

---

## 13. Disposal Considerations

Must be sent to a suitable incineration plant, observing local regulations.

Contaminated packaging:

Uncleaned empties should be disposed of in the same manner as the contents.

---

## 14. Transport Information

### Domestic transport:

UN number or ID number: UN 1760

UN proper shipping name: CORROSIVE LIQUID, N.O.S. (HYDROXYPROPYL ACRYLATE, STABILIZED)

Transport hazard class(es): 8

Packing group: II

Environmental hazards: no

Special precautions for user: None known

### Sea transport

IMDG

UN number or ID number: UN 1760

UN proper shipping name: CORROSIVE LIQUID, N.O.S. (HYDROXYPROPYL ACRYLATE, STABILIZED)

Transport hazard class(es): 8

Packing group: II

Environmental hazards: no

Marine pollutant: NO

Special precautions for user: EmS: F-A; S-B

### Air transport

IATA/ICAO

BASF Safety data sheet  
Date / Revised: 29.03.2024  
Product: **Hydroxypropyl Acrylate (HPA)**

Version: 8.0

(30041308/SDS\_GEN\_TH/EN)

Date of print: 23.10.2025

UN number or ID number:	UN 1760
UN proper shipping name:	CORROSIVE LIQUID, N.O.S. (HYDROXYPROPYL ACRYLATE, STABILIZED)
Transport hazard class(es):	8
Packing group:	II
Environmental hazards:	No Mark as dangerous for the environment is needed
Special precautions for user:	None known

**Further information**

According to SP386 it is ensured that the level of chemical stabilization is sufficient to prevent dangerous polymerization during total duration of carriage. This information is valid for the recently stabilized product.

---

## 15. Regulatory Information

**Other regulations**

If other regulatory information applies that is not already provided elsewhere in this safety data sheet, then it is described in this subsection.

---

## 16. Other Information

Safe Handling and Storage aspects are covered in a brochure which is available on request.

---

Vertical lines in the left hand margin indicate an amendment from the previous version.

The data contained in this safety data sheet are based on our current knowledge and experience and describe the product only with regard to safety requirements. This safety data sheet is neither a Certificate of Analysis (CoA) nor technical data sheet and shall not be mistaken for a specification agreement. Identified uses in this safety data sheet do neither represent an agreement on the corresponding contractual quality of the substance/mixture nor a contractually designated use. It is the responsibility of the recipient of the product to ensure any proprietary rights and existing laws and legislation are observed.