

Efka[®] PA 4401

General

High-molecular weight dispersing agent

Efka[®] PA 4401 is a polymeric dispersant for stabilizing inorganic and organic pigments. This results in:

- Improved gloss and DOI
- Reduced flooding
- High color strength
- Broad compatibility from low- to high-polarity systems, including nitrocellulose.

Chemical nature

Modified polyacrylate

Properties

Physical form

Clear yellowish liquid

Technical data

(not supply specification)

Solvent	n-butyl acetate/2-butanol	
Density	(20 °C)	0.94 – 0.96 g/cm ³
Solid content	(1h at 120 °C)	49.0 – 51.0 %
Flash point	24 °C	
Amine value	(20 °C)	49.0 – 53.0 mg KOH/g
Color value	Gardner (20 °C)	≤ 5

Application

Efka® PA 4401 is recommended for all kinds of high-quality solvent-based industrial coatings including automotive topcoats as well as pigment concentrates.

Care should be taken with Efka® PA 4401 because of its tendency to yellowing and gelling when combined with chlorinated polymers. It also has a tendency to yellowing when combined with solvent-free epoxies.

Recommended concentrations

Calculation method for the required amount of active ingredient on pigment:

Inorganic pigments	10 % of oil absorption value
Organic pigments	25 – 50 % of BET value
Carbon blacks	20 % of DBP absorption value

Efka® PA 4401 should be incorporated in the mill base before adding the pigments.

Storage

Efka® PA 4401 should be stored in a cool and dry place.

Contacts worldwide

Asia BASF East Asia Regional Headquarters Limited 36/F, Two Taikoo Place, Taikoo Place, 979 King's Road, Quarry Bay, Hong Kong formulation-additives-asia@basf.com	North America BASF Corporation 11501 Steele Creek Road Charlotte, NC 28273 USA formulation-additives-nafta@basf.com
Europe BASF SE Formulation Additives 67056 Ludwigshafen Germany formulation-additives-europe@basf.com	South America BASF S.A Rochaverá - Crystal Tower Av. das Nações Unidas, 14.171 Morumbi - São Paulo-SP Brazil formulation-additives-south-america@basf.com

Validity

This Technical Data Sheet is valid for all versions of the Efka® PA 4401.

Safety

When handling this product, please comply with the advice and information given in the safety data sheet and observe protective and workplace hygiene measures adequate for handling chemicals.

Note

The data contained in this publication are based on our current knowledge and experience. In view of the many factors that may affect processing and application of our product, these data do not relieve processors from carrying out their own investigations and tests; neither do these data imply any guarantee of certain properties, nor the suitability of the product for a specific purpose. Any descriptions, drawings, photographs, data, proportions, weights, etc. given herein may change without prior information and do not constitute the agreed contractual quality of the product. The agreed contractual quality of the product results exclusively from the statements made in the product specification. It is the responsibility of the recipient of our product to ensure that any proprietary rights and existing laws and legislation are observed.