

Revision date : 2024/04/04 Page: 1/11
Version: 6.0 (30692213/SDS_GEN_MX/EN)

1. Identification

Product identifier used on the label

Hydropalat® WE 3185 EL

Recommended use of the chemical and restriction on use

Recommended use*: wetting agent, additives for inks, varnishes or coatings, Levelling Agent Unsuitable for use: Not intended for sale to or use by the general public.

Details of the supplier of the safety data sheet

Company:

BASF Mexicana S.A. de C.V. Av. Insurgentes Sur 975 Col. CD. De Los Deportes, C.P. 03710 Ciudad de México MÉXICO

Telephone: +52 55 5325 2600

Emergency telephone number

24 Hour Emergency Response Information

SETIQ: 1800-00-214-(Rep. Mexicana) or 55-59-15-88 (CDMX)

Telephone: +1-800-849-5204 or +1-833-229-1000

Other means of identification

Chemical family: alcohol ethoxylate, Polymer, Starting materials listed in EINECS

Synonyms: Use: Raw material for the chemical-technical industry

2. Hazards Identification

According to Regulation NOM-018-STPS-2015

Classification of the product

Acute Tox. 4 (oral) Acute toxicity

Eye Dam./Irrit. 1 Serious eye damage/eye irritation

^{*} The "Recommended use" identified for this product is provided solely to comply with a Federal requirement and is not part of the seller's published specification. The terms of this Safety Data Sheet (SDS) do not create or infer any warranty, express or implied, including by incorporation into or reference in the seller's sales agreement.

Hydropalat® WE 3185 EL

Revision date: 2024/04/04 Page: 2/11 Version: 6.0 (30692213/SDS_GEN_MX/EN)

Label elements

Pictogram:



Signal Word: Danger

Hazard Statement:

H318 Causes serious eye damage.

H302 Harmful if swallowed.

Precautionary Statements (Prevention):

P280 Wear eye and face protection.

P270 Do not eat, drink or smoke when using this product.
P264 Wash contaminated body parts thoroughly after handling.

Precautionary Statements (Response):

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER or physician.

P330 Rinse mouth.

Precautionary Statements (Disposal):

P501 Dispose of contents and container to hazardous or special waste

collection point.

Hazards not otherwise classified

No specific dangers known, if the regulations/notes for storage and handling are considered.

Labeling of special preparations (GHS):

This surfactant complies with the biodegradability criteria as laid down in Regulation (EC)

No.648/2004 on detergents. Data to support this assertion are held at the disposal of the competent authorities of the Member States and will be made available to them at their direct request or at the request of a detergent manufacturer.

The following percentage of the mixture consists of components(s) with unknown hazards regarding the acute toxicity: 96 - 97 % Inhalation - vapour

The following percentage of the mixture consists of components(s) with unknown hazards regarding the acute toxicity: 96 - 97 % Inhalation - mist

3. Composition / Information on Ingredients

According to Regulation NOM-018-STPS-2015

Hexan-1-ol, ethoxylated

CAS Number: Trade Secret

Content (W/W): >= 75.0 - <= 100.0%

Synonym: No data available.

Glycol Ether

Revision date: 2024/04/04 Page: 3/11 Version: 6.0 (30692213/SDS_GEN_MX/EN)

CAS Number: Trade Secret Content (W/W): >= 1.0 - < 7.0% Synonym: No data available.

4. First-Aid Measures

Description of first aid measures

General advice:

Remove contaminated clothing.

If inhaled:

Keep patient calm, remove to fresh air, seek medical attention. Immediately administer a corticosteroid from a controlled/metered dose inhaler.

If on skin:

Immediately wash thoroughly with plenty of water, apply sterile dressings, consult a skin specialist.

If in eyes:

Immediately wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.

If swallowed:

Immediately rinse mouth and then drink 200-300 ml of water, seek medical attention.

Most important symptoms and effects, both acute and delayed

Symptoms: Eye irritation, nausea, severe pain, itching

Indication of any immediate medical attention and special treatment needed

Note to physician

Treatment: Treat according to symptoms (decontamination, vital functions), no known specific antidote.

5. Fire-Fighting Measures

Extinguishing media

Suitable extinguishing media: water spray, dry powder, foam

Special hazards arising from the substance or mixture

Hazards during fire-fighting:

harmful vapours, carbon oxides

Evolution of fumes/fog. The substances/groups of substances mentioned can be released in case of fire.

Advice for fire-fighters

Protective equipment for fire-fighting:

Firefighters should be equipped with self-contained breathing apparatus and turn-out gear.

Revision date: 2024/04/04 Page: 4/11 Version: 6.0 (30692213/SDS GEN MX/EN)

Further information:

The degree of risk is governed by the burning substance and the fire conditions. Contaminated extinguishing water must be disposed of in accordance with official regulations.

6. Accidental release measures

Further accidental release measures:

High risk of slipping due to leakage/spillage of product.

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel: Use personal protective clothing. Information regarding personal protective measures, see section 8.

For emergency responders: Take appropriate protective measures.

Environmental precautions

Do not discharge into drains/surface waters/groundwater.

Methods and material for containment and cleaning up

For small amounts: Pick up with absorbent material (e.g. sand, sawdust, general-purpose binder). Dispose of absorbed material in accordance with regulations.

For large amounts: Pump off product.

Place absorbed material in the same container as the spilled substance/product for disposal.

7. Handling and Storage

Precautions for safe handling

No eating, drinking, smoking or tobacco use at the place of work. Wash hands before breaks and at end of work. Remove contaminated clothing and protective equipment before entering eating areas.

Protection against fire and explosion:

No special precautions necessary.

Conditions for safe storage, including any incompatibilities

Suitable materials for containers: Stainless steel 1.4301 (V2), Stainless steel 1.4401, Stainless steel 1.4539, Stainless steel 1.4541, Stainless steel 1.4571, glass, High density polyethylene (HDPE), Low density polyethylene (LDPE), Carbon steel (Iron), tinned carbon steel (Tinplate)

Further information on storage conditions: Keep container tightly closed and dry; store in a cool place.

The packed product is not damaged by low temperatures or by frost. Bulk must be protected from solidification.

Protect from temperatures above: 70 °C

Properties of the product change irreversibly on exceeding the limit temperature.

8. Exposure Controls/Personal Protection

No substance specific occupational exposure limits known.

Hydropalat® WE 3185 EL

Revision date: 2024/04/04 Page: 5/11
Version: 6.0 (30692213/SDS_GEN_MX/EN)

Personal protective equipment

Respiratory protection:

Wear respiratory protection if ventilation is inadequate. Breathing protection if breathable aerosols/dust are formed.

Hand protection:

Chemical resistant protective gloves

Eye protection:

Tightly fitting safety goggles (chemical goggles).

Body protection:

Body protection must be chosen based on level of activity and exposure.

General safety and hygiene measures:

Wear protective clothing as necessary to minimize contact. Handle in accordance with good industrial hygiene and safety practice. No eating, drinking, smoking or tobacco use at the place of work. Handle in accordance with good industrial hygiene and safety practice.

9. Physical and Chemical Properties

Form: liquid

Odour: product specific colourless to yellowish

pH value: approx. 7 (DIN EN 1262)

(50 g/l, 23 °C)

Melting point: $< 0 \, ^{\circ}\text{C}$ (other)

Boiling point: $> 200 \, ^{\circ}\text{C}$ (internal test)

(1,013 hPa)

Flash point: 176 °C (DIN 51758)

Flammability: not flammable

Lower explosion limit: For liquids not relevant for

classification and labelling. The lower explosion point may be 5 - 15 °C

below the flash point.

Upper explosion limit: For liquids not relevant for

classification and labelling.

Autoignition: $> 250 \, ^{\circ}\text{C}$ (DIN 51794) Vapour pressure: $< 0.1 \, \text{hPa}$ (internal method)

(20 °C)

Density: approx. 1 g/cm3 (DIN 51757)

(20°C)

Relative density: No data available. Vapour density: not determined

Partitioning coefficient n- Study technically not feasible.

octanol/water (log Pow):

Self-ignition not self-igniting

temperature:

Thermal decomposition: > 150 °C (internal method)

Viscosity, dynamic: not determined

Viscosity, kinematic: approx. 20 mm2/s (internal method)

(23 °C)

Hydropalat® WE 3185 EL

Revision date: 2024/04/04 Page: 6/11 Version: 6.0 (30692213/SDS_GEN_MX/EN)

Particle size: The substance / product is marketed

or used in a non solid or granular

form.

Solubility in water: (15 °C) soluble

soluble

solvent(s): alcohols,
Evaporation rate: Value can be approximated from

Henry's Law Constant or vapor

pressure.

Other Information: If necessary, information on other physical and chemical

parameters is indicated in this section.

10. Stability and Reactivity

Solubility (qualitative):

Reactivity

No hazardous reactions if stored and handled as prescribed/indicated.

Corrosion to metals:

Corrosive effects to metal are not anticipated.

Oxidizing properties: not fire-propagating

Formation of Remarks: Forms no flammable gases in the

flammable gases: presence of water.

Chemical stability

The product is stable if stored and handled as prescribed/indicated.

Peroxides: The product does not contain peroxides. The product/the substance has

not a tendency towards the formation of peroxide.

Possibility of hazardous reactions

No hazardous reactions when stored and handled according to instructions.

The product is chemically stable.

Conditions to avoid

See SDS section 7 - Handling and storage.

Incompatible materials

caustics, halogens, Alkalines, acids, reactive chemicals

Hazardous decomposition products

Decomposition products:

Hazardous decomposition products: No hazardous decomposition products if stored and handled as prescribed/indicated.

Thermal decomposition:

> 150 °C (internal method)

Hydropalat® WE 3185 EL

Revision date: 2024/04/04 Page: 7/11
Version: 6.0 (30692213/SDS_GEN_MX/EN)

11. Toxicological information

Primary routes of exposure

Routes of entry for solids and liquids are ingestion and inhalation, but may include eye or skin contact. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquefied gases.

Acute Toxicity/Effects

Oral

Type of value: LD50

Species: rat

Value: > 300 - 2,000 mg/kg (OECD Guideline 423)

Information on: Hexan-1-ol, ethoxylated

Type of value: LD50

Species: rat

Value: > 300 - 2,000 mg/kg (OECD Guideline 423)

Inhalation

Type of value: LC50

Species: rat not determined

Dermal

Type of value: LD50

Species: rat

Value: > 2,000 mg/kg (OECD Guideline 402)

Information on: Glycol Ether

Type of value: LD50

Species: rabbit (male/female)

Value: 2,001 - 2,216 mg/kg (similar to OECD guideline 402)

Assessment other acute effects

No data available.

Skin

Species: rabbit Result: non-irritant Method: other

The product has not been tested. The statement has been derived from the properties of the

individual components.

Information on: Glycol Ether

Species: rabbit Result: non-irritant

Method: Directive 84/449/EEC, B.4

Literature data.

Information on: Hexan-1-ol, ethoxylated

Species: rabbit Method: other

Hydropalat® WE 3185 EL

Revision date: 2024/04/04 Page: 8/11
Version: 6.0 (30692213/SDS_GEN_MX/EN)

Eye

Species: rabbit

Result: Risk of serious damage to eyes.

Method: other

The product has not been tested. The statement has been derived from the properties of the

individual components.

Information on: Glycol Ether

Species: rabbit

Result: Risk of serious damage to eyes.

Method: OECD Guideline 405

Information on: Hexan-1-ol, ethoxylated

Species: rabbit Method: other

The statement for irritation of the mucous membrane was derived from products of similar

composition.

·

Sensitization

Assessment of sensitization: No data available.

Aspiration Hazard

No aspiration hazard expected.

Chronic Toxicity/Effects

Repeated dose toxicity

Assessment of repeated dose toxicity: Not classified, due to lack of data.

Genetic toxicity

Assessment of mutagenicity: Not classified, due to lack of data.

Carcinogenicity

Assessment of carcinogenicity: Not classified, due to lack of data.

Reproductive toxicity

Assessment of reproduction toxicity: Not classified, due to lack of data.

Teratogenicity

Assessment of teratogenicity: Not classified, due to lack of data.

Other Information

The product has not been tested. The statements on toxicology have been derived from products of a similar structure and composition.

12. Ecological Information

Toxicity

Toxicity to fish

LC50 (96 h) > 100 mg/l, Brachydanio rerio (OECD 203; ISO 7346; 84/449/EWG, C.1)

Hydropalat® WE 3185 EL

Revision date: 2024/04/04 Page: 9/11 Version: 6.0 (30692213/SDS_GEN_MX/EN)

Aquatic invertebrates

EC50 (48 h) > 100 mg/l, Daphnia magna (OECD Guideline 202, part 1)

Aquatic plants

EC50 (72 h) > 100 mg/l, Scenedesmus subspicatus (Guideline 92/69/EEC, C.3)

EC10 (72 h) > 100 mg/l (growth rate), Scenedesmus subspicatus (Guideline 92/69/EEC, C.3)

Chronic toxicity to fish

No data available.

Chronic toxicity to aquatic invertebrates

No data available.

Assessment of terrestrial toxicity

No data available concerning terrestrial toxicity.

Microorganisms/Effect on activated sludge

Toxicity to microorganisms

EC50: > 1,000 mg/l

Inhibition of degradation activity in activated sludge is not to be anticipated during correct introduction of low concentrations.

Persistence and degradability

Elimination information

> 60 % CO2 formation relative to the theoretical value (28 d) (OECD 301B; ISO 9439; 92/69/EWG, C.4-C) Readily biodegradable.

Bioaccumulative potential

Assessment bioaccumulation potential

Accumulation in organisms is not to be expected.

Mobility in soil

Assessment transport between environmental compartments

The substance will not evaporate into the atmosphere from the water surface. Adsorption to solid soil phase is possible.

Additional information

Sum parameter

Chemical oxygen demand (COD): (calculated) approx. 2,140 mg/g

Add. remarks environm. fate & pathway:

Treatment in biological waste water treatment plants has to be performed according to local and administrative regulations.

Other ecotoxicological advice:

Revision date: 2024/04/04 Page: 10/11 Version: 6.0 (30692213/SDS_GEN_MX/EN)

The product has not been tested. The statements on ecotoxicology have been derived from products of a similar structure and composition. Do not allow to enter soil, waterways or waste water channels.

13. Disposal considerations

Waste disposal of substance:

Dispose of in accordance with national, state and local regulations. It is the waste generator's responsibility to determine if a particular waste is hazardous under RCRA.

Container disposal:

Dispose of in accordance with national, state and local regulations.

14. Transport Information

Land transport

TDG

Not classified as a dangerous good under transport regulations

Sea transport

IMDG

Not classified as a dangerous good under transport regulations

Air transport IATA/ICAO

Not classified as a dangerous good under transport regulations

15. Regulatory Information

Federal Regulations

Not applicable

NFPA Hazard codes:

Health: 2 Fire: 1 Reactivity: 0 Special:

HMIS III rating

Health: 2 Flammability: 1 Physical hazard: 0

16. Other Information

SDS Prepared by:

BASF NA Product Regulations SDS Prepared on: 2024/04/04

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in

Revision date: 2024/04/04 Page: 11/11
Version: 6.0 (30692213/SDS_GEN_MX/EN)

a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

Hydropalat® WE 3185 EL is a registered trademark of BASF Mexicana or BASF SE

This information is considered accurate but is not exhaustive and shall only be used as a guideline based on current knowledge of the chemical substance or mixture. Safety precautions suitable for the product must be applied.

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK. **END OF DATA SHEET**