

# Safety data sheet

Page: 1/14

BASF Safety data sheet according to the United Nations' Globally Harmonized System (UN GHS)

Date / Revised: 08.10.2025 Version: 5.3

Product: Kaurit® Glue 385

(ID no. 30034926/SDS\_GEN\_00/EN)

Date of print 09.10.2025

### 1. Identification

**Product identifier** 

# Kaurit® Glue 385

# Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses: Chemical Recommended use: Chemical

# Details of the supplier of the safety data sheet

Company:
BASF SE
67056 Ludwigshafen
GERMANY
Division Monomers

Telephone: +49 621 60 42737

E-mail address: pss.monomers@basf.com

# **Emergency telephone number**

International emergency number: Telephone: +49 180 2273-112

# 2. Hazards Identification

Date / Revised: 08.10.2025 Version: 5.3

Product: Kaurit® Glue 385

(ID no. 30034926/SDS\_GEN\_00/EN)

Date of print 09.10.2025

#### Classification of the substance or mixture

#### According to UN GHS criteria

Skin Sens. 1 Carc. 1B

For the classifications not written out in full in this section the full text can be found in section 16.

#### Label elements

# Globally Harmonized System (GHS)

#### Pictogram:





# Signal Word:

Danger

#### Hazard Statement:

H317 May cause an allergic skin reaction.

H350 May cause cancer.

# Precautionary Statements (Prevention):

P280 Wear protective gloves, protective clothing and eye protection or face

protection.

P201 Obtain special instructions before use.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P202 Do not handle until all safety precautions have been read and

understood.

P272 Contaminated work clothing should not be allowed out of the workplace.

### Precautionary Statements (Response):

P308 + P311 IF exposed or concerned: Call a POISON CENTER or physician.

P303 IF ON SKIN (or hair):

P361 Take off immediately all contaminated clothing.

P352 Wash with plenty of soap and water.
P363 Wash contaminated clothing before reuse.

# Precautionary Statements (Storage):

P405 Store locked up.

### Precautionary Statements (Disposal):

P501 Dispose of contents and container to hazardous or special waste

collection point.

#### Other hazards

Date / Revised: 08.10.2025 Version: 5.3

Product: Kaurit® Glue 385

(ID no. 30034926/SDS\_GEN\_00/EN)

Date of print 09.10.2025

#### According to UN GHS criteria

No specific dangers known, if the regulations/notes for storage and handling are considered. If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

# 3. Composition/Information on Ingredients

# **Substances**

Not applicable

#### **Mixtures**

# Chemical nature

Polymer based on: Urea, Formaldehyde

in water

# Hazardous ingredients (GHS)

According to UN GHS criteria

#### Formaldehyde

Content (W/W): >= 0,3 % - < 1 % Flam. Liq. 4

CAS Number: 50-00-0 Acute Tox. 2 (Inhalation - vapour)

EC-Number: 200-001-8 Acute Tox. 3 (oral)
INDEX-Number: 605-001-00-5 Acute Tox. 3 (dermal)

DEX-Number: 605-001-00-5 Acute Tox. 3 (derma Skin Corr. 1B

Eye Dam. 1 Skin Sens. 1A Carc. 1B

Aquatic Acute 2

H227, H330, H317, H350, H314, H301 + H311,

H401

# Specific concentration limit:

Eye Irrit. 2: 5 - < 25 %

STOT SE 3, irr. to respiratory syst.: >= 5 %

Skin Sens. 1: >= 0,2 % Skin Irrit. 2: 5 - < 25 % Skin Corr. 1B: >= 25 %

Methanol

Date / Revised: 08.10.2025 Version: 5.3

Product: Kaurit® Glue 385

(ID no. 30034926/SDS\_GEN\_00/EN)

Date of print 09.10.2025

Content (W/W): >= 0.3 % - < 1 % Flam. Liq. 2

CAS Number: 67-56-1 Acute Tox. 3 (Inhalation - vapour)

EC-Number: 200-659-6 Acute Tox. 3 (oral)
INDEX-Number: 603-001-00-X Acute Tox. 3 (dermal)

STOT SE (Central nervous system, Optic nerve)

1

H225, H301 + H311 + H331, H370

Specific concentration limit: STOT SE 2: 3 - < 10 % STOT SE 1: >= 10 %

For the classifications not written out in full in this section the full text can be found in section 16.

### 4. First-Aid Measures

# **Description of first aid measures**

First aid personnel should pay attention to their own safety. If the patient is likely to become unconscious, place and transport in stable sideways position (recovery position). Immediately remove contaminated clothing.

#### If inhaled:

Keep patient calm, remove to fresh air, seek medical attention.

#### On skin contact:

Immediately wash thoroughly with soap and water, seek medical attention.

#### On contact with eyes:

Wash affected eyes for at least 15 minutes under running water with eyelids held open.

#### On ingestion:

Immediately rinse mouth and then drink 200-300 ml of water, seek medical attention.

### Most important symptoms and effects, both acute and delayed

Symptoms: Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11., (Further) symptoms and / or effects are not known so far

Hazards: Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11. (Further) symptoms and / or effects are not known so far

### Indication of any immediate medical attention and special treatment needed

Treatment: Treat according to symptoms (decontamination, vital functions), no known specific antidote.

Date / Revised: 08.10.2025 Version: 5.3

Product: Kaurit® Glue 385

(ID no. 30034926/SDS\_GEN\_00/EN)

Date of print 09.10.2025

# 5. Fire-Fighting Measures

# **Extinguishing media**

Suitable extinguishing media: water spray, foam, carbon dioxide, dry powder

Unsuitable extinguishing media for safety reasons: water jet

# Special hazards arising from the substance or mixture

Formaldehyde, Methanol, Carbon monoxide, Carbon dioxide, nitrogen oxides The substances/groups of substances mentioned can be released in case of fire.

# Advice for fire-fighters

Further information:

Fire debris must be disposed of in accordance with offical regulations. In case of combustion evolution of toxic gases/vapours possible. Do not allow to enter drains or waterways. Forms slippery surfaces with water.

# 6. Accidental Release Measures

Forms slippery surfaces with water.

# Personal precautions, protective equipment and emergency procedures

Avoid contact with the skin, eyes and clothing. Handle in accordance with good industrial hygiene and safety practice. Information regarding personal protective measures, see section 8.

# **Environmental precautions**

Do not allow to enter soil, waterways or waste water channels. Prevent entry into drains and surface waters. Ensure compliance with local regulations before discharging into effluent treatment plants.

### Methods and material for containment and cleaning up

For large amounts: Sweep/shovel up.

For residues: Pick up with suitable absorbent material.

# 7. Handling and Storage

# Precautions for safe handling

Handle in accordance with good industrial hygiene and safety practice.

Inform workers about possible hazards caused by the release of formaldehyde during processing.

Protection against fire and explosion:

No special precautions necessary.

### Conditions for safe storage, including any incompatibilities

Date / Revised: 08.10.2025 Version: 5.3

Product: Kaurit® Glue 385

(ID no. 30034926/SDS\_GEN\_00/EN)

Date of print 09.10.2025

Suitable materials for containers: Carbon steel (Iron), Stainless steel 1.4401, Stainless steel 1.4301

Further information on storage conditions: Keep in a cool place.

# Specific end use(s)

For the relevant identified use(s) listed in Section 1 the advice mentioned in this section 7 is to be observed.

# 8. Exposure Controls/Personal Protection

# **Control parameters**

Components with occupational exposure limits

50-00-0: Formaldehyde

57-13-6: Urea 67-56-1: Methanol

# **Exposure controls**

#### Personal protective equipment

Respiratory protection:

Breathing protection if gases/vapours are formed. Gas filter for gases/vapours of inorganic compounds (e.g. EN 14387 Type B)

#### Hand protection:

Chemical resistant protective gloves (EN ISO 374-1)

Suitable materials also with prolonged, direct contact (Recommended: Protective index 6, corresponding > 480 minutes of permeation time according to EN ISO 374-1):

butyl rubber (butyl) - 0.7 mm coating thickness

nitrile rubber (NBR) - 0.4 mm coating thickness

#### Eye protection:

Safety glasses with side-shields (frame goggles) (e.g. EN 166)

# Body protection:

Body protection must be chosen depending on activity and possible exposure, e.g. apron, protecting boots, chemical-protection suit (according to EN 14605 in case of splashes or EN ISO 13982 in case of dust).

#### General safety and hygiene measures

Handle in accordance with good industrial hygiene and safety practice. Do not inhale vapours or dust.

# 9. Physical and Chemical Properties

# 9.1. Information on basic physical and chemical properties

State of matter: liquid Form: liquid

Date / Revised: 08.10.2025 Version: 5.3

Product: Kaurit® Glue 385

(ID no. 30034926/SDS\_GEN\_00/EN)

(other)

Date of print 09.10.2025

Colour: white, translucent to opaque

Odour: almost odourless

Odour threshold:

No data available.

Melting point:

not applicable

boiling temperature: approx. 100 °C

Flammability: not flammable, not self-igniting

Lower explosion limit:

For liquids not relevant for classification and labelling.

Upper explosion limit:

For liquids not relevant for classification and labelling.

Flash point:

not applicable

Auto-ignition temperature:

not applicable

Thermal decomposition: No decomposition if correctly stored and handled. pH value: approx. 8 (DIN ISO 976)

(20°C)

Viscosity, kinematic:

No data available.

Viscosity, dynamic: 600 - 800 mPa.s (DIN EN ISO 3219, Annex B)

(20 °C)

Solubility in water: miscible

Partitioning coefficient n-octanol/water (log Kow): < 1,0

The statements are based on the properties of the individual

components.

Vapour pressure: 17 mbar

(20 °C) 95 mbar (50 °C) 122 mbar (55 °C)

Density: 1,29 - 1,30 g/cm<sup>3</sup> (ISO 2811-3)

(20 °C)

Relative vapour density (air):

not determined

Particle characteristics

Particle size distribution: The substance / product is marketed or used in a non solid or granular

form. -

#### 9.2. Other information

#### Information with regard to physical hazard classes

**Explosives** 

Explosion hazard: not explosive

Oxidizing properties

Fire promoting properties: not fire-propagating

Other safety characteristics

Hygroscopy: Non-hygroscopic

Solids content: 64,5 - 66,5 % (DIN EN ISO 3251)

Other Information: none

Date / Revised: 08.10.2025 Version: 5.3

Product: Kaurit® Glue 385

(ID no. 30034926/SDS\_GEN\_00/EN)

Date of print 09.10.2025

Evaporation rate:

Value can be approximated from Henry's Law Constant or vapor pressure.

# 10. Stability and Reactivity

# Reactivity

No hazardous reactions if stored and handled as prescribed/indicated.

# **Chemical stability**

The product is chemically stable.

# Possibility of hazardous reactions

During processing with acids, water and / or heat formaldehyde will be released, which may act as a sensitizer.

### Conditions to avoid

> 30 °C

Avoid heat. Avoid freezing. See SDS section 7 - Handling and storage.

### Incompatible materials

Substances to avoid:

Organic Peroxides, strong bases, strong acids, acid anhydrides

# Hazardous decomposition products

:

Formaldehyde

# 11. Toxicological Information

# Information on toxicological effects

# **Acute toxicity**

Assessment of acute toxicity:

Virtually nontoxic after a single ingestion. The inhalation of a highly enriched/saturated vapor-air-mixture represents an unlikely acute hazard.

Experimental/calculated data: LD50 rat (oral): > 5.000 mg/kg

rat (by inhalation): 7 h (IRT)

No mortality within the stated exposition time as shown in animal studies.

Date / Revised: 08.10.2025 Version: 5.3

Product: Kaurit® Glue 385

(ID no. 30034926/SDS\_GEN\_00/EN)

Date of print 09.10.2025

#### Irritation

Assessment of irritating effects: Irritating to skin. Not irritating to the eyes.

Experimental/calculated data:

Skin corrosion/irritation rabbit: Irritant. (Draize test)

Serious eye damage/irritation rabbit: non-irritant

Serious eye damage/irritation rabbit: non-irritant (Draize test)

#### Respiratory/Skin sensitization

Assessment of sensitization:

May produce an allergic reaction. Sensitization after skin contact possible. The product has not been tested. The statement has been derived from the properties of the individual components.

#### Germ cell mutagenicity

Assessment of mutagenicity:

Not mutagenic (EU Technical Guidance Document 2003)

# Carcinogenicity

Assessment of carcinogenicity:

The substance caused cancer in animal studies.

Information on: Formaldehyde Assessment of carcinogenicity:

After lifelong inhalation exposure to concentrations that were severely damaging to the nasal epithelium, nasal tumors were induced in rats; in other species these findings were not found or were considerably less pronounced. The International Agency for Research on Cancer (IARC) has classified formaldehyde as a Group 1 (known) human carcinogen based on epidemiological evidence linking formaldehyde exposure to occurrence of nasopharyngeal cancer and leukemia. No adverse health effects are anticipated if recommended personal protective equipment and industrial hygiene practices are used.

-----

#### Reproductive toxicity

Assessment of reproduction toxicity: No reproductive toxic effects reported.

#### Developmental toxicity

Assessment of teratogenicity: Not a teratogen.

Specific target organ toxicity (single exposure)

Assessment of STOT single:

Date / Revised: 08.10.2025 Version: 5.3

Product: Kaurit® Glue 385

(ID no. 30034926/SDS\_GEN\_00/EN)

Date of print 09.10.2025

Based on the available information there is no specific target organ toxicity to be expected after a single exposure.

#### Repeated dose toxicity and Specific target organ toxicity (repeated exposure)

Information on: Formaldehyde

Assessment of repeated dose toxicity:

After repeated exposure the prominent effect is local irritation.

Information on: Methanol

Assessment of repeated dose toxicity:

The substance may cause blindness after repeated ingestion. The substance may cause blindness

after repeated inhalation.

\_\_\_\_\_

#### Aspiration hazard

No aspiration hazard expected.

# 12. Ecological Information

### **Toxicity**

Assessment of aquatic toxicity:

There is a high probability that the product is not acutely harmful to aquatic organisms.

Toxicity to fish:

LC50 (48 h) > 500 mg/l, Leuciscus idus (static)

Nominal concentration.

Microorganisms/Effect on activated sludge:

activated sludge, industrial (DIN EN ISO 8192-OECD 209-88/302/EEC,P. C, aerobic) Inhibition of degradation activity in activated sludge is not to be anticipated during correct introduction of low concentrations.

# Persistence and degradability

Assessment biodegradation and elimination (H2O):

The product has not been tested.

Elimination information:

No data available.

#### **Bioaccumulative potential**

Assessment bioaccumulation potential:

Based on its structural properties, the polymer is not biologically available. Accumulation in organisms is not to be expected.

Date / Revised: 08.10.2025 Version: 5.3

Product: Kaurit® Glue 385

(ID no. 30034926/SDS\_GEN\_00/EN)

Date of print 09.10.2025

# Mobility in soil

Assessment transport between environmental compartments:

Volatility: The substance will not evaporate into the atmosphere from the water surface.

Information on: Formaldehyde

Assessment transport between environmental compartments:

Volatility: The substance will not evaporate into the atmosphere from the water surface.

Adsorption in soil: Adsorption to solid soil phase is not expected.

Information on: Methanol

Assessment transport between environmental compartments:

Volatility: The substance will not evaporate into the atmosphere from the water surface.

Adsorption in soil: Adsorption to solid soil phase is not expected.

\_\_\_\_\_

#### Other adverse effects

The product does not contain substances that are listed in Regulation (EC) 1005/2009 on substances that deplete the ozone layer.

#### **Additional information**

Other ecotoxicological advice:

Do not release untreated into natural waters. Inhibition of degradation activity in activated sludge is not to be anticipated during correct introduction of low concentrations. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

# 13. Disposal Considerations

#### Waste treatment methods

Incinerate in suitable incineration plant, observing local authority regulations.

# 14. Transport Information

# **Land transport**

ADR

Not classified as a dangerous good under transport regulations

UN number or ID number:
UN proper shipping name:
Transport hazard class(es):
Packing group:
Environmental hazards:
Special precautions for

Not applicable
Not applicable
Not applicable
Not applicable
Not applicable
Not applicable

Date / Revised: 08.10.2025 Version: 5.3

Product: Kaurit® Glue 385

(ID no. 30034926/SDS\_GEN\_00/EN)

Date of print 09.10.2025

user

**RID** 

Not classified as a dangerous good under transport regulations

UN number or ID number: Not applicable UN proper shipping name: Not applicable Transport hazard class(es): Not applicable Packing group: Not applicable Environmental hazards: Not applicable

Special precautions for

user

Not applicable None known

# **Inland waterway transport**

ADN

Not classified as a dangerous good under transport regulations

UN number or ID number:
UN proper shipping name:
Transport hazard class(es):
Packing group:
Not applicable
Not applicable
Not applicable
Not applicable
Not applicable

Special precautions for

user:

Not applicable None known

#### Transport in inland waterway vessel

Not classified as a dangerous good under transport regulations

UN number or ID number:
UN proper shipping name:
Transport hazard class(es):
Packing group:
Not applicable
Not applicable
Not applicable
Not applicable
Not applicable

# Sea transport

**IMDG** 

Not classified as a dangerous good under transport regulations

UN number or ID number:
UN proper shipping name:
Transport hazard class(es):
Packing group:
Environmental hazards:
Special precautions for

Not applicable
Not applicable
Not applicable
Not applicable
Not applicable
Not applicable

user

Air transport

### IATA/ICAO

Not classified as a dangerous good under transport regulations

Date / Revised: 08.10.2025 Version: 5.3

Product: Kaurit® Glue 385

(ID no. 30034926/SDS\_GEN\_00/EN)

Date of print 09.10.2025

UN number or ID number
UN proper shipping name:
Transport hazard class(es):
Packing group:
Environmental hazards:
Special precautions for

Not applicable
Not applicable
Not applicable
Not applicable
Not applicable
Not applicable

user

# Maritime transport in bulk according to IMO instruments

Maritime transport in bulk is not intended.

# 15. Regulatory Information

# Safety, health and environmental regulations/legislation specific for the substance or mixture

If other regulatory information applies that is not already provided elsewhere in this safety data sheet, then it is described in this subsection.

#### 16. Other Information

Full text of classifications, hazard symbols and hazard statements, if mentioned in section 2 or 3:

Skin Sens.
Carc.
Flam. Liq.
Acute Tox.
Skin Corr.
Skin Corr.
Skin Sensitization
Carcinogenicity
Flammable liquids
Acute toxicity
Skin corrosion
Serious eye damage

Aquatic Acute Hazardous to the aquatic environment - acute STOT SE Specific target organ toxicity — single exposure

Eye Irrit. Eye irritation
Skin Irrit. Skin irritation
H227 Combustible liquid.
H330 Fatal if inhaled.

H317 May cause an allergic skin reaction.

H350 May cause cancer.

H314 Causes severe skin burns and eye damage. H301 + H311 Toxic if swallowed or in contact with skin.

H401 Toxic to aquatic life.

H225 Highly flammable liquid and vapour.

H301 + H311 + H331 Toxic if swallowed, in contact with skin or if inhaled.

H370 Causes damage to organs (Central nervous system, Optic nerve).

The data contained in this safety data sheet are based on our current knowledge and experience and describe the product only with regard to safety requirements. This safety data sheet is neither a Certificate of Analysis (CoA) nor technical data sheet and shall not be mistaken for a specification agreement. Identified uses in this safety data sheet do neither represent an agreement on the corresponding contractual quality of the substance/mixture nor a contractually designated use. It is the responsibility of the recipient of the product to ensure any proprietary rights and existing laws and legislation are observed.

Page: 14/14

Safety data sheet according to the United Nations' Globally Harmonized System (UN GHS)

Date / Revised: 08.10.2025 Version: 5.3

Product: Kaurit® Glue 385

(ID no. 30034926/SDS\_GEN\_00/EN)

Date of print 09.10.2025

Vertical lines in the left hand margin indicate an amendment from the previous version.