

Revision date: 2025/06/27 Page: 1/13

Version: 11.0 (30034845/SDS\_GEN\_US/EN)

#### 1. Identification

#### Product identifier used on the label

# BUTYLGLYCOL

### Recommended use of the chemical and restriction on use

Recommended use\*: process chemical, solvent(s) Recommended use\*: process chemical; solvent(s)

Unsuitable for use: Not intended for sale to or use by the general public.

# Details of the supplier of the safety data sheet

Company:

BASF CORPORATION 100 Park Avenue Florham Park, NJ 07932, USA

,

Telephone: +1 973 245-6000

# **Emergency telephone number**

24 Hour Emergency Response Information

CHEMTREC: 1-800-424-9300

BASF HOTLINE: 1-800-832-HELP (4357)

Other means of identification

Chemical family: organic compounds

# 2. Hazards Identification

# According to Regulation 2024 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

# Classification of the product

Flam. Liq. 4 Flammable liquids
Eye Irrit. 2A Eye irritation
Acute Tox. 4 (oral) Acute toxicity
Skin Irrit. 2 Skin irritation

<sup>\*</sup> The "Recommended use" identified for this product is provided solely to comply with a Federal requirement and is not part of the seller's published specification. The terms of this Safety Data Sheet (SDS) do not create or infer any warranty, express or implied, including by incorporation into or reference in the seller's sales agreement.

Revision date: 2025/06/27 Page: 2/13 Version: 11.0 (30034845/SDS GEN US/EN)

#### Label elements

#### Pictogram:



# Signal Word: Warning

Hazard Statement:

H227 Combustible liquid.

H319 Causes serious eye irritation.

H315 Causes skin irritation. H302 Harmful if swallowed.

Precautionary Statements (Prevention):

P280 Wear protective gloves and eye protection or face protection.

P280 Wear eye protection.

P210 Keep away from heat, hot surfaces, sparks, open flames and other

ignition sources. No smoking.

P270 Do not eat, drink or smoke when using this product.
P264 Wash contaminated body parts thoroughly after handling.

Precautionary Statements (Response):

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P301 + P312 IF SWALLOWED: Call a POISON CENTER or doctor/physician if you

feel unwell.

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

P330 Rinse mouth.

P332 + P313 If skin irritation occurs: Get medical attention.
P337 + P313 If eve irritation persists: Get medical attention.

P362 + P364 Take off contaminated clothing and wash it before reuse.

P370 + P378 In case of fire: Use alcohol-resistant foam, carbon dioxide, dry powder

or water spray for extinction.

Precautionary Statements (Storage):

P403 Store in a well-ventilated place.

Precautionary Statements (Disposal):

P501 Dispose of contents/container in accordance with local regulations.

### Hazards not otherwise classified

No data available.

# 3. Composition / Information on Ingredients

# According to Regulation 2024 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

2-butoxyethanol

CAS Number: 111-76-2

Revision date: 2025/06/27 Page: 3/13 Version: 11.0 (30034845/SDS GEN US/EN)

Content (W/W): > 99.0 - < 100.0%

Synonym: 2-Butoxyethanol; Ethylene glycol monobutyl ether

# 4. First-Aid Measures

# **Description of first aid measures**

#### General advice:

Remove contaminated clothing.

#### If inhaled:

Keep patient calm, remove to fresh air, seek medical attention.

#### If on skin:

Wash thoroughly with soap and water

#### If in eyes:

Hold eyes open and rinse slowly and gently with water for 15 to 20 minutes. Remove contact lenses, if present, after first 5 minutes, then continue rinsing. Seek medical attention.

#### If swallowed:

Immediately rinse mouth and then drink 200-300 ml of water, seek medical attention.

# Most important symptoms and effects, both acute and delayed

Symptoms: Overexposure may cause:, skin irritation, irritation of respiratory tract, erythema, nausea, headache, vomiting, diarrhea, abdominal cramps, hemolysis, blood in urine, CNS depression Hazards: Skin resorption hazard.

Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11. (Further) symptoms and / or effects are not known so far

# Indication of any immediate medical attention and special treatment needed

#### Note to physician

Treatment: Treat according to symptoms (decontamination, vital functions), no

known specific antidote.

# 5. Fire-Fighting Measures

# **Extinguishing media**

Suitable extinguishing media:

dry powder, water spray, carbon dioxide, alcohol-resistant foam

Unsuitable extinguishing media for safety reasons: water jet

Additional information:

Use extinguishing measures to suit surroundings.

Revision date: 2025/06/27 Page: 4/13 Version: 11.0 (30034845/SDS GEN US/EN)

# Special hazards arising from the substance or mixture

Hazards during fire-fighting:

Flammable liquid Cool endangered containers with water-spray. See SDS section 7 - Handling and storage.

### Advice for fire-fighters

Protective equipment for fire-fighting:

Firefighters should be equipped with self-contained breathing apparatus and turn-out gear. Special protective equipment for firefighters

#### Further information:

Vapours are heavier than air and may accumulate in low areas and travel a considerable distance up to the source of ignition. If exposed to fire, keep containers cool by spraying with water. Flash fire may occur. Do not flood burning material with water due to potential spreading of fire.

#### **Impact Sensitivity:**

Remarks: Based on the chemical structure there is no shock-sensitivity.

### 6. Accidental release measures

#### Further accidental release measures:

High risk of slipping due to leakage/spillage of product.

Release of substance/product can cause fire or explosion. Shut off or stop source of leak. Shut off or stop released substance/product under safe conditions.

Pack in tightly closed containers for disposal.

#### Personal precautions, protective equipment and emergency procedures

No special precautions necessary. Extinguish sources of ignition nearby and downwind. Wear suitable personal protective clothing and equipment. Use antistatic tools. Avoid contact with skin and eyes. Ensure adequate ventilation.

### **Environmental precautions**

Do not discharge into drains/surface waters/groundwater. In case of release into waterways, immediately notify the appropriate authorities downstream of the spill so they can determine if further action is needed.

#### Methods and material for containment and cleaning up

For residues: Rinse away with water.

Spills should be contained, solidified, and placed in suitable containers for disposal.

# 7. Handling and Storage

### Precautions for safe handling

Ensure adequate ventilation. Do not apply to hot surfaces. Proper ventilation and respiratory protection is required when sanding, flame cutting, welding or brazing coated surfaces. Do not puncture, drop, or slide containers. Containers under pressure should be opened with care to release pressure.

Protection against fire and explosion:

Revision date: 2025/06/27 Page: 5/13 Version: 11.0 (30034845/SDS GEN US/EN)

Use antistatic tools. Exhaust fans should be explosion proof. Provide adequate ventilation to remove solvent vapors from lower levels or work areas and to prevent solvent contact with ignition sources. Sealed containers should be protected against heat as this results in pressure build-up. Avoid all sources of ignition: heat, sparks, open flame. Ground conductive equipment properly to prevent electrostatic discharge. Electrical handling equipment should be explosion-proof.

# Conditions for safe storage, including any incompatibilities

Store well away from other substances.

Further information on storage conditions: Avoid extreme heat. Keep away from sources of ignition - No smoking. Keep container tightly closed. Protect from direct sunlight.

Storage stability:

Storage temperature: <= 35 °C

The stability data given is only valid when stored under oxygen free inert gases or in containers that are impermeable to oxygen.

# 8. Exposure Controls/Personal Protection

### Components with occupational exposure limits

2-butoxyethanol ACGIH, US: TWA value 20 ppm;

OSHA Z1: PEL 50 ppm 240 mg/m3;

OSHA Z1: Skin Designation; The substance can be

absorbed through the skin.

NIO ID, US: IDLH 700 ppm; IDLH values based on the

1994 Revised Criteria

NIO ID, US: LEL 1.1 %;

### Advice on system design:

Provide local exhaust ventilation to maintain recommended P.E.L. Provide local exhaust ventilation to control vapours. Exhaust fans should be explosion proof.

### Personal protective equipment

#### Respiratory protection:

Wear a NIOSH-certified (or equivalent) organic vapour/particulate respirator. Do not exceed the maximum use concentration for the respirator facepiece/cartridge combination. Observe OSHA regulations for respirator use (29 CFR 1910.134).

# Hand protection:

Chemical resistant protective gloves, Consult with glove manufacturer for testing data.

#### Eye protection:

Tightly fitting safety goggles (chemical goggles). Wear face shield if splashing hazard exists.

#### **Body protection:**

Body protection must be chosen depending on activity and possible exposure, e.g. head protection, apron, protective boots, chemical-protection suit.

#### General safety and hygiene measures:

Work place should be equipped with a shower and an eye wash. Handle in accordance with good industrial hygiene and safety practice. When using, do not eat, drink or smoke.

Revision date: 2025/06/27 Page: 6/13 Version: 11.0 (30034845/SDS GEN US/EN)

# 9. Physical and Chemical Properties

Physical state: liquid
Form: liquid
Odour: ether-like
Odour threshold: not determined
Colour: colourless
pH value: (20 °C)

miscible, neutral

Melting point: -74.8 °C

Literature data.

Freezing point: -70.4 °C

Boiling point: 173.5 °C (other)

(1,013 hPa)

Flash point: 67 °C (DIN 51758, closed

cup)

Flammability: Combustible liquid. (derived from flash

point)

kinematic viscosity))

Lower explosion limit: 1.1 %(V)

For liquids not relevant for

classification and labelling. The lower explosion point may be 5 - 15 °C

below the flash point.

Upper explosion limit: 10.6 %(V)

For liquids not relevant for classification and labelling.

Heat of Combustion: 30.04 kJ/g

Autoignition: 232 °C (DIN EN 14522) Vapour pressure: 0.8 hPa (measured)

(20°C)

Literature data.

1.17 hPa (measured)

( 25 °C) Literature data.

Density: 0.9000 g/cm3 (DIN 51757)

(20 °C, 1,013 hPa)

Relative density: 0.9000

( 20 °C)

Relative vapour density: 4.08 (calculated)

(20°C)

Heavier than air.

Partitioning coefficient n- 0.81 (measured)

octanol/water (log Pow): (25 °C)

The data refers to the undissociated

form of the substance.

Self-ignition 20 °C

temperature: Based on its structural properties the

product is not classified as self-

igniting.

(20°C)

Thermal decomposition: No decomposition if stored and handled as

prescribed/indicated.

Viscosity, dynamic: 3.3 mPa.s (calculated (from

The value was determined by

calculation from the detected

kinematic viscosity.

Revision date: 2025/06/27 Page: 7/13 Version: 11.0 (30034845/SDS GEN US/EN)

Viscosity, kinematic: 3.642 mm2/s (Capilliary (20 °C) viscometer)

Solubility in water: 900 g/l

( 20 °C)

Literature data.

Solubility (qualitative): soluble

solvent(s): organic solvents,

Molecular weight: 118.18 g/mol

Evaporation rate: Value can be approximated from

Henry's Law Constant or vapor

pressure.

Particle characteristics

Particle size distribution: The substance / product is marketed or used in a non solid or granular

form.

# 10. Stability and Reactivity

## Reactivity

No hazardous reactions if stored and handled as prescribed/indicated., When heated can give off ignitable vapours.

Corrosion to metals:

No corrosive effect on metal.

Oxidizing properties:

Based on its structural properties the product is not classified as oxidizing.

Formation of Remarks: Forms no flammable gases in the

flammable gases: presence of water.

# **Chemical stability**

The product is stable if stored and handled as prescribed/indicated.

#### Possibility of hazardous reactions

The product is chemically stable.

#### Conditions to avoid

Avoid all sources of ignition: heat, sparks, open flame. Avoid extreme heat.

#### Incompatible materials

amines

### **Hazardous decomposition products**

Decomposition products:

Hazardous decomposition products: No hazardous decomposition products if stored and handled as prescribed/indicated.

Thermal decomposition:

No decomposition if stored and handled as prescribed/indicated.

Revision date: 2025/06/27 Page: 8/13 Version: 11.0 (30034845/SDS GEN US/EN)

# 11. Toxicological information

#### Primary routes of exposure

Routes of entry for solids and liquids are ingestion and inhalation, but may include eye or skin contact. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquefied gases.

# **Acute Toxicity/Effects**

### Acute toxicity

Assessment of acute toxicity: Of moderate toxicity after single ingestion. The inhalation of a highly enriched/saturated vapor-air-mixture represents an unlikely acute hazard. Virtually nontoxic after a single skin contact.

#### Information on: 2-butoxyethanol

Assessment of acute toxicity:Of moderate toxicity after single ingestion. The inhalation of a highly enriched/saturated vapor-air-mixture represents an unlikely acute hazard. Virtually nontoxic after a single skin contact.

-----

#### Oral

Type of value: LD50 Species: guinea pig

Value: 1,200 mg/kg (similar to OECD guideline 401)

#### Inhalation

Type of value: LC0 Species: guinea pig

Value: > 2.25 mg/l (similar to OECD guideline 403)

Exposure time: 4 h
The vapour was tested.

No mortality was observed. The European Union (EU) has classified this substance as 'toxic' (Cat.

3).

#### **Dermal**

Type of value: LD50 Species: guinea pig

Value: > 2,000 mg/kg (OECD Guideline 402)

#### Assessment other acute effects

Assessment of STOT single:

Based on the available information there is no specific target organ toxicity to be expected after a single exposure.

#### Irritation / corrosion

Assessment of irritating effects: Eye contact causes irritation. Skin contact causes irritation.

#### <u>Skin</u>

Species: rabbit Result: Irritant. Method: BASF-Test

Eye

Species: rabbit

Revision date: 2025/06/27 Page: 9/13 Version: 11.0 (30034845/SDS\_GEN\_US/EN)

Result: Irritant.

Method: OECD Guideline 405

#### Sensitization

Assessment of sensitization: Skin sensitizing effects were not observed in animal studies.

Guinea pig maximization test

Species: guinea pig Result: Non-sensitizing. Method: OECD Guideline 406

Aspiration Hazard not applicable

#### **Chronic Toxicity/Effects**

# Repeated dose toxicity

Assessment of repeated dose toxicity: Damages blood cells. Due to the species specific mode of action, the effects are not expected to occur in humans.

#### Genetic toxicity

Assessment of mutagenicity: The substance was not mutagenic in bacteria. The substance was not mutagenic in mammalian cell culture. The substance was not mutagenic in studies with mammals.

### Carcinogenicity

Assessment of carcinogenicity: Indication of possible carcinogenic effect in animal tests. A clear indication of an increased risk of cancer in humans has so far not been shown. IARC Group 3 (not classifiable as to human carcinogenicity).

#### Reproductive toxicity

Assessment of reproduction toxicity: The results of animal studies gave no indication of a fertility impairing effect.

#### Teratogenicity

Assessment of teratogenicity: In animal studies the substance did not cause malformations.

#### Other Information

Skin resorption hazard.

### 12. Ecological Information

### **Toxicity**

#### Aquatic toxicity

Assessment of aquatic toxicity:

There is a high probability that the product is not acutely harmful to aquatic organisms. Based on long-term (chronic) toxicity study data, the product is very likely not harmful to aquatic organisms. The inhibition of the degradation activity of activated sludge is not anticipated when introduced to biological treatment plants in appropriate low concentrations.

#### Toxicity to fish

LC50 (96 h) 1,474 mg/l, Oncorhynchus mykiss (OECD Guideline 203, static) Nominal concentration. Literature data.

#### Aquatic invertebrates

Revision date: 2025/06/27 Page: 10/13 Version: 11.0 (30034845/SDS GEN US/EN)

EC50 (48 h) 1,550 mg/l, Daphnia magna (OECD Guideline 202, part 1, static) Nominal concentration. Literature data.

#### Aquatic plants

EC50 (72 h) 1,840 mg/l (growth rate), Pseudokirchneriella subcapitata (OECD Guideline 201, static) Nominal concentration. Literature data.

# Chronic toxicity to fish

No observed effect concentration (21 d) > 100 mg/l, Brachydanio rerio (OECD Guideline 204, semistatic)

Nominal concentration. Literature data. Limit concentration test only (LIMIT test).

# Chronic toxicity to aquatic invertebrates

No observed effect concentration (21 d) 100 mg/l, Daphnia magna (OECD Guideline 211, semistatic) Nominal concentration. Literature data.

### Assessment of terrestrial toxicity

No data available concerning terrestrial toxicity.

# Microorganisms/Effect on activated sludge

#### Toxicity to microorganisms

DIN 38412 Part 8 static

bacterium/Toxic limit concentration (16 h): > 700 mg/l

Nominal concentration. Literature data.

#### Persistence and degradability

#### Assessment biodegradation and elimination (H2O)

Readily biodegradable (according to OECD criteria).

#### Elimination information

90 % CO2 formation relative to the theoretical value (28 d) (OECD 301B; ISO 9439; 92/69/EWG, C.4-C) (aerobic, activated sludge)

### Assessment of stability in water

Substance is readily biodegradable, therefore hydrolysis is not expected to be relevant.

### Bioaccumulative potential

### Assessment bioaccumulation potential

Because of the n-octanol/water distribution coefficient (log Pow) accumulation in organisms is not to be expected.

#### Bioaccumulation potential

No data available.

# Mobility in soil

### Assessment transport between environmental compartments

The substance will not evaporate into the atmosphere from the water surface. Adsorption to solid soil phase is not expected.

# Additional information

Revision date: 2025/06/27 Page: 11/13 Version: 11.0 (30034845/SDS\_GEN\_US/EN)

Adsorbable organically-bound halogen(AOX):

This product contains no organically-bound halogen.

# 13. Disposal considerations

### Waste disposal of substance:

Dispose of in accordance with national, state and local regulations. Do not incinerate closed containers. Do not discharge into drains/surface waters/groundwater.

#### Container disposal:

WARNING: Empty containers may still contain hazardous residue. Do not reuse containers without commercial reconditioning.

RCRA: D001

# 14. Transport Information

#### Land transport

**USDOT** 

Classified as combustible liquid in containers greater than 119

gallons.

Sea transport

**IMDG** 

Not classified as a dangerous good under transport regulations

Air transport IATA/ICAO

Not classified as a dangerous good under transport regulations

# 15. Regulatory Information

# **Federal Regulations**

# Registration status:

Chemical TSCA, US released / listed

**EPCRA 311/312 (Hazard categories):** Refer to SDS section 2 for GHS hazard classes applicable for this product.

**EPCRA 313:** 

<u>CAS Number</u> Chemical name 2-butoxyethanol

### **State regulations**

State RTKCAS NumberChemical nameNJ111-76-22-butoxyethanolPA111-76-22-butoxyethanol

# Safe Drinking Water & Toxic Enforcement Act, CA Prop. 65:

Revision date: 2025/06/27 Page: 12/13 Version: 11.0 (30034845/SDS GEN US/EN)

**WARNING:** This product can expose you to chemicals including ETHYLENE GLYCOL (INGESTED), which is known to the State of California to cause birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov.

NFPA Hazard codes:

Health: 2 Fire: 2 Reactivity: 0 Special:

**HMIS III rating** 

Health: 2<sup>m</sup> Flammability: 2 Physical hazard:0

### Assessment of the hazard classes according to UN GHS criteria (most recent version):

Acute Tox.4 (oral)Acute toxicityEye Irrit.2AEye irritationSkin Irrit.2Skin irritationFlam. Liq.4Flammable liquids

#### 16. Other Information

#### SDS Prepared by:

BASF NA Product Regulations SDS Prepared on: 2025/06/27

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION. DESIGNS. DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK. Date / Revised: 2025/06/27 Version: 11.0

Date / Previous version: 2024/03/29 Previous version: 10.0

Revision date: 2025/06/27 Page: 13/13 Version: 11.0 (30034845/SDS\_GEN\_US/EN)

END OF DATA SHEET