

Safety data sheet

Page: 1/13

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 27.01.2025 Version: 3.0

Date / Previous version: 02.08.2020 Previous version: 2.0

Product: Kollidon® 90 F

(ID no. 30034978/SDS_GEN_UA/EN)

Date of print 21.10.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Kollidon® 90 F

Chemical name: Polyvinylpyrrolidone

CAS Number: 9003-39-8

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses: pharmaceutical excipient

1.3. Details of the supplier of the safety data sheet

Company:
«BASF T.O.V.» LLC
139, Velyka Vasylkivska str
Kyiv
UKRAINE
03150

Telephone: +38 044 591 55 95 (96) E-mail address: basf.ukraine@basf.com

1.4. Emergency telephone number

Telephone: +49 180 22 73 11 20

0 800 30 72 72 (valid from Ukraine only !!)

Telefax number: +38 044 591 55 97

SECTION 2: Hazards Identification

2.1. Classification of the substance or mixture

According to Regulation (EC) No 1272/2008 [CLP]

No need for classification according to GHS criteria for this product.

Date / Revised: 27.01.2025 Version: 3.0

Date / Previous version: 02.08.2020 Previous version: 2.0

Product: Kollidon® 90 F

(ID no. 30034978/SDS_GEN_UA/EN)

Date of print 21.10.2025

2.2. Label elements

According to Regulation (EC) No 1272/2008 [CLP]

The product does not require a hazard warning label in accordance with GHS criteria.

2.3. Other hazards

According to Regulation (EC) No 1272/2008 [CLP]

The product is under certain conditions capable of dust explosion.

SECTION 3: Composition/Information on Ingredients

3.1. Substances

Chemical nature

2-Pyrrolidinone, 1-ethenyl-, homopolymer

CAS Number: 9003-39-8

Regulatory relevant ingredients

Formic acid

Content (W/W): > 0 % - < 1 % Flam. Liq. 3

CAS Number: 64-18-6 Acute Tox. 3 (Inhalation - vapour)

EC-Number: 200-579-1 Acute Tox. 4 (oral) INDEX-Number: 607-001-00-0 Skin Corr./Irrit. 1A Eye Dam./Irrit. 1

Substance with EU occupational H226, H314, H331, H302

EUH071

exposure limit

Specific concentration limit:

Skin Corr./Irrit. 2: 2 - < 10 % Eye Dam./Irrit. 2: 2 - < 10 % Skin Corr./Irrit. 1A: >= 90 %

Skin Corr./Irrit. 1B: 10 - < 90 %

For the classifications not written out in full in this section, including the hazard classes and the hazard statements, the full text is listed in section 16.

3.2. Mixtures

Not applicable

Date / Revised: 27.01.2025 Version: 3.0

Date / Previous version: 02.08.2020 Previous version: 2.0

Product: Kollidon® 90 F

(ID no. 30034978/SDS_GEN_UA/EN)

Date of print 21.10.2025

SECTION 4: First-Aid Measures

4.1. Description of first aid measures

Remove contaminated clothing.

If inhaled:

Keep patient calm, remove to fresh air.

On skin contact:

Wash thoroughly with soap and water

On contact with eyes:

Wash affected eyes for at least 15 minutes under running water with eyelids held open.

On ingestion:

Rinse mouth and then drink 200-300 ml of water.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms: (Further) symptoms and / or effects are not known so far

Hazards: No hazards anticipated.

4.3. Indication of any immediate medical attention and special treatment needed

Treatment: Symptomatic treatment (decontamination, vital functions).

SECTION 5: Fire-Fighting Measures

5.1. Extinguishing media

Suitable extinguishing media: foam, water spray, dry powder

5.2. Special hazards arising from the substance or mixture

Endangering substances: harmful vapours, carbon oxides, nitrogen oxides Advice: The substances/groups of substances mentioned can be released in case of fire. Dust explosion hazard.

5.3. Advice for fire-fighters

Special protective equipment:

Wear a self-contained breathing apparatus.

Further information:

Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

Date / Revised: 27.01.2025 Version: 3.0

Date / Previous version: 02.08.2020 Previous version: 2.0

Product: Kollidon® 90 F

(ID no. 30034978/SDS_GEN_UA/EN)

Date of print 21.10.2025

SECTION 6: Accidental Release Measures

Avoid the formation and build-up of dust - danger of dust explosion.

6.1. Personal precautions, protective equipment and emergency procedures

Avoid dust formation. Use personal protective clothing. Information regarding personal protective measures, see section 8.

6.2. Environmental precautions

Do not discharge into drains/surface waters/groundwater.

6.3. Methods and material for containment and cleaning up

For small amounts: Pick up with suitable appliance and dispose of.

For large amounts: Sweep/shovel up.

Dispose of absorbed material in accordance with regulations. Avoid raising dust.

6.4. Reference to other sections

Information regarding exposure controls/personal protection and disposal considerations can be found in section 8 and 13.

SECTION 7: Handling and Storage

7.1. Precautions for safe handling

Avoid dust formation. Provide exhaust ventilation if dust is formed.

Protection against fire and explosion:

The product is capable of dust explosion. Avoid dust formation. Prevent electrostatic charge - sources of ignition should be kept well clear - fire extinguishers should be kept handy. Use explosion-proof apparatus and fittings.

7.2. Conditions for safe storage, including any incompatibilities

Further information on storage conditions: Containers should be stored tightly sealed in a dry place. Protect against heat.

Storage stability:

No specific storage temperature necessary.

7.3. Specific end use(s)

For the relevant identified use(s) listed in Section 1 the advice mentioned in this section 7 is to be observed.

Date / Revised: 27.01.2025 Version: 3.0

Date / Previous version: 02.08.2020 Previous version: 2.0

Product: Kollidon® 90 F

(ID no. 30034978/SDS_GEN_UA/EN)

Date of print 21.10.2025

SECTION 8: Exposure Controls/Personal Protection

8.1. Control parameters

Components with occupational exposure limits

No substance specific occupational exposure limits known.

8.2. Exposure controls

Personal protective equipment

Respiratory protection:

Breathing protection if breathable aerosols/dust are formed. Particle filter with low efficiency for solid particles (e.g. EN 143 or 149, Type P1or FFP1)

Hand protection:

Wear chemical resistant protective gloves.

Eye protection:

Safety glasses with side-shields (frame goggles) (e.g. EN 166)

Body protection:

Body protection must be chosen based on level of activity and exposure.

General safety and hygiene measures

Handle in accordance with good industrial hygiene and safety practice. Wearing of closed work clothing is recommended. No eating, drinking, smoking or tobacco use at the place of work. Hands and/or face should be washed before breaks and at the end of the shift. Store work clothing separately.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

State of matter: solid
Form: powder
Colour: white to cream
Odour: almost odourless

Odour threshold:

not determined

melting range: >= 130 °C

The substance / product

decomposes.

Boiling point:

The product is a non-volatile solid.

Flammability: not highly flammable (other)
Lower explosion limit: 50 g/m3 (air)

For solids not relevant for classification and labelling.

Upper explosion limit:

For solids not relevant for classification and labelling.

Date / Revised: 27.01.2025 Version: 3.0

Date / Previous version: 02.08.2020 Previous version: 2.0

Product: Kollidon® 90 F

(ID no. 30034978/SDS_GEN_UA/EN)

Date of print 21.10.2025

Flash point:

not applicable

Auto-ignition temperature: 425 °C (DIN 51794)

Thermal decomposition: 170 °C (DSC (DIN 51007))

It is not a self-decompositionable substance.

SADT: Not a substance liable to self-decomposition according to UN transport

regulations, class 4.1.

pH value: 4,0 - 7,0 (Ph. Eur. 2.2.3)

(water, 50 g/l)

Viscosity, dynamic: 10.000 - 30.000 mPa.s (DIN EN ISO 2555 (RVT))

(20 %(m), 23 °C)

Solubility in water:

> 270 g/l (23 °C)

Solubility (qualitative) solvent(s): organic solvents

soluble

Partitioning coefficient n-octanol/water (log Kow):

not determined

Information on: Polyvinylpyrrolidone

Partitioning coefficient n-octanol/water (log Kow): -3,4

Vapour pressure:

not applicable

Relative density:

No data available.

Density: 1,2 g/cm3

(20 °C)

Relative vapour density (air):

The product is a non-volatile solid.

9.2. Other information

Information with regard to physical hazard classes

Explosives

Explosion hazard: Product is not explosive, however a

dust explosion could result from an

air / dust mixture.

Oxidizing properties

Fire promoting properties: not fire-propagating

Self-heating substances and mixtures

Self heating ability: It is a substance capable of (UN Test N.4 (self heating

spontaneous heating according to UN transport regulations class 4.2. Based on test results packaging <

3m3 are exempted from the

classification.

Corrosion to metals

Corrosive effects to metal are not anticipated.

substances))

Date / Revised: 27.01.2025 Version: 3.0

Date / Previous version: 02.08.2020 Previous version: 2.0

Product: Kollidon® 90 F

(ID no. 30034978/SDS_GEN_UA/EN)

Date of print 21.10.2025

Other safety characteristics

Bulk density: approx. 400 - 600 kg/m3 (DIN EN ISO 60)

Miscibility with water:

soluble

Evaporation rate:

The product is a non-volatile solid.

SECTION 10: Stability and Reactivity

10.1. Reactivity

No hazardous reactions if stored and handled as prescribed/indicated.

Corrosion to metals: Corrosive effects to metal are not anticipated.

10.2. Chemical stability

The product is stable if stored and handled as prescribed/indicated.

10.3. Possibility of hazardous reactions

Dust explosion hazard.

10.4. Conditions to avoid

Avoid dust formation. Avoid electro-static charge. Avoid all sources of ignition: heat, sparks, open flame. See SDS section 7 - Handling and storage.

10.5. Incompatible materials

Substances to avoid:

No substances known that should be avoided.

10.6. Hazardous decomposition products

Hazardous decomposition products:

No hazardous decomposition products if stored and handled as prescribed/indicated.

SECTION 11: Toxicological Information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Assessment of acute toxicity:

Virtually nontoxic after a single ingestion. Virtually nontoxic by inhalation.

Experimental/calculated data:

LD50 rat (oral): > 2.000 mg/kg (BASF-Test)

LC50 rat (by inhalation): > 5,2 mg/l 4 h (OECD Guideline 403)

Date / Revised: 27.01.2025 Version: 3.0

Date / Previous version: 02.08.2020 Previous version: 2.0

Product: Kollidon® 90 F

(ID no. 30034978/SDS_GEN_UA/EN)

Date of print 21.10.2025

Irritation

Assessment of irritating effects: Not irritating to eyes and skin.

Experimental/calculated data:

Skin corrosion/irritation

rabbit: non-irritant (Draize test) Serious eye damage/irritation rabbit: non-irritant (Draize test) Respiratory/Skin sensitization

No data available.

Germ cell mutagenicity

Assessment of mutagenicity:

The substance was not mutagenic in studies with mammals.

Carcinogenicity

Assessment of carcinogenicity:

In long-term animal studies in which the substance was given in high doses by feed, a carcinogenic effect was not observed.

Reproductive toxicity

Assessment of reproduction toxicity:

Not expected to cause reproductive toxicity (based on composition).

Developmental toxicity

Assessment of teratogenicity:

No indications of a developmental toxic / teratogenic effect were seen in animal studies.

Specific target organ toxicity (single exposure)

Assessment of STOT single:

Based on the available information there is no specific target organ toxicity to be expected after a single exposure.

Repeated dose toxicity and Specific target organ toxicity (repeated exposure)

Assessment of repeated dose toxicity:

None known

Aspiration hazard

No aspiration hazard expected.

Interactive effects

No data available.

Date / Revised: 27.01.2025 Version: 3.0

Date / Previous version: 02.08.2020 Previous version: 2.0

Product: Kollidon® 90 F

(ID no. 30034978/SDS_GEN_UA/EN)

Date of print 21.10.2025

11.2. Information on other hazards

SECTION 12: Ecological Information

12.1. Toxicity

Assessment of aquatic toxicity:

There is a high probability that the product is not acutely harmful to aquatic organisms. The inhibition of the degradation activity of activated sludge is not anticipated when introduced to biological treatment plants in appropriate low concentrations.

Toxicity to fish:

LC50 (96 h) > 10.000 mg/l, Leuciscus idus (DIN 38412 Part 15, static)

Microorganisms/Effect on activated sludge:

EC20 (0,5 h) > 1.995 mg/l, activated sludge, industrial (OECD Guideline 209, aerobic)

12.2. Persistence and degradability

Assessment biodegradation and elimination (H2O):

Poorly eliminated from water.

Information on:2-Pyrrolidinone, 1-ethenyl-, homopolymer

Elimination information:

< 10 % DOC reduction (15 d) (OECD Guideline 302 B) (aerobic, activated sludge, industrial) Poorly eliminated from water.

12.3. Bioaccumulative potential

Bioaccumulation potential:

Based on its structural properties, the polymer is not biologically available. Accumulation in organisms is not to be expected.

12.4. Mobility in soil

Assessment transport between environmental compartments: Adsorption in soil: No data available.

12.5. Results of PBT and vPvB assessment

According to Regulation (EC) No.453/2010: The product does not fulfill the criteria for PBT (Persistent/bioaccumulative/toxic) and vPvB (very persistent/very bioaccumulative).

Date / Revised: 27.01.2025 Version: 3.0

Date / Previous version: 02.08.2020 Previous version: 2.0

Product: Kollidon® 90 F

(ID no. 30034978/SDS_GEN_UA/EN)

Date of print 21.10.2025

12.6. Endocrine disrupting properties

12.7. Other adverse effects

The substance is not listed in Regulation (EC) 1005/2009 on substances that deplete the ozone layer.

Additional information

Other ecotoxicological advice:

Ecological data are determined by analogy.

SECTION 13: Disposal Considerations

13.1. Waste treatment methods

Must be sent to a suitable incineration plant, observing local regulations.

A waste code in accordance with the European waste catalog (EWC) cannot be specified, due to dependence on the usage.

Observe national and local legal requirements.

Contaminated packaging:

Uncontaminated packaging can be re-used. Packs that cannot be cleaned should be disposed of in the same manner as the contents.

SECTION 14: Transport Information

Land transport

ADR

UN number or ID number: UN3088

UN proper shipping name: SELF-HEATING SOLID, ORGANIC, N.O.S. (1-ETHENYL-2-

PYRROLIDINONE, HOMOPOLYMER)

Transport hazard class(es): 4.2
Packing group: III
Environmental hazards: no

Special precautions for Tunnel code: E

user: Not dangerous goods of class 4.2 in packages up to 3000 litres

capacity.

RID

UN number or ID number: UN3088

UN proper shipping name: SELF-HEATING SOLID, ORGANIC, N.O.S. (1-ETHENYL-2-

PYRROLIDINONE, HOMOPOLYMER)

Transport hazard class(es): 4.2

Date / Revised: 27.01.2025 Version: 3.0

Date / Previous version: 02.08.2020 Previous version: 2.0

Product: Kollidon® 90 F

(ID no. 30034978/SDS_GEN_UA/EN)

Date of print 21.10.2025

Packing group: III Environmental hazards: no

Special precautions for Not dangerous goods of class 4.2 in packages up to 3000 litres

user:

capacity.

Inland waterway transport

ADN

UN number or ID number: UN3088

UN proper shipping name: SELF-HEATING SOLID, ORGANIC, N.O.S. (1-ETHENYL-2-

PYRROLIDINONE, HOMOPOLYMER)

Transport hazard class(es): 4.2 Packing group: III Environmental hazards: no

Special precautions for Not dangerous goods of class 4.2 in packages up to 3000 litres

user: capacity.

Transport in inland waterway vessel

Not evaluated

Sea transport

IMDG

UN number or ID number: UN 3088

UN proper shipping name: SELF-HEATING SOLID, ORGANIC, N.O.S. (1-ETHENYL-2-

PYRROLIDINONE, HOMOPOLYMER)

Transport hazard class(es): 4.2 Packing group: III Environmental hazards: no

Marine pollutant: NO

Special precautions for EmS: F-A; S-J

user: Not dangerous goods of class 4.2 in packages up to 3000 litres

capacity.

Air transport

IATA/ICAO

UN number or ID number: UN 3088

UN proper shipping name: SELF-HEATING SOLID, ORGANIC, N.O.S. (1-ETHENYL-2-

PYRROLIDINONE, HOMOPOLYMER)

Date / Revised: 27.01.2025 Version: 3.0

Date / Previous version: 02.08.2020 Previous version: 2.0

Product: Kollidon® 90 F

(ID no. 30034978/SDS_GEN_UA/EN)

Date of print 21.10.2025

Transport hazard class(es): 4.2 Packing group: III

Environmental hazards: No Mark as dangerous for the environment is needed

Special precautions for Not dangerous goods of class 4.2 in packages up to 3000 litres

user: capacity.

14.1. UN number or ID number

See corresponding entries for "UN number or ID number" for the respective regulations in the tables above.

14.2. UN proper shipping name

See corresponding entries for "UN proper shipping name" for the respective regulations in the tables above.

14.3. Transport hazard class(es)

See corresponding entries for "Transport hazard class(es)" for the respective regulations in the tables above.

14.4. Packing group

See corresponding entries for "Packing group" for the respective regulations in the tables above.

14.5. Environmental hazards

See corresponding entries for "Environmental hazards" for the respective regulations in the tables above.

14.6. Special precautions for user

See corresponding entries for "Special precautions for user" for the respective regulations in the tables above.

14.7. Maritime transport in bulk according to IMO instruments

Maritime transport in bulk is not intended.

Further information

Not dangerous goods of class 4.2 in packages up to 3000 litres capacity.

SECTION 15: Regulatory Information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

If other regulatory information applies that is not already provided elsewhere in this safety data sheet, then it is described in this subsection.

Date / Revised: 27.01.2025 Version: 3.0

Date / Previous version: 02.08.2020 Previous version: 2.0

Product: Kollidon® 90 F

(ID no. 30034978/SDS GEN UA/EN)

Date of print 21.10.2025

SECTION 16: Other Information

Any other intended applications should be discussed with the manufacturer. Corresponding occupational protection measurements must be followed.

<u>Full text of the classifications, including the hazard classes and the hazard statements, if mentioned in section 2 or 3:</u>

Flam. Liq. Flammable liquids
Acute Tox. Acute toxicity

Skin Corr./Irrit. Skin corrosion/irritation

Eye Dam./Irrit. Serious eye damage/eye irritation H226 Flammable liquid and vapour.

H314 Causes severe skin burns and eye damage.

H331 Toxic if inhaled. H302 Harmful if swallowed.

EUH071 Corrosive to the respiratory tract.

Abbreviations

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road. ADN = The European Agreement concerning the International Carriage of Dangerous Goods by Inland waterways. ATE = Acute Toxicity Estimates. CAO = Cargo Aircraft Only. CAS = Chemical Abstract Service. CLP = Classification, Labelling and Packaging of substances and mixtures. DIN = German national organization for standardization. DNEL = Derived No Effect Level. EC50 = Effective concentration median for 50% of the population. EC = European Community. EN = European Standards. IARC = International Agency for Research on Cancer, IATA = International Air Transport Association. IBC-Code = Intermediate Bulk Container code. IMDG = International Maritime Dangerous Goods Code. ISO = International Organization for Standardization. STEL = Short-Term Exposure Limit. LC50 = Lethal concentration median for 50% of the population. LD50 = Lethal dose median for 50% of the population. TLV = Threshold Limit Value. MARPOL = The International Convention for the Prevention of Pollution from Ships. NEN = Dutch Norm. NOEC = No Observed Effect Concentration. OEL = Occupational Exposure Limit. OECD = Organization for Economic Cooperation and Development. PBT = Persistent, Bioaccumulative and Toxic. PNEC = Predicted No Effect Level. PPM = Parts per million. RID = The European Agreement concerning the International Carriage of Dangerous Goods by Rail. TWA = Time Weight Average. UN-number = UN number at transport. vPvB = very Persistent and very Bioaccumulative.

The data contained in this safety data sheet are based on our current knowledge and experience and describe the product only with regard to safety requirements. This safety data sheet is neither a Certificate of Analysis (CoA) nor technical data sheet and shall not be mistaken for a specification agreement. Identified uses in this safety data sheet do neither represent an agreement on the corresponding contractual quality of the substance/mixture nor a contractually designated use. It is the responsibility of the recipient of the product to ensure any proprietary rights and existing laws and legislation are observed.

Vertical lines in the left hand margin indicate an amendment from the previous version.