

Acronal® S 504 na

Acronal S 504 na is a versatile dispersion used as the base polymer for paper strengthening via saturation, and also finds utility as a binder in adhesive applications.

Chemical nature Acrylic dispersion containing styrene and acrylonitrile

Properties

Typical PropertiesSolids content
% ~ 50.0
pH value
~ 7.5

Viscosity at 23 °C cps ~ 350 – 950

(Brookfield RV, Spindle #2, at 20 rpm)

Further properties of Density g/cm³ approx. 1.04

the dispersion Freeze/thaw resistance not resistant to freezing

Dispersion type anionic

Properties of the film

Appearance clear, transparent

Flexible yes Surface tack-free

Compatible with

General Acronal S 504 na is compatible with a wide range of materials, including those commonly used in

coating colors

Polymer dispersions Anionic dispersions and those containing a protective colloid

Thickeners Rheovis® AS 1125

Pigments Adhesives can be colored with the water-dispersable Dispers® or Luconyl® preparations

Application

Features Acronal S 504 na is used in a wide variety of applications as it is flexible, yet strong. It exhibits good

water resistance. It has utility in paper saturation, print coating and other applications where high

filler acceptance is needed. It also exhibits strong adhesion to metal, paint, and wood.

Processing When Acronal S 504 na is mixed with other materials, the final mixture should be adjusted to

pH > 6, which increases the mechanical stability.

Safety

General The usual safety precautions when handling chemicals must be observed. These include the

measures described in Federal, State and Local health and safety regulations, thorough ventilation

of the workplace, good skin care and wearing of protective goggles.

Safety Data Sheet All safety information is provided in the Safety Data Sheet for Acronal S 504 na.

Storage

Please refer to the "Handling and Storage of Polymer Dispersions" brochure.

Important

WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, THEY ARE PROVIDED FOR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, BASF RECOMMENDS THAT THE READER MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR A PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESCRIPTIONS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF BASE'S TERMS AND CONDITIONS OF SALE, FURTHER, THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY BASF HEREUNDER ARE GIVEN GRATIS AND BASF ASSUMES NO OBLIGATION OR LIABILITY FOR THE DESCRIPTIONS, DESIGNS, DATA OR INFORMATION GIVEN OR RESULTS OBTAINED. ALL SUCH BEING GIVEN AND ACCEPTED AT THE READER'S RISK.

Acronal is a registered trademark of BASF Group.

© BASF Corporation, 2024



BASF Corporation is fully committed to the Responsible Care® initiative in the USA, Canada, and Mexico. For more information on Responsible Care® go to: U.S.: www.basf.us/responsiblecare_usa Canada: www.basf.us/responsiblecare_canada México: www.basf.us/responsiblecare mexico

BASF Corporation

Dispersions and Resins 11501 Steele Creek Road Charlotte, North Carolina 28273 Phone: (800) 251 – 0612 Email: CustCare-Charlotte@basf.com www.basf.us/dpsolutions

November 2024 Rev 6