1. Identification

Product identifier used on the label

SOLVENON® PM

Recommended use of the chemical and restriction on use

Recommended use*: solvent(s)
Recommended use*: industrial chemicals
Unsuitable for use: Not intended for sale to or use by the general public.

* The “Recommended use” identified for this product is provided solely to comply with a Federal requirement and is not part of the seller's published specification. The terms of this Safety Data Sheet (SDS) do not create or infer any warranty, express or implied, including by incorporation into or reference in the seller's sales agreement.

Details of the supplier of the safety data sheet

Company:
BASF Mexicana S.A. de C.V.
Av. Insurgentes Sur 975
Col. CD. De Los Deportes,
C.P. 03710 Ciudad de México
MÉXICO

Telephone: +52 55 5325 2600

Emergency telephone number

24 Hour Emergency Response Information
SETIQ: 1800-00-214-(Rep. Mexicana) or 55-59-15-88 (CDMX)
Telephone: +1-800-849-5204 or +1-833-229-1000

Other means of identification

Molecular formula: C4H10O2
Synonyms: 1-METHOXYPROPAN-2-OL

2. Hazards Identification

According to Regulation NOM-018-STPS-2015

Classification of the product

Flam. Liq.	3	Flammable liquids

Repr.	1B (unborn child)	Reproductive toxicity
STOT SE	3 (Vapours may cause drowsiness and dizziness.)	Specific target organ toxicity — single exposure

Label elements

Pictogram:

Signal Word:
Danger

Hazard Statement:

H226	Flammable liquid and vapour.
H336	May cause drowsiness or dizziness.
H360	May damage the unborn child.

Precautionary Statements (Prevention):

P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves, protective clothing and eye protection or face protection.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P201	Obtain special instructions before use.
P261	Avoid breathing mist or vapour or spray.
P243	Take action to prevent static discharges.
P202	Do not handle until all safety precautions have been read and understood.
P241	Use explosion-proof electrical, ventilating and lighting equipment.
P240	Ground and bond container and receiving equipment.
P242	Use non-sparking tools.

Precautionary Statements (Response):

P312	Call a POISON CENTER or physician if you feel unwell.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P308 + P313	IF exposed or concerned: Get medical attention.
P370 + P378	In case of fire: Use alcohol-resistant foam, carbon dioxide, dry powder or water spray for extinction.

Precautionary Statements (Storage):

P233	Keep container tightly closed.
P403 + P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.

Precautionary Statements (Disposal):

P501	Dispose of contents/container in accordance with local regulations.

Hazards not otherwise classified

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.
See section 12 - Results of PBT and vPvB assessment.

3. Composition / Information on Ingredients

According to Regulation NOM-018-STPS-2015

1-methoxypropan-2-ol
CAS Number: 107-98-2
Content (W/W): >= 99.5 - <= 100.0%
Synonym: 1-Methoxy-2-propanol; Propylene glycol monomethyl ether

2-methoxypropanol
CAS Number: 1589-47-5
Content (W/W): >= 0.0 - < 0.3%
Synonym: 2-Methoxypropanol

4. First-Aid Measures

Description of first aid measures

General advice:
First aid personnel should pay attention to their own safety. If the patient is likely to become unconscious, place and transport in stable sideways position (recovery position). Immediately remove contaminated clothing.

If inhaled:
Keep patient calm, remove to fresh air, seek medical attention.

If on skin:
Wash thoroughly with soap and water

If in eyes:
Wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.

If swallowed:
Immediately rinse mouth and then drink 200-300 ml of water, seek medical attention.

Most important symptoms and effects, both acute and delayed

Symptoms: Overexposure may cause:, lacrimation
Hazards: Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11. (Further) symptoms and / or effects are not known so far

Indication of any immediate medical attention and special treatment needed

Note to physician
Treatment: Treat according to symptoms (decontamination, vital functions), no known specific antidote.

5. Fire-Fighting Measures

Extinguishing media

Suitable extinguishing media:
dry powder, water spray, carbon dioxide, alcohol-resistant foam

Unsuitable extinguishing media for safety reasons:
water jet

Additional information:
Use extinguishing measures to suit surroundings.

Special hazards arising from the substance or mixture

Hazards during fire-fighting:
Flammable liquid Cool endangered containers with water-spray. See SDS section 7 - Handling and storage.

Advice for fire-fighters

Protective equipment for fire-fighting:
Wear a self-contained breathing apparatus. Special protective equipment for firefighters

Further information:
Evacuate area of all unnecessary personnel. Fight fire from maximum distance.

Extend fire extinguishing measures to the surroundings. Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

Impact Sensitivity:
Remarks: Based on the chemical structure there is no shock-sensitivity.

6. Accidental release measures

Further accidental release measures:
High risk of slipping due to leakage/spillage of product.

Release of substance/product can cause fire or explosion. Shut off or stop source of leak. Shut off or stop released substance/product under safe conditions.

Pack in tightly closed containers for disposal.

Personal precautions, protective equipment and emergency procedures

Handle in accordance with good industrial hygiene and safety practice.

Avoid all sources of ignition: heat, sparks, open flame. Use antistatic tools.

Environmental precautions

Discharge into the environment must be avoided. Collect contaminated washing water for appropriate disposal.

Methods and material for containment and cleaning up

Pick up with suitable appliance and dispose of. Spills should be contained, solidified, and placed in suitable containers for disposal. Dispose of absorbed material in accordance with regulations.

7. Handling and Storage

Precautions for safe handling

Handle in accordance with good industrial hygiene and safety practice.

Protection against fire and explosion:
Avoid all sources of ignition: heat, sparks, open flame. Ground all transfer equipment properly to prevent electrostatic discharge.

Conditions for safe storage, including any incompatibilities

Further information on storage conditions: Keep container tightly closed and dry; store in a cool place.

8. Exposure Controls/Personal Protection

Components with occupational exposure limits

1-methoxypropan-2-ol	OEL, MX:	TWA value 100 ppm ;
	OEL, MX:	STEL value 150 ppm ;

Advice on system design:
Provide local exhaust ventilation to control vapours/mists.

Personal protective equipment

Respiratory protection:
Gas filter for gases/vapours of organic compounds (boiling point >65 °C, e. g. EN 14387 Type A)

Hand protection:
Chemical resistant protective gloves (EN ISO 374-1), Suitable materials also with prolonged, direct contact (Recommended: Protective index 6, corresponding > 480 minutes of permeation time according to EN ISO 374-1):, butyl rubber (butyl) - 0.7 mm coating thickness, Manufacturer's directions for use should be observed because of great diversity of types., Supplementary note: The specifications are based on tests, literature data and information of glove manufacturers or are derived from similar substances by analogy. Due to many conditions (e.g. temperature) it must be considered, that the practical usage of a chemical-protective glove in practice may be much shorter than the permeation time determined through testing.

Eye protection:
Safety glasses with side-shields (frame goggles) (e.g. EN 166)

Body protection:
Body protection must be chosen depending on activity and possible exposure, e.g. apron, protecting boots, chemical-protection suit (according to EN 14605 in case of splashes or EN ISO 13982 in case of dust).

General safety and hygiene measures:
Handle in accordance with good industrial hygiene and safety practice. Wearing of closed work clothing is required additionally to the stated personal protection equipment.

9. Physical and Chemical Properties

Form:	liquid	
Odour:	mild, alcohol-like	
Odour threshold:	not determined	
Colour:	colourless	
pH value:	(20 °C) soluble, neutral	
Melting point:	-95 °C (1,013 hPa) Literature data.	(other)
Freezing point:	No data available.	
Boiling point:	119.8 °C (1,013 hPa)	(other)
Boiling range:	No data available.	
Flash point:	31.5 °C	(DIN 51755, closed cup)
Flammability:	Flammable liquid and vapour.	(derived from flash - and boiling point)
Lower explosion limit:	1.7 %(V) (27 °C) The lower explosion point of the substance/mixture has been determined. The explosion point describes the temperature of a flammable liquid at which the concentration of the saturated vapour mixed with air equals the lower explosion limit.	(air)
Upper explosion limit:	For liquids not relevant for classification and labelling.	
Autoignition:	287 °C	(Directive 92/69/EEC, A.15)
Vapour pressure:	17.1 hPa (25.1 °C) dynamic	(measured)
Density:	0.92 g/cm3 (20 °C, 1,013 hPa)	(DIN 51757)
Relative density:	0.92 (20 °C)	
Vapour density:	3.1 (20 °C) Heavier than air.	(calculated)
Partitioning coefficient n-octanol/water (log Pow):	-0.43 (25 °C) Literature data.	(measured)
Self-ignition temperature:	20 °C Based on its structural properties the product is not classified as self-igniting.	
Thermal decomposition:	No data available.	

Viscosity, dynamic:	1.81 mPa.s (20 °C) Literature data.
Solubility in water:	(20 °C) Literature data., miscible
Solubility (qualitative):	soluble solvent(s): organic solvents,
Molar mass:	90.12 g/mol
Evaporation rate:	Value can be approximated from Henry's Law Constant or vapor pressure.

10. Stability and Reactivity

Reactivity
When heated can give off ignitable vapours.

Corrosion to metals:
No corrosive effect on metal.

Oxidizing properties:
Based on its structural properties the product is not classified as oxidizing.

Formation of flammable gases:	Remarks:	Forms no flammable gases in the presence of water.

Chemical stability
The product is stable if stored and handled as prescribed/indicated.

Possibility of hazardous reactions
Reacts with strong oxidizing agents.

Conditions to avoid
Avoid extreme heat. Avoid sources of ignition.

Incompatible materials
strong oxidizing agents

Hazardous decomposition products

Decomposition products:
Hazardous decomposition products: No hazardous decomposition products if stored and handled as prescribed/indicated.

Thermal decomposition:
No data available.

11. Toxicological information

Primary routes of exposure

Routes of entry for solids and liquids are ingestion and inhalation, but may include eye or skin contact. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquefied gases.

Acute Toxicity/Effects

Acute toxicity
Assessment of acute toxicity: Of low toxicity after single ingestion. Virtually nontoxic by inhalation. Virtually nontoxic after a single skin contact.

Oral
Type of value: LD50
Species: rat (male/female)
Value: 4,016 mg/kg (similar to OECD guideline 401)

Inhalation
Type of value: LC0
Species: rat
Value: (similar to OECD guideline 403)
Exposure time: 6 h
The vapour was tested.

Dermal
Type of value: LD50
Species: rat
Value: > 2,000 mg/kg (similar to OECD guideline 402)

Assessment other acute effects
Assessment of STOT single:
Possible narcotic effects (drowsiness or dizziness).

Irritation / corrosion
Assessment of irritating effects: Not irritating to the skin. Not irritating to the eyes.

Skin
Species: rabbit
Result: non-irritant
Method: similar to OECD guideline 404

Eye
Species: rabbit
Result: non-irritant
Method: similar to OECD guideline 405

Sensitization
Assessment of sensitization: Skin sensitizing effects were not observed in animal studies.

Species: guinea pig
Result: Non-sensitizing.
Method: other

Aspiration Hazard
not applicable

Chronic Toxicity/Effects

Repeated dose toxicity

Assessment of repeated dose toxicity: May affect the liver as indicated in animal studies. The substance may cause damage to the kidney after repeated inhalation. Effect found in rodents only. The relevance to humans is questionable.

Genetic toxicity
Assessment of mutagenicity: The substance was not mutagenic in bacteria. The substance was not mutagenic in mammalian cell culture. The substance was not mutagenic in a test with mammals.
Genetic toxicity in vitro: similar to OECD guideline 471 Ames-test with and without metabolic activation negative
similar to OECD guideline 473 Chromosomal Aberration Test CHO cells:with and without metabolic activation negative
similar to OECD guideline 476 Mammalian cell gene mutation assay V79 cells:without metabolic activation negative

Carcinogenicity
Assessment of carcinogenicity: In long-term studies in rats and mice in which the substance was given by inhalation, a carcinogenic effect was not observed.

Reproductive toxicity
Assessment of reproduction toxicity: The potential to impair fertility cannot be excluded when given at maternally toxic doses.

Teratogenicity
Assessment of teratogenicity: No indications of a developmental toxic / teratogenic effect were seen in animal studies.

Information on: 2-methoxypropanol
Assessment of teratogenicity: Indications of possible developmental toxicity/teratogenicity were seen in animal studies.

Experiences in humans
High concentrations have a narcotizing effect.

12. Ecological Information

Toxicity

Aquatic toxicity
Assessment of aquatic toxicity:
There is a high probability that the product is not acutely harmful to aquatic organisms. The inhibition of the degradation activity of activated sludge is not anticipated when introduced to biological treatment plants in appropriate low concentrations.

Toxicity to fish
LC50 (96 h) > 6,800 mg/l, Leuciscus idus (DIN 38412 Part 15, static)
Nominal concentration.

Aquatic invertebrates
LC50 (48 h) 23,300 mg/l, Daphnia magna (Daphnia test acute, static)
Nominal concentration.

Aquatic plants
EC50 (7 d) > 1,000 mg/l (growth rate), Pseudokirchneriella subcapitata (Algal growth inhibition test)

Nominal concentration.

Chronic toxicity to fish
No data available.

Chronic toxicity to aquatic invertebrates
No data available.

Microorganisms/Effect on activated sludge

Toxicity to microorganisms
OECD Guideline 209 activated sludge, domestic/EC50 (3 h): > 1,000 mg/l
Nominal concentration. Literature data.

Persistence and degradability

Assessment biodegradation and elimination (H2O)
Readily biodegradable (according to OECD criteria).

Elimination information

90 - 100 % DOC reduction (28 d) (OECD 301E/92/69/EWG, C.4-B) (aerobic, municipal sewage treatment plant effluent)

Assessment of stability in water
According to structural properties, hydrolysis is not expected/probable.
The product has not been tested. The statement has been derived from the structure of the product.

Information on Stability in Water (Hydrolysis)
According to structural properties, hydrolysis is not expected/probable.

Bioaccumulative potential

Assessment bioaccumulation potential
Because of the n-octanol/water distribution coefficient (log Pow) accumulation in organisms is not to be expected.

Bioaccumulation potential
No data available.

Mobility in soil

Assessment transport between environmental compartments
The substance will not evaporate into the atmosphere from the water surface.
Adsorption to solid soil phase is not expected.

Additional information

Adsorbable organically-bound halogen(AOX):
This product contains no organically-bound halogen.

Other ecotoxicological advice:
Inhibition of degradation activity in activated sludge is not to be anticipated during correct introduction of low concentrations.

13. Disposal considerations

Waste disposal of substance:
Dispose of in accordance with national, state and local regulations.

14. Transport Information

Land transport
TDG

Hazard class:	3
Packing group:	III
ID number:	UN 3092
Hazard label:	3
Proper shipping name:	1-METHOXY-2-PROPANOL

Sea transport
IMDG

Hazard class:	3
Packing group:	III
ID number:	UN 3092
Hazard label:	3
Marine pollutant:	NO
Proper shipping name:	1-METHOXY-2-PROPANOL

Air transport
IATA/ICAO

Hazard class:	3
Packing group:	III
ID number:	UN 3092
Hazard label:	3
Proper shipping name:	1-METHOXY-2-PROPANOL

15. Regulatory Information

Federal Regulations

Not applicable

NFPA Hazard codes:
Health: 1 Fire: 3 Reactivity: 0 Special:

HMIS III rating
Health: 1 Flammability: 3 Physical hazard: 0

Assessment of the hazard classes according to UN GHS criteria (most recent version):

STOT SE	3 (Vapours may cause drowsiness and dizziness.)	Specific target organ toxicity — single exposure

Flam. Liq.	3	Flammable liquids
Acute Tox.	5 (oral)	Acute toxicity

16. Other Information

SDS Prepared by:
BASF NA Product Regulations
SDS Prepared on: 2023/10/06

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.