

Revision date: 2025/08/06 Page: 1/11
Version: 6.0 (30041184/SDS GEN MX/EN)

## 1. Identification

## Product identifier used on the label

## Lutavit® Calpan 98%

## Recommended use of the chemical and restriction on use

Recommended use\*: feed additive(s)

Unsuitable for use: Not intended for sale to or use by the general public.

## Details of the supplier of the safety data sheet

#### Company:

BASF Mexicana S.A. de C.V. Av. Insurgentes Sur 975 Col. CD. De Los Deportes, C.P. 03710 Ciudad de México MÉXICO

Telephone: +52 55 5325 2600

## **Emergency telephone number**

24 Hour Emergency Response Information

SETIQ: 1800-00-214-(Rep. Mexicana) or 55-59-15-88 (CDMX)

Telephone: +1-800-849-5204 or +1-833-229-1000

Other means of identification

Synonyms: Calcium pantothenate, D-form

## 2. Hazards Identification

## **According to Regulation NOM-018-STPS-2015**

## Classification of the product

Combustible Dust Combustible Dust (1) Combustible Dust

## Label elements

<sup>\*</sup> The "Recommended use" identified for this product is provided solely to comply with a Federal requirement and is not part of the seller's published specification. The terms of this Safety Data Sheet (SDS) do not create or infer any warranty, express or implied, including by incorporation into or reference in the seller's sales agreement.

Lutavit® Calpan 98%

Revision date: 2025/08/06 Page: 2/11
Version: 6.0 (30041184/SDS\_GEN\_MX/EN)

Signal Word: Warning

vvarning

Hazard Statement:

May form combustible dust concentration in air.

## Hazards not otherwise classified

The product is under certain conditions capable of dust explosion.

## 3. Composition / Information on Ingredients

## According to Regulation NOM-018-STPS-2015

Under the referenced regulation, this product does not contain any components classified for health hazards above the relevant cut off value.

## 4. First-Aid Measures

## **Description of first aid measures**

#### General advice:

Remove contaminated clothing.

## If inhaled:

Keep patient calm, remove to fresh air.

#### If on skin:

Wash thoroughly with soap and water

## If in eyes:

Wash affected eyes for at least 15 minutes under running water with eyelids held open.

#### If swallowed:

Rinse mouth and then drink 200-300 ml of water.

## Most important symptoms and effects, both acute and delayed

Symptoms: No applicable information available.

## Indication of any immediate medical attention and special treatment needed

Note to physician

Treatment: Symptomatic treatment (decontamination, vital functions).

## 5. Fire-Fighting Measures

## **Extinguishing media**

Revision date: 2025/08/06 Page: 3/11 Version: 6.0 (30041184/SDS\_GEN\_MX/EN)

Suitable extinguishing media: water spray, foam, dry powder, carbon dioxide

Unsuitable extinguishing media for safety reasons: water jet

Additional information:

Avoid whirling up the material/product because of the danger of dust explosion.

## Special hazards arising from the substance or mixture

Hazards during fire-fighting:

harmful vapours, carbon oxides, nitrogen oxides

The substances/groups of substances mentioned can be released in case of fire. Burning produces harmful and toxic fumes. Dust explosion hazard.

Dust explosion hazard.

## Advice for fire-fighters

Protective equipment for fire-fighting:

Wear a self-contained breathing apparatus.

#### **Further information:**

Dust can form an explosive mixture with air. Dispose of fire debris and contaminated extinguishing water in accordance with official regulations. Cool endangered containers with water-spray.

Dusty conditions may ignite explosively in the presence of an ignition source causing flash fire.

## 6. Accidental release measures

## Further accidental release measures:

Avoid dispersal of dust in the air (e.g. by clearing dusty surfaces with compressed air). Avoid the formation and build-up of dust - danger of dust explosion. Dust in sufficient concentration can result in an explosive mixture in air. Handle to minimize dusting and eliminate open flame and other sources of ignition.

## Personal precautions, protective equipment and emergency procedures

Avoid dust formation. Information regarding personal protective measures, see section 8. Use personal protective clothing.

## **Environmental precautions**

Do not discharge into drains/surface waters/groundwater.

## Methods and material for containment and cleaning up

For small amounts: Contain with dust binding material and dispose of.

For large amounts: Sweep/shovel up.

Dispose of absorbed material in accordance with regulations. Avoid raising dust.

Nonsparking tools should be used.

Lutavit® Calpan 98%

Revision date: 2025/08/06 Page: 4/11 Version: 6.0 (30041184/SDS\_GEN\_MX/EN)

## 7. Handling and Storage

## Precautions for safe handling

Avoid dust formation. Provide exhaust ventilation if dust is formed.

Protection against fire and explosion:

Avoid dust formation. Dust in sufficient concentration can result in an explosive mixture in air. Handle to minimize dusting and eliminate open flame and other sources of ignition. Routine housekeeping should be instituted to ensure that dusts do not accumulate on surfaces. Dry powders can build static electricity charges when subjected to the friction of transfer and mixing operations. Provide adequate precautions, such as electrical grounding and bonding, or inert atmospheres. Refer to NFPA 660 (2025) Standard for Combustible Dust and Particulate Solids. NFPA 660 is a combination of Standards NFPA 61 (Agriculture and Food), NFPA 484 (Metals), NFPA 652 (Fundamentals of Combustible Dusts), NFPA 654 (Standard for the Prevention of Fire and Dust Explosions from the Manufacturing, Processing, and Handling of Combustible Particulate Solids), NFPA 65 (Sulfur), and NFPA 664 (Woodworking/Processing). Consult NFPA 660 standard for relevant commodity-specific and general safety information.

## Conditions for safe storage, including any incompatibilities

Suitable materials for containers: Low density polyethylene (LDPE), Galvanized carbon steel (Zinc), Stainless steel 1.4301 (V2), Stainless steel 1.4401, glass, Paper/Fibreboard, High density polyethylene (HDPE), Aluminium, tinned carbon steel (Tinplate), Carbon steel (Iron)

Further information on storage conditions: Keep container tightly closed and dry; store in a cool place.

## 8. Exposure Controls/Personal Protection

No substance specific occupational exposure limits known.

## Advice on system design:

Provide local exhaust ventilation to control dust.

It is recommended that all dust control equipment such as local exhaust ventilation and material transport systems involved in handling of this product contain explosion relief vents or an explosion suppression system or an oxygen deficient environment. Ensure that dust-handling systems (such as exhaust ducts, dust collectors, vessels, and processing equipment) are designed in a manner to prevent the escape of dust into the work area (i.e., there is no leakage from the equipment). Use only appropriately classified electrical equipment and powered industrial trucks.

## Personal protective equipment

## Respiratory protection:

Wear a NIOSH-certified (or equivalent) particulate respirator.

#### Hand protection:

Wear impermeable chemical resistant protective gloves.

## Eye protection:

Wear safety goggles (chemical goggles) if there is potential for airborne dust exposures.

## **Body protection:**

Body protection must be chosen based on level of activity and exposure.

Revision date: 2025/08/06 Page: 5/11

Version: 6.0 (30041184/SDS\_GEN\_MX/EN)

## General safety and hygiene measures:

Handle in accordance with good industrial hygiene and safety practice. Wearing of closed work clothing is recommended. Avoid inhalation of dusts. Wash thoroughly after handling.

## 9. Physical and Chemical Properties

Physical state: solid Form: granules

Odour: almost odourless
Odour threshold: not applicable

Colour: white pH value: 6.5 - 9.5

(50 g/l, 20 °C)
Melting temperature: approx. 190 °C
Freezing point: No data available.

Freezing point: No data decomposition point: 195 °C

(1,013 hPa) Decomposes on

heating.

Flash point: not applicable, the product is a solid

Flammability: not highly flammable (UN Test N.1 (ready combustible solids))

Lower explosion limit: For solids not relevant for

classification and labelling.

Upper explosion limit: For solids not relevant for

classification and labelling.

Autoignition: 430 °C (VDI 2263, sheet 1, 2.6 (May 1990))

SADT: No data available.

Vapour pressure: not applicable

Density: 1.162 g/cm3
( 25 °C)

Relative density: No data available. Bulk density: approx. 600 kg/m3

Relative vapour density: The product is a non-volatile solid.

Partitioning coefficient n- -3.9

octanol/water (log Pow): (25 °C)
Self-ignition not self-igniting

temperature:

430 °C (VDI 2263, sheet 1, 2.6 (May 1990))

(measured)

Thermal decomposition: >= 130 °C (DSC (DIN 51007))
Viscosity, dynamic: not applicable, the product is a solid

Viscosity, kinematic: No data available.

Solubility in water: (20 °C)

soluble, clear

Solubility (qualitative): soluble

solvent(s): organic solvents,

Molecular weight: not applicable

Evaporation rate: The product is a non-volatile solid.

Particle characteristics

No applicable information available.

## **Lutavit® Calpan 98%**

Revision date: 2025/08/06 Page: 6/11 Version: 6.0 (30041184/SDS\_GEN\_MX/EN)

## 10. Stability and Reactivity

## Reactivity

No hazardous reactions if stored and handled as prescribed/indicated.

Corrosion to metals:

Corrosive effects to metal are not anticipated.

Oxidizing properties:

Based on its structural properties the product is not classified as oxidizing.

Minimum ignition energy:

(VDI 2263, sheet 1, 2.5 (May 1990)) The product is capable of dust explosion.

Formation of Remarks: Forms no flammable gases in the

flammable gases: presence of water.

## **Chemical stability**

The product is stable if stored and handled as prescribed/indicated.

Peroxides: The product does not contain peroxides.

## Possibility of hazardous reactions

Dust explosion hazard.

## Conditions to avoid

Avoid dust formation. Avoid electro-static discharge. Avoid all sources of ignition: heat, sparks, open flame.

#### **Incompatible materials**

None known during use and storage if used according to instructions.

## Hazardous decomposition products

Decomposition products:

Hazardous decomposition products: No hazardous decomposition products if stored and handled as prescribed/indicated.

Thermal decomposition:

>= 130 °C (DSC (DIN 51007))

## 11. Toxicological information

## Primary routes of exposure

Routes of entry for solids and liquids are ingestion and inhalation, but may include eye or skin contact. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquefied gases.

## **Acute Toxicity/Effects**

**Acute toxicity** 

**Lutavit® Calpan 98%** 

Revision date: 2025/08/06 Page: 7/11
Version: 6.0 (30041184/SDS\_GEN\_MX/EN)

Assessment of acute toxicity: Virtually nontoxic after a single ingestion. Virtually nontoxic by inhalation.

Oral

Type of value: LD50 Species: rat (male/female)

Value: > 5,000 mg/kg (BASF-Test)

Inhalation

Type of value: LC0

Species: rat (male/female) Value: 2.14 mg/l (IRT) Exposure time: 7 h Tested as dust aerosol.

Inhalation-risk test (IRT): No mortality within 7 hours as shown in animal studies. The inhalation of a

highly saturated vapor-air mixture represents no acute hazard.

Type of value: LC50

Species: rat

Value: > 5.2 mg/l (OECD Guideline 403)

Exposure time: 4 h

no data

**Dermal** 

No data available.

## Assessment other acute effects

Assessment of STOT single:

Based on the available information there is no specific target organ toxicity to be expected after a single exposure.

## <u>Irritation / corrosion</u>

Assessment of irritating effects: Not irritating to eyes and skin.

Skin

Species: rabbit Result: non-irritant Method: Draize test

Eye

Species: rabbit Result: non-irritant Method: Draize test

## **Sensitization**

Assessment of sensitization: No sensitizing effect.

Guinea pig maximization test

Species: guinea pig Result: Non-sensitizing.

Method: other

## **Aspiration Hazard**

No aspiration hazard expected.

## Lutavit® Calpan 98%

Revision date: 2025/08/06 Page: 8/11 Version: 6.0 (30041184/SDS GEN MX/EN)

## **Chronic Toxicity/Effects**

## Repeated dose toxicity

Assessment of repeated dose toxicity: Based on available data, the classification criteria are not met.

## **Genetic toxicity**

Assessment of mutagenicity: Based on available data, the classification criteria are not met.

## Carcinogenicity

Assessment of carcinogenicity: Not classified, due to lack of data.

#### Reproductive toxicity

Assessment of reproduction toxicity: Based on available data, the classification criteria are not met.

## **Teratogenicity**

Assessment of teratogenicity: Not classified, due to lack of data.

## 12. Ecological Information

## **Toxicity**

## Aquatic toxicity

Assessment of aquatic toxicity:

There is a high probability that the product is not acutely harmful to aquatic organisms. Depending on local conditions and existing concentrations, disturbances in the biodegradation process of activated sludge are possible.

## Toxicity to fish

LC50 (96 h) > 10,000 mg/l, Leuciscus idus (DIN 38412 Part 15, static)

The details of the toxic effect relate to the nominal concentration.

#### Aquatic invertebrates

EC50 (48 h) > 580 mg/l, Daphnia magna (DIN 38412 Part 11, static)

The details of the toxic effect relate to the nominal concentration.

## Aquatic plants

EC50 (72 h) > 500 mg/l (growth rate), Scenedesmus subspicatus (DIN 38412 Part 9, static)

The details of the toxic effect relate to the nominal concentration.

## Chronic toxicity to fish

No data available.

#### Chronic toxicity to aquatic invertebrates

No data available.

## Assessment of terrestrial toxicity

No data available.

## Persistence and degradability

## Assessment biodegradation and elimination (H2O)

Not readily biodegradable (by OECD criteria). Biodegradable. Easily eliminated from water. The product has not been tested. The statement has been derived from the properties of the individual components.

Lutavit® Calpan 98%

Revision date: 2025/08/06

Revision date: 2025/08/06 Page: 9/11 Version: 6.0 (30041184/SDS\_GEN\_MX/EN)

## **Elimination information**

> 90 % DOC reduction (28 d) (OECD Guideline 302 B) (aerobic, activated sludge)

## Assessment of stability in water

According to structural properties, hydrolysis is not expected/probable.

## Information on Stability in Water (Hydrolysis)

No data available.

## Bioaccumulative potential

## Assessment bioaccumulation potential

Because of the n-octanol/water distribution coefficient (log Pow) accumulation in organisms is not to be expected.

## Bioaccumulation potential

Because of the n-octanol/water distribution coefficient (log Pow) accumulation in organisms is not to be expected.

## Mobility in soil

## Assessment transport between environmental compartments

The substance will not evaporate into the atmosphere from the water surface.

Adsorption to solid soil phase is not expected.

## 13. Disposal considerations

## Waste disposal of substance:

Observe national and local legal requirements.

## Container disposal:

Uncontaminated packaging can be re-used. Packs that cannot be cleaned should be disposed of in the same manner as the contents.

## 14. Transport Information

## Land transport

**TDG** 

Not classified as a dangerous good under transport regulations

## Sea transport

IMDG

Not classified as a dangerous good under transport regulations

## Air transport

IATA/ICAO

Not classified as a dangerous good under transport regulations

Revision date: 2025/08/06 Page: 10/11 Version: 6.0 (30041184/SDS GEN MX/EN)

## 15. Regulatory Information

## **Federal Regulations**

Not applicable

**NFPA Hazard codes:** 

Health: 0 Fire: 1 Reactivity: 0 Special:

**HMIS III rating** 

Health: 0 Flammability: 1 Physical hazard: 0

Assessment of the hazard classes according to UN GHS criteria (most recent version):

## 16. Other Information

## SDS Prepared by:

BASF NA Product Regulations SDS Prepared on: 2025/08/06

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

Lutavit® Calpan 98% is a registered trademark of BASF Mexicana or BASF SE

This information is considered accurate but is not exhaustive and shall only be used as a guideline based on current knowledge of the chemical substance or mixture. Safety precautions suitable for the product must be applied.

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO

Revision date: 2025/08/06 Page: 11/11 Version: 6.0 (30041184/SDS\_GEN\_MX/EN)

OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK. Any other intended applications should be discussed with the manufacturer. Corresponding occupational protection measurements must be followed.

Date / Revised: 2025/08/06 Version: 6.0
Date / Previous version: 2022/08/31 Previous version: 5.0

**END OF DATA SHEET**