

Safety data sheet

Page: 1/17

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 25.09.2019

Version: 5.0

Date previous version: 18.08.2016

Previous version: 4.1

Product: **Basonat® LR 9056**

(ID no. 30591253/SDS_GEN_GB/EN)

Date of print 10.10.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Basonat® LR 9056

UFI: MPUE-M4ST-R00G-DYAF

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses: Raw material, for industrial use only

Uses advised against: All consumer uses are strongly advised against. The hazardous properties of the substance require safety measures which can, in principle, not be sufficiently ensured in the home worker sector.

1.3. Details of the supplier of the safety data sheet

Company:

BASF SE
67056 Ludwigshafen
GERMANY

Contact address:

BASF plc
4th and 5th Floors, 2 Stockport Exchange
Railway Road, Stockport, SK1 3GG
UNITED KINGDOM

Telephone: +44 161 475 3000

E-mail address: product-safety-uk-and-ireland@basf.com

1.4. Emergency telephone number

International emergency number:

Telephone: +49 180 2273-112

SECTION 2: Hazards Identification

2.1. Classification of the substance or mixture

For the classification of the mixture the following methods have been applied: extrapolation on the concentration levels of the hazardous substances, on basis of test results and after evaluation of experts. The methodologies used are mentioned at the respective test results.

According to Regulation (EC) No 1272/2008 [CLP]

Acute Tox. 4 (Inhalation - mist)

Skin Sens. 1

STOT SE 3 (irritating to respiratory system)

Aquatic Chronic 3

| H332, H317, H335, H412

For the classifications not written out in full in this section the full text can be found in section 16.

2.2. Label elements

Globally Harmonized System, EU (GHS)

Pictogram:



Signal Word:

Warning

Hazard Statement:

H332	Harmful if inhaled.
H317	May cause an allergic skin reaction.
H335	May cause respiratory irritation.
H412	Harmful to aquatic life with long lasting effects.

Precautionary Statements (Prevention):

P280	Wear protective gloves.
P271	Use only outdoors or in a well-ventilated area.
P260	Do not breathe mist or vapour.
P273	Avoid release to the environment.
P272	Contaminated work clothing should not be allowed out of the workplace.

Precautionary Statements (Response):

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 25.09.2019

Version: 5.0

Date previous version: 18.08.2016

Previous version: 4.1

Product: **Basonat® LR 9056**

(ID no. 30591253/SDS_GEN_GB/EN)

Date of print 10.10.2025

P312	Call a POISON CENTER or doctor/physician if you feel unwell.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P303 + P352	IF ON SKIN (or hair): Wash with plenty of soap and water.
P333 + P311	If skin irritation or rash occurs: Call a POISON CENTER or doctor/physician.
P362 + P364	Take off contaminated clothing and wash it before reuse.

Precautionary Statements (Storage):

P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.

Precautionary Statements (Disposal):

P501	Dispose of contents/container to hazardous or special waste collection point.
------	---

Labeling of special preparations (GHS):

EUH204: Contains isocyanates. May produce an allergic reaction.

According to Regulation (EC) No 1272/2008 [CLP]**Hazard determining component(s) for labelling:** HDI oligomers, isocyanurate

UFI: MPUE-M4ST-R00G-DYAF

2.3. Other hazardsAccording to Regulation (EC) No 1272/2008 [CLP]

No specific dangers known, if the regulations/notes for storage and handling are considered.

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

SECTION 3: Composition/Information on Ingredients**3.1. Substances**

Not applicable

3.2. MixturesChemical nature

polyfunctional polyisocyanate

Hazardous ingredients (GHS)

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 25.09.2019

Version: 5.0

Date previous version: 18.08.2016

Previous version: 4.1

Product: **Basonat® LR 9056**

(ID no. 30591253/SDS_GEN_GB/EN)

Date of print 10.10.2025

according to Regulation (EC) No. 1272/2008

| HDI oligomers, isocyanurate

Content (W/W): $\geq 60\%$ - $\leq 80\%$	Acute Tox. 4 (Inhalation - mist)
CAS Number: 28182-81-2	Skin Sens. 1
REACH registration number: 01-2119485796-17	STOT SE 3 (irr. to respiratory syst.)
	H332, H317, H335

Poly(oxy-1,2-ethanediyl), .alpha.-methyl-.omega.-hydroxy-, polymer with 1,6-diisocyanatohexane, block

Content (W/W): $\geq 20\%$ - $\leq 35\%$	Aquatic Chronic 3
CAS Number: 143472-08-6	H412

hexamethylene-di-isocyanate

Content (W/W): $< 0.1\%$	Acute Tox. 4 (oral)
CAS Number: 822-06-0	Acute Tox. 1 (Inhalation - mist)
EC-Number: 212-485-8	Skin Corr./Irrit. 2
REACH registration number: 01-2119457571-37	Eye Dam./Irrit. 2
INDEX-Number: 615-011-00-1	Resp. Sens. 1
	Skin Sens. 1
	STOT SE 3 (irr. to respiratory syst.)
	H319, H315, H330, H302, H334, H317, H335

Specific concentration limit:

Skin Sens. 1: $\geq 0.5\%$
Resp. Sens. 1: $\geq 0.5\%$

For the classifications not written out in full in this section, including the hazard classes and the hazard statements, the full text is listed in section 16.

SECTION 4: First-Aid Measures

4.1. Description of first aid measures

Immediately remove contaminated clothing.

If inhaled:

If difficulties occur after vapour/aerosol has been inhaled, remove to fresh air and seek medical attention.

On skin contact:

Wash thoroughly with soap and water.

On contact with eyes:

Wash affected eyes for at least 15 minutes under running water with eyelids held open.

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 25.09.2019

Version: 5.0

Date previous version: 18.08.2016

Previous version: 4.1

Product: **Basonat® LR 9056**

(ID no. 30591253/SDS_GEN_GB/EN)

Date of print 10.10.2025

On ingestion:

Rinse mouth and then drink 200-300 ml of water. Do not induce vomiting unless told to by a poison control center or doctor.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms: Additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11.,
(Further) symptoms and / or effects are not known so far

4.3. Indication of any immediate medical attention and special treatment needed

Treatment: Treat according to symptoms (decontamination, vital functions), no known specific antidote.

SECTION 5: Fire-Fighting Measures**5.1. Extinguishing media**

Suitable extinguishing media:
water spray, dry powder, foam

Unsuitable extinguishing media for safety reasons:
water jet

5.2. Special hazards arising from the substance or mixture

harmful vapours

Evolution of fumes/fog. The substances/groups of substances mentioned can be released in case of fire.

5.3. Advice for fire-fighters

Special protective equipment:

Wear a self-contained breathing apparatus.

Further information:

The degree of risk is governed by the burning substance and the fire conditions. Contaminated extinguishing water must be disposed of in accordance with official regulations.

SECTION 6: Accidental Release Measures**6.1. Personal precautions, protective equipment and emergency procedures**

Use personal protective clothing. Breathing protection required.

6.2. Environmental precautions

Contain contaminated water/firefighting water. Do not discharge into drains/surface waters/groundwater.

6.3. Methods and material for containment and cleaning up

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 25.09.2019

Version: 5.0

Date previous version: 18.08.2016

Previous version: 4.1

Product: **Basonat® LR 9056**

(ID no. 30591253/SDS_GEN_GB/EN)

Date of print 10.10.2025

For large amounts: Pump off product.

For residues: Pick up with suitable absorbent material. Dispose of absorbed material in accordance with regulations.

6.4. Reference to other sections

Information regarding exposure controls/personal protection and disposal considerations can be found in section 8 and 13.

SECTION 7: Handling and Storage

7.1. Precautions for safe handling

Avoid handling of the substance in case of known skin complaints, hypersensitivity reactions, chronic respiratory disease, asthmatic attacks or bronchial attacks. Avoid contact with the skin, eyes and clothing. Avoid inhalation of dusts/mists/vapours. Avoid frequent and direct contact with substance. Ensure good work practices are implemented. Regular inspection and maintenance of equipment and machines. Clean equipment and the work area every day. Engineering controls have to be used to reduce exposures. Minimise exposure by partial enclosure of the operation or equipment and provide extract ventilation at openings. Worker should receive a pre-placement and subsequently a periodically medical examination including a pulmonary function test. Wear suitable face shield. Wear an impervious suit. Use suitable eye protection. Wear chemically resistant gloves in combination with 'basic' employee training. Change gloves, if duration of activity exceeds break through time. Use a local exhaust ventilation with adequate effectiveness. In case of insufficient ventilation, wear suitable respiratory equipment.

Protection against fire and explosion:

Take precautionary measures against static discharges.

7.2. Conditions for safe storage, including any incompatibilities

Further information on storage conditions: Keep container tightly closed and in a cool place. Keep container dry.

Storage stability:

If moisture enters isocyanate containers, CO₂ forms and pressure builds up.

Protect from temperatures above: 50 °C

7.3. Specific end use(s)

For the relevant identified use(s) listed in Section 1 the advice mentioned in this section 7 is to be observed.

SECTION 8: Exposure Controls/Personal Protection

8.1. Control parameters

Components with occupational exposure limits

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 25.09.2019

Version: 5.0

Date previous version: 18.08.2016

Previous version: 4.1

Product: **Basonat® LR 9056**

(ID no. 30591253/SDS_GEN_GB/EN)

Date of print 10.10.2025

822-06-0: hexamethylene-di-isocyanate

STEL value 0.07 mg/m³ (WEL/EH 40 (UK))

Measured as: NCO

TWA value 0.02 mg/m³ (WEL/EH 40 (UK))

Measured as: NCO

Components with PNEC

28182-81-2: HDI oligomers, isocyanurate

freshwater: 0.127 mg/l

marine water: 0.0127 mg/l

intermittent release: 1.27 mg/l

sediment (freshwater): 266700 mg/kg

marine water: 26670 mg/kg

soil: 53182 mg/kg

STP: 38.28 mg/l

DNEL

Data refer to the lead substance

Components with DNEL

28182-81-2: HDI oligomers, isocyanurate

worker: Short-term exposure - local effects, Inhalation: 1 mg/m³

worker: Long-term exposure - local effects, Inhalation: 0.5 mg/m³

8.2. Exposure controls

Personal protective equipment

Respiratory protection:

For short-term or slight exposure, use a respiratory mask with filter, for intensive or long-term exposure wear full respiratory protection apparatus Combination filter for gases/vapours of organic compounds and solid and liquid particles (f.e. EN 14387 Type A-P2)

Hand protection:

Chemical resistant protective gloves (EN 374)

Suitable materials for short-term contact (recommended: At least protective index 2, corresponding > 30 minutes of permeation time according to EN 374)

nitrile rubber (NBR) - 0.4 mm coating thickness

fluoroelastomer (FKM) - 0.7 mm coating thickness

Supplementary note: The specifications are based on tests, literature data and information of glove manufacturers or are derived from similar substances by analogy. Due to many conditions (e.g. temperature) it must be considered, that the practical usage of a chemical-protective glove in practice may be much shorter than the permeation time determined through testing.

Manufacturer's directions for use should be observed because of great diversity of types.

Eye protection:

Safety glasses with side-shields (frame goggles) (f.e. EN 166) and face shield

Body protection:

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 25.09.2019

Version: 5.0

Date previous version: 18.08.2016

Previous version: 4.1

Product: **Basonat® LR 9056**

(ID no. 30591253/SDS_GEN_GB/EN)

Date of print 10.10.2025

Body protection must be chosen depending on activity and possible exposure, e.g. apron, protecting boots, chemical-protection suit (according to EN 14605 in case of splashes or EN ISO 13982 in case of dust).

General safety and hygiene measures

Handle in accordance with good industrial hygiene and safety practice. Wearing of closed work clothing is required additionally to the stated personal protection equipment. Do not breathe vapour/aerosol/spray mists. Ensure adequate ventilation. Clean equipment, work area and clothing regularly.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Form:	liquid	
Colour:	colourless to yellowish	
Odour:	faint specific odour	
Odour threshold:	not determined	
pH value:	not applicable	
Melting point:	approx. -46 °C	(DIN 51583)
Boiling point:	not determined	
Flash point:	168 °C	(DIN EN 22719; ISO 2719)
Evaporation rate:	not determined	
Flammability:	not flammable	(derived from flash point)
Lower explosion limit:	As a result of our experience with this product and our knowledge of its composition we do not expect any hazard as long as the product is used appropriately and in accordance with the intended use.	
Upper explosion limit:	As a result of our experience with this product and our knowledge of its composition we do not expect any hazard as long as the product is used appropriately and in accordance with the intended use.	
Ignition temperature:	414 °C	(DIN EN 14522)
Vapour pressure:	< 0.0001 hPa (20 °C)	
Density:	1.16 g/cm ³ (20 °C)	

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 25.09.2019

Version: 5.0

Date previous version: 18.08.2016

Previous version: 4.1

Product: **Basonat® LR 9056**

(ID no. 30591253/SDS_GEN_GB/EN)

Date of print 10.10.2025

	1.14 g/cm ³ (50 °C)	
Relative density:	1.16 (20 °C)	
Relative vapour density (air):	not determined	
Solubility in water:	Reacts with water.	
Solubility (qualitative) solvent(s):	polar solvents soluble	
Partitioning coefficient n-octanol/water (log K _{ow}):	Study scientifically not justified.	
Self ignition:	not self-igniting	
Thermal decomposition:	No decomposition if used correctly.	
Viscosity, dynamic:	1,500 - 3,000 mPa.s (23 °C, 50 1/s)	(DIN EN ISO 3219)
Explosion hazard:	not explosive	
Fire promoting properties:	not fire-propagating	

9.2. Other information

Self heating ability:	It is not a substance capable of spontaneous heating.
Miscibility with water:	
Hygroscopy:	Reacts with water. hygroscopic
Surface tension:	
	Based on chemical structure, surface activity is not to be expected.
Grain size distribution:	The substance / product is marketed or used in a non solid or granular form.

SECTION 10: Stability and Reactivity

10.1. Reactivity

No hazardous reactions if stored and handled as prescribed/indicated.

10.2. Chemical stability

The product is stable if stored and handled as prescribed/indicated.

10.3. Possibility of hazardous reactions

Reacts with alcohols. Reacts with amines. Reacts with substances which contain active hydrogen. Reacts with water, with formation of carbon dioxide. The formation of gaseous decomposition products builds up pressure in tightly closed containers.

10.4. Conditions to avoid

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 25.09.2019

Version: 5.0

Date previous version: 18.08.2016

Previous version: 4.1

Product: **Basonat® LR 9056**

(ID no. 30591253/SDS_GEN_GB/EN)

Date of print 10.10.2025

Avoid moisture. Avoid humidity. Avoid direct contact with water.

10.5. Incompatible materials

Substances to avoid:
water, alcohols, amines

10.6. Hazardous decomposition products

Hazardous decomposition products:
No hazardous decomposition products if stored and handled as prescribed/indicated.

SECTION 11: Toxicological Information

11.1. Information on toxicological effects

Acute toxicity

Assessment of acute toxicity:

Virtually nontoxic after a single ingestion. Of moderate toxicity after short-term inhalation. The product has not been tested. The statement has been derived from the properties of the individual components.

Experimental/calculated data:

LD50 rat (oral): > 2,000 mg/kg

The product has not been tested. The statement has been derived from the properties of the individual components.

LC50 rat (by inhalation): > 1 - 5 mg/l 4 h

The substance from the isocyanate substance class has been tested in a form (respirable aerosol) that is different from the forms in which the product is placed on the market and used. Therefore, the test result is not adequate for the purpose of classification and labelling of the product. Based on expert judgement and available data, a modified classification and labeling for acute inhalation toxicity is justified. The generation of a respirable aerosol must be prevented! The product has not been tested. The statement has been derived from the properties of the individual components.

LD50 rat (dermal):

not determined

Information on: HDI oligomers, isocyanurate

Experimental/calculated data:

LC50 rat (by inhalation): 0.467 mg/l 4 h (OECD Guideline 403)

The test result applies only to the substance transferred into respirable aerosol (particles < 20 µm).

An aerosol was tested.

Irritation

Assessment of irritating effects:

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 25.09.2019

Version: 5.0

Date previous version: 18.08.2016

Previous version: 4.1

Product: **Basonat® LR 9056**

(ID no. 30591253/SDS_GEN_GB/EN)

Date of print 10.10.2025

Not irritating to eyes and skin. The product has not been tested. The statement has been derived from the properties of the individual components.

Experimental/calculated data:

Skin corrosion/irritation rabbit: non-irritant (OECD Guideline 404)

The product has not been tested. The statement has been derived from the properties of the individual components.

Serious eye damage/irritation rabbit: non-irritant (OECD Guideline 405)

The product has not been tested. The statement has been derived from the properties of the individual components.

Respiratory/Skin sensitization

Experimental/calculated data:

Guinea pig maximization test guinea pig: skin sensitizing

sensitizing effect in animal tests The product has not been tested. The statement has been derived from the properties of the individual components.

Germ cell mutagenicity

Assessment of mutagenicity:

Based on the ingredients, there is no suspicion of a mutagenic effect.

Carcinogenicity

Assessment of carcinogenicity:

No data available.

Reproductive toxicity

Assessment of reproduction toxicity:

No data available.

Developmental toxicity

Assessment of teratogenicity:

No data available.

Specific target organ toxicity (single exposure)

Assessment of STOT single:

Causes temporary irritation of the respiratory tract.

Repeated dose toxicity and Specific target organ toxicity (repeated exposure)

Assessment of repeated dose toxicity:

No data available.

Aspiration hazard

No aspiration hazard expected.

SECTION 12: Ecological Information

12.1. Toxicity

Assessment of aquatic toxicity:

The inhibition of the degradation activity of activated sludge is not anticipated when introduced to biological treatment plants in appropriate low concentrations.

Toxicity to fish:

LC50 (96 h), Fish

not determined

Aquatic invertebrates:

EC50 (48 h) 10 - 100 mg/l, Daphnia magna

The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Aquatic plants:

EC50 (72 h), algae

not determined

Microorganisms/Effect on activated sludge:

EC50 (3 h) > 1,000 mg/l, bacteria

The inhibition of the degradation activity of activated sludge is not anticipated when introduced to biological treatment plants in appropriate low concentrations.

Chronic toxicity to fish:

No data available.

Chronic toxicity to aquatic invertebrates:

No data available.

Assessment of terrestrial toxicity:

Study scientifically not justified.

12.2. Persistence and degradability

Assessment biodegradation and elimination (H₂O):

The substance can be virtually eliminated from water in suitable effluent treatment plants by biodegradation, stripping and mechanical separation.

Elimination information:

Not readily biodegradable (by OECD criteria).

12.3. Bioaccumulative potential

Assessment bioaccumulation potential:

The product has not been tested.

12.4. Mobility in soil

Assessment transport between environmental compartments:

Volatility: The substance will not evaporate into the atmosphere from the water surface.

Adsorption in soil: No data available.

12.5. Results of PBT and vPvB assessment

According to Annex XIII of Regulation (EC) No.1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH): The product does not contain a substance fulfilling the PBT (persistent/bioaccumulative/toxic) criteria or the vPvB (very persistent/very bioaccumulative) criteria.

12.6. Other adverse effects

The product does not contain substances that are listed in Annex I of Regulation (EC) 2037/2000 on substances that deplete the ozone layer.

12.7. Additional information

Add. remarks environm. fate & pathway:

Treatment in biological waste water treatment plants has to be performed according to local and administrative regulations.

Other ecotoxicological advice:

Do not release untreated into natural waters. The local regulations on waste-water treatment must be followed.

SECTION 13: Disposal Considerations

13.1. Waste treatment methods

Incinerate in suitable incineration plant, observing local authority regulations.

The UK Environmental Protection (Duty of Care) Regulations (EP) and amendments should be noted (United Kingdom).

This product and any uncleaned containers must be disposed of as hazardous waste in accordance with the 2005 Hazardous Waste Regulations and amendments (United Kingdom)

Contaminated packaging:

Uncontaminated packaging can be re-used.

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 25.09.2019

Version: 5.0

Date previous version: 18.08.2016

Previous version: 4.1

Product: **Basonat® LR 9056**

(ID no. 30591253/SDS_GEN_GB/EN)

Date of print 10.10.2025

Packs that cannot be cleaned should be disposed of in the same manner as the contents.

Refer to manufacturer/supplier for information on recovery/recycling.

SECTION 14: Transport Information

Land transport

ADR

Not classified as a dangerous good under transport regulations

UN number: Not applicable

UN proper shipping name: Not applicable

Transport hazard class(es): Not applicable

Packing group: Not applicable

Environmental hazards: Not applicable

Special precautions for user: None known

RID

Not classified as a dangerous good under transport regulations

UN number: Not applicable

UN proper shipping name: Not applicable

Transport hazard class(es): Not applicable

Packing group: Not applicable

Environmental hazards: Not applicable

Special precautions for user: None known

Inland waterway transport

ADN

Not classified as a dangerous good under transport regulations

UN number: Not applicable

UN proper shipping name: Not applicable

Transport hazard class(es): Not applicable

Packing group: Not applicable

Environmental hazards: Not applicable

Special precautions for user: None known

Transport in inland waterway vessel

Not evaluated

Sea transport

IMDG

	Not classified as a dangerous good under transport regulations
UN number:	Not applicable
UN proper shipping name:	Not applicable
Transport hazard class(es):	Not applicable
Packing group:	Not applicable
Environmental hazards:	Not applicable
Special precautions for user	None known

Air transport**IATA/ICAO**

	Not classified as a dangerous good under transport regulations
UN number:	Not applicable
UN proper shipping name:	Not applicable
Transport hazard class(es):	Not applicable
Packing group:	Not applicable
Environmental hazards:	Not applicable
Special precautions for user	None known

14.1. UN number

See corresponding entries for "UN number" for the respective regulations in the tables above.

14.2. UN proper shipping name

See corresponding entries for "UN proper shipping name" for the respective regulations in the tables above.

14.3. Transport hazard class(es)

See corresponding entries for "Transport hazard class(es)" for the respective regulations in the tables above.

14.4. Packing group

See corresponding entries for "Packing group" for the respective regulations in the tables above.

14.5. Environmental hazards

See corresponding entries for "Environmental hazards" for the respective regulations in the tables above.

14.6. Special precautions for user

See corresponding entries for "Special precautions for user" for the respective regulations in the tables above.

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 25.09.2019

Version: 5.0

Date previous version: 18.08.2016

Previous version: 4.1

Product: **Basonat® LR 9056**

(ID no. 30591253/SDS_GEN_GB/EN)

Date of print 10.10.2025

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Regulation:	Not evaluated
Shipment approved:	Not evaluated
Pollution name:	Not evaluated
Pollution category:	Not evaluated
Ship Type:	Not evaluated

SECTION 15: Regulatory Information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**Prohibitions, Restrictions and Authorizations

Annex XVII of Regulation (EC) No 1907/2006: Number on List: 3

If other regulatory information applies that is not already provided elsewhere in this safety data sheet, then it is described in this subsection.

The data should be considered when making any assessment under the Control of Substances Hazardous to Health Regulations (COSHH), and related guidance, for example, 'COSHH Essentials' (United Kingdom).

15.2. Chemical Safety Assessment

Assessment of safe use has been performed for the mixture and the result is documented in section 7 and 8 of the SDS

SECTION 16: Other InformationFull text of the classifications, including the hazard classes and the hazard statements, if mentioned in section 2 or 3:

Acute Tox.	Acute toxicity
Skin Sens.	Skin sensitization
STOT SE	Specific target organ toxicity — single exposure
Aquatic Chronic	Hazardous to the aquatic environment - chronic
Skin Corr./Irrit.	Skin corrosion/irritation
Eye Dam./Irrit.	Serious eye damage/eye irritation
Resp. Sens.	Respiratory sensitization
H332	Harmful if inhaled.
H317	May cause an allergic skin reaction.
H335	May cause respiratory irritation.
H412	Harmful to aquatic life with long lasting effects.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H330	Fatal if inhaled.
H302	Harmful if swallowed.

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 25.09.2019

Version: 5.0

Date previous version: 18.08.2016

Previous version: 4.1

Product: **Basonat® LR 9056**

(ID no. 30591253/SDS_GEN_GB/EN)

Date of print 10.10.2025

H334

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Abbreviations

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road.
ADN = The European Agreement concerning the International Carriage of Dangerous Goods by Inland waterways. ATE = Acute Toxicity Estimates. CAO = Cargo Aircraft Only. CAS = Chemical Abstract Service. CLP = Classification, Labelling and Packaging of substances and mixtures. DIN = German national organization for standardization. DNEL = Derived No Effect Level. EC50 = Effective concentration median for 50% of the population. EC = European Community. EN = European Standards. IARC = International Agency for Research on Cancer. IATA = International Air Transport Association. IBC-Code = Intermediate Bulk Container code. IMDG = International Maritime Dangerous Goods Code. ISO = International Organization for Standardization. STEL = Short-Term Exposure Limit. LC50 = Lethal concentration median for 50% of the population. LD50 = Lethal dose median for 50% of the population. TLV = Threshold Limit Value. MARPOL = The International Convention for the Prevention of Pollution from Ships. NEN = Dutch Norm. NOEC = No Observed Effect Concentration. OEL = Occupational Exposure Limit. OECD = Organization for Economic Cooperation and Development. PBT = Persistent, Bioaccumulative and Toxic. PNEC = Predicted No Effect Level. PPM = Parts per million. RID = The European Agreement concerning the International Carriage of Dangerous Goods by Rail. TWA = Time Weight Average. UN-number = UN number at transport. vPvB = very Persistent and very Bioaccumulative.

The data contained in this safety data sheet are based on our current knowledge and experience and describe the product only with regard to safety requirements. This safety data sheet is neither a Certificate of Analysis (CoA) nor technical data sheet and shall not be mistaken for a specification agreement. Identified uses in this safety data sheet do neither represent an agreement on the corresponding contractual quality of the substance/mixture nor a contractually designated use. It is the responsibility of the recipient of the product to ensure any proprietary rights and existing laws and legislation are observed.

Vertical lines in the left hand margin indicate an amendment from the previous version.