

Safety data sheet

Page: 1/126

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 01.08.2025 Version: 3.0 Date / Previous version: 24.06.2025 Previous version: 2.0

Product: Sodium Metabisulfite photo, non food grade

(ID no. 30042379/SDS_GEN_DE/EN)

Date of print 22.10.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Sodium Metabisulfite photo, non food grade

Chemical name: Disodium disulphite INDEX-Number: 016-063-00-2 CAS Number: 7681-57-4

REACH registration number: 01-2119531326-45-0002, 01-2119531326-45-0000

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses: Chemical

Recommended use: inorganic reducing agents, initial product for chemical syntheses, process

chemical, Textile chemical

For the detailed identified uses of the product see appendix of the safety data sheet.

1.3. Details of the supplier of the safety data sheet

Company:
BASF SE
67056 Ludwigshafen
GERMANY
Division Monomers

Telephone: +49 621 60 42737

E-mail address: pss.monomers@basf.com

1.4. Emergency telephone number

International emergency number: Telephone: +49 180 2273-112

Date / Revised: 01.08.2025 Version: 3.0
Date / Previous version: 24.06.2025 Previous version: 2.0

Product: Sodium Metabisulfite photo, non food grade

(ID no. 30042379/SDS_GEN_DE/EN)

Date of print 22.10.2025

SECTION 2: Hazards Identification

2.1. Classification of the substance or mixture

According to Regulation (EC) No 1272/2008 [CLP]

Acute Tox. 4 (oral) H302 Harmful if swallowed.

Eye Dam. 1 H318 Causes serious eye damage.

For the classifications not written out in full in this section the full text can be found in section 16.

2.2. Label elements

According to Regulation (EC) No 1272/2008 [CLP]

Pictogram:





Signal Word:

Danger

Hazard Statement:

H318 Causes serious eye damage.

H302 Harmful if swallowed.

Precautionary Statements (Prevention):

P280 Wear eye and face protection.

P270 Do not eat, drink or smoke when using this product.
P264 Wash contaminated body parts thoroughly after handling.

Precautionary Statements (Response):

P310 Immediately call a POISON CENTER or physician.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P301 + P330 IF SWALLOWED: rinse mouth.

Precautionary Statements (Disposal):

P501 Dispose of contents and container to hazardous or special waste

collection point.

Labeling of special preparations (GHS):

EUH031: Contact with acids liberates toxic gas.

Hazard determining component(s) for labelling: sodium metabisulphite

Date / Revised: 01.08.2025 Version: 3.0
Date / Previous version: 24.06.2025 Previous version: 2.0

Product: Sodium Metabisulfite photo, non food grade

(ID no. 30042379/SDS_GEN_DE/EN)

Date of print 22.10.2025

2.3. Other hazards

According to Regulation (EC) No 1272/2008 [CLP]

No specific dangers known, if the regulations/notes for storage and handling are considered. If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

The product does not contain a substance above legal limits fulfilling the PBT (persistent/bioaccumulative/toxic) criteria or the vPvB (very persistent/very bioaccumulative) criteria. Product does not contain a substance above legal limits included in the list established in accordance with Article 59(1) of Regulation (EC) No 1907/2006 for having endocrine disrupting properties or is identified to have endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

SECTION 3: Composition/Information on Ingredients

3.1. Substances

Chemical nature

Na2S2O5

sodium metabisulphite

Acute Tox. 4 (oral)
CAS Number: 7681-57-4 Eye Dam. 1
EC-Number: 231-673-0 H318, H302
INDEX-Number: 016-063-00-2 EUH031

Regulatory relevant ingredients

sodium metabisulphite

Content (W/W): >= 95 % - <= 100 Acute Tox. 4 (oral) % Eye Dam. 1

CAS Number: 7681-57-4 H318, H302 EC-Number: 231-673-0 EUH031

INDEX-Number: 016-063-00-2

For the classifications not written out in full in this section, including the hazard classes and the hazard statements, the full text is listed in section 16.

3.2. Mixtures

Not applicable

Date / Revised: 01.08.2025 Version: 3.0
Date / Previous version: 24.06.2025 Previous version: 2.0

Product: Sodium Metabisulfite photo, non food grade

(ID no. 30042379/SDS_GEN_DE/EN)

Date of print 22.10.2025

SECTION 4: First-Aid Measures

4.1. Description of first aid measures

Remove contaminated clothing.

If inhaled:

If difficulties occur after dust has been inhaled, remove to fresh air and seek medical attention. After inhalation of decomposition products: Immediately administer a corticosteroid from a controlled/metered dose inhaler. Seek medical attention.

On skin contact:

Wash thoroughly with soap and water

On contact with eyes:

Immediately wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.

On ingestion:

Immediately rinse mouth and then drink 200-300 ml of water, seek medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms: Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11., Many individuals are sensitive to sulphite additives and may experience a range of symptoms, including dermatitis, urticaria, angio-oedema, abdominal pain, diarrhoea, bronchoconstriction and anaphylaxis.

Hazards: Risk of sulfur dioxide formation by reaction with gastric acid after swallowing.

4.3. Indication of any immediate medical attention and special treatment needed

Treatment: Treat according to symptoms (decontamination, vital functions), no known specific antidote.

SECTION 5: Fire-Fighting Measures

5.1. Extinguishing media

Suitable extinguishing media: water spray, carbon dioxide, foam, dry powder

Unsuitable extinguishing media for safety reasons: water jet

Additional information:

Product will not burn.

Use extinguishing measures to suit surroundings.

Date / Revised: 01.08.2025 Version: 3.0
Date / Previous version: 24.06.2025 Previous version: 2.0

Product: Sodium Metabisulfite photo, non food grade

(ID no. 30042379/SDS_GEN_DE/EN)

Date of print 22.10.2025

5.2. Special hazards arising from the substance or mixture

Endangering substances: sulphur dioxide

Advice: The substances/groups of substances mentioned can be released if the product is involved in a fire.

5.3. Advice for fire-fighters

Special protective equipment:

Wear self-contained breathing apparatus and chemical-protective clothing.

Further information:

Product itself is non-combustible; fire extinguishing method of surrounding areas must be considered. Contaminated extinguishing water must be disposed of in accordance with official regulations. In case of fire and/or explosion do not breathe fumes.

SECTION 6: Accidental Release Measures

6.1. Personal precautions, protective equipment and emergency procedures

Avoid contact with the skin, eyes and clothing. Use personal protective clothing. Ensure adequate ventilation. Avoid dust formation.

6.2. Environmental precautions

Do not discharge into drains/surface waters/groundwater. Do not discharge into the subsoil/soil. Retain and dispose of contaminated wash water.

6.3. Methods and material for containment and cleaning up

Sweep/shovel up. Dispose of absorbed material in accordance with regulations.

6.4. Reference to other sections

Information regarding exposure controls/personal protection and disposal considerations can be found in section 8 and 13.

SECTION 7: Handling and Storage

7.1. Precautions for safe handling

Use only in well-ventilated areas. Avoid dust formation. Avoid contact with skin and eyes.

Protection against fire and explosion:

The substance/product is non-combustible. No special precautions necessary.

7.2. Conditions for safe storage, including any incompatibilities

Segregate from acids and acid forming substances. Segregate from oxidants.

Date / Revised: 01.08.2025 Version: 3.0
Date / Previous version: 24.06.2025 Previous version: 2.0

Product: Sodium Metabisulfite photo, non food grade

(ID no. 30042379/SDS_GEN_DE/EN)

Date of print 22.10.2025

Suitable materials for containers: rubberized, Polyester resin, glass reinforced (Palatal A410), Stainless steel 1.4541, Stainless steel 1.4571, High density polyethylene (HDPE), Low density polyethylene (LDPE)

Further information on storage conditions: Keep away from heat. Keep container tightly closed in a cool, well-ventilated place. Keep container dry. The product consumes oxygen. Danger of lack of oxygen in containers and tanks.

Storage class according to TRGS 510 (originally VCI, Germany): (13) Non-combustible solids

7.3. Specific end use(s)

See exposure scenario(s) in the attachment to this safety data sheet.

SECTION 8: Exposure Controls/Personal Protection

8.1. Control parameters

Components with occupational exposure limits

No occupational exposure limits known.

The nuisance dust limit value is to be kept.

The substance mentioned develops if the regulation/notes for storage and handling are not observed.

7446-09-5: sulphur dioxide

Short Term Exposure Classification: (TRGS 900 (DE))

Category I: Substances for which the localized effect has an assigned exposure limit or for substances with a sensitizing effect in respiratory passages

OEL 1,3 mg/m3; 0,5 ppm (TRGS 900 (DE))

Ceiling limit value/factor: 2

If the occupational exposure limit value (AGW) and the biological limit value (BGW) are complied with, there should be no risk of damage for the unborn

child (see TRGS 900, Number 2.7)

TWA value 1,3 mg/m3; 0,5 ppm (EU SCOEL)

Ceiling limit value/factor: 8HR

STEL value 2,7 mg/m3; 1,0 ppm (EU SCOEL)

Ceiling limit value/factor: 15 min

PNEC

freshwater: 1 mg/l

marine water: 0,1 mg/l

STP: 75,4 mg/l

Date / Revised: 01.08.2025 Version: 3.0
Date / Previous version: 24.06.2025 Previous version: 2.0

Product: Sodium Metabisulfite photo, non food grade

(ID no. 30042379/SDS_GEN_DE/EN)

Date of print 22.10.2025

DNEL

worker:

Long-term exposure- systemic effects, Inhalation: 225,0 mg/m3

consumer:

Long-term exposure- systemic effects, Inhalation: 66,0 mg/m3

consumer:

Long-term exposure- systemic effects, oral: 8,6 mg/kg

8.2. Exposure controls

Personal protective equipment

Respiratory protection:

Breathing protection if dusts are formed. Suitable respiratory protection for lower concentrations or short-term effect: Particle filter with low efficiency for solid particles (e.g. EN 143 or 149, Type P1or FFP1) Breathing protection if gases/vapours are formed. Combination filter for gases/vapours of organic, inorganic, acid inorganic, alkaline compounds and toxic particles (e. g. EN 14387 Type ABEK-P3)

Hand protection:

Chemical resistant protective gloves (EN ISO 374-1)

Suitable materials also with prolonged, direct contact (Recommended: Protective index 6, corresponding > 480 minutes of permeation time according to EN ISO 374-1):
e.g. nitrile rubber (0.4 mm), chloroprene rubber (0.5 mm), polyvinylchloride (0.7 mm) and other Supplementary note: The specifications are based on tests, literature data and information of glove manufacturers or are derived from similar substances by analogy. Due to many conditions (e.g. temperature) it must be considered, that the practical usage of a chemical-protective glove in practice may be much shorter than the permeation time determined through testing. Manufacturer's directions for use should be observed because of great diversity of types.

Eve protection:

Tightly fitting safety goggles (splash goggles) (e.g. EN 166)

Body protection:

Body protection must be chosen depending on activity and possible exposure, e.g. apron, protecting boots, chemical-protection suit (according to EN 14605 in case of splashes or EN ISO 13982 in case of dust).

General safety and hygiene measures

Handle in accordance with good industrial hygiene and safety practice. Do not inhale vapours or dust. Hands and/or face should be washed before breaks and at the end of the shift.

Date / Revised: 01.08.2025 Version: 3.0 Date / Previous version: 24.06.2025 Previous version: 2.0

Product: Sodium Metabisulfite photo, non food grade

(ID no. 30042379/SDS_GEN_DE/EN)

Date of print 22.10.2025

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

State of matter: solid

Form: powder, crystalline
Colour: white to slightly yellow
Odour: faint odour, of sulfur dioxide

Odour threshold:

Not determined due to potential

health hazard by inhalation.

decomposition point: > 150 °C (other)

The substance / product

decomposes.

Boiling point:

The substance / product decomposes therefore not

determined.

Flammability: not flammable (other)

Lower explosion limit:

For solids not relevant for classification and labelling.

Upper explosion limit:

For solids not relevant for classification and labelling.

Flash point:

not applicable, the product is a solid

Auto-ignition temperature:

not applicable

Thermal decomposition: 150 °C

To avoid thermal decomposition, do not overheat.

pH value: 4,0 - 4,8 (OECD Guideline 122)

(5 %(m), 20 °C)

Viscosity, kinematic:

not applicable, the product is a solid

Viscosity, dynamic:

not applicable

Solubility in water: Literature data.

667 g/l (25 °C)

Partitioning coefficient n-octanol/water (log Kow):

not applicable

Vapour pressure:

The vapour pressure of the aqueous solution consists of the partial pressure for water and the partial pressure for sulphur dioxide.

Density: 2,36 g/cm3 (OECD Guideline 109)

(20 °C)

Relative vapour density (air):

The product is a non-volatile solid.

Date / Revised: 01.08.2025 Version: 3.0 Date / Previous version: 24.06.2025 Previous version: 2.0

Product: Sodium Metabisulfite photo, non food grade

(ID no. 30042379/SDS_GEN_DE/EN)

Date of print 22.10.2025

Particle characteristics

Particle size distribution: 95 µm (D50, ISO 13320-1)

Test substance: other TS

fine particles -

9.2. Other information

Information with regard to physical hazard classes

Explosives

Explosion hazard: not explosive (Directive 92/69/EEC, A.14)

Impact sensitivity:

Based on the chemical structure there is no shock-sensitivity.

Oxidizing properties

Fire promoting properties: Based on its structural properties

the product is not classified as

oxidizing.

Flammable solids

Burning rate: 0 mm/s, 0 s (Directive 92/69/EEC, A.10)

Self-heating substances and mixtures

Self heating ability: It is not a substance capable of

spontaneous heating.

Other safety characteristics

Bulk density: 1.000 - 1.200 kg/m3

pKA:

not applicable

Evaporation rate:

The product is a non-volatile solid.

SECTION 10: Stability and Reactivity

10.1. Reactivity

No hazardous reactions if stored and handled as prescribed/indicated.

10.2. Chemical stability

The product is stable if stored and handled as prescribed/indicated.

10.3. Possibility of hazardous reactions

Reacts with nitrites. Reacts with nitrates. Reacts with oxidizing agents. Generation of sulphur dioxide upon exposure to acids. (or conditions.) The product consumes oxygen.

10.4. Conditions to avoid

Avoid humidity.

Date / Revised: 01.08.2025 Version: 3.0
Date / Previous version: 24.06.2025 Previous version: 2.0

Product: Sodium Metabisulfite photo, non food grade

(ID no. 30042379/SDS_GEN_DE/EN)

Date of print 22.10.2025

10.5. Incompatible materials

Substances to avoid: nitrites, nitrates, oxidizing agents, acids

10.6. Hazardous decomposition products

Hazardous decomposition products: sulphur dioxide

SECTION 11: Toxicological Information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Assessment of acute toxicity:

Of moderate toxicity after single ingestion. Virtually nontoxic by inhalation. Virtually nontoxic after a single skin contact. The product has not been fully tested. The statements have been derived in parts from products of a similar structure or composition.

Experimental/calculated data:

LD50 rat (oral): 1.540 mg/kg (OECD Guideline 401)

LC50 rat (by inhalation): > 5,5 mg/l 4 h (IRT)

The product has not been tested. The statement has been derived from substances/products of a similar structure or composition. Tested as dust aerosol.

LD50 rat (dermal): > 2.000 mg/kg (OECD Guideline 402)

The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Irritation

Experimental/calculated data:

Skin corrosion/irritation

rabbit: non-irritant (OECD Guideline 404)

Serious eye damage/irritation

rabbit: irreversible damage (OECD Guideline 405)

Respiratory/Skin sensitization

Assessment of sensitization:

Skin sensitizing effects were not observed in animal studies. A sensitizing effect on particularly sensitive individuals cannot be excluded.

Experimental/calculated data:

Mouse Local Lymph Node Assay (LLNA) mouse: Non-sensitizing. (OECD Guideline 429)

Date / Revised: 01.08.2025 Version: 3.0
Date / Previous version: 24.06.2025 Previous version: 2.0

Product: Sodium Metabisulfite photo, non food grade

(ID no. 30042379/SDS_GEN_DE/EN)

Date of print 22.10.2025

Germ cell mutagenicity

Assessment of mutagenicity:

No mutagenic effect was found in various tests with bacteria and mammalian cell culture. The substance was not mutagenic in studies with mammals.

Carcinogenicity

Assessment of carcinogenicity:

In long-term studies in rats in which the substance was given by feed, a carcinogenic effect was not observed.

Reproductive toxicity

Assessment of reproduction toxicity:

The results of animal studies gave no indication of a fertility impairing effect.

Developmental toxicity

Assessment of teratogenicity:

No indications of a developmental toxic / teratogenic effect were seen in animal studies.

Experiences in humans

Experimental/calculated data:

With sensitive persons it can lead to an over sensitive reaction.

Specific target organ toxicity (single exposure)

Assessment of STOT single:

Apart from effects causing lethality, no specific target organ toxicity was observed in experimental studies.

Repeated dose toxicity and Specific target organ toxicity (repeated exposure)

Assessment of repeated dose toxicity:

No substance-specific organtoxicity was observed after repeated administration to animals.

Aspiration hazard

not applicable

Interactive effects

No data available.

11.2. Information on other hazards

Endocrine disrupting properties

Date / Revised: 01.08.2025 Version: 3.0
Date / Previous version: 24.06.2025 Previous version: 2.0

Product: Sodium Metabisulfite photo, non food grade

(ID no. 30042379/SDS_GEN_DE/EN)

Date of print 22.10.2025

The substance is not identified to have endocrine disrupting properties according to Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 nor is included in the Candidate List of substances of very high concern according to EU REACh Article 59 for having endocrine disrupting properties.

SECTION 12: Ecological Information

12.1. Toxicity

Assessment of aquatic toxicity:

Acutely harmful for aquatic organisms. The inhibition of the degradation activity of activated sludge is not anticipated when introduced to biological treatment plants in appropriate low concentrations.

Toxicity to fish:

LC50 (96 h) 316 mg/l, Leuciscus idus (DIN 38412 Part 15, static)

The details of the toxic effect relate to the nominal concentration. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Aquatic invertebrates:

EC50 (48 h) 89 mg/l, Daphnia magna (Directive 79/831/EEC, static)

Nominal concentration.

Aquatic plants:

EC50 (72 h) 43,8 mg/l (growth rate), algae (other, static)

Nominal concentration.

Microorganisms/Effect on activated sludge:

No observed effect concentration (3 h) > 1.000 mg/l, (OECD Guideline 209, aquatic)

The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Chronic toxicity to fish:

No observed effect concentration (34 d) > 316 mg/l, Brachydanio rerio (OECD Guideline 210, Flow through.)

The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Chronic toxicity to aquatic invertebrates:

No observed effect concentration (21 d) > 10 mg/l, Daphnia magna (OECD Guideline 202, part 2, semistatic)

Nominal concentration.

Assessment of terrestrial toxicity:

Study scientifically not justified.

12.2. Persistence and degradability

Date / Revised: 01.08.2025 Version: 3.0
Date / Previous version: 24.06.2025 Previous version: 2.0

Product: Sodium Metabisulfite photo, non food grade

(ID no. 30042379/SDS_GEN_DE/EN)

Date of print 22.10.2025

Assessment biodegradation and elimination (H2O):

Inorganic product which cannot be eliminated from water by biological purification processes.

Assessment of stability in water:

According to structural properties, hydrolysis is not expected/probable.

Study scientifically not justified.

12.3. Bioaccumulative potential

Assessment bioaccumulation potential:

Accumulation in organisms is not to be expected.

Bioaccumulation potential:

Study scientifically not justified.

12.4. Mobility in soil

Assessment transport between environmental compartments:

Volatility: The substance will not evaporate into the atmosphere from the water surface.

Adsorption in soil: Adsorption to solid soil phase is not expected.

12.5. Results of PBT and vPvB assessment

According to Annex XIII of Regulation (EC) No.1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH): The product does not fulfill the criteria for PBT (Persistent/bioaccumulative/toxic) and vPvB (very persistent/very bioaccumulative). Self classification

12.6. Endocrine disrupting properties

The substance is not identified to have endocrine disrupting properties according to Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 nor is included in the Candidate List of substances of very high concern according to EU REACh Article 59 for having endocrine disrupting properties.

12.7. Other adverse effects

The substance is not listed in Regulation (EC) 1005/2009 on substances that deplete the ozone layer.

Results of PMT and vPvM assessment

PMT assessment does not apply. vPvM assessment does not apply.

Date / Revised: 01.08.2025 Version: 3.0 Date / Previous version: 24.06.2025 Previous version: 2.0

Product: Sodium Metabisulfite photo, non food grade

(ID no. 30042379/SDS_GEN_DE/EN)

Date of print 22.10.2025

Additional information

Sum parameter

Chemical oxygen demand (COD): (calculated) 165 mg/g

Other ecotoxicological advice:

Higher concentrations of the substance may cause a strong chemical oxygen consumption in biological sewage-treatment plants and/or waterways.

SECTION 13: Disposal Considerations

13.1. Waste treatment methods

Must be disposed of or incinerated in accordance with local regulations.

Observe national and local legal requirements.

Contaminated packaging:

Contaminated packaging should be emptied as far as possible; then it can be passed on for recycling after being thoroughly cleaned.

SECTION 14: Transport Information

Land transport

ADR

Not classified as a dangerous good under transport regulations

UN number or ID number: Not applicable UN proper shipping name: Not applicable Transport hazard class(es): Not applicable Packing group: Not applicable Environmental hazards: Not applicable None known Special precautions for

user

RID

Not classified as a dangerous good under transport regulations

UN number or ID number: Not applicable Not applicable UN proper shipping name: Transport hazard class(es): Not applicable Packing group: Not applicable Environmental hazards: Not applicable

Special precautions for

user

None known

Inland waterway transport

Date / Revised: 01.08.2025 Version: 3.0
Date / Previous version: 24.06.2025 Previous version: 2.0

Product: Sodium Metabisulfite photo, non food grade

(ID no. 30042379/SDS_GEN_DE/EN)

Date of print 22.10.2025

ADN

Not classified as a dangerous good under transport regulations

UN number or ID number:
UN proper shipping name:
Transport hazard class(es):
Packing group:
Environmental hazards:
Special precautions for

Not applicable
Not applicable
Not applicable
Not applicable
Not applicable
Not applicable

user:

Transport in inland waterway vessel

Not evaluated

Sea transport

IMDG

Not classified as a dangerous good under transport regulations

UN number or ID number:
UN proper shipping name:
Transport hazard class(es):
Packing group:
Environmental hazards:
Special precautions for
Not applicable
Not applicable
Not applicable
Not applicable
Not applicable

user

Air transport

IATA/ICAO

Not classified as a dangerous good under transport regulations

UN number or ID number:
UN proper shipping name:
Transport hazard class(es):
Packing group:
Environmental hazards:
Special precautions for

Not applicable
Not applicable
Not applicable
Not applicable
Not applicable

user

14.1. UN number or ID number

See corresponding entries for "UN number or ID number" for the respective regulations in the tables above.

14.2. UN proper shipping name

Date / Revised: 01.08.2025 Version: 3.0
Date / Previous version: 24.06.2025 Previous version: 2.0

Product: Sodium Metabisulfite photo, non food grade

(ID no. 30042379/SDS_GEN_DE/EN)

Date of print 22.10.2025

See corresponding entries for "UN proper shipping name" for the respective regulations in the tables above.

14.3. Transport hazard class(es)

See corresponding entries for "Transport hazard class(es)" for the respective regulations in the tables above.

14.4. Packing group

See corresponding entries for "Packing group" for the respective regulations in the tables above.

14.5. Environmental hazards

See corresponding entries for "Environmental hazards" for the respective regulations in the tables above.

14.6. Special precautions for user

See corresponding entries for "Special precautions for user" for the respective regulations in the tables above.

14.7. Maritime transport in bulk according to IMO instruments

Maritime transport in bulk is not intended.

SECTION 15: Regulatory Information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Prohibitions, Restrictions and Authorizations

Annex XVII of Regulation (EC) No 1907/2006: Number on List: 75

Classification according to 'TA-Luft' (Germany):

5.2.1: total dust, including fine dust

Water hazard class (§6 AwSV para.4 (Legal binding announcement of the substance in the Federal Gazette)): (1) Weakly water polluting. ID-No.: 1169

If other regulatory information applies that is not already provided elsewhere in this safety data sheet, then it is described in this subsection.

15.2. Chemical Safety Assessment

Chemical Safety Assessment performed

Date / Revised: 01.08.2025 Version: 3.0 Date / Previous version: 24.06.2025 Previous version: 2.0

Product: Sodium Metabisulfite photo, non food grade

(ID no. 30042379/SDS_GEN_DE/EN)

Date of print 22.10.2025

SECTION 16: Other Information

Assessment of the hazard classes according to UN GHS criteria (most recent version)

Acute Tox. 4 (oral) Eye Dam./Irrit. 1 Aquatic Acute 3

chemical industry

Full text of the classifications, including the hazard classes and the hazard statements, if mentioned

in section 2 or 3:

Acute Tox. Acute toxicity

Eye Dam. Serious eye damage

H318 Causes serious eye damage.

H302 Harmful if swallowed.

EUH031 Contact with acids liberates toxic gas.

Abbreviations

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road. ADN = The European Agreement concerning the International Carriage of Dangerous Goods by Inland waterways. ATE = Acute Toxicity Estimates. CAO = Cargo Aircraft Only. CAS = Chemical Abstract Service. CLP = Classification, Labelling and Packaging of substances and mixtures. DIN = German national organization for standardization. DNEL = Derived No Effect Level. EC50 = Effective concentration median for 50% of the population. EC = European Community. EN = European Standards. IARC = International Agency for Research on Cancer. IATA = International Air Transport Association. IBC-Code = Intermediate Bulk Container code. IMDG = International Maritime Dangerous Goods Code. ISO = International Organization for Standardization. STEL = Short-Term Exposure Limit. LC50 = Lethal concentration median for 50% of the population. LD50 = Lethal dose median for 50% of the population. TLV = Threshold Limit Value. MARPOL = The International Convention for the Prevention of Pollution from Ships, NEN = Dutch Norm, NOEC = No Observed Effect Concentration, OEL = Occupational Exposure Limit. OECD = Organization for Economic Cooperation and Development. PBT = Persistent, Bioaccumulative and Toxic. PNEC = Predicted No Effect Level. PPM = Parts per million. RID = The European Agreement concerning the International Carriage of Dangerous Goods by Rail. TWA = Time Weight Average. UN-number = UN number at transport. vPvB = very Persistent and very Bioaccumulative.

The data contained in this safety data sheet are based on our current knowledge and experience and describe the product only with regard to safety requirements. This safety data sheet is neither a Certificate of Analysis (CoA) nor technical data sheet and shall not be mistaken for a specification agreement. Identified uses in this safety data sheet do neither represent an agreement on the corresponding contractual quality of the substance/mixture nor a contractually designated use. It is the responsibility of the recipient of the product to ensure any proprietary rights and existing laws and legislation are observed.

Date / Revised: 01.08.2025 Version: 3.0
Date / Previous version: 24.06.2025 Previous version: 2.0

Product: Sodium Metabisulfite photo, non food grade

(ID no. 30042379/SDS_GEN_DE/EN)

Date of print 22.10.2025

Annex: Exposure Scenarios

Index

1. Formulation, Manufacture of fine chemicals

F; ERC2, ERC3; PROC3, PROC4, PROC5, PROC8b, PROC9, PROC15, PROC26, PROC28; PC21, PC20

2. Formulation, Use in/as Photochemicals

F; ERC2, ERC3; PROC3, PROC4, PROC5, PROC8b, PROC9, PROC15, PROC26, PROC28; PC30

3. Industrial applications

IS; SU9, SU8; ERC6b; PROC3, PROC1, PROC4, PROC8b, PROC9, PROC26, PROC28; PC20

- **4.** Industrial applications, Intermediate for the manufacture of bulk chemicals, materials and resins IS; SU9, SU8; ERC6a; PROC3, PROC8b, PROC9, PROC15, PROC26, PROC28
- **5.** Industrial applications, Manufacture of fine chemicals IS; SU9, SU24, SU20; ERC6b; PROC3, PROC2, PROC1, PROC4, PROC5, PROC8b, PROC9, PROC15, PROC26, PROC28; PC21, PC20
- **6.** Industrial applications, Use in/as Photochemicals IS; SU7, SU6b; ERC6b; PROC3, PROC4, PROC5, PROC7, PROC8b, PROC9, PROC10, PROC13, PROC15, PROC26, PROC28; PC30
- **7.** Professional applications, Use as laboratory reagent/agent, Manufacture of fine chemicals PW; SU24, SU20; ERC8b; PROC3, PROC2, PROC1, PROC4, PROC5, PROC8a, PROC9, PROC8b, PROC15, PROC26; PC21, PC20
- **8.** Professional applications, Use in/as Photochemicals PW; SU7, SU6b; ERC8e; PROC3, PROC4, PROC5, PROC8b, PROC9, PROC8a, PROC10, PROC11, PROC13, PROC15, PROC19, PROC26; PC30
- **9.** Consumer applications, Use in/as Photochemicals C; ERC8e; PC30
- **10.**Service life of articles, Use in leather tanning, finishing, impregnation, (use in professional settings) SL; ERC10a; PROC21

* * * * * * * * * * * * * * * *

1. Short title of exposure scenario

Formulation, Manufacture of fine chemicals

F; ERC2, ERC3; PROC3, PROC4, PROC5, PROC8b, PROC9, PROC15, PROC26, PROC28; PC21, PC20

Date / Revised: 01.08.2025 Version: 3.0
Date / Previous version: 24.06.2025 Previous version: 2.0

Product: Sodium Metabisulfite photo, non food grade

(ID no. 30042379/SDS_GEN_DE/EN)

Date of print 22.10.2025

Control of exposure and risk management measures

Contributing exposure scenario	
Use descriptors covered	ERC2: Formulation into mixture As no environmental hazard was identified no environmental-related exposure assessment and risk characterization was performed.
Operational conditions	

Contributing exposure scenario	
Use descriptors covered	ERC3: Formulation into solid matrix As no environmental hazard was identified no environmental-related exposure assessment and risk characterization was performed.
Operational conditions	

Contributing exposure scenario	
Use descriptors covered	PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition Use domain: industrial
Operational conditions	
Concentration of the substance	sodium metabisulphite Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	0,009 Pa
Process temperature	40 °C
	Corresponds to a vapour pressure < 0.01 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Operation is carried out at ambient or elevated temperatures
Risk Management Measures	
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %
Supervision in place to check that the RMMs in place are being used correctly and OCs followed. Clean	
equipment and the work area every day. Change clothes immediately after contamination. Ensure good work	

Date / Revised: 01.08.2025 Version: 3.0
Date / Previous version: 24.06.2025 Previous version: 2.0

Product: Sodium Metabisulfite photo, non food grade

(ID no. 30042379/SDS_GEN_DE/EN)

practices are implemented. Wash off any skin contamination immediately. Ensure minimization of manual phases Provide basic employee training to prevent/minimize exposures. Minimise number of staff exposed. Avoid contact with contaminated tools. Containment as appropriate Provide a good standard of general or controlled ventilation (5 to 10 air changes per hour) Wear suitable face shield, Wear suitable working clothes. Avoid contact with eyes.	
Use suitable eye protection. Exposure estimate and reference to	its source
Assessment method	EASY TRA v6.1, Workplace measurements
	Worker - inhalation, long-term - systemic
Exposure estimate	0,01 mg/m³
Risk Characterization Ratio (RCR)	0,000044
Assessment method	Qualitative assessment
	Worker - inhalation

Contributing exposure scenario	
Use descriptors covered	PROC4: Chemical production where opportunity for exposure arises Use domain: industrial
Operational conditions	
Concentration of the substance	sodium metabisulphite Content: >= 0 % - <= 100 %
Physical state	Solid, low dustiness
Vapour pressure of the substance during use	0,009 Pa
Process temperature	40 °C
	Corresponds to a vapour pressure < 0.01 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Operation is carried out at ambient or elevated temperatures
Risk Management Measures	
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %
Supervision in place to check that the	

Date / Revised: 01.08.2025 Version: 3.0
Date / Previous version: 24.06.2025 Previous version: 2.0

Product: Sodium Metabisulfite photo, non food grade

(ID no. 30042379/SDS_GEN_DE/EN)

RMMs in place are being used correctly and OCs followed. Clean equipment and the work area every day. Change clothes immediately after contamination. Ensure good work practices are implemented. Wash off any skin contamination immediately. Ensure minimization of manual phases Provide basic employee training to prevent/minimize exposures. Minimise number of staff exposed. Avoid contact with contaminated tools. Containment as appropriate Provide a good standard of general or controlled ventilation (5 to 10 air changes per hour) Wear suitable face shield, Wear suitable working clothes. Avoid contact with eyes. Use suitable eye protection. Exposure estimate and reference to it.	ts source EASY TRA v6.1, Workplace measurements Worker - inhalation, long-term - systemic
Exposure estimate	0,5 mg/m³
Risk Characterization Ratio (RCR)	0,002222
Assessment method	Qualitative assessment
	Worker - inhalation

Contributing exposure scenario	
Use descriptors covered	PROC4: Chemical production where opportunity for exposure arises Use domain: industrial
Operational conditions	
Concentration of the substance	sodium metabisulphite Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	0,009 Pa
Process temperature	40 °C
	Corresponds to a vapour pressure < 0.01 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Operation is carried out at ambient or elevated temperatures

Date / Revised: 01.08.2025 Version: 3.0
Date / Previous version: 24.06.2025 Previous version: 2.0

Product: Sodium Metabisulfite photo, non food grade

(ID no. 30042379/SDS_GEN_DE/EN)

Risk Management Measures	
Provide a good standard of general	
ventilation (not less than 3 - 5 air	Effectiveness: 30 %
changes per hour)	
Supervision in place to check that the	
RMMs in place are being used	
correctly and OCs followed. Clean	
equipment and the work area every	
day. Change clothes immediately after	
contamination. Ensure good work	
practices are implemented. Wash off	
any skin contamination immediately.	
Ensure minimization of manual	
phases Provide basic employee	
training to prevent/minimize	
exposures. Minimise number of staff	
exposed. Avoid contact with	
contaminated tools.	
Containment as appropriate Provide a	
good standard of general or controlled	
ventilation (5 to 10 air changes per	
hour)	
Wear suitable face shield, Wear	
suitable working clothes.	
Avoid contact with eyes.	
Use suitable eye protection.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v6.1, Workplace measurements
	Worker - inhalation, long-term - systemic
Exposure estimate	0,05 mg/m³
Risk Characterization Ratio (RCR)	0,000222
Assessment method	Qualitative assessment
	Worker - inhalation

Contributing exposure scenario	
Use descriptors covered	PROC5: Mixing or blending in batch processes Use domain: industrial
Operational conditions	
Concentration of the substance	sodium metabisulphite Content: >= 0 % - <= 100 %
Physical state	Solid, low dustiness
Vapour pressure of the substance during use	0,009 Pa
Process temperature	40 °C
	Corresponds to a vapour pressure < 0.01 Pa
Duration and Frequency of activity	480 min 5 days per week

Date / Revised: 01.08.2025 Version: 3.0
Date / Previous version: 24.06.2025 Previous version: 2.0

Product: Sodium Metabisulfite photo, non food grade

(ID no. 30042379/SDS_GEN_DE/EN)

Indoor/Outdoor	Indoor
	Operation is carried out at ambient or elevated
	temperatures
Risk Management Measures	
Provide a good standard of general	
ventilation (not less than 3 - 5 air	Effectiveness: 30 %
changes per hour)	
Supervision in place to check that the	
RMMs in place are being used	
correctly and OCs followed. Clean	
equipment and the work area every	
day. Change clothes immediately after	
contamination. Ensure good work practices are implemented. Wash off	
any skin contamination immediately.	
Ensure minimization of manual	
phases Provide basic employee	
training to prevent/minimize	
exposures. Minimise number of staff	
exposed. Avoid contact with	
contaminated tools.	
Containment as appropriate Provide a	
good standard of general or controlled	
ventilation (5 to 10 air changes per	
hour)	
Wear suitable face shield, Wear	
suitable working clothes.	
Avoid contact with eyes.	
Use suitable eye protection.	
Exposure estimate and reference to i	
Assessment method	EASY TRA v6.1, Workplace measurements
	Worker - inhalation, long-term - systemic
Exposure estimate	0,5 mg/m³
Risk Characterization Ratio (RCR)	0,002222
Assessment method	Qualitative assessment
	Worker - inhalation

Contributing exposure scenario	
Use descriptors covered	PROC5: Mixing or blending in batch processes Use domain: industrial
Operational conditions	
Concentration of the substance	sodium metabisulphite Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	0,009 Pa

Date / Revised: 01.08.2025 Version: 3.0
Date / Previous version: 24.06.2025 Previous version: 2.0

Product: Sodium Metabisulfite photo, non food grade

(ID no. 30042379/SDS_GEN_DE/EN)

Process temperature	40 °C
	Corresponds to a vapour pressure < 0.01 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Operation is carried out at ambient or elevated temperatures
Risk Management Measures	
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %
Supervision in place to check that the RMMs in place are being used correctly and OCs followed. Clean equipment and the work area every day. Change clothes immediately after contamination. Ensure good work practices are implemented. Wash off any skin contamination immediately. Ensure minimization of manual phases Provide basic employee training to prevent/minimize exposures. Minimise number of staff exposed. Avoid contact with contaminated tools.	
Containment as appropriate Provide a good standard of general or controlled ventilation (5 to 10 air changes per hour)	
Wear suitable face shield, Wear suitable working clothes.	
Avoid contact with eyes.	
Use suitable eye protection.	
Exposure estimate and reference to i	
Assessment method	EASY TRA v6.1, Workplace measurements
Exposure estimate	Worker - inhalation, long-term - systemic 0,05 mg/m³
Exposure estimate Risk Characterization Ratio (RCR)	0,000222
Assessment method	Qualitative assessment
Assessment method	Worker - inhalation
	vvoikei - iiiiiaialioii

Contributing exposure scenario	
Use descriptors covered	PROC8b: Transfer of substance or mixture (charging and discharging) at dedicated facilities Use domain: industrial
	Additional PROC(s) covered: Transfer of substance or preparation into small containers (dedicated filling line,

Date / Revised: 01.08.2025 Version: 3.0
Date / Previous version: 24.06.2025 Previous version: 2.0

Product: Sodium Metabisulfite photo, non food grade

(ID no. 30042379/SDS_GEN_DE/EN)

	including weighing).
Operational conditions	
Concentration of the substance	sodium metabisulphite Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	0,009 Pa
Process temperature	40 °C
	Corresponds to a vapour pressure < 0.01 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Operation is carried out at ambient or elevated temperatures
Risk Management Measures	
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %
Supervision in place to check that the RMMs in place are being used correctly and OCs followed. Clean equipment and the work area every day. Change clothes immediately after contamination. Ensure good work practices are implemented. Wash off any skin contamination immediately. Ensure minimization of manual phases Provide basic employee training to prevent/minimize exposures. Minimise number of staff exposed. Avoid contact with contaminated tools. Containment as appropriate Provide a good standard of general or controlled ventilation (5 to 10 air changes per	
hour)	
Wear suitable face shield, Wear suitable working clothes.	
Avoid contact with eyes.	
Use suitable eye protection.	
Exposure estimate and reference to i	
Assessment method	EASY TRA v6.1, Workplace measurements Worker - inhalation, long-term - systemic
Exposure estimate	0,01 mg/m ³
Risk Characterization Ratio (RCR)	0,000044
Assessment method	Qualitative assessment

Date / Revised: 01.08.2025 Version: 3.0
Date / Previous version: 24.06.2025 Previous version: 2.0

Product: Sodium Metabisulfite photo, non food grade

(ID no. 30042379/SDS_GEN_DE/EN)

Date of print 22.10.2025

Worker - inhalation

Contributing exposure scenario		
Use descriptors covered	PROC15: Use a laboratory reagent. Use domain: industrial	
Operational conditions		
Concentration of the substance	sodium metabisulphite Content: >= 0 % - <= 100 %	
Physical state	Solid, low dustiness	
Vapour pressure of the substance during use	0,009 Pa	
Process temperature	40 °C	
	Corresponds to a vapour pressure < 0.01 Pa	
Duration and Frequency of activity	480 min 5 days per week	
Indoor/Outdoor	Indoor	
	Operation is carried out at ambient or elevated temperatures	
Risk Management Measures		
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %	
Supervision in place to check that the RMMs in place are being used correctly and OCs followed. Clean equipment and the work area every day. Change clothes immediately after contamination. Ensure good work practices are implemented. Wash off any skin contamination immediately. Ensure minimization of manual phases Provide basic employee training to prevent/minimize exposures. Minimise number of staff exposed. Avoid contact with contaminated tools. Containment as appropriate Provide a		
good standard of general or controlled ventilation (5 to 10 air changes per hour)		
Wear suitable face shield, Wear		
suitable working clothes.		
Avoid contact with eyes. Use suitable eye protection.		
Exposure estimate and reference to its source		
Assessment method	EASY TRA v6.1, Workplace measurements	
<u> </u>		

Date / Revised: 01.08.2025 Version: 3.0
Date / Previous version: 24.06.2025 Previous version: 2.0

Product: Sodium Metabisulfite photo, non food grade

(ID no. 30042379/SDS_GEN_DE/EN)

	Worker - inhalation, long-term - systemic
Exposure estimate	0,1 mg/m³
Risk Characterization Ratio (RCR)	0,000444
Assessment method	Qualitative assessment
	Worker - inhalation

Contributing exposure scenario	
Use descriptors covered	PROC15: Use a laboratory reagent. Use domain: industrial
Operational conditions	
Concentration of the substance	sodium metabisulphite Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	0,009 Pa
Process temperature	40 °C
	Corresponds to a vapour pressure < 0.01 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Operation is carried out at ambient or elevated temperatures
Risk Management Measures	
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %
Supervision in place to check that the RMMs in place are being used correctly and OCs followed. Clean equipment and the work area every day. Change clothes immediately after contamination. Ensure good work practices are implemented. Wash off any skin contamination immediately. Ensure minimization of manual phases Provide basic employee training to prevent/minimize exposures. Minimise number of staff exposed. Avoid contact with contaminated tools. Containment as appropriate Provide a	
good standard of general or controlled ventilation (5 to 10 air changes per hour)	
Wear suitable face shield, Wear suitable working clothes.	

Date / Revised: 01.08.2025 Version: 3.0
Date / Previous version: 24.06.2025 Previous version: 2.0

Product: Sodium Metabisulfite photo, non food grade

(ID no. 30042379/SDS_GEN_DE/EN)

Avoid contact with eyes.	
Use suitable eye protection.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v6.1, Workplace measurements
	Worker - inhalation, long-term - systemic
Exposure estimate	0,01 mg/m ³
Risk Characterization Ratio (RCR)	0,000044
Assessment method	Qualitative assessment
	Worker - inhalation

Contributing exposure scenario	Contributing exposure scenario		
Use descriptors covered	PROC26: Handling of solid inorganic substances at ambient temperature Use domain: industrial		
Operational conditions			
Concentration of the substance	sodium metabisulphite Content: >= 0 % - <= 100 %		
Physical state	Solid, low dustiness		
Vapour pressure of the substance during use	0,009 Pa		
Process temperature	40 °C		
	Corresponds to a vapour pressure < 0.01 Pa		
Duration and Frequency of activity	480 min 5 days per week		
Indoor/Outdoor	Indoor		
	Operation is carried out at ambient or elevated temperatures		
Risk Management Measures			
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %		
Supervision in place to check that the RMMs in place are being used correctly and OCs followed. Clean equipment and the work area every day. Change clothes immediately after contamination. Ensure good work practices are implemented. Wash off any skin contamination immediately. Ensure minimization of manual phases Provide basic employee training to prevent/minimize exposures. Minimise number of staff exposed. Avoid contact with contaminated tools. Containment as appropriate Provide a			

Date / Revised: 01.08.2025 Version: 3.0
Date / Previous version: 24.06.2025 Previous version: 2.0

Product: Sodium Metabisulfite photo, non food grade

(ID no. 30042379/SDS_GEN_DE/EN)

good standard of general or controlled ventilation (5 to 10 air changes per hour)	
Wear suitable face shield, Wear	
suitable working clothes.	
Avoid contact with eyes.	
Use suitable eye protection.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v6.1, Workplace measurements
	Worker - inhalation, long-term - systemic
Exposure estimate	1,5 mg/m³
Risk Characterization Ratio (RCR)	0,006667
Assessment method	Qualitative assessment
	Worker - inhalation

Contributing exposure scenario	
Use descriptors covered	PROC26: Handling of solid inorganic substances at ambient temperature Use domain: industrial
Operational conditions	
Concentration of the substance	sodium metabisulphite Content: >= 0 % - <= 100 %
Physical state	Solid, low dustiness
Vapour pressure of the substance during use	0,009 Pa
Process temperature	40 °C
	Corresponds to a vapour pressure < 0.01 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Operation is carried out at ambient or elevated temperatures
Risk Management Measures	
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %
Supervision in place to check that the RMMs in place are being used correctly and OCs followed. Clean equipment and the work area every day. Change clothes immediately after contamination. Ensure good work practices are implemented. Wash off any skin contamination immediately. Ensure minimization of manual phases Provide basic employee	

Date / Revised: 01.08.2025 Version: 3.0
Date / Previous version: 24.06.2025 Previous version: 2.0

Product: Sodium Metabisulfite photo, non food grade

(ID no. 30042379/SDS_GEN_DE/EN)

training to prevent/minimize exposures. Minimise number of staff exposed. Avoid contact with contaminated tools.	
Containment as appropriate Provide a good standard of general or controlled ventilation (5 to 10 air changes per hour)	
Wear suitable face shield, Wear	
suitable working clothes.	
Avoid contact with eyes.	
Use suitable eye protection.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v6.1, Workplace measurements
	Worker - inhalation, long-term - systemic
Exposure estimate	1,5 mg/m³
Risk Characterization Ratio (RCR)	0,006667
Assessment method	Qualitative assessment
	Worker - inhalation

Contributing exposure scenario	
Use descriptors covered	PROC28: Manual maintenance (cleaning and repair) of machinery Use domain: industrial
Operational conditions	
Concentration of the substance	sodium metabisulphite Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	0,009 Pa
Process temperature	40 °C
	Corresponds to a vapour pressure < 0.01 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Operation is carried out at ambient or elevated temperatures
Risk Management Measures	
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %
Supervision in place to check that the RMMs in place are being used correctly and OCs followed. Clean equipment and the work area every day. Change clothes immediately after	

Version: 3.0

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Previous version: 24.06.2025

Previous version: 24.06.2025

Product: Sodium Metabisulfite photo, non food grade

(ID no. 30042379/SDS_GEN_DE/EN)

Date of print 22.10.2025

Previous version: 2.0

contamination. Ensure good work practices are implemented. Wash off any skin contamination immediately. Ensure minimization of manual phases Provide basic employee training to prevent/minimize exposures. Minimise number of staff exposed. Avoid contact with contaminated tools. Containment as appropriate Provide a good standard of general or controlled ventilation (5 to 10 air changes per	
hour)	
Wear suitable face shield, Wear suitable working clothes.	
Avoid contact with eyes.	
Use suitable eye protection.	
Exposure estimate and reference to it	ts source
Assessment method	EASY TRA v6.1, Workplace measurements
	Worker - inhalation, long-term - systemic
Exposure estimate	0,05 mg/m³
Risk Characterization Ratio (RCR)	0,000222
Assessment method	Qualitative assessment
	Worker - inhalation

Contributing exposure scenario	
Use descriptors covered	PROC28: Manual maintenance (cleaning and repair) of machinery Use domain: industrial
Operational conditions	
Concentration of the substance	sodium metabisulphite Content: >= 0 % - <= 100 %
Physical state	Solid, low dustiness
Vapour pressure of the substance during use	0,009 Pa
Process temperature	40 °C
	Corresponds to a vapour pressure < 0.01 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Operation is carried out at ambient or elevated temperatures
Risk Management Measures	
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %

Page: 32/126

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 01.08.2025 Version: 3.0
Date / Previous version: 24.06.2025 Previous version: 2.0

Product: Sodium Metabisulfite photo, non food grade

(ID no. 30042379/SDS_GEN_DE/EN)

Date of print 22.10.2025

Supervision in place to check that the RMMs in place are being used correctly and OCs followed. Clean equipment and the work area every day. Change clothes immediately after contamination. Ensure good work practices are implemented. Wash off any skin contamination immediately. Ensure minimization of manual phases Provide basic employee training to prevent/minimize exposures. Minimise number of staff exposed. Avoid contact with contaminated tools. Containment as appropriate Provide a good standard of general or controlled ventilation (5 to 10 air changes per hour) Wear suitable face shield, Wear suitable working clothes. Avoid contact with eyes. Use suitable eye protection. Exposure estimate and reference to its suitable working are being used.	its source
Assessment method	EASY TRA v6.1, Workplace measurements
	Worker - inhalation, long-term - systemic
Exposure estimate	1,5 mg/m³
Risk Characterization Ratio (RCR)	0,006667
Assessment method	Qualitative assessment
	Worker - inhalation

* * * * * * * * * * * * * * * *

2. Short title of exposure scenario

Formulation, Use in/as Photochemicals

F; ERC2, ERC3; PROC3, PROC4, PROC5, PROC8b, PROC9, PROC15, PROC26, PROC28; PC30

Control of exposure and risk management measures

Contributing exposure scenario	
Use descriptors covered	ERC2: Formulation into mixture As no environmental hazard was identified no environmental-related exposure assessment and risk characterization was performed.
Operational conditions	

Contributing exposure scenario	
Use descriptors covered	ERC3: Formulation into solid matrix

Date / Revised: 01.08.2025 Version: 3.0
Date / Previous version: 24.06.2025 Previous version: 2.0

Product: Sodium Metabisulfite photo, non food grade

(ID no. 30042379/SDS_GEN_DE/EN)

	As no environmental hazard was identified no environmental-related exposure assessment and risk characterization was performed.
Operational conditions	

Contributing ovnesure seems:	
Contributing exposure scenario	
Use descriptors covered	PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition Use domain: industrial
Operational conditions	
	sodium metabisulphite
Concentration of the substance	Content: >= 0 % - <= 100 %
Physical state	Solid, low dustiness
Vapour pressure of the substance during use	0,009 Pa
Process temperature	40 °C
	Corresponds to a vapour pressure < 0.01 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Operation is carried out at ambient or elevated temperatures
Risk Management Measures	
Provide a good standard of general	
ventilation (not less than 3 - 5 air	Effectiveness: 30 %
changes per hour)	
Supervision in place to check that the RMMs in place are being used correctly and OCs followed. Clean equipment and the work area every day. Change clothes immediately after contamination. Ensure good work practices are implemented. Wash off any skin contamination immediately. Ensure minimization of manual phases Provide basic employee training to prevent/minimize exposures. Minimise number of staff	
exposed. Avoid contact with contaminated tools.	
Containment as appropriate Provide a good standard of general or controlled ventilation (5 to 10 air changes per hour)	

to Regulation (EC) No 1907/2006. Date / Revised: 01.08.2025

Version: 3.0 Previous version: 2.0

Date / Previous version: 24.06.2025 Product: **Sodium Metabisulfite photo, non food grade**

(ID no. 30042379/SDS_GEN_DE/EN)

Wear suitable face shield, Wear suitable working clothes.	
Avoid contact with eyes.	
Use suitable eye protection.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v6.1, Workplace measurements
	Worker - inhalation, long-term - systemic
Exposure estimate	0,1 mg/m ³
Risk Characterization Ratio (RCR)	0,000444
Assessment method	Qualitative assessment
	Worker - inhalation

Contributing exposure scenario	
Use descriptors covered	PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition Use domain: industrial
Operational conditions	
Concentration of the substance	sodium metabisulphite Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	0,009 Pa
Process temperature	40 °C
	Corresponds to a vapour pressure < 0.01 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Operation is carried out at ambient or elevated temperatures
Risk Management Measures	
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %
Supervision in place to check that the RMMs in place are being used correctly and OCs followed. Clean equipment and the work area every day. Change clothes immediately after contamination. Ensure good work practices are implemented. Wash off any skin contamination immediately. Ensure minimization of manual phases Provide basic employee training to prevent/minimize	

Date / Revised: 01.08.2025 Version: 3.0
Date / Previous version: 24.06.2025 Previous version: 2.0

Product: Sodium Metabisulfite photo, non food grade

(ID no. 30042379/SDS_GEN_DE/EN)

exposures. Minimise number of staff exposed. Avoid contact with contaminated tools.	
Containment as appropriate Provide a	
good standard of general or controlled ventilation (5 to 10 air changes per	
hour)	
Wear suitable face shield, Wear	
suitable working clothes.	
Avoid contact with eyes.	
Use suitable eye protection.	
Exposure estimate and reference to	its source
Assessment method	EASY TRA v6.1, Workplace measurements
	Worker - inhalation, long-term - systemic
Exposure estimate	0,01 mg/m³
Risk Characterization Ratio (RCR)	0,000044
Assessment method	Qualitative assessment
	Worker - inhalation

Contributing exposure scenario	
Use descriptors covered	PROC4: Chemical production where opportunity for exposure arises Use domain: industrial
Operational conditions	
Concentration of the substance	sodium metabisulphite Content: >= 0 % - <= 100 %
Physical state	Solid, low dustiness
Vapour pressure of the substance during use	0,009 Pa
Process temperature	40 °C
	Corresponds to a vapour pressure < 0.01 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Operation is carried out at ambient or elevated temperatures
Risk Management Measures	
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %
Supervision in place to check that the RMMs in place are being used correctly and OCs followed. Clean equipment and the work area every day. Change clothes immediately after contamination. Ensure good work	

Date / Revised: 01.08.2025 Version: 3.0
Date / Previous version: 24.06.2025 Previous version: 2.0

Product: Sodium Metabisulfite photo, non food grade

(ID no. 30042379/SDS_GEN_DE/EN)

practices are implemented. Wash off any skin contamination immediately. Ensure minimization of manual phases Provide basic employee training to prevent/minimize exposures. Minimise number of staff	
exposed. Avoid contact with	
contaminated tools.	
Containment as appropriate Provide a	
good standard of general or controlled	
ventilation (5 to 10 air changes per	
hour)	
Wear suitable face shield, Wear	
suitable working clothes.	
Avoid contact with eyes.	
Use suitable eye protection.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v6.1, Workplace measurements
	Worker - inhalation, long-term - systemic
Exposure estimate	0,5 mg/m³
Risk Characterization Ratio (RCR)	0,002222
Assessment method	Qualitative assessment
	Worker - inhalation

Contributing exposure scenario	
Use descriptors covered	PROC4: Chemical production where opportunity for exposure arises Use domain: industrial
Operational conditions	
Concentration of the substance	sodium metabisulphite Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	0,009 Pa
Process temperature	40 °C
	Corresponds to a vapour pressure < 0.01 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Operation is carried out at ambient or elevated temperatures
Risk Management Measures	
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %
Supervision in place to check that the	

Date / Revised: 01.08.2025 Version: 3.0
Date / Previous version: 24.06.2025 Previous version: 2.0

Product: Sodium Metabisulfite photo, non food grade

(ID no. 30042379/SDS_GEN_DE/EN)

RMMs in place are being used correctly and OCs followed. Clean equipment and the work area every day. Change clothes immediately after contamination. Ensure good work practices are implemented. Wash off any skin contamination immediately. Ensure minimization of manual phases Provide basic employee training to prevent/minimize exposures. Minimise number of staff exposed. Avoid contact with contaminated tools. Containment as appropriate Provide a good standard of general or controlled ventilation (5 to 10 air changes per hour) Wear suitable face shield, Wear suitable working clothes. Avoid contact with eyes. Use suitable eye protection. Exposure estimate and reference to its Assessment method	EASY TRA v6.1, Workplace measurements
Fun cours estimate	Worker - inhalation, long-term - systemic
Exposure estimate	0,05 mg/m³
Risk Characterization Ratio (RCR)	0,000222
Assessment method	Qualitative assessment
	Worker - inhalation

Contributing exposure scenario	
Use descriptors covered	PROC5: Mixing or blending in batch processes Use domain: industrial
Operational conditions	
Concentration of the substance	sodium metabisulphite Content: >= 0 % - <= 100 %
Physical state	Solid, low dustiness
Vapour pressure of the substance during use	0,009 Pa
Process temperature	40 °C
	Corresponds to a vapour pressure < 0.01 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Operation is carried out at ambient or elevated temperatures
Risk Management Measures	

Date / Revised: 01.08.2025 Version: 3.0
Date / Previous version: 24.06.2025 Previous version: 2.0

Product: Sodium Metabisulfite photo, non food grade

(ID no. 30042379/SDS_GEN_DE/EN)

Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %
Supervision in place to check that the RMMs in place are being used correctly and OCs followed. Clean equipment and the work area every day. Change clothes immediately after contamination. Ensure good work practices are implemented. Wash off any skin contamination immediately. Ensure minimization of manual phases Provide basic employee training to prevent/minimize exposures. Minimise number of staff	
exposed. Avoid contact with contaminated tools.	
Containment as appropriate Provide a good standard of general or controlled ventilation (5 to 10 air changes per hour)	
Wear suitable face shield, Wear	
suitable working clothes.	
Avoid contact with eyes.	
Use suitable eye protection.	to course
Exposure estimate and reference to i	
Assessment method	EASY TRA v6.1, Workplace measurements
Evenous estimate	Worker - inhalation, long-term - systemic
Exposure estimate	0,5 mg/m³
Risk Characterization Ratio (RCR)	0,002222
Assessment method	Qualitative assessment
	Worker - inhalation

Contributing exposure scenario	
Use descriptors covered	PROC5: Mixing or blending in batch processes Use domain: industrial
Operational conditions	
Concentration of the substance	sodium metabisulphite Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	0,009 Pa
Process temperature	40 °C
	Corresponds to a vapour pressure < 0.01 Pa
Duration and Frequency of activity	480 min 5 days per week

Date / Revised: 01.08.2025 Version: 3.0 Date / Previous version: 24.06.2025 Previous version: 2.0

Product: Sodium Metabisulfite photo, non food grade

(ID no. 30042379/SDS_GEN_DE/EN)

Indoor/Outdoor	Indoor
	Operation is carried out at ambient or elevated
	temperatures
Risk Management Measures	
Provide a good standard of general	
ventilation (not less than 3 - 5 air	Effectiveness: 30 %
changes per hour)	
Supervision in place to check that the	
RMMs in place are being used	
correctly and OCs followed. Clean	
equipment and the work area every	
day. Change clothes immediately after	
contamination. Ensure good work	
practices are implemented. Wash off	
any skin contamination immediately. Ensure minimization of manual	
phases Provide basic employee	
training to prevent/minimize	
exposures. Minimise number of staff	
exposed. Avoid contact with	
contaminated tools.	
Containment as appropriate Provide a	
good standard of general or controlled	
ventilation (5 to 10 air changes per	
hour)	
Wear suitable face shield, Wear	
suitable working clothes.	
Avoid contact with eyes.	
Use suitable eye protection.	
Exposure estimate and reference to i	
Assessment method	EASY TRA v6.1, Workplace measurements
	Worker - inhalation, long-term - systemic
Exposure estimate	0,05 mg/m ³
Risk Characterization Ratio (RCR)	0,000222
Assessment method	Qualitative assessment
	Worker - inhalation

Contributing exposure scenario		
Use descriptors covered	PROC8b: Transfer of substance or mixture (charging and discharging) at dedicated facilities Use domain: industrial	
	Additional PROC(s) covered: Transfer of substance or preparation into small containers (dedicated filling line, including weighing).	
Operational conditions		
Concentration of the substance	sodium metabisulphite Content: >= 0 % - <= 100 %	

Date / Revised: 01.08.2025 Version: 3.0
Date / Previous version: 24.06.2025 Previous version: 2.0

Product: Sodium Metabisulfite photo, non food grade

(ID no. 30042379/SDS_GEN_DE/EN)

Physical state	liquid
Vapour pressure of the substance during use	0,009 Pa
Process temperature	40 °C
	Corresponds to a vapour pressure < 0.01 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Operation is carried out at ambient or elevated temperatures
Risk Management Measures	
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %
Supervision in place to check that the RMMs in place are being used correctly and OCs followed. Clean equipment and the work area every day. Change clothes immediately after contamination. Ensure good work practices are implemented. Wash off any skin contamination immediately. Ensure minimization of manual phases Provide basic employee training to prevent/minimize exposures. Minimise number of staff exposed. Avoid contact with contaminated tools.	
Containment as appropriate Provide a good standard of general or controlled ventilation (5 to 10 air changes per hour)	
Wear suitable face shield, Wear suitable working clothes.	
Avoid contact with eyes.	
Use suitable eye protection.	
Exposure estimate and reference to	ts source
Assessment method	EASY TRA v6.1, Workplace measurements
	Worker - inhalation, long-term - systemic
Exposure estimate	0,01 mg/m³
Risk Characterization Ratio (RCR)	0,000044
Assessment method	Qualitative assessment
	Worker - inhalation

Contributing exposure scenario	
Use descriptors covered	PROC15: Use a laboratory reagent. Use domain: industrial

Date / Revised: 01.08.2025 Version: 3.0
Date / Previous version: 24.06.2025 Previous version: 2.0

Product: Sodium Metabisulfite photo, non food grade

(ID no. 30042379/SDS_GEN_DE/EN)

Operational conditions	
-	sodium metabisulphite
Concentration of the substance	Content: >= 0 % - <= 100 %
Physical state	Solid, low dustiness
Vapour pressure of the substance during use	0,009 Pa
Process temperature	40 °C
	Corresponds to a vapour pressure < 0.01 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Operation is carried out at ambient or elevated temperatures
Risk Management Measures	
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %
Supervision in place to check that the RMMs in place are being used correctly and OCs followed. Clean equipment and the work area every day. Change clothes immediately after contamination. Ensure good work practices are implemented. Wash off any skin contamination immediately. Ensure minimization of manual phases Provide basic employee training to prevent/minimize exposures. Minimise number of staff exposed. Avoid contact with contaminated tools. Containment as appropriate Provide a good standard of general or controlled	
ventilation (5 to 10 air changes per hour) Wear suitable face shield, Wear	
suitable working clothes.	
Avoid contact with eyes.	
Use suitable eye protection.	
Exposure estimate and reference to it	ts source
Assessment method	EASY TRA v6.1, Workplace measurements
	Worker - inhalation, long-term - systemic
Exposure estimate	0,1 mg/m³
Risk Characterization Ratio (RCR)	0,000444
Assessment method	Qualitative assessment

Date / Revised: 01.08.2025 Version: 3.0
Date / Previous version: 24.06.2025 Previous version: 2.0

Product: Sodium Metabisulfite photo, non food grade

(ID no. 30042379/SDS_GEN_DE/EN)

Contributing exposure scenario	
Continuum CAPOSUIE SCENATIO	PROC15: Use a laboratory reagent.
Use descriptors covered	Use domain: industrial
Operational conditions	
	sodium metabisulphite
Concentration of the substance	Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	0,009 Pa
Process temperature	40 °C
	Corresponds to a vapour pressure < 0.01 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Operation is carried out at ambient or elevated temperatures
Risk Management Measures	
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %
Supervision in place to check that the RMMs in place are being used correctly and OCs followed. Clean equipment and the work area every day. Change clothes immediately after contamination. Ensure good work practices are implemented. Wash off any skin contamination immediately. Ensure minimization of manual phases Provide basic employee training to prevent/minimize exposures. Minimise number of staff exposed. Avoid contact with contaminated tools. Containment as appropriate Provide a good standard of general or controlled ventilation (5 to 10 air changes per hour)	
Wear suitable face shield, Wear suitable working clothes.	
Avoid contact with eyes.	
Use suitable eye protection.	
Exposure estimate and reference to	ts source
Assessment method	EASY TRA v6.1, Workplace measurements
	Worker - inhalation, long-term - systemic
Exposure estimate	0,01 mg/m ³

Date / Revised: 01.08.2025 Version: 3.0
Date / Previous version: 24.06.2025 Previous version: 2.0

Product: Sodium Metabisulfite photo, non food grade

(ID no. 30042379/SDS_GEN_DE/EN)

Risk Characterization Ratio (RCR)	0,000044
Assessment method	Qualitative assessment
	Worker - inhalation

Contributing exposure scenario	
Use descriptors covered	PROC26: Handling of solid inorganic substances at ambient temperature Use domain: industrial
Operational conditions	
Concentration of the substance	sodium metabisulphite Content: >= 0 % - <= 100 %
Physical state	Solid, low dustiness
Vapour pressure of the substance during use	0,009 Pa
Process temperature	40 °C
	Corresponds to a vapour pressure < 0.01 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Operation is carried out at ambient or elevated temperatures
Risk Management Measures	
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %
Supervision in place to check that the RMMs in place are being used correctly and OCs followed. Clean equipment and the work area every day. Change clothes immediately after contamination. Ensure good work practices are implemented. Wash off any skin contamination immediately. Ensure minimization of manual phases Provide basic employee training to prevent/minimize exposures. Minimise number of staff exposed. Avoid contact with contaminated tools. Containment as appropriate Provide a good standard of general or controlled ventilation (5 to 10 air changes per	
hour) Wear suitable face shield, Wear suitable working clothes.	
Avoid contact with eyes.	
Use suitable eye protection.	

Date / Revised: 01.08.2025 Version: 3.0
Date / Previous version: 24.06.2025 Previous version: 2.0

Product: Sodium Metabisulfite photo, non food grade

(ID no. 30042379/SDS_GEN_DE/EN)

Exposure estimate and reference to its source	
Assessment method	EASY TRA v6.1, Workplace measurements
	Worker - inhalation, long-term - systemic
Exposure estimate	1,5 mg/m³
Risk Characterization Ratio (RCR)	0,006667
Assessment method	Qualitative assessment
	Worker - inhalation

Contributing exposure scenario	
Use descriptors covered	PROC26: Handling of solid inorganic substances at ambient temperature Use domain: industrial
Operational conditions	
	sodium metabisulphite
Concentration of the substance	Content: >= 0 % - <= 100 %
Physical state	Solid, low dustiness
Vapour pressure of the substance during use	0,009 Pa
Process temperature	40 °C
	Corresponds to a vapour pressure < 0.01 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Operation is carried out at ambient or elevated temperatures
Risk Management Measures	
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %
Supervision in place to check that the RMMs in place are being used correctly and OCs followed. Clean equipment and the work area every day. Change clothes immediately after contamination. Ensure good work practices are implemented. Wash off any skin contamination immediately. Ensure minimization of manual phases Provide basic employee training to prevent/minimize exposures. Minimise number of staff exposed. Avoid contact with contaminated tools.	
Containment as appropriate Provide a good standard of general or controlled ventilation (5 to 10 air changes per	

Date / Revised: 01.08.2025 Version: 3.0
Date / Previous version: 24.06.2025 Previous version: 2.0

Product: Sodium Metabisulfite photo, non food grade

(ID no. 30042379/SDS_GEN_DE/EN)

hour)	
Wear suitable face shield, Wear	
suitable working clothes.	
Avoid contact with eyes.	
Use suitable eye protection.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v6.1, Workplace measurements
	Worker - inhalation, long-term - systemic
Exposure estimate	1,5 mg/m³
Risk Characterization Ratio (RCR)	0,006667
Assessment method	Qualitative assessment
	Worker - inhalation

Contributing exposure scenario	
Use descriptors covered	PROC28: Manual maintenance (cleaning and repair) of machinery Use domain: industrial
Operational conditions	
Concentration of the substance	sodium metabisulphite Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	0,009 Pa
Process temperature	40 °C
	Corresponds to a vapour pressure < 0.01 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Operation is carried out at ambient or elevated temperatures
Risk Management Measures	
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %
Supervision in place to check that the RMMs in place are being used correctly and OCs followed. Clean equipment and the work area every day. Change clothes immediately after contamination. Ensure good work practices are implemented. Wash off any skin contamination immediately. Ensure minimization of manual phases Provide basic employee training to prevent/minimize exposures. Minimise number of staff	

Date / Revised: 01.08.2025 Version: 3.0
Date / Previous version: 24.06.2025 Previous version: 2.0

Product: Sodium Metabisulfite photo, non food grade

(ID no. 30042379/SDS_GEN_DE/EN)

exposed. Avoid contact with contaminated tools.	
Containment as appropriate Provide a	
good standard of general or controlled ventilation (5 to 10 air changes per	
hour)	
Wear suitable face shield, Wear	
suitable working clothes.	
Avoid contact with eyes.	
Use suitable eye protection.	
Exposure estimate and reference to it	its source
Assessment method	EASY TRA v6.1, Workplace measurements
	Worker - inhalation, long-term - systemic
Exposure estimate	0,05 mg/m³
Risk Characterization Ratio (RCR)	0,000222
Assessment method	Qualitative assessment
	Worker - inhalation

Contributing exposure scenario		
Use descriptors covered	PROC28: Manual maintenance (cleaning and repair) of machinery Use domain: industrial	
Operational conditions	I	
Concentration of the substance	sodium metabisulphite Content: >= 0 % - <= 100 %	
Physical state	Solid, low dustiness	
Vapour pressure of the substance during use	0,009 Pa	
Process temperature	40 °C	
	Corresponds to a vapour pressure < 0.01 Pa	
Duration and Frequency of activity	480 min 5 days per week	
Indoor/Outdoor	Indoor	
	Operation is carried out at ambient or elevated temperatures	
Risk Management Measures		
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %	
Supervision in place to check that the RMMs in place are being used correctly and OCs followed. Clean equipment and the work area every day. Change clothes immediately after contamination. Ensure good work practices are implemented. Wash off		

Date / Revised: 01.08.2025 Version: 3.0
Date / Previous version: 24.06.2025 Previous version: 2.0

Product: Sodium Metabisulfite photo, non food grade

(ID no. 30042379/SDS_GEN_DE/EN)

Date of print 22.10.2025

any skin contamination immediately. Ensure minimization of manual phases Provide basic employee training to prevent/minimize exposures. Minimise number of staff exposed. Avoid contact with contaminated tools. Containment as appropriate Provide a good standard of general or controlled ventilation (5 to 10 air changes per hour) Wear suitable face shield, Wear	
suitable working clothes. Avoid contact with eyes.	
Use suitable eye protection.	
, ,	140 000000
Exposure estimate and reference to its source	
Assessment method	EASY TRA v6.1, Workplace measurements
	Worker - inhalation, long-term - systemic
Exposure estimate	1,5 mg/m³
Risk Characterization Ratio (RCR)	0,006667
Assessment method	Qualitative assessment
	Worker - inhalation

* * * * * * * * * * * * * * * *

3. Short title of exposure scenario

Industrial applications

IS; SU9, SU8; ERC6b; PROC3, PROC1, PROC4, PROC8b, PROC9, PROC26, PROC28; PC20

Control of exposure and risk management measures

Contributing exposure scenario	1
Use descriptors covered	ERC6b: Use of reactive processing aid at industrial site (no inclusion into or onto article) As no environmental hazard was identified no environmental-related exposure assessment and risk characterization was performed.
Operational conditions	,

Contributing exposure scenario	
Use descriptors covered	PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition Use domain: industrial
	Additional PROC(s) covered: Chemical production or

Date / Revised: 01.08.2025 Version: 3.0 Date / Previous version: 24.06.2025 Previous version: 2.0

Product: Sodium Metabisulfite photo, non food grade

(ID no. 30042379/SDS_GEN_DE/EN)

	refinery in closed process without likelihood of exposure or processes with equivalent containment conditions.
Operational conditions	
Concentration of the substance	sodium metabisulphite Content: >= 0 % - <= 100 %
Physical state	Solid, low dustiness
Vapour pressure of the substance during use	0,009 Pa
Process temperature	40 °C
	Corresponds to a vapour pressure < 0.01 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Operation is carried out at ambient or elevated temperatures
Risk Management Measures	
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %
Supervision in place to check that the RMMs in place are being used correctly and OCs followed. Clean equipment and the work area every day. Change clothes immediately after contamination. Ensure good work practices are implemented. Wash off any skin contamination immediately. Ensure minimization of manual phases Provide basic employee training to prevent/minimize exposures. Minimise number of staff exposed. Avoid contact with contaminated tools. Containment as appropriate Provide a	
good standard of general or controlled ventilation (5 to 10 air changes per hour)	
Wear suitable face shield, Wear suitable working clothes.	
Avoid contact with eyes.	
Use suitable eye protection.	<u></u>
Exposure estimate and reference to	
Assessment method	EASY TRA v6.1, Workplace measurements
Exposure estimate	Worker - inhalation, long-term - systemic 0,1 mg/m³
Risk Characterization Ratio (RCR)	0,000444

Date / Revised: 01.08.2025 Version: 3.0
Date / Previous version: 24.06.2025 Previous version: 2.0

Product: Sodium Metabisulfite photo, non food grade

(ID no. 30042379/SDS_GEN_DE/EN)

Assessment method	Qualitative assessment
	Worker - inhalation

Our (ell arthur annual annual a		
Contributing exposure scenario	DDOOA OLANGALAN LAGAA LA	
	PROC4: Chemical production where opportunity for	
Use descriptors covered	exposure arises	
p	Use domain: industrial	
Operational conditions		
•	sodium metabisulphite	
Concentration of the substance	Content: >= 0 % - <= 100 %	
Physical state	Solid, low dustiness	
Vapour pressure of the substance	0,009 Pa	
during use	,	
<u> </u>	40 °C	
Process temperature		
	Corresponds to a vapour pressure < 0.01 Pa	
D. office of Free Control	480 min 5 days per week	
Duration and Frequency of activity	y - r	
Indoor/Outdoor	Indoor	
	Operation is carried out at ambient or elevated	
	temperatures	
Risk Management Measures	•	
Provide a good standard of general		
ventilation (not less than 3 - 5 air	Effectiveness: 30 %	
changes per hour)		
Supervision in place to check that the		
RMMs in place are being used		
correctly and OCs followed. Clean		
equipment and the work area every		
day. Change clothes immediately after		
contamination. Ensure good work		
practices are implemented. Wash off		
any skin contamination immediately.		
Ensure minimization of manual		
phases Provide basic employee		
training to prevent/minimize		
exposures. Minimise number of staff		
exposed. Avoid contact with		
contaminated tools.		
Containment as appropriate Provide a		
good standard of general or controlled		
ventilation (5 to 10 air changes per		
hour)		
Wear suitable face shield, Wear		
suitable working clothes.		
Avoid contact with eyes.		
Use suitable eye protection.		
Exposure estimate and reference to i	ts source	

to Regulation (EC) No 1907/2006. Date / Revised: 01.08.2025

Version: 3.0 Previous version: 2.0

Date / Previous version: 24.06.2025 Product: **Sodium Metabisulfite photo, non food grade**

(ID no. 30042379/SDS_GEN_DE/EN)

Assessment method	EASY TRA v6.1, Workplace measurements
	Worker - inhalation, long-term - systemic
Exposure estimate	0,5 mg/m³
Risk Characterization Ratio (RCR)	0,002222
Assessment method	Qualitative assessment
	Worker - inhalation

Contributing avaccure accurate	
Contributing exposure scenario	DDOON T. (())
Use descriptors covered	PROC8b: Transfer of substance or mixture (charging and discharging) at dedicated facilities Use domain: industrial
	Additional PROC(s) covered: Transfer of substance or preparation into small containers (dedicated filling line, including weighing).
Operational conditions	I
Concentration of the substance	sodium metabisulphite Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	0,009 Pa
Process temperature	40 °C
	Corresponds to a vapour pressure < 0.01 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Operation is carried out at ambient or elevated temperatures
Risk Management Measures	
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %
Supervision in place to check that the RMMs in place are being used correctly and OCs followed. Clean equipment and the work area every day. Change clothes immediately after	
contamination. Ensure good work practices are implemented. Wash off any skin contamination immediately. Ensure minimization of manual phases Provide basic employee	
training to prevent/minimize exposures. Minimise number of staff exposed. Avoid contact with contaminated tools.	

Date / Revised: 01.08.2025 Version: 3.0
Date / Previous version: 24.06.2025 Previous version: 2.0

Product: Sodium Metabisulfite photo, non food grade

(ID no. 30042379/SDS_GEN_DE/EN)

Containment as appropriate Provide a good standard of general or controlled ventilation (5 to 10 air changes per hour)		
Wear suitable face shield, Wear		
suitable working clothes.		
Avoid contact with eyes.		
Use suitable eye protection.		
Exposure estimate and reference to its source		
Assessment method	EASY TRA v6.1, Workplace measurements	
	Worker - inhalation, long-term - systemic	
Exposure estimate	0,01 mg/m³	
Risk Characterization Ratio (RCR)	0,000044	
Assessment method	Qualitative assessment	
	Worker - inhalation	

Contributing exposure scenario	
Use descriptors covered	PROC26: Handling of solid inorganic substances at ambient temperature Use domain: industrial
Operational conditions	
Concentration of the substance	sodium metabisulphite Content: >= 0 % - <= 100 %
Physical state	Solid, low dustiness
Vapour pressure of the substance during use	0,009 Pa
Process temperature	40 °C
	Corresponds to a vapour pressure < 0.01 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Operation is carried out at ambient or elevated temperatures
Risk Management Measures	
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %
Supervision in place to check that the RMMs in place are being used correctly and OCs followed. Clean equipment and the work area every day. Change clothes immediately after contamination. Ensure good work practices are implemented. Wash off any skin contamination immediately. Ensure minimization of manual	

Date / Revised: 01.08.2025 Version: 3.0
Date / Previous version: 24.06.2025 Previous version: 2.0

Product: Sodium Metabisulfite photo, non food grade

(ID no. 30042379/SDS_GEN_DE/EN)

phases Provide basic employee training to prevent/minimize exposures. Minimise number of staff exposed. Avoid contact with contaminated tools. Containment as appropriate Provide a	
good standard of general or controlled	
ventilation (5 to 10 air changes per	
hour)	
Wear suitable face shield, Wear	
suitable working clothes.	
Avoid contact with eyes.	
Use suitable eye protection.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v6.1, Workplace measurements
	Worker - inhalation, long-term - systemic
Exposure estimate	1,5 mg/m³
Risk Characterization Ratio (RCR)	0,006667
Assessment method	Qualitative assessment
	Worker - inhalation

Contributing exposure scenario	
Use descriptors covered	PROC28: Manual maintenance (cleaning and repair) of machinery Use domain: industrial
Operational conditions	
Concentration of the substance	sodium metabisulphite Content: >= 0 % - <= 100 %
Physical state	Solid, low dustiness
Vapour pressure of the substance during use	0,009 Pa
Process temperature	40 °C
	Corresponds to a vapour pressure < 0.01 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Operation is carried out at ambient or elevated temperatures
Risk Management Measures	
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %
Supervision in place to check that the RMMs in place are being used correctly and OCs followed. Clean equipment and the work area every	

to Regulation (EC) No 1907/2006.

Date / Revised: 01.08.2025 Version: 3.0 Date / Previous version: 24.06.2025 Previous version: 2.0

Product: Sodium Metabisulfite photo, non food grade

(ID no. 30042379/SDS_GEN_DE/EN)

day. Change clothes immediately after contamination. Ensure good work practices are implemented. Wash off any skin contamination immediately. Ensure minimization of manual phases Provide basic employee training to prevent/minimize exposures. Minimise number of staff exposed. Avoid contact with contaminated tools. Containment as appropriate Provide a good standard of general or controlled ventilation (5 to 10 air changes per	
hour) Wear suitable face shield, Wear	
suitable working clothes.	
Avoid contact with eyes.	
Use suitable eye protection.	
Exposure estimate and reference to i	ts source
Assessment method	EASY TRA v6.1, Workplace measurements
	Worker - inhalation, long-term - systemic
Exposure estimate	1,5 mg/m³
Risk Characterization Ratio (RCR)	0,006667
Assessment method	Qualitative assessment
	Worker - inhalation

Contributing avacques cooperie	
Contributing exposure scenario	
Use descriptors covered	PROC28: Manual maintenance (cleaning and repair) of machinery Use domain: industrial
Operational conditions	
Concentration of the substance	sodium metabisulphite Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	0,009 Pa
Process temperature	40 °C
	Corresponds to a vapour pressure < 0.01 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Operation is carried out at ambient or elevated temperatures
Risk Management Measures	
Provide a good standard of general ventilation (not less than 3 - 5 air	Effectiveness: 30 %

Date / Revised: 01.08.2025 Version: 3.0
Date / Previous version: 24.06.2025 Previous version: 2.0

Product: Sodium Metabisulfite photo, non food grade

(ID no. 30042379/SDS_GEN_DE/EN)

Date of print 22.10.2025

changes per hour)	
Supervision in place to check that the	
RMMs in place are being used	
correctly and OCs followed. Clean	
equipment and the work area every	
day. Change clothes immediately after	
contamination. Ensure good work	
practices are implemented. Wash off	
any skin contamination immediately.	
Ensure minimization of manual	
phases Provide basic employee	
training to prevent/minimize	
exposures. Minimise number of staff exposed. Avoid contact with	
contaminated tools.	
Containment as appropriate Provide a	
good standard of general or controlled	
ventilation (5 to 10 air changes per	
hour)	
Wear suitable face shield, Wear	
suitable working clothes.	
Avoid contact with eyes.	
Use suitable eye protection.	
Exposure estimate and reference to it	
Assessment method	EASY TRA v6.1, Workplace measurements
	Worker - inhalation, long-term - systemic
Exposure estimate	0,05 mg/m³
Risk Characterization Ratio (RCR)	0,000222
Assessment method	Qualitative assessment
	Worker - inhalation

4. Short title of exposure scenario

Industrial applications, Intermediate for the manufacture of bulk chemicals, materials and resins IS; SU9, SU8; ERC6a; PROC3, PROC8b, PROC9, PROC15, PROC26, PROC28

Control of exposure and risk management measures

Contributing exposure scenario	
Use descriptors covered	ERC6a: Use of intermediate As no environmental hazard was identified no environmental-related exposure assessment and risk characterization was performed.
Operational conditions	

Contributing exposure scenario

Date / Revised: 01.08.2025 Version: 3.0
Date / Previous version: 24.06.2025 Previous version: 2.0

Product: Sodium Metabisulfite photo, non food grade

(ID no. 30042379/SDS_GEN_DE/EN)

Use descriptors covered	PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition Use domain: industrial
Operational conditions	
Concentration of the substance	sodium metabisulphite Content: >= 0 % - <= 100 %
Physical state	Solid, low dustiness
Vapour pressure of the substance during use	0,009 Pa
Process temperature	40 °C
	Corresponds to a vapour pressure < 0.01 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Operation is carried out at ambient or elevated temperatures
Risk Management Measures	·
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %
Supervision in place to check that the RMMs in place are being used correctly and OCs followed. Clean equipment and the work area every day. Change clothes immediately after contamination. Ensure good work practices are implemented. Wash off any skin contamination immediately. Ensure minimization of manual phases Provide basic employee training to prevent/minimize exposures. Minimise number of staff exposed. Avoid contact with contaminated tools. Containment as appropriate Provide a good standard of general or controlled ventilation (5 to 10 air changes per hour)	
Wear suitable face shield, Wear suitable working clothes.	
Avoid contact with eyes.	
Use suitable eye protection.	
Exposure estimate and reference to i	ts source
Assessment method	EASY TRA v6.1, Workplace measurements Worker - inhalation, long-term - systemic

to Regulation (EC) No 1907/2006.

Date / Revised: 01.08.2025 Version: 3.0 Date / Previous version: 24.06.2025 Previous version: 2.0

Product: Sodium Metabisulfite photo, non food grade

(ID no. 30042379/SDS_GEN_DE/EN)

Exposure estimate	0,1 mg/m³
Risk Characterization Ratio (RCR)	0,000444
Assessment method	Qualitative assessment
	Worker - inhalation

Contributing exposure scenario	
Use descriptors covered	PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition Use domain: industrial
Operational conditions	
Concentration of the substance	sodium metabisulphite Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	0,009 Pa
Process temperature	40 °C
	Corresponds to a vapour pressure < 0.01 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Operation is carried out at ambient or elevated temperatures
Risk Management Measures	
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %
Supervision in place to check that the RMMs in place are being used correctly and OCs followed. Clean equipment and the work area every day. Change clothes immediately after contamination. Ensure good work practices are implemented. Wash off any skin contamination immediately. Ensure minimization of manual phases Provide basic employee training to prevent/minimize exposures. Minimise number of staff exposed. Avoid contact with contaminated tools. Containment as appropriate Provide a good standard of general or controlled ventilation (5 to 10 air changes per hour)	
Wear suitable face shield, Wear	

Date / Revised: 01.08.2025 Version: 3.0
Date / Previous version: 24.06.2025 Previous version: 2.0

Product: Sodium Metabisulfite photo, non food grade

(ID no. 30042379/SDS_GEN_DE/EN)

suitable working clothes.	
Avoid contact with eyes.	
Use suitable eye protection.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v6.1, Workplace measurements
	Worker - inhalation, long-term - systemic
Exposure estimate	0,01 mg/m³
Risk Characterization Ratio (RCR)	0,000044
Assessment method	Qualitative assessment
	Worker - inhalation

Contributing exposure scenario	
Use descriptors covered	PROC8b: Transfer of substance or mixture (charging and discharging) at dedicated facilities Use domain: industrial
	Additional PROC(s) covered: Transfer of substance or preparation into small containers (dedicated filling line, including weighing).
Operational conditions	
Concentration of the substance	sodium metabisulphite Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	0,009 Pa
Process temperature	40 °C
	Corresponds to a vapour pressure < 0.01 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Operation is carried out at ambient or elevated temperatures
Risk Management Measures	•
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %
Supervision in place to check that the RMMs in place are being used correctly and OCs followed. Clean equipment and the work area every day. Change clothes immediately after contamination. Ensure good work practices are implemented. Wash off any skin contamination immediately. Ensure minimization of manual phases Provide basic employee	

Date / Revised: 01.08.2025 Version: 3.0
Date / Previous version: 24.06.2025 Previous version: 2.0

Product: Sodium Metabisulfite photo, non food grade

(ID no. 30042379/SDS_GEN_DE/EN)

training to prevent/minimize exposures. Minimise number of staff exposed. Avoid contact with contaminated tools.	
Containment as appropriate Provide a good standard of general or controlled ventilation (5 to 10 air changes per hour)	
Wear suitable face shield, Wear suitable working clothes.	
Avoid contact with eyes.	
Use suitable eye protection.	
Exposure estimate and reference to it	its source
Assessment method	EASY TRA v6.1, Workplace measurements
	Worker - inhalation, long-term - systemic
Exposure estimate	0,01 mg/m³
Risk Characterization Ratio (RCR)	0,000044
Assessment method	Qualitative assessment
	Worker - inhalation

Contributing exposure scenario	
Use descriptors covered	PROC15: Use a laboratory reagent. Use domain: industrial
Operational conditions	
Concentration of the substance	sodium metabisulphite Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	0,009 Pa
Process temperature	40 °C
	Corresponds to a vapour pressure < 0.01 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Operation is carried out at ambient or elevated temperatures
Risk Management Measures	
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %
Supervision in place to check that the RMMs in place are being used correctly and OCs followed. Clean equipment and the work area every day. Change clothes immediately after contamination. Ensure good work	

Date / Revised: 01.08.2025 Version: 3.0
Date / Previous version: 24.06.2025 Previous version: 2.0

Product: Sodium Metabisulfite photo, non food grade

(ID no. 30042379/SDS_GEN_DE/EN)

practices are implemented. Wash off any skin contamination immediately. Ensure minimization of manual phases Provide basic employee training to prevent/minimize exposures. Minimise number of staff exposed. Avoid contact with contaminated tools. Containment as appropriate Provide a good standard of general or controlled ventilation (5 to 10 air changes per hour) Wear suitable face shield, Wear		
suitable working clothes.		
Avoid contact with eyes.		
Use suitable eye protection.		
Exposure estimate and reference to its source		
Assessment method	EASY TRA v6.1, Workplace measurements	
	Worker - inhalation, long-term - systemic	
Exposure estimate	0,01 mg/m³	
Risk Characterization Ratio (RCR)	0,000044	
Assessment method	Qualitative assessment	
	Worker - inhalation	

Contributing exposure scenario	
·	PROC15: Use a laboratory reagent.
Use descriptors covered	Use domain: industrial
Operational conditions	
	sodium metabisulphite
Concentration of the substance	Content: >= 0 % - <= 100 %
Physical state	Solid, low dustiness
Vapour pressure of the substance	0,009 Pa
during use	0,000 1 0
	40 °C
Process temperature	
	Corresponds to a vapour pressure < 0.01 Pa
Duration and Francisco of activity	480 min 5 days per week
Duration and Frequency of activity	
Indoor/Outdoor	Indoor
	Operation is carried out at ambient or elevated
	temperatures
Risk Management Measures	
Provide a good standard of general	
ventilation (not less than 3 - 5 air	Effectiveness: 30 %
changes per hour)	
Supervision in place to check that the	
RMMs in place are being used	

Date / Revised: 01.08.2025 Version: 3.0
Date / Previous version: 24.06.2025 Previous version: 2.0

Product: Sodium Metabisulfite photo, non food grade

(ID no. 30042379/SDS_GEN_DE/EN)

correctly and OCs followed. Clean equipment and the work area every day. Change clothes immediately after contamination. Ensure good work practices are implemented. Wash off any skin contamination immediately. Ensure minimization of manual phases Provide basic employee training to prevent/minimize exposures. Minimise number of staff exposed. Avoid contact with contaminated tools. Containment as appropriate Provide a good standard of general or controlled ventilation (5 to 10 air changes per hour) Wear suitable face shield, Wear suitable working clothes. Avoid contact with eyes. Use suitable eye protection. Exposure estimate and reference to its Assessment method	EASY TRA v6.1, Workplace measurements
Evacoura estimata	Worker - inhalation, long-term - systemic
Exposure estimate	0,1 mg/m³
Risk Characterization Ratio (RCR)	0,000444
Assessment method	Qualitative assessment
	Worker - inhalation

Contributing exposure scenario	
Use descriptors covered	PROC26: Handling of solid inorganic substances at ambient temperature Use domain: industrial
Operational conditions	
Concentration of the substance	sodium metabisulphite Content: >= 0 % - <= 100 %
Physical state	Solid, low dustiness
Vapour pressure of the substance during use	0,009 Pa
Process temperature	40 °C
	Corresponds to a vapour pressure < 0.01 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Operation is carried out at ambient or elevated temperatures
Risk Management Measures	

Date / Previous version: 24.06.2025

Version: 3.0

Previous version: 24.06.2025

Previous version: 2.0

Product: Sodium Metabisulfite photo, non food grade

(ID no. 30042379/SDS_GEN_DE/EN)

Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %
Supervision in place to check that the RMMs in place are being used correctly and OCs followed. Clean equipment and the work area every day. Change clothes immediately after contamination. Ensure good work practices are implemented. Wash off any skin contamination immediately. Ensure minimization of manual phases Provide basic employee training to prevent/minimize exposures. Minimise number of staff	
exposed. Avoid contact with contaminated tools.	
Containment as appropriate Provide a good standard of general or controlled ventilation (5 to 10 air changes per hour)	
Wear suitable face shield, Wear	
suitable working clothes.	
Avoid contact with eyes.	
Use suitable eye protection. Exposure estimate and reference to it.	te course
Assessment method	EASY TRA v6.1, Workplace measurements
Evenous estimate	Worker - inhalation, long-term - systemic
Exposure estimate	1,5 mg/m³
Risk Characterization Ratio (RCR)	0,006667
Assessment method	Qualitative assessment
	Worker - inhalation

Contributing exposure scenario	
Use descriptors covered	PROC28: Manual maintenance (cleaning and repair) of machinery Use domain: industrial
Operational conditions	
Concentration of the substance	sodium metabisulphite Content: >= 0 % - <= 100 %
Physical state	Solid, low dustiness
Vapour pressure of the substance during use	0,009 Pa
Process temperature	40 °C
	Corresponds to a vapour pressure < 0.01 Pa
Duration and Frequency of activity	480 min 5 days per week

Date / Revised: 01.08.2025 Version: 3.0 Date / Previous version: 24.06.2025 Previous version: 2.0

Product: Sodium Metabisulfite photo, non food grade

(ID no. 30042379/SDS_GEN_DE/EN)

Indoor/Outdoor	Indoor
	Operation is carried out at ambient or elevated
	temperatures
Risk Management Measures	
Provide a good standard of general	
ventilation (not less than 3 - 5 air	Effectiveness: 30 %
changes per hour)	
Supervision in place to check that the	
RMMs in place are being used	
correctly and OCs followed. Clean	
equipment and the work area every	
day. Change clothes immediately after	
contamination. Ensure good work	
practices are implemented. Wash off any skin contamination immediately.	
Ensure minimization of manual	
phases Provide basic employee	
training to prevent/minimize	
exposures. Minimise number of staff	
exposed. Avoid contact with	
contaminated tools.	
Containment as appropriate Provide a	
good standard of general or controlled	
ventilation (5 to 10 air changes per	
hour)	
Wear suitable face shield, Wear	
suitable working clothes.	
Avoid contact with eyes.	
Use suitable eye protection.	
Exposure estimate and reference to i	
Assessment method	EASY TRA v6.1, Workplace measurements
	Worker - inhalation, long-term - systemic
Exposure estimate	1,5 mg/m³
Risk Characterization Ratio (RCR)	0,006667
Assessment method	Qualitative assessment
	Worker - inhalation

Contributing exposure scenario	
Use descriptors covered	PROC28: Manual maintenance (cleaning and repair) of machinery Use domain: industrial
Operational conditions	
Concentration of the substance	sodium metabisulphite Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance	0.009 Pa

Date / Revised: 01.08.2025 Version: 3.0
Date / Previous version: 24.06.2025 Previous version: 2.0

Product: Sodium Metabisulfite photo, non food grade

(ID no. 30042379/SDS_GEN_DE/EN)

Date of print 22.10.2025

during use	
Process temperature	40 °C
	Corresponds to a vapour pressure < 0.01 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Operation is carried out at ambient or elevated temperatures
Risk Management Measures	
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %
Supervision in place to check that the RMMs in place are being used correctly and OCs followed. Clean equipment and the work area every day. Change clothes immediately after contamination. Ensure good work practices are implemented. Wash off any skin contamination immediately. Ensure minimization of manual phases Provide basic employee training to prevent/minimize exposures. Minimise number of staff exposed. Avoid contact with contaminated tools. Containment as appropriate Provide a good standard of general or controlled ventilation (5 to 10 air changes per hour)	
Wear suitable face shield, Wear	
suitable working clothes.	
Avoid contact with eyes.	
Use suitable eye protection.	<u> </u>
Exposure estimate and reference to	
Assessment method	EASY TRA v6.1, Workplace measurements
Evaceura actimata	Worker - inhalation, long-term - systemic
Exposure estimate Risk Characterization Ratio (RCR)	0,05 mg/m³ 0,000222
Assessment method	Qualitative assessment
Assessment method	Worker - inhalation
	Worker - Illiaation

* * * * * * * * * * * * * * *

5. Short title of exposure scenario

Industrial applications, Manufacture of fine chemicals

Date / Revised: 01.08.2025 Version: 3.0
Date / Previous version: 24.06.2025 Previous version: 2.0

Product: Sodium Metabisulfite photo, non food grade

(ID no. 30042379/SDS_GEN_DE/EN)

Date of print 22.10.2025

IS; SU9, SU24, SU20; ERC6b; PROC3, PROC2, PROC1, PROC4, PROC5, PROC8b, PROC9, PROC15, PROC26, PROC28; PC21, PC20

Control of exposure and risk management measures

Contributing exposure scenario	
Use descriptors covered	ERC6b: Use of reactive processing aid at industrial site (no inclusion into or onto article) As no environmental hazard was identified no environmental-related exposure assessment and risk characterization was performed.
Operational conditions	

Contributing exposure scenario	
Use descriptors covered	PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition Use domain: industrial
	Additional PROC(s) covered: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions.
Operational conditions	
Concentration of the substance	sodium metabisulphite Content: >= 0 % - <= 100 %
Physical state	Solid, low dustiness
Vapour pressure of the substance during use	0,009 Pa
Process temperature	40 °C
	Corresponds to a vapour pressure < 0.01 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Operation is carried out at ambient or elevated temperatures
Risk Management Measures	
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %
Supervision in place to check that the RMMs in place are being used	

Date / Revised: 01.08.2025 Version: 3.0
Date / Previous version: 24.06.2025 Previous version: 2.0

Product: Sodium Metabisulfite photo, non food grade

(ID no. 30042379/SDS_GEN_DE/EN)

correctly and OCs followed. Clean equipment and the work area every day. Change clothes immediately after contamination. Ensure good work practices are implemented. Wash off any skin contamination immediately. Ensure minimization of manual phases Provide basic employee training to prevent/minimize exposures. Minimise number of staff exposed. Avoid contact with contaminated tools. Containment as appropriate Provide a good standard of general or controlled ventilation (5 to 10 air changes per hour) Wear suitable face shield, Wear suitable working clothes. Avoid contact with eyes. Use suitable eye protection. Exposure estimate and reference to its Assessment method	EASY TRA v6.1, Workplace measurements
	Worker - inhalation, long-term - systemic
Exposure estimate	0,1 mg/m³
Risk Characterization Ratio (RCR)	0,000444
Assessment method	Qualitative assessment
	Worker - inhalation

Contributing exposure scenario	
Use descriptors covered	PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition Use domain: industrial
	Additional PROC(s) covered: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions.
Operational conditions	
Concentration of the substance	sodium metabisulphite Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	0,009 Pa
Process temperature	40 °C

Date / Revised: 01.08.2025 Version: 3.0
Date / Previous version: 24.06.2025 Previous version: 2.0

Product: Sodium Metabisulfite photo, non food grade

(ID no. 30042379/SDS_GEN_DE/EN)

	Corresponds to a vapour pressure < 0.01 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Operation is carried out at ambient or elevated
	temperatures
Risk Management Measures	
Provide a good standard of general	
ventilation (not less than 3 - 5 air	Effectiveness: 30 %
changes per hour)	
Supervision in place to check that the	
RMMs in place are being used	
correctly and OCs followed. Clean	
equipment and the work area every	
day. Change clothes immediately after	
contamination. Ensure good work	
practices are implemented. Wash off	
any skin contamination immediately.	
Ensure minimization of manual	
phases Provide basic employee	
training to prevent/minimize exposures. Minimise number of staff	
exposed. Avoid contact with	
contaminated tools.	
Containment as appropriate Provide a	
good standard of general or controlled	
ventilation (5 to 10 air changes per	
hour)	
Wear suitable face shield, Wear	
suitable working clothes.	
Avoid contact with eyes.	
Use suitable eye protection.	
Exposure estimate and reference to	its source
Assessment method	EASY TRA v6.1, Workplace measurements
	Worker - inhalation, long-term - systemic
Exposure estimate	0,01 mg/m³
Risk Characterization Ratio (RCR)	0,000044
Assessment method	Qualitative assessment
	Worker - inhalation

Contributing exposure scenario	
Use descriptors covered	PROC4: Chemical production where opportunity for exposure arises Use domain: industrial
Operational conditions	
Concentration of the substance	sodium metabisulphite Content: >= 0 % - <= 100 %

Date / Revised: 01.08.2025 Version: 3.0
Date / Previous version: 24.06.2025 Previous version: 2.0

Product: Sodium Metabisulfite photo, non food grade

(ID no. 30042379/SDS_GEN_DE/EN)

Physical state	Solid, low dustiness
Vapour pressure of the substance during use	0,009 Pa
Process temperature	40 °C
	Corresponds to a vapour pressure < 0.01 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Operation is carried out at ambient or elevated temperatures
Risk Management Measures	
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %
Supervision in place to check that the RMMs in place are being used correctly and OCs followed. Clean equipment and the work area every day. Change clothes immediately after contamination. Ensure good work practices are implemented. Wash off any skin contamination immediately. Ensure minimization of manual phases Provide basic employee training to prevent/minimize exposures. Minimise number of staff exposed. Avoid contact with contaminated tools.	
Containment as appropriate Provide a good standard of general or controlled ventilation (5 to 10 air changes per hour)	
Wear suitable face shield, Wear	
suitable working clothes. Avoid contact with eyes.	
Use suitable eye protection.	
Exposure estimate and reference to i	ts source
Assessment method	EASY TRA v6.1, Workplace measurements
	Worker - inhalation, long-term - systemic
Exposure estimate	0,5 mg/m ³
Risk Characterization Ratio (RCR)	0,002222
Assessment method	Qualitative assessment
	Worker - inhalation

Contributing exposure scenario	
Use descriptors covered	PROC4: Chemical production where opportunity for
	exposure arises

Date / Revised: 01.08.2025 Version: 3.0
Date / Previous version: 24.06.2025 Previous version: 2.0

Product: Sodium Metabisulfite photo, non food grade

(ID no. 30042379/SDS_GEN_DE/EN)

	Use domain: industrial
Operational conditions	
Concentration of the substance	sodium metabisulphite Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	0,009 Pa
Process temperature	40 °C
	Corresponds to a vapour pressure < 0.01 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Operation is carried out at ambient or elevated temperatures
Risk Management Measures	
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %
Supervision in place to check that the RMMs in place are being used correctly and OCs followed. Clean equipment and the work area every day. Change clothes immediately after contamination. Ensure good work practices are implemented. Wash off any skin contamination immediately. Ensure minimization of manual phases Provide basic employee training to prevent/minimize exposures. Minimise number of staff exposed. Avoid contact with contaminated tools. Containment as appropriate Provide a good standard of general or controlled ventilation (5 to 10 air changes per hour)	
Wear suitable face shield, Wear suitable working clothes.	
Avoid contact with eyes.	
Use suitable eye protection.	
Exposure estimate and reference to i	
Assessment method	EASY TRA v6.1, Workplace measurements Worker - inhalation, long-term - systemic
Exposure estimate	0,05 mg/m ³
Risk Characterization Ratio (RCR)	0,000222
Assessment method	Qualitative assessment

Date / Revised: 01.08.2025 Version: 3.0
Date / Previous version: 24.06.2025 Previous version: 2.0

Product: Sodium Metabisulfite photo, non food grade

(ID no. 30042379/SDS_GEN_DE/EN)

Date of print 22.10.2025

Worker - inhalation

Contributing exposure scenario		
<u> </u>	PROC5: Mixing or blending in batch processes	
Use descriptors covered	Use domain: industrial	
Operational conditions	I.	
	sodium metabisulphite	
Concentration of the substance	Content: >= 0 % - <= 100 %	
Physical state	Solid, low dustiness	
Vapour pressure of the substance during use	0,009 Pa	
Process temperature	40 °C	
	Corresponds to a vapour pressure < 0.01 Pa	
Duration and Frequency of activity	480 min 5 days per week	
Indoor/Outdoor	Indoor	
	Operation is carried out at ambient or elevated temperatures	
Risk Management Measures		
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %	
Supervision in place to check that the RMMs in place are being used correctly and OCs followed. Clean equipment and the work area every day. Change clothes immediately after contamination. Ensure good work practices are implemented. Wash off any skin contamination immediately. Ensure minimization of manual phases Provide basic employee training to prevent/minimize exposures. Minimise number of staff exposed. Avoid contact with contaminated tools. Containment as appropriate Provide a		
good standard of general or controlled ventilation (5 to 10 air changes per hour)		
Wear suitable face shield, Wear		
suitable working clothes. Avoid contact with eyes.		
Use suitable eye protection.		
Exposure estimate and reference to i	its source	
Assessment method	EASY TRA v6.1, Workplace measurements	

Date / Revised: 01.08.2025 Version: 3.0 Date / Previous version: 24.06.2025 Previous version: 2.0

Product: Sodium Metabisulfite photo, non food grade

(ID no. 30042379/SDS_GEN_DE/EN)

	Worker - inhalation, long-term - systemic
Exposure estimate	0,5 mg/m³
Risk Characterization Ratio (RCR)	0,002222
Assessment method	Qualitative assessment
	Worker - inhalation

Contributing exposure scenario	
Contributing exposure scenario	
Use descriptors covered	PROC5: Mixing or blending in batch processes Use domain: industrial
	SSS GSMain industrial
Operational conditions	
	sodium metabisulphite
Concentration of the substance	Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance	0,009 Pa
during use	0,0001 a
Process temperature	40 °C
r locess temperature	
	Corresponds to a vapour pressure < 0.01 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Operation is carried out at ambient or elevated
	temperatures
Risk Management Measures	
Provide a good standard of general	
ventilation (not less than 3 - 5 air	Effectiveness: 30 %
changes per hour)	
Supervision in place to check that the	
RMMs in place are being used	
correctly and OCs followed. Clean equipment and the work area every	
day. Change clothes immediately after	
contamination. Ensure good work	
practices are implemented. Wash off	
any skin contamination immediately.	
Ensure minimization of manual	
phases Provide basic employee	
training to prevent/minimize	
exposures. Minimise number of staff	
exposed. Avoid contact with	
contaminated tools.	
Containment as appropriate Provide a	
good standard of general or controlled	
ventilation (5 to 10 air changes per	
hour)	
Wear suitable face shield, Wear	
suitable working clothes.	

Date / Revised: 01.08.2025 Version: 3.0
Date / Previous version: 24.06.2025 Previous version: 2.0

Product: Sodium Metabisulfite photo, non food grade

(ID no. 30042379/SDS_GEN_DE/EN)

Avoid contact with eyes.	
Use suitable eye protection.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v6.1, Workplace measurements
	Worker - inhalation, long-term - systemic
Exposure estimate	0,05 mg/m³
Risk Characterization Ratio (RCR)	0,000222
Assessment method	Qualitative assessment
	Worker - inhalation

Contributing exposure scenario	
Use descriptors covered	PROC8b: Transfer of substance or mixture (charging and discharging) at dedicated facilities Use domain: industrial
	Additional PROC(s) covered: Transfer of substance or preparation into small containers (dedicated filling line, including weighing).
Operational conditions	
Concentration of the substance	sodium metabisulphite Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	0,009 Pa
Process temperature	40 °C
	Corresponds to a vapour pressure < 0.01 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Operation is carried out at ambient or elevated temperatures
Risk Management Measures	
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %
Supervision in place to check that the RMMs in place are being used correctly and OCs followed. Clean equipment and the work area every day. Change clothes immediately after contamination. Ensure good work practices are implemented. Wash off any skin contamination immediately. Ensure minimization of manual phases Provide basic employee training to prevent/minimize	

Date / Revised: 01.08.2025 Version: 3.0
Date / Previous version: 24.06.2025 Previous version: 2.0

Product: Sodium Metabisulfite photo, non food grade

(ID no. 30042379/SDS_GEN_DE/EN)

exposures. Minimise number of staff exposed. Avoid contact with contaminated tools.	
Containment as appropriate Provide a	
good standard of general or controlled ventilation (5 to 10 air changes per	
hour)	
Wear suitable face shield, Wear	
suitable working clothes.	
Avoid contact with eyes.	
Use suitable eye protection.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v6.1, Workplace measurements
	Worker - inhalation, long-term - systemic
Exposure estimate	0,01 mg/m³
Risk Characterization Ratio (RCR)	0,000044
Assessment method	Qualitative assessment
	Worker - inhalation

Contributing exposure scenario	
Has descriptors solvered	PROC15: Use a laboratory reagent.
Use descriptors covered	Use domain: industrial
Operational conditions	
	sodium metabisulphite
Concentration of the substance	Content: >= 0 % - <= 100 %
Physical state	Solid, low dustiness
Vapour pressure of the substance during use	0,009 Pa
Process temperature	40 °C
	Corresponds to a vapour pressure < 0.01 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Operation is carried out at ambient or elevated temperatures
Risk Management Measures	
Provide a good standard of general ventilation (not less than 3 - 5 air	Effectiveness: 30 %
changes per hour)	
Supervision in place to check that the	
RMMs in place are being used	
correctly and OCs followed. Clean equipment and the work area every	
day. Change clothes immediately after	
contamination. Ensure good work	
practices are implemented. Wash off	

Date / Revised: 01.08.2025 Version: 3.0
Date / Previous version: 24.06.2025 Previous version: 2.0

Product: Sodium Metabisulfite photo, non food grade

(ID no. 30042379/SDS_GEN_DE/EN)

any skin contamination immediately. Ensure minimization of manual phases Provide basic employee training to prevent/minimize exposures. Minimise number of staff exposed. Avoid contact with contaminated tools. Containment as appropriate Provide a good standard of general or controlled ventilation (5 to 10 air changes per hour)	
Wear suitable face shield, Wear	
suitable working clothes.	
Avoid contact with eyes.	
Use suitable eye protection.	
Exposure estimate and reference to it	ts source
Assessment method	EASY TRA v6.1, Workplace measurements
	Worker - inhalation, long-term - systemic
Exposure estimate	0,1 mg/m³
Risk Characterization Ratio (RCR)	0,000444
Assessment method	Qualitative assessment
	Worker - inhalation

Contributing exposure scenario	
Use descriptors covered	PROC15: Use a laboratory reagent. Use domain: industrial
Operational conditions	
Concentration of the substance	sodium metabisulphite Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	0,009 Pa
Process temperature	40 °C
	Corresponds to a vapour pressure < 0.01 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Operation is carried out at ambient or elevated temperatures
Risk Management Measures	
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %
Supervision in place to check that the RMMs in place are being used correctly and OCs followed. Clean	

to Regulation (EC) No 1907/2006.

Date / Revised: 01.08.2025 Version: 3.0 Date / Previous version: 24.06.2025 Previous version: 2.0

Product: Sodium Metabisulfite photo, non food grade

(ID no. 30042379/SDS_GEN_DE/EN)

equipment and the work area every day. Change clothes immediately after contamination. Ensure good work practices are implemented. Wash off any skin contamination immediately. Ensure minimization of manual phases Provide basic employee training to prevent/minimize exposures. Minimise number of staff exposed. Avoid contact with contaminated tools. Containment as appropriate Provide a good standard of general or controlled ventilation (5 to 10 air changes per hour)	
Wear suitable face shield, Wear	
suitable working clothes.	
Avoid contact with eyes.	
Use suitable eye protection.	
Exposure estimate and reference to it	ts source
Assessment method	EASY TRA v6.1, Workplace measurements
	Worker - inhalation, long-term - systemic
Exposure estimate	0,01 mg/m³
Risk Characterization Ratio (RCR)	0,000044
Assessment method	Qualitative assessment
	Worker - inhalation

Contributing exposure scenario	
Use descriptors covered	PROC26: Handling of solid inorganic substances at ambient temperature Use domain: industrial
Operational conditions	•
Concentration of the substance	sodium metabisulphite Content: >= 0 % - <= 100 %
Physical state	Solid, low dustiness
Vapour pressure of the substance during use	0,009 Pa
Process temperature	40 °C
	Corresponds to a vapour pressure < 0.01 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Operation is carried out at ambient or elevated temperatures
Risk Management Measures	
Provide a good standard of general	Effectiveness: 30 %

Date / Revised: 01.08.2025 Version: 3.0
Date / Previous version: 24.06.2025 Previous version: 2.0

Product: Sodium Metabisulfite photo, non food grade

(ID no. 30042379/SDS_GEN_DE/EN)

ventilation (not less than 3 - 5 air	
changes per hour)	
Supervision in place to check that the	
RMMs in place are being used	
correctly and OCs followed. Clean	
equipment and the work area every	
day. Change clothes immediately after	
contamination. Ensure good work	
practices are implemented. Wash off	
any skin contamination immediately.	
Ensure minimization of manual	
phases Provide basic employee	
training to prevent/minimize	
exposures. Minimise number of staff	
exposed. Avoid contact with	
contaminated tools.	
Containment as appropriate Provide a	
good standard of general or controlled	
ventilation (5 to 10 air changes per	
hour)	
Wear suitable face shield, Wear	
suitable working clothes.	
Avoid contact with eyes.	
Use suitable eye protection.	
Exposure estimate and reference to it	
Assessment method	EASY TRA v6.1, Workplace measurements
	Worker - inhalation, long-term - systemic
Exposure estimate	1,5 mg/m³
Risk Characterization Ratio (RCR)	0,006667
Assessment method	Qualitative assessment
	Worker - inhalation

Contributing exposure scenario	
Use descriptors covered	PROC28: Manual maintenance (cleaning and repair) of machinery Use domain: industrial
Operational conditions	
Concentration of the substance	sodium metabisulphite Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	0,009 Pa
Process temperature	40 °C
	Corresponds to a vapour pressure < 0.01 Pa
Duration and Frequency of activity	480 min 5 days per week

Date / Revised: 01.08.2025 Version: 3.0 Date / Previous version: 24.06.2025 Previous version: 2.0

Product: Sodium Metabisulfite photo, non food grade

(ID no. 30042379/SDS_GEN_DE/EN)

Indoor/Outdoor	Indoor
	Operation is carried out at ambient or elevated
	temperatures
Risk Management Measures	
Provide a good standard of general	
ventilation (not less than 3 - 5 air	Effectiveness: 30 %
changes per hour)	
Supervision in place to check that the	
RMMs in place are being used	
correctly and OCs followed. Clean	
equipment and the work area every	
day. Change clothes immediately after	
contamination. Ensure good work	
practices are implemented. Wash off	
any skin contamination immediately.	
Ensure minimization of manual	
phases Provide basic employee	
training to prevent/minimize	
exposures. Minimise number of staff	
exposed. Avoid contact with	
contaminated tools.	
Containment as appropriate Provide a	
good standard of general or controlled	
ventilation (5 to 10 air changes per	
hour)	
Wear suitable face shield, Wear	
suitable working clothes.	
Avoid contact with eyes.	
Use suitable eye protection.	
Exposure estimate and reference to	
Assessment method	EASY TRA v6.1, Workplace measurements
	Worker - inhalation, long-term - systemic
Exposure estimate	0,05 mg/m³
Risk Characterization Ratio (RCR)	0,000222
Assessment method	Qualitative assessment
	Worker - inhalation

Contributing exposure scenario	
Use descriptors covered	PROC28: Manual maintenance (cleaning and repair) of machinery Use domain: industrial
Operational conditions	
Concentration of the substance	sodium metabisulphite Content: >= 0 % - <= 100 %
Physical state	Solid, low dustiness
Vapour pressure of the substance during use	0,009 Pa

Date / Revised: 01.08.2025 Version: 3.0
Date / Previous version: 24.06.2025 Previous version: 2.0

Product: Sodium Metabisulfite photo, non food grade

(ID no. 30042379/SDS_GEN_DE/EN)

Date of print 22.10.2025

Process temperature	40 °C
	Corresponds to a vapour pressure < 0.01 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Operation is carried out at ambient or elevated temperatures
Risk Management Measures	•
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %
Supervision in place to check that the RMMs in place are being used correctly and OCs followed. Clean equipment and the work area every day. Change clothes immediately after contamination. Ensure good work practices are implemented. Wash off any skin contamination immediately. Ensure minimization of manual phases Provide basic employee training to prevent/minimize exposures. Minimise number of staff exposed. Avoid contact with contaminated tools. Containment as appropriate Provide a	
good standard of general or controlled ventilation (5 to 10 air changes per hour)	
Wear suitable face shield, Wear	
suitable working clothes.	
Avoid contact with eyes.	
Use suitable eye protection.	
Exposure estimate and reference to i	
Assessment method	EASY TRA v6.1, Workplace measurements
	Worker - inhalation, long-term - systemic
Exposure estimate	1,5 mg/m³
Risk Characterization Ratio (RCR)	0,006667
Assessment method	Qualitative assessment
	Worker - inhalation

6. Short title of exposure scenario

Industrial applications, Use in/as Photochemicals IS; SU7, SU6b; ERC6b; PROC3, PROC4, PROC5, PROC7, PROC8b, PROC9, PROC10, PROC13, PROC15, PROC26, PROC28; PC30

Date / Revised: 01.08.2025 Version: 3.0 Date / Previous version: 24.06.2025 Previous version: 2.0

Product: Sodium Metabisulfite photo, non food grade

(ID no. 30042379/SDS_GEN_DE/EN)

Date of print 22.10.2025

Control of exposure and risk management measures

Contributing exposure scenario	
Use descriptors covered	ERC6b: Use of reactive processing aid at industrial site (no inclusion into or onto article) As no environmental hazard was identified no environmental-related exposure assessment and risk characterization was performed.
Operational conditions	

Contributing exposure scenario		
Use descriptors covered	PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition Use domain: industrial	
Operational conditions		
Concentration of the substance	sodium metabisulphite Content: >= 0 % - <= 100 %	
Physical state	Solid, low dustiness	
Vapour pressure of the substance during use	0,009 Pa	
Process temperature	40 °C	
	Corresponds to a vapour pressure < 0.01 Pa	
Duration and Frequency of activity	480 min 5 days per week	
Indoor/Outdoor	Indoor	
	Operation is carried out at ambient or elevated temperatures	
Risk Management Measures		
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %	
Supervision in place to check that the RMMs in place are being used correctly and OCs followed. Clean equipment and the work area every day. Change clothes immediately after contamination. Ensure good work practices are implemented. Wash off any skin contamination immediately. Ensure minimization of manual phases Provide basic employee training to prevent/minimize exposures. Minimise number of staff exposed. Avoid contact with		

Date / Revised: 01.08.2025 Version: 3.0
Date / Previous version: 24.06.2025 Previous version: 2.0

Product: Sodium Metabisulfite photo, non food grade

(ID no. 30042379/SDS_GEN_DE/EN)

contaminated tools.		
Containment as appropriate Provide a		
good standard of general or controlled		
ventilation (5 to 10 air changes per		
hour)		
Wear suitable face shield, Wear		
suitable working clothes.		
Avoid contact with eyes.		
Use suitable eye protection.		
Exposure estimate and reference to its source		
Assessment method	EASY TRA v6.1, Workplace measurements	
	Worker - inhalation, long-term - systemic	
Exposure estimate	0,1 mg/m³	
Risk Characterization Ratio (RCR)	0,000444	
Assessment method	Qualitative assessment	
	Worker - inhalation	

Contributing exposure scenario		
Use descriptors covered	PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition Use domain: industrial	
Operational conditions	L	
Concentration of the substance	sodium metabisulphite Content: >= 0 % - <= 100 %	
Physical state	liquid	
Vapour pressure of the substance during use	0,009 Pa	
Process temperature	40 °C	
	Corresponds to a vapour pressure < 0.01 Pa	
Duration and Frequency of activity	480 min 5 days per week	
Indoor/Outdoor	Indoor	
	Operation is carried out at ambient or elevated temperatures	
Risk Management Measures		
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %	
Supervision in place to check that the RMMs in place are being used correctly and OCs followed. Clean equipment and the work area every day. Change clothes immediately after contamination. Ensure good work		

Date / Revised: 01.08.2025 Version: 3.0
Date / Previous version: 24.06.2025 Previous version: 2.0

Product: Sodium Metabisulfite photo, non food grade

(ID no. 30042379/SDS_GEN_DE/EN)

practices are implemented. Wash off any skin contamination immediately. Ensure minimization of manual phases Provide basic employee training to prevent/minimize exposures. Minimise number of staff exposed. Avoid contact with contaminated tools. Containment as appropriate Provide a good standard of general or controlled ventilation (5 to 10 air changes per hour) Wear suitable face shield, Wear suitable working clothes.	
Avoid contact with eyes.	
Use suitable eye protection.	ito course
Exposure estimate and reference to it	
Assessment method	EASY TRA v6.1, Workplace measurements
F	Worker - inhalation, long-term - systemic
Exposure estimate	0,01 mg/m³
Risk Characterization Ratio (RCR)	0,000044
Assessment method	Qualitative assessment
	Worker - inhalation

Contributing exposure scenario	
Use descriptors covered	PROC4: Chemical production where opportunity for exposure arises Use domain: industrial
Operational conditions	
Concentration of the substance	sodium metabisulphite Content: >= 0 % - <= 100 %
Physical state	Solid, low dustiness
Vapour pressure of the substance during use	0,009 Pa
Process temperature	40 °C
	Corresponds to a vapour pressure < 0.01 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Operation is carried out at ambient or elevated temperatures
Risk Management Measures	
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %
Supervision in place to check that the	

Date / Revised: 01.08.2025 Version: 3.0
Date / Previous version: 24.06.2025 Previous version: 2.0

Product: Sodium Metabisulfite photo, non food grade

(ID no. 30042379/SDS_GEN_DE/EN)

RMMs in place are being used correctly and OCs followed. Clean equipment and the work area every day. Change clothes immediately after contamination. Ensure good work practices are implemented. Wash off any skin contamination immediately. Ensure minimization of manual phases Provide basic employee training to prevent/minimize exposures. Minimise number of staff exposed. Avoid contact with contaminated tools. Containment as appropriate Provide a good standard of general or controlled ventilation (5 to 10 air changes per hour) Wear suitable face shield, Wear suitable working clothes. Avoid contact with eyes. Use suitable eye protection. Exposure estimate and reference to it Assessment method	EASY TRA v6.1, Workplace measurements
Fun action of	Worker - inhalation, long-term - systemic
Exposure estimate	0,5 mg/m³
Risk Characterization Ratio (RCR)	0,002222
Assessment method	Qualitative assessment
	Worker - inhalation

Contributing exposure scenario	
Use descriptors covered	PROC4: Chemical production where opportunity for exposure arises Use domain: industrial
Operational conditions	
Concentration of the substance	sodium metabisulphite Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	0,009 Pa
Process temperature	40 °C
	Corresponds to a vapour pressure < 0.01 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Operation is carried out at ambient or elevated temperatures

Date / Revised: 01.08.2025 Version: 3.0
Date / Previous version: 24.06.2025 Previous version: 2.0

Product: Sodium Metabisulfite photo, non food grade

(ID no. 30042379/SDS_GEN_DE/EN)

Risk Management Measures	Risk Management Measures	
Provide a good standard of general		
ventilation (not less than 3 - 5 air	Effectiveness: 30 %	
changes per hour)		
Supervision in place to check that the		
RMMs in place are being used		
correctly and OCs followed. Clean		
equipment and the work area every		
day. Change clothes immediately after		
contamination. Ensure good work		
practices are implemented. Wash off		
any skin contamination immediately.		
Ensure minimization of manual		
phases Provide basic employee		
training to prevent/minimize		
exposures. Minimise number of staff		
exposed. Avoid contact with		
contaminated tools.		
Containment as appropriate Provide a		
good standard of general or controlled		
ventilation (5 to 10 air changes per		
hour)		
Wear suitable face shield, Wear		
suitable working clothes.		
Avoid contact with eyes.		
Use suitable eye protection.	4	
Exposure estimate and reference to i		
Assessment method	EASY TRA v6.1, Workplace measurements	
	Worker - inhalation, long-term - systemic	
Exposure estimate	0,05 mg/m³	
Risk Characterization Ratio (RCR)	0,000222	
Assessment method	Qualitative assessment	
	Worker - inhalation	

Contributing exposure scenario	
Use descriptors covered	PROC5: Mixing or blending in batch processes Use domain: industrial
Operational conditions	
Concentration of the substance	sodium metabisulphite Content: >= 0 % - <= 100 %
Physical state	Solid, low dustiness
Vapour pressure of the substance during use	0,009 Pa
Process temperature	40 °C
	Corresponds to a vapour pressure < 0.01 Pa
Duration and Frequency of activity	480 min 5 days per week

Date / Revised: 01.08.2025 Version: 3.0 Date / Previous version: 24.06.2025 Previous version: 2.0

Product: Sodium Metabisulfite photo, non food grade

(ID no. 30042379/SDS_GEN_DE/EN)

Indoor/Outdoor	Indoor
	Operation is carried out at ambient or elevated
	temperatures
Risk Management Measures	
Provide a good standard of general	
ventilation (not less than 3 - 5 air	Effectiveness: 30 %
changes per hour)	
Supervision in place to check that the	
RMMs in place are being used	
correctly and OCs followed. Clean	
equipment and the work area every	
day. Change clothes immediately after	
contamination. Ensure good work	
practices are implemented. Wash off	
any skin contamination immediately. Ensure minimization of manual	
phases Provide basic employee	
training to prevent/minimize	
exposures. Minimise number of staff	
exposed. Avoid contact with	
contaminated tools.	
Containment as appropriate Provide a	
good standard of general or controlled	
ventilation (5 to 10 air changes per	
hour)	
Wear suitable face shield, Wear	
suitable working clothes.	
Avoid contact with eyes.	
Use suitable eye protection.	
Exposure estimate and reference to i	
Assessment method	EASY TRA v6.1, Workplace measurements
	Worker - inhalation, long-term - systemic
Exposure estimate	0,5 mg/m³
Risk Characterization Ratio (RCR)	0,002222
Assessment method	Qualitative assessment
	Worker - inhalation

Contributing exposure scenario		
Use descriptors covered	PROC5: Mixing or blending in batch processes Use domain: industrial	
Operational conditions		
Concentration of the substance	sodium metabisulphite Content: >= 0 % - <= 100 %	
Physical state	liquid	
Vapour pressure of the substance during use	0,009 Pa	

Date / Revised: 01.08.2025 Version: 3.0
Date / Previous version: 24.06.2025 Previous version: 2.0

Product: Sodium Metabisulfite photo, non food grade

(ID no. 30042379/SDS_GEN_DE/EN)

Process temperature	40 °C
	Corresponds to a vapour pressure < 0.01 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Operation is carried out at ambient or elevated
	temperatures
Risk Management Measures	
Provide a good standard of general	
ventilation (not less than 3 - 5 air	Effectiveness: 30 %
changes per hour)	
Supervision in place to check that the	
RMMs in place are being used	
correctly and OCs followed. Clean	
equipment and the work area every	
day. Change clothes immediately after	
contamination. Ensure good work	
practices are implemented. Wash off	
any skin contamination immediately. Ensure minimization of manual	
phases Provide basic employee	
training to prevent/minimize	
exposures. Minimise number of staff	
exposed. Avoid contact with	
contaminated tools.	
Containment as appropriate Provide a	
good standard of general or controlled	
ventilation (5 to 10 air changes per	
hour)	
Wear suitable face shield, Wear	
suitable working clothes.	
Avoid contact with eyes.	
Use suitable eye protection.	
Exposure estimate and reference to it	
Assessment method	EASY TRA v6.1, Workplace measurements
	Worker - inhalation, long-term - systemic
Exposure estimate	0,05 mg/m ³
Risk Characterization Ratio (RCR)	0,000222
Assessment method	Qualitative assessment
	Worker - inhalation

Contributing exposure scenario		
Use descriptors covered	PROC7: Industrial spraying Use domain: industrial	
Operational conditions		
Concentration of the substance	sodium metabisulphite Content: >= 0 % - <= 100 %	

Date / Revised: 01.08.2025 Version: 3.0
Date / Previous version: 24.06.2025 Previous version: 2.0

Product: Sodium Metabisulfite photo, non food grade

(ID no. 30042379/SDS_GEN_DE/EN)

Physical state	liquid
Vapour pressure of the substance during use	0,009 Pa
Process temperature	40 °C
	Corresponds to a vapour pressure < 0.01 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Operation is carried out at ambient or elevated temperatures
Risk Management Measures	
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %
Supervision in place to check that the RMMs in place are being used correctly and OCs followed. Clean equipment and the work area every day. Change clothes immediately after contamination. Ensure good work practices are implemented. Wash off any skin contamination immediately. Ensure minimization of manual phases Provide basic employee training to prevent/minimize exposures. Minimise number of staff exposed. Avoid contact with contaminated tools.	
Containment as appropriate Provide a good standard of general or controlled ventilation (5 to 10 air changes per hour)	
Wear suitable face shield, Wear	
suitable working clothes. Avoid contact with eyes.	
Use suitable eye protection.	
Exposure estimate and reference to it	ts source
Assessment method	EASY TRA v6.1, Workplace measurements
	Worker - inhalation, long-term - systemic
Exposure estimate	4,4 mg/m³
Risk Characterization Ratio (RCR)	0,019556
Assessment method	Qualitative assessment
	Worker - inhalation

Contributing exposure scenario	
Use descriptors covered	PROC8b: Transfer of substance or mixture (charging and discharging) at dedicated facilities

to Regulation (EC) No 1907/2006.

Date / Revised: 01.08.2025 Version: 3.0 Date / Previous version: 24.06.2025 Previous version: 2.0

Product: Sodium Metabisulfite photo, non food grade

(ID no. 30042379/SDS_GEN_DE/EN)

	Use domain: industrial
	Additional PROC(s) covered: Transfer of substance or preparation into small containers (dedicated filling line, including weighing).
Operational conditions	
Concentration of the substance	sodium metabisulphite Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	0,009 Pa
Process temperature	40 °C
	Corresponds to a vapour pressure < 0.01 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Operation is carried out at ambient or elevated temperatures
Risk Management Measures	, ,
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %
Supervision in place to check that the RMMs in place are being used correctly and OCs followed. Clean equipment and the work area every day. Change clothes immediately after contamination. Ensure good work practices are implemented. Wash off any skin contamination immediately. Ensure minimization of manual phases Provide basic employee training to prevent/minimize exposures. Minimise number of staff exposed. Avoid contact with contaminated tools. Containment as appropriate Provide a good standard of general or controlled ventilation (5 to 10 air changes per hour) Wear suitable face shield, Wear suitable working clothes.	
Avoid contact with eyes.	
Use suitable eye protection.	
Exposure estimate and reference to	its source
Assessment method	EASY TRA v6.1, Workplace measurements
	Worker - inhalation, long-term - systemic

Date / Revised: 01.08.2025 Version: 3.0
Date / Previous version: 24.06.2025 Previous version: 2.0

Product: Sodium Metabisulfite photo, non food grade

(ID no. 30042379/SDS_GEN_DE/EN)

Exposure estimate	0,01 mg/m³
Risk Characterization Ratio (RCR)	0,000044
Assessment method	Qualitative assessment
	Worker - inhalation

Contributing exposure scenario	
Use descriptors covered	PROC10: Roller application or brushing Use domain: industrial
Operational conditions	
Concentration of the substance	sodium metabisulphite Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	0,009 Pa
Process temperature	40 °C
	Corresponds to a vapour pressure < 0.01 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Operation is carried out at ambient or elevated temperatures
Risk Management Measures	
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %
Supervision in place to check that the RMMs in place are being used correctly and OCs followed. Clean equipment and the work area every day. Change clothes immediately after contamination. Ensure good work practices are implemented. Wash off any skin contamination immediately. Ensure minimization of manual phases Provide basic employee training to prevent/minimize exposures. Minimise number of staff exposed. Avoid contact with contaminated tools. Containment as appropriate Provide a good standard of general or controlled ventilation (5 to 10 air changes per hour)	
Wear suitable face shield, Wear suitable working clothes.	
Avoid contact with eyes.	

to Regulation (EC) No 1907/2006.

Date / Revised: 01.08.2025 Version: 3.0 Date / Previous version: 24.06.2025 Previous version: 2.0

Product: Sodium Metabisulfite photo, non food grade

(ID no. 30042379/SDS_GEN_DE/EN)

Use suitable eye protection.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v6.1, Workplace measurements
	Worker - inhalation, long-term - systemic
Exposure estimate	0,05 mg/m³
Risk Characterization Ratio (RCR)	0,000222
Assessment method	Qualitative assessment
	Worker - inhalation

Contributing exposure scenario	
Use descriptors covered	PROC13: Treatment of articles by dipping and pouring. Use domain: industrial
Operational conditions	I
Concentration of the substance	sodium metabisulphite Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	0,009 Pa
Process temperature	40 °C
	Corresponds to a vapour pressure < 0.01 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Operation is carried out at ambient or elevated temperatures
Risk Management Measures	
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %
Supervision in place to check that the RMMs in place are being used correctly and OCs followed. Clean equipment and the work area every day. Change clothes immediately after contamination. Ensure good work practices are implemented. Wash off any skin contamination immediately. Ensure minimization of manual phases Provide basic employee training to prevent/minimize exposures. Minimise number of staff exposed. Avoid contact with contaminated tools.	
Containment as appropriate Provide a good standard of general or controlled ventilation (5 to 10 air changes per	

Date / Revised: 01.08.2025 Version: 3.0
Date / Previous version: 24.06.2025 Previous version: 2.0

Product: Sodium Metabisulfite photo, non food grade

(ID no. 30042379/SDS_GEN_DE/EN)

hour)	
Wear suitable face shield, Wear	
suitable working clothes.	
Avoid contact with eyes.	
Use suitable eye protection.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v6.1, Workplace measurements
	Worker - inhalation, long-term - systemic
Exposure estimate	0,01 mg/m³
Risk Characterization Ratio (RCR)	0,000044
Assessment method	Qualitative assessment
	Worker - inhalation

Contributing exposure scenario	Contributing exposure scenario	
Use descriptors covered	PROC15: Use a laboratory reagent. Use domain: industrial	
Operational conditions		
Concentration of the substance	sodium metabisulphite Content: >= 0 % - <= 100 %	
Physical state	Solid, low dustiness	
Vapour pressure of the substance during use	0,009 Pa	
Process temperature	40 °C	
	Corresponds to a vapour pressure < 0.01 Pa	
Duration and Frequency of activity	480 min 5 days per week	
Indoor/Outdoor	Indoor	
	Operation is carried out at ambient or elevated temperatures	
Risk Management Measures		
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %	
Supervision in place to check that the RMMs in place are being used correctly and OCs followed. Clean equipment and the work area every day. Change clothes immediately after contamination. Ensure good work practices are implemented. Wash off any skin contamination immediately. Ensure minimization of manual phases Provide basic employee training to prevent/minimize exposures. Minimise number of staff exposed. Avoid contact with		

Date / Revised: 01.08.2025 Version: 3.0
Date / Previous version: 24.06.2025 Previous version: 2.0

Product: Sodium Metabisulfite photo, non food grade

(ID no. 30042379/SDS_GEN_DE/EN)

contaminated tools.		
Containment as appropriate Provide a		
good standard of general or controlled		
ventilation (5 to 10 air changes per		
hour)		
Wear suitable face shield, Wear		
suitable working clothes.		
Avoid contact with eyes.		
Use suitable eye protection.		
Exposure estimate and reference to its source		
Assessment method	EASY TRA v6.1, Workplace measurements	
	Worker - inhalation, long-term - systemic	
Exposure estimate	0,1 mg/m³	
Risk Characterization Ratio (RCR)	0,000444	
Assessment method	Qualitative assessment	
	Worker - inhalation	

Contributing exposure scenario	Contributing exposure scenario	
	PROC15: Use a laboratory reagent.	
Use descriptors covered	Use domain: industrial	
Operational conditions		
	sodium metabisulphite	
Concentration of the substance	Content: >= 0 % - <= 100 %	
Physical state	liquid	
Vapour pressure of the substance	0,009 Pa	
during use		
Process temperature	40 °C	
	Corresponds to a vapour pressure < 0.01 Pa	
Duration and Frequency of activity	480 min 5 days per week	
Indoor/Outdoor	Indoor	
	Operation is carried out at ambient or elevated	
	temperatures	
Risk Management Measures		
Provide a good standard of general		
ventilation (not less than 3 - 5 air	Effectiveness: 30 %	
changes per hour)		
Supervision in place to check that the		
RMMs in place are being used		
correctly and OCs followed. Clean		
equipment and the work area every day. Change clothes immediately after		
contamination. Ensure good work		
practices are implemented. Wash off		
any skin contamination immediately.		
Ensure minimization of manual		

Date / Revised: 01.08.2025 Version: 3.0
Date / Previous version: 24.06.2025 Previous version: 2.0

Product: Sodium Metabisulfite photo, non food grade

(ID no. 30042379/SDS_GEN_DE/EN)

phases Provide basic employee training to prevent/minimize exposures. Minimise number of staff exposed. Avoid contact with contaminated tools. Containment as appropriate Provide a good standard of general or controlled ventilation (5 to 10 air changes per	
hour)	
Wear suitable face shield, Wear suitable working clothes.	
Avoid contact with eyes.	
Use suitable eye protection.	
Exposure estimate and reference to	its source
Assessment method	EASY TRA v6.1, Workplace measurements
	Worker - inhalation, long-term - systemic
Exposure estimate	0,01 mg/m³
Risk Characterization Ratio (RCR)	0,000044
Assessment method	Qualitative assessment
	Worker - inhalation

Contributing exposure scenario	
Use descriptors covered	PROC26: Handling of solid inorganic substances at ambient temperature Use domain: industrial
Operational conditions	
Concentration of the substance	sodium metabisulphite Content: >= 0 % - <= 100 %
Physical state	Solid, low dustiness
Vapour pressure of the substance during use	0,009 Pa
Process temperature	40 °C
	Corresponds to a vapour pressure < 0.01 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Operation is carried out at ambient or elevated temperatures
Risk Management Measures	
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %
Supervision in place to check that the RMMs in place are being used correctly and OCs followed. Clean equipment and the work area every	

to Regulation (EC) No 1907/2006.

Date / Revised: 01.08.2025 Version: 3.0 Date / Previous version: 24.06.2025 Previous version: 2.0

Product: Sodium Metabisulfite photo, non food grade

(ID no. 30042379/SDS_GEN_DE/EN)

day. Change clothes immediately after contamination. Ensure good work practices are implemented. Wash off any skin contamination immediately. Ensure minimization of manual phases Provide basic employee training to prevent/minimize exposures. Minimise number of staff exposed. Avoid contact with contaminated tools. Containment as appropriate Provide a good standard of general or controlled ventilation (5 to 10 air changes per	
hour) Wear suitable face shield, Wear	
suitable working clothes.	
Avoid contact with eyes.	
Use suitable eye protection.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v6.1, Workplace measurements
	Worker - inhalation, long-term - systemic
Exposure estimate	1,5 mg/m³
Risk Characterization Ratio (RCR)	0,006667
Assessment method	Qualitative assessment
	Worker - inhalation

Contributing exposure scenario	
Use descriptors covered	PROC28: Manual maintenance (cleaning and repair) of machinery Use domain: industrial
Operational conditions	
Concentration of the substance	sodium metabisulphite Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	0,009 Pa
Process temperature	40 °C
	Corresponds to a vapour pressure < 0.01 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Operation is carried out at ambient or elevated temperatures
Risk Management Measures	
Provide a good standard of general ventilation (not less than 3 - 5 air	Effectiveness: 30 %

Date / Revised: 01.08.2025 Version: 3.0
Date / Previous version: 24.06.2025 Previous version: 2.0

Product: Sodium Metabisulfite photo, non food grade

(ID no. 30042379/SDS_GEN_DE/EN)

changes per hour)	
Supervision in place to check that the	
RMMs in place are being used	
correctly and OCs followed. Clean	
equipment and the work area every	
day. Change clothes immediately after	
contamination. Ensure good work	
practices are implemented. Wash off	
any skin contamination immediately.	
Ensure minimization of manual	
phases Provide basic employee	
training to prevent/minimize exposures. Minimise number of staff	
exposed. Avoid contact with	
contaminated tools.	
Containment as appropriate Provide a	
good standard of general or controlled	
ventilation (5 to 10 air changes per	
hour)	
Wear suitable face shield, Wear	
suitable working clothes.	
Avoid contact with eyes.	
Use suitable eye protection.	
Exposure estimate and reference to it	
Assessment method	EASY TRA v6.1, Workplace measurements
	Worker - inhalation, long-term - systemic
Exposure estimate	0,05 mg/m³
Risk Characterization Ratio (RCR)	0,000222
Assessment method	Qualitative assessment
	Worker - inhalation

Contributing exposure scenario	
Use descriptors covered	PROC28: Manual maintenance (cleaning and repair) of machinery Use domain: industrial
Operational conditions	
Concentration of the substance	sodium metabisulphite Content: >= 0 % - <= 100 %
Physical state	Solid, low dustiness
Vapour pressure of the substance during use	0,009 Pa
Process temperature	40 °C
	Corresponds to a vapour pressure < 0.01 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor

Page: 94/126

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 01.08.2025 Version: 3.0
Date / Previous version: 24.06.2025 Previous version: 2.0

Product: Sodium Metabisulfite photo, non food grade

(ID no. 30042379/SDS_GEN_DE/EN)

Date of print 22.10.2025

	Operation is carried out at ambient or elevated temperatures
Risk Management Measures	temperatures
Provide a good standard of general	
ventilation (not less than 3 - 5 air	Effectiveness: 30 %
changes per hour)	
Supervision in place to check that the	
RMMs in place are being used	
correctly and OCs followed. Clean	
equipment and the work area every	
day. Change clothes immediately after	
contamination. Ensure good work	
practices are implemented. Wash off	
any skin contamination immediately.	
Ensure minimization of manual	
phases Provide basic employee	
training to prevent/minimize exposures. Minimise number of staff	
exposed. Avoid contact with	
contaminated tools.	
Containment as appropriate Provide a	
good standard of general or controlled	
ventilation (5 to 10 air changes per	
hour)	
Wear suitable face shield, Wear	
suitable working clothes.	
Avoid contact with eyes.	
Use suitable eye protection.	
Exposure estimate and reference to i	_
Assessment method	EASY TRA v6.1, Workplace measurements
	Worker - inhalation, long-term - systemic
Exposure estimate	1,5 mg/m³
Risk Characterization Ratio (RCR)	0,006667
Assessment method	Qualitative assessment
	Worker - inhalation

* * * * * * * * * * * * * * * * * *

7. Short title of exposure scenario

Professional applications, Use as laboratory reagent/agent, Manufacture of fine chemicals PW; SU24, SU20; ERC8b; PROC3, PROC2, PROC1, PROC4, PROC5, PROC8a, PROC9, PROC8b, PROC15, PROC26; PC21, PC20

Control of exposure and risk management measures

Contributing exposure scenario	
Use descriptors covered	ERC8b: Widespread use of reactive processing aid (no inclusion into or onto article, indoor)

Date / Revised: 01.08.2025 Version: 3.0
Date / Previous version: 24.06.2025 Previous version: 2.0

Product: Sodium Metabisulfite photo, non food grade

(ID no. 30042379/SDS_GEN_DE/EN)

	As no environmental hazard was identified no environmental-related exposure assessment and risk characterization was performed.
Operational conditions	

PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition Use domain: professional
Additional PROC(s) covered: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions.
sodium metabisulphite Content: >= 0 % - <= 100 %
Solid, low dustiness
0,009 Pa
40 °C
Corresponds to a vapour pressure < 0.01 Pa
480 min 5 days per week
Indoor
Operation is carried out at ambient or elevated temperatures

Date / Revised: 01.08.2025 Version: 3.0
Date / Previous version: 24.06.2025 Previous version: 2.0

Product: Sodium Metabisulfite photo, non food grade

(ID no. 30042379/SDS_GEN_DE/EN)

Containment as appropriate Provide a good standard of general or controlled ventilation (5 to 10 air changes per hour)	
Wear suitable face shield, Wear	
suitable working clothes.	
Avoid contact with eyes.	
Use suitable eye protection.	
Exposure estimate and reference to it	its source
Assessment method	EASY TRA v6.1, Workplace measurements
	Worker - inhalation, long-term - systemic
Exposure estimate	0,1 mg/m³
Risk Characterization Ratio (RCR)	0,000444
Assessment method	Qualitative assessment
	Worker - inhalation

Contributing exposure scenario	
Use descriptors covered	PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition Use domain: professional
	Additional PROC(s) covered: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions.
Operational conditions	1
Concentration of the substance	sodium metabisulphite Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	0,009 Pa
Process temperature	40 °C
	Corresponds to a vapour pressure < 0.01 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Operation is carried out at ambient or elevated temperatures
Risk Management Measures	
Supervision in place to check that the	
RMMs in place are being used correctly and OCs followed. Clean	

Date / Revised: 01.08.2025 Version: 3.0
Date / Previous version: 24.06.2025 Previous version: 2.0

Product: Sodium Metabisulfite photo, non food grade

(ID no. 30042379/SDS_GEN_DE/EN)

equipment and the work area every day. Change clothes immediately after contamination. Ensure good work practices are implemented. Wash off any skin contamination immediately. Ensure minimization of manual phases Provide basic employee training to prevent/minimize exposures. Minimise number of staff exposed. Avoid contact with contaminated tools. Containment as appropriate Provide a good standard of general or controlled ventilation (5 to 10 air changes per hour)	
Wear suitable face shield, Wear	
suitable working clothes.	
Avoid contact with eyes.	
Use suitable eye protection.	
Exposure estimate and reference to it	ts source
Assessment method	EASY TRA v6.1, Workplace measurements
	Worker - inhalation, long-term - systemic
Exposure estimate	0,01 mg/m³
Risk Characterization Ratio (RCR)	0,000044
Assessment method	Qualitative assessment
	Worker - inhalation

Contributing exposure scenario	
Use descriptors covered	PROC4: Chemical production where opportunity for exposure arises Use domain: professional
Operational conditions	
Concentration of the substance	sodium metabisulphite Content: >= 0 % - <= 100 %
Physical state	Solid, low dustiness
Vapour pressure of the substance during use	0,009 Pa
Process temperature	40 °C
	Corresponds to a vapour pressure < 0.01 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Operation is carried out at ambient or elevated temperatures
Risk Management Measures	
Supervision in place to check that the	

Date / Revised: 01.08.2025 Version: 3.0
Date / Previous version: 24.06.2025 Previous version: 2.0

Product: Sodium Metabisulfite photo, non food grade

(ID no. 30042379/SDS_GEN_DE/EN)

RMMs in place are being used correctly and OCs followed. Clean equipment and the work area every day. Change clothes immediately after contamination. Ensure good work practices are implemented. Wash off any skin contamination immediately. Ensure minimization of manual phases Provide basic employee training to prevent/minimize exposures. Minimise number of staff exposed. Avoid contact with contaminated tools. Containment as appropriate Provide a good standard of general or controlled ventilation (5 to 10 air changes per hour) Wear suitable face shield, Wear suitable working clothes. Avoid contact with eyes. Use suitable eye protection. Exposure estimate and reference to it.	its source EASY TRA v6.1, Workplace measurements
	Worker - inhalation, long-term - systemic
Exposure estimate	1 mg/m³
Risk Characterization Ratio (RCR)	0,004444
Assessment method	Qualitative assessment
	Worker - inhalation

Contributing exposure scenario	
Use descriptors covered	PROC4: Chemical production where opportunity for exposure arises Use domain: professional
Operational conditions	
Concentration of the substance	sodium metabisulphite Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	0,009 Pa
Process temperature	40 °C
	Corresponds to a vapour pressure < 0.01 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Operation is carried out at ambient or elevated temperatures

Date / Revised: 01.08.2025 Version: 3.0
Date / Previous version: 24.06.2025 Previous version: 2.0

Product: Sodium Metabisulfite photo, non food grade

(ID no. 30042379/SDS_GEN_DE/EN)

Risk Management Measures	
Supervision in place to check that the	
RMMs in place are being used	
correctly and OCs followed. Clean	
equipment and the work area every	
day. Change clothes immediately after	
contamination. Ensure good work	
practices are implemented. Wash off	
any skin contamination immediately.	
Ensure minimization of manual	
phases Provide basic employee	
training to prevent/minimize	
exposures. Minimise number of staff	
exposed. Avoid contact with	
contaminated tools.	
Containment as appropriate Provide a	
good standard of general or controlled	
ventilation (5 to 10 air changes per	
hour)	
Wear suitable face shield, Wear	
suitable working clothes.	
Avoid contact with eyes.	
Use suitable eye protection.	
Exposure estimate and reference to i	
Assessment method	EASY TRA v6.1, Workplace measurements
	Worker - inhalation, long-term - systemic
Exposure estimate	0,05 mg/m³
Risk Characterization Ratio (RCR)	0,000222
Assessment method	Qualitative assessment
	Worker - inhalation

Contributing exposure scenario	
Use descriptors covered	PROC5: Mixing or blending in batch processes Use domain: professional
Operational conditions	
Concentration of the substance	sodium metabisulphite Content: >= 0 % - <= 100 %
Physical state	Solid, low dustiness
Vapour pressure of the substance during use	0,009 Pa
Process temperature	40 °C
	Corresponds to a vapour pressure < 0.01 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Operation is carried out at ambient or elevated

Page: 100/126

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 01.08.2025 Version: 3.0
Date / Previous version: 24.06.2025 Previous version: 2.0

Product: Sodium Metabisulfite photo, non food grade

(ID no. 30042379/SDS_GEN_DE/EN)

	temperatures
Risk Management Measures	·
Supervision in place to check that the RMMs in place are being used correctly and OCs followed. Clean equipment and the work area every day. Change clothes immediately after contamination. Ensure good work practices are implemented. Wash off any skin contamination immediately. Ensure minimization of manual	
phases Provide basic employee training to prevent/minimize exposures. Minimise number of staff exposed. Avoid contact with contaminated tools.	
Containment as appropriate Provide a good standard of general or controlled ventilation (5 to 10 air changes per hour)	
Wear suitable face shield, Wear suitable working clothes.	
Avoid contact with eyes.	
Use suitable eye protection.	
Exposure estimate and reference to it	
Assessment method	EASY TRA v6.1, Workplace measurements
	Worker - inhalation, long-term - systemic
Exposure estimate	1 mg/m³
Risk Characterization Ratio (RCR)	0,004444
Assessment method	Qualitative assessment
	Worker - inhalation

Contributing exposure scenario	
Use descriptors covered	PROC5: Mixing or blending in batch processes Use domain: professional
Operational conditions	
Concentration of the substance	sodium metabisulphite Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	0,009 Pa
Process temperature	40 °C
	Corresponds to a vapour pressure < 0.01 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor

Page: 101/126

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 01.08.2025 Version: 3.0
Date / Previous version: 24.06.2025 Previous version: 2.0

Product: Sodium Metabisulfite photo, non food grade

(ID no. 30042379/SDS_GEN_DE/EN)

	Operation is carried out at ambient or elevated temperatures
Risk Management Measures	
Supervision in place to check that the	
RMMs in place are being used	
correctly and OCs followed. Clean	
equipment and the work area every	
day. Change clothes immediately after	
contamination. Ensure good work	
practices are implemented. Wash off	
any skin contamination immediately.	
Ensure minimization of manual	
phases Provide basic employee	
training to prevent/minimize	
exposures. Minimise number of staff	
exposed. Avoid contact with	
contaminated tools.	
Containment as appropriate Provide a good standard of general or controlled	
ventilation (5 to 10 air changes per	
hour)	
Wear suitable face shield, Wear	
suitable working clothes.	
Avoid contact with eyes.	
Use suitable eye protection.	
Exposure estimate and reference to it	ts source
Assessment method	EASY TRA v6.1, Workplace measurements
	Worker - inhalation, long-term - systemic
Exposure estimate	0,05 mg/m³
Risk Characterization Ratio (RCR)	0,000222
Assessment method	Qualitative assessment
	Worker - inhalation

Contributing exposure scenario	
Use descriptors covered	PROC8a: Transfer of substance or mixture (charging and discharging) at non-dedicated facilities Use domain: professional
	Additional PROC(s) covered: Transfer of substance or preparation into small containers (dedicated filling line, including weighing). Transfer of substance or mixture (charging and discharging) at dedicated facilities
Operational conditions	
Concentration of the substance	sodium metabisulphite Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	0,009 Pa

Date / Revised: 01.08.2025 Version: 3.0
Date / Previous version: 24.06.2025 Previous version: 2.0

Product: Sodium Metabisulfite photo, non food grade

(ID no. 30042379/SDS_GEN_DE/EN)

Process temperature	40 °C
	Corresponds to a vapour pressure < 0.01 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Operation is carried out at ambient or elevated
	temperatures
Risk Management Measures	
Supervision in place to check that the	
RMMs in place are being used	
correctly and OCs followed. Clean	
equipment and the work area every	
day. Change clothes immediately after	
contamination. Ensure good work	
practices are implemented. Wash off	
any skin contamination immediately.	
Ensure minimization of manual	
phases Provide basic employee	
training to prevent/minimize	
exposures. Minimise number of staff	
exposed. Avoid contact with	
contaminated tools.	
Containment as appropriate Provide a	
good standard of general or controlled	
ventilation (5 to 10 air changes per	
hour)	
Wear suitable face shield, Wear	
suitable working clothes.	
Avoid contact with eyes.	
Use suitable eye protection.	
Exposure estimate and reference to it	ts source
Assessment method	EASY TRA v6.1, Workplace measurements
	Worker - inhalation, long-term - systemic
Exposure estimate	0,05 mg/m ³
Risk Characterization Ratio (RCR)	0,000222
Assessment method	Qualitative assessment
	Worker - inhalation

Contributing exposure scenario	
Use descriptors covered	PROC15: Use a laboratory reagent. Use domain: professional
Operational conditions	
	sodium metabisulphite
Concentration of the substance	Content: >= 0 % - <= 100 %
Physical state	Solid, low dustiness
Vapour pressure of the substance	0,009 Pa

Page: 103/126

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 01.08.2025 Version: 3.0
Date / Previous version: 24.06.2025 Previous version: 2.0

Product: Sodium Metabisulfite photo, non food grade

(ID no. 30042379/SDS_GEN_DE/EN)

Process temperature Corresponds to a vapour pressure < 0.01 Pa 480 min 5 days per week Indoor/Outdoor Indoor Operation is carried out at ambient or elevated temperatures Risk Management Measures Supervision in place to check that the RMMs in place are being used correctly and OCs followed. Clean equipment and the work area every day. Change clothes immediately after contamination. Ensure good work practices are implemented. Wash off any skin contamination immediately. Ensure minimization of manual phases Provide basic employee training to prevent/minimize exposures. Minimise number of staff exposed. Avoid contact with	during use	
Duration and Frequency of activity Indoor/Outdoor Indoor Operation is carried out at ambient or elevated temperatures Risk Management Measures Supervision in place to check that the RMMs in place are being used correctly and OCs followed. Clean equipment and the work area every day. Change clothes immediately after contamination. Ensure good work practices are implemented. Wash off any skin contamination immediately. Ensure minimization of manual phases Provide basic employee training to prevent/minimize exposures. Minimise number of staff exposed. Avoid contact with	Process temperature	40 °C
Indoor/Outdoor Operation is carried out at ambient or elevated temperatures Risk Management Measures Supervision in place to check that the RMMs in place are being used correctly and OCs followed. Clean equipment and the work area every day. Change clothes immediately after contamination. Ensure good work practices are implemented. Wash off any skin contamination immediately. Ensure minimization of manual phases Provide basic employee training to prevent/minimize exposures. Minimise number of staff exposed. Avoid contact with		Corresponds to a vapour pressure < 0.01 Pa
Operation is carried out at ambient or elevated temperatures Risk Management Measures Supervision in place to check that the RMMs in place are being used correctly and OCs followed. Clean equipment and the work area every day. Change clothes immediately after contamination. Ensure good work practices are implemented. Wash off any skin contamination immediately. Ensure minimization of manual phases Provide basic employee training to prevent/minimize exposures. Minimise number of staff exposed. Avoid contact with	Duration and Frequency of activity	480 min 5 days per week
Risk Management Measures Supervision in place to check that the RMMs in place are being used correctly and OCs followed. Clean equipment and the work area every day. Change clothes immediately after contamination. Ensure good work practices are implemented. Wash off any skin contamination immediately. Ensure minimization of manual phases Provide basic employee training to prevent/minimize exposures. Minimise number of staff exposed. Avoid contact with	Indoor/Outdoor	Indoor
Risk Management Measures Supervision in place to check that the RMMs in place are being used correctly and OCs followed. Clean equipment and the work area every day. Change clothes immediately after contamination. Ensure good work practices are implemented. Wash off any skin contamination immediately. Ensure minimization of manual phases Provide basic employee training to prevent/minimize exposures. Minimise number of staff exposed. Avoid contact with		Operation is carried out at ambient or elevated
Supervision in place to check that the RMMs in place are being used correctly and OCs followed. Clean equipment and the work area every day. Change clothes immediately after contamination. Ensure good work practices are implemented. Wash off any skin contamination immediately. Ensure minimization of manual phases Provide basic employee training to prevent/minimize exposures. Minimise number of staff exposed. Avoid contact with		temperatures
RMMs in place are being used correctly and OCs followed. Clean equipment and the work area every day. Change clothes immediately after contamination. Ensure good work practices are implemented. Wash off any skin contamination immediately. Ensure minimization of manual phases Provide basic employee training to prevent/minimize exposures. Minimise number of staff exposed. Avoid contact with		
correctly and OCs followed. Clean equipment and the work area every day. Change clothes immediately after contamination. Ensure good work practices are implemented. Wash off any skin contamination immediately. Ensure minimization of manual phases Provide basic employee training to prevent/minimize exposures. Minimise number of staff exposed. Avoid contact with		
equipment and the work area every day. Change clothes immediately after contamination. Ensure good work practices are implemented. Wash off any skin contamination immediately. Ensure minimization of manual phases Provide basic employee training to prevent/minimize exposures. Minimise number of staff exposed. Avoid contact with		
day. Change clothes immediately after contamination. Ensure good work practices are implemented. Wash off any skin contamination immediately. Ensure minimization of manual phases Provide basic employee training to prevent/minimize exposures. Minimise number of staff exposed. Avoid contact with	•	
contamination. Ensure good work practices are implemented. Wash off any skin contamination immediately. Ensure minimization of manual phases Provide basic employee training to prevent/minimize exposures. Minimise number of staff exposed. Avoid contact with		
practices are implemented. Wash off any skin contamination immediately. Ensure minimization of manual phases Provide basic employee training to prevent/minimize exposures. Minimise number of staff exposed. Avoid contact with		
any skin contamination immediately. Ensure minimization of manual phases Provide basic employee training to prevent/minimize exposures. Minimise number of staff exposed. Avoid contact with		
Ensure minimization of manual phases Provide basic employee training to prevent/minimize exposures. Minimise number of staff exposed. Avoid contact with		
phases Provide basic employee training to prevent/minimize exposures. Minimise number of staff exposed. Avoid contact with		
training to prevent/minimize exposures. Minimise number of staff exposed. Avoid contact with		
exposures. Minimise number of staff exposed. Avoid contact with		
exposed. Avoid contact with		
contaminated tools.		
Containment as appropriate Provide a		
good standard of general or controlled		
ventilation (5 to 10 air changes per	,	
hour) Wear suitable face shield, Wear	,	
suitable working clothes.		
Avoid contact with eyes.		
Use suitable eye protection.		
Exposure estimate and reference to its source		its source
Assessment method EASY TRA v6.1, Workplace measurements	•	
Worker - inhalation, long-term - systemic	ASSESSINGIL INCLINU	
Exposure estimate 0,1 mg/m³	Exposure estimate	· · ·
Risk Characterization Ratio (RCR) 0,000444		
Assessment method Qualitative assessment	1 /	
Worker - inhalation		

Contributing exposure scenario	
Use descriptors covered	PROC15: Use a laboratory reagent. Use domain: professional
Operational conditions	·
	sodium metabisulphite
Concentration of the substance	Content: >= 0 % - <= 100 %
Physical state	liquid

Page: 104/126

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 01.08.2025 Version: 3.0 Date / Previous version: 24.06.2025 Previous version: 2.0

Product: Sodium Metabisulfite photo, non food grade

(ID no. 30042379/SDS_GEN_DE/EN)

Vapour pressure of the substance during use	0,009 Pa
Process temperature	40 °C
	Corresponds to a vapour pressure < 0.01 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Operation is carried out at ambient or elevated temperatures
Risk Management Measures	temperatures
Supervision in place to check that the RMMs in place are being used correctly and OCs followed. Clean equipment and the work area every day. Change clothes immediately after contamination. Ensure good work practices are implemented. Wash off any skin contamination immediately. Ensure minimization of manual phases Provide basic employee training to prevent/minimize exposures. Minimise number of staff exposed. Avoid contact with contaminated tools.	
Containment as appropriate Provide a good standard of general or controlled ventilation (5 to 10 air changes per hour)	
Wear suitable face shield, Wear	
suitable working clothes.	
Avoid contact with eyes.	
Use suitable eye protection.	
Exposure estimate and reference to i	
Assessment method	EASY TRA v6.1, Workplace measurements
	Worker - inhalation, long-term - systemic
Exposure estimate	0,01 mg/m³
Risk Characterization Ratio (RCR)	0,00044
Assessment method	Qualitative assessment
	Worker - inhalation

Contributing exposure scenario	
Use descriptors covered	PROC26: Handling of solid inorganic substances at ambient temperature Use domain: professional
Operational conditions	
Concentration of the substance	sodium metabisulphite Content: >= 0 % - <= 100 %

Date / Revised: 01.08.2025 Version: 3.0
Date / Previous version: 24.06.2025 Previous version: 2.0

Product: Sodium Metabisulfite photo, non food grade

(ID no. 30042379/SDS_GEN_DE/EN)

Date of print 22.10.2025

Physical state	Solid, low dustiness
Vapour pressure of the substance during use	0,009 Pa
Process temperature	40 °C
	Corresponds to a vapour pressure < 0.01 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Operation is carried out at ambient or elevated temperatures
Risk Management Measures	
Supervision in place to check that the RMMs in place are being used correctly and OCs followed. Clean equipment and the work area every day. Change clothes immediately after contamination. Ensure good work practices are implemented. Wash off any skin contamination immediately. Ensure minimization of manual phases Provide basic employee training to prevent/minimize exposures. Minimise number of staff exposed. Avoid contact with contaminated tools. Containment as appropriate Provide a	
good standard of general or controlled ventilation (5 to 10 air changes per hour)	
Wear suitable face shield, Wear	
suitable working clothes.	
Avoid contact with eyes.	
Use suitable eye protection.	
Exposure estimate and reference to	
Assessment method	EASY TRA v6.1, Workplace measurements
Evaccura actimata	Worker - inhalation, long-term - systemic 3 mg/m ³
Risk Characterization Ratio (RCR)	0,013333
Assessment method	Qualitative assessment
ASSESSITION THE HIDO	Worker - inhalation
	Tronto: illidiation

* * * * * * * * * * * * * * *

8. Short title of exposure scenario

Professional applications, Use in/as Photochemicals

Date / Revised: 01.08.2025 Version: 3.0
Date / Previous version: 24.06.2025 Previous version: 2.0

Product: Sodium Metabisulfite photo, non food grade

(ID no. 30042379/SDS_GEN_DE/EN)

Date of print 22.10.2025

PW; SU7, SU6b; ERC8e; PROC3, PROC4, PROC5, PROC8b, PROC9, PROC8a, PROC10, PROC11, PROC13, PROC15, PROC19, PROC26; PC30

Control of exposure and risk management measures

Contributing exposure scenario	
Use descriptors covered	ERC8e: Widespread use of reactive processing aid (no inclusion into or onto article, outdoor) As no environmental hazard was identified no environmental-related exposure assessment and risk characterization was performed.
Operational conditions	

Contributing exposure scenario	
Use descriptors covered	PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition Use domain: professional
Operational conditions	
Concentration of the substance	sodium metabisulphite Content: >= 0 % - <= 100 %
Physical state	Solid, low dustiness
Vapour pressure of the substance during use	0,009 Pa
Process temperature	40 °C
	Corresponds to a vapour pressure < 0.01 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Operation is carried out at ambient or elevated temperatures
Risk Management Measures	
Supervision in place to check that the RMMs in place are being used correctly and OCs followed. Clean equipment and the work area every day. Change clothes immediately after contamination. Ensure good work practices are implemented. Wash off any skin contamination immediately. Ensure minimization of manual phases Provide basic employee training to prevent/minimize exposures. Minimise number of staff	
exposed. Avoid contact with	

Page: 107/126

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 01.08.2025 Version: 3.0
Date / Previous version: 24.06.2025 Previous version: 2.0

Product: Sodium Metabisulfite photo, non food grade

(ID no. 30042379/SDS_GEN_DE/EN)

contaminated tools.	
Containment as appropriate Provide a good standard of general or controlled ventilation (5 to 10 air changes per hour)	
Wear suitable face shield, Wear	
suitable working clothes.	
Avoid contact with eyes.	
Use suitable eye protection.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v6.1, Workplace measurements
	Worker - inhalation, long-term - systemic
Exposure estimate	0,1 mg/m³
Risk Characterization Ratio (RCR)	0,000444
Assessment method	Qualitative assessment
	Worker - inhalation

Contributing exposure scenario	
Use descriptors covered	PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition Use domain: professional
Operational conditions	L
Concentration of the substance	sodium metabisulphite Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	0,009 Pa
Process temperature	40 °C
	Corresponds to a vapour pressure < 0.01 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Operation is carried out at ambient or elevated temperatures
Risk Management Measures	
Supervision in place to check that the RMMs in place are being used correctly and OCs followed. Clean equipment and the work area every day. Change clothes immediately after contamination. Ensure good work practices are implemented. Wash off	
any skin contamination immediately. Ensure minimization of manual	

Page: 108/126

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 01.08.2025 Version: 3.0
Date / Previous version: 24.06.2025 Previous version: 2.0

Product: Sodium Metabisulfite photo, non food grade

(ID no. 30042379/SDS_GEN_DE/EN)

phases Provide basic employee training to prevent/minimize exposures. Minimise number of staff exposed. Avoid contact with contaminated tools.	
Containment as appropriate Provide a good standard of general or controlled ventilation (5 to 10 air changes per hour)	
Wear suitable face shield, Wear suitable working clothes.	
Avoid contact with eyes.	
Use suitable eye protection.	
Exposure estimate and reference to	its source
Assessment method	EASY TRA v6.1, Workplace measurements
	Worker - inhalation, long-term - systemic
Exposure estimate	0,01 mg/m³
Risk Characterization Ratio (RCR)	0,000044
Assessment method	Qualitative assessment
	Worker - inhalation

Contributing exposure scenario	
Use descriptors covered	PROC4: Chemical production where opportunity for exposure arises Use domain: professional
Operational conditions	
Concentration of the substance	sodium metabisulphite Content: >= 0 % - <= 100 %
Physical state	Solid, low dustiness
Vapour pressure of the substance during use	0,009 Pa
Process temperature	40 °C
	Corresponds to a vapour pressure < 0.01 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Operation is carried out at ambient or elevated temperatures
Risk Management Measures	
Supervision in place to check that the RMMs in place are being used correctly and OCs followed. Clean equipment and the work area every day. Change clothes immediately after contamination. Ensure good work practices are implemented. Wash off	

Page: 109/126

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 01.08.2025 Version: 3.0 Date / Previous version: 24.06.2025 Previous version: 2.0

Product: Sodium Metabisulfite photo, non food grade

(ID no. 30042379/SDS_GEN_DE/EN)

any skin contamination immediately. Ensure minimization of manual phases Provide basic employee training to prevent/minimize exposures. Minimise number of staff exposed. Avoid contact with contaminated tools. Containment as appropriate Provide a good standard of general or controlled ventilation (5 to 10 air changes per hour)		
Wear suitable face shield, Wear		
suitable working clothes.		
Avoid contact with eyes.		
Use suitable eye protection.		
Exposure estimate and reference to its source		
Assessment method	EASY TRA v6.1, Workplace measurements	
	Worker - inhalation, long-term - systemic	
Exposure estimate	1 mg/m³	
Risk Characterization Ratio (RCR)	0,004444	
Assessment method	Qualitative assessment	
	Worker - inhalation	

Contributing exposure scenario	
Use descriptors covered	PROC4: Chemical production where opportunity for exposure arises Use domain: professional
Operational conditions	
Concentration of the substance	sodium metabisulphite Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	0,009 Pa
Process temperature	40 °C
	Corresponds to a vapour pressure < 0.01 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Operation is carried out at ambient or elevated temperatures
Risk Management Measures	
Supervision in place to check that the RMMs in place are being used	
correctly and OCs followed. Clean equipment and the work area every day. Change clothes immediately after	

Page: 110/126

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 01.08.2025 Version: 3.0
Date / Previous version: 24.06.2025 Previous version: 2.0

Product: Sodium Metabisulfite photo, non food grade

(ID no. 30042379/SDS_GEN_DE/EN)

contamination. Ensure good work practices are implemented. Wash off any skin contamination immediately. Ensure minimization of manual phases Provide basic employee training to prevent/minimize exposures. Minimise number of staff exposed. Avoid contact with contaminated tools.	
Containment as appropriate Provide a	
good standard of general or controlled	
ventilation (5 to 10 air changes per hour)	
Wear suitable face shield, Wear	
suitable working clothes.	
Avoid contact with eyes.	
Use suitable eye protection.	
Exposure estimate and reference to i	ts source
Assessment method	EASY TRA v6.1, Workplace measurements
	Worker - inhalation, long-term - systemic
Exposure estimate	0,05 mg/m³
Risk Characterization Ratio (RCR)	0,000222
Assessment method	Qualitative assessment
	Worker - inhalation

Contributing exposure scenario	
	PROC5: Mixing or blending in batch processes
Use descriptors covered	Use domain: professional
Operational conditions	
	sodium metabisulphite
Concentration of the substance	Content: >= 0 % - <= 100 %
Physical state	Solid, low dustiness
Vapour pressure of the substance	0,009 Pa
during use	
Process temperature	40 °C
1 100000 tomporataro	
	Corresponds to a vapour pressure < 0.01 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Operation is carried out at ambient or elevated
	temperatures
Risk Management Measures	
Supervision in place to check that the	
RMMs in place are being used	
correctly and OCs followed. Clean	
equipment and the work area every	

Date / Revised: 01.08.2025 Version: 3.0
Date / Previous version: 24.06.2025 Previous version: 2.0

Product: Sodium Metabisulfite photo, non food grade

(ID no. 30042379/SDS_GEN_DE/EN)

day. Change clothes immediately after contamination. Ensure good work practices are implemented. Wash off any skin contamination immediately. Ensure minimization of manual phases Provide basic employee training to prevent/minimize exposures. Minimise number of staff exposed. Avoid contact with contaminated tools. Containment as appropriate Provide a good standard of general or controlled ventilation (5 to 10 air changes per	
hour) Wear suitable face shield, Wear	
suitable working clothes.	
Avoid contact with eyes.	
Use suitable eye protection.	
Exposure estimate and reference to it	ts source
Assessment method	EASY TRA v6.1, Workplace measurements
	Worker - inhalation, long-term - systemic
Exposure estimate	1 mg/m³
Risk Characterization Ratio (RCR)	0,004444
Assessment method	Qualitative assessment
	Worker - inhalation

Contributing exposure scenario	
Use descriptors covered	PROC5: Mixing or blending in batch processes Use domain: professional
Operational conditions	
Concentration of the substance	sodium metabisulphite Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	0,009 Pa
Process temperature	40 °C
	Corresponds to a vapour pressure < 0.01 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Operation is carried out at ambient or elevated temperatures
Risk Management Measures	
Supervision in place to check that the	
RMMs in place are being used	
correctly and OCs followed. Clean	

Date / Revised: 01.08.2025 Version: 3.0
Date / Previous version: 24.06.2025 Previous version: 2.0

Product: Sodium Metabisulfite photo, non food grade

(ID no. 30042379/SDS_GEN_DE/EN)

equipment and the work area every day. Change clothes immediately after contamination. Ensure good work practices are implemented. Wash off any skin contamination immediately. Ensure minimization of manual phases Provide basic employee training to prevent/minimize exposures. Minimise number of staff exposed. Avoid contact with contaminated tools. Containment as appropriate Provide a good standard of general or controlled ventilation (5 to 10 air changes per hour)			
Wear suitable face shield, Wear			
suitable working clothes.			
Avoid contact with eyes.			
Use suitable eye protection.			
Exposure estimate and reference to it	Exposure estimate and reference to its source		
Assessment method	EASY TRA v6.1, Workplace measurements		
	Worker - inhalation, long-term - systemic		
Exposure estimate	0,05 mg/m³		
Risk Characterization Ratio (RCR)	0,000222		
Assessment method	Qualitative assessment		
	Worker - inhalation		

Contributing exposure scenario	
Use descriptors covered	PROC8b: Transfer of substance or mixture (charging and discharging) at dedicated facilities Use domain: professional
	Additional PROC(s) covered: Transfer of substance or preparation into small containers (dedicated filling line, including weighing). Transfer of substance or mixture (charging and discharging) at non-dedicated facilities
Operational conditions	•
Concentration of the substance	sodium metabisulphite Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	0,009 Pa
Process temperature	40 °C
	Corresponds to a vapour pressure < 0.01 Pa
Duration and Frequency of activity	480 min 5 days per week

Date / Revised: 01.08.2025 Version: 3.0
Date / Previous version: 24.06.2025 Previous version: 2.0

Product: Sodium Metabisulfite photo, non food grade

(ID no. 30042379/SDS_GEN_DE/EN)

Indoor/Outdoor	Indoor
	Operation is carried out at ambient or elevated
	temperatures
Risk Management Measures	
Supervision in place to check that the	
RMMs in place are being used	
correctly and OCs followed. Clean	
equipment and the work area every	
day. Change clothes immediately after	
contamination. Ensure good work	
practices are implemented. Wash off	
any skin contamination immediately.	
Ensure minimization of manual	
phases Provide basic employee	
training to prevent/minimize	
exposures. Minimise number of staff	
exposed. Avoid contact with	
contaminated tools.	
Containment as appropriate Provide a	
good standard of general or controlled	
ventilation (5 to 10 air changes per	
hour)	
Wear suitable face shield, Wear	
suitable working clothes.	
Avoid contact with eyes.	
Use suitable eye protection.	40.00000
Exposure estimate and reference to i	
Assessment method	EASY TRA v6.1, Workplace measurements
Fun course action at	Worker - inhalation, long-term - systemic
Exposure estimate	0,05 mg/m³
Risk Characterization Ratio (RCR)	0,000222
Assessment method	Qualitative assessment
	Worker - inhalation

Contributing exposure scenario	
	PROC10: Roller application or brushing
Use descriptors covered	Use domain: professional
Operational conditions	
	sodium metabisulphite
Concentration of the substance	Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	0,009 Pa
Process temperature	40 °C
	Corresponds to a vapour pressure < 0.01 Pa
Duration and Frequency of activity	480 min 5 days per week

Date / Revised: 01.08.2025 Version: 3.0
Date / Previous version: 24.06.2025 Previous version: 2.0

Product: Sodium Metabisulfite photo, non food grade

(ID no. 30042379/SDS_GEN_DE/EN)

Indoor/Outdoor	Indoor
	Operation is carried out at ambient or elevated temperatures
Risk Management Measures	
Supervision in place to check that the RMMs in place are being used correctly and OCs followed. Clean equipment and the work area every day. Change clothes immediately after contamination. Ensure good work practices are implemented. Wash off any skin contamination immediately. Ensure minimization of manual phases Provide basic employee training to prevent/minimize exposures. Minimise number of staff exposed. Avoid contact with contaminated tools.	
Containment as appropriate Provide a good standard of general or controlled ventilation (5 to 10 air changes per hour)	
Wear suitable face shield, Wear suitable working clothes.	
Avoid contact with eyes.	
Use suitable eye protection.	
Exposure estimate and reference to	
Assessment method	EASY TRA v6.1, Workplace measurements
	Worker - inhalation, long-term - systemic
Exposure estimate	0,05 mg/m ³
Risk Characterization Ratio (RCR)	0,000222
Assessment method	Qualitative assessment
	Worker - inhalation

Contributing exposure scenario	
Use descriptors covered	PROC11: Non industrial spraying Use domain: professional
Operational conditions	
Concentration of the substance	sodium metabisulphite Content: >= 0 % - <= 100 %
Physical state	Solid, medium dustiness
Vapour pressure of the substance during use	0,009 Pa
Process temperature	40 °C
	Corresponds to a vapour pressure < 0.01 Pa

Date / Revised: 01.08.2025 Version: 3.0
Date / Previous version: 24.06.2025 Previous version: 2.0

Product: Sodium Metabisulfite photo, non food grade

(ID no. 30042379/SDS_GEN_DE/EN)

Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Operation is carried out at ambient or elevated temperatures
Risk Management Measures	
Supervision in place to check that the RMMs in place are being used correctly and OCs followed. Clean equipment and the work area every day. Change clothes immediately after contamination. Ensure good work practices are implemented. Wash off any skin contamination immediately. Ensure minimization of manual phases Provide basic employee training to prevent/minimize exposures. Minimise number of staff	
exposed. Avoid contact with contaminated tools.	
Containment as appropriate Provide a good standard of general or controlled ventilation (5 to 10 air changes per hour)	
Wear suitable face shield, Wear suitable working clothes.	
Avoid contact with eyes.	
Use suitable eye protection.	
Exposure estimate and reference to it	
Assessment method	EASY TRA v6.1, Workplace measurements
	Worker - inhalation, long-term - systemic
Exposure estimate	5,5 mg/m ³
Risk Characterization Ratio (RCR)	0,024444
Assessment method	Qualitative assessment
	Worker - inhalation

Contributing exposure scenario	
Use descriptors covered	PROC11: Non industrial spraying Use domain: professional
Operational conditions	
Concentration of the substance	sodium metabisulphite Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	0,009 Pa
Process temperature	40 °C

Date / Revised: 01.08.2025 Version: 3.0
Date / Previous version: 24.06.2025 Previous version: 2.0

Product: Sodium Metabisulfite photo, non food grade

(ID no. 30042379/SDS_GEN_DE/EN)

	Corresponds to a vapour pressure < 0.01 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Operation is carried out at ambient or elevated
	temperatures
Risk Management Measures	
Supervision in place to check that the	
RMMs in place are being used	
correctly and OCs followed. Clean	
equipment and the work area every	
day. Change clothes immediately after	
contamination. Ensure good work	
practices are implemented. Wash off	
any skin contamination immediately.	
Ensure minimization of manual	
phases Provide basic employee	
training to prevent/minimize	
exposures. Minimise number of staff	
exposed. Avoid contact with	
contaminated tools.	
Containment as appropriate Provide a	
good standard of general or controlled	
ventilation (5 to 10 air changes per hour)	
Wear suitable face shield, Wear	
suitable working clothes.	
Avoid contact with eyes.	
Use suitable eye protection.	
Exposure estimate and reference to	its source
Assessment method	EASY TRA v6.1, Workplace measurements
7.00000mont motilod	Worker - inhalation, long-term - systemic
Exposure estimate	5,5 mg/m ³
Risk Characterization Ratio (RCR)	0,024444
Assessment method	Qualitative assessment
	Worker - inhalation
	1

Contributing exposure scenario	
Use descriptors covered	PROC13: Treatment of articles by dipping and pouring. Use domain: professional
Operational conditions	
Concentration of the substance	sodium metabisulphite Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	0,009 Pa
Process temperature	40 °C

Date / Revised: 01.08.2025 Version: 3.0
Date / Previous version: 24.06.2025 Previous version: 2.0

Product: Sodium Metabisulfite photo, non food grade

(ID no. 30042379/SDS_GEN_DE/EN)

	Corresponds to a vapour pressure < 0.01 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Operation is carried out at ambient or elevated temperatures
Risk Management Measures	
Supervision in place to check that the RMMs in place are being used correctly and OCs followed. Clean equipment and the work area every day. Change clothes immediately after contamination. Ensure good work practices are implemented. Wash off any skin contamination immediately. Ensure minimization of manual phases Provide basic employee training to prevent/minimize exposures. Minimise number of staff exposed. Avoid contact with contaminated tools.	
Containment as appropriate Provide a good standard of general or controlled ventilation (5 to 10 air changes per hour)	
Wear suitable face shield, Wear suitable working clothes.	
Avoid contact with eyes.	
Use suitable eye protection.	
Exposure estimate and reference to i	ts source
Assessment method	EASY TRA v6.1, Workplace measurements
	Worker - inhalation, long-term - systemic
Exposure estimate	0,05 mg/m ³
Risk Characterization Ratio (RCR)	0,000222
Assessment method	Qualitative assessment
	Worker - inhalation

Contributing exposure scenario	
Use descriptors covered	PROC15: Use a laboratory reagent. Use domain: professional
Operational conditions	
Concentration of the substance	sodium metabisulphite Content: >= 0 % - <= 100 %
Physical state	Solid, low dustiness
Vapour pressure of the substance during use	0,009 Pa

to Regulation (EC) No 1907/2006. Date / Revised: 01.08.2025

Version: 3.0 Previous version: 2.0

Date / Previous version: 24.06.2025 Product: **Sodium Metabisulfite photo, non food grade**

(ID no. 30042379/SDS_GEN_DE/EN)

Process temperature	40 °C
	Corresponds to a vapour pressure < 0.01 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Operation is carried out at ambient or elevated
	temperatures
Risk Management Measures	
Supervision in place to check that the RMMs in place are being used correctly and OCs followed. Clean equipment and the work area every day. Change clothes immediately after contamination. Ensure good work practices are implemented. Wash off any skin contamination immediately. Ensure minimization of manual phases Provide basic employee training to prevent/minimize exposures. Minimise number of staff exposed. Avoid contact with contaminated tools. Containment as appropriate Provide a	
good standard of general or controlled ventilation (5 to 10 air changes per	
hour)	
Wear suitable face shield, Wear suitable working clothes.	
Avoid contact with eyes.	
Use suitable eye protection.	
Exposure estimate and reference to i	ts source
Assessment method	EASY TRA v6.1, Workplace measurements
7.00000.mont motilod	Worker - inhalation, long-term - systemic
Exposure estimate	0,1 mg/m ³
Risk Characterization Ratio (RCR)	0,000444
Assessment method	Qualitative assessment
	Worker - inhalation

Contributing exposure scenario	
Use descriptors covered	PROC15: Use a laboratory reagent. Use domain: professional
Operational conditions	
Concentration of the substance	sodium metabisulphite Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance	0,009 Pa

Date / Revised: 01.08.2025 Version: 3.0 Date / Previous version: 24.06.2025 Previous version: 2.0

Product: Sodium Metabisulfite photo, non food grade

(ID no. 30042379/SDS_GEN_DE/EN)

during use	
Process temperature	40 °C
	Corresponds to a vapour pressure < 0.01 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Operation is carried out at ambient or elevated temperatures
Risk Management Measures	
Supervision in place to check that the RMMs in place are being used correctly and OCs followed. Clean equipment and the work area every day. Change clothes immediately after contamination. Ensure good work practices are implemented. Wash off any skin contamination immediately. Ensure minimization of manual phases Provide basic employee training to prevent/minimize exposures. Minimise number of staff exposed. Avoid contact with contaminated tools.	
Containment as appropriate Provide a good standard of general or controlled ventilation (5 to 10 air changes per hour)	
Wear suitable face shield, Wear suitable working clothes.	
Avoid contact with eyes.	
Use suitable eye protection.	
Exposure estimate and reference to	
Assessment method	EASY TRA v6.1, Workplace measurements
Evaceure estimate	Worker - inhalation, long-term - systemic
Exposure estimate	0,01 mg/m³
Risk Characterization Ratio (RCR)	0,00044
Assessment method	Qualitative assessment
	Worker - inhalation

Contributing exposure scenario	
Use descriptors covered	PROC19: Manual activities involving hand contact Use domain: professional
Operational conditions	
	sodium metabisulphite
Concentration of the substance	Content: >= 0 % - <= 100 %
Physical state	Solid, low dustiness

Date / Revised: 01.08.2025 Version: 3.0
Date / Previous version: 24.06.2025 Previous version: 2.0

Product: Sodium Metabisulfite photo, non food grade

(ID no. 30042379/SDS_GEN_DE/EN)

Vapour pressure of the substance during use	0,009 Pa
Process temperature	40 °C
	Corresponds to a vapour pressure < 0.01 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Operation is carried out at ambient or elevated temperatures
Risk Management Measures	
Supervision in place to check that the RMMs in place are being used correctly and OCs followed. Clean equipment and the work area every day. Change clothes immediately after contamination. Ensure good work practices are implemented. Wash off any skin contamination immediately. Ensure minimization of manual phases Provide basic employee training to prevent/minimize exposures. Minimise number of staff exposed. Avoid contact with contaminated tools.	
Containment as appropriate Provide a good standard of general or controlled ventilation (5 to 10 air changes per hour)	
Wear suitable face shield, Wear	
suitable working clothes.	
Avoid contact with eyes.	
Use suitable eye protection.	
Exposure estimate and reference to i	
Assessment method	EASY TRA v6.1, Workplace measurements
	Worker - inhalation, long-term - systemic
Exposure estimate	0,5 mg/m³
Risk Characterization Ratio (RCR)	0,002222
Assessment method	Qualitative assessment
	Worker - inhalation

Contributing exposure scenario	
Use descriptors covered	PROC19: Manual activities involving hand contact Use domain: professional
Operational conditions	
Concentration of the substance	sodium metabisulphite Content: >= 0 % - <= 100 %

Date / Revised: 01.08.2025 Version: 3.0
Date / Previous version: 24.06.2025 Previous version: 2.0

Product: Sodium Metabisulfite photo, non food grade

(ID no. 30042379/SDS_GEN_DE/EN)

Physical state	liquid
Vapour pressure of the substance during use	0,009 Pa
Process temperature	40 °C
	Corresponds to a vapour pressure < 0.01 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Operation is carried out at ambient or elevated temperatures
Risk Management Measures	
Supervision in place to check that the RMMs in place are being used correctly and OCs followed. Clean equipment and the work area every day. Change clothes immediately after contamination. Ensure good work practices are implemented. Wash off any skin contamination immediately. Ensure minimization of manual phases Provide basic employee training to prevent/minimize exposures. Minimise number of staff exposed. Avoid contact with contaminated tools. Containment as appropriate Provide a	
good standard of general or controlled ventilation (5 to 10 air changes per	
hour)	
Wear suitable face shield, Wear suitable working clothes.	
Avoid contact with eyes.	
Use suitable eye protection.	
Exposure estimate and reference to i	ts source
Assessment method	EASY TRA v6.1, Workplace measurements
	Worker - inhalation, long-term - systemic
Exposure estimate	0,05 mg/m ³
Risk Characterization Ratio (RCR)	0,000222
Assessment method	Qualitative assessment
	Worker - inhalation

Contributing exposure scenario	
Use descriptors covered	PROC26: Handling of solid inorganic substances at ambient temperature Use domain: professional
Operational conditions	
Concentration of the substance	sodium metabisulphite

Date / Revised: 01.08.2025 Version: 3.0
Date / Previous version: 24.06.2025 Previous version: 2.0

Product: Sodium Metabisulfite photo, non food grade

(ID no. 30042379/SDS_GEN_DE/EN)

Date of print 22.10.2025

	Content: >= 0 % - <= 100 %
Physical state	Solid, low dustiness
Vapour pressure of the substance during use	0,009 Pa
Process temperature	40 °C
	Corresponds to a vapour pressure < 0.01 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Operation is carried out at ambient or elevated temperatures
Risk Management Measures	
Supervision in place to check that the RMMs in place are being used correctly and OCs followed. Clean equipment and the work area every day. Change clothes immediately after contamination. Ensure good work practices are implemented. Wash off any skin contamination immediately. Ensure minimization of manual phases Provide basic employee training to prevent/minimize exposures. Minimise number of staff exposed. Avoid contact with contaminated tools. Containment as appropriate Provide a good standard of general or controlled ventilation (5 to 10 air changes per	
hour) Wear suitable face shield, Wear	
suitable working clothes.	
Avoid contact with eyes.	
Use suitable eye protection.	
Exposure estimate and reference to	
Assessment method	EASY TRA v6.1, Workplace measurements
Evangura actimata	Worker - inhalation, long-term - systemic 3 mg/m ³
Exposure estimate Risk Characterization Ratio (RCR)	0,013333
Assessment method	Qualitative assessment
	Worker - inhalation

9. Short title of exposure scenario

Consumer applications, Use in/as Photochemicals

Date / Revised: 01.08.2025 Version: 3.0
Date / Previous version: 24.06.2025 Previous version: 2.0

Product: Sodium Metabisulfite photo, non food grade

(ID no. 30042379/SDS_GEN_DE/EN)

Date of print 22.10.2025

C; ERC8e; PC30

Control of exposure and risk management measures

Contributing exposure scenario	
Use descriptors covered	ERC8e: Widespread use of reactive processing aid (no inclusion into or onto article, outdoor) As no environmental hazard was identified no environmental-related exposure assessment and risk characterization was performed.
Operational conditions	

Contributing exposure scenario		
Use descriptors covered	PC30: Photochemicals.	
Operational conditions		
	sodium metabisulphite	
Concentration of the substance	Content: >= 0 % - <= 20 %	
Vapour pressure of the substance during use	0,00001 Pa	
Duration and Frequency of activity	1 uses per day	
Indoor/Outdoor	Indoor	
Exposure estimate and reference to its source		
Assessment method	EASY TRA v6.1, Other consideration (non-standard tool)	
	Consumer - inhalation, long-term - systemic	
Exposure estimate	0,0001 mg/m ³	
Risk Characterization Ratio (RCR)	0,000001	
Assessment method	EASY TRA v6.1, Other consideration (non-standard tool)	
	Consumer - oral, long-term - systemic	
Exposure estimate	0,0001 mg/kg bw/day	
Risk Characterization Ratio (RCR)	0,000001	
Guidance to Downstream Users		
For scaling see: http://www.ecetoc.org	g/tra	

Contributing exposure scenario	
Use descriptors covered	PC30: Photochemicals.
Operational conditions	•
Concentration of the substance	sodium metabisulphite Content: >= 0 % - <= 20 %
Vapour pressure of the substance during use	0,00001 Pa
Duration and Frequency of activity	Exposure duration: 15 min 365 uses per year
Indoor/Outdoor	Indoor

Date / Revised: 01.08.2025 Version: 3.0
Date / Previous version: 24.06.2025 Previous version: 2.0

Product: Sodium Metabisulfite photo, non food grade

(ID no. 30042379/SDS_GEN_DE/EN)

Exposure estimate and reference to its source	
Assessment method	EASY TRA v6.1, Other consideration (non-standard tool)
	Consumer - inhalation, long-term - systemic
Exposure estimate	0,024 mg/m³
Risk Characterization Ratio (RCR)	0,000364
Assessment method	EASY TRA v6.1, Other consideration (non-standard tool)
	Consumer - oral, long-term - systemic
Exposure estimate	0,0001 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,000001
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/	tra

Contributing exposure scenario		
Use descriptors covered	PC30: Photochemicals.	
Operational conditions		
	sodium metabisulphite	
Concentration of the substance	Content: >= 0 % - <= 10 %	
Vapour pressure of the substance during use	0,00001 Pa	
Duration and Frequency of activity	1 uses per day	
Indoor/Outdoor	Indoor	
Exposure estimate and reference to its source		
Assessment method	EASY TRA v6.1, Other consideration (non-standard tool)	
	Consumer - inhalation, long-term - systemic	
Exposure estimate	0,0001 mg/m ³	
Risk Characterization Ratio (RCR)	0,000001	
Assessment method	EASY TRA v6.1, Other consideration (non-standard tool)	
	Consumer - oral, long-term - systemic	
Exposure estimate	0,0001 mg/kg bw/day	
Risk Characterization Ratio (RCR)	0,000001	
Guidance to Downstream Users		
For scaling see: http://www.ecetoc.org	/tra	

Contributing exposure scenario	
Use descriptors covered	PC30: Photochemicals.
Operational conditions	
Concentration of the substance	sodium metabisulphite Content: >= 0 % - <= 10 %
Vapour pressure of the substance during use	0,00001 Pa
Duration and Frequency of activity	1 uses per day
Indoor/Outdoor	Indoor
Exposure estimate and reference to its source	

Date / Revised: 01.08.2025 Version: 3.0
Date / Previous version: 24.06.2025 Previous version: 2.0

Product: Sodium Metabisulfite photo, non food grade

(ID no. 30042379/SDS_GEN_DE/EN)

Date of print 22.10.2025

Assessment method	EASY TRA v6.1, Other consideration (non-standard tool)
	Consumer - inhalation, long-term - systemic
Exposure estimate	0,0001 mg/m³
Risk Characterization Ratio (RCR)	0,000001
Assessment method	EASY TRA v6.1, Other consideration (non-standard tool)
	Consumer - oral, long-term - systemic
Exposure estimate	0,0001 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,000001
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org	g/tra

* * * * * * * * * * * * * * * *

10. Short title of exposure scenario

Service life of articles, Use in leather tanning, finishing, impregnation, (use in professional settings) SL; ERC10a; PROC21

Control of exposure and risk management measures

Contributing exposure scenario	
Use descriptors covered	ERC10a: Widespread use of articles with low release (outdoor) As no environmental hazard was identified no environmental-related exposure assessment and risk characterization was performed.
Operational conditions	

Contributing exposure scenario	
Use descriptors covered	PROC21: Low energy manipulation and handling of substances bound in/on materials or articles Use domain: professional
Operational conditions	
	sodium metabisulphite
Concentration of the substance	Content: >= 0 % - <= 1 %
Physical state	Solid, low dustiness
Vapour pressure of the substance during use	0,009 Pa
Process temperature	40 °C
	Corresponds to a vapour pressure < 0.01 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Operation is carried out at ambient or elevated temperatures

Date / Revised: 01.08.2025 Version: 3.0
Date / Previous version: 24.06.2025 Previous version: 2.0

Product: Sodium Metabisulfite photo, non food grade

(ID no. 30042379/SDS_GEN_DE/EN)

Date of print 22.10.2025

Risk Management Measures	
Supervision in place to check that the	
RMMs in place are being used	
correctly and OCs followed. Clean	
equipment and the work area every	
day. Change clothes immediately after	
contamination. Ensure good work	
practices are implemented. Wash off	
any skin contamination immediately.	
Ensure minimization of manual	
phases Provide basic employee	
training to prevent/minimize	
exposures. Minimise number of staff	
exposed. Avoid contact with	
contaminated tools.	
Containment as appropriate Provide a	
good standard of general or controlled	
ventilation (5 to 10 air changes per	
hour)	
Wear suitable face shield, Wear	
suitable working clothes.	
Avoid contact with eyes.	
Use suitable eye protection.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v6.1, Workplace measurements
	Worker - inhalation, long-term - systemic
Exposure estimate	0,05 mg/m³
Risk Characterization Ratio (RCR)	0,000222
Assessment method	Qualitative assessment
	Worker - inhalation

* * * * * * * * * * * * * * * *