

Styrofan® 5406

Chemical Nature	Aqueous dispersion	of a carboxylated st	tyrene/butadiene cond	olymer used in coating
Onemical Nature	Aqueous dispersion	or a carboxyrated st	tyrenerbutatione copt	nymer asca m coaming

formulations

			_					_	
S	ρ	П	rt	ρ	n	റ	r	μ	
	ㄷ		I L	ㄷ	u	u		_	

Typical PropertiesSolids content
pH value

Solids content
pH value

52.0 – 53.0
6.4 – 7.4

pH value 6.4 – 7.4 Viscosity at 23 °C cps 200 – 700

(Brookfield RV, Spindle #2, at 20 rpm)

Other properties of
the dispersionDensitylbs/galca. 8.3Dispersion typeanionic

Compatible with Styrofan 5406 is compatible with other substances commonly used in coatings and saturation

applications.

Thickeners Sterocoll® FS, Rheovis AS 1125 and casein solutions

* The above values should not be taken as specification.

Application

Processing Styrofan 5406 is a frothable dispersion. Its dried films are very strong and exhibit excellent water

resistance.

Styrofan 5406 demonstrates excellent runnability in coating applications.

Styrofan 5406 is ideally suited for binder applications.

Safety

General The usual safety precautions when handling chemicals must be observed. These include the

measures described in Federal, State and Local health and safety regulations, thorough ventilation

of the workplace, good skin care and wearing of protective goggles.

Safety Data Sheet All safety information is provided in the Safety Data Sheet for Styrofan 5406.

Storage

Please refer to the "Handling and Storage of Polymer Dispersions" brochure.

Important

The descriptions, designs, and data contained herein are presented for your guidance only. Because there are many factors under your control which may affect processing or application/use it is necessary for you to make appropriate tests to determine whether the product is suitable for your particular purpose prior to use. NO WARRANTIES OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, OR DATA MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, DATA OR DESIGNS PROVIDED BE PRESUMED TO BE A PART OF OUR TERMS AND CONDITIONS OF SALE. Further, you expressly understand and agree that the descriptions, designs, and data furnished by BASF hereunder are given gratis and BASF assumes no obligation or liability for same or results obtained from use thereof, all such being given to you and accepted by you at your risk.

Styrofan is a registered trademark of BASF Group.

© BASF Corporation, 2025



BASF Corporation is fully committed to the Responsible Care® initiative in the USA, Canada, and Mexico.
For more information on Responsible Care® go to:
U.S.: www.basf.us/responsiblecare_usa
Canada: www.basf.us/responsiblecare_canada
México: www.basf.us/responsiblecare_mexico

BASF Corporation Dispersions and Resins 11501 Steele Creek Road Charlotte, North Carolina 28273 Phone: (800) 251 – 0612

Email: CustCare-Charlotte@basf.com

Email: edtech-info@basf.com www.basf.us/formulation-additives