



We create chemistry

## Safety Data Sheet

### ULTRAMID® A3HG6 HR BLACK 23591 POLYAMIDE

Revision date : 2025/09/17

Version: 7.0

Page: 1/9

(30043125/SDS\_GEN\_CA/EN)

## 1. Identification

**Product identifier used on the label**

**ULTRAMID® A3HG6 HR BLACK 23591  
POLYAMIDE**

**Recommended use of the chemical and restriction on use**

Recommended use\*: Polymer

Recommended use\*: Polymer; for industrial processing only

Suitable for use in industrial sector: Polymers industry

Unsuitable for use: Uses other than recommended

\* The "Recommended use" identified for this product is provided solely to comply with a Federal requirement and is not part of the seller's published specification. The terms of this Safety Data Sheet (SDS) do not create or infer any warranty, express or implied, including by incorporation into or reference in the seller's sales agreement.

**Details of the supplier of the safety data sheet**

Company:

BASF Canada Inc.

5025 Creekbank Road

Building A, Floor 2

Mississauga, ON, L4W 0B6, CANADA

Telephone: +1 289 360-1300

**Emergency telephone number**

24 Hour Emergency Response Information

CHEMTREC: 1-800-424-9300

BASF HOTLINE: (800) 454-COPE (2673)

**Other means of identification**

Synonyms: Polamide (PA 66)

## 2. Hazards Identification

According to Hazardous Products Regulations (HPR) (SOR/2022-272)

**Classification of the product**

# Safety Data Sheet

## ULTRAMID® A3HG6 HR BLACK 23591 POLYAMIDE

Revision date: 2025/09/17

Page: 2/9

Version: 7.0

(30043125/SDS\_GEN\_CA/EN)

No need for classification according to GHS criteria for this product.

### Label elements

The product does not require a hazard warning label in accordance with GHS criteria.

### Hazards not otherwise classified

No specific dangers known, if the regulations/notes for storage and handling are considered.

Labeling of special preparations (GHS):

UNDER HOT MELT PROCESSING CONDITIONS, WEAR PERSONAL PROTECTIVE EQUIPMENT TO PREVENT THERMAL BURNS.

---

## 3. Composition / Information on Ingredients

### According to Hazardous Products Regulations (HPR) (SOR/2022-272)

carbon black

CAS Number: 1333-86-4

Content (W/W):  $\geq 0.1$  -  $\leq 1.0\%$

Synonym: C.I. 77266

The actual concentration is withheld as a trade secret.

---

## 4. First-Aid Measures

### Description of first aid measures

#### General advice:

Avoid contact with the skin, eyes and clothing. Remove contaminated clothing.

#### If inhaled:

Remove the affected individual into fresh air and keep the person calm. If difficulties occur after dust has been inhaled, remove to fresh air and seek medical attention.

#### If on skin:

Burns caused by molten material require hospital treatment.

#### If in eyes:

In case of contact with the eyes, rinse immediately for at least 15 minutes with plenty of water. If irritation develops, seek medical attention.

#### If swallowed:

Rinse mouth and then drink 200-300 ml of water. Ingestion is not likely in the available physical form. If ingested, seek medical attention.

### Most important symptoms and effects, both acute and delayed

# Safety Data Sheet

## ULTRAMID® A3HG6 HR BLACK 23591 POLYAMIDE

Revision date: 2025/09/17

Page: 3/9

Version: 7.0

(30043125/SDS\_GEN\_CA/EN)

Symptoms: (Further) symptoms and / or effects are not known so far

No data available.

Hazards: No hazard is expected under intended use and appropriate handling.

### Indication of any immediate medical attention and special treatment needed

#### Note to physician

Treatment:

Treat according to symptoms (decontamination, vital functions), no known specific antidote.

---

## 5. Fire-Fighting Measures

Suitable extinguishing media:  
water spray, foam, dry powder

Unsuitable extinguishing media for safety reasons:  
water jet

### Special hazards arising from the substance or mixture

Hazards during fire-fighting:

Ammonium hydroxide, carbon monoxide, cyclopentanone, hydrogen cyanide, amine derivatives, nitriles

Under special fire conditions traces of other toxic substances are possible. Formation of further decomposition and oxidation products depends upon the fire conditions.

### Advice for fire-fighters

Protective equipment for fire-fighting:

Firefighters should be equipped with self-contained breathing apparatus and turn-out gear. Wear self-contained breathing apparatus and chemical-protective clothing.

### Further information:

Dispose of fire debris and contaminated extinguishing water in accordance with official regulations. Keep adjacent fire-exposed buildings, equipment, and materials cool with water spray.

---

## 6. Accidental release measures

### Further accidental release measures:

High risk of slipping due to leakage/spillage of product.

### Personal precautions, protective equipment and emergency procedures

No special precautions necessary.

### Environmental precautions

No special precautions necessary.

### Methods and material for containment and cleaning up

For small amounts: Pick up with suitable appliance and dispose of.

For large amounts: Pick up with suitable appliance and dispose of.

For residues: Sweep/shovel up.

Dispose of absorbed material in accordance with regulations.

# Safety Data Sheet

## ULTRAMID® A3HG6 HR BLACK 23591 POLYAMIDE

Revision date: 2025/09/17

Version: 7.0

Page: 4/9

(30043125/SDS\_GEN\_CA/EN)

---

### 7. Handling and Storage

#### Precautions for safe handling

Provide suction extractors if dust is formed. Any unavoidable deposit of dust must be regularly removed.

Protection against fire and explosion:

Take precautionary measures against static discharges.

#### Conditions for safe storage, including any incompatibilities

The product in undamaged packing need not be stored separately.

Suitable materials for containers: Low density polyethylene (LDPE), High density polyethylene (HDPE), Aluminium, Carbon steel (Iron)

Further information on storage conditions: Keep container tightly closed. Avoid deposition of dust. Protect against moisture.

Storage stability:

Protect against moisture.

---

### 8. Exposure Controls/Personal Protection

#### Components with occupational exposure limits

carbon black	ACGIH, US:	TWA value	3 mg/m3	Inhalable fraction ;
	OSHA Z1:	PEL	3.5 mg/m3 ;	

#### Advice on system design:

Ensure adequate ventilation. Provide local exhaust ventilation to control dusts/vapours.

#### Personal protective equipment

##### Respiratory protection:

Wear respiratory protection if ventilation is inadequate. Wear a NIOSH-certified (or equivalent) organic vapour/particulate respirator.

##### Hand protection:

Wear gloves to prevent contact during mechanical processing and/or hot melt conditions., Chemical resistant protective gloves, Suitable materials, rubber, plastic

##### Eye protection:

Safety glasses with side-shields. Tightly fitting safety goggles (chemical goggles).

##### Body protection:

Body protection must be chosen based on level of activity and exposure.

##### General safety and hygiene measures:

No special precautions necessary. Wash soiled clothing immediately.

---

# Safety Data Sheet

## ULTRAMID® A3HG6 HR BLACK 23591 POLYAMIDE

Revision date: 2025/09/17

Page: 5/9

Version: 7.0

(30043125/SDS\_GEN\_CA/EN)

### 9. Physical and Chemical Properties

Physical state:	solid	
Form:	pellets	
Odour:	odourless	
Odour threshold:	not applicable	
Colour:	various, depending on the colourant	
pH value:	not applicable	
Melting temperature:	approx. 260 °C ( 1,013 hPa)	(DIN 53765)
Freezing point:	No data available.	
Boiling range:	The substance / product decomposes therefore not determined.	
Sublimation point:	No applicable information available.	
Flash point:	> 400 °C	(Unspecified)
Flammability:	not self-igniting	(derived from flash point)
Flammability of Aerosol Products:	not applicable, the product does not form flammable aerosoles	
Lower explosion limit:	For solids not relevant for classification and labelling.	
Upper explosion limit:	For solids not relevant for classification and labelling.	
Autoignition:	> 400 °C	(ASTM D1929)
Vapour pressure:	not applicable	
Density:	1.15 - 1.60 g/cm3 ( 20 °C, 1,013 hPa)	(EN ISO 1183-1)
Relative density:	Study does not need to be conducted.	
Bulk density:	500 - 800 kg/m3 ( 20 °C, 1,013 hPa)	(DIN 53466)
Relative vapour density:	not applicable	
Partitioning coefficient n- octanol/water (log Pow):	not applicable	
Self-ignition temperature:	not self-igniting	
Thermal decomposition:	> 320 °C (TGA)	
Viscosity, dynamic:	not applicable, the product is a solid	
Viscosity, kinematic:	not applicable, the product is a solid	
Solubility in water:	( 20 °C, 1,013 hPa) insoluble	
Solubility (quantitative):	No applicable information available.	
Solubility (qualitative):	No applicable information available.	
Molecular weight:	No data available.	
Evaporation rate:	The product is a non-volatile solid.	
<b>Particle characteristics</b>		
Particle size distribution:	spheroidal	
Specific Surface Area:	0.0 m²/g	(MSSA, ISO 9227)

### 10. Stability and Reactivity

#### Reactivity

No hazardous reactions if stored and handled as prescribed/indicated.

# Safety Data Sheet

## ULTRAMID® A3HG6 HR BLACK 23591 POLYAMIDE

Revision date: 2025/09/17

Page: 6/9

Version: 7.0

(30043125/SDS\_GEN\_CA/EN)

Corrosion to metals:  
No corrosive effect on metal.

Oxidizing properties:  
not fire-propagating

### Chemical stability

The product is stable if stored and handled as prescribed/indicated.  
The product is chemically stable.

### Possibility of hazardous reactions

The product is chemically stable.  
No hazardous reactions known.

### Conditions to avoid

Temperature: > 320 degrees Celsius

### Incompatible materials

No substances known that should be avoided.

### Hazardous decomposition products

Decomposition products:  
Possible decomposition products: Ammonium hydroxide, carbon monoxide, carbon dioxide, cyclopentanone, hydrogen cyanide, amines, nitriles

Thermal decomposition:  
> 320 °C (TGA)

---

## 11. Toxicological information

### Primary routes of exposure

Routes of entry for solids and liquids are ingestion and inhalation, but may include eye or skin contact. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquefied gases.

### Acute Toxicity/Effects

#### Acute toxicity

Assessment of acute toxicity: Contact with molten product may cause thermal burns. The resin in pelleted form poses a low hazard.

#### Inhalation

Not inhalable due to the physico-chemical properties of the product.

#### Dermal

Type of value: ATE  
Value: > 5,000 mg/kg

#### Assessment other acute effects

No applicable information available.

# Safety Data Sheet

## ULTRAMID® A3HG6 HR BLACK 23591 POLYAMIDE

Revision date: 2025/09/17

Version: 7.0

Page: 7/9

(30043125/SDS\_GEN\_CA/EN)

### Irritation / corrosion

Assessment of irritating effects: Thermal decomposition products of the substance can irritate the eyes, skin, and respiratory tract.

### Sensitization

Assessment of sensitization: Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses.

### Aspiration Hazard

No aspiration hazard expected.

## **Chronic Toxicity/Effects**

### Repeated dose toxicity

Assessment of repeated dose toxicity: Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses.

### Genetic toxicity

Assessment of mutagenicity: Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses.

### Carcinogenicity

#### *Information on: carbon black*

*Assessment of carcinogenicity: IARC (International Agency for Research on Cancer) has classified this substance as group 2B (The agent is possibly carcinogenic to humans). In long-term animal studies in which the substance was given by inhalation in high concentrations, a carcinogenic effect was observed. A clear indication of an increased risk of cancer in humans has so far not been shown. No carcinogenic potential can be deduced from other studies with rats and mice.*

-----

### Reproductive toxicity

Assessment of reproduction toxicity: Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses.

### Teratogenicity

Assessment of teratogenicity: Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses.

### Other Information

Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses.

---

## **12. Ecological Information**

### **Toxicity**

# Safety Data Sheet

## ULTRAMID® A3HG6 HR BLACK 23591 POLYAMIDE

Revision date: 2025/09/17

Page: 8/9

Version: 7.0

(30043125/SDS\_GEN\_CA/EN)

### Aquatic toxicity

#### Assessment of aquatic toxicity:

The product has not been tested. The statement has been derived from the structure of the product. There is a high probability that the product is not acutely harmful to aquatic organisms.

### Persistence and degradability

#### Assessment biodegradation and elimination (H<sub>2</sub>O)

Experience shows this product to be inert and non-degradable.

The product is virtually insoluble in water and can thus be separated from water mechanically in suitable effluent treatment plants.

#### Elimination information

Poorly biodegradable.

#### Assessment of stability in water

According to structural properties, hydrolysis is not expected/probable.

### Bioaccumulative potential

#### Assessment bioaccumulation potential

Does not significantly accumulate in organisms.

#### Bioaccumulation potential

Because of the product's consistency and low water solubility, bioavailability is improbable.

### Mobility in soil

#### Assessment transport between environmental compartments

Adsorption to solid soil phase is not expected.

### Additional information

#### Adsorbable organically-bound halogen(AOX):

This product contains no organically-bound halogen.

#### Other ecotoxicological advice:

The product is a polymeric compound.

---

## 13. Disposal considerations

### Waste disposal of substance:

Check for possible recycling. Incinerate in suitable incineration plant, observing local authority regulations.

### Container disposal:

Dispose of in accordance with national, state and local regulations.

---

## 14. Transport Information

### Land transport

TDG



# Safety Data Sheet

## ULTRAMID® A3HG6 HR BLACK 23591 POLYAMIDE

Revision date: 2025/09/17

Page: 9/9

Version: 7.0

(30043125/SDS\_GEN\_CA/EN)

Not classified as a dangerous good under transport regulations

### Sea transport

IMDG

Not classified as a dangerous good under transport regulations

### Air transport

IATA/ICAO

Not classified as a dangerous good under transport regulations

## 15. Regulatory Information

### Federal Regulations

#### Registration status:

Chemical DSL, CA

DSL listed and/or otherwise compliant.

#### NFPA Hazard codes:

Health: 1 Fire: 1 Reactivity: 0 Special:

## 16. Other Information

### SDS Prepared by:

BASF NA Product Regulations

SDS Prepared on: 2025/09/17

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

ULTRAMID® A3HG6 HR BLACK 23591 POLYAMIDE is a registered trademark of BASF Canada or BASF SE

Date / Revised: 2025/09/17

Version: 7.0

Date / Previous version: 2025/02/21

Previous version: 6.0

END OF DATA SHEET