

# Safety Data Sheet

## BUTYL ACRYLATE

Revision date : 2025/10/06  
Version: 15.0

Page: 1/15  
(30041258/SDS\_GEN\_US/EN)

### 1. Identification

#### Product identifier used on the label

**BUTYL ACRYLATE**

#### Recommended use of the chemical and restriction on use

Recommended use\*: Monomer.

Recommended use\*: Monomer.; Intermediate

Unsuitable for use: cosmetics; Pharmaceutical

\* The "Recommended use" identified for this product is provided solely to comply with a Federal requirement and is not part of the seller's published specification. The terms of this Safety Data Sheet (SDS) do not create or infer any warranty, express or implied, including by incorporation into or reference in the seller's sales agreement.

#### Details of the supplier of the safety data sheet

##### Company:

BASF CORPORATION  
100 Park Avenue  
Florham Park, NJ 07932, USA

Telephone: +1 973 245-6000

#### Emergency telephone number

##### 24 Hour Emergency Response Information

CHEMTREC: 1-800-424-9300

BASF HOTLINE: 1-800-832-HELP (4357)

##### **Other means of identification**

Molecular formula: C7 H12 O2

Chemical family: acrylates

Synonyms: Acrylic acid, butyl ester

Butyl 2-propenoate; 2-Propenoic acid, butyl ester

### 2. Hazards Identification

#### According to Regulation 2024 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

##### Classification of the product

Flam. Liq.	3	Flammable liquids
Acute Tox.	4 (Inhalation - vapour)	Acute toxicity

# Safety Data Sheet

## BUTYL ACRYLATE

Revision date: 2025/10/06  
Version: 15.0

Page: 2/15  
(30041258/SDS\_GEN\_US/EN)

Skin Irrit.	2	Skin irritation
Eye Irrit.	2A	Eye irritation
Skin Sens.	1B	Skin sensitization
STOT SE	3 (irritating to respiratory system)	Specific target organ toxicity — single exposure
Aquatic Acute	2	Hazardous to the aquatic environment - acute
Aquatic Chronic	3	Hazardous to the aquatic environment - chronic

### Label elements

Pictogram:



Signal Word:  
Warning

Hazard Statement:

H226	Flammable liquid and vapour.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H332	Harmful if inhaled.
H317	May cause an allergic skin reaction.
H335	May cause respiratory irritation.
H412	Harmful to aquatic life with long lasting effects.
H401	Toxic to aquatic life.

Precautionary Statements (Prevention):

P280	Wear protective gloves and eye protection or face protection.
P271	Use only outdoors or in a well-ventilated area.
P260	Do not breathe mist or vapour.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P273	Avoid release to the environment.
P243	Take action to prevent static discharges.
P241	Use explosion-proof electrical, ventilating and lighting equipment.
P272	Contaminated work clothing should not be allowed out of the workplace.
P264	Wash contaminated body parts thoroughly after handling.
P242	Use non-sparking tools.
P240	Ground and bond container and receiving equipment.

Precautionary Statements (Response):

# Safety Data Sheet

## BUTYL ACRYLATE

Revision date: 2025/10/06  
Version: 15.0

Page: 3/15  
(30041258/SDS\_GEN\_US/EN)

P312	Call a POISON CENTER or physician if you feel unwell.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P333 + P313	If skin irritation or rash occurs: Get medical attention.
P362 + P364	Take off contaminated clothing and wash it before reuse.
P332 + P313	If skin irritation occurs: Get medical attention.
P337 + P313	If eye irritation persists: Get medical attention.
P370 + P378	In case of fire: Use water spray, dry powder, foam or carbon dioxide for extinction.

### Precautionary Statements (Storage):

P403 + P235	Store in a well-ventilated place. Keep cool.
P233	Keep container tightly closed.
P405	Store locked up.

### Precautionary Statements (Disposal):

P501	Dispose of contents/container in accordance with local regulations.
------	---

## Hazards not otherwise classified

No applicable information available.

### Labeling of special preparations (GHS):

Risk of hazardous polymerization under certain conditions (e.g. elevated temperatures, low inhibitor and oxygen concentration). Do not blanket with nitrogen.

---

## 3. Composition / Information on Ingredients

### According to Regulation 2024 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

#### n-butyl acrylate

CAS Number: 141-32-2  
Content (W/W):  $\geq 80.0$  -  $\leq 100.0\%$   
Synonym: 2-Propenoic acid butyl ester; Butyl acrylate

#### but-1-ene

CAS Number: 106-98-9  
Content (W/W):  $< 0.1\%$   
Synonym: n-Buten-1

The actual concentration is withheld as a trade secret.

---

## 4. First-Aid Measures

### Description of first aid measures

# Safety Data Sheet

## BUTYL ACRYLATE

Revision date: 2025/10/06  
Version: 15.0

Page: 4/15  
(30041258/SDS\_GEN\_US/EN)

### General advice:

First aid personnel should pay attention to their own safety. If the patient is likely to become unconscious, place and transport in stable sideways position (recovery position). Immediately remove contaminated clothing.

### If inhaled:

Keep patient calm, remove to fresh air, seek medical attention.

### If on skin:

Wash thoroughly with soap and water

### If in eyes:

Hold eyes open and rinse slowly and gently with water for 15 to 20 minutes. Remove contact lenses, if present, after first 5 minutes, then continue rinsing.

### If swallowed:

Immediately rinse mouth and then drink 200-300 ml of water, seek medical attention.

### Most important symptoms and effects, both acute and delayed

Symptoms: Overexposure may cause: Eye irritation, skin irritation, erythema, nausea, headache, vomiting, dizziness, diarrhea, abdominal cramps

### Indication of any immediate medical attention and special treatment needed

#### Note to physician

Treatment: Treat according to symptoms (decontamination, vital functions), no known specific antidote.

---

## 5. Fire-Fighting Measures

### Extinguishing media

Suitable extinguishing media:  
dry powder, water spray, carbon dioxide, foam

Unsuitable extinguishing media for safety reasons:  
water jet

Additional information:  
Use extinguishing measures to suit surroundings.

### Special hazards arising from the substance or mixture

Hazards during fire-fighting:  
Risk of violent self-polymerization if overheated in a container. Cool endangered containers with water-spray.

The product is combustible. See SDS section 7 - Handling and storage.

### Advice for fire-fighters

Protective equipment for fire-fighting:  
Firefighters should be equipped with self-contained breathing apparatus and turn-out gear. Special protective equipment for firefighters

# Safety Data Sheet

## BUTYL ACRYLATE

Revision date: 2025/10/06  
Version: 15.0

Page: 5/15  
(30041258/SDS\_GEN\_US/EN)

### Further information:

Extend fire extinguishing measures to the surroundings. Fight fire from maximum distance. Vapours are heavier than air and may accumulate in low areas and travel a considerable distance up to the source of ignition.

In case of a fire in the vicinity a restabilization system should be used if the temperature in the bulk storage-tank reaches 45°C. Evacuate area of all unnecessary personnel. In case of a fire in the vicinity evacuate all personnel in a greater area if the temperature in the bulk storage-tank reaches 60°C.

Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

### Impact Sensitivity:

Remarks: Based on the chemical structure there is no shock-sensitivity.

---

## 6. Accidental release measures

### Further accidental release measures:

High risk of slipping due to leakage/spillage of product.

Release of substance/product can cause fire or explosion. Shut off or stop source of leak. Shut off or stop released substance/product under safe conditions.

Pack in tightly closed containers for disposal.

### Personal precautions, protective equipment and emergency procedures

Handle in accordance with good industrial hygiene and safety practice.

Avoid all sources of ignition: heat, sparks, open flame. Use antistatic tools.

### Environmental precautions

Discharge into the environment must be avoided.

### Methods and material for containment and cleaning up

For large amounts: Pump off product.

Spills should be contained, solidified, and placed in suitable containers for disposal. Dispose of absorbed material in accordance with regulations. Ensure adequate ventilation. Suppress gases/vapours/mists with water spray jet. Clean contaminated floors and objects thoroughly with water and detergents, observing environmental regulations. Cleaning operations should be carried out only while wearing breathing apparatus. Pick up with suitable appliance and dispose of.

---

## 7. Handling and Storage

### Precautions for safe handling

The substance/ product may be handled only by appropriately trained personnel. Facility parts must be checked for polymer residues and cleaned on regular basis in order to avoid hazardous reactions.

Ensure thorough ventilation of stores and work areas. Encapsulation or exhaust ventilation required. When filling, transferring, or emptying of containers, adequate local exhaust ventilation is necessary. Vent waste air to atmosphere only through suitable separators. Check the condition of seals and connector screw threads.

# Safety Data Sheet

## BUTYL ACRYLATE

Revision date: 2025/10/06  
Version: 15.0

Page: 6/15  
(30041258/SDS\_GEN\_US/EN)

The temperatures which must be avoided are to be considered. Protect against heat. Protect from direct sunlight. Protect contents from the effects of light. Do not open warm or swollen product containers. Remove persons to safety and alert fire brigade.

Ensure adequate inhibitor and dissolved oxygen level.

Avoid inhalation of dusts/mists/vapours. Avoid aerosol formation. Avoid all direct contact with the substance/product.

Protection against fire and explosion:

Avoid all sources of ignition: heat, sparks, open flame. Substance/product can form explosive mixture with air. Ground all transfer equipment properly to prevent electrostatic discharge. It is recommended that all conductive parts of the machinery are grounded. Explosion-proof equipment is not necessary when loading and processing of the product takes place at a minimum of 5 °C below the flash point.

Heated containers should be cooled to prevent polymerization. If exposed to fire, keep containers cool by spraying with water. Emergency cooling must be provided for the eventuality of a fire in the vicinity.

Vapours are heavier than air and may accumulate in low areas and travel a considerable distance up to the source of ignition.

### Conditions for safe storage, including any incompatibilities

Segregate from oxidizing agents. Segregate from reducing agents. Segregate from peroxides. See SDS section 10 - Stability and reactivity.

Further information on storage conditions: Prior to storage ensure that the transfer equipment used and the intended storage containers do not contain other substances/products. Before transfer to stock the identity of the product must be proved to be without doubt. The entrance to storage rooms is to be granted only to appropriately trained personnel.

The stabilizer is only effective in the presence of oxygen. Maintain contact with atmosphere containing 5 - 21% oxygen. Never use tanks with inert-gas installation for storage.

Risk of polymerization. Protect against heat. Protect from direct sunlight. Avoid UV-light and other radiation with high energy. Protect against contamination.

In case of bulk storage, the storage-tanks should at least be equipped with two high temperature alert devices.

Even if the product is stored and handled as prescribed/indicated it should be used up within the indicated duration of storage.

Storage stability:

Storage temperature: < 35 °C

Storage duration: 12 Months

The stated storage temperature should be noted.

Avoid prolonged storage.

This product should be processed as soon as possible.

Ensure adequate inhibitor and dissolved oxygen level.

Do not store with less than 10 % headspace above liquid.

Storage stability is based upon ambient temperatures and conditions described.

It is recommended to keep a safe distance of +2 degrees above the crystallization range.

The product is stabilized, the shelf life should be noted.

Storage temperature: 45 °C

A restabilization system should be used if the temperature in the bulk storage-tank reaches the indicated value.

Storage temperature: 60 °C

# Safety Data Sheet

## BUTYL ACRYLATE

Revision date: 2025/10/06  
Version: 15.0

Page: 7/15  
(30041258/SDS\_GEN\_US/EN)

All personnel in a greater area should be evacuated if the temperature in the bulk storage-tank reaches the indicated value.

### 8. Exposure Controls/Personal Protection

#### Components with occupational exposure limits

n-butyl acrylate	ACGIH, US:	TWA value 2 ppm ;
	NIO ID, US:	IDLH 113 ppm ; New/updated values (2016-present). IDLH values based on the 2014 publication Current Intelligence Bulletin (CIB) 66: Derivation of Immediately Dangerous to Life or Health (IDLH).
	NIO ID, US:	LEL 1.2 % ;

#### **Advice on system design:**

Provide local exhaust ventilation to maintain recommended P.E.L.

#### Personal protective equipment

##### **Respiratory protection:**

Wear a NIOSH-certified (or equivalent) organic vapour/particulate respirator as needed. At concentrations < 250 ppm, use a chemical cartridge respirator. At concentrations > 250 ppm, use an air-supplied or self-contained breathing apparatus.

##### **Hand protection:**

Chemical resistant protective gloves

##### **Eye protection:**

Tightly fitting safety goggles (chemical goggles).

##### **Body protection:**

light protective clothing

##### **General safety and hygiene measures:**

Avoid contact with the skin, eyes and clothing. Avoid inhalation of vapour. Wearing of closed work clothing is required additionally to the stated personal protection equipment. Wash soiled clothing immediately.

### 9. Physical and Chemical Properties

Physical state:	liquid
Form:	liquid
Odour:	acrylic-like ester-like
Odour threshold:	not determined
Colour:	colourless
pH value:	not applicable
Melting point:	-64.6 °C The substance / product does not decompose. Literature data.
Freezing point:	No data available.

# Safety Data Sheet

## BUTYL ACRYLATE

Revision date: 2025/10/06

Version: 15.0

Page: 8/15

(30041258/SDS\_GEN\_US/EN)

Boiling point:	147 °C ( 1,013 hPa)	
Boiling range:	No data available.	
Sublimation point:	No applicable information available.	
Flash point:	38 °C	(DIN 51755, closed cup)
Flammability:	Flammable liquid and vapour.	(derived from flash point)
Lower explosion limit:	For liquids not relevant for classification and labelling. The lower explosion point may be 5 - 15 °C below the flash point.	
Upper explosion limit:	For liquids not relevant for classification and labelling.	
Heat of Combustion:	31.83 kJ/g	
Autoignition:	275 °C	(DIN 51794)
SADT:	Not a substance/mixture liable to self-decomposition according to GHS.	
Vapour pressure:	5 hPa ( 22.2 °C)	
Density:	0.899 g/cm3 ( 20 °C) 0.8689 g/cm3 ( 50 °C) 0.8639 g/cm3 ( 55 °C)	(calculated)
Relative density:	0.9 ( 20 °C)	
Relative vapour density:	4.41 ( 20 °C) Heavier than air.	(calculated)
Partitioning coefficient n-octanol/water (log Pow):	2.38 ( 25 °C)	(measured)
Self-ignition temperature:	Based on its structural properties the product is not classified as self-igniting.	
Thermal decomposition:	No decomposition if stored and handled as prescribed/indicated.	
Viscosity, dynamic:	0.88 mPa.s ( 20 °C) 0.66 mPa.s ( 40 °C)	
Viscosity, kinematic:	( 20 °C) not determined	
Solubility in water:	1.7 g/l ( 20 °C)	
Solubility (quantitative):	No applicable information available.	
Solubility (qualitative):	miscible solvent(s): organic solvents,	
Molecular weight:	128.17 g/mol	
Evaporation rate:	No data available.	

### Particle characteristics

Particle size distribution: The substance / product is marketed or used in a non solid or granular form.



# Safety Data Sheet

## BUTYL ACRYLATE

Revision date: 2025/10/06  
Version: 15.0

Page: 9/15  
(30041258/SDS\_GEN\_US/EN)

### 10. Stability and Reactivity

#### Reactivity

No hazardous reactions if stored and handled as prescribed/indicated.

Corrosion to metals:

No corrosive effect on metal.

Oxidizing properties:

Based on its structural properties the product is not classified as oxidizing.

Formation of  
flammable gases:

Remarks:

Forms no flammable gases in the  
presence of water.

#### Chemical stability

The product is stable if stored and handled as prescribed/indicated.

#### Possibility of hazardous reactions

Explosion and fire hazard exists under confined conditions. Ignitable air mixtures can form when the product is heated above the flash point and/or when sprayed or atomized. Formation of explosive gas/air mixtures.

Polymerization coupled with heat formation.

Risk of spontaneous polymerization by oxygen depletion of the liquid phase. Risk of spontaneous polymerization when heated or in the presence of UV radiation. Risk of spontaneous and violent self-polymerization if inhibitor is lost or product is exposed to excessive heat. Polymerization produces gases which may burst closed or confined containers. Reactions may cause ignition.

Risk of spontaneous polymerization in the presence of starters for radical chain reactions (e.g. peroxides). Reacts with nitric acid. Risk of spontaneous polymerization in the presence of oxidizing agents.

Hazardous reactions in presence of mentioned substances to avoid.

The product is stabilized against spontaneous polymerization prior to despatch. The product is stable if stored and handled as prescribed/indicated.

#### Conditions to avoid

Avoid heat. Avoid oxygen content above the product of less than 5 %. Avoid UV-light and other radiation with high energy. Avoid direct sunlight. Avoid prolonged storage. Avoid inhibitor loss. Avoid excessive temperatures. Avoid all sources of ignition: heat, sparks, open flame. Avoid freezing. Avoid moisture.

Do not blanket with nitrogen.

#### Incompatible materials

radical formers, free radical initiators, peroxides, mercaptans, nitro-compounds, perborates, azides, ether, ketones, aldehydes, amines, nitrates, nitrites, oxidizing agents, reducing agents, strong bases, alkaline reactive substances, acid anhydrides, acid chlorides, concentrated mineral acids, metal salts  
polyvinylchloride  
Inert gas

#### Hazardous decomposition products

Decomposition products:

Hazardous decomposition products: No hazardous decomposition products if stored and handled as prescribed/indicated.

# Safety Data Sheet

## BUTYL ACRYLATE

Revision date: 2025/10/06  
Version: 15.0

Page: 10/15  
(30041258/SDS\_GEN\_US/EN)

Thermal decomposition:  
No decomposition if stored and handled as prescribed/indicated.

---

## 11. Toxicological information

### Primary routes of exposure

Routes of entry for solids and liquids are ingestion and inhalation, but may include eye or skin contact. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquefied gases.

### Acute Toxicity/Effects

#### Acute toxicity

Assessment of acute toxicity: Of moderate toxicity after short-term inhalation. Of low toxicity after single ingestion. Of low toxicity after short-term skin contact.

#### Oral

Type of value: LD50  
Species: rat  
Value: 3,150 mg/kg (BASF-Test)

#### Inhalation

Type of value: LC50  
Species: rat  
Value: 10.3 mg/l (OECD Guideline 403)  
Exposure time: 4 h  
The vapour was tested.

#### Dermal

Type of value: LD50  
Species: rabbit  
Value: 2,000 - 3,024 mg/kg (other)

#### Assessment other acute effects

Assessment of STOT single:  
Causes temporary irritation of the respiratory tract.

#### Irritation / corrosion

Assessment of irritating effects: Eye contact causes irritation. Skin contact causes irritation.

#### Skin

Species: rabbit  
Result: Irritant.  
Method: BASF-Test

#### Eye

Species: rabbit  
Result: Irritant.  
Method: other

#### Sensitization

Assessment of sensitization: Sensitization after skin contact possible.

# Safety Data Sheet

## BUTYL ACRYLATE

Revision date: 2025/10/06

Version: 15.0

Page: 11/15

(30041258/SDS\_GEN\_US/EN)

Mouse Local Lymph Node Assay (LLNA)

Species: mouse

Result: skin sensitizing

Method: OECD Guideline 429

### Aspiration Hazard

not applicable

## **Chronic Toxicity/Effects**

### Repeated dose toxicity

Assessment of repeated dose toxicity: After repeated exposure the prominent effect is local irritation. The substance may cause damage to the olfactory epithelium after repeated inhalation.

### Genetic toxicity

Assessment of mutagenicity: The substance was not mutagenic in bacteria. The substance was not mutagenic in mammalian cell culture. The substance was not mutagenic in a test with mammals. The product has not been fully tested. The statements have been derived in parts from products of a similar structure or composition.

### Carcinogenicity

Assessment of carcinogenicity: In long-term animal studies in which the substance was given by inhalation, a carcinogenic effect was not observed. The substance showed no carcinogenic activity in animals after chronic administration to the skin. IARC Group 3 (not classifiable as to human carcinogenicity).

### Reproductive toxicity

Assessment of reproduction toxicity: The results of animal studies gave no indication of a fertility impairing effect.

### Teratogenicity

Assessment of teratogenicity: No indications of a developmental toxic / teratogenic effect were seen in animal studies.

---

## **12. Ecological Information**

### **Toxicity**

#### Aquatic toxicity

Assessment of aquatic toxicity:

Acutely toxic for aquatic organisms. Harmful to aquatic organisms based on long-term (chronic) toxicity study data. The inhibition of the degradation activity of activated sludge is not anticipated when introduced to biological treatment plants in appropriate low concentrations.

#### Toxicity to fish

LC50 (96 h) 2.1 mg/l, Cyprinodon variegatus (OECD Guideline 203, Flow through.)

The statement of the toxic effect relates to the analytically determined concentration.

#### Aquatic invertebrates

EC50 (48 h) 8.2 mg/l, Daphnia magna (OECD Guideline 202, part 1, Flow through.)

The statement of the toxic effect relates to the analytically determined concentration.

#### Aquatic plants

EC50 (96 h) 2.65 mg/l, Selenastrum capricornutum (OECD Guideline 201, static)

The statement of the toxic effect relates to the analytically determined concentration.

# Safety Data Sheet

## BUTYL ACRYLATE

Revision date: 2025/10/06  
Version: 15.0

Page: 12/15  
(30041258/SDS\_GEN\_US/EN)

### Chronic toxicity to fish

No data available.

### Chronic toxicity to aquatic invertebrates

No observed effect concentration (21 d) 0.136 mg/l, Daphnia magna (OECD Guideline 211, semistatic)

The statement of the toxic effect relates to the analytically determined concentration.

### Assessment of terrestrial toxicity

No effects at the highest test concentration.

The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

### Soil living organisms

Toxicity to soil dwelling organisms:

EC50 (28 d) > 1,000 mg/kg, soil dwelling microorganisms (OECD Guideline 217)

The product has not been tested. The statement has been derived from substances/products of a similar structure or composition. The details of the toxic effect relate to the nominal concentration.

### Toxicity to terrestrial plants

No data available.

### Other terrestrial non-mammals

No data available.

## **Microorganisms/Effect on activated sludge**

### Toxicity to microorganisms

other aerobic

activated sludge, industrial/EC0 (3 d): > 150 mg/l

Nominal concentration.

## **Persistence and degradability**

### Assessment biodegradation and elimination (H2O)

Readily biodegradable (according to OECD criteria).

### Elimination information

80 - 90 % TIC of the ThIC (28 d) (ISO 14593) (aerobic, activated sludge, domestic)

### Assessment of stability in water

In contact with water the substance will hydrolyse slowly.

### Information on Stability in Water (Hydrolysis)

$t_{1/2}$  1,100 d (25 °C, pH value 7), (OECD Guideline 111, pH 7)

In contact with water the substance will hydrolyse slowly.

## **Bioaccumulative potential**

### Assessment bioaccumulation potential

Accumulation in organisms is not to be expected.

# Safety Data Sheet

## BUTYL ACRYLATE

Revision date: 2025/10/06  
Version: 15.0

Page: 13/15  
(30041258/SDS\_GEN\_US/EN)

### Bioaccumulation potential

Bioconcentration factor: 17.3 (calculated)

Accumulation in organisms is not to be expected.

### **Mobility in soil**

#### Assessment transport between environmental compartments

The substance will not evaporate into the atmosphere from the water surface.

Adsorption to solid soil phase is not expected.

### **Additional information**

Other ecotoxicological advice:

Do not release untreated into natural waters. Acutely toxic for aquatic organisms.

---

## 13. Disposal considerations

### **Waste disposal of substance:**

Incinerate or dispose of in a RCRA-licensed facility. Do not discharge into drains/surface waters/groundwater.

### **Container disposal:**

WARNING: Empty containers may still contain hazardous residue. Flammable vapors may exist in containers in which residues of this product remain. Empty containers with less than 1 inch of residue may be landfilled at a licensed facility. Recommend crushing, puncturing or other means to prevent unauthorized use of used containers. If containers are not empty, they must be disposed of in a RCRA-licensed facility.

---

## 14. Transport Information

### **Land transport**

USDOT

Hazard class: 3

Packing group: III

ID number: UN 2348

Hazard label: 3

Proper shipping name: BUTYL ACRYLATES, STABILIZED

### **Sea transport**

IMDG

Hazard class: 3

Packing group: III

ID number: UN 2348

Hazard label: 3

Marine pollutant: NO

Proper shipping name: BUTYL ACRYLATES, STABILIZED

### **Air transport**

IATA/ICAO

Hazard class: 3

Packing group: III

ID number: UN 2348

Hazard label: 3

Proper shipping name: BUTYL ACRYLATES, STABILIZED

# Safety Data Sheet

## BUTYL ACRYLATE

Revision date: 2025/10/06  
Version: 15.0

Page: 14/15  
(30041258/SDS\_GEN\_US/EN)

### 15. Regulatory Information

#### Federal Regulations

##### Registration status:

Chemical TSCA, US

All substances are TSCA listed and active.

**EPCRA 311/312 (Hazard categories):** Refer to SDS section 2 for GHS hazard classes applicable for this product.

##### EPCRA 313:

<u>CAS Number</u>	<u>Chemical name</u>
141-32-2	n-butyl acrylate

#### State regulations

<u>State RTK</u>	<u>CAS Number</u>	<u>Chemical name</u>
NJ	141-32-2	n-butyl acrylate
PA	141-32-2	n-butyl acrylate

##### NFPA Hazard codes:

Health: 2 Fire: 2 Reactivity: 2 Special:

##### HMIS III rating

Health: 2 $\alpha$  Flammability: 2 Physical hazard: 2

#### Assessment of the hazard classes according to UN GHS criteria (most recent version):

Aquatic Acute	2	Hazardous to the aquatic environment - acute
Aquatic Chronic	3	Hazardous to the aquatic environment - chronic
Acute Tox.	5 (oral)	Acute toxicity
Acute Tox.	4 (Inhalation - vapour)	Acute toxicity
Acute Tox.	5 (dermal)	Acute toxicity
Skin Irrit.	2	Skin irritation
Eye Irrit.	2A	Eye irritation
STOT SE	3 (irritating to respiratory system)	Specific target organ toxicity — single exposure
Flam. Liq.	3	Flammable liquids
Skin Sens.	1B	Skin sensitization

### 16. Other Information

##### SDS Prepared by:

BASF NA Product Regulations  
SDS Prepared on: 2025/10/06

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in

# Safety Data Sheet

## BUTYL ACRYLATE

Revision date: 2025/10/06

Version: 15.0

Page: 15/15

(30041258/SDS\_GEN\_US/EN)

a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.

Date / Revised: 2025/10/06

Version: 15.0

Date / Previous version: 2024/06/18

Previous version: 14.1

END OF DATA SHEET