

# Safety data sheet

Page: 1/86

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 03.04.2024

Version: 1.0

Date / Previous version: not applicable

Previous version: none

Product: **BUTYL TRIGLYCOL**

(ID no. 30034746/SDS\_GEN\_AT/EN)

Date of print 21.10.2025

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

## BUTYL TRIGLYCOL

Chemical name: Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol

REACH registration number: 01-2119531322-53-0000

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses: Chemical

For the detailed identified uses of the product see appendix of the safety data sheet.

### 1.3. Details of the supplier of the safety data sheet

Company:  
BASF SE  
67056 Ludwigshafen  
GERMANY

Contact address:  
BASF Oesterreich GmbH  
Handelskai 94-96  
1200 Wien  
AUSTRIA

Telephone: +43 (0)664 8396135

E-mail address: product-safety-oesterreich@basf.com

### 1.4. Emergency telephone number

VergiftungsInformationsZentrale Österreich:  
+43 1 406 43 43

International emergency number:  
Telephone: +49 180 2273-112

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 03.04.2024

Version: 1.0

Date / Previous version: not applicable

Previous version: none

Product: **BUTYL TRIGLYCOL**

(ID no. 30034746/SDS\_GEN\_AT/EN)

Date of print 21.10.2025

## SECTION 2: Hazards Identification

### 2.1. Classification of the substance or mixture

According to Regulation (EC) No 1272/2008 [CLP]

Eye Dam./Irrit. 1

H318 Causes serious eye damage.

Specific Concentration Limits According to Regulation (EC) No 1272/2008 [CLP]

Eye Dam./Irrit. 1:  $\geq 30\%$

Eye Dam./Irrit. 2:  $20 - < 30\%$

For the classifications not written out in full in this section the full text can be found in section 16.

### 2.2. Label elements

According to Regulation (EC) No 1272/2008 [CLP]

Pictogram:



Signal Word:

Danger

Hazard Statement:

H318 Causes serious eye damage.

Precautionary Statements (Prevention):

P280 Wear eye and face protection.

Precautionary Statements (Response):

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER or physician.

Labeling of special preparations (GHS):

EUH066: Repeated exposure may cause skin dryness or cracking.

Hazard determining component(s) for labelling: 2-[2-(2-butoxyethoxy)ethoxy]ethanol

### 2.3. Other hazards

According to Regulation (EC) No 1272/2008 [CLP]

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

See section 12 - Results of PBT and vPvB assessment.

Product does not contain a substance above legal limits included in the list established in accordance with Article 59(1) of Regulation (EC) No 1907/2006 for having endocrine disrupting properties or is identified to have endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 03.04.2024

Version: 1.0

Date / Previous version: not applicable

Previous version: none

Product: **BUTYL TRIGLYCOL**

(ID no. 30034746/SDS\_GEN\_AT/EN)

Date of print 21.10.2025

The product does not fulfill the criteria for PBT (Persistent/bioaccumulative/toxic) and vPvB (very persistent/very bioaccumulative).

## SECTION 3: Composition/Information on Ingredients

### 3.1. Substances

#### Chemical nature

Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol

Eye Dam./Irrit. 1  
H318  
EUH066

#### Specific concentration limit:

Eye Dam./Irrit. 1:  $\geq 30\%$   
Eye Dam./Irrit. 2:  $20 - < 30\%$

#### Regulatory relevant ingredients

2-[2-(2-butoxyethoxy)ethoxy]ethanol

Content (W/W):  $\geq 61\% - \leq 80\%$  Eye Dam./Irrit. 1

CAS Number: 143-22-6 H318

EC-Number: 205-592-6

INDEX-Number: 603-183-00-0

#### Specific concentration limit:

Eye Dam./Irrit. 2:  $20 - < 30\%$   
Eye Dam./Irrit. 1:  $\geq 30\%$

3,6,9,12-Tetraoxahexadecan-1-ol

Content (W/W):  $\geq 15\% - \leq 33\%$  Eye Dam./Irrit. 2

CAS Number: 1559-34-8 H319

EC-Number: 216-322-1

For the classifications not written out in full in this section, including the hazard classes and the hazard statements, the full text is listed in section 16.

### 3.2. Mixtures

Not applicable

## SECTION 4: First-Aid Measures

### 4.1. Description of first aid measures

Remove contaminated clothing.

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 03.04.2024

Version: 1.0

Date / Previous version: not applicable

Previous version: none

Product: **BUTYL TRIGLYCOL**

(ID no. 30034746/SDS\_GEN\_AT/EN)

Date of print 21.10.2025

If inhaled:

Keep patient calm, remove to fresh air. Immediately administer a corticosteroid from a controlled/metered dose inhaler.

On skin contact:

Immediately wash thoroughly with plenty of water, apply sterile dressings, consult a skin specialist.

On contact with eyes:

Immediately wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.

On ingestion:

Immediately rinse mouth and then drink 200-300 ml of water, seek medical attention.

#### **4.2. Most important symptoms and effects, both acute and delayed**

Symptoms: Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11., (Further) symptoms and / or effects are not known so far

Hazards: Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11. (Further) symptoms and / or effects are not known so far

#### **4.3. Indication of any immediate medical attention and special treatment needed**

Treatment: Treat according to symptoms (decontamination, vital functions), no known specific antidote.

---

## **SECTION 5: Fire-Fighting Measures**

### **5.1. Extinguishing media**

Suitable extinguishing media:

dry powder, water spray, carbon dioxide, alcohol-resistant foam

Unsuitable extinguishing media for safety reasons:

water jet

Additional information:

Use extinguishing measures to suit surroundings.

### **5.2. Special hazards arising from the substance or mixture**

Advice: The product is combustible. Cool endangered containers with water-spray. See SDS section 7 - Handling and storage.

### **5.3. Advice for fire-fighters**

Special protective equipment:

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 03.04.2024

Version: 1.0

Date / Previous version: not applicable

Previous version: none

Product: **BUTYL TRIGLYCOL**

(ID no. 30034746/SDS\_GEN\_AT/EN)

Date of print 21.10.2025

Wear a self-contained breathing apparatus. Special protective equipment for firefighters

Further information:

Evacuate area of all unnecessary personnel. Fight fire from maximum distance.

Extend fire extinguishing measures to the surroundings. Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

---

## SECTION 6: Accidental Release Measures

High risk of slipping due to leakage/spillage of product.

Shut off or stop source of leak. Shut off or stop released substance/product under safe conditions.

Pack in tightly closed containers for disposal.

### 6.1. Personal precautions, protective equipment and emergency procedures

Handle in accordance with good industrial hygiene and safety practice.

### 6.2. Environmental precautions

Discharge into the environment must be avoided.

### 6.3. Methods and material for containment and cleaning up

Pick up with suitable appliance and dispose of. Spills should be contained, solidified, and placed in suitable containers for disposal. Dispose of absorbed material in accordance with regulations.

### 6.4. Reference to other sections

Information regarding exposure controls/personal protection and disposal considerations can be found in section 8 and 13.

---

## SECTION 7: Handling and Storage

### 7.1. Precautions for safe handling

Prevent contact with air/oxygen (formation of peroxide). Ensure thorough ventilation of stores and work areas.

Protection against fire and explosion:

No special precautions necessary. Substance/product is non-flammable.

### 7.2. Conditions for safe storage, including any incompatibilities

Further information on storage conditions: Containers should be stored tightly sealed in a dry place.

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 03.04.2024

Version: 1.0

Date / Previous version: not applicable

Previous version: none

Product: **BUTYL TRIGLYCOL**

(ID no. 30034746/SDS\_GEN\_AT/EN)

Date of print 21.10.2025

### 7.3. Specific end use(s)

For the relevant identified use(s) listed in Section 1 the advice mentioned in this section 7 is to be observed.

---

## SECTION 8: Exposure Controls/Personal Protection

### 8.1. Control parameters

Components with occupational exposure limits

No substance specific occupational exposure limits known.

#### PNEC

freshwater: 1,5 mg/l

marine water: 0,15 mg/l

intermittent release: 5 mg/l

STP: 200 mg/l

sediment (freshwater): 5,77 mg/kg

sediment (marine water): 0,13 mg/kg

soil: 0,45 mg/kg

oral (secondary poisoning): 111 mg/kg

#### DNEL

worker:

Long-term exposure- systemic effects, dermal: 208 mg/kg

worker:

Long-term exposure- systemic effects, Inhalation: 195 mg/m<sup>3</sup>, 23 ppm

consumer:

Long-term exposure- systemic effects, dermal: 125 mg/kg

consumer:

Long-term exposure- systemic effects, Inhalation: 117 mg/m<sup>3</sup>

consumer:

Long-term exposure- systemic effects, oral: 12,5 mg/kg

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 03.04.2024

Version: 1.0

Date / Previous version: not applicable

Previous version: none

Product: **BUTYL TRIGLYCOL**

(ID no. 30034746/SDS\_GEN\_AT/EN)

Date of print 21.10.2025

## 8.2. Exposure controls

### Personal protective equipment

Respiratory protection:

Wear respiratory protection if ventilation is inadequate. Gas filter for gases/vapours of organic compounds (boiling point >65 °C, e. g. EN 14387 Type A)

Hand protection:

Chemical resistant protective gloves (EN ISO 374-1)

Suitable materials also with prolonged, direct contact (Recommended: Protective index 6, corresponding > 480 minutes of permeation time according to EN ISO 374-1):

nitrile rubber (NBR) - 0.4 mm coating thickness

Manufacturer's directions for use should be observed because of great diversity of types.

Supplementary note: The specifications are based on tests, literature data and information of glove manufacturers or are derived from similar substances by analogy. Due to many conditions (e.g. temperature) it must be considered, that the practical usage of a chemical-protective glove in practice may be much shorter than the permeation time determined through testing.

Eye protection:

Tightly fitting safety goggles (splash goggles) (e.g. EN 166)

Body protection:

Body protection must be chosen depending on activity and possible exposure, e.g. apron, protecting boots, chemical-protection suit (according to EN 14605 in case of splashes or EN ISO 13982 in case of dust).

### General safety and hygiene measures

Handle in accordance with good industrial hygiene and safety practice. Wearing of closed work clothing is required additionally to the stated personal protection equipment.

### Environmental exposure controls

All appropriate measures must be taken to prevent the release of this product to the environment and to limit the dispersion of any release when it occurs. Suitable risk management measures should be in place.

---

## SECTION 9: Physical and Chemical Properties

### 9.1. Information on basic physical and chemical properties

State of matter:	liquid
Form:	liquid
Colour:	colourless
Odour:	almost odourless
Odour threshold:	
	not determined
Melting temperature:	approx. -45 °C

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 03.04.2024

Version: 1.0

Date / Previous version: not applicable

Previous version: none

Product: **BUTYL TRIGLYCOL**

(ID no. 30034746/SDS\_GEN\_AT/EN)

Date of print 21.10.2025

Boiling range:	265 - 350 °C (1.013 mbar)	(DIN 53171)
Flammability:	hardly combustible	(derived from flash point)
Lower explosion limit:	For liquids not relevant for classification and labelling., The lower explosion point may be 5 - 15 °C below the flash point.	
Upper explosion limit:	For liquids not relevant for classification and labelling.	
Flash point:	131 °C The product has not been tested. The statement has been derived from the properties of the individual components.	(ISO 2719, closed cup)
Auto-ignition temperature:	202 °C The product has not been tested. The statement has been derived from the properties of the individual components.	(DIN 51794)
Thermal decomposition:	No decomposition if stored and handled as prescribed/indicated.	
pH value:	(20 °C) neutral	
Viscosity, dynamic:	10,6 mPa.s (20 °C) 9,1 mPa.s (25 °C) The product has not been tested. The statement has been derived from substances/products of a similar structure or composition., Literature data.	
	5,58 mPa.s (40 °C)	
Thixotropy:	not thixotropic	
Solubility in water:	The product has not been tested. The statement has been derived from the properties of the individual components., Literature data.	
	989 g/l (20 °C)	
Solubility (qualitative) solvent(s):	organic solvents soluble	
Partitioning coefficient n-octanol/water (log Kow):	0,51 (25 °C; pH value: 7) The statements are based on the properties of the individual components.	(OECD Guideline 107)



BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 03.04.2024

Version: 1.0

Date / Previous version: not applicable

Previous version: none

Product: **BUTYL TRIGLYCOL**

(ID no. 30034746/SDS\_GEN\_AT/EN)

Date of print 21.10.2025

Vapour pressure:	0,002 mbar (20 °C)	(measured)
	0,02 mbar (50 °C)	(measured)
Relative density:	0,9917 (20 °C)	
Density:	0,9917 g/cm <sup>3</sup> (20 °C)	(ISO 2811-3)
Relative vapour density (air):> 1 (20 °C)		(estimated)
	Heavier than air.	

#### Particle characteristics

Particle size distribution: The substance / product is marketed or used in a non solid or granular form. -

## **9.2. Other information**

### **Information with regard to physical hazard classes**

#### Explosives

Explosion hazard: Based on the chemical structure there is no indication of explosive properties.

#### Oxidizing properties

Fire promoting properties: Based on its structural properties the product is not classified as oxidizing.

#### Pyrophoric properties

Self-ignition temperature: Test type: Spontaneous self-ignition at room-temperature.

Based on its structural properties the product is not classified as self-igniting.

#### Self-heating substances and mixtures

Self heating ability: not applicable, the product is a liquid

#### Substances and mixtures, which emit flammable gases in contact with water

Formation of flammable gases: Forms no flammable gases in the presence of water.

#### Corrosion to metals

Corrosive effects to metal are not anticipated.

### **Other safety characteristics**

Miscibility with water:  
(20 °C)  
miscible

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 03.04.2024

Version: 1.0

Date / Previous version: not applicable

Previous version: none

Product: **BUTYL TRIGLYCOL**

(ID no. 30034746/SDS\_GEN\_AT/EN)

Date of print 21.10.2025

pKA:	The substance does not dissociate.	
Surface tension:	61,2 - 61,5 mN/m (20 °C; 1 g/l)	(OECD Guideline 115)
SAPT-Temperature:	Study scientifically not justified.	
Evaporation rate:	Value can be approximated from Henry's Law Constant or vapor pressure.	

## SECTION 10: Stability and Reactivity

### 10.1. Reactivity

No hazardous reactions if stored and handled as prescribed/indicated.

Corrosion to metals:	Corrosive effects to metal are not anticipated.	
Formation of flammable gases:	Remarks:	Forms no flammable gases in the presence of water.

### 10.2. Chemical stability

The product is stable if stored and handled as prescribed/indicated.

### 10.3. Possibility of hazardous reactions

Reacts with light metals, with evolution of hydrogen. Reacts with strong oxidizing agents.

### 10.4. Conditions to avoid

No special precautions other than good housekeeping of chemicals.

### 10.5. Incompatible materials

Substances to avoid:  
strong oxidizing agents

### 10.6. Hazardous decomposition products

Hazardous decomposition products:  
No hazardous decomposition products if stored and handled as prescribed/indicated.

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 03.04.2024

Version: 1.0

Date / Previous version: not applicable

Previous version: none

Product: **BUTYL TRIGLYCOL**

(ID no. 30034746/SDS\_GEN\_AT/EN)

Date of print 21.10.2025

## SECTION 11: Toxicological Information

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

Assessment of acute toxicity:

In animal studies the substance is virtually nontoxic after a single ingestion. Of low toxicity after short-term skin contact. The inhalation of a highly enriched/saturated vapor-air-mixture represents an unlikely acute hazard.

Experimental/calculated data:

LD50 rat (oral): > 5.170 mg/kg (BASF-Test)

The product has not been tested. The statement has been derived from the properties of the individual components.

LC0 rat (by inhalation): 3,46 mg/l 8 h (IRT)

No mortality was observed. The product has not been tested. The statement has been derived from the properties of the individual components. The vapour was tested.

LD50 rabbit (dermal): 3.540 mg/kg

The product has not been tested. The statement has been derived from the properties of the individual components.

#### Irritation

Assessment of irritating effects:

Not irritating to the skin. May cause severe damage to the eyes.

Experimental/calculated data:

Skin corrosion/irritation

rabbit: non-irritant (BASF-Test)

The product has not been tested. The statement has been derived from the properties of the individual components.

Serious eye damage/irritation

rabbit: irreversible damage (OECD Guideline 405)

The product has not been tested. The statement has been derived from the properties of the individual components.

#### Respiratory/Skin sensitization

Assessment of sensitization:

No sensitizing effect.

Experimental/calculated data:

Guinea pig maximization test guinea pig: Non-sensitizing. (OECD Guideline 406)

The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

#### Germ cell mutagenicity

Assessment of mutagenicity:

The substance was not mutagenic in bacteria. The substance was not mutagenic in mammalian cell culture. The product has not been tested. The statement has been derived from the properties of the individual components.

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 03.04.2024

Version: 1.0

Date / Previous version: not applicable

Previous version: none

Product: **BUTYL TRIGLYCOL**

(ID no. 30034746/SDS\_GEN\_AT/EN)

Date of print 21.10.2025

### Carcinogenicity

Assessment of carcinogenicity:

No data available.

### Reproductive toxicity

Assessment of reproduction toxicity:

Animal studies gave no indication of a fertility impairing effect at doses which were not toxic to the parental animals. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

### Developmental toxicity

Assessment of teratogenicity:

Animal studies gave no indication of a developmental toxic effect at doses that were not toxic to the parental animals. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

### Specific target organ toxicity (single exposure)

Assessment of STOT single:

Based on the available information there is no specific target organ toxicity to be expected after a single exposure.

### Repeated dose toxicity and Specific target organ toxicity (repeated exposure)

Assessment of repeated dose toxicity:

Repeated oral exposure to large quantities may affect certain organs. Repeated dermal uptake of the substance did not cause substance-related effects. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

### Aspiration hazard

No aspiration hazard expected.

### Interactive effects

No data available.

## **11.2. Information on other hazards**

### Endocrine disrupting properties

The substance is not identified to have endocrine disrupting properties according to Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 nor is included in the Candidate List of substances of very high concern according to EU REACH Article 59 for having endocrine disrupting properties.

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 03.04.2024

Version: 1.0

Date / Previous version: not applicable

Previous version: none

Product: **BUTYL TRIGLYCOL**

(ID no. 30034746/SDS\_GEN\_AT/EN)

Date of print 21.10.2025

---

## SECTION 12: Ecological Information

### 12.1. Toxicity

Assessment of aquatic toxicity:

There is a high probability that the product is not acutely harmful to aquatic organisms. The inhibition of the degradation activity of activated sludge is not anticipated when introduced to biological treatment plants in appropriate low concentrations.

Toxicity to fish:

LC50 (96 h) 2.200 - 4.600 mg/l, *Leuciscus idus* (DIN 38412 Part 15, static)

The details of the toxic effect relate to the nominal concentration. The product has not been tested. The statement has been derived from the properties of the individual components.

Aquatic invertebrates:

EC50 (48 h) > 500 mg/l, *Daphnia magna* (Directive 92/69/EEC, C.2, static)

The details of the toxic effect relate to the nominal concentration. The product has not been tested. The statement has been derived from the properties of the individual components.

Aquatic plants:

EC10 (72 h) 612,6 mg/l (growth rate), *Desmodesmus subspicatus* (DIN 38412 Part 8, static)

The details of the toxic effect relate to the nominal concentration. The product has not been tested. The statement has been derived from the properties of the individual components.

Microorganisms/Effect on activated sludge:

EC10 (30 min) > 1.995 mg/l, activated sludge, industrial (OECD Guideline 209, aquatic)

The details of the toxic effect relate to the nominal concentration. The product has not been tested. The statement has been derived from the properties of the individual components.

Chronic toxicity to fish:

Study does not need to be conducted.

Chronic toxicity to aquatic invertebrates:

Study does not need to be conducted.

Assessment of terrestrial toxicity:

No data available.

### 12.2. Persistence and degradability

Assessment biodegradation and elimination (H<sub>2</sub>O):

Readily biodegradable (according to OECD criteria).

Elimination information:

85 % BOD of the ThOD (28 d) (OECD 301D; 92/69/EEC, C.4-E) (aerobic, other bacteria)

The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 03.04.2024

Version: 1.0

Date / Previous version: not applicable

Previous version: none

Product: **BUTYL TRIGLYCOL**

(ID no. 30034746/SDS\_GEN\_AT/EN)

Date of print 21.10.2025

76 % BOD of the ThOD (28 d) (OECD 301D; 92/69/EWG, C.4-E) (aerobic, predominantly domestic sewage, non-adapted)

The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Assessment of stability in water:

According to structural properties, hydrolysis is not expected/probable.

### 12.3. Bioaccumulative potential

Assessment bioaccumulation potential:

Because of the n-octanol/water distribution coefficient (log Pow) accumulation in organisms is not to be expected.

Bioaccumulation potential:

No data available.

### 12.4. Mobility in soil

Assessment transport between environmental compartments:

Volatility: No data available.

Adsorption in soil: Adsorption to solid soil phase is not expected.

### 12.5. Results of PBT and vPvB assessment

According to Annex XIII of Regulation (EC) No.1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH): The product does not fulfill the criteria for PBT (Persistent/bioaccumulative/toxic) and vPvB (very persistent/very bioaccumulative). Self classification

### 12.6. Endocrine disrupting properties

The substance is not identified to have endocrine disrupting properties according to Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 nor is included in the Candidate List of substances of very high concern according to EU REACH Article 59 for having endocrine disrupting properties.

### 12.7. Other adverse effects

The substance is not listed in Regulation (EC) 1005/2009 on substances that deplete the ozone layer.

#### Additional information

Adsorbable organically-bound halogen (AOX):

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 03.04.2024

Version: 1.0

Date / Previous version: not applicable

Previous version: none

Product: **BUTYL TRIGLYCOL**

(ID no. 30034746/SDS\_GEN\_AT/EN)

Date of print 21.10.2025

This product contains no organically-bound halogen.

Other ecotoxicological advice:

Do not discharge product into the environment without control.

---

## SECTION 13: Disposal Considerations

### 13.1. Waste treatment methods

Must be sent to a suitable incineration plant, observing local regulations.

Waste code (regional specific) (Austria):  
55356 glycol ether

Contaminated packaging:

Contaminated packaging should be emptied as far as possible; then it can be passed on for recycling after being thoroughly cleaned.

---

## SECTION 14: Transport Information

### Land transport

ADR

	Not classified as a dangerous good under transport regulations
UN number or ID number:	Not applicable
UN proper shipping name:	Not applicable
Transport hazard class(es):	Not applicable
Packing group:	Not applicable
Environmental hazards:	Not applicable
Special precautions for user	None known

RID

	Not classified as a dangerous good under transport regulations
UN number or ID number:	Not applicable
UN proper shipping name:	Not applicable
Transport hazard class(es):	Not applicable
Packing group:	Not applicable
Environmental hazards:	Not applicable
Special precautions for user	None known

### Inland waterway transport

ADN

Not classified as a dangerous good under transport regulations

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 03.04.2024

Version: 1.0

Date / Previous version: not applicable

Previous version: none

Product: **BUTYL TRIGLYCOL**

(ID no. 30034746/SDS\_GEN\_AT/EN)

Date of print 21.10.2025

UN number or ID number:	Not applicable
UN proper shipping name:	Not applicable
Transport hazard class(es):	Not applicable
Packing group:	Not applicable
Environmental hazards:	Not applicable
Special precautions for user:	None known

#### Transport in inland waterway vessel

	Not classified as a dangerous good under transport regulations
UN number or ID number:	Not applicable
UN proper shipping name:	Not applicable
Transport hazard class(es):	Not applicable
Packing group:	Not applicable
Environmental hazards:	Not applicable

#### Sea transport

##### IMDG

	Not classified as a dangerous good under transport regulations
UN number or ID number:	Not applicable
UN proper shipping name:	Not applicable
Transport hazard class(es):	Not applicable
Packing group:	Not applicable
Environmental hazards:	Not applicable
Special precautions for user:	None known

#### Air transport

##### IATA/ICAO

	Not classified as a dangerous good under transport regulations
UN number or ID number:	Not applicable
UN proper shipping name:	Not applicable
Transport hazard class(es):	Not applicable
Packing group:	Not applicable
Environmental hazards:	Not applicable
Special precautions for user:	None known

#### **14.1. UN number or ID number**

See corresponding entries for "UN number or ID number" for the respective regulations in the tables above.



BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 03.04.2024

Version: 1.0

Date / Previous version: not applicable

Previous version: none

Product: **BUTYL TRIGLYCOL**

(ID no. 30034746/SDS\_GEN\_AT/EN)

Date of print 21.10.2025

#### **14.2. UN proper shipping name**

See corresponding entries for "UN proper shipping name" for the respective regulations in the tables above.

#### **14.3. Transport hazard class(es)**

See corresponding entries for "Transport hazard class(es)" for the respective regulations in the tables above.

#### **14.4. Packing group**

See corresponding entries for "Packing group" for the respective regulations in the tables above.

#### **14.5. Environmental hazards**

See corresponding entries for "Environmental hazards" for the respective regulations in the tables above.

#### **14.6. Special precautions for user**

See corresponding entries for "Special precautions for user" for the respective regulations in the tables above.

#### **14.7. Maritime transport in bulk according to IMO instruments**

Maritime transport in bulk is not intended.

---

### **SECTION 15: Regulatory Information**

#### **15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

##### Prohibitions, Restrictions and Authorizations

Annex XVII of Regulation (EC) No 1907/2006: Number on List: 3

Directive 2012/18/EU - Control of Major Accident Hazards involving dangerous substances (EU):

Listed in above regulation: no

Classification applies for standard conditions of temperature and pressure.

Water hazard class (§6 AwSV para.4 (Legal binding announcement of the substance in the Federal Gazette)): (1) Weakly water polluting. ID-No.: 8520

The regulations of the 'Arbeitnehmer/Innenschutzgesetz' (Austria) and associated ordinances have to be observed.

#### **15.2. Chemical Safety Assessment**

Chemical Safety Assessment performed

---

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 03.04.2024

Version: 1.0

Date / Previous version: not applicable

Previous version: none

Product: **BUTYL TRIGLYCOL**

(ID no. 30034746/SDS\_GEN\_AT/EN)

Date of print 21.10.2025

## SECTION 16: Other Information

Assessment of the hazard classes according to UN GHS criteria (most recent version)

Eye Dam./Irrit. 1

Acute Tox. 5 (dermal)

Full text of the classifications, including the hazard classes and the hazard statements, if mentioned in section 2 or 3:

Eye Dam./Irrit.

Serious eye damage/eye irritation

H318

Causes serious eye damage.

H319

Causes serious eye irritation.

### Abbreviations

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road.  
 ADN = The European Agreement concerning the International Carriage of Dangerous Goods by Inland waterways. ATE = Acute Toxicity Estimates. CAO = Cargo Aircraft Only. CAS = Chemical Abstract Service. CLP = Classification, Labelling and Packaging of substances and mixtures. DIN = German national organization for standardization. DNEL = Derived No Effect Level. EC50 = Effective concentration median for 50% of the population. EC = European Community. EN = European Standards. IARC = International Agency for Research on Cancer. IATA = International Air Transport Association. IBC-Code = Intermediate Bulk Container code. IMDG = International Maritime Dangerous Goods Code. ISO = International Organization for Standardization. STEL = Short-Term Exposure Limit. LC50 = Lethal concentration median for 50% of the population. LD50 = Lethal dose median for 50% of the population. TLV = Threshold Limit Value. MARPOL = The International Convention for the Prevention of Pollution from Ships. NEN = Dutch Norm. NOEC = No Observed Effect Concentration. OEL = Occupational Exposure Limit. OECD = Organization for Economic Cooperation and Development. PBT = Persistent, Bioaccumulative and Toxic. PNEC = Predicted No Effect Level. PPM = Parts per million. RID = The European Agreement concerning the International Carriage of Dangerous Goods by Rail. TWA = Time Weight Average. UN-number = UN number at transport. vPvB = very Persistent and very Bioaccumulative.

The data contained in this safety data sheet are based on our current knowledge and experience and describe the product only with regard to safety requirements. This safety data sheet is neither a Certificate of Analysis (CoA) nor technical data sheet and shall not be mistaken for a specification agreement. Identified uses in this safety data sheet do neither represent an agreement on the corresponding contractual quality of the substance/mixture nor a contractually designated use. It is the responsibility of the recipient of the product to ensure any proprietary rights and existing laws and legislation are observed.

Vertical lines in the left hand margin indicate an amendment from the previous version.

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 03.04.2024

Version: 1.0

Date / Previous version: not applicable

Previous version: none

Product: **BUTYL TRIGLYCOL**

(ID no. 30034746/SDS\_GEN\_AT/EN)

Date of print 21.10.2025

## Annex: Exposure Scenarios

### Index

1. Manufacture of substance, (use in industrial settings)  
SU8; ERC1; PROC1, PROC2, PROC8a, PROC8b, PROC9, PROC15
2. Use in/as Formulation, (use in industrial settings)  
SU10; ERC2; PROC3, PROC5, PROC8a, PROC8b, PROC9, PROC14, PROC15, PROC19
3. Use in Hydraulic fluids, (use in industrial settings)  
ERC7; PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC9, PROC17
4. Use in Coatings, (use in industrial settings)  
ERC4, ERC5; PROC1, PROC2, PROC3, PROC4, PROC6, PROC7, PROC8a, PROC8b, PROC9, PROC10, PROC13, PROC15
5. Use as processing aid, (use in industrial settings)  
ERC4; PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC9, PROC15
6. Use in Hydraulic fluids, (use in professional settings)  
ERC9a, ERC9b; PROC1, PROC2, PROC3, PROC4, PROC9, PROC17, PROC19, PROC20
7. Use in Coatings, (use in professional settings)  
ERC8a, ERC8b, ERC8d, ERC8f; PROC1, PROC2, PROC3, PROC4, PROC6, PROC9, PROC10, PROC11, PROC13, PROC15, PROC19
8. Use in Cleaning Agents, (use in professional settings)  
ERC8a, ERC8d; PROC2, PROC3, PROC4, PROC8b, PROC9, PROC10, PROC11, PROC13
9. Use in Hydraulic fluids, (consumer use)  
ERC9a, ERC9b; PC17
10. Use in Coatings, (consumer use)  
ERC8a, ERC8b, ERC8d, ERC8f; PC1, PC9a, PC9b, PC9c, PC15, PC18, PC23, PC26, PC31, PC39
11. Use in Cleaning Agents, (consumer use)  
ERC8a, ERC8d; PC35

\*\*\*\*\*

### 1. Short title of exposure scenario

Manufacture of substance, (use in industrial settings)  
SU8; ERC1; PROC1, PROC2, PROC8a, PROC8b, PROC9, PROC15

### Control of exposure and risk management measures

Contributing exposure scenario
--------------------------------

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 03.04.2024

Version: 1.0

Date / Previous version: not applicable

Previous version: none

Product: **BUTYL TRIGLYCOL**

(ID no. 30034746/SDS\_GEN\_AT/EN)

Date of print 21.10.2025

<b>Use descriptors covered</b>	ERC1: Manufacture of the substance As no environmental hazard was identified no environmental-related exposure assessment and risk characterization was performed.
<b>Operational conditions</b>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC1: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions. Use domain: industrial
<b>Operational conditions</b>	
Concentration of the substance	Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	0,014 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
<b>Risk Management Measures</b>	
Use suitable eye protection.	
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	0,0343 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,000686
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	0,095 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,000487
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC2: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions Use domain: industrial
<b>Operational conditions</b>	
Concentration of the substance	Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 03.04.2024

Version: 1.0

Date / Previous version: not applicable

Previous version: none

Product: **BUTYL TRIGLYCOL**

(ID no. 30034746/SDS\_GEN\_AT/EN)

Date of print 21.10.2025

	Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	0,014 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
<b>Risk Management Measures</b>	
Use suitable eye protection.	
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	1,3714 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,027429
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	9,5 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,048718
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC8a: Transfer of substance or mixture (charging and discharging) at non-dedicated facilities Use domain: industrial
<b>Operational conditions</b>	
Concentration of the substance	Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	0,014 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
<b>Risk Management Measures</b>	
Use suitable eye protection.	
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	13,7143 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,274286

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 03.04.2024

Version: 1.0

Date / Previous version: not applicable

Previous version: none

Product: **BUTYL TRIGLYCOL**

(ID no. 30034746/SDS\_GEN\_AT/EN)

Date of print 21.10.2025

Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	95 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,487179
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC8b: Transfer of substance or mixture (charging and discharging) at dedicated facilities Use domain: industrial
<b>Operational conditions</b>	
Concentration of the substance	Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	0,014 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
<b>Risk Management Measures</b>	
Use suitable eye protection.	
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	13,7143 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,274286
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	47,5 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,24359
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing). Use domain: industrial
<b>Operational conditions</b>	
Concentration of the substance	Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol Content: >= 0 % - <= 100 %

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 03.04.2024

Version: 1.0

Date / Previous version: not applicable

Previous version: none

Product: **BUTYL TRIGLYCOL**

(ID no. 30034746/SDS\_GEN\_AT/EN)

Date of print 21.10.2025

Physical state	liquid
Vapour pressure of the substance during use	0,014 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
<b>Risk Management Measures</b>	
Use suitable eye protection.	
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	6,8571 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,137143
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	47,5 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,24359
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC15: Use a laboratory reagent. Use domain: industrial
<b>Operational conditions</b>	
Concentration of the substance	Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	0,014 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
<b>Risk Management Measures</b>	
Use suitable eye protection.	
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	0,3429 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,006857
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	47,5 mg/m <sup>3</sup>

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 03.04.2024

Version: 1.0

Date / Previous version: not applicable

Previous version: none

Product: **BUTYL TRIGLYCOL**

(ID no. 30034746/SDS\_GEN\_AT/EN)

Date of print 21.10.2025

Risk Characterization Ratio (RCR)	0,24359
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

\*\*\*\*\*

## 2. Short title of exposure scenario

Use in/as Formulation, (use in industrial settings)

SU10; ERC2; PROC3, PROC5, PROC8a, PROC8b, PROC9, PROC14, PROC15, PROC19

## Control of exposure and risk management measures

Contributing exposure scenario	
Use descriptors covered	ERC2: Formulation into mixture As no environmental hazard was identified no environmental-related exposure assessment and risk characterization was performed.
<b>Operational conditions</b>	

Contributing exposure scenario	
Use descriptors covered	PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition Use domain: industrial
<b>Operational conditions</b>	
Concentration of the substance	Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	0,014 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
<b>Risk Management Measures</b>	
Use suitable eye protection.	
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	0,6857 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,013714
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker



BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 03.04.2024

Version: 1.0

Date / Previous version: not applicable

Previous version: none

Product: **BUTYL TRIGLYCOL**

(ID no. 30034746/SDS\_GEN\_AT/EN)

Date of print 21.10.2025

	Worker - inhalation, long-term - systemic
Exposure estimate	28,5 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,146154
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC5: Mixing or blending in batch processes Use domain: industrial
<b>Operational conditions</b>	
Concentration of the substance	Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	0,014 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
<b>Risk Management Measures</b>	
Use suitable eye protection.	
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	13,7143 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,274286
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	47,5 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,24359
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC8a: Transfer of substance or mixture (charging and discharging) at non-dedicated facilities Use domain: industrial
<b>Operational conditions</b>	
Concentration of the substance	Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance	0,014 Pa

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 03.04.2024

Version: 1.0

Date / Previous version: not applicable

Previous version: none

Product: **BUTYL TRIGLYCOL**

(ID no. 30034746/SDS\_GEN\_AT/EN)

Date of print 21.10.2025

during use	
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
<b>Risk Management Measures</b>	
Use suitable eye protection.	
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	13,7143 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,274286
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	95 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,487179
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC8b: Transfer of substance or mixture (charging and discharging) at dedicated facilities Use domain: industrial
<b>Operational conditions</b>	
Concentration of the substance	Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	0,014 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
<b>Risk Management Measures</b>	
Use suitable eye protection.	
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	13,7143 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,274286
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	47,5 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,24359

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 03.04.2024

Version: 1.0

Date / Previous version: not applicable

Previous version: none

Product: **BUTYL TRIGLYCOL**

(ID no. 30034746/SDS\_GEN\_AT/EN)

Date of print 21.10.2025

### **Guidance to Downstream Users**

For scaling see: <http://www.ecetoc.org/tra>

### **Contributing exposure scenario**

<b>Use descriptors covered</b>	PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing). Use domain: industrial
<b>Operational conditions</b>	
Concentration of the substance	Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	0,014 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor

### **Risk Management Measures**

Use suitable eye protection.

### **Exposure estimate and reference to its source**

Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	6,8571 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,137143
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	47,5 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,24359

### **Guidance to Downstream Users**

For scaling see: <http://www.ecetoc.org/tra>

### **Contributing exposure scenario**

<b>Use descriptors covered</b>	PROC14: Tableting, compression, extrusion, pelletisation, granulation Use domain: industrial
<b>Operational conditions</b>	
Concentration of the substance	Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	0,014 Pa
Process temperature	20 °C

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 03.04.2024

Version: 1.0

Date / Previous version: not applicable

Previous version: none

Product: **BUTYL TRIGLYCOL**

(ID no. 30034746/SDS\_GEN\_AT/EN)

Date of print 21.10.2025

Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
<b>Risk Management Measures</b>	
Use suitable eye protection.	
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	3,4286 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,068571
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	47,5 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,24359
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC15: Use a laboratory reagent. Use domain: industrial
<b>Operational conditions</b>	
Concentration of the substance	Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	0,014 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
<b>Risk Management Measures</b>	
Use suitable eye protection.	
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	0,3429 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,006857
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	47,5 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,24359
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 03.04.2024

Version: 1.0

Date / Previous version: not applicable

Previous version: none

Product: **BUTYL TRIGLYCOL**

(ID no. 30034746/SDS\_GEN\_AT/EN)

Date of print 21.10.2025

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC19: Manual activities involving hand contact Use domain: industrial
<b>Operational conditions</b>	
Concentration of the substance	Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	0,014 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
<b>Risk Management Measures</b>	
Wear chemically resistant gloves in combination with 'basic' employee training.	Effectiveness: 90 %
Use suitable eye protection.	
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	14,1429 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,282857
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	95 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,487179
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

\*\*\*\*\*

### 3. Short title of exposure scenario

Use in Hydraulic fluids, (use in industrial settings)

ERC7; PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC9, PROC17

### Control of exposure and risk management measures

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	ERC7: Use of functional fluid at industrial site As no environmental hazard was identified no environmental-related exposure assessment and risk characterization was performed.

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 03.04.2024

Version: 1.0

Date / Previous version: not applicable

Previous version: none

Product: **BUTYL TRIGLYCOL**

(ID no. 30034746/SDS\_GEN\_AT/EN)

Date of print 21.10.2025

### **Operational conditions**

#### **Contributing exposure scenario**

<b>Use descriptors covered</b>	PROC1: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions. Use domain: industrial
--------------------------------	--

#### **Operational conditions**

Concentration of the substance	Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	0,014 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor

#### **Risk Management Measures**

Use suitable eye protection.

#### **Exposure estimate and reference to its source**

Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	0,0343 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,000686
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	0,095 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,000487

#### **Guidance to Downstream Users**

For scaling see: <http://www.ecetoc.org/tra>

#### **Contributing exposure scenario**

<b>Use descriptors covered</b>	PROC2: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions Use domain: industrial
--------------------------------	---

#### **Operational conditions**

Concentration of the substance	Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	0,014 Pa

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 03.04.2024

Version: 1.0

Date / Previous version: not applicable

Previous version: none

Product: **BUTYL TRIGLYCOL**

(ID no. 30034746/SDS\_GEN\_AT/EN)

Date of print 21.10.2025

Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
<b>Risk Management Measures</b>	
Use suitable eye protection.	
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	1,3714 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,027429
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	9,5 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,048718
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition Use domain: industrial
<b>Operational conditions</b>	
Concentration of the substance	Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	0,014 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
<b>Risk Management Measures</b>	
Use suitable eye protection.	
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	0,6857 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,013714
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	28,5 mg/m <sup>3</sup>

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 03.04.2024

Version: 1.0

Date / Previous version: not applicable

Previous version: none

Product: **BUTYL TRIGLYCOL**

(ID no. 30034746/SDS\_GEN\_AT/EN)

Date of print 21.10.2025

Risk Characterization Ratio (RCR)	0,146154
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC4: Chemical production where opportunity for exposure arises Use domain: industrial
<b>Operational conditions</b>	
Concentration of the substance	Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	0,014 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
<b>Risk Management Measures</b>	
Use suitable eye protection.	
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	6,8571 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,137143
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	47,5 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,24359
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC8a: Transfer of substance or mixture (charging and discharging) at non-dedicated facilities Use domain: industrial
<b>Operational conditions</b>	
Concentration of the substance	Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	0,014 Pa



BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 03.04.2024

Version: 1.0

Date / Previous version: not applicable

Previous version: none

Product: **BUTYL TRIGLYCOL**

(ID no. 30034746/SDS\_GEN\_AT/EN)

Date of print 21.10.2025

Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
<b>Risk Management Measures</b>	
Use suitable eye protection.	
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	13,7143 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,274286
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	95 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,487179
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC8b: Transfer of substance or mixture (charging and discharging) at dedicated facilities Use domain: industrial
<b>Operational conditions</b>	
Concentration of the substance	Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	0,014 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
<b>Risk Management Measures</b>	
Use suitable eye protection.	
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	13,7143 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,274286
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	47,5 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,24359
<b>Guidance to Downstream Users</b>	

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 03.04.2024

Version: 1.0

Date / Previous version: not applicable

Previous version: none

Product: **BUTYL TRIGLYCOL**

(ID no. 30034746/SDS\_GEN\_AT/EN)

Date of print 21.10.2025

For scaling see: <http://www.ecetoc.org/tra>

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing). Use domain: industrial
<b>Operational conditions</b>	
Concentration of the substance	Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	0,014 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
<b>Risk Management Measures</b>	
Use suitable eye protection.	
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	6,8571 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,137143
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	47,5 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,24359
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC17: Lubrication at high energy conditions in metal working operations Use domain: industrial
<b>Operational conditions</b>	
Concentration of the substance	Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	0,014 Pa
Process temperature	20 °C

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 03.04.2024

Version: 1.0

Date / Previous version: not applicable

Previous version: none

Product: **BUTYL TRIGLYCOL**

(ID no. 30034746/SDS\_GEN\_AT/EN)

Date of print 21.10.2025

Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
<b>Risk Management Measures</b>	
Provide a good standard of general or controlled ventilation (5 to 10 air changes per hour)	Effectiveness: 70 %
Use suitable eye protection.	
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	27,4286 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,548571
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	57 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,292308
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

\*\*\*\*\*

#### 4. Short title of exposure scenario

Use in Coatings, (use in industrial settings)

ERC4, ERC5; PROC1, PROC2, PROC3, PROC4, PROC6, PROC7, PROC8a, PROC8b, PROC9, PROC10, PROC13, PROC15

#### Control of exposure and risk management measures

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	ERC4: Use of non-reactive processing aid at industrial site (no inclusion into or onto article) As no environmental hazard was identified no environmental-related exposure assessment and risk characterization was performed.
<b>Operational conditions</b>	
<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	ERC5: Use at industrial site leading to inclusion into/onto article As no environmental hazard was identified no environmental-related exposure assessment and risk characterization was performed.
<b>Operational conditions</b>	
<b>Contributing exposure scenario</b>	

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 03.04.2024

Version: 1.0

Date / Previous version: not applicable

Previous version: none

Product: **BUTYL TRIGLYCOL**

(ID no. 30034746/SDS\_GEN\_AT/EN)

Date of print 21.10.2025

<b>Use descriptors covered</b>	PROC1: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions. Use domain: industrial
<b>Operational conditions</b>	
Concentration of the substance	Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	0,014 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
<b>Risk Management Measures</b>	
Use suitable eye protection.	
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	0,0343 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,000686
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	0,095 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,000487
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC2: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions Use domain: industrial
<b>Operational conditions</b>	
Concentration of the substance	Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	0,014 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 03.04.2024

Version: 1.0

Date / Previous version: not applicable

Previous version: none

Product: **BUTYL TRIGLYCOL**

(ID no. 30034746/SDS\_GEN\_AT/EN)

Date of print 21.10.2025

Indoor/Outdoor	Indoor
<b>Risk Management Measures</b>	
Use suitable eye protection.	
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	1,3714 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,027429
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	9,5 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,048718
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition Use domain: industrial
<b>Operational conditions</b>	
Concentration of the substance	Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	0,014 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
<b>Risk Management Measures</b>	
Use suitable eye protection.	
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	0,6857 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,013714
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	28,5 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,146154
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 03.04.2024

Version: 1.0

Date / Previous version: not applicable

Previous version: none

Product: **BUTYL TRIGLYCOL**

(ID no. 30034746/SDS\_GEN\_AT/EN)

Date of print 21.10.2025

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC4: Chemical production where opportunity for exposure arises Use domain: industrial
<b>Operational conditions</b>	
Concentration of the substance	Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	0,014 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
<b>Risk Management Measures</b>	
Use suitable eye protection.	
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	6,8571 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,137143
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	47,5 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,24359
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC6: Calendering operations Use domain: industrial
<b>Operational conditions</b>	
Concentration of the substance	Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	0,014 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 03.04.2024

Version: 1.0

Date / Previous version: not applicable

Previous version: none

Product: **BUTYL TRIGLYCOL**

(ID no. 30034746/SDS\_GEN\_AT/EN)

Date of print 21.10.2025

Indoor/Outdoor	Indoor
<b>Risk Management Measures</b>	
Use suitable eye protection.	
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	27,4286 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,548571
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	47,5 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,24359
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC7: Industrial spraying Use domain: industrial
<b>Operational conditions</b>	
Concentration of the substance	Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	0,014 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Room size	100 m3
Application rate	10 l/min
<b>Risk Management Measures</b>	
Wear chemically resistant gloves in combination with 'basic' employee training.	Effectiveness: 90 %
Ensure that the task is being carried out outside the breathing zone of a worker (distance head-product greater than 1m). Ensure that the task is not carried out overhead. Ensure that the direction of airflow is clearly away from the worker. Regular inspection and maintenance of equipment and machines. Clean equipment and the work area every day.	
Use suitable eye protection.	

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 03.04.2024

Version: 1.0

Date / Previous version: not applicable

Previous version: none

Product: **BUTYL TRIGLYCOL**

(ID no. 30034746/SDS\_GEN\_AT/EN)

Date of print 21.10.2025

<b>Exposure estimate and reference to its source</b>	
Assessment method	RISKOFDERM v2.1
	Worker - dermal, long-term - systemic
Exposure estimate	22,02 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,4404
Assessment method	Stoffenmanager v5.6
	Worker - inhalation, long-term - systemic
Exposure estimate	14,81 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,075949
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="https://www.stoffenmanager.nl/default.aspx">https://www.stoffenmanager.nl/default.aspx</a> For scaling see: <a href="http://www.tno.nl">http://www.tno.nl</a> and search for "riskofderm".	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC8a: Transfer of substance or mixture (charging and discharging) at non-dedicated facilities Use domain: industrial
<b>Operational conditions</b>	
Concentration of the substance	Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	0,014 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
<b>Risk Management Measures</b>	
Use suitable eye protection.	
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	13,7143 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,274286
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	95 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,487179
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC8b: Transfer of substance or mixture (charging and discharging) at dedicated facilities Use domain: industrial



BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 03.04.2024

Version: 1.0

Date / Previous version: not applicable

Previous version: none

Product: **BUTYL TRIGLYCOL**

(ID no. 30034746/SDS\_GEN\_AT/EN)

Date of print 21.10.2025

<b>Operational conditions</b>	
Concentration of the substance	Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	0,014 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
<b>Risk Management Measures</b>	
Use suitable eye protection.	
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	13,7143 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,274286
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	47,5 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,24359
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
Use descriptors covered	PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing). Use domain: industrial
<b>Operational conditions</b>	
Concentration of the substance	Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	0,014 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
<b>Risk Management Measures</b>	
Use suitable eye protection.	
<b>Exposure estimate and reference to its source</b>	

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 03.04.2024

Version: 1.0

Date / Previous version: not applicable

Previous version: none

Product: **BUTYL TRIGLYCOL**

(ID no. 30034746/SDS\_GEN\_AT/EN)

Date of print 21.10.2025

Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	6,8571 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,137143
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	47,5 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,24359
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC10: Roller application or brushing Use domain: industrial
<b>Operational conditions</b>	
Concentration of the substance	Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	0,014 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
<b>Risk Management Measures</b>	
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %
Use suitable eye protection.	
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	27,4286 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,548571
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	66,5 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,341026
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC13: Treatment of articles by dipping and pouring. Use domain: industrial

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 03.04.2024

Version: 1.0

Date / Previous version: not applicable

Previous version: none

Product: **BUTYL TRIGLYCOL**

(ID no. 30034746/SDS\_GEN\_AT/EN)

Date of print 21.10.2025

<b>Operational conditions</b>	
Concentration of the substance	Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	0,014 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
<b>Risk Management Measures</b>	
Use suitable eye protection.	
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	13,7143 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,274286
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	95 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,487179
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC15: Use a laboratory reagent. Use domain: industrial
<b>Operational conditions</b>	
Concentration of the substance	Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	0,014 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
<b>Risk Management Measures</b>	
Use suitable eye protection.	
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 03.04.2024

Version: 1.0

Date / Previous version: not applicable

Previous version: none

Product: **BUTYL TRIGLYCOL**

(ID no. 30034746/SDS\_GEN\_AT/EN)

Date of print 21.10.2025

Exposure estimate	0,3429 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,006857
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	47,5 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,24359
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

\*\*\*\*\*

## 5. Short title of exposure scenario

Use as processing aid, (use in industrial settings)

ERC4; PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC9, PROC15

## Control of exposure and risk management measures

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	ERC4: Use of non-reactive processing aid at industrial site (no inclusion into or onto article) As no environmental hazard was identified no environmental-related exposure assessment and risk characterization was performed.
<b>Operational conditions</b>	
<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC1: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions. Use domain: industrial
<b>Operational conditions</b>	
Concentration of the substance	Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	0,014 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
<b>Risk Management Measures</b>	
Use suitable eye protection.	
<b>Exposure estimate and reference to its source</b>	

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 03.04.2024

Version: 1.0

Date / Previous version: not applicable

Previous version: none

Product: **BUTYL TRIGLYCOL**

(ID no. 30034746/SDS\_GEN\_AT/EN)

Date of print 21.10.2025

Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	0,0343 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,000686
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	0,095 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,000487
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC2: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions Use domain: industrial
<b>Operational conditions</b>	
Concentration of the substance	Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	0,014 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
<b>Risk Management Measures</b>	
Use suitable eye protection.	
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	1,3714 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,027429
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	9,5 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,048718
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 03.04.2024

Version: 1.0

Date / Previous version: not applicable

Previous version: none

Product: **BUTYL TRIGLYCOL**

(ID no. 30034746/SDS\_GEN\_AT/EN)

Date of print 21.10.2025

	Use domain: industrial
<b>Operational conditions</b>	
Concentration of the substance	Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	0,014 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
<b>Risk Management Measures</b>	
Use suitable eye protection.	
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	0,6857 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,013714
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	28,5 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,146154
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
Use descriptors covered	PROC4: Chemical production where opportunity for exposure arises Use domain: industrial
<b>Operational conditions</b>	
Concentration of the substance	Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	0,014 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
<b>Risk Management Measures</b>	
Use suitable eye protection.	

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 03.04.2024

Version: 1.0

Date / Previous version: not applicable

Previous version: none

Product: **BUTYL TRIGLYCOL**

(ID no. 30034746/SDS\_GEN\_AT/EN)

Date of print 21.10.2025

<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	6,8571 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,137143
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	47,5 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,24359
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC8a: Transfer of substance or mixture (charging and discharging) at non-dedicated facilities Use domain: industrial
<b>Operational conditions</b>	
Concentration of the substance	Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	0,014 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
<b>Risk Management Measures</b>	
Use suitable eye protection.	
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	13,7143 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,274286
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	95 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,487179
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC8b: Transfer of substance or mixture (charging and discharging) at dedicated facilities Use domain: industrial

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 03.04.2024

Version: 1.0

Date / Previous version: not applicable

Previous version: none

Product: **BUTYL TRIGLYCOL**

(ID no. 30034746/SDS\_GEN\_AT/EN)

Date of print 21.10.2025

<b>Operational conditions</b>	
Concentration of the substance	Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	0,014 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
<b>Risk Management Measures</b>	
Use suitable eye protection.	
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	13,7143 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,274286
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	47,5 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,24359
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing). Use domain: industrial
<b>Operational conditions</b>	
Concentration of the substance	Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	0,014 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
<b>Risk Management Measures</b>	
Use suitable eye protection.	
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker



BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 03.04.2024

Version: 1.0

Date / Previous version: not applicable

Previous version: none

Product: **BUTYL TRIGLYCOL**

(ID no. 30034746/SDS\_GEN\_AT/EN)

Date of print 21.10.2025

	Worker - dermal, long-term - systemic
Exposure estimate	6,8571 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,137143
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	47,5 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,24359
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC15: Use a laboratory reagent. Use domain: industrial
<b>Operational conditions</b>	
Concentration of the substance	Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	0,014 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
<b>Risk Management Measures</b>	
Use suitable eye protection.	
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	0,3429 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,006857
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	47,5 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,24359
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

\*\*\*\*\*

## 6. Short title of exposure scenario

Use in Hydraulic fluids, (use in professional settings)

ERC9a, ERC9b; PROC1, PROC2, PROC3, PROC4, PROC9, PROC17, PROC19, PROC20

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 03.04.2024

Version: 1.0

Date / Previous version: not applicable

Previous version: none

Product: **BUTYL TRIGLYCOL**

(ID no. 30034746/SDS\_GEN\_AT/EN)

Date of print 21.10.2025

## Control of exposure and risk management measures

Contributing exposure scenario	
Use descriptors covered	ERC9a: Widespread use of functional fluid (indoor) As no environmental hazard was identified no environmental-related exposure assessment and risk characterization was performed.
<b>Operational conditions</b>	
Contributing exposure scenario	
Use descriptors covered	ERC9b: Widespread use of functional fluid (outdoor) As no environmental hazard was identified no environmental-related exposure assessment and risk characterization was performed.
<b>Operational conditions</b>	
Contributing exposure scenario	
Use descriptors covered	PROC1: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions. Use domain: professional
<b>Operational conditions</b>	
Concentration of the substance	Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	0,014 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
<b>Risk Management Measures</b>	
Use suitable eye protection.	
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	0,0343 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,000686
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	0,095 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,000487
<b>Guidance to Downstream Users</b>	

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 03.04.2024

Version: 1.0

Date / Previous version: not applicable

Previous version: none

Product: **BUTYL TRIGLYCOL**

(ID no. 30034746/SDS\_GEN\_AT/EN)

Date of print 21.10.2025

For scaling see: <http://www.ecetoc.org/tra>

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC2: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions Use domain: professional
<b>Operational conditions</b>	
Concentration of the substance	Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	0,014 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
<b>Risk Management Measures</b>	
Use suitable eye protection.	
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	1,3714 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,027429
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	47,5 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,24359
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition Use domain: professional
<b>Operational conditions</b>	
Concentration of the substance	Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance	0,014 Pa

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 03.04.2024

Version: 1.0

Date / Previous version: not applicable

Previous version: none

Product: **BUTYL TRIGLYCOL**

(ID no. 30034746/SDS\_GEN\_AT/EN)

Date of print 21.10.2025

during use	
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
<b>Risk Management Measures</b>	
Use suitable eye protection.	
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	0,6857 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,013714
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	28,5 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,146154
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC4: Chemical production where opportunity for exposure arises Use domain: professional
<b>Operational conditions</b>	
Concentration of the substance	Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	0,014 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
<b>Risk Management Measures</b>	
Use suitable eye protection.	
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	6,8571 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,137143
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	95 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,487179

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 03.04.2024

Version: 1.0

Date / Previous version: not applicable

Previous version: none

Product: **BUTYL TRIGLYCOL**

(ID no. 30034746/SDS\_GEN\_AT/EN)

Date of print 21.10.2025

### **Guidance to Downstream Users**

For scaling see: <http://www.ecetoc.org/tra>

### **Contributing exposure scenario**

<b>Use descriptors covered</b>	PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing). Use domain: professional
<b>Operational conditions</b>	
Concentration of the substance	Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	0,014 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor

### **Risk Management Measures**

Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)

Effectiveness: 30 %

Use suitable eye protection.

### **Exposure estimate and reference to its source**

Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	6,8571 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,137143
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	66,5 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,341026

### **Guidance to Downstream Users**

For scaling see: <http://www.ecetoc.org/tra>

### **Contributing exposure scenario**

<b>Use descriptors covered</b>	PROC17: Lubrication at high energy conditions in metal working operations Use domain: professional
<b>Operational conditions</b>	
Concentration of the substance	Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol Content: >= 0 % - <= 100 %
Physical state	liquid

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 03.04.2024

Version: 1.0

Date / Previous version: not applicable

Previous version: none

Product: **BUTYL TRIGLYCOL**

(ID no. 30034746/SDS\_GEN\_AT/EN)

Date of print 21.10.2025

Vapour pressure of the substance during use	0,014 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
<b>Risk Management Measures</b>	
Provide a good standard of general or controlled ventilation (5 to 10 air changes per hour)	Effectiveness: 70 %
Use suitable chemically resistant gloves.	Effectiveness: 80 %
Use suitable eye protection.	
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	5,4857 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,109714
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	142,5 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,730769
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC19: Manual activities involving hand contact Use domain: professional
<b>Operational conditions</b>	
Concentration of the substance	Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	0,014 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
<b>Risk Management Measures</b>	
Provide a good standard of general or controlled ventilation (5 to 10 air changes per hour)	Effectiveness: 70 %
Wear chemically resistant gloves in combination with 'basic' employee	Effectiveness: 90 %

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 03.04.2024

Version: 1.0

Date / Previous version: not applicable

Previous version: none

Product: **BUTYL TRIGLYCOL**

(ID no. 30034746/SDS\_GEN\_AT/EN)

Date of print 21.10.2025

training.	
Use suitable eye protection.	
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	14,1429 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,282857
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	71,25 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,365385
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC20: Use of functional fluids in small devices Use domain: professional
<b>Operational conditions</b>	
Concentration of the substance	Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	0,014 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
<b>Risk Management Measures</b>	
Use suitable eye protection.	
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	1,7143 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,034286
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	47,5 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,24359
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

\*\*\*\*\*

## 7. Short title of exposure scenario

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 03.04.2024

Version: 1.0

Date / Previous version: not applicable

Previous version: none

Product: **BUTYL TRIGLYCOL**

(ID no. 30034746/SDS\_GEN\_AT/EN)

Date of print 21.10.2025

Use in Coatings, (use in professional settings)

ERC8a, ERC8b, ERC8d, ERC8f; PROC1, PROC2, PROC3, PROC4, PROC6, PROC9, PROC10, PROC11, PROC13, PROC15, PROC19

## Control of exposure and risk management measures

Contributing exposure scenario	
Use descriptors covered	ERC8a: Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor) As no environmental hazard was identified no environmental-related exposure assessment and risk characterization was performed.
Operational conditions	
Contributing exposure scenario	
Use descriptors covered	ERC8b: Widespread use of reactive processing aid (no inclusion into or onto article, indoor) As no environmental hazard was identified no environmental-related exposure assessment and risk characterization was performed.
Operational conditions	
Contributing exposure scenario	
Use descriptors covered	ERC8d: Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor) As no environmental hazard was identified no environmental-related exposure assessment and risk characterization was performed.
Operational conditions	
Contributing exposure scenario	
Use descriptors covered	ERC8f: Widespread use leading to inclusion into/onto article (outdoor) As no environmental hazard was identified no environmental-related exposure assessment and risk characterization was performed.
Operational conditions	
Contributing exposure scenario	
Use descriptors covered	PROC1: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions. Use domain: professional
Operational conditions	



BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 03.04.2024

Version: 1.0

Date / Previous version: not applicable

Previous version: none

Product: **BUTYL TRIGLYCOL**

(ID no. 30034746/SDS\_GEN\_AT/EN)

Date of print 21.10.2025

Concentration of the substance	Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	0,014 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
<b>Risk Management Measures</b>	
Use suitable eye protection.	
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	0,0343 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,000686
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	0,095 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,000487
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
Use descriptors covered	PROC2: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions Use domain: professional
<b>Operational conditions</b>	
Concentration of the substance	Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	0,014 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
<b>Risk Management Measures</b>	
Use suitable eye protection.	
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 03.04.2024

Version: 1.0

Date / Previous version: not applicable

Previous version: none

Product: **BUTYL TRIGLYCOL**

(ID no. 30034746/SDS\_GEN\_AT/EN)

Date of print 21.10.2025

	Worker - dermal, long-term - systemic
Exposure estimate	1,3714 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,027429
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	47,5 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,24359
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition Use domain: professional
<b>Operational conditions</b>	
Concentration of the substance	Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	0,014 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
<b>Risk Management Measures</b>	
Use suitable eye protection.	
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	0,6857 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,013714
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	28,5 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,146154
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC4: Chemical production where opportunity for exposure arises Use domain: professional

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 03.04.2024

Version: 1.0

Date / Previous version: not applicable

Previous version: none

Product: **BUTYL TRIGLYCOL**

(ID no. 30034746/SDS\_GEN\_AT/EN)

Date of print 21.10.2025

<b>Operational conditions</b>	
Concentration of the substance	Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	0,014 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
<b>Risk Management Measures</b>	
Use suitable eye protection.	
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	6,8571 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,137143
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	95 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,487179
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC6: Calendering operations Use domain: professional
<b>Operational conditions</b>	
Concentration of the substance	Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	0,014 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
<b>Risk Management Measures</b>	
Use suitable chemically resistant gloves.	Effectiveness: 80 %
Use suitable eye protection.	
<b>Exposure estimate and reference to its source</b>	

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 03.04.2024

Version: 1.0

Date / Previous version: not applicable

Previous version: none

Product: **BUTYL TRIGLYCOL**

(ID no. 30034746/SDS\_GEN\_AT/EN)

Date of print 21.10.2025

Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	5,4857 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,109714
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	95 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,487179
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing). Use domain: professional
<b>Operational conditions</b>	
Concentration of the substance	Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	0,014 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
<b>Risk Management Measures</b>	
Use suitable eye protection.	
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	6,8571 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,137143
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	95 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,487179
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC10: Roller application or brushing Use domain: professional
<b>Operational conditions</b>	
Concentration of the substance	Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 03.04.2024

Version: 1.0

Date / Previous version: not applicable

Previous version: none

Product: **BUTYL TRIGLYCOL**

(ID no. 30034746/SDS\_GEN\_AT/EN)

Date of print 21.10.2025

	3,6,9,12-tetraoxahexadecan-1-ol Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	0,014 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
<b>Risk Management Measures</b>	
Provide a good standard of general or controlled ventilation (5 to 10 air changes per hour)	Effectiveness: 70 %
Use suitable chemically resistant gloves.	Effectiveness: 80 %
Use suitable eye protection.	
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	5,4857 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,109714
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	71,25 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,365385
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC11: Non industrial spraying Use domain: professional
<b>Operational conditions</b>	
Concentration of the substance	Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	0,014 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Room size	100 m <sup>3</sup>
Application rate	10 l/min

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 03.04.2024

Version: 1.0

Date / Previous version: not applicable

Previous version: none

Product: **BUTYL TRIGLYCOL**

(ID no. 30034746/SDS\_GEN\_AT/EN)

Date of print 21.10.2025

<b>Risk Management Measures</b>	
Wear chemically resistant gloves in combination with 'basic' employee training.	Effectiveness: 90 %
Ensure that the task is being carried out outside the breathing zone of a worker (distance head-product greater than 1m). Ensure that the task is not carried out overhead. Regular inspection and maintenance of equipment and machines. Ensure that the direction of airflow is clearly away from the worker.	
Use suitable eye protection.	
<b>Exposure estimate and reference to its source</b>	
Assessment method	RISKOFDERM v2.1
	Worker - dermal, long-term - systemic
Exposure estimate	22,02 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,4404
Assessment method	Stoffenmanager v5.6
	Worker - inhalation, long-term - systemic
Exposure estimate	14,81 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,075949
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="https://www.stoffenmanager.nl/default.aspx">https://www.stoffenmanager.nl/default.aspx</a> For scaling see: <a href="http://www.tno.nl">http://www.tno.nl</a> and search for "riskofderm".	
<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC13: Treatment of articles by dipping and pouring. Use domain: professional
<b>Operational conditions</b>	
Concentration of the substance	Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	0,014 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
<b>Risk Management Measures</b>	
Use suitable eye protection.	
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 03.04.2024

Version: 1.0

Date / Previous version: not applicable

Previous version: none

Product: **BUTYL TRIGLYCOL**

(ID no. 30034746/SDS\_GEN\_AT/EN)

Date of print 21.10.2025

Exposure estimate	13,7143 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,274286
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	95 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,487179
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC15: Use a laboratory reagent. Use domain: professional
<b>Operational conditions</b>	
Concentration of the substance	Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	0,014 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
<b>Risk Management Measures</b>	
Use suitable eye protection.	
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	0,3429 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,006857
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	47,5 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,24359
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC19: Manual activities involving hand contact Use domain: professional
<b>Operational conditions</b>	
Concentration of the substance	Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol Content: >= 0 % - <= 100 %

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 03.04.2024

Version: 1.0

Date / Previous version: not applicable

Previous version: none

Product: **BUTYL TRIGLYCOL**

(ID no. 30034746/SDS\_GEN\_AT/EN)

Date of print 21.10.2025

Physical state	liquid
Vapour pressure of the substance during use	0,014 Pa
Process temperature	20 °C
Duration and Frequency of activity	240 min 5 days per week
Indoor/Outdoor	Indoor
<b>Risk Management Measures</b>	
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %
Wear chemically resistant gloves in combination with 'basic' employee training.	Effectiveness: 90 %
Use suitable eye protection.	
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	14,1429 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,282857
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	99,75 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,511538
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

\*\*\*\*\*

## 8. Short title of exposure scenario

Use in Cleaning Agents, (use in professional settings)

ERC8a, ERC8d; PROC2, PROC3, PROC4, PROC8b, PROC9, PROC10, PROC11, PROC13

## Control of exposure and risk management measures

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	ERC8a: Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor) As no environmental hazard was identified no environmental-related exposure assessment and risk characterization was performed.
<b>Operational conditions</b>	
<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	ERC8d: Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor)



BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 03.04.2024

Version: 1.0

Date / Previous version: not applicable

Previous version: none

Product: **BUTYL TRIGLYCOL**

(ID no. 30034746/SDS\_GEN\_AT/EN)

Date of print 21.10.2025

	As no environmental hazard was identified no environmental-related exposure assessment and risk characterization was performed.
--	---

### **Operational conditions**

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC2: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions Use domain: professional
<b>Operational conditions</b>	
Concentration of the substance	Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	0,014 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
<b>Risk Management Measures</b>	
Use suitable eye protection.	
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	1,3714 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,027429
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	47,5 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,24359
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition Use domain: professional
<b>Operational conditions</b>	
Concentration of the substance	Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 03.04.2024

Version: 1.0

Date / Previous version: not applicable

Previous version: none

Product: **BUTYL TRIGLYCOL**

(ID no. 30034746/SDS\_GEN\_AT/EN)

Date of print 21.10.2025

	Content: $\geq 0 \%$ - $\leq 100 \%$
Physical state	liquid
Vapour pressure of the substance during use	0,014 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
<b>Risk Management Measures</b>	
Use suitable eye protection.	
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	0,6857 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,013714
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	28,5 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,146154
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC4: Chemical production where opportunity for exposure arises Use domain: professional
<b>Operational conditions</b>	
Concentration of the substance	Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol Content: $\geq 0 \%$ - $\leq 100 \%$
Physical state	liquid
Vapour pressure of the substance during use	0,014 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
<b>Risk Management Measures</b>	
Use suitable eye protection.	
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	6,8571 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,137143

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 03.04.2024

Version: 1.0

Date / Previous version: not applicable

Previous version: none

Product: **BUTYL TRIGLYCOL**

(ID no. 30034746/SDS\_GEN\_AT/EN)

Date of print 21.10.2025

Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	95 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,487179
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC8b: Transfer of substance or mixture (charging and discharging) at dedicated facilities Use domain: professional
<b>Operational conditions</b>	
Concentration of the substance	Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	0,014 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
<b>Risk Management Measures</b>	
Use suitable eye protection.	
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	13,7143 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,274286
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	95 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,487179
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing). Use domain: professional
<b>Operational conditions</b>	
Concentration of the substance	Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol Content: >= 0 % - <= 100 %

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 03.04.2024

Version: 1.0

Date / Previous version: not applicable

Previous version: none

Product: **BUTYL TRIGLYCOL**

(ID no. 30034746/SDS\_GEN\_AT/EN)

Date of print 21.10.2025

Physical state	liquid
Vapour pressure of the substance during use	0,014 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
<b>Risk Management Measures</b>	
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %
Use suitable eye protection.	
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	6,8571 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,137143
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	66,5 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,341026
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC10: Roller application or brushing Use domain: professional
<b>Operational conditions</b>	
Concentration of the substance	Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	0,014 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
<b>Risk Management Measures</b>	
Provide a good standard of general or controlled ventilation (5 to 10 air changes per hour)	Effectiveness: 70 %
Use suitable chemically resistant gloves.	Effectiveness: 80 %
Use suitable eye protection.	

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 03.04.2024

Version: 1.0

Date / Previous version: not applicable

Previous version: none

Product: **BUTYL TRIGLYCOL**

(ID no. 30034746/SDS\_GEN\_AT/EN)

Date of print 21.10.2025

<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	5,4857 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,109714
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	71,25 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,365385
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC11: Non industrial spraying Use domain: professional
<b>Operational conditions</b>	
Concentration of the substance	Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	0,014 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Room size	100 m <sup>3</sup>
Application rate	10 l/min
<b>Risk Management Measures</b>	
Wear chemically resistant gloves in combination with 'basic' employee training.	Effectiveness: 90 %
Ensure that the task is being carried out outside the breathing zone of a worker (distance head-product greater than 1m). Ensure that the task is not carried out overhead. Ensure that the direction of airflow is clearly away from the worker. Regular inspection and maintenance of equipment and machines.	
Use suitable eye protection.	
<b>Exposure estimate and reference to its source</b>	
Assessment method	RISKOFDERM v2.1
	Worker - dermal, long-term - systemic
Exposure estimate	22,02 mg/kg bw/day

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 03.04.2024

Version: 1.0

Date / Previous version: not applicable

Previous version: none

Product: **BUTYL TRIGLYCOL**

(ID no. 30034746/SDS\_GEN\_AT/EN)

Date of print 21.10.2025

Risk Characterization Ratio (RCR)	0,4404
Assessment method	Stoffenmanager v5.6
	Worker - inhalation, long-term - systemic
Exposure estimate	14,81 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,075949
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="https://www.stoffenmanager.nl/default.aspx">https://www.stoffenmanager.nl/default.aspx</a> For scaling see: <a href="http://www.tno.nl">http://www.tno.nl</a> and search for "riskofderm".	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC13: Treatment of articles by dipping and pouring. Use domain: professional
<b>Operational conditions</b>	
Concentration of the substance	Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	0,014 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
<b>Risk Management Measures</b>	
Use suitable eye protection.	
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	13,7143 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,274286
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	95 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,487179
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

\*\*\*\*\*

## 9. Short title of exposure scenario

Use in Hydraulic fluids, (consumer use)

ERC9a, ERC9b; PC17

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 03.04.2024

Version: 1.0

Date / Previous version: not applicable

Previous version: none

Product: **BUTYL TRIGLYCOL**

(ID no. 30034746/SDS\_GEN\_AT/EN)

Date of print 21.10.2025

## Control of exposure and risk management measures

Contributing exposure scenario	
Use descriptors covered	ERC9a: Widespread use of functional fluid (indoor) As no environmental hazard was identified no environmental-related exposure assessment and risk characterization was performed.
<b>Operational conditions</b>	
Contributing exposure scenario	
Use descriptors covered	ERC9b: Widespread use of functional fluid (outdoor) As no environmental hazard was identified no environmental-related exposure assessment and risk characterization was performed.
<b>Operational conditions</b>	
Contributing exposure scenario	
Use descriptors covered	PC17: Hydraulic Fluids.
<b>Operational conditions</b>	
Concentration of the substance	Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol Content: >= 0 % - <= 30 %
Vapour pressure of the substance during use	0,014 Pa
Process temperature	20 °C
Duration and Frequency of activity	Exposure duration: 60 min Relevant for inhalative exposure estimates
Duration and Frequency of activity	4 uses per year
Room size	34 m3
Ventilation rate per hour	1,5
body weight	65 kg
Uptake fraction dermal	100 %
	Amount per use 220 g Relevant for inhalative exposure estimates
	Amount per use 220 g Relevant for dermal exposure estimates
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Dermal model: instant application, Uptake model: Uptake fraction
	Consumer - dermal, long-term - systemic
Exposure estimate	11,1275 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,4451

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 03.04.2024

Version: 1.0

Date / Previous version: not applicable

Previous version: none

Product: **BUTYL TRIGLYCOL**

(ID no. 30034746/SDS\_GEN\_AT/EN)

Date of print 21.10.2025

	The calculation is based on the internal chronic dose.
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Inhalation model: evaporation model - instantaneous release
	Consumer - inhalation, long-term - systemic
Exposure estimate	0,4592 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,003924
	The exposure calculation is based on the mean concentration per year.
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp">http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp</a>	

\*\*\*\*\*

## 10. Short title of exposure scenario

Use in Coatings, (consumer use)

ERC8a, ERC8b, ERC8d, ERC8f; PC1, PC9a, PC9b, PC9c, PC15, PC18, PC23, PC26, PC31, PC39

## Control of exposure and risk management measures

Contributing exposure scenario	
Use descriptors covered	ERC8a: Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor) As no environmental hazard was identified no environmental-related exposure assessment and risk characterization was performed.
<b>Operational conditions</b>	

Contributing exposure scenario	
Use descriptors covered	ERC8b: Widespread use of reactive processing aid (no inclusion into or onto article, indoor) As no environmental hazard was identified no environmental-related exposure assessment and risk characterization was performed.
<b>Operational conditions</b>	

Contributing exposure scenario	
Use descriptors covered	ERC8d: Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor) As no environmental hazard was identified no environmental-related exposure assessment and risk characterization was performed.
<b>Operational conditions</b>	

Contributing exposure scenario	
Use descriptors covered	ERC8f: Widespread use leading to inclusion into/onto



BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 03.04.2024

Version: 1.0

Date / Previous version: not applicable

Previous version: none

Product: **BUTYL TRIGLYCOL**

(ID no. 30034746/SDS\_GEN\_AT/EN)

Date of print 21.10.2025

	article (outdoor) As no environmental hazard was identified no environmental-related exposure assessment and risk characterization was performed.
<b>Operational conditions</b>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PC1: Adhesives, Sealants
<b>Operational conditions</b>	
Concentration of the substance	Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol Content: $\geq 0\%$ - $\leq 50\%$
Vapour pressure of the substance during use	0,014 Pa
Process temperature	20 °C
Duration and Frequency of activity	Exposure duration: 240 min Relevant for inhalative exposure estimates
Duration and Frequency of activity	Application duration: 10 min Relevant for inhalative exposure estimates
Duration and Frequency of activity	52 uses per year
Room size	20 m <sup>3</sup>
Ventilation rate per hour	0,6
Temperature (Application)	20 °C
body weight	65 kg
Uptake fraction dermal	100 %
	Amount per use 0,08 g Relevant for dermal exposure estimates
Release area	200 cm <sup>2</sup>
	Release area increases over time
Release duration	10 min
	Relevant for inhalative exposure estimates
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Dermal model: instant application, Uptake model: Uptake fraction
	Consumer - dermal, long-term - systemic
Exposure estimate	0,0877 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,003507
	The calculation is based on the internal chronic dose.
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Inhalation model: exposure to vapour - evaporation
	Consumer - inhalation, long-term - systemic
Exposure estimate	0,0285 mg/m <sup>3</sup>

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 03.04.2024

Version: 1.0

Date / Previous version: not applicable

Previous version: none

Product: **BUTYL TRIGLYCOL**

(ID no. 30034746/SDS\_GEN\_AT/EN)

Date of print 21.10.2025

Risk Characterization Ratio (RCR)	0,000243
	The exposure calculation is based on the mean concentration per year.
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp">http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PC9a: Coatings and paints, thinners, paint removers
<b>Operational conditions</b>	
Concentration of the substance	Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol Content: >= 0 % - <= 50 %
Vapour pressure of the substance during use	0,014 Pa
Process temperature	20 °C
Duration and Frequency of activity	Exposure duration: 60 min Relevant for inhalative exposure estimates
Duration and Frequency of activity	Application duration: 60 min Relevant for inhalative exposure estimates
Duration and Frequency of activity	52 uses per year
Room size	20 m <sup>3</sup>
Ventilation rate per hour	0,6
Temperature (Application)	20 °C
body weight	65 kg
Uptake fraction dermal	100 %
	Amount per use 0,5 g Relevant for dermal exposure estimates
Release area	20000 cm <sup>2</sup>
	Release area increases over time
Release duration	60 min
	Relevant for inhalative exposure estimates
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Dermal model: instant application, Uptake model: Uptake fraction
	Consumer - dermal, long-term - systemic
Exposure estimate	0,5479 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,021918
	The calculation is based on the internal chronic dose.
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Inhalation model: exposure to vapour - evaporation
	Consumer - inhalation, long-term - systemic
Exposure estimate	0,0071 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,000061

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 03.04.2024

Version: 1.0

Date / Previous version: not applicable

Previous version: none

Product: **BUTYL TRIGLYCOL**

(ID no. 30034746/SDS\_GEN\_AT/EN)

Date of print 21.10.2025

	The exposure calculation is based on the mean concentration per year.
--	---

### **Guidance to Downstream Users**

For scaling see: <http://www.rivm.nl/en/healthandddisease/productsafety/ConsExpo.jsp>

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PC9b: Fillers, putties, plasters, modelling clay
<b>Operational conditions</b>	
Concentration of the substance	Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol Content: $\geq 0\%$ - $\leq 50\%$
Vapour pressure of the substance during use	0,014 Pa
Process temperature	20 °C
Duration and Frequency of activity	Exposure duration: 240 min Relevant for inhalative exposure estimates
Duration and Frequency of activity	Application duration: 20 min Relevant for inhalative exposure estimates
Duration and Frequency of activity	52 uses per year
Room size	20 m <sup>3</sup>
Ventilation rate per hour	0,6
Temperature (Application)	20 °C
body weight	65 kg
Uptake fraction dermal	100 %
	Amount per use 0,05 g Relevant for dermal exposure estimates
Release area	200 cm <sup>2</sup>
	Release area increases over time
Release duration	20 min
	Relevant for inhalative exposure estimates
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Dermal model: instant application, Uptake model: Uptake fraction
	Consumer - dermal, long-term - systemic
Exposure estimate	0,0548 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,002192
	The calculation is based on the internal chronic dose.
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Inhalation model: exposure to vapour - evaporation
	Consumer - inhalation, long-term - systemic
Exposure estimate	0,0283 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,000242
	The exposure calculation is based on the mean

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 03.04.2024

Version: 1.0

Date / Previous version: not applicable

Previous version: none

Product: **BUTYL TRIGLYCOL**

(ID no. 30034746/SDS\_GEN\_AT/EN)

Date of print 21.10.2025

	concentration per year.
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp">http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PC9c: Finger paints
<b>Operational conditions</b>	
Concentration of the substance	Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol Content: >= 0 % - <= 50 %
Vapour pressure of the substance during use	0,014 Pa
Process temperature	20 °C
Duration and Frequency of activity	Exposure duration: 132 min Relevant for inhalative exposure estimates
Duration and Frequency of activity	Application duration: 120 min Relevant for inhalative exposure estimates
Duration and Frequency of activity	52 uses per year
Room size	20 m <sup>3</sup>
Ventilation rate per hour	0,6
Temperature (Application)	20 °C
body weight	65 kg
Uptake fraction dermal	100 %
Release area	100000 cm <sup>2</sup>
	Release area increases over time
Release duration	120 min
	Relevant for inhalative exposure estimates
Contact rate	30 mg/min
Release duration	120 min
	Relevant for dermal exposure estimates
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Dermal model: constant application rate, Uptake model: Uptake fraction
	Consumer - dermal, long-term - systemic
Exposure estimate	3,9452 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,157808
	The calculation is based on the internal chronic dose.
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Inhalation model: exposure to vapour - evaporation
	Consumer - inhalation, long-term - systemic
Exposure estimate	0,0097 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,000083
	The exposure calculation is based on the mean

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 03.04.2024

Version: 1.0

Date / Previous version: not applicable

Previous version: none

Product: **BUTYL TRIGLYCOL**

(ID no. 30034746/SDS\_GEN\_AT/EN)

Date of print 21.10.2025

	concentration per year.
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp">http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp</a>	
<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PC15: Non-metal-surface treatment products.
<b>Operational conditions</b>	
Concentration of the substance	Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol Content: $\geq 0\%$ - $\leq 20\%$
Vapour pressure of the substance during use	0,014 Pa
Process temperature	20 °C
Duration and Frequency of activity	Exposure duration: 240 min Relevant for inhalative exposure estimates
Duration and Frequency of activity	Application duration: 30 min Relevant for inhalative exposure estimates
Duration and Frequency of activity	104 uses per year
Room size	58 m <sup>3</sup>
Ventilation rate per hour	0,5
Temperature (Application)	20 °C
body weight	65 kg
Uptake fraction dermal	100 %
	Amount per use 19 g Relevant for dermal exposure estimates
Release area	220000 cm <sup>2</sup>
	Release area increases over time
Release duration	30 min
	Relevant for inhalative exposure estimates
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Dermal model: instant application, Uptake model: Uptake fraction
	Consumer - dermal, long-term - systemic
Exposure estimate	16,6575 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,666301
	The calculation is based on the internal chronic dose.
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Inhalation model: exposure to vapour - evaporation
	Consumer - inhalation, long-term - systemic
Exposure estimate	0,0012 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,00001
	The exposure calculation is based on the mean concentration per year.

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 03.04.2024

Version: 1.0

Date / Previous version: not applicable

Previous version: none

Product: **BUTYL TRIGLYCOL**

(ID no. 30034746/SDS\_GEN\_AT/EN)

Date of print 21.10.2025

### **Guidance to Downstream Users**

For scaling see: <http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp>

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PC18: Ink and Toners.
<b>Operational conditions</b>	
Concentration of the substance	Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol Content: >= 0 % - <= 50 %
Vapour pressure of the substance during use	0,014 Pa
Process temperature	20 °C
Duration and Frequency of activity	Exposure duration: 132 min Relevant for inhalative exposure estimates
Duration and Frequency of activity	Application duration: 120 min Relevant for inhalative exposure estimates
Duration and Frequency of activity	104 uses per year
Room size	20 m3
Ventilation rate per hour	0,6
Temperature (Application)	20 °C
body weight	65 kg
Uptake fraction dermal	100 %
Release area	100000 cm <sup>2</sup>
	Release area increases over time
Release duration	120 min
	Relevant for inhalative exposure estimates
Contact rate	30 mg/min
Release duration	120 min
	Relevant for dermal exposure estimates
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Dermal model: constant application rate, Uptake model: Uptake fraction
	Consumer - dermal, long-term - systemic
Exposure estimate	7,8904 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,315616
	The calculation is based on the internal chronic dose.
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Inhalation model: exposure to vapour - evaporation
	Consumer - inhalation, long-term - systemic
Exposure estimate	0,0194 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,000166
	The exposure calculation is based on the mean concentration per year.

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 03.04.2024

Version: 1.0

Date / Previous version: not applicable

Previous version: none

Product: **BUTYL TRIGLYCOL**

(ID no. 30034746/SDS\_GEN\_AT/EN)

Date of print 21.10.2025

### **Guidance to Downstream Users**

For scaling see: <http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp>

### **Contributing exposure scenario**

<b>Use descriptors covered</b>	PC23: Leather tanning, dye, finishing, impregnation and care products.
--------------------------------	--

### **Operational conditions**

Concentration of the substance	Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol Content: >= 0 % - <= 50 %
Vapour pressure of the substance during use	0,014 Pa
Process temperature	20 °C
Duration and Frequency of activity	Exposure duration: 60 min Relevant for inhalative exposure estimates
Duration and Frequency of activity	6 uses per year
Room size	30 m3
Ventilation rate per hour	0,5
body weight	65 kg
Uptake fraction dermal	100 %
	Amount per use 100 g Relevant for inhalative exposure estimates
	Amount per use 100 g Relevant for dermal exposure estimates

### **Exposure estimate and reference to its source**

Assessment method	EASY TRA v4.1, ConsExpo v4.1, Dermal model: instant application, Uptake model: Uptake fraction
	Consumer - dermal, long-term - systemic
Exposure estimate	12,6449 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,505796
	The calculation is based on the internal chronic dose.
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Inhalation model: evaporation model - instantaneous release
	Consumer - inhalation, long-term - systemic
Exposure estimate	0,8984 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,007679
	The exposure calculation is based on the mean concentration per year.

### **Guidance to Downstream Users**

For scaling see: <http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp>

### **Contributing exposure scenario**

<b>Use descriptors covered</b>	PC26: Paper and Board dye, finishing and impregnation
--------------------------------	---

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 03.04.2024

Version: 1.0

Date / Previous version: not applicable

Previous version: none

Product: **BUTYL TRIGLYCOL**

(ID no. 30034746/SDS\_GEN\_AT/EN)

Date of print 21.10.2025

	products: including bleaches and other processing aids
<b>Operational conditions</b>	
Concentration of the substance	Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol Content: >= 0 % - <= 25 %
Vapour pressure of the substance during use	0,014 Pa
Process temperature	20 °C
Duration and Frequency of activity	Exposure duration: 20 min Relevant for inhalative exposure estimates
Duration and Frequency of activity	4 uses per year
Room size	34 m3
Ventilation rate per hour	1,5
body weight	65 kg
Uptake fraction dermal	100 %
Spray duration	900 sec
Contact rate	100 mg/min
Release duration	15 min
	Relevant for dermal exposure estimates
<b>Risk Management Measures</b>	
Consumer Measures	Ensure spraying away from persons.
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Dermal model: constant application rate, Uptake model: Uptake fraction
	Consumer - dermal, long-term - systemic
Exposure estimate	0,0632 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,002529
	The calculation is based on the internal chronic dose.
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Inhalation model: Exposure to spray/dust
	Consumer - inhalation, long-term - systemic
Exposure estimate	0,0542 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,000463
	The exposure calculation is based on the mean concentration per year.
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.rivm.nl/en/healthandddisease/productsafety/ConsExpo.jsp">http://www.rivm.nl/en/healthandddisease/productsafety/ConsExpo.jsp</a>	
<b>Contributing exposure scenario</b>	
Use descriptors covered	PC31: Polishes and Wax Blends.
<b>Operational conditions</b>	
Concentration of the substance	Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and



BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 03.04.2024

Version: 1.0

Date / Previous version: not applicable

Previous version: none

Product: **BUTYL TRIGLYCOL**

(ID no. 30034746/SDS\_GEN\_AT/EN)

Date of print 21.10.2025

	3,6,9,12-tetraoxahexadecan-1-ol Content: >= 0 % - <= 50 %
Vapour pressure of the substance during use	0,014 Pa
Process temperature	20 °C
Duration and Frequency of activity	Exposure duration: 60 min Relevant for inhalative exposure estimates
Duration and Frequency of activity	Application duration: 60 min Relevant for inhalative exposure estimates
Duration and Frequency of activity	104 uses per year
Room size	34 m3
Ventilation rate per hour	1,5
Temperature (Application)	20 °C
body weight	65 kg
Uptake fraction dermal	100 %
	Amount per use 0,25 g Relevant for dermal exposure estimates
Release area	150000 cm <sup>2</sup>
	Release area increases over time
Release duration	60 min
	Relevant for inhalative exposure estimates
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Dermal model: instant application, Uptake model: Uptake fraction
	Consumer - dermal, long-term - systemic
Exposure estimate	0,5479 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,021918
	The calculation is based on the internal chronic dose.
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Inhalation model: exposure to vapour - evaporation
	Consumer - inhalation, long-term - systemic
Exposure estimate	0,0144 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,000123
	The exposure calculation is based on the mean concentration per year.
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.rivm.nl/en/healthandddisease/productsafety/ConsExpo.jsp">http://www.rivm.nl/en/healthandddisease/productsafety/ConsExpo.jsp</a>	
<b>Contributing exposure scenario</b>	
Use descriptors covered	PC39: Cosmetics, personal care products.
<b>Operational conditions</b>	
Concentration of the substance	Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 03.04.2024

Version: 1.0

Date / Previous version: not applicable

Previous version: none

Product: **BUTYL TRIGLYCOL**

(ID no. 30034746/SDS\_GEN\_AT/EN)

Date of print 21.10.2025

	Content: $\geq 0\%$ - $\leq 50\%$
Vapour pressure of the substance during use	0,014 Pa
Process temperature	20 °C
Duration and Frequency of activity	730 uses per year
body weight	61 kg
Uptake fraction dermal	100 %
	Amount per use 0,8 g Relevant for dermal exposure estimates
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Dermal model: instant application, Uptake model: Uptake fraction
	Consumer - dermal, long-term - systemic
Exposure estimate	13,1148 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,52459
	The calculation is based on the internal chronic dose.
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp">http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp</a>	

\*\*\*\*\*

## 11. Short title of exposure scenario

Use in Cleaning Agents, (consumer use)  
ERC8a, ERC8d; PC35

## Control of exposure and risk management measures

Contributing exposure scenario	
<b>Use descriptors covered</b>	ERC8a: Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor) As no environmental hazard was identified no environmental-related exposure assessment and risk characterization was performed.
<b>Operational conditions</b>	
Contributing exposure scenario	
<b>Use descriptors covered</b>	ERC8d: Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor) As no environmental hazard was identified no environmental-related exposure assessment and risk characterization was performed.

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 03.04.2024

Version: 1.0

Date / Previous version: not applicable

Previous version: none

Product: **BUTYL TRIGLYCOL**

(ID no. 30034746/SDS\_GEN\_AT/EN)

Date of print 21.10.2025

### **Operational conditions**

#### **Contributing exposure scenario**

<b>Use descriptors covered</b>	PC35: Washing and Cleaning Products (including solvent based products).
--------------------------------	---

#### **Operational conditions**

Concentration of the substance	Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol Content: $\geq 0\%$ - $\leq 5\%$
Vapour pressure of the substance during use	0,014 Pa
Process temperature	20 °C
Duration and Frequency of activity	Exposure duration: 20 min Relevant for inhalative exposure estimates
Duration and Frequency of activity	Application duration: 20 min Relevant for inhalative exposure estimates
Duration and Frequency of activity	128 uses per year
Room size	20 m <sup>3</sup>
Ventilation rate per hour	0,5
Temperature (Application)	20 °C
body weight	65 kg
Uptake fraction dermal	100 %
	Amount per use 27 g Relevant for dermal exposure estimates
Release area	100000 cm <sup>2</sup>
	Release area increases over time
Release duration	20 min
	Relevant for inhalative exposure estimates

#### **Exposure estimate and reference to its source**

Assessment method	EASY TRA v4.1, ConsExpo v4.1, Dermal model: instant application, Uptake model: Uptake fraction
	Consumer - dermal, long-term - systemic
Exposure estimate	7,2835 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,291338
	The calculation is based on the internal chronic dose.
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Inhalation model: exposure to vapour - evaporation
	Consumer - inhalation, long-term - systemic
Exposure estimate	0,0001 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,000001
	The exposure calculation is based on the mean concentration per year.

#### **Guidance to Downstream Users**

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 03.04.2024

Version: 1.0

Date / Previous version: not applicable

Previous version: none

Product: **BUTYL TRIGLYCOL**

(ID no. 30034746/SDS\_GEN\_AT/EN)

Date of print 21.10.2025

For scaling see: <http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp>

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PC35: Washing and Cleaning Products (including solvent based products).
<b>Operational conditions</b>	
Concentration of the substance	Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol Content: >= 0 % - <= 15 %
Vapour pressure of the substance during use	0,014 Pa
Process temperature	20 °C
Duration and Frequency of activity	Exposure duration: 10 min Relevant for inhalative exposure estimates
Duration and Frequency of activity	128 uses per year
Room size	20 m3
Ventilation rate per hour	2,5
body weight	65 kg
Uptake fraction dermal	100 %
Spray duration	24,6 sec
Contact rate	46 mg/min
Release duration	0,41 min
	Relevant for dermal exposure estimates
<b>Risk Management Measures</b>	
Consumer Measures	Ensure spraying away from persons.
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Dermal model: constant application rate, Uptake model: Uptake fraction
	Consumer - dermal, long-term - systemic
Exposure estimate	0,0153 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,000611
	The calculation is based on the internal chronic dose.
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Inhalation model: Exposure to spray/dust
	Consumer - inhalation, long-term - systemic
Exposure estimate	0,0017 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,000014
	The exposure calculation is based on the mean concentration per year.
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp">http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp</a>	

**Contributing exposure scenario**

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 03.04.2024

Version: 1.0

Date / Previous version: not applicable

Previous version: none

Product: **BUTYL TRIGLYCOL**

(ID no. 30034746/SDS\_GEN\_AT/EN)

Date of print 21.10.2025

<b>Use descriptors covered</b>	PC35: Washing and Cleaning Products (including solvent based products).
<b>Operational conditions</b>	
Concentration of the substance	Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol Content: $\geq 0\%$ - $\leq 15\%$
Vapour pressure of the substance during use	0,014 Pa
Process temperature	20 °C
Duration and Frequency of activity	Exposure duration: 60 min Relevant for inhalative exposure estimates
Duration and Frequency of activity	Application duration: 10 min Relevant for inhalative exposure estimates
Duration and Frequency of activity	128 uses per year
Room size	20 m <sup>3</sup>
Ventilation rate per hour	2,5
Temperature (Application)	20 °C
body weight	65 kg
Uptake fraction dermal	100 %
	Amount per use 0,16 g Relevant for dermal exposure estimates
Release area	17100 cm <sup>2</sup>
	Release area is constant
Release duration	10 min
	Relevant for inhalative exposure estimates
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Dermal model: instant application, Uptake model: Uptake fraction
	Consumer - dermal, long-term - systemic
Exposure estimate	0,1295 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,005179
	The calculation is based on the internal chronic dose.
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Inhalation model: exposure to vapour - evaporation
	Consumer - inhalation, long-term - systemic
Exposure estimate	0,0004 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,000004
	The exposure calculation is based on the mean concentration per year.
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp">http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp</a>	

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 03.04.2024

Version: 1.0

Date / Previous version: not applicable

Previous version: none

Product: **BUTYL TRIGLYCOL**

(ID no. 30034746/SDS\_GEN\_AT/EN)

Date of print 21.10.2025

\*\*\*\*\*