

Safety data sheet

Page: 1/31

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 26.09.2025

Version: 3.0

Date / Previous version: 18.09.2023

Previous version: 2.0

Product: **4-Hydroxybutyl Acrylate (4-HBA)**

(ID no. 30041244/SDS_GEN_DE/EN)

Date of print 16.10.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

4-Hydroxybutyl Acrylate (4-HBA)

Chemical name: 4-hydroxybutyl acrylate

CAS Number: 2478-10-6

REACH registration number: 01-2119957314-36-0000

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses: Monomer.

Recommended use: for industrial use only

For the detailed identified uses of the product see appendix of the safety data sheet.

1.3. Details of the supplier of the safety data sheet

Company:

BASF SE

67056 Ludwigshafen

GERMANY

Operating Division Petrochemicals

Telephone: +49 621 60-42151

E-mail address: sds-petrochemicals@basf.com

1.4. Emergency telephone number

International emergency number:

Telephone: +49 180 2273-112

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 26.09.2025

Version: 3.0

Date / Previous version: 18.09.2023

Previous version: 2.0

Product: **4-Hydroxybutyl Acrylate (4-HBA)**

(ID no. 30041244/SDS_GEN_DE/EN)

Date of print 16.10.2025

SECTION 2: Hazards Identification

2.1. Classification of the substance or mixture

According to Regulation (EC) No 1272/2008 [CLP]

Acute Tox. 4 (oral)	H302 Harmful if swallowed.
Skin Irrit. 2	H315 Causes skin irritation.
Eye Dam. 1	H318 Causes serious eye damage.
Skin Sens. 1	H317 May cause an allergic skin reaction.

For the classifications not written out in full in this section the full text can be found in section 16.

2.2. Label elements

According to Regulation (EC) No 1272/2008 [CLP]

Pictogram:



Signal Word:

Danger

Hazard Statement:

H318	Causes serious eye damage.
H315	Causes skin irritation.
H302	Harmful if swallowed.
H317	May cause an allergic skin reaction.

Precautionary Statements (Prevention):

P280	Wear protective gloves and eye protection or face protection.
P261	Avoid breathing mist or vapour or spray.

Precautionary Statements (Response):

P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER or physician.
P302 + P352	IF ON SKIN: Wash with plenty of soap and water.

Precautionary Statements (Disposal):

P501	Dispose of contents and container to hazardous or special waste collection point.
------	---

Hazard determining component(s) for labelling: 4-Hydroxybutyl acrylate

2.3. Other hazards

According to Regulation (EC) No 1272/2008 [CLP]

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 26.09.2025

Version: 3.0

Date / Previous version: 18.09.2023

Previous version: 2.0

Product: **4-Hydroxybutyl Acrylate (4-HBA)**

(ID no. 30041244/SDS_GEN_DE/EN)

Date of print 16.10.2025

See section 12 - Results of PBT and vPvB assessment.

Product does not contain a substance above legal limits included in the list established in accordance with Article 59(1) of Regulation (EC) No 1907/2006 for having endocrine disrupting properties or is identified to have endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605. The product does not fulfill the criteria for PBT (Persistent/bioaccumulative/toxic) and vPvB (very persistent/very bioaccumulative).
Skin resorption hazard.

SECTION 3: Composition/Information on Ingredients

3.1. Substances

Chemical nature

4-Hydroxybutyl acrylate

CAS Number: 2478-10-6
EC-Number: 219-606-3

Acute Tox. 4 (oral)
Skin Irrit. 2
Eye Dam. 1
Skin Sens. 1
H318, H315, H302, H317

Regulatory relevant ingredients

4-Hydroxybutyl acrylate

Content (W/W): $\geq 97\%$ - $\leq 100\%$
CAS Number: 2478-10-6
EC-Number: 219-606-3

Acute Tox. 4 (oral)
Skin Irrit. 2
Eye Dam. 1
Skin Sens. 1
H318, H315, H302, H317

tetramethylene diacrylate

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 26.09.2025

Version: 3.0

Date / Previous version: 18.09.2023

Previous version: 2.0

Product: **4-Hydroxybutyl Acrylate (4-HBA)**

(ID no. 30041244/SDS_GEN_DE/EN)

Date of print 16.10.2025

Content (W/W): $\geq 0\%$ - $\leq 0,5\%$	Acute Tox. 4 (Inhalation - vapour)
CAS Number: 1070-70-8	Acute Tox. 4 (oral)
EC-Number: 213-979-6	Acute Tox. 3 (dermal)
INDEX-Number: 607-119-00-2	Skin Corr. 1B
	Eye Dam. 1
	Skin Sens. 1
	Aquatic Chronic 3
	H314, H311, H317, H302 + H332, H412
	<u>Differing classification according to current knowledge and the criteria given in Annex I of Regulation (EC) No. 1272/2008</u>
	Acute Tox. 4 (Inhalation - vapour)
	Acute Tox. 4 (oral)
	Acute Tox. 3 (dermal)
	Skin Corr. 1B
	Eye Dam. 1
	Skin Sens. 1A
	Aquatic Chronic 3
acrylic acid	
Content (W/W): $\geq 0\%$ - $\leq 0,3\%$	Acute Tox. 4 (Inhalation - vapour)
CAS Number: 79-10-7	Acute Tox. 4 (oral)
EC-Number: 201-177-9	Aquatic Chronic 2
INDEX-Number: 607-061-00-8	Aquatic Acute 1
	Acute Tox. 4 (dermal)
Substance with EU occupational exposure limit	Flam. Liq. 3
	Eye Dam. 1
	Skin Corr. 1A
	M-factor acute: 1
	H226, H314, H302 + H312 + H332, H411, H400
	<u>Specific concentration limit:</u>
	STOT SE 3, irr. to respiratory syst.: 1 - < 5 %

For the classifications not written out in full in this section, including the hazard classes and the hazard statements, the full text is listed in section 16.

3.2. Mixtures

Not applicable

SECTION 4: First-Aid Measures

4.1. Description of first aid measures

Remove contaminated clothing.

If inhaled:

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 26.09.2025

Version: 3.0

Date / Previous version: 18.09.2023

Previous version: 2.0

Product: **4-Hydroxybutyl Acrylate (4-HBA)**

(ID no. 30041244/SDS_GEN_DE/EN)

Date of print 16.10.2025

Keep patient calm, remove to fresh air, seek medical attention. Immediately administer a corticosteroid from a controlled/metered dose inhaler.

On skin contact:

Immediately wash thoroughly with plenty of water, apply sterile dressings, consult a skin specialist.

On contact with eyes:

Immediately wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.

On ingestion:

Immediately rinse mouth and then drink 200-300 ml of water, seek medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms: Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11.

Hazards: Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11. (Further) symptoms and / or effects are not known so far

4.3. Indication of any immediate medical attention and special treatment needed

Treatment: Treat according to symptoms (decontamination, vital functions), no known specific antidote.

SECTION 5: Fire-Fighting Measures

5.1. Extinguishing media

Suitable extinguishing media:

dry powder, water spray, carbon dioxide, foam

Unsuitable extinguishing media for safety reasons:

water jet

Additional information:

Use extinguishing measures to suit surroundings.

5.2. Special hazards arising from the substance or mixture

Advice: Risk of violent self-polymerization if overheated in a container. Cool endangered containers with water-spray.

Advice: The product is combustible. See SDS section 7 - Handling and storage.

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 26.09.2025

Version: 3.0

Date / Previous version: 18.09.2023

Previous version: 2.0

Product: **4-Hydroxybutyl Acrylate (4-HBA)**

(ID no. 30041244/SDS_GEN_DE/EN)

Date of print 16.10.2025

5.3. Advice for fire-fighters

Special protective equipment:

Wear a self-contained breathing apparatus. Special protective equipment for firefighters

Further information:

Extend fire extinguishing measures to the surroundings. Fight fire from maximum distance. Vapours are heavier than air and may accumulate in low areas and travel a considerable distance up to the source of ignition.

In case of a fire in the vicinity a restabilization system should be used if the temperature in the bulk storage-tank reaches 45°C. Evacuate area of all unnecessary personnel. In case of a fire in the vicinity evacuate all personnel in a greater area if the temperature in the bulk storage-tank reaches 60°C.

Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

SECTION 6: Accidental Release Measures

High risk of slipping due to leakage/spillage of product.

Release of substance/product can cause fire or explosion. Shut off or stop source of leak. Shut off or stop released substance/product under safe conditions.

Pack in tightly closed containers for disposal.

6.1. Personal precautions, protective equipment and emergency procedures

Handle in accordance with good industrial hygiene and safety practice.

Avoid all sources of ignition: heat, sparks, open flame. Use antistatic tools.

6.2. Environmental precautions

Discharge into the environment must be avoided.

6.3. Methods and material for containment and cleaning up

For large amounts: Pump off product.

Spills should be contained, solidified, and placed in suitable containers for disposal. Dispose of absorbed material in accordance with regulations. Ensure adequate ventilation. Suppress gases/vapours/mists with water spray jet. Clean contaminated floors and objects thoroughly with water and detergents, observing environmental regulations. Cleaning operations should be carried out only while wearing breathing apparatus. Pick up with suitable appliance and dispose of.

6.4. Reference to other sections

Information regarding exposure controls/personal protection and disposal considerations can be found in section 8 and 13.

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 26.09.2025

Version: 3.0

Date / Previous version: 18.09.2023

Previous version: 2.0

Product: **4-Hydroxybutyl Acrylate (4-HBA)**

(ID no. 30041244/SDS_GEN_DE/EN)

Date of print 16.10.2025

SECTION 7: Handling and Storage

7.1. Precautions for safe handling

The substance/ product may be handled only by appropriately trained personnel. Facility parts must be checked for polymer residues and cleaned on regular basis in order to avoid hazardous reactions.

Ensure thorough ventilation of stores and work areas. Encapsulation or exhaust ventilation required. When filling, transferring, or emptying of containers, adequate local exhaust ventilation is necessary. Vent waste air to atmosphere only through suitable separators. Check the condition of seals and connector screw threads.

The temperatures which must be avoided are to be considered. Protect against heat. Protect from direct sunlight. Protect contents from the effects of light. Do not open warm or swollen product containers. Remove persons to safety and alert fire brigade.

Ensure adequate inhibitor and dissolved oxygen level.

Avoid inhalation of dusts/mists/vapours. Avoid aerosol formation. Avoid all direct contact with the substance/product.

Protection against fire and explosion:

Avoid all sources of ignition: heat, sparks, open flame. Substance/product can form explosive mixture with air. Ground all transfer equipment properly to prevent electrostatic discharge. It is recommended that all conductive parts of the machinery are grounded. Explosion-proof equipment is not necessary when loading and processing of the product takes place at a minimum of 5 °C below the flash point.

Heated containers should be cooled to prevent polymerization. If exposed to fire, keep containers cool by spraying with water. Emergency cooling must be provided for the eventuality of a fire in the vicinity.

Temperature class: T2 (Autoignition temperature >300 °C).

7.2. Conditions for safe storage, including any incompatibilities

Further information on storage conditions: Prior to storage ensure that the transfer equipment used and the intended storage containers do not contain other substances/products. Before transfer to stock the identity of the product must be proved to be without doubt. The entrance to storage rooms is to be granted only to appropriately trained personnel.

The stabilizer is only effective in the presence of oxygen. Maintain contact with atmosphere containing 5 - 21% oxygen. Never use tanks with inert-gas installation for storage.

Risk of polymerization. Protect against heat. Protect from direct sunlight. Avoid UV-light and other radiation with high energy. Protect against contamination.

In case of bulk storage, the storage-tanks should at least be equipped with two high temperature alert devices.

Even if the product is stored and handled as prescribed/indicated it should be used up within the indicated duration of storage.

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 26.09.2025

Version: 3.0

Date / Previous version: 18.09.2023

Previous version: 2.0

Product: **4-Hydroxybutyl Acrylate (4-HBA)**

(ID no. 30041244/SDS_GEN_DE/EN)

Date of print 16.10.2025

Storage class according to TRGS 510 (originally VCI, Germany): (10) Combustible liquids

Storage stability:

Storage temperature: $\leq 25\text{ }^{\circ}\text{C}$

Storage duration: 6 Months

The stated storage temperature should be noted.

Avoid prolonged storage.

This product should be processed as soon as possible.

Ensure adequate inhibitor and dissolved oxygen level.

Check frequently to ensure that stabilizer content is adequate.

The product is stabilized, the shelf life should be noted.

Do not store with less than 10 % headspace above liquid.

Storage stability is based upon ambient temperatures and conditions described.

Storage temperature: $45\text{ }^{\circ}\text{C}$

A restabilization system should be used if the temperature in the bulk storage-tank reaches the indicated value.

Storage temperature: $60\text{ }^{\circ}\text{C}$

All personnel in a greater area should be evacuated if the temperature in the bulk storage-tank reaches the indicated value.

7.3. Specific end use(s)

See exposure scenario(s) in the attachment to this safety data sheet.

SECTION 8: Exposure Controls/Personal Protection

8.1. Control parameters

Components with occupational exposure limits

The surveillance of the workplace by exposure measurements may be necessary, in order to prove the efficiency of safety measures, for example ventilation or the need of respiratory protection. Since this requires a specific competency, only accredited laboratories should be contracted. Regarding suitable methods to assess inhalation exposure, the European Standards EN 482, 689 and 14042 are to be considered. In addition, the TRGS 402 has to be observed in Germany.

79-10-7: acrylic acid

Short Term Exposure Classification: (TRGS 900 (DE))

Category I: Substances for which the localized effect has an assigned exposure limit or for substances with a sensitizing effect in respiratory passages

STEL value 59 mg/m^3 ; 20 ppm (OEL (EU))

indicative

TWA value 29 mg/m^3 ; 10 ppm (OEL (EU))

indicative

OEL 30 mg/m^3 ; 10 ppm (TRGS 900 (DE))

Ceiling limit value/factor: 2

If the occupational exposure limit value (AGW) and the biological limit value (BGW) are complied with, there should be no risk of damage for the unborn child (see TRGS 900, Number 2.7)

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 26.09.2025

Version: 3.0

Date / Previous version: 18.09.2023

Previous version: 2.0

Product: **4-Hydroxybutyl Acrylate (4-HBA)**

(ID no. 30041244/SDS_GEN_DE/EN)

Date of print 16.10.2025

Short Term Exposure Factor: (TRGS 900 (DE))

Ceiling limit value/factor: 1

Substance listed with exceeding factor and category of short time value.

Skin Designation (TRGS 900 (DE))

The substance can be absorbed through the skin.

PNEC

STP: 10 mg/l

freshwater: 0,0136 mg/l

marine water: 0,0014 mg/l

sediment (freshwater): 0,0626 mg/kg

sediment (marine water): 0,0063 mg/kg

soil: 0,0045 mg/kg

DNEL

worker:

Long-term exposure- systemic effects, dermal: 8,2 mg/kg

worker:

Long-term exposure- systemic effects, Inhalation: 1,98 mg/m³

worker:

Long-term exposure - local effects, Inhalation: 3 mg/m³

worker:

Short-term exposure - local effects, Inhalation: 3 mg/m³

8.2. Exposure controls

Appropriate engineering controls

Ensure adequate ventilation.

Personal protective equipment

Respiratory protection:

Suitable respiratory protection for lower concentrations or short-term effect: Gas filter for gases/vapours of organic compounds (boiling point >65 °C, e. g. EN 14387 Type A)

Hand protection:

Suitable materials also with prolonged, direct contact (Recommended: Protective index 6, corresponding > 480 minutes of permeation time according to EN ISO 374-1):

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 26.09.2025

Version: 3.0

Date / Previous version: 18.09.2023

Previous version: 2.0

Product: **4-Hydroxybutyl Acrylate (4-HBA)**

(ID no. 30041244/SDS_GEN_DE/EN)

Date of print 16.10.2025

fluoroelastomer (FKM) - 0.7 mm coating thickness

nitrile rubber (NBR) - 0.4 mm coating thickness

Manufacturer's directions for use should be observed because of great diversity of types.

Supplementary note: The specifications are based on tests, literature data and information of glove manufacturers or are derived from similar substances by analogy. Due to many conditions (e.g. temperature) it must be considered, that the practical usage of a chemical-protective glove in practice may be much shorter than the permeation time determined through testing.

Eye protection:

Tightly fitting safety goggles (splash goggles) (e.g. EN 166)

Body protection:

Body protection must be chosen depending on activity and possible exposure, e.g. apron, protecting boots, chemical-protection suit (according to EN 14605 in case of splashes or EN ISO 13982 in case of dust).

General safety and hygiene measures

Wearing of closed work clothing is required additionally to the stated personal protection equipment. Avoid inhalation of vapour. Avoid contact with the skin, eyes and clothing. Handle in accordance with good industrial hygiene and safety practice.

Environmental exposure controls

All appropriate measures must be taken to prevent the release of this product to the environment and to limit the dispersion of any release when it occurs. Suitable risk management measures should be in place.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

State of matter:	liquid	
Form:	liquid	
Colour:	colourless	
Odour:	odourless	
Odour threshold:	not determined	
Melting point:	-80 °C	
	Literature data.	
Boiling point:	236 °C	(measured)
	(1.013 hPa)	
Flammability:	hardly combustible	(derived from flash point)
Lower explosion limit:	For liquids not relevant for classification and labelling., The lower explosion point may be 5 - 15 °C below the flash point.	

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 26.09.2025

Version: 3.0

Date / Previous version: 18.09.2023

Previous version: 2.0

Product: **4-Hydroxybutyl Acrylate (4-HBA)**

(ID no. 30041244/SDS_GEN_DE/EN)

Date of print 16.10.2025

Upper explosion limit:	For liquids not relevant for classification and labelling.	
Flash point:	130 °C Literature data.	(Unspecified, other)
Auto-ignition temperature:	335 °C	(Regulation 440/2008/EC, A.15)
Thermal decomposition:	155 °C, 571 J/g (DSC (OECD 113))	
SADT:	Not a substance/mixture liable to self-decomposition according to GHS.	
pH value:	neutral	
Viscosity, kinematic:	10,2 mm ² /s (20 °C)	(calculated (from dynamic viscosity))
Viscosity, dynamic:	10,7 mPa.s (20 °C)	(OECD Guideline 114)
Thixotropy:	not thixotropic	
Solubility in water:	miscible 1.000 g/l (20 °C)	
Solubility (qualitative) solvent(s):	organic solvents miscible	
Partitioning coefficient n-octanol/water (log Kow):	0,77 (25 °C)	(measured)
Vapour pressure:	approx. 0,005 hPa (20 °C)	(measured)
Relative density:	1,0393 (20 °C)	
Density:	1,0393 g/cm ³ (20 °C)	(OECD Guideline 109)
Relative vapour density (air):	4,97 (20 °C)	(calculated)
	Heavier than air.	

Particle characteristics

Particle size distribution: The substance / product is marketed or used in a non solid or granular form. -

9.2. Other information

Information with regard to physical hazard classes

Explosives

Explosion hazard: Based on the chemical structure there is no indication of explosive properties.

Oxidizing properties

Fire promoting properties: Based on its structural properties the product is not classified as oxidizing.

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 26.09.2025

Version: 3.0

Date / Previous version: 18.09.2023

Previous version: 2.0

Product: **4-Hydroxybutyl Acrylate (4-HBA)**

(ID no. 30041244/SDS_GEN_DE/EN)

Date of print 16.10.2025

Pyrophoric properties

Self-ignition temperature: Temperature: 20 °C

Test type: Spontaneous self-ignition at room-temperature.

Based on its structural properties the product is not classified as self-igniting.

Self-heating substances and mixtures

Self heating ability: not applicable, the product is a liquid

Substances and mixtures, which emit flammable gases in contact with water

Formation of flammable gases:

Forms no flammable gases in the presence of water.

Corrosion to metals

No corrosive effect on metal.

Other safety characteristics

pKA:

The substance does not dissociate.

Adsorption/water - soil:

KOC: 10; log KOC: 1

(calculated)

Adsorption to solid soil phase is possible.

Surface tension:

Based on chemical structure, surface activity is not to be expected.

Molar mass:

144,17 g/mol

SAPT-Temperature:

According to SP386 it is ensured that the level of chemical stabilization is sufficient to prevent dangerous polymerization during total duration of carriage. - This information is valid for the recently stabilized product.

Evaporation rate:

Value can be approximated from Henry's Law Constant or vapor pressure.

SECTION 10: Stability and Reactivity

10.1. Reactivity

No hazardous reactions if stored and handled as prescribed/indicated.

Corrosion to metals: No corrosive effect on metal.

Formation of flammable gases:

Remarks:

Forms no flammable gases in the presence of water.

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 26.09.2025

Version: 3.0

Date / Previous version: 18.09.2023

Previous version: 2.0

Product: **4-Hydroxybutyl Acrylate (4-HBA)**

(ID no. 30041244/SDS_GEN_DE/EN)

Date of print 16.10.2025

10.2. Chemical stability

The product is stable if stored and handled as prescribed/indicated.

10.3. Possibility of hazardous reactions

Explosion and fire hazard exists under confined conditions. Ignitable air mixtures can form when the product is heated above the flash point and/or when sprayed or atomized. Formation of explosive gas/air mixtures.

Polymerization coupled with heat formation.

Risk of spontaneous polymerization by oxygen depletion of the liquid phase. Risk of spontaneous polymerization when heated or in the presence of UV radiation. Risk of spontaneous and violent self-polymerization if inhibitor is lost or product is exposed to excessive heat. Polymerization produces gases which may burst closed or confined containers. Reactions may cause ignition.

Risk of spontaneous polymerization in the presence of starters for radical chain reactions (e.g. peroxides). Reacts with nitric acid. Risk of spontaneous polymerization in the presence of oxidizing agents.

Hazardous reactions in presence of mentioned substances to avoid.

The product is stabilized against spontaneous polymerization prior to despatch. The product is stable if stored and handled as prescribed/indicated.

10.4. Conditions to avoid

Avoid heat. Avoid oxygen content above the product of less than 5 %. Avoid UV-light and other radiation with high energy. Avoid direct sunlight. Avoid prolonged storage. Avoid inhibitor loss. Avoid excessive temperatures. Avoid all sources of ignition: heat, sparks, open flame. Avoid freezing. Avoid moisture.

10.5. Incompatible materials

Substances to avoid:

radical formers, free radical initiators, peroxides, mercaptans, nitro-compounds, perborates, azides, ether, ketones, aldehydes, amines, nitrates, nitrites, oxidizing agents, reducing agents, strong bases, alkaline reactive substances, acid anhydrides, acid chlorides, concentrated mineral acids, metal salts
Inert gas

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 26.09.2025

Version: 3.0

Date / Previous version: 18.09.2023

Previous version: 2.0

Product: **4-Hydroxybutyl Acrylate (4-HBA)**

(ID no. 30041244/SDS_GEN_DE/EN)

Date of print 16.10.2025

10.6. Hazardous decomposition products

Hazardous decomposition products:

No hazardous decomposition products if stored and handled as prescribed/indicated.

SECTION 11: Toxicological Information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Assessment of acute toxicity:

Of moderate toxicity after single ingestion. The inhalation of a highly enriched/saturated vapor-air-mixture represents an unlikely acute hazard. Virtually nontoxic after a single skin contact.

Experimental/calculated data:

LD50 rat (oral): 871 mg/kg (BASF-Test)

LC0 rat (by inhalation): 0,17 mg/l 8 h (BASF-Test)

No mortality within the stated exposition time as shown in animal studies. The vapour was tested.

LD50 rat (dermal): > 2.000 mg/kg (OECD Guideline 402)

Irritation

Assessment of irritating effects:

Skin contact causes irritation. May cause severe damage to the eyes.

Experimental/calculated data:

Skin corrosion/irritation

rabbit: Irritant. (BASF-Test)

Skin corrosion/irritation

rabbit: Irritant. (OECD Guideline 404)

Serious eye damage/irritation

rabbit: irreversible damage (Draize test)

Respiratory/Skin sensitization

Assessment of sensitization:

Sensitization after skin contact possible.

Experimental/calculated data:

other In vitro assay: skin sensitizing (In vitro skin sensitization test battery)

Germ cell mutagenicity

Assessment of mutagenicity:

The substance was not mutagenic in bacteria. The substance was mutagenic in various cell culture test systems; however, these results could not be confirmed in tests with mammals. The product has not been fully tested. The statements have been derived in parts from products of a similar structure or composition.

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 26.09.2025

Version: 3.0

Date / Previous version: 18.09.2023

Previous version: 2.0

Product: **4-Hydroxybutyl Acrylate (4-HBA)**

(ID no. 30041244/SDS_GEN_DE/EN)

Date of print 16.10.2025

Carcinogenicity

Assessment of carcinogenicity:

In long-term animal studies in which the substance was given by inhalation, a carcinogenic effect was not observed. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Reproductive toxicity

Assessment of reproduction toxicity:

The results of animal studies gave no indication of a fertility impairing effect. The product has not been fully tested. The statements have been derived in parts from products of a similar structure or composition.

Developmental toxicity

Assessment of teratogenicity:

No indications of a developmental toxic / teratogenic effect were seen in animal studies. The product has not been fully tested. The statements have been derived in parts from products of a similar structure or composition.

Specific target organ toxicity (single exposure)

Assessment of STOT single:

Based on the available information there is no specific target organ toxicity to be expected after a single exposure.

Repeated dose toxicity and Specific target organ toxicity (repeated exposure)

Assessment of repeated dose toxicity:

After repeated exposure the prominent effect is local irritation. The product has not been fully tested. The statements have been derived in parts from products of a similar structure or composition.

Aspiration hazard

not applicable

not applicable

Interactive effects

No data available.

11.2. Information on other hazards

Endocrine disrupting properties

The substance is not identified to have endocrine disrupting properties according to Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 nor is included in the Candidate List of

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 26.09.2025

Version: 3.0

Date / Previous version: 18.09.2023

Previous version: 2.0

Product: **4-Hydroxybutyl Acrylate (4-HBA)**

(ID no. 30041244/SDS_GEN_DE/EN)

Date of print 16.10.2025

substances of very high concern according to EU REACH Article 59 for having endocrine disrupting properties.

SECTION 12: Ecological Information

12.1. Toxicity

Assessment of aquatic toxicity:

Acutely harmful for aquatic organisms. The inhibition of the degradation activity of activated sludge is not anticipated when introduced to biological treatment plants in appropriate low concentrations.

Toxicity to fish:

LC50 (96 h) approx. 14,66 mg/l, *Leuciscus idus* (DIN 38412 Part 15, static)

The details of the toxic effect relate to the nominal concentration.

Aquatic invertebrates:

EC50 (48 h) 23 mg/l, *Daphnia magna* (Directive 79/831/EEC, static)

The details of the toxic effect relate to the nominal concentration.

Aquatic plants:

EC50 (72 h) 13,6 mg/l (growth rate), *Scenedesmus subspicatus* (OECD Guideline 201, static)

The details of the toxic effect relate to the nominal concentration.

Microorganisms/Effect on activated sludge:

EC50 (0,5 h) > 1.000 mg/l, activated sludge, domestic (DIN EN ISO 8192-OECD 209-88/302/EEC,P. C, aerobic)

Nominal concentration.

Chronic toxicity to fish:

No data available.

Chronic toxicity to aquatic invertebrates:

No data available.

Assessment of terrestrial toxicity:

No data available.

Soil living organisms:

No data available.

Terrestrial plants:

No data available.

Other terrestrial non-mammals:

No data available.

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 26.09.2025

Version: 3.0

Date / Previous version: 18.09.2023

Previous version: 2.0

Product: **4-Hydroxybutyl Acrylate (4-HBA)**

(ID no. 30041244/SDS_GEN_DE/EN)

Date of print 16.10.2025

12.2. Persistence and degradability

Assessment biodegradation and elimination (H₂O):

Readily biodegradable (according to OECD criteria).

Elimination information:

90 - 100 % DOC reduction (21 d) (OECD 301 A (new version)) (aerobic, activated sludge, domestic, non-adapted)

Assessment of stability in water:

According to structural properties, hydrolysis is not expected/probable.

Information on Stability in Water (Hydrolysis):

t_{1/2} 1,061 a, 50 % (25 °C, pH value 8), (calculated, other)

12.3. Bioaccumulative potential

Assessment bioaccumulation potential:

Because of the n-octanol/water distribution coefficient (log Pow) accumulation in organisms is not to be expected.

Bioaccumulation potential:

No data available.

12.4. Mobility in soil

Assessment transport between environmental compartments:

Volatility: The substance will not evaporate into the atmosphere from the water surface.

Adsorption in soil: Adsorption to solid soil phase is not expected.

12.5. Results of PBT and vPvB assessment

According to Annex XIII of Regulation (EC) No.1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH): Not fulfilling PBT (persistent/bioaccumulative/toxic) criteria.

According to Annex XIII of Regulation (EC) No.1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH): Not fulfilling vPvB (very persistent/very bioaccumulative) criteria.

According to Annex XIII of Regulation (EC) No.1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH): No conclusion can be reached based on available information. No data available.

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 26.09.2025

Version: 3.0

Date / Previous version: 18.09.2023

Previous version: 2.0

Product: **4-Hydroxybutyl Acrylate (4-HBA)**

(ID no. 30041244/SDS_GEN_DE/EN)

Date of print 16.10.2025

12.6. Endocrine disrupting properties

The substance is not identified to have endocrine disrupting properties according to Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 nor is included in the Candidate List of substances of very high concern according to EU REACH Article 59 for having endocrine disrupting properties.

12.7. Other adverse effects

| The substance is not listed in Regulation (EU) 2024/590 on substances that deplete the ozone layer.

Results of PMT and vPvM assessment

| Substance is not included in the list established in accordance with Article 59(1) of Regulation (EC) No 1907/2006 for having PMT/vPvM properties.

Additional information

Adsorbable organically-bound halogen (AOX):
This product contains no organically-bound halogen.

SECTION 13: Disposal Considerations

13.1. Waste treatment methods

Must be sent to a suitable incineration plant, observing local regulations.

Contaminated packaging:
Uncleaned empties should be disposed of in the same manner as the contents.

SECTION 14: Transport Information

Land transport

ADR

	Not classified as a dangerous good under transport regulations
UN number or ID number:	Not applicable
UN proper shipping name:	Not applicable
Transport hazard class(es):	Not applicable
Packing group:	Not applicable
Environmental hazards:	Not applicable
Special precautions for user	None known

RID

Not classified as a dangerous good under transport regulations

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 26.09.2025

Version: 3.0

Date / Previous version: 18.09.2023

Previous version: 2.0

Product: **4-Hydroxybutyl Acrylate (4-HBA)**

(ID no. 30041244/SDS_GEN_DE/EN)

Date of print 16.10.2025

UN number or ID number:	Not applicable
UN proper shipping name:	Not applicable
Transport hazard class(es):	Not applicable
Packing group:	Not applicable
Environmental hazards:	Not applicable
Special precautions for user:	None known

Inland waterway transport

ADN

	Not classified as a dangerous good under transport regulations
UN number or ID number:	Not applicable
UN proper shipping name:	Not applicable
Transport hazard class(es):	Not applicable
Packing group:	Not applicable
Environmental hazards:	Not applicable
Special precautions for user:	None known

Transport in inland waterway vessel

Not evaluated

Sea transport

IMDG

	Not classified as a dangerous good under transport regulations
UN number or ID number:	Not applicable
UN proper shipping name:	Not applicable
Transport hazard class(es):	Not applicable
Packing group:	Not applicable
Environmental hazards:	Not applicable
Special precautions for user:	None known

Air transport

IATA/ICAO

	Not classified as a dangerous good under transport regulations
UN number or ID number:	Not applicable
UN proper shipping name:	Not applicable
Transport hazard class(es):	Not applicable
Packing group:	Not applicable
Environmental hazards:	Not applicable

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 26.09.2025

Version: 3.0

Date / Previous version: 18.09.2023

Previous version: 2.0

Product: **4-Hydroxybutyl Acrylate (4-HBA)**

(ID no. 30041244/SDS_GEN_DE/EN)

Date of print 16.10.2025

Special precautions for user None known

14.1. UN number or ID number

See corresponding entries for "UN number or ID number" for the respective regulations in the tables above.

14.2. UN proper shipping name

See corresponding entries for "UN proper shipping name" for the respective regulations in the tables above.

14.3. Transport hazard class(es)

See corresponding entries for "Transport hazard class(es)" for the respective regulations in the tables above.

14.4. Packing group

See corresponding entries for "Packing group" for the respective regulations in the tables above.

14.5. Environmental hazards

See corresponding entries for "Environmental hazards" for the respective regulations in the tables above.

14.6. Special precautions for user

See corresponding entries for "Special precautions for user" for the respective regulations in the tables above.

14.7. Maritime transport in bulk according to IMO instruments

Maritime transport in bulk is not intended.

SECTION 15: Regulatory Information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Prohibitions, Restrictions and Authorizations

Annex XVII of Regulation (EC) No 1907/2006: Number on List: 3, 75

Hazardous Incident Ordinance (Germany):

Listed in above regulation: no

| Classification applies for standard conditions of temperature and pressure.

Directive 2012/18/EU - Control of Major Accident Hazards involving dangerous substances (EU):

Listed in above regulation: no

| Classification applies for standard conditions of temperature and pressure.

Classification according to 'TA-Luft' (Germany):

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 26.09.2025

Version: 3.0

Date / Previous version: 18.09.2023

Previous version: 2.0

Product: **4-Hydroxybutyl Acrylate (4-HBA)**

(ID no. 30041244/SDS_GEN_DE/EN)

Date of print 16.10.2025

5.2.5 class I: Organic gases class I
acrylic acid

0,30 %

Water hazard class (§6 AwSV para.4 (Legal binding announcement of the substance in the Federal Gazette)): (1) Weakly water polluting. ID-No.: 8905

The specifications of the Technical Rule for Hazardous Substances (TRGS) 401 must be observed (TRGS 401: Risks resulting from skin contact - identification, assessment, measures).

German Regulation TA Luft (Technical Instruction on Air Quality Control, i.e. first Directive to the Federal Immission Control Ordinance)

Law on the Protection of Working Youth

15.2. Chemical Safety Assessment

Chemical Safety Assessment performed

SECTION 16: Other Information

Assessment of the hazard classes according to UN GHS criteria (most recent version)

Aquatic Acute 3
Acute Tox. 4 (oral)
Skin Irrit. 2
Eye Dam. 1
Skin Sens. 1

This product is of industrial quality and unless otherwise specified or agreed intended exclusively for industrial use. Any other intended applications should be discussed with the manufacturer. Safe Handling and Storage aspects are covered in a brochure which is available on request.

Full text of the classifications, including the hazard classes and the hazard statements, if mentioned in section 2 or 3:

Acute Tox.	Acute toxicity
Skin Irrit.	Skin irritation
Eye Dam.	Serious eye damage
Skin Sens.	Skin sensitization
Skin Corr.	Skin corrosion
Aquatic Chronic	Hazardous to the aquatic environment - chronic
Aquatic Acute	Hazardous to the aquatic environment - acute
Flam. Liq.	Flammable liquids
STOT SE	Specific target organ toxicity — single exposure
H318	Causes serious eye damage.
H315	Causes skin irritation.
H302	Harmful if swallowed.
H317	May cause an allergic skin reaction.
H314	Causes severe skin burns and eye damage.
H311	Toxic in contact with skin.

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 26.09.2025

Version: 3.0

Date / Previous version: 18.09.2023

Previous version: 2.0

Product: **4-Hydroxybutyl Acrylate (4-HBA)**

(ID no. 30041244/SDS_GEN_DE/EN)

Date of print 16.10.2025

H302 + H332	Harmful if swallowed or if inhaled.
H412	Harmful to aquatic life with long lasting effects.
H226	Flammable liquid and vapour.
H302 + H312 + H332	Harmful if swallowed, in contact with skin or if inhaled.
H411	Toxic to aquatic life with long lasting effects.
H400	Very toxic to aquatic life.

Abbreviations

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road.
 ADN = The European Agreement concerning the International Carriage of Dangerous Goods by Inland waterways. ATE = Acute Toxicity Estimates. CAO = Cargo Aircraft Only. CAS = Chemical Abstract Service. CLP = Classification, Labelling and Packaging of substances and mixtures. DIN = German national organization for standardization. DNEL = Derived No Effect Level. EC50 = Effective concentration median for 50% of the population. EC = European Community. EN = European Standards. IARC = International Agency for Research on Cancer. IATA = International Air Transport Association. IBC-Code = Intermediate Bulk Container code. IMDG = International Maritime Dangerous Goods Code. ISO = International Organization for Standardization. STEL = Short-Term Exposure Limit. LC50 = Lethal concentration median for 50% of the population. LD50 = Lethal dose median for 50% of the population. TLV = Threshold Limit Value. MARPOL = The International Convention for the Prevention of Pollution from Ships. NEN = Dutch Norm. NOEC = No Observed Effect Concentration. OEL = Occupational Exposure Limit. OECD = Organization for Economic Cooperation and Development. PBT = Persistent, Bioaccumulative and Toxic. PNEC = Predicted No Effect Level. PPM = Parts per million. RID = The European Agreement concerning the International Carriage of Dangerous Goods by Rail. TWA = Time Weight Average. UN-number = UN number at transport. vPvB = very Persistent and very Bioaccumulative.

The data contained in this safety data sheet are based on our current knowledge and experience and describe the product only with regard to safety requirements. This safety data sheet is neither a Certificate of Analysis (CoA) nor technical data sheet and shall not be mistaken for a specification agreement. Identified uses in this safety data sheet do neither represent an agreement on the corresponding contractual quality of the substance/mixture nor a contractually designated use. It is the responsibility of the recipient of the product to ensure any proprietary rights and existing laws and legislation are observed.

Vertical lines in the left hand margin indicate an amendment from the previous version.

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 26.09.2025

Version: 3.0

Date / Previous version: 18.09.2023

Previous version: 2.0

Product: **4-Hydroxybutyl Acrylate (4-HBA)**

(ID no. 30041244/SDS_GEN_DE/EN)

Date of print 16.10.2025

Annex: Exposure Scenarios

Index

1. Polymer production, Use as Monomer, (use in industrial settings)
IS; SU8, SU9; ERC6c, ERC6d; PROC1, PROC2, PROC3, PROC4, PROC5, PROC8a, PROC8b, PROC9; PC19, PC32

2. Use as laboratory reagent/agent, (use in industrial settings)
IS; SU8, SU9, SU24; ERC1; PROC15; PC19, PC21

1. Short title of exposure scenario

Polymer production, Use as Monomer, (use in industrial settings)
IS; SU8, SU9; ERC6c, ERC6d; PROC1, PROC2, PROC3, PROC4, PROC5, PROC8a, PROC8b, PROC9; PC19, PC32

Control of exposure and risk management measures

Contributing exposure scenario	
Use descriptors covered	ERC6c: Use of monomer in polymerisation processes at industrial site (inclusion or not into/onto article)
Operational conditions	
Annual amount used in the EU	999.000 kg
Minimum emission days per year	60
Emission factor air	0,001 %
Emission factor water	0,1 %
Emission factor soil	0 %
Receive Surf. Water (Flow Rate).	43.560 m3/min
Dilution factor river	187,75
Dilution factor coast	1.877,47
Risk Management Measures	
Soil treatment measures considered suitable are, e.g.	No application of sludge to soil
Type of STP	Municipal STP
Assumed sewage treatment plant flow (m3/d)	335.890 m3/d
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Environment
Risk Characterization Ratio (RCR)	0,022227

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 26.09.2025

Version: 3.0

Date / Previous version: 18.09.2023

Previous version: 2.0

Product: **4-Hydroxybutyl Acrylate (4-HBA)**

(ID no. 30041244/SDS_GEN_DE/EN)

Date of print 16.10.2025

	Risk from environmental exposure is driven by marine water.
Maximum amount of safe use	44.946 kg/d
Risk from environmental exposure is driven by marine water.	

Contributing exposure scenario

Use descriptors covered	ERC6d: Use of reactive process regulators in polymerisation processes at industrial site (inclusion or not into/onto article) As no environmental hazard was identified no environmental-related exposure assessment and risk characterization was performed.
Operational conditions	

Contributing exposure scenario

Use descriptors covered	PROC1: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions. Use domain: industrial
Operational conditions	
Concentration of the substance	4-Hydroxybutyl acrylate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	0,5 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Assumes activities are at ambient temperature.	

Risk Management Measures

Wear chemically resistant gloves in combination with 'basic' employee training.	Effectiveness: 90 %
Use suitable eye protection.	

Exposure estimate and reference to its source

Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	0,0034 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,000418
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	0,0601 mg/m ³
Risk Characterization Ratio (RCR)	0,030338

Guidance to Downstream Users

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 26.09.2025

Version: 3.0

Date / Previous version: 18.09.2023

Previous version: 2.0

Product: **4-Hydroxybutyl Acrylate (4-HBA)**

(ID no. 30041244/SDS_GEN_DE/EN)

Date of print 16.10.2025

For scaling see: <http://www.ecetoc.org/tra>

Contributing exposure scenario	
Use descriptors covered	PROC2: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions Use domain: industrial
Operational conditions	
Concentration of the substance	4-Hydroxybutyl acrylate Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	0,5 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Risk Management Measures	
Local exhaust ventilation	Effectiveness: 90 %
Wear chemically resistant gloves in combination with 'basic' employee training.	Effectiveness: 90 %
Use suitable eye protection.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	0,1371 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,016725
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	0,6007 mg/m ³
Risk Characterization Ratio (RCR)	0,303385
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition Use domain: industrial
Operational conditions	
Concentration of the substance	4-Hydroxybutyl acrylate Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 26.09.2025

Version: 3.0

Date / Previous version: 18.09.2023

Previous version: 2.0

Product: **4-Hydroxybutyl Acrylate (4-HBA)**

(ID no. 30041244/SDS_GEN_DE/EN)

Date of print 16.10.2025

Vapour pressure of the substance during use	0,5 Pa
Duration and Frequency of activity	240 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Risk Management Measures	
Local exhaust ventilation	Effectiveness: 90 %
Wear chemically resistant gloves in combination with 'basic' employee training.	Effectiveness: 90 %
Use suitable eye protection.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	0,0686 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,008362
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	1,0813 mg/m ³
Risk Characterization Ratio (RCR)	0,546092
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC4: Chemical production where opportunity for exposure arises Use domain: industrial
Operational conditions	
Concentration of the substance	4-Hydroxybutyl acrylate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	0,5 Pa
Duration and Frequency of activity	240 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Risk Management Measures	
Wear suitable respiratory protection.	Effectiveness: 90 %
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %
Wear chemically resistant gloves in combination with 'basic' employee training.	Effectiveness: 90 %
Use suitable eye protection.	

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 26.09.2025

Version: 3.0

Date / Previous version: 18.09.2023

Previous version: 2.0

Product: **4-Hydroxybutyl Acrylate (4-HBA)**

(ID no. 30041244/SDS_GEN_DE/EN)

Date of print 16.10.2025

Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	0,6857 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,083624
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	1,2615 mg/m ³
Risk Characterization Ratio (RCR)	0,637108
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC5: Mixing or blending in batch processes Use domain: industrial
Operational conditions	
Concentration of the substance	4-Hydroxybutyl acrylate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	0,5 Pa
Duration and Frequency of activity	240 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Risk Management Measures	
Local exhaust ventilation	Effectiveness: 90 %
Wear chemically resistant gloves in combination with specific activity training	Effectiveness: 95 %
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %
Use suitable eye protection.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	0,6857 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,083624
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	1,2615 mg/m ³
Risk Characterization Ratio (RCR)	0,637108
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 26.09.2025

Version: 3.0

Date / Previous version: 18.09.2023

Previous version: 2.0

Product: **4-Hydroxybutyl Acrylate (4-HBA)**

(ID no. 30041244/SDS_GEN_DE/EN)

Date of print 16.10.2025

Use descriptors covered	PROC8a: Transfer of substance or mixture (charging and discharging) at non-dedicated facilities Use domain: industrial
Operational conditions	
Concentration of the substance	4-Hydroxybutyl acrylate Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	0,5 Pa
Duration and Frequency of activity	240 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Risk Management Measures	
Local exhaust ventilation	Effectiveness: 90 %
Wear chemically resistant gloves in combination with 'basic' employee training.	Effectiveness: 90 %
Provide a good standard of general or controlled ventilation (5 to 10 air changes per hour)	Effectiveness: 70 %
Use suitable eye protection.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	1,3714 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,167247
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	1,0813 mg/m ³
Risk Characterization Ratio (RCR)	0,546092
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC8b: Transfer of substance or mixture (charging and discharging) at dedicated facilities Use domain: industrial
Operational conditions	
Concentration of the substance	4-Hydroxybutyl acrylate Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	0,5 Pa
	Air concentration is limited to the saturated air

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 26.09.2025

Version: 3.0

Date / Previous version: 18.09.2023

Previous version: 2.0

Product: **4-Hydroxybutyl Acrylate (4-HBA)**

(ID no. 30041244/SDS_GEN_DE/EN)

Date of print 16.10.2025

	concentration of the pure compound.
Duration and Frequency of activity	240 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Risk Management Measures	
Local exhaust ventilation	Effectiveness: 95 %
Wear chemically resistant gloves in combination with 'basic' employee training.	Effectiveness: 90 %
Use suitable eye protection.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	1,3714 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,167247
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	0,8729 mg/m ³
Risk Characterization Ratio (RCR)	0,440838
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing). Use domain: industrial
Operational conditions	
Concentration of the substance	4-Hydroxybutyl acrylate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	0,5 Pa
Duration and Frequency of activity	240 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Risk Management Measures	
Local exhaust ventilation	Effectiveness: 90 %
Wear chemically resistant gloves in combination with 'basic' employee training.	Effectiveness: 90 %
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %
Use suitable eye protection.	
Exposure estimate and reference to its source	

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 26.09.2025

Version: 3.0

Date / Previous version: 18.09.2023

Previous version: 2.0

Product: **4-Hydroxybutyl Acrylate (4-HBA)**

(ID no. 30041244/SDS_GEN_DE/EN)

Date of print 16.10.2025

Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	0,6857 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,083624
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	1,2615 mg/m ³
Risk Characterization Ratio (RCR)	0,637108
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

2. Short title of exposure scenario

Use as laboratory reagent/agent, (use in industrial settings)

IS; SU8, SU9, SU24; ERC1; PROC15; PC19, PC21

Control of exposure and risk management measures

Contributing exposure scenario	
Use descriptors covered	ERC6c: Use of monomer in polymerisation processes at industrial site (inclusion or not into/onto article)
Operational conditions	
Annual amount used in the EU	1.000 kg
Minimum emission days per year	20
Emission factor air	5 %
Emission factor water	5 %
Emission factor soil	0 %
Receive Surf. Water (Flow Rate).	18.000 m3/d
Dilution factor river	10
Dilution factor coast	100
Risk Management Measures	
Soil treatment measures considered suitable are, e.g.	No application of sludge to soil
Type of STP	Municipal STP
Assumed sewage treatment plant flow (m3/d)	2.000 m3/d
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Environment
Risk Characterization Ratio (RCR)	0,095597
Risk from environmental exposure is driven by marine	

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 26.09.2025

Version: 3.0

Date / Previous version: 18.09.2023

Previous version: 2.0

Product: **4-Hydroxybutyl Acrylate (4-HBA)**

(ID no. 30041244/SDS_GEN_DE/EN)

Date of print 16.10.2025

	water.
Maximum amount of safe use	52,3 kg/d
Risk from environmental exposure is driven by marine water.	

Contributing exposure scenario	
Use descriptors covered	PROC15: Use a laboratory reagent. Use domain: industrial
Operational conditions	
Concentration of the substance	4-Hydroxybutyl acrylate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	0,5 Pa
	Air concentration is limited to the saturated air concentration of the pure compound.
Duration and Frequency of activity	60 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Risk Management Measures	
Local exhaust ventilation	Effectiveness: 90 %
Wear chemically resistant gloves in combination with 'basic' employee training.	Effectiveness: 90 %
Use suitable eye protection.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	0,0343 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,004181
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	0,5819 mg/m ³
Risk Characterization Ratio (RCR)	0,293892
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	
