

# Safety data sheet

Page: 1/70

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 21.09.2023

Version: 2.0

Date previous version: 31.08.2023

Previous version: 1.0

Date / First version: 31.08.2023

Product: **BUTYL GLYCOL ACETATE**

(ID no. 30034846/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

## BUTYL GLYCOL ACETATE

Chemical name: 2-butoxyethyl acetate

CAS Number: 112-07-2

REACH registration number: 01-2119475112-47-0002

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses: Chemical, solvent(s)

For the detailed identified uses of the product see appendix of the safety data sheet.

### 1.3. Details of the supplier of the safety data sheet

Company:

BASF SE  
67056 Ludwigshafen  
GERMANY

Contact address:

BASF Hellas S.A.  
Sindos Industrial Area  
57022 Sindos  
GREECE

Telephone: +30 2310 797-195

E-mail address: gr-psr-hellas@basf.com

### 1.4. Emergency telephone number

Greek Poison Information Centre  
0030 210 7793777 (24 hours / 7 days)

International emergency number:

Telephone: +49 180 2273-112

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 21.09.2023

Version: 2.0

Date previous version: 31.08.2023

Previous version: 1.0

Date / First version: 31.08.2023

Product: **BUTYL GLYCOL ACETATE**

(ID no. 30034846/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

## SECTION 2: Hazards Identification

### 2.1. Classification of the substance or mixture

According to Regulation (EC) No 1272/2008 [CLP]

Acute Tox. 4 (Inhalation - vapour) H332 Harmful if inhaled.

Acute Tox. 4 (oral) H302 Harmful if swallowed.

Acute Tox. 4 (dermal) H312 Harmful in contact with skin.

For the classifications not written out in full in this section the full text can be found in section 16.

### 2.2. Label elements

According to Regulation (EC) No 1272/2008 [CLP]

Pictogram:



Signal Word:

Warning

Hazard Statement:

H302 + H312 + H332 Harmful if swallowed, in contact with skin or if inhaled.

Precautionary Statements (Prevention):

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves and clothing.

P260 Do not breathe mist or vapour.

Precautionary Statements (Response):

P312 Call a POISON CENTER or physician if you feel unwell.

P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Precautionary Statements (Disposal):

P501 Dispose of contents and container to hazardous or special waste collection point.

Hazard determining component(s) for labelling: 2-butoxyethyl acetate

### 2.3. Other hazards

According to Regulation (EC) No 1272/2008 [CLP]

Product does not contain a substance above legal limits included in the list established in accordance with Article 59(1) of Regulation (EC) No 1907/2006 for having endocrine disrupting

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 21.09.2023

Version: 2.0

Date previous version: 31.08.2023

Previous version: 1.0

Date / First version: 31.08.2023

Product: **BUTYL GLYCOL ACETATE**

(ID no. 30034846/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

properties or is identified to have endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605. If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture. See section 12 - Results of PBT and vPvB assessment.

## SECTION 3: Composition/Information on Ingredients

### 3.1. Substances

#### Chemical nature

2-butoxyethyl acetate

Content (W/W):  $\geq 99\%$

Acute Tox. 4 (Inhalation - vapour)

CAS Number: 112-07-2

Acute Tox. 4 (oral)

EC-Number: 203-933-3

Acute Tox. 4 (dermal)

INDEX-Number: 607-038-00-2

H302 + H312 + H332

#### Regulatory relevant ingredients

2-butoxyethyl acetate

Content (W/W):  $\geq 99\% - \leq 100\%$

Acute Tox. 4 (Inhalation - vapour)

%

Acute Tox. 4 (oral)

CAS Number: 112-07-2

Acute Tox. 4 (dermal)

EC-Number: 203-933-3

H302 + H312 + H332

INDEX-Number: 607-038-00-2

For the classifications not written out in full in this section, including the hazard classes and the hazard statements, the full text is listed in section 16.

### 3.2. Mixtures

Not applicable

## SECTION 4: First-Aid Measures

### 4.1. Description of first aid measures

If the patient is likely to become unconscious, place and transport in stable sideways position (recovery position). First aid personnel should pay attention to their own safety.

Remove contaminated clothing.

If inhaled:

Keep patient calm, remove to fresh air, seek medical attention.

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 21.09.2023

Version: 2.0

Date previous version: 31.08.2023

Previous version: 1.0

Date / First version: 31.08.2023

Product: **BUTYL GLYCOL ACETATE**

(ID no. 30034846/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

On skin contact:

Wash thoroughly with soap and water

On contact with eyes:

Wash affected eyes for at least 15 minutes under running water with eyelids held open.

On ingestion:

Immediately rinse mouth and then drink 200-300 ml of water, seek medical attention.

#### **4.2. Most important symptoms and effects, both acute and delayed**

Symptoms: Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11.

Hazards: Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11. (Further) symptoms and / or effects are not known so far

#### **4.3. Indication of any immediate medical attention and special treatment needed**

Treatment: Treat according to symptoms (decontamination, vital functions), no known specific antidote.

---

### **SECTION 5: Fire-Fighting Measures**

#### **5.1. Extinguishing media**

Suitable extinguishing media:

dry powder, water spray, carbon dioxide, foam

Unsuitable extinguishing media for safety reasons:

water jet

Additional information:

Use extinguishing measures to suit surroundings.

#### **5.2. Special hazards arising from the substance or mixture**

Advice: Flammable liquid Cool endangered containers with water-spray. See SDS section 7 - Handling and storage.

#### **5.3. Advice for fire-fighters**

Special protective equipment:

Wear a self-contained breathing apparatus. Special protective equipment for firefighters

Further information:

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 21.09.2023

Version: 2.0

Date previous version: 31.08.2023

Previous version: 1.0

Date / First version: 31.08.2023

Product: **BUTYL GLYCOL ACETATE**

(ID no. 30034846/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

| Evacuate area of all unnecessary personnel. Fight fire from maximum distance.

| Extend fire extinguishing measures to the surroundings. Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

---

## SECTION 6: Accidental Release Measures

High risk of slipping due to leakage/spillage of product.

| Release of substance/product can cause fire or explosion. Shut off or stop source of leak. Shut off or stop released substance/product under safe conditions.

Pack in tightly closed containers for disposal.

### 6.1. Personal precautions, protective equipment and emergency procedures

Avoid inhalation. Handle in accordance with good industrial hygiene and safety practice.

| Avoid all sources of ignition: heat, sparks, open flame. Use antistatic tools.

### 6.2. Environmental precautions

Do not discharge into the subsoil/soil. Do not discharge into drains/surface waters/groundwater.

### 6.3. Methods and material for containment and cleaning up

For large amounts: Pump off product.

For residues: Pick up with suitable absorbent material (e.g. sand, sawdust, general-purpose binder, kieselguhr). Dispose of absorbed material in accordance with regulations. Spills should be contained, solidified, and placed in suitable containers for disposal.

### 6.4. Reference to other sections

Information regarding exposure controls/personal protection and disposal considerations can be found in section 8 and 13.

---

## SECTION 7: Handling and Storage

### 7.1. Precautions for safe handling

Ensure thorough ventilation of stores and work areas. Prevent contact with air/oxygen (formation of peroxide). Handle in accordance with good industrial hygiene and safety practice.

Protection against fire and explosion:

Prevent electrostatic charge - sources of ignition should be kept well clear - fire extinguishers should be kept handy. Avoid all sources of ignition: heat, sparks, open flame. Ground all transfer equipment properly to prevent electrostatic discharge.

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 21.09.2023

Version: 2.0

Date previous version: 31.08.2023

Previous version: 1.0

Date / First version: 31.08.2023

Product: **BUTYL GLYCOL ACETATE**

(ID no. 30034846/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

## 7.2. Conditions for safe storage, including any incompatibilities

Further information on storage conditions: Keep container tightly closed in a cool, well-ventilated place. Protect from air.

## 7.3. Specific end use(s)

See exposure scenario(s) in the attachment to this safety data sheet.

---

## SECTION 8: Exposure Controls/Personal Protection

### 8.1. Control parameters

Components with occupational exposure limits

112-07-2: 2-butoxyethyl acetate

TWA value 133 mg/m<sup>3</sup> ; 20 ppm (OEL (EU))

indicative

Skin Designation (OEL (EU))

The substance can be absorbed through the skin.

STEL value 333 mg/m<sup>3</sup> ; 50 ppm (OEL (EU))

indicative

TWA value 135 mg/m<sup>3</sup> ; 20 ppm (OEL (GR))

STEL value 270 mg/m<sup>3</sup> ; 40 ppm (OEL (GR))

Ceiling limit value/factor: 15 min

### PNEC

freshwater: 0,304 mg/l

marine water: 0,0304 mg/l

intermittent release: 0,56 mg/l

sediment (freshwater): 2,03 mg/kg

sediment (marine water): 0,203 mg/kg

soil: 0,42 mg/kg

STP: 90 mg/l

oral (secondary poisoning): 0,06 mg/kg

### DNEL

worker:

Long-term exposure- systemic effects, dermal: 169 mg/kg

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 21.09.2023

Version: 2.0

Date previous version: 31.08.2023

Previous version: 1.0

Date / First version: 31.08.2023

Product: **BUTYL GLYCOL ACETATE**

(ID no. 30034846/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

worker:

Long-term exposure- systemic effects, Inhalation: 133 mg/m<sup>3</sup>

worker:

Short-term exposure - local effects, Inhalation: 333 mg/m<sup>3</sup>

consumer:

Long-term exposure- systemic effects, dermal: 102 mg/kg

consumer:

Long-term exposure- systemic effects, oral: 8,6 mg/kg

consumer:

Short-term exposure - systemic effects, oral: 36 mg/kg

consumer:

Long-term exposure- systemic effects, Inhalation: 80 mg/m<sup>3</sup>

consumer:

Short-term exposure - local effects, Inhalation: 200 mg/m<sup>3</sup>

worker:

Short-term exposure - systemic effects, dermal: 120 mg/kg

consumer:

Short-term exposure - systemic effects, dermal: 72 mg/kg

## 8.2. Exposure controls

### Personal protective equipment

Respiratory protection:

Wear respiratory protection if ventilation is inadequate. Gas filter for gases/vapours of organic compounds (boiling point >65 °C, e. g. EN 14387 Type A)

Hand protection:

Chemical resistant protective gloves (EN ISO 374-1)

Suitable materials also with prolonged, direct contact (Recommended: Protective index 6, corresponding > 480 minutes of permeation time according to EN ISO 374-1):

butyl rubber (butyl) - 0.7 mm coating thickness

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 21.09.2023

Version: 2.0

Date previous version: 31.08.2023

Previous version: 1.0

Date / First version: 31.08.2023

Product: **BUTYL GLYCOL ACETATE**

(ID no. 30034846/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

Manufacturer's directions for use should be observed because of great diversity of types.

Supplementary note: The specifications are based on tests, literature data and information of glove manufacturers or are derived from similar substances by analogy. Due to many conditions (e.g. temperature) it must be considered, that the practical usage of a chemical-protective glove in practice may be much shorter than the permeation time determined through testing.

Eye protection:

Safety glasses with side-shields (frame goggles) (e.g. EN 166)

Body protection:

Body protection must be chosen depending on activity and possible exposure, e.g. apron, protecting boots, chemical-protection suit (according to EN 14605 in case of splashes or EN ISO 13982 in case of dust).

#### General safety and hygiene measures

Avoid inhalation of vapour. Avoid contact with the skin, eyes and clothing. Wearing of closed work clothing is required additionally to the stated personal protection equipment. Handle in accordance with good industrial hygiene and safety practice.

#### Environmental exposure controls

All appropriate measures must be taken to prevent the release of this product to the environment and to limit the dispersion of any release when it occurs. Suitable risk management measures should be in place.

---

## SECTION 9: Physical and Chemical Properties

### 9.1. Information on basic physical and chemical properties

State of matter:	liquid	
Form:	liquid	
Colour:	colourless	
Odour:	ester-like	
Odour threshold:		
	not determined	
Melting point:	-63,5 °C (1.013,25 hPa) Literature data.	
Boiling range:	184 - 195 °C (1.013 hPa)	(DIN 53171)
Flammability:	Combustible liquid.	(derived from flash point)



BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 21.09.2023

Version: 2.0

Date previous version: 31.08.2023

Previous version: 1.0

Date / First version: 31.08.2023

Product: **BUTYL GLYCOL ACETATE**

(ID no. 30034846/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

Lower explosion limit:	1,0 %(V) (73 °C) The lower explosion point of the substance/mixture has been determined. The explosion point describes the temperature of a flammable liquid at which the concentration of the saturated vapour mixed with air equals the lower explosion limit.	
Upper explosion limit:	6,1 %(V) (106,9 °C) The upper explosion point of the substance/mixture has been determined. This explosion point describes the temperature of a flammable liquid at which the concentration of the saturated vapour mixed with air equals the upper explosion limit.	
Flash point:	78 °C	(closed cup)
Auto-ignition temperature:	280 °C	
Thermal decomposition:	No decomposition if stored and handled as prescribed/indicated.	
pH value:	not applicable, of low solubility	
Viscosity, kinematic:	1,923 mm <sup>2</sup> /s (20 °C)	
Viscosity, dynamic:	1,8 mPa.s (20 °C)	
Thixotropy:	Literature data.	
Solubility in water:	not thixotropic	
	Literature data.	
	15 g/l (20 °C)	
Solubility (qualitative) solvent(s):	organic solvents soluble	
Partitioning coefficient n-octanol/water (log Kow):	1,51 (25 °C; pH value: 7) The data refers to the undissociated form of the substance.	(OECD Guideline 107)
Vapour pressure:	0,5 hPa (20 °C)	
	Literature data.	
Relative density:	0,935 - 0,942 (20 °C)	
Density:	0,935 - 0,942 g/cm <sup>3</sup> (20 °C)	(DIN 51757)

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 21.09.2023

Version: 2.0

Date previous version: 31.08.2023

Previous version: 1.0

Date / First version: 31.08.2023

Product: **BUTYL GLYCOL ACETATE**

(ID no. 30034846/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

Relative vapour density (air):> 1 (estimated)  
(20 °C)  
Heavier than air.

#### Particle characteristics

Particle size distribution: The substance / product is marketed or used in a non solid or granular form. -

## **9.2. Other information**

### **Information with regard to physical hazard classes**

#### Explosives

Explosion hazard: Based on the chemical structure there is no indication of explosive properties.  
Impact sensitivity: not shock-sensitive  
Based on the chemical structure there is no shock-sensitivity.

#### Oxidizing properties

Fire promoting properties: Based on its structural properties the product is not classified as oxidizing.

#### Pyrophoric properties

Self-ignition temperature: Test type: Spontaneous self-ignition at room-temperature.  
Based on its structural properties the product is not classified as self-igniting.

#### Self-heating substances and mixtures

Self heating ability: not applicable, the product is a liquid

#### Substances and mixtures, which emit flammable gases in contact with water

Formation of flammable gases:  
Forms no flammable gases in the presence of water.

#### Corrosion to metals

Corrosive effects to metal are not anticipated.

### **Other safety characteristics**

pKA:  
The substance does not dissociate.  
Adsorption/water - soil: KOC: 15,08; log KOC: 1,18 (calculated)  
Surface tension:  
Based on chemical structure, surface activity is not to be expected.  
Molar mass: 160,21 g/mol  
SAPT-Temperature:

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 21.09.2023

Version: 2.0

Date previous version: 31.08.2023

Previous version: 1.0

Date / First version: 31.08.2023

Product: **BUTYL GLYCOL ACETATE**

(ID no. 30034846/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

Evaporation rate: Study scientifically not justified.  
Value can be approximated from Henry's Law Constant or vapor pressure.

---

## SECTION 10: Stability and Reactivity

### 10.1. Reactivity

| When heated can give off ignitable vapours.

Corrosion to metals:	Corrosive effects to metal are not anticipated.
Formation of flammable gases:	Remarks: Forms no flammable gases in the presence of water.

### 10.2. Chemical stability

The product is stable if stored and handled as prescribed/indicated.

### 10.3. Possibility of hazardous reactions

Reacts with strong oxidizing agents.

### 10.4. Conditions to avoid

No special precautions other than good housekeeping of chemicals.

### 10.5. Incompatible materials

Substances to avoid:  
strong oxidizing agents

### 10.6. Hazardous decomposition products

Hazardous decomposition products:  
No hazardous decomposition products if stored and handled as prescribed/indicated.

---

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 21.09.2023

Version: 2.0

Date previous version: 31.08.2023

Previous version: 1.0

Date / First version: 31.08.2023

Product: **BUTYL GLYCOL ACETATE**

(ID no. 30034846/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

## SECTION 11: Toxicological Information

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

Assessment of acute toxicity:

Of moderate toxicity after single ingestion. Of moderate toxicity after short-term skin contact. The inhalation of a highly enriched/saturated vapor-air-mixture represents an unlikely acute hazard. The European Union (EU) has classified this substance as 'harmful' after inhalation.

Experimental/calculated data:

LD50 rat (oral): approx. 1.880 mg/kg (OECD Guideline 401)

LC50 rat (by inhalation): > 400 ppm 4 h (OECD Guideline 403)

No mortality was observed. Highest concentration technically achievable. The vapour was tested.

LD50 rabbit (dermal): approx. 1.500 mg/kg

#### Irritation

Assessment of irritating effects:

Not irritating to the skin. Not irritating to the eyes.

Experimental/calculated data:

Skin corrosion/irritation

rabbit: non-irritant (BASF-Test)

Serious eye damage/irritation

rabbit: non-irritant (BASF-Test)

#### Respiratory/Skin sensitization

Assessment of sensitization:

Skin sensitizing effects were not observed in animal studies.

Experimental/calculated data:

Buehler test guinea pig: Non-sensitizing. (Guideline 92/69/EEC, B.6)

#### Germ cell mutagenicity

Assessment of mutagenicity:

The substance was not mutagenic in bacteria. The substance was not mutagenic in mammalian cell culture. The substance was not mutagenic in a test with mammals. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

#### Carcinogenicity

Assessment of carcinogenicity:

In long-term animal studies in which the substance was given by inhalation, a carcinogenic effect was not observed.

#### Reproductive toxicity

Assessment of reproduction toxicity:

The results of animal studies gave no indication of a fertility impairing effect. The product has not been tested. The statement has been derived from the structure of the product.

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 21.09.2023

Version: 2.0

Date previous version: 31.08.2023

Previous version: 1.0

Date / First version: 31.08.2023

Product: **BUTYL GLYCOL ACETATE**

(ID no. 30034846/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

#### Developmental toxicity

Assessment of teratogenicity:

In animal studies the substance did not cause malformations. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

#### Specific target organ toxicity (single exposure)

Assessment of STOT single:

Based on the available information there is no specific target organ toxicity to be expected after a single exposure.

#### Repeated dose toxicity and Specific target organ toxicity (repeated exposure)

Assessment of repeated dose toxicity:

Damages blood cells. Due to the species specific mode of action, the effects are not expected to occur in humans.

#### Aspiration hazard

not applicable

#### Interactive effects

No data available.

### **11.2. Information on other hazards**

#### Endocrine disrupting properties

The substance is not identified to have endocrine disrupting properties according to Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 nor is included in the Candidate List of substances of very high concern according to EU REACH Article 59 for having endocrine disrupting properties.

---

## **SECTION 12: Ecological Information**

### **12.1. Toxicity**

Assessment of aquatic toxicity:

Acutely harmful for aquatic organisms. The inhibition of the degradation activity of activated sludge is not anticipated when introduced to biological treatment plants in appropriate low concentrations.

Toxicity to fish:

LC50 (96 h) 28,3 mg/l, *Oncorhynchus mykiss* (OECD Guideline 203, static)

The details of the toxic effect relate to the nominal concentration. Literature data.

Aquatic invertebrates:

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 21.09.2023

Version: 2.0

Date previous version: 31.08.2023

Previous version: 1.0

Date / First version: 31.08.2023

Product: **BUTYL GLYCOL ACETATE**

(ID no. 30034846/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

EC50 (48 h) 37 mg/l, *Daphnia magna* (DIN 38412 Part 11, static)  
The details of the toxic effect relate to the nominal concentration.

Aquatic plants:

EC50 (72 h) 1.570 mg/l (growth rate), *Pseudokirchneriella subcapitata* (ISO 8692, static)  
The details of the toxic effect relate to the nominal concentration. Literature data.

EC0 (72 h) 300 mg/l (growth rate), *Pseudokirchneriella subcapitata* (ISO 8692, static)  
The details of the toxic effect relate to the nominal concentration. Literature data.

Microorganisms/Effect on activated sludge:

EC20 (180 min) > 1.000 mg/l, (DIN EN ISO 8192, aerobic)  
The details of the toxic effect relate to the nominal concentration.

Chronic toxicity to fish:

No data available.

Chronic toxicity to aquatic invertebrates:

EC10 (7 d) 30,4 mg/l, *Ceriodaphnia dubia* (OECD Guideline 211, semistatic)  
The details of the toxic effect relate to the nominal concentration.

Assessment of terrestrial toxicity:

No data available concerning terrestrial toxicity.

## 12.2. Persistence and degradability

Assessment biodegradation and elimination (H<sub>2</sub>O):

Readily biodegradable (according to OECD criteria).

Elimination information:

88 % BOD of the ThOD (28 d) (OECD 301F; ISO 9408; 92/69/EEC, C.4-D) (aerobic, activated sludge, domestic)

Assessment of stability in water:

No data available.

## 12.3. Bioaccumulative potential

Assessment bioaccumulation potential:

Because of the n-octanol/water distribution coefficient (log Pow) accumulation in organisms is not to be expected.

Bioaccumulation potential:

No data available.

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 21.09.2023

Version: 2.0

Date previous version: 31.08.2023

Previous version: 1.0

Date / First version: 31.08.2023

Product: **BUTYL GLYCOL ACETATE**

(ID no. 30034846/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

## 12.4. Mobility in soil

Assessment transport between environmental compartments:

Volatility: The substance will not evaporate into the atmosphere from the water surface.

Adsorption in soil: Adsorption to solid soil phase is possible.

## 12.5. Results of PBT and vPvB assessment

According to Annex XIII of Regulation (EC) No.1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH): The product does not fulfill the criteria for PBT (Persistent/bioaccumulative/toxic) and vPvB (very persistent/very bioaccumulative). Self classification

## 12.6. Endocrine disrupting properties

The substance is not identified to have endocrine disrupting properties according to Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 nor is included in the Candidate List of substances of very high concern according to EU REACH Article 59 for having endocrine disrupting properties.

## 12.7. Other adverse effects

The substance is not listed in Regulation (EC) 1005/2009 on substances that deplete the ozone layer.

## 12.8. Additional information

Adsorbable organically-bound halogen (AOX):

This product contains no organically-bound halogen.

---

# SECTION 13: Disposal Considerations

## 13.1. Waste treatment methods

Must be sent to a suitable incineration plant, observing local regulations.

Contaminated packaging:

Contaminated packaging should be emptied as far as possible; then it can be passed on for recycling after being thoroughly cleaned.

---

# SECTION 14: Transport Information

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 21.09.2023

Version: 2.0

Date previous version: 31.08.2023

Previous version: 1.0

Date / First version: 31.08.2023

Product: **BUTYL GLYCOL ACETATE**

(ID no. 30034846/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

### Land transport

#### ADR

	Not classified as a dangerous good under transport regulations
UN number or ID number:	Not applicable
UN proper shipping name:	Not applicable
Transport hazard class(es):	Not applicable
Packing group:	Not applicable
Environmental hazards:	Not applicable
Special precautions for user	None known

#### RID

	Not classified as a dangerous good under transport regulations
UN number or ID number:	Not applicable
UN proper shipping name:	Not applicable
Transport hazard class(es):	Not applicable
Packing group:	Not applicable
Environmental hazards:	Not applicable
Special precautions for user	None known

### Inland waterway transport

#### ADN

	Not classified as a dangerous good under transport regulations
UN number or ID number:	Not applicable
UN proper shipping name:	Not applicable
Transport hazard class(es):	Not applicable
Packing group:	Not applicable
Environmental hazards:	Not applicable
Special precautions for user:	None known

#### Transport in inland waterway vessel

Not evaluated

### Sea transport

#### IMDG

	Not classified as a dangerous good under transport regulations
UN number or ID number:	Not applicable
UN proper shipping name:	Not applicable
Transport hazard class(es):	Not applicable



BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 21.09.2023

Version: 2.0

Date previous version: 31.08.2023

Previous version: 1.0

Date / First version: 31.08.2023

Product: **BUTYL GLYCOL ACETATE**

(ID no. 30034846/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

Packing group:	Not applicable
Environmental hazards:	Not applicable
Special precautions for user	None known

### **Air transport**

IATA/ICAO

	Not classified as a dangerous good under transport regulations
UN number or ID number:	Not applicable
UN proper shipping name:	Not applicable
Transport hazard class(es):	Not applicable
Packing group:	Not applicable
Environmental hazards:	Not applicable
Special precautions for user	None known

#### **14.1. UN number or ID number**

See corresponding entries for "UN number or ID number" for the respective regulations in the tables above.

#### **14.2. UN proper shipping name**

See corresponding entries for "UN proper shipping name" for the respective regulations in the tables above.

#### **14.3. Transport hazard class(es)**

See corresponding entries for "Transport hazard class(es)" for the respective regulations in the tables above.

#### **14.4. Packing group**

See corresponding entries for "Packing group" for the respective regulations in the tables above.

#### **14.5. Environmental hazards**

See corresponding entries for "Environmental hazards" for the respective regulations in the tables above.

#### **14.6. Special precautions for user**

See corresponding entries for "Special precautions for user" for the respective regulations in the tables above.

#### **14.7. Maritime transport in bulk according to IMO instruments**

Maritime transport in bulk is not intended.

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 21.09.2023

Version: 2.0

Date previous version: 31.08.2023

Previous version: 1.0

Date / First version: 31.08.2023

Product: **BUTYL GLYCOL ACETATE**

(ID no. 30034846/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

## SECTION 15: Regulatory Information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### Prohibitions, Restrictions and Authorizations

Annex XVII of Regulation (EC) No 1907/2006: Number on List: 3, 75

Directive 2012/18/EU - Control of Major Accident Hazards involving dangerous substances (EU):  
Listed in above regulation: no

If other regulatory information applies that is not already provided elsewhere in this safety data sheet, then it is described in this subsection.

### 15.2. Chemical Safety Assessment

Chemical Safety Assessment performed

## SECTION 16: Other Information

Assessment of the hazard classes according to UN GHS criteria (most recent version)

Aquatic Acute 3

Acute Tox. 4 (dermal)

Flam. Liq. 4

Acute Tox. 4 (oral)

Full text of the classifications, including the hazard classes and the hazard statements, if mentioned in section 2 or 3:

Acute Tox.

Acute toxicity

H302 + H312 + H332

Harmful if swallowed, in contact with skin or if inhaled.

#### Abbreviations

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road.  
ADN = The European Agreement concerning the International Carriage of Dangerous Goods by Inland waterways. ATE = Acute Toxicity Estimates. CAO = Cargo Aircraft Only. CAS = Chemical Abstract Service. CLP = Classification, Labelling and Packaging of substances and mixtures. DIN = German national organization for standardization. DNEL = Derived No Effect Level. EC50 = Effective concentration median for 50% of the population. EC = European Community. EN = European Standards. IARC = International Agency for Research on Cancer. IATA = International Air Transport Association. IBC-Code = Intermediate Bulk Container code. IMDG = International Maritime Dangerous Goods Code. ISO = International Organization for Standardization. STEL = Short-Term Exposure Limit. LC50 = Lethal concentration median for 50% of the population. LD50 = Lethal dose median for 50% of the population. TLV = Threshold Limit Value. MARPOL = The International Convention for the Prevention of Pollution from Ships. NEN = Dutch Norm. NOEC = No Observed Effect Concentration. OEL = Occupational Exposure Limit. OECD = Organization for Economic Cooperation and Development. PBT = Persistent, Bioaccumulative and Toxic. PNEC = Predicted No Effect Level. PPM = Parts per million. RID = The

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 21.09.2023

Version: 2.0

Date previous version: 31.08.2023

Previous version: 1.0

Date / First version: 31.08.2023

Product: **BUTYL GLYCOL ACETATE**

(ID no. 30034846/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

European Agreement concerning the International Carriage of Dangerous Goods by Rail. TWA = Time Weight Average. UN-number = UN number at transport. vPvB = very Persistent and very Bioaccumulative.

The data contained in this safety data sheet are based on our current knowledge and experience and describe the product only with regard to safety requirements. This safety data sheet is neither a Certificate of Analysis (CoA) nor technical data sheet and shall not be mistaken for a specification agreement. Identified uses in this safety data sheet do neither represent an agreement on the corresponding contractual quality of the substance/mixture nor a contractually designated use. It is the responsibility of the recipient of the product to ensure any proprietary rights and existing laws and legislation are observed.

Vertical lines in the left hand margin indicate an amendment from the previous version.

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 21.09.2023

Version: 2.0

Date previous version: 31.08.2023

Previous version: 1.0

Date / First version: 31.08.2023

Product: **BUTYL GLYCOL ACETATE**

(ID no. 30034846/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

## Annex: Exposure Scenarios

### Index

1. Manufacture of substance, Use as a Process chemical, (use in industrial settings)  
IS; ERC1; PROC1, PROC2, PROC3, PROC8a, PROC8b, PROC15
2. Distribution of substance, (use in industrial settings)  
IS; ERC2, ERC3; PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC9, PROC15
3. Formulation & (re)packing of substances and mixtures, (use in industrial settings)  
IS; ERC2, ERC3; PROC1, PROC2, PROC3, PROC4, PROC5, PROC8a, PROC8b, PROC9, PROC15
4. Use in Coatings, (use in industrial settings)  
IS; ERC4; PROC1, PROC2, PROC3, PROC4, PROC5, PROC7, PROC8a, PROC8b, PROC9, PROC10, PROC13, PROC15
5. Use in Coatings, (use in professional settings)  
PW; ERC8a, ERC8d; PROC1, PROC2, PROC3, PROC4, PROC5, PROC8a, PROC8b, PROC10, PROC11, PROC13, PROC15, PROC19
6. Use in Coatings, (consumer use)  
C; ERC8a, ERC8d; PC9a
7. Use in Cleaning Agents, (use in industrial settings)  
IS; ERC4; PROC2, PROC3, PROC4, PROC7, PROC8a, PROC8b, PROC10, PROC13
8. Use in Cleaning Agents, (use in professional settings)  
PW; ERC8a, ERC8d; PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC10, PROC11, PROC13
9. Use in Cleaning Agents, (consumer use)  
C; ERC8a, ERC8d; PC35

\*\*\*\*\*

### 1. Short title of exposure scenario

Manufacture of substance, Use as a Process chemical, (use in industrial settings)  
IS; ERC1; PROC1, PROC2, PROC3, PROC8a, PROC8b, PROC15

### Control of exposure and risk management measures

Contributing exposure scenario	
Use descriptors covered	ERC1: Manufacture of the substance As no environmental hazard was identified no environmental-related exposure assessment and risk characterization was performed.

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 21.09.2023

Version: 2.0

Date previous version: 31.08.2023

Previous version: 1.0

Date / First version: 31.08.2023

Product: **BUTYL GLYCOL ACETATE**

(ID no. 30034846/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

### **Operational conditions**

#### **Contributing exposure scenario**

<b>Use descriptors covered</b>	PROC1: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions. Use domain: industrial
--------------------------------	--

#### **Operational conditions**

Concentration of the substance	2-butoxyethyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	49,995895 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor

#### **Exposure estimate and reference to its source**

Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	0,0343 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,000336
Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	0,0668 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,000502

#### **Guidance to Downstream Users**

For scaling see: <http://www.ecetoc.org/tra>

#### **Contributing exposure scenario**

<b>Use descriptors covered</b>	PROC2: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions Use domain: industrial
--------------------------------	---

#### **Operational conditions**

Concentration of the substance	2-butoxyethyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	49,995895 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 21.09.2023

Version: 2.0

Date previous version: 31.08.2023

Previous version: 1.0

Date / First version: 31.08.2023

Product: **BUTYL GLYCOL ACETATE**

(ID no. 30034846/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

Indoor/Outdoor	Indoor
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	1,3714 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,013445
Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	6,6755 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,050191
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition Use domain: industrial
<b>Operational conditions</b>	
Concentration of the substance	2-butoxyethyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	49,995895 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	0,6857 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,006723
Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	20,0264 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,150574
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC8a: Transfer of substance or mixture (charging and discharging) at non-dedicated facilities

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 21.09.2023

Version: 2.0

Date previous version: 31.08.2023

Previous version: 1.0

Date / First version: 31.08.2023

Product: **BUTYL GLYCOL ACETATE**

(ID no. 30034846/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

	Use domain: industrial
<b>Operational conditions</b>	
Concentration of the substance	2-butoxyethyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	49,995895 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	13,7143 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,134454
Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	66,7545 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,501914
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC8b: Transfer of substance or mixture (charging and discharging) at dedicated facilities Use domain: industrial
<b>Operational conditions</b>	
Concentration of the substance	2-butoxyethyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	49,995895 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	13,7143 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,134454

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 21.09.2023

Version: 2.0

Date previous version: 31.08.2023

Previous version: 1.0

Date / First version: 31.08.2023

Product: **BUTYL GLYCOL ACETATE**

(ID no. 30034846/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	33,3773 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,250957
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC15: Use a laboratory reagent. Use domain: industrial
<b>Operational conditions</b>	
Concentration of the substance	2-butoxyethyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	49,995895 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	0,3429 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,003361
Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	33,3773 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,250957
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

\*\*\*\*\*

## 2. Short title of exposure scenario

Distribution of substance, (use in industrial settings)

IS; ERC2, ERC3; PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC9, PROC15

## Control of exposure and risk management measures

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	ERC2: Formulation into mixture As no environmental hazard was identified no environmental-related exposure assessment and risk



BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 21.09.2023

Version: 2.0

Date previous version: 31.08.2023

Previous version: 1.0

Date / First version: 31.08.2023

Product: **BUTYL GLYCOL ACETATE**

(ID no. 30034846/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

	characterization was performed.
--	---------------------------------

#### **Operational conditions**

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	ERC3: Formulation into solid matrix As no environmental hazard was identified no environmental-related exposure assessment and risk characterization was performed.
<b>Operational conditions</b>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC1: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions. Use domain: industrial
<b>Operational conditions</b>	
Concentration of the substance	2-butoxyethyl acetate Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	49,995895 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	0,0343 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,000336
Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	0,0668 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,000502
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC2: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions Use domain: industrial

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 21.09.2023

Version: 2.0

Date previous version: 31.08.2023

Previous version: 1.0

Date / First version: 31.08.2023

Product: **BUTYL GLYCOL ACETATE**

(ID no. 30034846/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

<b>Operational conditions</b>	
Concentration of the substance	2-butoxyethyl acetate Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	49,995895 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	1,3714 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,013445
Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	6,6755 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,050191
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition Use domain: industrial
<b>Operational conditions</b>	
Concentration of the substance	2-butoxyethyl acetate Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	49,995895 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	0,6857 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,006723

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 21.09.2023

Version: 2.0

Date previous version: 31.08.2023

Previous version: 1.0

Date / First version: 31.08.2023

Product: **BUTYL GLYCOL ACETATE**

(ID no. 30034846/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	20,0264 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,150574
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC4: Chemical production where opportunity for exposure arises Use domain: industrial
<b>Operational conditions</b>	
Concentration of the substance	2-butoxyethyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	49,995895 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	6,8571 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,067227
Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	33,3773 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,250957
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC8a: Transfer of substance or mixture (charging and discharging) at non-dedicated facilities Use domain: industrial
<b>Operational conditions</b>	
Concentration of the substance	2-butoxyethyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	49,995895 Pa

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 21.09.2023

Version: 2.0

Date previous version: 31.08.2023

Previous version: 1.0

Date / First version: 31.08.2023

Product: **BUTYL GLYCOL ACETATE**

(ID no. 30034846/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	13,7143 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,134454
Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	66,7545 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,501914
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC8b: Transfer of substance or mixture (charging and discharging) at dedicated facilities Use domain: industrial
<b>Operational conditions</b>	
Concentration of the substance	2-butoxyethyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	49,995895 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	13,7143 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,134454
Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	33,3773 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,250957
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC9: Transfer of substance or preparation into small

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 21.09.2023

Version: 2.0

Date previous version: 31.08.2023

Previous version: 1.0

Date / First version: 31.08.2023

Product: **BUTYL GLYCOL ACETATE**

(ID no. 30034846/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

	containers (dedicated filling line, including weighing). Use domain: industrial
<b>Operational conditions</b>	
Concentration of the substance	2-butoxyethyl acetate Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	49,995895 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	6,8571 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,067227
Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	33,3773 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,250957
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC15: Use a laboratory reagent. Use domain: industrial
<b>Operational conditions</b>	
Concentration of the substance	2-butoxyethyl acetate Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	49,995895 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	0,3429 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,003361

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 21.09.2023

Version: 2.0

Date previous version: 31.08.2023

Previous version: 1.0

Date / First version: 31.08.2023

Product: **BUTYL GLYCOL ACETATE**

(ID no. 30034846/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	33,3773 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,250957
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

\*\*\*\*\*

### 3. Short title of exposure scenario

Formulation & (re)packing of substances and mixtures, (use in industrial settings)

IS; ERC2, ERC3; PROC1, PROC2, PROC3, PROC4, PROC5, PROC8a, PROC8b, PROC9, PROC15

### Control of exposure and risk management measures

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	ERC2: Formulation into mixture As no environmental hazard was identified no environmental-related exposure assessment and risk characterization was performed.
<b>Operational conditions</b>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	ERC3: Formulation into solid matrix As no environmental hazard was identified no environmental-related exposure assessment and risk characterization was performed.
<b>Operational conditions</b>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC1: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions. Use domain: industrial
<b>Operational conditions</b>	
Concentration of the substance	2-butoxyethyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	49,995895 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 21.09.2023

Version: 2.0

Date previous version: 31.08.2023

Previous version: 1.0

Date / First version: 31.08.2023

Product: **BUTYL GLYCOL ACETATE**

(ID no. 30034846/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

Indoor/Outdoor	Indoor
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	0,0343 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,000336
Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	0,0668 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,000502
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC2: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions Use domain: industrial
<b>Operational conditions</b>	
Concentration of the substance	2-butoxyethyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	49,995895 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	1,3714 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,013445
Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	6,6755 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,050191
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 21.09.2023

Version: 2.0

Date previous version: 31.08.2023

Previous version: 1.0

Date / First version: 31.08.2023

Product: **BUTYL GLYCOL ACETATE**

(ID no. 30034846/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

	containment condition Use domain: industrial
<b>Operational conditions</b>	
Concentration of the substance	2-butoxyethyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	49,995895 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	0,6857 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,006723
Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	20,0264 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,150574
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC4: Chemical production where opportunity for exposure arises Use domain: industrial
<b>Operational conditions</b>	
Concentration of the substance	2-butoxyethyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	49,995895 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	6,8571 mg/kg bw/day



BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 21.09.2023

Version: 2.0

Date previous version: 31.08.2023

Previous version: 1.0

Date / First version: 31.08.2023

Product: **BUTYL GLYCOL ACETATE**

(ID no. 30034846/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

Risk Characterization Ratio (RCR)	0,067227
Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	33,3773 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,250957
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC5: Mixing or blending in batch processes Use domain: industrial
<b>Operational conditions</b>	
Concentration of the substance	2-butoxyethyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	49,995895 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	13,7143 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,134454
Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	33,3773 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,250957
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC8a: Transfer of substance or mixture (charging and discharging) at non-dedicated facilities Use domain: industrial
<b>Operational conditions</b>	
Concentration of the substance	2-butoxyethyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	49,995895 Pa

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 21.09.2023

Version: 2.0

Date previous version: 31.08.2023

Previous version: 1.0

Date / First version: 31.08.2023

Product: **BUTYL GLYCOL ACETATE**

(ID no. 30034846/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	13,7143 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,134454
Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	66,7545 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,501914
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC8b: Transfer of substance or mixture (charging and discharging) at dedicated facilities Use domain: industrial
<b>Operational conditions</b>	
Concentration of the substance	2-butoxyethyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	49,995895 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	13,7143 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,134454
Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	33,3773 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,250957
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC9: Transfer of substance or preparation into small

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 21.09.2023

Version: 2.0

Date previous version: 31.08.2023

Previous version: 1.0

Date / First version: 31.08.2023

Product: **BUTYL GLYCOL ACETATE**

(ID no. 30034846/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

	containers (dedicated filling line, including weighing). Use domain: industrial
<b>Operational conditions</b>	
Concentration of the substance	2-butoxyethyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	49,995895 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	6,8571 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,067227
Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	33,3773 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,250957
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC15: Use a laboratory reagent. Use domain: industrial
<b>Operational conditions</b>	
Concentration of the substance	2-butoxyethyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	49,995895 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	0,3429 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,003361

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 21.09.2023

Version: 2.0

Date previous version: 31.08.2023

Previous version: 1.0

Date / First version: 31.08.2023

Product: **BUTYL GLYCOL ACETATE**

(ID no. 30034846/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	33,3773 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,250957
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

\*\*\*\*\*

#### 4. Short title of exposure scenario

Use in Coatings, (use in industrial settings)

IS; ERC4; PROC1, PROC2, PROC3, PROC4, PROC5, PROC7, PROC8a, PROC8b, PROC9, PROC10, PROC13, PROC15

#### Control of exposure and risk management measures

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	ERC4: Use of non-reactive processing aid at industrial site (no inclusion into or onto article) As no environmental hazard was identified no environmental-related exposure assessment and risk characterization was performed.
<b>Operational conditions</b>	
<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC1: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions. Use domain: industrial
<b>Operational conditions</b>	
Concentration of the substance	2-butoxyethyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	49,995895 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	0,0343 mg/kg bw/day

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 21.09.2023

Version: 2.0

Date previous version: 31.08.2023

Previous version: 1.0

Date / First version: 31.08.2023

Product: **BUTYL GLYCOL ACETATE**

(ID no. 30034846/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

Risk Characterization Ratio (RCR)	0,000336
Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	0,0668 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,000502
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC2: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions Use domain: industrial
<b>Operational conditions</b>	
Concentration of the substance	2-butoxyethyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	49,995895 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	1,3714 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,013445
Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	6,6755 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,050191
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition Use domain: industrial
<b>Operational conditions</b>	
Concentration of the substance	2-butoxyethyl acetate Content: >= 0 % - <= 100 %

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 21.09.2023

Version: 2.0

Date previous version: 31.08.2023

Previous version: 1.0

Date / First version: 31.08.2023

Product: **BUTYL GLYCOL ACETATE**

(ID no. 30034846/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

Physical state	liquid
Vapour pressure of the substance during use	49,995895 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	0,6857 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,006723
Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	20,0264 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,150574
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC4: Chemical production where opportunity for exposure arises Use domain: industrial
<b>Operational conditions</b>	
Concentration of the substance	2-butoxyethyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	49,995895 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	6,8571 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,067227
Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	33,3773 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,250957
<b>Guidance to Downstream Users</b>	

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 21.09.2023

Version: 2.0

Date previous version: 31.08.2023

Previous version: 1.0

Date / First version: 31.08.2023

Product: **BUTYL GLYCOL ACETATE**

(ID no. 30034846/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

For scaling see: <http://www.ecetoc.org/tra>

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC5: Mixing or blending in batch processes Use domain: industrial
<b>Operational conditions</b>	
Concentration of the substance	2-butoxyethyl acetate Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	49,995895 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	13,7143 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,134454
Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	33,3773 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,250957
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC7: Industrial spraying Use domain: industrial
<b>Operational conditions</b>	
Concentration of the substance	2-butoxyethyl acetate Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	49,995895 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
<b>Risk Management Measures</b>	
Local exhaust ventilation	Effectiveness: 95 %

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 21.09.2023

Version: 2.0

Date previous version: 31.08.2023

Previous version: 1.0

Date / First version: 31.08.2023

Product: **BUTYL GLYCOL ACETATE**

(ID no. 30034846/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

Wear chemically resistant gloves in combination with 'basic' employee training.	Effectiveness: 90 %
Regular inspection and maintenance of equipment and machines. Ensure that the task is being carried out outside the breathing zone of a worker (distance head-product greater than 1m). Ensure that the task is not carried out overhead. Ensure that the direction of airflow is clearly away from the worker.	
<b>Exposure estimate and reference to its source</b>	
Assessment method	RISKOFDERM v2.1
	Worker - dermal, long-term - systemic
Exposure estimate	6,26 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,061373
Assessment method	Stoffenmanager v4.0
	Worker - inhalation, long-term - systemic
Exposure estimate	110,59 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,831504
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="https://www.stoffenmanager.nl/default.aspx">https://www.stoffenmanager.nl/default.aspx</a> For scaling see: <a href="http://www.tno.nl">http://www.tno.nl</a> and search for "riskofderm".	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC8a: Transfer of substance or mixture (charging and discharging) at non-dedicated facilities Use domain: industrial
<b>Operational conditions</b>	
Concentration of the substance	2-butoxyethyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	49,995895 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	13,7143 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,134454
Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker



BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 21.09.2023

Version: 2.0

Date previous version: 31.08.2023

Previous version: 1.0

Date / First version: 31.08.2023

Product: **BUTYL GLYCOL ACETATE**

(ID no. 30034846/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

	Worker - inhalation, long-term - systemic
Exposure estimate	66,7545 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,501914
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC8b: Transfer of substance or mixture (charging and discharging) at dedicated facilities Use domain: industrial
<b>Operational conditions</b>	
Concentration of the substance	2-butoxyethyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	49,995895 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	13,7143 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,134454
Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	33,3773 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,250957
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing). Use domain: industrial
<b>Operational conditions</b>	
Concentration of the substance	2-butoxyethyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	49,995895 Pa
Process temperature	20 °C

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 21.09.2023

Version: 2.0

Date previous version: 31.08.2023

Previous version: 1.0

Date / First version: 31.08.2023

Product: **BUTYL GLYCOL ACETATE**

(ID no. 30034846/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	6,8571 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,067227
Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	33,3773 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,250957
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC10: Roller application or brushing Use domain: industrial
<b>Operational conditions</b>	
Concentration of the substance	2-butoxyethyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	49,995895 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
<b>Risk Management Measures</b>	
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	27,4286 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,268908
Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	46,7282 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,351339
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 21.09.2023

Version: 2.0

Date previous version: 31.08.2023

Previous version: 1.0

Date / First version: 31.08.2023

Product: **BUTYL GLYCOL ACETATE**

(ID no. 30034846/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC13: Treatment of articles by dipping and pouring. Use domain: industrial
<b>Operational conditions</b>	
Concentration of the substance	2-butoxyethyl acetate Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	49,995895 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	13,7143 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,134454
Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	66,7545 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,501914
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC15: Use a laboratory reagent. Use domain: industrial
<b>Operational conditions</b>	
Concentration of the substance	2-butoxyethyl acetate Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	49,995895 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	0,3429 mg/kg bw/day

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 21.09.2023

Version: 2.0

Date previous version: 31.08.2023

Previous version: 1.0

Date / First version: 31.08.2023

Product: **BUTYL GLYCOL ACETATE**

(ID no. 30034846/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

Risk Characterization Ratio (RCR)	0,003361
Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	33,3773 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,250957
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

\*\*\*\*\*

## 5. Short title of exposure scenario

Use in Coatings, (use in professional settings)

PW; ERC8a, ERC8d; PROC1, PROC2, PROC3, PROC4, PROC5, PROC8a, PROC8b, PROC10, PROC11, PROC13, PROC15, PROC19

## Control of exposure and risk management measures

Contributing exposure scenario	
Use descriptors covered	ERC8a: Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor) As no environmental hazard was identified no environmental-related exposure assessment and risk characterization was performed.
<b>Operational conditions</b>	
Contributing exposure scenario	
Use descriptors covered	ERC8d: Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor) As no environmental hazard was identified no environmental-related exposure assessment and risk characterization was performed.
<b>Operational conditions</b>	
Contributing exposure scenario	
Use descriptors covered	PROC1: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions. Use domain: professional
<b>Operational conditions</b>	
Concentration of the substance	2-butoxyethyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance	49,995895 Pa

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 21.09.2023

Version: 2.0

Date previous version: 31.08.2023

Previous version: 1.0

Date / First version: 31.08.2023

Product: **BUTYL GLYCOL ACETATE**

(ID no. 30034846/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

during use	
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	0,0343 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,000336
Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	0,0668 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,000502
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC2: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions Use domain: professional
<b>Operational conditions</b>	
Concentration of the substance	2-butoxyethyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	49,995895 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	1,3714 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,013445
Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	33,3773 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,250957
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 21.09.2023

Version: 2.0

Date previous version: 31.08.2023

Previous version: 1.0

Date / First version: 31.08.2023

Product: **BUTYL GLYCOL ACETATE**

(ID no. 30034846/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition Use domain: professional
<b>Operational conditions</b>	
Concentration of the substance	2-butoxyethyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	49,995895 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	0,6857 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,006723
Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	20,0264 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,150574
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC4: Chemical production where opportunity for exposure arises Use domain: professional
<b>Operational conditions</b>	
Concentration of the substance	2-butoxyethyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	49,995895 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 21.09.2023

Version: 2.0

Date previous version: 31.08.2023

Previous version: 1.0

Date / First version: 31.08.2023

Product: **BUTYL GLYCOL ACETATE**

(ID no. 30034846/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	6,8571 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,067227
Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	66,7545 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,501914
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC5: Mixing or blending in batch processes Use domain: professional
<b>Operational conditions</b>	
Concentration of the substance	2-butoxyethyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	49,995895 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	13,7143 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,134454
Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	66,7545 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,501914
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC8a: Transfer of substance or mixture (charging and discharging) at non-dedicated facilities Use domain: professional
<b>Operational conditions</b>	
Concentration of the substance	2-butoxyethyl acetate Content: >= 0 % - <= 100 %

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 21.09.2023

Version: 2.0

Date previous version: 31.08.2023

Previous version: 1.0

Date / First version: 31.08.2023

Product: **BUTYL GLYCOL ACETATE**

(ID no. 30034846/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

Physical state	liquid
Vapour pressure of the substance during use	49,995895 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
<b>Risk Management Measures</b>	
Provide a good standard of general or controlled ventilation (5 to 10 air changes per hour)	Effectiveness: 70 %
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	13,7143 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,134454
Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	50,0659 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,376435
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC8b: Transfer of substance or mixture (charging and discharging) at dedicated facilities Use domain: professional
<b>Operational conditions</b>	
Concentration of the substance	2-butoxyethyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	49,995895 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	13,7143 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,134454
Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker



BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 21.09.2023

Version: 2.0

Date previous version: 31.08.2023

Previous version: 1.0

Date / First version: 31.08.2023

Product: **BUTYL GLYCOL ACETATE**

(ID no. 30034846/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

	Worker - inhalation, long-term - systemic
Exposure estimate	66,7545 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,501914
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC10: Roller application or brushing Use domain: professional
<b>Operational conditions</b>	
Concentration of the substance	2-butoxyethyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	49,995895 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
<b>Risk Management Measures</b>	
Provide a good standard of general or controlled ventilation (5 to 10 air changes per hour)	Effectiveness: 70 %
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	27,4286 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,268908
Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	50,0659 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,376435
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC11: Non industrial spraying Use domain: professional
<b>Operational conditions</b>	
Concentration of the substance	2-butoxyethyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance	49,995895 Pa

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 21.09.2023

Version: 2.0

Date previous version: 31.08.2023

Previous version: 1.0

Date / First version: 31.08.2023

Product: **BUTYL GLYCOL ACETATE**

(ID no. 30034846/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

during use	
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
<b>Risk Management Measures</b>	
Wear suitable respiratory protection.	Effectiveness: 90 %
Wear chemically resistant gloves in combination with 'basic' employee training.	Effectiveness: 90 %
Ensure that the task is being carried out outside the breathing zone of a worker (distance head-product greater than 1m). Ensure that the task is not carried out overhead. Ensure that the direction of airflow is clearly away from the worker.	
<b>Exposure estimate and reference to its source</b>	
Assessment method	RISKOFDERM v2.1
	Worker - dermal, long-term - systemic
Exposure estimate	6,26 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,061373
Assessment method	Stoffenmanager v4.0
	Worker - inhalation, long-term - systemic
Exposure estimate	83,69 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,629248
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="https://www.stoffenmanager.nl/default.aspx">https://www.stoffenmanager.nl/default.aspx</a> For scaling see: <a href="http://www.tno.nl">http://www.tno.nl</a> and search for "riskofderm".	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC13: Treatment of articles by dipping and pouring. Use domain: professional
<b>Operational conditions</b>	
Concentration of the substance	2-butoxyethyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	49,995895 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
<b>Exposure estimate and reference to its source</b>	

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 21.09.2023

Version: 2.0

Date previous version: 31.08.2023

Previous version: 1.0

Date / First version: 31.08.2023

Product: **BUTYL GLYCOL ACETATE**

(ID no. 30034846/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	13,7143 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,134454
Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	66,7545 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,501914
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC15: Use a laboratory reagent. Use domain: professional
<b>Operational conditions</b>	
Concentration of the substance	2-butoxyethyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	49,995895 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	0,3429 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,003361
Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	33,3773 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,250957
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC19: Manual activities involving hand contact Use domain: professional
<b>Operational conditions</b>	
Concentration of the substance	2-butoxyethyl acetate Content: >= 0 % - <= 25 %
Physical state	liquid

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 21.09.2023

Version: 2.0

Date previous version: 31.08.2023

Previous version: 1.0

Date / First version: 31.08.2023

Product: **BUTYL GLYCOL ACETATE**

(ID no. 30034846/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

Vapour pressure of the substance during use	49,995895 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
<b>Risk Management Measures</b>	
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %
Use suitable chemically resistant gloves.	Effectiveness: 80 %
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	16,9714 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,166387
Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	70,0922 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,527009
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

\*\*\*\*\*

## 6. Short title of exposure scenario

Use in Coatings, (consumer use)

C; ERC8a, ERC8d; PC9a

## Control of exposure and risk management measures

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	ERC8a: Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor) As no environmental hazard was identified no environmental-related exposure assessment and risk characterization was performed.
<b>Operational conditions</b>	
<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	ERC8d: Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor) As no environmental hazard was identified no environmental-related exposure assessment and risk

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 21.09.2023

Version: 2.0

Date previous version: 31.08.2023

Previous version: 1.0

Date / First version: 31.08.2023

Product: **BUTYL GLYCOL ACETATE**

(ID no. 30034846/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

	characterization was performed.
<b>Operational conditions</b>	
<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PC9a: Coatings and paints, thinners, paint removers
<b>Operational conditions</b>	
Concentration of the substance	2-butoxyethyl acetate Content: $\geq 0\%$ - $\leq 5\%$
Vapour pressure of the substance during use	49,995895 Pa
Process temperature	20 °C
Duration and Frequency of activity	Exposure duration: 132 min Relevant for inhalative exposure estimates
Duration and Frequency of activity	Application duration: 120 min Relevant for inhalative exposure estimates
Duration and Frequency of activity	3 uses per year Relevant for inhalative exposure estimates
Duration and Frequency of activity	3 uses per year Relevant for dermal exposure estimates
Temperature (Application)	20 °C
body weight	65 kg
Uptake fraction dermal	100 %
Release area	150000 cm <sup>2</sup>
	Release area increases over time
Release duration	120 min
	Relevant for inhalative exposure estimates
Contact rate	30 mg/min
Release duration	120 min
	Relevant for dermal exposure estimates
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v3.6, ConsExpo v4.1, Dermal model: constant application rate, Uptake model: Uptake fraction
	Consumer - dermal, long-term - systemic
Exposure estimate	0,0228 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,000632
	The calculation is based on the internal chronic dose.
Assessment method	EASY TRA v3.6, ConsExpo v4.1, Inhalation model: exposure to vapour - evaporation
	Consumer - inhalation, long-term - systemic
Exposure estimate	0,0934 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,001394
	The exposure calculation is based on the mean

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 21.09.2023

Version: 2.0

Date previous version: 31.08.2023

Previous version: 1.0

Date / First version: 31.08.2023

Product: **BUTYL GLYCOL ACETATE**

(ID no. 30034846/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

	concentration per year.
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.rivm.nl/en/healthandddisease/productsafety/ConsExpo.jsp">http://www.rivm.nl/en/healthandddisease/productsafety/ConsExpo.jsp</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PC9a: Coatings and paints, thinners, paint removers
<b>Operational conditions</b>	
Concentration of the substance	2-butoxyethyl acetate Content: $\geq 0\%$ - $\leq 5\%$
Vapour pressure of the substance during use	49,995895 Pa
Process temperature	20 °C
Duration and Frequency of activity	Exposure duration: 120 min Relevant for inhalative exposure estimates
Duration and Frequency of activity	Application duration: 120 min Relevant for inhalative exposure estimates
Duration and Frequency of activity	3 uses per year Relevant for inhalative exposure estimates
Duration and Frequency of activity	3 uses per year Relevant for dermal exposure estimates
Temperature (Application)	20 °C
body weight	65 kg
Uptake fraction dermal	100 %
	Amount per use 0,5 g Relevant for dermal exposure estimates
Release area	20000 cm <sup>2</sup>
	Release area increases over time
Release duration	120 min
	Relevant for inhalative exposure estimates
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v3.6, ConsExpo v4.1, Dermal model: instant application, Uptake model: Uptake fraction
	Consumer - dermal, long-term - systemic
Exposure estimate	0,0032 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,000088
	The calculation is based on the internal chronic dose.
Assessment method	EASY TRA v3.6, ConsExpo v4.1, Inhalation model: exposure to vapour - evaporation
	Consumer - inhalation, long-term - systemic
Exposure estimate	0,7527 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,011235
	The exposure calculation is based on the mean concentration per year.

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 21.09.2023

Version: 2.0

Date previous version: 31.08.2023

Previous version: 1.0

Date / First version: 31.08.2023

Product: **BUTYL GLYCOL ACETATE**

(ID no. 30034846/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

### **Guidance to Downstream Users**

For scaling see: <http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp>

\*\*\*\*\*

## **7. Short title of exposure scenario**

Use in Cleaning Agents, (use in industrial settings)

IS; ERC4; PROC2, PROC3, PROC4, PROC7, PROC8a, PROC8b, PROC10, PROC13

## **Control of exposure and risk management measures**

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	ERC4: Use of non-reactive processing aid at industrial site (no inclusion into or onto article) As no environmental hazard was identified no environmental-related exposure assessment and risk characterization was performed.
<b>Operational conditions</b>	
<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC2: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions Use domain: industrial
<b>Operational conditions</b>	
Concentration of the substance	2-butoxyethyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	49,995895 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	1,3714 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,013445
Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	6,6755 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,050191

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 21.09.2023

Version: 2.0

Date previous version: 31.08.2023

Previous version: 1.0

Date / First version: 31.08.2023

Product: **BUTYL GLYCOL ACETATE**

(ID no. 30034846/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

### **Guidance to Downstream Users**

For scaling see: <http://www.ecetoc.org/tra>

### **Contributing exposure scenario**

<b>Use descriptors covered</b>	PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition Use domain: industrial
--------------------------------	---

### **Operational conditions**

Concentration of the substance	2-butoxyethyl acetate Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	49,995895 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor

### **Exposure estimate and reference to its source**

Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	0,6857 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,006723
Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	20,0264 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,150574

### **Guidance to Downstream Users**

For scaling see: <http://www.ecetoc.org/tra>

### **Contributing exposure scenario**

<b>Use descriptors covered</b>	PROC4: Chemical production where opportunity for exposure arises Use domain: industrial
--------------------------------	--

### **Operational conditions**

Concentration of the substance	2-butoxyethyl acetate Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	49,995895 Pa
Process temperature	20 °C



BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 21.09.2023

Version: 2.0

Date previous version: 31.08.2023

Previous version: 1.0

Date / First version: 31.08.2023

Product: **BUTYL GLYCOL ACETATE**

(ID no. 30034846/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	6,8571 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,067227
Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	33,3773 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,250957
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC7: Industrial spraying Use domain: industrial
<b>Operational conditions</b>	
Concentration of the substance	2-butoxyethyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	49,995895 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
<b>Risk Management Measures</b>	
Local exhaust ventilation	Effectiveness: 95 %
Wear chemically resistant gloves in combination with 'basic' employee training.	Effectiveness: 90 %
Regular inspection and maintenance of equipment and machines. Ensure that the task is being carried out outside the breathing zone of a worker (distance head-product greater than 1m). Ensure that the task is not carried out overhead. Ensure that the direction of airflow is clearly away from the worker.	
<b>Exposure estimate and reference to its source</b>	
Assessment method	RISKOFDERM v2.1
	Worker - dermal, long-term - systemic

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 21.09.2023

Version: 2.0

Date previous version: 31.08.2023

Previous version: 1.0

Date / First version: 31.08.2023

Product: **BUTYL GLYCOL ACETATE**

(ID no. 30034846/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

Exposure estimate	6,26 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,061373
Assessment method	Stoffenmanager v4.0
	Worker - inhalation, long-term - systemic
Exposure estimate	110,59 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,831504
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="https://www.stoffenmanager.nl/default.aspx">https://www.stoffenmanager.nl/default.aspx</a> For scaling see: <a href="http://www.tno.nl">http://www.tno.nl</a> and search for "riskofderm".	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC8a: Transfer of substance or mixture (charging and discharging) at non-dedicated facilities Use domain: industrial
<b>Operational conditions</b>	
Concentration of the substance	2-butoxyethyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	49,995895 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	13,7143 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,134454
Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	66,7545 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,501914
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC8b: Transfer of substance or mixture (charging and discharging) at dedicated facilities Use domain: industrial
<b>Operational conditions</b>	
Concentration of the substance	2-butoxyethyl acetate Content: >= 0 % - <= 100 %

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 21.09.2023

Version: 2.0

Date previous version: 31.08.2023

Previous version: 1.0

Date / First version: 31.08.2023

Product: **BUTYL GLYCOL ACETATE**

(ID no. 30034846/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

Physical state	liquid
Vapour pressure of the substance during use	49,995895 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	13,7143 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,134454
Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	33,3773 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,250957
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC10: Roller application or brushing Use domain: industrial
<b>Operational conditions</b>	
Concentration of the substance	2-butoxyethyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	49,995895 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
<b>Risk Management Measures</b>	
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	27,4286 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,268908
Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	46,7282 mg/m <sup>3</sup>

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 21.09.2023

Version: 2.0

Date previous version: 31.08.2023

Previous version: 1.0

Date / First version: 31.08.2023

Product: **BUTYL GLYCOL ACETATE**

(ID no. 30034846/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

Risk Characterization Ratio (RCR)	0,351339
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC13: Treatment of articles by dipping and pouring. Use domain: industrial
<b>Operational conditions</b>	
Concentration of the substance	2-butoxyethyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	49,995895 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	13,7143 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,134454
Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	66,7545 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,501914
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

\*\*\*\*\*

## 8. Short title of exposure scenario

Use in Cleaning Agents, (use in professional settings)

PW; ERC8a, ERC8d; PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC10, PROC11, PROC13

## Control of exposure and risk management measures

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	ERC8a: Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor) As no environmental hazard was identified no environmental-related exposure assessment and risk characterization was performed.

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 21.09.2023

Version: 2.0

Date previous version: 31.08.2023

Previous version: 1.0

Date / First version: 31.08.2023

Product: **BUTYL GLYCOL ACETATE**

(ID no. 30034846/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

### **Operational conditions**

#### **Contributing exposure scenario**

<b>Use descriptors covered</b>	ERC8d: Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor) As no environmental hazard was identified no environmental-related exposure assessment and risk characterization was performed.
--------------------------------	--

### **Operational conditions**

#### **Contributing exposure scenario**

<b>Use descriptors covered</b>	PROC2: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions Use domain: professional
--------------------------------	---

### **Operational conditions**

Concentration of the substance	2-butoxyethyl acetate Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	49,995895 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor

### **Exposure estimate and reference to its source**

Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	1,3714 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,013445
Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	33,3773 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,250957

### **Guidance to Downstream Users**

For scaling see: <http://www.ecetoc.org/tra>

#### **Contributing exposure scenario**

<b>Use descriptors covered</b>	PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition Use domain: professional
--------------------------------	---

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 21.09.2023

Version: 2.0

Date previous version: 31.08.2023

Previous version: 1.0

Date / First version: 31.08.2023

Product: **BUTYL GLYCOL ACETATE**

(ID no. 30034846/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

<b>Operational conditions</b>	
Concentration of the substance	2-butoxyethyl acetate Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	49,995895 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	0,6857 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,006723
Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	20,0264 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,150574
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC4: Chemical production where opportunity for exposure arises Use domain: professional
<b>Operational conditions</b>	
Concentration of the substance	2-butoxyethyl acetate Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	49,995895 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	6,8571 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,067227
Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 21.09.2023

Version: 2.0

Date previous version: 31.08.2023

Previous version: 1.0

Date / First version: 31.08.2023

Product: **BUTYL GLYCOL ACETATE**

(ID no. 30034846/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

Exposure estimate	66,7545 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,501914
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC8a: Transfer of substance or mixture (charging and discharging) at non-dedicated facilities Use domain: professional
<b>Operational conditions</b>	
Concentration of the substance	2-butoxyethyl acetate Content: >= 0 % - <= 25 %
Physical state	liquid
Vapour pressure of the substance during use	49,995895 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
<b>Risk Management Measures</b>	
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	8,2286 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,080672
Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	70,0922 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,527009
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC8b: Transfer of substance or mixture (charging and discharging) at dedicated facilities Use domain: professional
<b>Operational conditions</b>	
Concentration of the substance	2-butoxyethyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 21.09.2023

Version: 2.0

Date previous version: 31.08.2023

Previous version: 1.0

Date / First version: 31.08.2023

Product: **BUTYL GLYCOL ACETATE**

(ID no. 30034846/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

Vapour pressure of the substance during use	49,995895 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	13,7143 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,134454
Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	66,7545 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,501914
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC10: Roller application or brushing Use domain: professional
<b>Operational conditions</b>	
Concentration of the substance	2-butoxyethyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	49,995895 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
<b>Risk Management Measures</b>	
Local exhaust ventilation	Effectiveness: 80 %
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	
In case no general ventilation is used: Reduce concentration to less than 25%	
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	27,4286 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,268908



BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 21.09.2023

Version: 2.0

Date previous version: 31.08.2023

Previous version: 1.0

Date / First version: 31.08.2023

Product: **BUTYL GLYCOL ACETATE**

(ID no. 30034846/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	33,3773 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,250957
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC11: Non industrial spraying Use domain: professional
<b>Operational conditions</b>	
Concentration of the substance	2-butoxyethyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	49,995895 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
<b>Risk Management Measures</b>	
Wear suitable respiratory protection.	Effectiveness: 90 %
Ensure that the task is being carried out outside the breathing zone of a worker (distance head-product greater than 1m). Ensure that the task is not carried out overhead. Ensure that the direction of airflow is clearly away from the worker.	
Use suitable chemically resistant gloves.	Effectiveness: 90 %
<b>Exposure estimate and reference to its source</b>	
Assessment method	RISKOFDERM v2.1
	Worker - dermal, long-term - systemic
Exposure estimate	6,26 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,061373
Assessment method	Stoffenmanager v4.0
	Worker - inhalation, long-term - systemic
Exposure estimate	83,69 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,629248
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="https://www.stoffenmanager.nl/default.aspx">https://www.stoffenmanager.nl/default.aspx</a> For scaling see: <a href="http://www.tno.nl">http://www.tno.nl</a> and search for "riskofderm".	

<b>Contributing exposure scenario</b>
---------------------------------------

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 21.09.2023

Version: 2.0

Date previous version: 31.08.2023

Previous version: 1.0

Date / First version: 31.08.2023

Product: **BUTYL GLYCOL ACETATE**

(ID no. 30034846/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

<b>Use descriptors covered</b>	PROC13: Treatment of articles by dipping and pouring. Use domain: professional
<b>Operational conditions</b>	
Concentration of the substance	2-butoxyethyl acetate Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	49,995895 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	13,7143 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,134454
Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	66,7545 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,501914
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

\*\*\*\*\*

## 9. Short title of exposure scenario

Use in Cleaning Agents, (consumer use)

C; ERC8a, ERC8d; PC35

## Control of exposure and risk management measures

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	ERC8a: Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor) As no environmental hazard was identified no environmental-related exposure assessment and risk characterization was performed.
<b>Operational conditions</b>	
<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	ERC8d: Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor)

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 21.09.2023

Version: 2.0

Date previous version: 31.08.2023

Previous version: 1.0

Date / First version: 31.08.2023

Product: **BUTYL GLYCOL ACETATE**

(ID no. 30034846/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

	As no environmental hazard was identified no environmental-related exposure assessment and risk characterization was performed.
<b>Operational conditions</b>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PC35: Washing and Cleaning Products (including solvent based products).
<b>Operational conditions</b>	
Concentration of the substance	2-butoxyethyl acetate Content: $\geq 0\%$ - $\leq 5\%$
Vapour pressure of the substance during use	49,995895 Pa
Process temperature	20 °C
Duration and Frequency of activity	Exposure duration: 240 min Relevant for inhalative exposure estimates
Duration and Frequency of activity	Application duration: 30 min Relevant for inhalative exposure estimates
Duration and Frequency of activity	125 uses per year Relevant for inhalative exposure estimates
Duration and Frequency of activity	125 uses per year Relevant for dermal exposure estimates
Temperature (Application)	20 °C
body weight	65 kg
Uptake fraction dermal	100 %
	Amount per use 27 g Relevant for dermal exposure estimates
Release area	100000 cm <sup>2</sup>
	Release area increases over time
Release duration	30 min
	Relevant for inhalative exposure estimates
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v3.6, ConsExpo v4.1, Dermal model: instant application, Uptake model: Uptake fraction
	Consumer - dermal, long-term - systemic
Exposure estimate	7,1128 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,197576
	The calculation is based on the internal chronic dose.
Assessment method	EASY TRA v3.6, ConsExpo v4.1, Inhalation model: exposure to vapour - evaporation
	Consumer - inhalation, long-term - systemic
Exposure estimate	1,0988 mg/m <sup>3</sup>

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 21.09.2023

Version: 2.0

Date previous version: 31.08.2023

Previous version: 1.0

Date / First version: 31.08.2023

Product: **BUTYL GLYCOL ACETATE**

(ID no. 30034846/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

Risk Characterization Ratio (RCR)	0,0164
	The exposure calculation is based on the mean concentration per year.
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp">http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PC35: Washing and Cleaning Products (including solvent based products).
<b>Operational conditions</b>	
Concentration of the substance	2-butoxyethyl acetate Content: >= 0 % - <= 9 %
Vapour pressure of the substance during use	49,995895 Pa
Process temperature	20 °C
Duration and Frequency of activity	Exposure duration: 60 min Relevant for inhalative exposure estimates
Duration and Frequency of activity	125 uses per year Relevant for inhalative exposure estimates
Duration and Frequency of activity	125 uses per year Relevant for dermal exposure estimates
Room size	15 m <sup>3</sup>
Ventilation rate per hour	2,5
body weight	65 kg
Uptake fraction dermal	100 %
Spray duration	24,6 sec
Contact rate	46 mg/min
Release duration	0,41 min
	Relevant for dermal exposure estimates
<b>Risk Management Measures</b>	
Consumer Measures	Ensure spraying away from persons.
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v3.6, ConsExpo v4.1, Dermal model: constant application rate, Uptake model: Uptake fraction
	Consumer - dermal, long-term - systemic
Exposure estimate	0,0089 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,000248
	The calculation is based on the internal chronic dose.
Assessment method	EASY TRA v3.6, ConsExpo v4.1, Inhalation model: Exposure to spray/dust
	Consumer - inhalation, long-term - systemic
Exposure estimate	0,0032 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,000047

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 21.09.2023

Version: 2.0

Date previous version: 31.08.2023

Previous version: 1.0

Date / First version: 31.08.2023

Product: **BUTYL GLYCOL ACETATE**

(ID no. 30034846/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

	The exposure calculation is based on the mean concentration per year.
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.rivm.nl/en/healthandddisease/productsafety/ConsExpo.jsp">http://www.rivm.nl/en/healthandddisease/productsafety/ConsExpo.jsp</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PC35: Washing and Cleaning Products (including solvent based products).
<b>Operational conditions</b>	
Concentration of the substance	2-butoxyethyl acetate Content: >= 0 % - <= 9 %
Vapour pressure of the substance during use	49,995895 Pa
Process temperature	20 °C
Duration and Frequency of activity	Exposure duration: 60 min Relevant for inhalative exposure estimates
Duration and Frequency of activity	Application duration: 12 min Relevant for inhalative exposure estimates
Duration and Frequency of activity	125 uses per year Relevant for inhalative exposure estimates
Duration and Frequency of activity	125 uses per year Relevant for dermal exposure estimates
Temperature (Application)	20 °C
body weight	65 kg
Uptake fraction dermal	100 %
	Amount per use 35 g Relevant for dermal exposure estimates
Release area	17100 cm <sup>2</sup>
	Release area is constant
Release duration	12 min
	Relevant for inhalative exposure estimates
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v3.6, ConsExpo v4.1, Dermal model: instant application, Uptake model: Uptake fraction Consumer - dermal, long-term - systemic
Exposure estimate	16,5964 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,461012
	The calculation is based on the internal chronic dose.
Assessment method	EASY TRA v3.6, ConsExpo v4.1, Inhalation model: exposure to vapour - evaporation Consumer - inhalation, long-term - systemic
Exposure estimate	0,8251 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,012316

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 21.09.2023

Version: 2.0

Date previous version: 31.08.2023

Previous version: 1.0

Date / First version: 31.08.2023

Product: **BUTYL GLYCOL ACETATE**

(ID no. 30034846/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

	The exposure calculation is based on the mean concentration per year.
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp">http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp</a>	

\*\*\*\*\*