

# **ACROFLOR® 10**

ACROFLOR 10 is a wax emulsion designed to promote black heel mark, scuff and mar resistance, water resistance, gloss, and coefficient of friction control.

Chemical Nature

Polyethylene wax emulsion

# **Properties**

**Typical Properties** 

Appearance semi-translucent emulsion

Non-volatile at 145°C (2g, 30 minutes) % ~ 26

pH (at 25°C) ~ 9.0-10.0

Viscosity (at 25°C) cps <20

Density (at 25°C) lbs/US gal 8.25

Density (at 25°C) | Ibs/US gal | 8.25 | Melting point (°C) | 130

# **Application**

ACROFLOR 10 is designed for application into floor finishes for black heel mark resistance improvement, scuff and mar resistance, and coefficient of friction modification. Formulations can be made, dependent on resin, for balance of burnishability with low-maintenance properties.

Typical loadings in a floor finish are between 4-15% wax solids on total solids. Loading level should be evaluated per application based on desired performance.

Formulations can be optimized for a variety of flooring substrates such as vinyl, vinyl composite, terrazzo, and concrete and quarry tile.

# Safety

General

The usual safety precautions when handling chemicals must be observed. These include the measures described in Federal, State and Local health and safety regulations, thorough ventilation of the workplace, good skin care and wearing of protective goggles.

Safety Data Sheet

All safety information is provided in the Safety Data Sheet for ACROFLOR 10.

## Storage

Please refer to the "Handling and Storage of Polymer Dispersions" brochure.

April 2023 page 1 of 2

<sup>\*</sup>These values should not be interpreted as specifications.

#### **Important**

WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, THEY ARE PROVIDED FOR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, BASF RECOMMENDS THAT THE READER MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR A PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESCRIPTIONS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF BASF'S TERMS AND CONDITIONS OF SALE. FURTHER, THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY BASF HEREUNDER ARE GIVEN GRATIS AND BASF ASSUMES NO OBLIGATION OR LIABILITY FOR THE DESCRIPTIONS, DESIGNS, DATA OR INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT THE READER'S RISK.

ACROFLOR is a trademark of BASF Group.

© BASF Corporation, 2023



BASF Corporation is fully committed to the Responsible Care® initiative in the USA, Canada, and Mexico. For more information on Responsible Care, go to: U.S.: www.basf.us/responsiblecare\_usa Canada: www.basf.us/responsiblecare\_canada

Canada: www.basf.us/responsiblecare\_canada México: www.basf.us/responsiblecare\_mexico

### **BASF Corporation**

Dispersions and Resins 11501 Steele Creek Road Charlotte, North Carolina 28273 Phone: (800) 251 – 0612

Email: CustCare-Charlotte@basf.com

www.basf.us/dpsolutions

page 2 of 2