

Safety data sheet

Page: 1/28

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 11.01.2023

Version: 13.0

Date previous version: 16.12.2020

Previous version: 12.0

Date / First version: 24.03.2003

Product: **Aluminium chloride anhydrous ground**

(ID no. 30041207/SDS_GEN_GB/EN)

Date of print 23.10.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Aluminium chloride anhydrous ground

Chemical name: aluminium chloride, anhydrous

INDEX-Number: 013-003-00-7

CAS Number: 7446-70-0

REACH registration number: 01-2119459371-39-0006, 01-2119459371-39-0002, 01-2119459371-39-0009

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses: Chemical

Recommended use: Intermediate, catalyst, process chemical

For the detailed identified uses of the product see appendix of the safety data sheet.

1.3. Details of the supplier of the safety data sheet

Company:

BASF SE
67056 Ludwigshafen
GERMANY

Contact address:

BASF plc
4th and 5th Floors, 2 Stockport Exchange
Railway Road, Stockport, SK1 3GG
UNITED KINGDOM

Telephone: +44 161 475 3000

E-mail address: product-safety-uk-and-ireland@basf.com

1.4. Emergency telephone number

International emergency number:

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 11.01.2023

Version: 13.0

Date previous version: 16.12.2020

Previous version: 12.0

Date / First version: 24.03.2003

Product: **Aluminium chloride anhydrous ground**

(ID no. 30041207/SDS_GEN_GB/EN)

Date of print 23.10.2025

Telephone: +49 180 2273-112

SECTION 2: Hazards Identification

2.1. Classification of the substance or mixture

According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567

Skin Corr./Irrit. 1B

H314 Causes severe skin burns and eye damage.

Eye Dam./Irrit. 1

H318 Causes serious eye damage.

For the classifications not written out in full in this section the full text can be found in section 16.

2.2. Label elements

According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567

Pictogram:



Signal Word:

Danger

Hazard Statement:

H314 Causes severe skin burns and eye damage.

Precautionary Statements (Prevention):

P280 Wear protective gloves, protective clothing and eye protection or face protection.

P260 Do not breathe dust or mist.

P264 Wash contaminated body parts thoroughly after handling.

Precautionary Statements (Response):

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER or physician.

P303 + P361 + P353 IF ON SKIN (or hair): Remove or Take off immediately all contaminated clothing. Rinse skin with water or shower.

P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P301 + P330 + P331 IF SWALLOWED: rinse mouth. Do NOT induce vomiting.

Precautionary Statements (Storage):

P405 Store locked up.

Precautionary Statements (Disposal):

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 11.01.2023

Version: 13.0

Date previous version: 16.12.2020

Previous version: 12.0

Date / First version: 24.03.2003

Product: **Aluminium chloride anhydrous ground**

(ID no. 30041207/SDS_GEN_GB/EN)

Date of print 23.10.2025

P501 Dispose of contents and container to hazardous or special waste collection point.

Labeling of special preparations (GHS):

EUH014: Reacts violently with water. EUH071: Corrosive to the respiratory tract.

Hazard determining component(s) for labelling: aluminium chloride, anhydrous

2.3. Other hazards

According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

Corrodes metals in the presence of water or moisture.

The product does not contain a substance above legal limits fulfilling the PBT (persistent/bioaccumulative/toxic) criteria or the vPvB (very persistent/very bioaccumulative) criteria.

SECTION 3: Composition/Information on Ingredients

3.1. Substances

Chemical nature

aluminium chloride, anhydrous

CAS Number: 7446-70-0

EC-Number: 231-208-1

INDEX-Number: 013-003-00-7

For the classifications not written out in full in this section, including the hazard classes and the hazard statements, the full text is listed in section 16.

3.2. Mixtures

Not applicable

SECTION 4: First-Aid Measures

4.1. Description of first aid measures

Immediately remove contaminated clothing. If the patient is likely to become unconscious, place and transport in stable sideways position (recovery position).

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 11.01.2023

Version: 13.0

Date previous version: 16.12.2020

Previous version: 12.0

Date / First version: 24.03.2003

Product: **Aluminium chloride anhydrous ground**

(ID no. 30041207/SDS_GEN_GB/EN)

Date of print 23.10.2025

If inhaled:

Keep patient calm, remove to fresh air. Immediately administer a corticosteroid from a controlled/metered dose inhaler.

On skin contact:

Wipe dry. Immediately wash thoroughly with plenty of water, apply sterile dressings, consult a skin specialist.

On contact with eyes:

Immediately wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.

On ingestion:

Immediately rinse mouth and then drink 200-300 ml of water, seek medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms: skin corrosion, irritates the eyes and respiratory tract

Hazards: No hazard is expected under intended use and appropriate handling.

4.3. Indication of any immediate medical attention and special treatment needed

Treatment: Treat according to symptoms (decontamination, vital functions), no known specific antidote.

SECTION 5: Fire-Fighting Measures

5.1. Extinguishing media

Suitable extinguishing media:
dry powder

Unsuitable extinguishing media for safety reasons:
water

5.2. Special hazards arising from the substance or mixture

Endangering substances: hydrogen chloride

Advice: The substances/groups of substances mentioned can be released if the product is involved in a fire.

5.3. Advice for fire-fighters

Special protective equipment:

Wear a self-contained breathing apparatus.

Further information:

Contaminated extinguishing water must be disposed of in accordance with official regulations.

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 11.01.2023

Version: 13.0

Date previous version: 16.12.2020

Previous version: 12.0

Date / First version: 24.03.2003

Product: **Aluminium chloride anhydrous ground**

(ID no. 30041207/SDS_GEN_GB/EN)

Date of print 23.10.2025

SECTION 6: Accidental Release Measures

6.1. Personal precautions, protective equipment and emergency procedures

Breathing protection required.

6.2. Environmental precautions

Due to the pH-value of the product, neutralization is generally required before discharging sewage into treatment plants.

6.3. Methods and material for containment and cleaning up

For large amounts: Sweep/shovel up. Dispose of absorbed material in accordance with regulations.

For residues: Rinse away with water.

Avoid raising dust.

6.4. Reference to other sections

Information regarding exposure controls/personal protection and disposal considerations can be found in section 8 and 13.

SECTION 7: Handling and Storage

7.1. Precautions for safe handling

Handle in accordance with good industrial hygiene and safety practice. Keep container tightly sealed. Before opening venting of container is recommended; beware of escaping gases and vapours. Avoid dust formation. Breathing must be protected when large quantities are decanted without local exhaust ventilation.

Protection against fire and explosion:

The substance/product is non-combustible.

7.2. Conditions for safe storage, including any incompatibilities

Suitable materials for containers: glass, enamelled, Carbon steel (Iron), polyvinylchloride (PVC), Stainless steel 1.4301 (V2)

Further information on storage conditions: Keep container tightly closed in a cool, well-ventilated place. Keep container dry.

Storage stability:

Product is hygroscopic.

Improper storage may result in pressure build up in the drums.

7.3. Specific end use(s)

See exposure scenario(s) in the attachment to this safety data sheet.

SECTION 8: Exposure Controls/Personal Protection

8.1. Control parameters

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 11.01.2023

Version: 13.0

Date previous version: 16.12.2020

Previous version: 12.0

Date / First version: 24.03.2003

Product: **Aluminium chloride anhydrous ground**

(ID no. 30041207/SDS_GEN_GB/EN)

Date of print 23.10.2025

Components with occupational exposure limits

7446-70-0: aluminium chloride, anhydrous

TWA value 2 mg/m³ (WEL/EH 40 (UK))

PNEC

freshwater:

No hazard identified.

marine water:

No hazard identified.

intermittent release:

No hazard identified.

sediment (freshwater):

No hazard identified.

sediment (marine water):

No hazard identified.

soil:

No hazard identified.

STP:

No hazard identified.

DNEL

consumer:

Long-term exposure- systemic effects, oral: 1.5 mg/kg

8.2. Exposure controls

Personal protective equipment

Respiratory protection:

Gas filter for gases/vapours of inorganic compounds (e.g. EN 14387 Type B) Combination filter for gases/vapours of organic, inorganic, acid inorganic, alkaline compounds and toxic particles (e. g. EN 14387 Type ABEK-P3)

Hand protection:

Chemical resistant protective gloves (EN ISO 374-1)

Suitable materials also with prolonged, direct contact (Recommended: Protective index 6, corresponding > 480 minutes of permeation time according to EN ISO 374-1):

polyvinylchloride (PVC) - 0.7 mm coating thickness

nitrile rubber (NBR) - 0.4 mm coating thickness

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 11.01.2023

Version: 13.0

Date previous version: 16.12.2020

Previous version: 12.0

Date / First version: 24.03.2003

Product: **Aluminium chloride anhydrous ground**

(ID no. 30041207/SDS_GEN_GB/EN)

Date of print 23.10.2025

Supplementary note: The specifications are based on tests, literature data and information of glove manufacturers or are derived from similar substances by analogy. Due to many conditions (e.g. temperature) it must be considered, that the practical usage of a chemical-protective glove in practice may be much shorter than the permeation time determined through testing. Manufacturer's directions for use should be observed because of great diversity of types.

Eye protection:

Tightly fitting safety goggles (cage goggles) (e.g. EN 166) and face shield.

Body protection:

chemical-protection suit (f.e. according to EN 14605)

General safety and hygiene measures

Handle in accordance with good industrial hygiene and safety practice. Take off immediately all contaminated clothing. Hands and/or face should be washed before breaks and at the end of the shift.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Form:	powder	
Colour:	yellowish	
Odour:	pungent odour	
Odour threshold:	Not determined due to potential health hazard by inhalation.	
pH value:	2.4 (100 g/l)	(OECD Guideline 122)
Melting point:	190 °C (2,500 hPa)	
Boiling point:	(1,013.25 hPa) Study scientifically not justified., Sublimation	
Sublimation temperature:	181.2 °C (1,013.25 hPa) Literature data.	
Flash point:	not applicable, the product is a solid	
Evaporation rate:	not applicable, The product is a non-volatile solid.	
Flammability:	not highly flammable	(Regulation 440/2008/EC, A.10)
Lower explosion limit:	For solids not relevant for classification and labelling.	

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 11.01.2023

Version: 13.0

Date previous version: 16.12.2020

Previous version: 12.0

Date / First version: 24.03.2003

Product: **Aluminium chloride anhydrous ground**

(ID no. 30041207/SDS_GEN_GB/EN)

Date of print 23.10.2025

Upper explosion limit:	For solids not relevant for classification and labelling.	
Vapour pressure:	< 1 mbar (20 °C) Literature data.	
Density:	2.44 g/cm ³ (25 °C) Literature data.	
Relative density:	2.48 Literature data.	(other)
Relative vapour density (air):	The product is a non-volatile solid.	
Solubility in water:	Literature data. 450 g/l (20 °C)	
Partitioning coefficient n-octanol/water (log Kow):	Study scientifically not justified.	
Self ignition:	Based on its structural properties the product is not classified as self-igniting.	Test type: Spontaneous self-ignition at room-temperature.
	not self-igniting	Test type: Self-ignition at high temperatures. (Method: Regulation 440/2008/EC, A.16)
Thermal decomposition:	No decomposition if correctly stored and handled.	
Viscosity, dynamic:	Study scientifically not justified.	
Viscosity, kinematic:	not applicable, the product is a solid	
Explosion hazard:	Based on the chemical structure there is no indication of explosive properties.	
Fire promoting properties:	not fire-propagating	(Regulation 440/2008/EC, A.17)

9.2. Other information

Self heating ability:	It is not a substance capable of spontaneous heating.
Bulk density:	1,200 kg/m ³
pKA:	Study scientifically not justified.
Hygroscopy:	hygroscopic

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 11.01.2023

Version: 13.0

Date previous version: 16.12.2020

Previous version: 12.0

Date / First version: 24.03.2003

Product: **Aluminium chloride anhydrous ground**

(ID no. 30041207/SDS_GEN_GB/EN)

Date of print 23.10.2025

Adsorption/water - soil:	KOC: 3700	(other)
	Following exposure to soil, adsorption to solid soil particles is probable, therefore contamination of groundwater is not expected.	
Surface tension:	Based on chemical structure, surface activity is not to be expected.	
Grain size distribution	10.0 µm	(D10, ISO 13320-1;; particle size by laser diffraction)
	118.0 µm	(D90, ISO 13320-1;; particle size by laser diffraction)
	430.0 µm	(D50, ISO 13320-1;; particle size by laser diffraction)
Molar mass:	133.34 g/mol	
Angle of repose:	41 °	(funnel test (plant lab))

SECTION 10: Stability and Reactivity

10.1. Reactivity

No hazardous reactions if stored and handled as prescribed/indicated.

Corrosion to metals:	Corrodes metals in the presence of water or moisture.	
Formation of flammable gases:	Remarks:	Forms no flammable gases in the presence of water.
	Method:	Flammability (Contact with water)

10.2. Chemical stability

The product is stable if stored and handled as prescribed/indicated.

10.3. Possibility of hazardous reactions

Reacts violently with water. Develops hydrochloric acid (HCL) on contact with water. The formation of gaseous decomposition products builds up pressure in tightly closed containers.

10.4. Conditions to avoid

See SDS section 7 - Handling and storage. Avoid humidity.

10.5. Incompatible materials

Substances to avoid:
water

10.6. Hazardous decomposition products

Hazardous decomposition products:

hydrogen chloride

The substances/substance groups mentioned are formed by hydrolysis.

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 11.01.2023

Version: 13.0

Date previous version: 16.12.2020

Previous version: 12.0

Date / First version: 24.03.2003

Product: **Aluminium chloride anhydrous ground**

(ID no. 30041207/SDS_GEN_GB/EN)

Date of print 23.10.2025

SECTION 11: Toxicological Information

11.1. Information on toxicological effects

Acute toxicity

Assessment of acute toxicity:

The toxicity of the product is based on its corrosivity.

Of low toxicity after single ingestion.

Experimental/calculated data:

LD50 rat (oral): 3,450 - 3,470 mg/kg

(by inhalation): Study does not need to be conducted.

(dermal): Study does not need to be conducted.

Irritation

Assessment of irritating effects:

Corrosive! Damages skin and eyes.

Experimental/calculated data:

Skin corrosion/irritation

: The European Union (EU) has classified this substance with 'Causes burns.' (R34).

Serious eye damage/irritation

: Study does not need to be conducted.

Respiratory/Skin sensitization

Assessment of sensitization:

Skin sensitizing effects were not observed in animal studies.

Experimental/calculated data:

Guinea pig maximization test guinea pig: Non-sensitizing.

Germ cell mutagenicity

Assessment of mutagenicity:

No mutagenic effect was found in various tests with microorganisms and mammals. The product has not been fully tested. The statements have been derived in parts from products of a similar structure or composition.

Carcinogenicity

Assessment of carcinogenicity:

No reliable data was available concerning carcinogenic activity. The chemical structure does not suggest a specific alert for such an effect.

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 11.01.2023

Version: 13.0

Date previous version: 16.12.2020

Previous version: 12.0

Date / First version: 24.03.2003

Product: **Aluminium chloride anhydrous ground**

(ID no. 30041207/SDS_GEN_GB/EN)

Date of print 23.10.2025

Reproductive toxicity

Assessment of reproduction toxicity:

The results of animal studies gave no indication of a fertility impairing effect. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Developmental toxicity

Assessment of teratogenicity:

The potential to cause toxicity to development cannot be excluded when given in high doses. The product has not been tested. The statement has been derived from the structure of the product.

Specific target organ toxicity (single exposure)

Remarks: No applicable information available.

Repeated dose toxicity and Specific target organ toxicity (repeated exposure)

Assessment of repeated dose toxicity:

The substance may cause damage to the upper respiratory tract after repeated inhalation, as shown in animal studies. After repeated administration the prominent effect is the induction of corrosion.

The information available on the product provides no indication of toxicity on target organs after repeated exposure. The product has not been fully tested. The statements have been derived in parts from products of a similar structure or composition.

Aspiration hazard

not applicable

SECTION 12: Ecological Information

12.1. Toxicity

Assessment of aquatic toxicity:

There is a high probability that the product is not acutely harmful to aquatic organisms. The effect strongly depends on the pH-value.

Toxicity to fish:

LC50 (96 h) 20.3 mg/l, Pimephales promelas (EPA 72-1, semistatic)

Aquatic invertebrates:

EC50 (48 h) 27.3 mg/l, Daphnia magna (Directive 84/449/EEC, C.2, static)

The details of the toxic effect relate to the nominal concentration.

Aquatic plants:

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 11.01.2023

Version: 13.0

Date previous version: 16.12.2020

Previous version: 12.0

Date / First version: 24.03.2003

Product: **Aluminium chloride anhydrous ground**

(ID no. 30041207/SDS_GEN_GB/EN)

Date of print 23.10.2025

EC50 (72 h) 1.05 mg/l (growth rate), *Pseudokirchneriella subcapitata* (OECD Guideline 201, static) other TS

EC10 (72 h) 0.16 mg/l (growth rate), *Pseudokirchneriella subcapitata* (OECD Guideline 201, static) other TS

Microorganisms/Effect on activated sludge:

EC10 (180 min) > 1,000 mg/l, activated sludge, domestic, non-adapted (OECD Guideline 209, aerobic)

The details of the toxic effect relate to the nominal concentration.

Chronic toxicity to fish:

No observed effect concentration (7 d) 0.16 mg/l, *Pimephales promelas* (other, semistatic)

Chronic toxicity to aquatic invertebrates:

No observed effect concentration (6 d) 0.34 mg/l, *Ceriodaphnia dubia* (other, semistatic)

Assessment of terrestrial toxicity:

No toxic effects have been observed in studies with soil living organisms.

Soil living organisms:

LC50 (14 d) > 1,000 mg/kg, *Eisenia* sp. (Range-finding-study, artificial soil)

The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Terrestrial plants:

No data available.

Other terrestrial non-mammals:

No data available.

12.2. Persistence and degradability

Assessment biodegradation and elimination (H₂O):

Not applicable for inorganic substances.

Elimination information:

not applicable

Assessment of stability in water:

In contact with water the substance will hydrolyse rapidly.

Information on Stability in Water (Hydrolysis):

not applicable

12.3. Bioaccumulative potential

Assessment bioaccumulation potential:

Significant accumulation in organisms is not to be expected.

Bioaccumulation potential:

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 11.01.2023

Version: 13.0

Date previous version: 16.12.2020

Previous version: 12.0

Date / First version: 24.03.2003

Product: **Aluminium chloride anhydrous ground**

(ID no. 30041207/SDS_GEN_GB/EN)

Date of print 23.10.2025

Bioconcentration factor (BCF): 400 - 1,365, Fish (other)

12.4. Mobility in soil

Assessment transport between environmental compartments:

Adsorption in soil: No data available.

12.5. Results of PBT and vPvB assessment

The product does not fulfill the criteria for PBT (Persistent/bioaccumulative/toxic) and vPvB (very persistent/very bioaccumulative).

12.6. Other adverse effects

The substance is not listed in Regulation (EC) 1005/2009 on substances that deplete the ozone layer.

12.7. Additional information

Other ecotoxicological advice:

Inhibition of degradation activity in activated sludge is not to be anticipated during correct introduction of low concentrations.

SECTION 13: Disposal Considerations

13.1. Waste treatment methods

The UK Environmental Protection (Duty of Care) Regulations (EP) and amendments should be noted (United Kingdom).

This product and any uncleaned containers must be disposed of as hazardous waste in accordance with the 2005 Hazardous Waste Regulations and amendments (United Kingdom)

Contaminated packaging:

Contaminated packaging should be emptied as far as possible; then it can be passed on for recycling after being thoroughly cleaned.

SECTION 14: Transport Information

Land transport

ADR

UN number or ID number: UN1726

UN proper shipping name: ALUMINIUM CHLORIDE, ANHYDROUS

Transport hazard class(es): 8

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 11.01.2023

Version: 13.0

Date previous version: 16.12.2020

Previous version: 12.0

Date / First version: 24.03.2003

Product: **Aluminium chloride anhydrous ground**

(ID no. 30041207/SDS_GEN_GB/EN)

Date of print 23.10.2025

Packing group: II
Environmental hazards: no
Special precautions for user: Tunnel code: E

RID

UN number or ID number: UN1726
UN proper shipping name: ALUMINIUM CHLORIDE, ANHYDROUS
Transport hazard class(es): 8
Packing group: II
Environmental hazards: no
Special precautions for user: None known

Inland waterway transport

ADN

UN number or ID number: UN1726
UN proper shipping name: ALUMINIUM CHLORIDE, ANHYDROUS
Transport hazard class(es): 8
Packing group: II
Environmental hazards: no
Special precautions for user: None known

Transport in inland waterway vessel

Not evaluated

Sea transport

IMDG

UN number or ID number: UN 1726
UN proper shipping name: ALUMINIUM CHLORIDE, ANHYDROUS
Transport hazard class(es): 8
Packing group: II
Environmental hazards: no
Marine pollutant: NO
Special precautions for user:

Air transport

IATA/ICAO

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 11.01.2023

Version: 13.0

Date previous version: 16.12.2020

Previous version: 12.0

Date / First version: 24.03.2003

Product: **Aluminium chloride anhydrous ground**

(ID no. 30041207/SDS_GEN_GB/EN)

Date of print 23.10.2025

UN number or ID number: UN 1726
UN proper shipping name: ALUMINIUM CHLORIDE, ANHYDROUS
Transport hazard class(es): 8
Packing group: II
Environmental hazards: No Mark as dangerous for the environment is needed
Special precautions for user: None known

14.1. UN number or ID number

See corresponding entries for "UN number or ID number" for the respective regulations in the tables above.

14.2. UN proper shipping name

See corresponding entries for "UN proper shipping name" for the respective regulations in the tables above.

14.3. Transport hazard class(es)

See corresponding entries for "Transport hazard class(es)" for the respective regulations in the tables above.

14.4. Packing group

See corresponding entries for "Packing group" for the respective regulations in the tables above.

14.5. Environmental hazards

See corresponding entries for "Environmental hazards" for the respective regulations in the tables above.

14.6. Special precautions for user

See corresponding entries for "Special precautions for user" for the respective regulations in the tables above.

14.7. Maritime transport in bulk according to IMO instruments

Maritime transport in bulk is not intended.

Further information

This product is subject to the most recent edition of "The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment Regulations" and their amendments (United Kingdom).

SECTION 15: Regulatory Information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Prohibitions, Restrictions and Authorizations

Annex XVII of Regulation (EC) No 1907/2006: Number on List: 75

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 11.01.2023

Version: 13.0

Date previous version: 16.12.2020

Previous version: 12.0

Date / First version: 24.03.2003

Product: **Aluminium chloride anhydrous ground**

(ID no. 30041207/SDS_GEN_GB/EN)

Date of print 23.10.2025

Directive 2012/18/EU - Control of Major Accident Hazards involving dangerous substances (EU):

List entry in regulation: O1

The data should be considered when making any assessment under the Control of Substances Hazardous to Health Regulations (COSHH), and related guidance, for example, 'COSHH Essentials' (United Kingdom).

If other regulatory information applies that is not already provided elsewhere in this safety data sheet, then it is described in this subsection.

15.2. Chemical Safety Assessment

Chemical Safety Assessment performed

SECTION 16: Other Information

Assessment of the hazard classes according to UN GHS criteria (most recent version)

Acute Tox. 5 (oral)

Skin Corr./Irrit. 1B

Eye Dam./Irrit. 1

This product is of industrial quality and unless otherwise specified or agreed intended exclusively for industrial use.

Full text of the classifications, including the hazard classes and the hazard statements, if mentioned in section 2 or 3:

Skin Corr./Irrit.

Skin corrosion/irritation

Eye Dam./Irrit.

Serious eye damage/eye irritation

H314

Causes severe skin burns and eye damage.

Abbreviations

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road.
ADN = The European Agreement concerning the International Carriage of Dangerous Goods by Inland waterways. ATE = Acute Toxicity Estimates. CAO = Cargo Aircraft Only. CAS = Chemical Abstract Service. CLP = Classification, Labelling and Packaging of substances and mixtures. DIN = German national organization for standardization. DNEL = Derived No Effect Level. EC50 = Effective concentration median for 50% of the population. EC = European Community. EN = European Standards. IARC = International Agency for Research on Cancer. IATA = International Air Transport Association. IBC-Code = Intermediate Bulk Container code. IMDG = International Maritime Dangerous Goods Code. ISO = International Organization for Standardization. STEL = Short-Term Exposure Limit. LC50 = Lethal concentration median for 50% of the population. LD50 = Lethal dose median for 50% of the population. TLV = Threshold Limit Value. MARPOL = The International Convention for the Prevention of Pollution from Ships. NEN = Dutch Norm. NOEC = No Observed Effect Concentration. OEL = Occupational Exposure Limit. OECD = Organization for Economic Cooperation and Development. PBT = Persistent, Bioaccumulative and Toxic. PNEC = Predicted No Effect Level. PPM = Parts per million. RID = The European Agreement concerning the International Carriage of Dangerous Goods by Rail. TWA = Time

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 11.01.2023

Version: 13.0

Date previous version: 16.12.2020

Previous version: 12.0

Date / First version: 24.03.2003

Product: **Aluminium chloride anhydrous ground**

(ID no. 30041207/SDS_GEN_GB/EN)

Date of print 23.10.2025

Weight Average. UN-number = UN number at transport. vPvB = very Persistent and very Bioaccumulative.

The data contained in this safety data sheet are based on our current knowledge and experience and describe the product only with regard to safety requirements. This safety data sheet is neither a Certificate of Analysis (CoA) nor technical data sheet and shall not be mistaken for a specification agreement. Identified uses in this safety data sheet do neither represent an agreement on the corresponding contractual quality of the substance/mixture nor a contractually designated use. It is the responsibility of the recipient of the product to ensure any proprietary rights and existing laws and legislation are observed.

Vertical lines in the left hand margin indicate an amendment from the previous version.

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 11.01.2023

Version: 13.0

Date previous version: 16.12.2020

Previous version: 12.0

Date / First version: 24.03.2003

Product: **Aluminium chloride anhydrous ground**

(ID no. 30041207/SDS_GEN_GB/EN)

Date of print 23.10.2025

Annex: Exposure Scenarios

Index

1. Use as Reactive process agent, (in inorganic synthesis), (in organic synthesis), (use in industrial settings)

SU8, SU9; ERC4, ERC6a, ERC6b; PROC1, PROC2, PROC3

2. After hydrolysis, Use as a Process chemical, Use in process water treatment, Use in sewage water treatment, (use in industrial settings)

ERC6b; PROC3, PROC5, PROC8b

3. Use in laboratories, (use in industrial settings)

ERC4, ERC6a, ERC6b; PROC15

4. After hydrolysis, Use as a Process chemical, Use in process water treatment, Use in sewage water treatment, (use in professional settings)

SU5, SU6b, SU23; ERC8b; PROC3, PROC5, PROC8b

5. Use in laboratories, (use in professional settings)

ERC8b; PROC15

1. Short title of exposure scenario

Use as Reactive process agent, (in inorganic synthesis), (in organic synthesis), (use in industrial settings)

SU8, SU9; ERC4, ERC6a, ERC6b; PROC1, PROC2, PROC3

Control of exposure and risk management measures

Contributing exposure scenario	
Use descriptors covered	ERC4: Use of non-reactive processing aid at industrial site (no inclusion into or onto article) As no environmental hazard was identified no environmental-related exposure assessment and risk characterization was performed.
Operational conditions	
Contributing exposure scenario	
Use descriptors covered	ERC6a: Use of intermediate As no environmental hazard was identified no environmental-related exposure assessment and risk characterization was performed.
Operational conditions	
Contributing exposure scenario	
Use descriptors covered	ERC6b: Use of reactive processing aid at industrial site (no

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 11.01.2023

Version: 13.0

Date previous version: 16.12.2020

Previous version: 12.0

Date / First version: 24.03.2003

Product: **Aluminium chloride anhydrous ground**

(ID no. 30041207/SDS_GEN_GB/EN)

Date of print 23.10.2025

	inclusion into or onto article) As no environmental hazard was identified no environmental-related exposure assessment and risk characterization was performed.
Operational conditions	

Contributing exposure scenario	
Use descriptors covered	PROC1: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions. Use domain: industrial
Operational conditions	
Physical state	Solid, low dustiness
Vapour pressure of the substance during use	0.003 Pa
Risk Management Measures	
Avoid skin contact. Clean up contamination as soon as they occur. Ensure good work practices are implemented. Provide basic employee training to prevent/minimize exposures. Supervision in place to check that the RMMs in place are being used correctly and OCs followed.	
Ensure material transfers are under containment or extract ventilation Fill containers/cans at dedicated filling points supplied with LEV Handle substance within closed system.	
Avoid inhalation of the product.	
Use suitable eye protection.	
Avoid skin contact.	
Wear suitable gloves tested to EN ISO 374-1.	
Avoid inhalation of the product.	
Exposure estimate and reference to its source	
Assessment method	Qualitative assessment

Contributing exposure scenario	
Use descriptors covered	PROC2: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions Use domain: industrial
Operational conditions	
Physical state	Solid, low dustiness

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 11.01.2023

Version: 13.0

Date previous version: 16.12.2020

Previous version: 12.0

Date / First version: 24.03.2003

Product: **Aluminium chloride anhydrous ground**

(ID no. 30041207/SDS_GEN_GB/EN)

Date of print 23.10.2025

Vapour pressure of the substance during use	0.003 Pa
Risk Management Measures	
Avoid skin contact. Clean up contamination as soon as they occur. Ensure good work practices are implemented. Provide basic employee training to prevent/minimize exposures. Supervision in place to check that the RMMs in place are being used correctly and OCs followed.	
Ensure material transfers are under containment or extract ventilation Fill containers/cans at dedicated filling points supplied with LEV Handle substance within closed system.	
Avoid inhalation of the product.	
Use suitable eye protection.	
Avoid skin contact.	
Wear suitable gloves tested to EN ISO 374-1.	
Avoid inhalation of the product.	
Exposure estimate and reference to its source	
Assessment method	Qualitative assessment

Contributing exposure scenario	
Use descriptors covered	PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition Use domain: industrial
Operational conditions	
Physical state	Solid, low dustiness
Vapour pressure of the substance during use	0.003 Pa
Risk Management Measures	
Avoid skin contact. Clean up contamination as soon as they occur. Ensure good work practices are implemented. Provide basic employee training to prevent/minimize exposures. Supervision in place to check that the RMMs in place are being used correctly and OCs followed.	
Ensure material transfers are under containment or extract ventilation Fill containers/cans at dedicated filling	

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 11.01.2023

Version: 13.0

Date previous version: 16.12.2020

Previous version: 12.0

Date / First version: 24.03.2003

Product: **Aluminium chloride anhydrous ground**

(ID no. 30041207/SDS_GEN_GB/EN)

Date of print 23.10.2025

points supplied with LEV Handle substance within closed system.	
Avoid inhalation of the product.	
Use suitable eye protection.	
Avoid skin contact.	
Wear suitable gloves tested to EN ISO 374-1.	
Avoid inhalation of the product.	
Exposure estimate and reference to its source	
Assessment method	Qualitative assessment

2. Short title of exposure scenario

After hydrolysis, Use as a Process chemical, Use in process water treatment, Use in sewage water treatment, (use in industrial settings)

ERC6b; PROC3, PROC5, PROC8b

Control of exposure and risk management measures

Contributing exposure scenario	
Use descriptors covered	ERC6b: Use of reactive processing aid at industrial site (no inclusion into or onto article) As no environmental hazard was identified no environmental-related exposure assessment and risk characterization was performed.
Operational conditions	

Contributing exposure scenario	
Use descriptors covered	PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition Use domain: industrial
Operational conditions	
Physical state	liquid
Vapour pressure of the substance during use	0.003 Pa
Risk Management Measures	
Avoid skin contact. Clean up contamination as soon as they occur. Ensure good work practices are implemented. Provide basic employee training to prevent/minimize exposures. Supervision in place to check that the RMMs in place are being used correctly and OCs	

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 11.01.2023

Version: 13.0

Date previous version: 16.12.2020

Previous version: 12.0

Date / First version: 24.03.2003

Product: **Aluminium chloride anhydrous ground**

(ID no. 30041207/SDS_GEN_GB/EN)

Date of print 23.10.2025

followed.	
Ensure material transfers are under containment or extract ventilation Fill containers/cans at dedicated filling points supplied with LEV Handle substance within closed system.	
Avoid inhalation of the product.	
Use suitable eye protection.	
Avoid skin contact.	
Wear suitable gloves tested to EN ISO 374-1.	
Ensure that no inhalable aerosols are generated.	
Avoid inhalation of the product.	
Exposure estimate and reference to its source	
Assessment method	Qualitative assessment

Contributing exposure scenario	
Use descriptors covered	PROC5: Mixing or blending in batch processes Use domain: industrial
Operational conditions	
Physical state	liquid
Vapour pressure of the substance during use	0.003 Pa
Risk Management Measures	
Avoid skin contact. Clean up contamination as soon as they occur. Ensure good work practices are implemented. Provide basic employee training to prevent/minimize exposures. Supervision in place to check that the RMMs in place are being used correctly and OCs followed.	
Ensure material transfers are under containment or extract ventilation Fill containers/cans at dedicated filling points supplied with LEV	
Avoid inhalation of the product.	
Use suitable eye protection.	
Avoid skin contact.	
Wear suitable gloves tested to EN ISO 374-1.	
Ensure that no inhalable aerosols are generated.	
Avoid inhalation of the product.	
Exposure estimate and reference to its source	
Assessment method	Qualitative assessment

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 11.01.2023

Version: 13.0

Date previous version: 16.12.2020

Previous version: 12.0

Date / First version: 24.03.2003

Product: **Aluminium chloride anhydrous ground**

(ID no. 30041207/SDS_GEN_GB/EN)

Date of print 23.10.2025

Contributing exposure scenario	
Use descriptors covered	PROC8b: Transfer of substance or mixture (charging and discharging) at dedicated facilities Use domain: industrial
Operational conditions	
Physical state	liquid
Vapour pressure of the substance during use	0.003 Pa
Risk Management Measures	
Avoid skin contact. Clean up contamination as soon as they occur. Ensure good work practices are implemented. Provide basic employee training to prevent/minimize exposures. Supervision in place to check that the RMMs in place are being used correctly and OCs followed.	
Ensure material transfers are under containment or extract ventilation Fill containers/cans at dedicated filling points supplied with LEV	
Avoid inhalation of the product.	
Use suitable eye protection.	
Avoid skin contact.	
Wear suitable gloves tested to EN ISO 374-1.	
Ensure that no inhalable aerosols are generated.	
Avoid inhalation of the product., In case of insufficient ventilation:, Wear a suitable respiratory protection with adequate effectiveness .	
Exposure estimate and reference to its source	
Assessment method	Qualitative assessment

3. Short title of exposure scenario

Use in laboratories, (use in industrial settings)

ERC4, ERC6a, ERC6b; PROC15

Control of exposure and risk management measures

Contributing exposure scenario	
Use descriptors covered	ERC4: Use of non-reactive processing aid at industrial site (no inclusion into or onto article)

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 11.01.2023

Version: 13.0

Date previous version: 16.12.2020

Previous version: 12.0

Date / First version: 24.03.2003

Product: **Aluminium chloride anhydrous ground**

(ID no. 30041207/SDS_GEN_GB/EN)

Date of print 23.10.2025

	As no environmental hazard was identified no environmental-related exposure assessment and risk characterization was performed.
--	---

Operational conditions

Contributing exposure scenario	
Use descriptors covered	ERC6a: Use of intermediate As no environmental hazard was identified no environmental-related exposure assessment and risk characterization was performed.
Operational conditions	

Contributing exposure scenario	
Use descriptors covered	ERC6b: Use of reactive processing aid at industrial site (no inclusion into or onto article) As no environmental hazard was identified no environmental-related exposure assessment and risk characterization was performed.
Operational conditions	

Contributing exposure scenario	
Use descriptors covered	PROC15: Use a laboratory reagent. Use domain: industrial
Operational conditions	
Physical state	Solid, low dustiness
Vapour pressure of the substance during use	0.003 Pa

Risk Management Measures

Avoid skin contact. Clean up contamination as soon as they occur. Ensure good work practices are implemented. Provide basic employee training to prevent/minimize exposures. Supervision in place to check that the RMMs in place are being used correctly and OCs followed.	
Ensure material transfers are under containment or extract ventilation Fill containers/cans at dedicated filling points supplied with LEV	
Avoid inhalation of the product.	
Use suitable eye protection.	
Avoid skin contact.	
Wear suitable gloves tested to EN	

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 11.01.2023

Version: 13.0

Date previous version: 16.12.2020

Previous version: 12.0

Date / First version: 24.03.2003

Product: **Aluminium chloride anhydrous ground**

(ID no. 30041207/SDS_GEN_GB/EN)

Date of print 23.10.2025

ISO 374-1.	
Avoid inhalation of the product., Use a local exhaust ventilation with adequate effectiveness.	
Exposure estimate and reference to its source	
Assessment method	Qualitative assessment

4. Short title of exposure scenario

After hydrolysis, Use as a Process chemical, Use in process water treatment, Use in sewage water treatment, (use in professional settings)

SU5, SU6b, SU23; ERC8b; PROC3, PROC5, PROC8b

Control of exposure and risk management measures

Contributing exposure scenario	
Use descriptors covered	ERC8b: Widespread use of reactive processing aid (no inclusion into or onto article, indoor) As no environmental hazard was identified no environmental-related exposure assessment and risk characterization was performed.
Operational conditions	

Contributing exposure scenario	
Use descriptors covered	PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition Use domain: professional
Operational conditions	
Physical state	liquid
Vapour pressure of the substance during use	0.003 Pa
Risk Management Measures	
Avoid skin contact. Clean up contamination as soon as they occur. Ensure good work practices are implemented. Provide basic employee training to prevent/minimize exposures. Supervision in place to check that the RMMs in place are being used correctly and OCs followed.	
Ensure material transfers are under containment or extract ventilation Fill containers/cans at dedicated filling points supplied with LEV Handle	

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 11.01.2023

Version: 13.0

Date previous version: 16.12.2020

Previous version: 12.0

Date / First version: 24.03.2003

Product: **Aluminium chloride anhydrous ground**

(ID no. 30041207/SDS_GEN_GB/EN)

Date of print 23.10.2025

substance within closed system.	
Avoid inhalation of the product.	
Use suitable eye protection.	
Avoid skin contact.	
Wear suitable gloves tested to EN ISO 374-1.	
Ensure that no inhalable aerosols are generated.	
Avoid inhalation of the product.	
Exposure estimate and reference to its source	
Assessment method	Qualitative assessment

Contributing exposure scenario	
Use descriptors covered	PROC5: Mixing or blending in batch processes Use domain: professional
Operational conditions	
Physical state	liquid
Vapour pressure of the substance during use	0.003 Pa
Risk Management Measures	
Avoid skin contact. Clean up contamination as soon as they occur. Ensure good work practices are implemented. Provide basic employee training to prevent/minimize exposures. Supervision in place to check that the RMMs in place are being used correctly and OCs followed.	
Ensure material transfers are under containment or extract ventilation Fill containers/cans at dedicated filling points supplied with LEV	
Avoid inhalation of the product.	
Use suitable eye protection.	
Avoid skin contact.	
Wear suitable gloves tested to EN ISO 374-1.	
Ensure that no inhalable aerosols are generated.	
Avoid inhalation of the product.	
Exposure estimate and reference to its source	
Assessment method	Qualitative assessment

Contributing exposure scenario	
Use descriptors covered	PROC8b: Transfer of substance or mixture (charging and discharging) at dedicated facilities Use domain: professional

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 11.01.2023

Version: 13.0

Date previous version: 16.12.2020

Previous version: 12.0

Date / First version: 24.03.2003

Product: **Aluminium chloride anhydrous ground**

(ID no. 30041207/SDS_GEN_GB/EN)

Date of print 23.10.2025

Operational conditions	
Physical state	liquid
Vapour pressure of the substance during use	0.003 Pa
Risk Management Measures	
Avoid skin contact. Clean up contamination as soon as they occur. Ensure good work practices are implemented. Provide basic employee training to prevent/minimize exposures. Supervision in place to check that the RMMs in place are being used correctly and OCs followed.	
Ensure material transfers are under containment or extract ventilation Fill containers/cans at dedicated filling points supplied with LEV	
Avoid inhalation of the product.	
Use suitable eye protection.	
Avoid skin contact.	
Wear suitable gloves tested to EN ISO 374-1.	
Ensure that no inhalable aerosols are generated.	
Avoid inhalation of the product., In case of insufficient ventilation:, Wear a suitable respiratory protection with adequate effectiveness .	
Exposure estimate and reference to its source	
Assessment method	Qualitative assessment

5. Short title of exposure scenario

Use in laboratories, (use in professional settings)

ERC8b; PROC15

Control of exposure and risk management measures

Contributing exposure scenario	
Use descriptors covered	ERC8b: Widespread use of reactive processing aid (no inclusion into or onto article, indoor) As no environmental hazard was identified no environmental-related exposure assessment and risk characterization was performed.
Operational conditions	

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 11.01.2023

Version: 13.0

Date previous version: 16.12.2020

Previous version: 12.0

Date / First version: 24.03.2003

Product: **Aluminium chloride anhydrous ground**

(ID no. 30041207/SDS_GEN_GB/EN)

Date of print 23.10.2025

Contributing exposure scenario	
Use descriptors covered	PROC15: Use a laboratory reagent. Use domain: professional
Operational conditions	
Physical state	Solid, low dustiness
Vapour pressure of the substance during use	0.003 Pa
Risk Management Measures	
Avoid skin contact. Clean up contamination as soon as they occur. Ensure good work practices are implemented. Provide basic employee training to prevent/minimize exposures. Supervision in place to check that the RMMs in place are being used correctly and OCs followed.	
Ensure material transfers are under containment or extract ventilation Fill containers/cans at dedicated filling points supplied with LEV	
Avoid inhalation of the product.	
Use suitable eye protection.	
Avoid skin contact.	
Wear suitable gloves tested to EN ISO 374-1.	
Avoid inhalation of the product., Use a local exhaust ventilation with adequate effectiveness.	
Exposure estimate and reference to its source	
Assessment method	Qualitative assessment
