

Product Data Sheet

PuriStar® R3-81 T5x3

Purification of Refinery Off-Gas Streams

PuriStar[®] R3-81 is a robust copper catalyst used in sulfided form for the removal of O₂, NO_x and traces of acetylene from refinery off-gas. PuriStar[®] R3-81 is the focal point of a group of products used for the recovery of ethylene from refinery off-gases.



BASF PuriStar® R3-81 comes in the form of tablets with a nominal diameter of 5 mm and height of 3 mm (approx. 3/16" x 1/8").

Product Application

Refinery off-gas (ROG) refers to a gas mixture consisting mostly of hydrogen, methane, ethylene, ethane and a number of different impurities. This type of gas is e.g. generated in catalytic cracking units (FCC, DCC, CPP). The H₂ and C₂H₄ present in the stream can be recovered in ethylene recovery units (ERU).

R3-81 is used in sulfided form. The sulfiding is typically done in situ (in the reactor itself). For smaller amounts, an ex-situ sulfiding at a recommended toller is also possible. For details, please contact BASF.

R3-81 removes O_2 , NO_x and traces of acetylene by selective hydrogenation while showing low olefin loss.

R3-81 is used in gases with high contents of CO and avoids the formation of carbonyls (like Ni carbonyls).

The operating temperature of R3-81 is 180 to 275°C (360 to 530°F) depending on the off-gas composition.

The composition and its properties make R3-81 suitable for regenerations and tolerant to poisons like AsH₃, chlorine or mercury.

Typical Properties	
Chemical	
Main Components	CuO
Balance	Silicate with promoters
Physical	
Crush Strength	Approx. 5 kg (11 lbs), side wall
Bulk Density	~ 900 kg/m³ (56 lbs/ft³), tapped ~ 830 kg/m³ (52 lbs/ft³), sock loaded

Packaging

- 800 kg net (1763.7 lbs) in 1150 l super sacks (IBC flexible)
- 100 kg net (220.5 lbs) in 120 l steel drums

Shipping Point

Ludwigshafen, Germany

About Us

BASF is a leading global manufacturer of catalysts for the chemical industry, with solutions across the chemical value chain. The business comprises chemical catalysts and adsorbents and custom catalysts. Priority is given to developing new and improved products that enable the chemical industry transformation to net-zero emissions.

BASF's chemical catalysts and adsorbents business is part of the company's Performance Chemicals division. The division's portfolio also includes refinery catalysts, fuel and lubricant solutions, as well as oilfield chemicals and mining solutions. Customers from a variety of industries including Chemicals, Plastics, Consumer Goods, Energy & Resources and Automotive & Transportation benefit from our innovative solutions

BASF - We create chemistry



Americas

BASF Corporation Phone: +1-732-205-5000

Email: catalysts-americas@basf.com

Asia Pacific

BASF (China) Company Limited Phone: +86-21-2039 2549 Email: catalysts-asia@basf.com

Europe, Middle East, Africa

BASF Services GmbH Tel: +49-30-2005 5000

Email: catalysts-europe@basf.com

Although all statements and information in this publication are believed to be accurate and reliable, they are presented gratis and for guidance only, and risks and liability for results obtained by use of the products or application of the suggestions described are assumed by the user. NO WARRANTIES OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH. Statements or suggestions concerning possible use of the products are made without representation or warranty that any such use is free of patent infringement and are not recommendations to infringe any patent. The user should not assume that toxicity data and safety measures are indicated or that other measures may not be required. © 2015 BASF