

Safety data sheet

Page: 1/15

BASF Safety data sheet according to the United Nations' Globally Harmonized System (UN GHS)

Date / Revised: 08.10.2025 Version: 9.0

Product: 3-METHYLBUTANOL-1

(ID no. 30036711/SDS_GEN_00/EN)

Date of print 08.10.2025

1. Identification

Product identifier

3-METHYLBUTANOL-1

Chemical name: 3-methylbutan-1-ol

CAS Number: 123-51-3

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses: process chemical, solvent(s)

Details of the supplier of the safety data sheet

Company:
BASF SE
67056 Ludwigshafen
GERMANY
Operating Division Petrochemicals

Telephone: +49 621 60-42151

E-mail address: sds-petrochemicals@basf.com

Emergency telephone number

International emergency number: Telephone: +49 180 2273-112

2. Hazards Identification

Date / Revised: 08.10.2025 Version: 9.0

Product: 3-METHYLBUTANOL-1

(ID no. 30036711/SDS_GEN_00/EN)

Date of print 08.10.2025

Classification of the substance or mixture

According to UN GHS criteria

Flam. Liq. 3

Acute Tox. 5 (dermal)

Skin Irrit. 2 Eye Dam. 1

STOT SE 3 (irritating to respiratory system)

Aquatic Chronic 2

For the classifications not written out in full in this section the full text can be found in section 16.

Label elements

Globally Harmonized System (GHS)

Pictogram:







Signal Word: Danger

Hazard Statement:

H226 Flammable liquid and vapour. H318 Causes serious eye damage.

H315 Causes skin irritation.

H313 May be harmful in contact with skin. H335 May cause respiratory irritation.

H411 Toxic to aquatic life with long lasting effects.

Precautionary Statements (Prevention):

P280 Wear protective gloves and eye protection or face protection.

P273 Avoid release to the environment.

P271 Use only outdoors or in a well-ventilated area.

P210 Keep away from heat, hot surfaces, sparks, open flames and other

ignition sources. No smoking.

P261 Avoid breathing mist or vapour or spray.
P243 Take action to prevent static discharges.

P241 Use explosion-proof electrical, ventilating and lighting equipment.

P264 Wash contaminated body parts thoroughly after handling. P240 Ground and bond container and receiving equipment.

P242 Use non-sparking tools.

Precautionary Statements (Response):

Date / Revised: 08.10.2025 Version: 9.0

Product: 3-METHYLBUTANOL-1

(ID no. 30036711/SDS_GEN_00/EN)

Date of print 08.10.2025

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER or physician.

P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for

breathing.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing.

Rinse skin with water or shower.

P391 Collect spillage.

P362 + P364 Take off contaminated clothing and wash it before reuse.

P370 + P378 In case of fire: Use alcohol-resistant foam, carbon dioxide, dry powder

or water spray for extinction.

Precautionary Statements (Storage):

P233 Keep container tightly closed.

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

Precautionary Statements (Disposal):

P501 Dispose of contents and container to hazardous or special waste

collection point.

Labeling of special preparations (GHS):

Repeated exposure may cause skin dryness or cracking.

Other hazards

According to UN GHS criteria

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

See section 12 - Results of PBT and vPvB assessment.

3. Composition/Information on Ingredients

Substances

Chemical nature

3-Methylbutan-1-ol (Content (W/W): >= 98,5 %)

CAS Number: 123-51-3 EC-Number: 204-633-5

Hazardous ingredients (GHS)

According to UN GHS criteria

Pentan-1-ol

Date / Revised: 08.10.2025 Version: 9.0

Product: 3-METHYLBUTANOL-1

(ID no. 30036711/SDS_GEN_00/EN)

Date of print 08.10.2025

Content (W/W): > 0 % - < 3 % Flam. Liq. 3
CAS Number: 71-41-0 Acute Tox. 5 (oral)
EC-Number: 200-752-1 Acute Tox. 5 (dermal)
INDEX-Number: 603-200-00-1 Skin Irrit. 2

Skin Irrit. 2 Eye Dam. 1

STOT SE 3 (irr. to respiratory syst.)

Aquatic Chronic 2

H226, H318, H315, H335, H303 + H313, H411

For the classifications not written out in full in this section the full text can be found in section 16.

Mixtures

Not applicable

4. First-Aid Measures

Description of first aid measures

First aid personnel should pay attention to their own safety. If the patient is likely to become unconscious, place and transport in stable sideways position (recovery position). Immediately remove contaminated clothing.

If inhaled:

Keep patient calm, remove to fresh air, seek medical attention. Immediately administer a corticosteroid from a controlled/metered dose inhaler.

On skin contact:

Immediately wash thoroughly with plenty of water, apply sterile dressings, consult a skin specialist.

On contact with eyes:

Immediately wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.

On ingestion:

Immediately rinse mouth and then drink 200-300 ml of water, seek medical attention.

Most important symptoms and effects, both acute and delayed

Symptoms: Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11., (Further) symptoms and / or effects are not known so far

Hazards: Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11. (Further) symptoms and / or effects are not known so far

Date / Revised: 08.10.2025 Version: 9.0

Product: 3-METHYLBUTANOL-1

(ID no. 30036711/SDS_GEN_00/EN)

Date of print 08.10.2025

Indication of any immediate medical attention and special treatment needed

Treatment: Treat according to symptoms (decontamination, vital functions), no known specific antidote.

5. Fire-Fighting Measures

Extinguishing media

Suitable extinguishing media:

dry powder, water spray, carbon dioxide, alcohol-resistant foam

Unsuitable extinguishing media for safety reasons: water jet

Additional information:

Use extinguishing measures to suit surroundings.

Special hazards arising from the substance or mixture

Flammable liquid Cool endangered containers with water-spray. See SDS section 7 - Handling and storage.

Advice for fire-fighters

Special protective equipment:

Wear a self-contained breathing apparatus. Special protective equipment for firefighters

Further information:

Evacuate area of all unnecessary personnel. Fight fire from maximum distance.

Extend fire extinguishing measures to the surroundings. Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

6. Accidental Release Measures

High risk of slipping due to leakage/spillage of product.

Release of substance/product can cause fire or explosion. Shut off or stop source of leak. Shut off or stop released substance/product under safe conditions.

Pack in tightly closed containers for disposal.

Personal precautions, protective equipment and emergency procedures

Handle in accordance with good industrial hygiene and safety practice.

Avoid all sources of ignition: heat, sparks, open flame. Use antistatic tools.

Environmental precautions

Discharge into the environment must be avoided.

Methods and material for containment and cleaning up

Date / Revised: 08.10.2025 Version: 9.0

Product: 3-METHYLBUTANOL-1

(ID no. 30036711/SDS_GEN_00/EN)

Date of print 08.10.2025

Pick up with suitable appliance and dispose of. Spills should be contained, solidified, and placed in suitable containers for disposal. Dispose of absorbed material in accordance with regulations.

7. Handling and Storage

Precautions for safe handling

Handle in accordance with good industrial hygiene and safety practice.

Protection against fire and explosion:

Avoid all sources of ignition: heat, sparks, open flame. Ground all transfer equipment properly to prevent electrostatic discharge.

Conditions for safe storage, including any incompatibilities

Further information on storage conditions: Containers should be stored tightly sealed in a dry place.

Specific end use(s)

For the relevant identified use(s) listed in Section 1 the advice mentioned in this section 7 is to be observed.

8. Exposure Controls/Personal Protection

Control parameters

Components with occupational exposure limits

71-41-0: Pentan-1-ol

123-51-3: 3-Methylbutan-1-ol

Exposure controls

Personal protective equipment

Respiratory protection:

Wear respiratory protection if ventilation is inadequate. Gas filter for gases/vapours of organic compounds (boiling point >65 °C, e. g. EN 14387 Type A)

Hand protection:

Chemical resistant protective gloves (EN ISO 374-1)

Suitable materials also with prolonged, direct contact (Recommended: Protective index 6, corresponding > 480 minutes of permeation time according to EN ISO 374-1): nitrile rubber (NBR) - 0.4 mm coating thickness

Manufacturer's directions for use should be observed because of great diversity of types. Supplementary note: The specifications are based on tests, literature data and information of glove manufacturers or are derived from similar substances by analogy. Due to many conditions (e.g. temperature) it must be considered, that the practical usage of a chemical-protective glove in practice may be much shorter than the permeation time determined through testing.

Eye protection:

Date / Revised: 08.10.2025 Version: 9.0

Product: 3-METHYLBUTANOL-1

(ID no. 30036711/SDS_GEN_00/EN)

Date of print 08.10.2025

Tightly fitting safety goggles (splash goggles) (e.g. EN 166)

Body protection:

Body protection must be chosen depending on activity and possible exposure, e.g. apron, protecting boots, chemical-protection suit (according to EN 14605 in case of splashes or EN ISO 13982 in case of dust).

General safety and hygiene measures

Avoid contact with the skin, eyes and clothing. Avoid inhalation of vapour. Wearing of closed work clothing is required additionally to the stated personal protection equipment.

9. Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

State of matter: liquid Form: liquid Colour: colourless Odour: sweetish

Odour threshold:

not determined

glass transition temperature: -147 °C (measured) Boiling point: 130.7 °C (measured)

(1.013,25 hPa)

Boiling range:

No data available.

Flammable. Flammability: (derived from flash point)

Lower explosion limit: 1,0 %(V) (air)

(37,4 °C)

Upper explosion limit:

For liquids not relevant for classification and labelling.

Flash point: 43.5 °C (ISO 13736, closed cup)

Auto-ignition temperature: 335 °C (DIN 51794)

Thermal decomposition: No decomposition if stored and handled as prescribed/indicated.

pH value: (internal method) 6,5 Viscosity, kinematic: 5,32 mm2/s (DIN 51562)

(20 °C)

Viscosity, dynamic: 4,3 mPa.s (20 °C)

Thixotropy: not thixotropic

Solubility in water: Literature data. (other)

26.400 mg/l, 2,64 %(m)

(19,8 °C)

Solubility (qualitative) solvent(s): organic solvents

soluble

Partitioning coefficient n-octanol/water (log Kow): 1,35 (measured)

(23 °C; pH value: approx. 6,5)

Vapour pressure: 3 hPa (measured)

(20 °C) dynamic

Relative density: 0,8080

(20 °C)

Date / Revised: 08.10.2025 Version: 9.0

Product: 3-METHYLBUTANOL-1

(ID no. 30036711/SDS_GEN_00/EN)

Date of print 08.10.2025

Density: 0,8080 g/cm3 (DIN 53217-5)

(20 °C)

Relative vapour density (air):3,03 (calculated)

(20 °C)

Heavier than air.

Particle characteristics

Particle size distribution: The substance / product is marketed or used in a non solid or granular

form. -

9.2. Other information

Information with regard to physical hazard classes

Explosives

Explosion hazard: Based on the chemical structure

there is no indication of explosive

properties.

Impact sensitivity: not shock-sensitive

Based on the chemical structure there is no shock-sensitivity.

Oxidizing properties

Fire promoting properties: Based on its structural properties

the product is not classified as

oxidizing.

Flammable liquids

Sustained combustibility:

not determined

Pyrophoric properties

Self-ignition temperature: Test type: Spontaneous self-

ignition at room-temperature.

(calculated)

Based on its structural properties the product is not classified as self-

igniting.

Self-heating substances and mixtures

Self heating ability: not applicable, the product is a liquid

Substances and mixtures, which emit flammable gases in contact with water

Formation of flammable gases:

Forms no flammable gases in the presence of water.

Corrosion to metals

No corrosive effect on metal.

Other safety characteristics

pKA:

The substance does not dissociate.

Adsorption/water - soil:

KOC: 5,32; log KOC: 0,73

Surface tension:

Based on chemical structure, surface

activity is not to be expected.

Molar mass:

88,15 g/mol

SAPT-Temperature:

Study scientifically not justified.

Evaporation rate:

Value can be approximated from Henry's Law Constant or vapor

pressure.

Date / Revised: 08.10.2025 Version: 9.0

Product: 3-METHYLBUTANOL-1

(ID no. 30036711/SDS_GEN_00/EN)

Date of print 08.10.2025

10. Stability and Reactivity

Reactivity

When heated can give off ignitable vapours.

Corrosion to metals: No corrosive effect on metal.

Formation of Remarks: Forms no flammable gases in the

flammable gases: presence of water.

Chemical stability

The product is stable if stored and handled as prescribed/indicated.

Possibility of hazardous reactions

No hazardous reactions if stored and handled as prescribed/indicated.

Conditions to avoid

No special precautions other than good housekeeping of chemicals.

Incompatible materials

Substances to avoid: strong oxidizing agents

Hazardous decomposition products

Hazardous decomposition products:

No hazardous decomposition products if stored and handled as prescribed/indicated.

11. Toxicological Information

Information on toxicological effects

Acute toxicity

Assessment of acute toxicity:

Virtually nontoxic after a single ingestion. The inhalation of a highly enriched/saturated vapor-air-mixture represents an unlikely acute hazard. Of low toxicity after short-term skin contact. The European Union (EU) has classified this substance as 'harmful' after inhalation.

Experimental/calculated data:

LD50 rat (oral): > 5.000 mg/kg (BASF-Test)

LD50 rabbit (dermal): approx. 3.216 mg/kg (similar to OECD guideline 402)

<u>Irritation</u>

Date / Revised: 08.10.2025 Version: 9.0

Product: 3-METHYLBUTANOL-1

(ID no. 30036711/SDS_GEN_00/EN)

Date of print 08.10.2025

Assessment of irritating effects:

Skin contact causes irritation. May cause severe damage to the eyes.

Experimental/calculated data:

Skin corrosion/irritation rabbit: Irritant. (Draize test)

Serious eye damage/irritation rabbit: irreversible damage (Draize test)

Respiratory/Skin sensitization

Assessment of sensitization:

There is no evidence of a skin-sensitizing potential. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Experimental/calculated data:

In vitro/in chemico test battery In vitro assay: Non-sensitizing. (In vitro skin sensitization test battery)

Germ cell mutagenicity

Assessment of mutagenicity:

The substance was not mutagenic in bacteria. The substance was not mutagenic in mammalian cell culture. The substance was not mutagenic in studies with mammals.

Carcinogenicity

Assessment of carcinogenicity:

A long-term carcinogenity study which does not meet the current requirements did not show a carcinogenic effect. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Reproductive toxicity

Assessment of reproduction toxicity:

The results of animal studies gave no indication of a fertility impairing effect.

Developmental toxicity

Assessment of teratogenicity:

No indications of a developmental toxic / teratogenic effect were seen in animal studies. No adverse effects on embryonic or fetal development were observed.

Specific target organ toxicity (single exposure)

Assessment of STOT single:

Causes temporary irritation of the respiratory tract.

Repeated dose toxicity and Specific target organ toxicity (repeated exposure)

Assessment of repeated dose toxicity:

No adverse effects were observed after repeated oral exposure in animal studies. No adverse effects were observed after repeated inhalative exposure in animal studies. The product has not been fully

Date / Revised: 08.10.2025 Version: 9.0

Product: 3-METHYLBUTANOL-1

(ID no. 30036711/SDS_GEN_00/EN)

Date of print 08.10.2025

tested. The statements have been derived in parts from products of a similar structure or composition.

Aspiration hazard

not applicable

12. Ecological Information

Toxicity

Assessment of aquatic toxicity:

There is a high probability that the product is not acutely harmful to aquatic organisms. The inhibition of the degradation activity of activated sludge is not anticipated when introduced to biological treatment plants in appropriate low concentrations. Toxic to aquatic organisms based on long-term (chronic) toxicity study data.

Toxicity to fish:

LC50 (96 h) > 120 mg/l, Salmo gairdneri, syn. O. mykiss (OECD 203; ISO 7346; 84/449/EWG, C.1, static)

Nominal concentration.

Aquatic invertebrates:

EC50 (48 h) > 100 mg/l, Daphnia magna (DIN 38412 Part 11, static)

Nominal concentration.

Aquatic plants:

EC50 (72 h) > 100 mg/l (growth rate), Scenedesmus subspicatus (DIN 38412 Part 9, static) Nominal concentration.

Microorganisms/Effect on activated sludge:

EC10 (3 h) 370 mg/l, activated sludge, domestic (OECD Guideline 209, aerobic)

Nominal concentration. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Chronic toxicity to fish:

No observed effect concentration (35 d) 10 mg/l, Brachydanio rerio (OECD Guideline 210, Flow through.)

The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Chronic toxicity to aquatic invertebrates:

EC10 (21 d) 0,059 mg/l, Daphnia magna (OECD Guideline 211, semistatic)

The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Assessment of terrestrial toxicity:

No data available.

Persistence and degradability

Assessment biodegradation and elimination (H2O):

Date / Revised: 08.10.2025 Version: 9.0

Product: 3-METHYLBUTANOL-1

(ID no. 30036711/SDS_GEN_00/EN)

Date of print 08.10.2025

Readily biodegradable (according to OECD criteria).

Elimination information:

84 % BOD of COD (27 d) (OECD 301F; ISO 9408; 92/69/EWG, C.4-D) (aerobic, activated sludge, domestic)

Assessment of stability in water:

According to structural properties, hydrolysis is not expected/probable.

Bioaccumulative potential

Assessment bioaccumulation potential:

Because of the n-octanol/water distribution coefficient (log Pow) accumulation in organisms is not to be expected.

Bioaccumulation potential:

No data available.

Mobility in soil

Assessment transport between environmental compartments:

Volatility: The substance will slowly evaporate into the atmosphere from the water surface.

Adsorption in soil: Adsorption to solid soil phase is not expected.

Results of PBT and vPvB assessment

According to Annex XIII of Regulation (EC) No.1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH): The product does not fulfill the criteria for PBT (Persistent/bioaccumulative/toxic) and vPvB (very persistent/very bioaccumulative). Self classification

Additional information

Adsorbable organically-bound halogen (AOX):

This product contains no organically-bound halogen.

13. Disposal Considerations

Waste treatment methods

Must be disposed of or incinerated in accordance with local regulations.

Contaminated packaging:

Contaminated packaging should be emptied as far as possible; then it can be passed on for recycling after being thoroughly cleaned.

Date / Revised: 08.10.2025 Version: 9.0

Product: 3-METHYLBUTANOL-1

(ID no. 30036711/SDS_GEN_00/EN)

Date of print 08.10.2025

14. Transport Information

Land transport

ADR

UN number or ID number: UN1105 UN proper shipping name: PENTANOLS

Transport hazard class(es): 3, EHSM

Packing group: III Environmental hazards: yes

Special precautions for Tunnel code: D/E

user:

RID

UN number or ID number: UN1105 UN proper shipping name: PENTANOLS

Transport hazard class(es): 3, EHSM Packing group: III Environmental hazards: yes

Special precautions for None known

user:

Inland waterway transport

ADN

UN number or ID number: UN1105 UN proper shipping name: PENTANOLS

Transport hazard class(es): 3, EHSM Packing group: III Environmental hazards: yes

Special precautions for None known

user:

Transport in inland waterway vessel

Not evaluated

Sea transport

IMDG

UN number or ID number: UN 1105 UN proper shipping name: PENTANOLS

Transport hazard class(es): 3, EHSM Packing group: III Environmental hazards: yes

Marine pollutant: NO

Date / Revised: 08.10.2025 Version: 9.0

Product: 3-METHYLBUTANOL-1

(ID no. 30036711/SDS_GEN_00/EN)

Date of print 08.10.2025

Special precautions for

user:

EmS: F-E; S-D

Air transport

IATA/ICAO

UN number or ID number: UN 1105
UN proper shipping name: PENTANOLS

Transport hazard class(es): 3 Packing group: III

Environmental hazards: No Mark as dangerous for the environment is needed

Special precautions for None known

user:

Maritime transport in bulk according to IMO instruments

Maritime transport in bulk is not intended.

15. Regulatory Information

Safety, health and environmental regulations/legislation specific for the substance or mixture

If other regulatory information applies that is not already provided elsewhere in this safety data sheet, then it is described in this subsection.

16. Other Information

Full text of classifications, hazard symbols and hazard statements, if mentioned in section 2 or 3:

Flam. Liq. Flammable liquids
Acute Tox. Acute toxicity
Skin Irrit. Skin irritation
Eye Dam. Serious eye damage

STOT SE Specific target organ toxicity — single exposure Aquatic Chronic Hazardous to the aquatic environment - chronic

H226 Flammable liquid and vapour. H318 Causes serious eye damage.

H315 Causes skin irritation.

H335 May cause respiratory irritation.

H303 + H313 May be harmful if swallowed or in contact with skin.

H411 Toxic to aquatic life with long lasting effects.

The data contained in this safety data sheet are based on our current knowledge and experience and describe the product only with regard to safety requirements. This safety data sheet is neither a Certificate of Analysis (CoA) nor technical data sheet and shall not be mistaken for a specification agreement. Identified uses in this safety data sheet do neither represent an agreement on the corresponding contractual quality of the substance/mixture nor a contractually designated use. It is the

Page: 15/15

Safety data sheet according to the United Nations' Globally Harmonized System (UN GHS)

Date / Revised: 08.10.2025 Version: 9.0

Product: 3-METHYLBUTANOL-1

(ID no. 30036711/SDS_GEN_00/EN)

Date of print 08.10.2025

responsibility of the recipient of the product to ensure any proprietary rights and existing laws and legislation are observed.

Vertical lines in the left hand margin indicate an amendment from the previous version.