

# Efka<sup>®</sup> RM 1410

Product description	Rheology modifier for medium-polarity solvent-base and solvent-free systems
Key benefits	<ul style="list-style-type: none"><li>■ Pseudoplastic rheology with thixotropic flow behavior, combining anti-sagging with good leveling</li><li>■ Liquid product form, offering easy handling</li><li>■ High thickening effectiveness with no influence on gloss and haze</li><li>■ Good compatibility with a wide range of binder types</li></ul>
Chemical nature	Solution of a modified urea in dimethyl sulfoxide

## Properties

Physical form	Clear to slightly turbid, yellowish liquid		
Technical data (not supply specification)	Solid content	DIN EN ISO 3251	~ 52 %
	Viscosity	DIN 53019-1	< 300 mPa.s
	Density	ISO 2811-1	~ 1.15 g/cm <sup>3</sup>

---

## Application

EFKA® RM 1410 is highly suited for medium polarity, solvent-bases and solvent-free coatings where thixotropic rheology behavior and minimized influence on gloss and haze are essential.

The product is also used in ambient curing resin systems to prevent sedimentation in filled, reactive casting resin systems such as epoxy, polyurethane, acrylate and polyester resins.

## Formulation guideline

0.2 - 2 % on total formulation.

The amount required for optimum performance should be determined in trials covering a concentration range, depending on polarity and solids of the formulation as well as the technical requirements (anti-settling or anti-sagging).

The additive should be added under moderate stirring to ensure an immediate and homogenous distribution. It is not necessary to control the temperature. The additive can be added into the grind stage as well as by post-addition to adjust the viscosity.

When used in reactive, catalyzed and cellulose nitrate containing systems the storage stability should be controlled.

---

## Storage

The product is moisture sensitive. It is recommended to store EFKA® RM 1410 in a dry place, in tightly closed containers at temperatures above 10 °C to ensure ease of handling and pourability. Warming the product above 20 °C helps to ensure this.

A possibly slight turbid aspect of the product has no negative impact on the thickening performance.

### Contacts worldwide

Asia  
BASF East Asia Regional Headquarters Limited  
36/F, Two Taikoo Place,  
Taikoo Place,  
979 King's Road,  
Quarry Bay, Hong Kong  
[formulation-additives-asia@basf.com](mailto:formulation-additives-asia@basf.com)

North America  
BASF Corporation  
11501 Steele Creek Road  
Charlotte, NC 28273  
USA  
[formulation-additives-nafta@basf.com](mailto:formulation-additives-nafta@basf.com)

Europe  
BASF SE  
Formulation Additives  
67056 Ludwigshafen  
Germany  
[formulation-additives-europe@basf.com](mailto:formulation-additives-europe@basf.com)

South America  
BASF S.A  
Rochaverá - Crystal Tower  
Av. das Nações Unidas, 14.171  
Morumbi - São Paulo-SP  
Brazil  
[formulation-additives-south-america@basf.com](mailto:formulation-additives-south-america@basf.com)

### Validity

This Technical Data Sheet is valid for all versions of the Efka® RM 1410.

### Safety

When handling this product, please comply with the advice and information given in the safety data sheet and observe protective and workplace hygiene measures adequate for handling chemicals.

### Note

The data contained in this publication are based on our current knowledge and experience. In view of the many factors that may affect processing and application of our product, these data do not relieve processors from carrying out their own investigations and tests; neither do these data imply any guarantee of certain properties, nor the suitability of the product for a specific purpose. Any descriptions, drawings, photographs, data, proportions, weights, etc. given herein may change without prior information and do not constitute the agreed contractual quality of the product. The agreed contractual quality of the product results exclusively from the statements made in the product specification. It is the responsibility of the recipient of our product to ensure that any proprietary rights and existing laws and legislation are observed.

® = Registered trademark

™ = Trademark of the BASF Group, unless otherwise noted

[www.basf.com/formulation-additives](http://www.basf.com/formulation-additives)