

Safety data sheet

Page: 1/10

BASF Safety data sheet

Date / Revised: 22.01.2025 Version: 1.1

Product: ULTRADUR® S 4090 G4 LS BLACK 15077 POLYBUTYLENE TEREPHTHALATE

(30036591/SDS_GEN_SG/EN)

Date of print: 14.10.2025

1. Substance/preparation and manufacturer/supplier identification

Product name:

ULTRADUR® S 4090 G4 LS BLACK 15077 POLYBUTYLENE TEREPHTHALATE

Use: Polymer

Recommended use: Polymer, for industrial processing only

Manufacturer/supplier:

BASF South East Asia Pte Ltd. 128 Beach Road #18-01 Guoco Midtown, 189773, Singapore Telephone: +65 8322 4420

Telefax number: +65 6 334-0330 E-mail address: benny.zou@basf.com

Emergency information:

Singapore Emergency Toll-Free Number:

Telephone: 1800-723-1361 International emergency number: Telephone: +49 180 2273-112

2. Hazard identification

Classification of the substance and mixture:

No need for classification according to GHS criteria for this product.

Label elements and precautionary statement:

The product does not require a hazard warning label in accordance with GHS criteria.

Date / Revised: 22.01.2025 Version: 1.1

Product: ULTRADUR® S 4090 G4 LS BLACK 15077 POLYBUTYLENE TEREPHTHALATE

(30036591/SDS_GEN_SG/EN)

Date of print: 14.10.2025

Other hazards which do not result in classification:

No specific dangers known, if the regulations/notes for storage and handling are considered.

3. Composition/information on ingredients

Chemical nature

Substance nature: mixture

Preparation based on:

polybutylene terephthalate (PBT), Styrene-acrylonitrile-copolymer, Butyl acrylate-styrene-acrylonitrile copolymer, Polyethyleneterephthalate (PET)

additives, fillers

4. First-Aid Measures

General advice:

Avoid contact with the skin, eyes and clothing.

If inhaled:

If difficulties occur after dust has been inhaled, remove to fresh air and seek medical attention.

On skin contact:

Burns caused by molten material require hospital treatment.

On contact with eyes:

In case of contact with the eyes, rinse immediately for at least 15 minutes with plenty of water. If irritation develops, seek medical attention.

On ingestion:

Rinse mouth and then drink 200-300 ml of water. If difficulties occur: Seek medical attention.

Note to physician:

Symptoms: (Further) symptoms and / or effects are not known so far

Hazards: No hazard is expected under intended use and appropriate handling.

Treatment: Treat according to symptoms (decontamination, vital functions), no known specific

antidote.

5. Fire-Fighting Measures

Suitable extinguishing media: water spray, dry powder, foam

Unsuitable extinguishing media for safety reasons:

water jet

Specific hazards:

At temperatures of > 300 °C can be emitted: carbon monoxide, tetrahydrofuran, acrylonitrile, styrene, alpha-Methylstyrene, n-butyl acrylate

Date / Revised: 22.01.2025 Version: 1.1

Product: ULTRADUR® S 4090 G4 LS BLACK 15077 POLYBUTYLENE TEREPHTHALATE

(30036591/SDS_GEN_SG/EN)

Date of print: 14.10.2025

Under special fire conditions traces of other toxic substances are possible. Formation of further decomposition and oxidation products depends upon the fire conditions.

Special protective equipment:

Wear a self-contained breathing apparatus.

Further information:

Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

6. Accidental Release Measures

Personal precautions:

No special precautions necessary.

Environmental precautions:

No special precautions necessary.

Methods for cleaning up or taking up:

For small amounts: Pick up with suitable appliance and dispose of. For large amounts: Pick up with suitable appliance and dispose of.

For residues: Sweep/shovel up.

Dispose of absorbed material in accordance with regulations.

Additional information: High risk of slipping due to leakage/spillage of product.

7. Handling and Storage

Handling

Avoid inhalation of dusts/mists/vapours. Exhaust ventilation at processing machines is required during thermal processing and/or machining.

Protection against fire and explosion:

Take precautionary measures against static discharges.

Storage

Segregate from foods and animal feeds.

Suitable materials for containers: Low density polyethylene (LDPE), High density polyethylene (HDPE), Aluminium, Carbon steel (Iron)

Further information on storage conditions: Keep container tightly closed and dry; store in a cool place. Avoid dust formation, product dust can form an explosive mixture with air.

Storage stability:

Protect against moisture.

8. Exposure controls and personal protection

Components with occupational exposure limits

Date / Revised: 22.01.2025 Version: 1.1

Product: ULTRADUR® S 4090 G4 LS BLACK 15077 POLYBUTYLENE TEREPHTHALATE

(30036591/SDS_GEN_SG/EN)

Date of print: 14.10.2025

The limit values will not be achieved if the product is processed proper and suitable ventilation is provided.

styrene, 100-42-5;

STEL value 426 mg/m3; 100 ppm (OEL (SG)) TWA value 213 mg/m3; 50 ppm (OEL (SG)) STEL value 20 ppm (ACGIHTLV) TWA value 10 ppm (ACGIHTLV)

alpha-Methylstyrene, 98-83-9;

TWA value 10 ppm (ACGIHTLV)

STEL value 483 mg/m3; 100 ppm (OEL (SG)) TWA value 242 mg/m3; 50 ppm (OEL (SG)) TWA value 242 mg/m3; 50 ppm (OEL (SG)) STEL value 483 mg/m3; 100 ppm (OEL (SG)) TWA value 10 ppm (ACGIHTLV)

n-butyl acrylate, 141-32-2; TWA value 2 ppm (ACGIHTLV)

TWA value 52 mg/m3; 10 ppm (OEL (SG))

tetrahydrofuran, 109-99-9;

TWA value 50 ppm (ACGIHTLV)
STEL value 100 ppm (ACGIHTLV)

TWA value 590 mg/m3; 200 ppm (OEL (SG)) STEL value 737 mg/m3; 250 ppm (OEL (SG))

Skin Designation (ACGIHTLV)

Danger of cutaneous absorption

acrylonitrile, 107-13-1;

TWA value 2 ppm (ACGIHTLV)
TWA value 4.3 mg/m3; 2 ppm (OEL (SG))

Skin Designation (ACGIHTLV)
Danger of cutaneous absorption
Skin Designation (ACGIHTLV)
Danger of cutaneous absorption

Personal protective equipment

Respiratory protection:

Breathing protection if breathable aerosols/dust are formed. Wear respiratory protection if ventilation is inadequate. (Particle filter EN 143 P2 or FFP2)

Hand protection:

Use additional heat protection gloves when handling hot molten masses (EN 407), e.g. of textile or leather.

Eye protection:

Safety glasses with side-shields (frame goggles) (e.g. EN 166)

Date / Revised: 22.01.2025 Version: 1.1

Product: ULTRADUR® S 4090 G4 LS BLACK 15077 POLYBUTYLENE TEREPHTHALATE

(30036591/SDS_GEN_SG/EN)

Date of print: 14.10.2025

Body protection:

Body protection must be chosen depending on activity and possible exposure, e.g. apron, protecting boots, chemical-protection suit (according to EN 14605 in case of splashes or EN ISO 13982 in case of dust).

General safety and hygiene measures:

Avoid inhalation of vapour. When using, do not eat, drink or smoke. Hands and/or face should be washed before breaks and at the end of the shift. After use of gloves apply skin-cleaning agents and skin cosmetics.

9. Physical and Chemical Properties

Form: granules
Colour: black
Odour: odourless
Odour threshold: not applicable

pH value:

not applicable

melting range: 220 - 225 °C (DIN EN ISO 3146)

(1,013 hPa)

Boiling range:

The substance / product decomposes therefore not

determined.

Sublimation point:

No applicable information available.

Flash point:

not applicable

Evaporation rate:

The product is a non-volatile solid.

Flammability (solid/gas): not self-igniting (derived from flash point)

Lower explosion limit:

For solids not relevant for classification and labelling.

Upper explosion limit:

For solids not relevant for classification and labelling.

Ignition temperature: > 400 °C (ASTM D1929)

Thermal decomposition: > 300 °C (TGA)

To avoid thermal decomposition, do

not overheat.

Self ignition: not self-igniting Test type: Spontaneous self-

ignition at room-temperature.

Date / Revised: 22.01.2025 Version: 1.1

Product: ULTRADUR® S 4090 G4 LS BLACK 15077 POLYBUTYLENE TEREPHTHALATE

(30036591/SDS_GEN_SG/EN)

(VDI 2263, sheet 1, 1.4.1 (May

Date of print: 14.10.2025

Self heating ability: It is not a substance capable of

spontaneous heating according to

1990))

UN transport regulations class 4.2.

Explosion hazard: not explosive

Fire promoting properties: not fire-propagating

Vapour pressure:

not applicable

Density: 1.30 - 1.50 g/cm3 (EN ISO 1183-1)

(20 °C, 1,013 hPa)

Relative density:

Study does not need to be

conducted.

Bulk density: 600 - 900 kg/m3 (DIN 53466)

(20 °C, 1,013 hPa)

Relative vapour density (air):

not applicable

Solubility in water: insoluble

(20 °C, 1,013 hPa)

Partitioning coefficient n-octanol/water (log Pow):

not applicable

Viscosity, dynamic:

not applicable, the product is a solid

Viscosity, kinematic:

not applicable, the product is a solid

Particle characteristics

Particle size distribution: spheroidal -

Specific Surface Area: 0.0 m²/g (MSSA, ISO 9227)

10. Stability and Reactivity

Conditions to avoid: Temperature: > 300 °C

See SDS section 7 - Handling and storage.

Thermal decomposition: > 300 °C (TGA)

To avoid thermal decomposition, do not overheat.

Substances to avoid:

No substances known that should be avoided.

Corrosion to metals: No corrosive effect on metal.

Hazardous reactions:

No hazardous reactions known.

Date / Revised: 22.01.2025 Version: 1.1

Product: ULTRADUR® S 4090 G4 LS BLACK 15077 POLYBUTYLENE TEREPHTHALATE

(30036591/SDS_GEN_SG/EN)

Date of print: 14.10.2025

The product is chemically stable.

Possible decomposition products:

carbon monoxide, tetrahydrofuran, acrylonitrile, styrene, alpha-Methylstyrene, water, n-butyl acrylate, carbon dioxide

Gaseous products of degradation can be given off if the product is greatly overheated.

Chemical stability:

The product is stable if stored and handled as prescribed/indicated.

The product is chemically stable.

Reactivity:

No hazardous reactions if stored and handled as prescribed/indicated.

11. Toxicological Information

Routes of exposure

Assessment of acute toxicity

Contact with molten product may cause thermal burns.

Symptoms

(Further) symptoms and / or effects are not known so far

Irritation

Assessment of irritating effects:

Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses.

Experimental/calculated data:

Serious eye damage/irritation:May cause mechanical irritation.

Respiratory/Skin sensitization

Assessment of sensitization:

Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses.

Germ cell mutagenicity

Assessment of mutagenicity:

Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses.

Carcinogenicity

Assessment of carcinogenicity:

Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses.

Reproductive toxicity

Date / Revised: 22.01.2025 Version: 1.1

Product: ULTRADUR® S 4090 G4 LS BLACK 15077 POLYBUTYLENE TEREPHTHALATE

(30036591/SDS_GEN_SG/EN)

Date of print: 14.10.2025

Assessment of reproduction toxicity:

Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses.

Developmental toxicity

Assessment of teratogenicity:

Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses.

Specific target organ toxicity (single exposure)

not applicable

Repeated dose toxicity and Specific target organ toxicity (repeated exposure)

Assessment of repeated dose toxicity:

Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses.

Aspiration hazard

No aspiration hazard expected.

Other relevant toxicity information

Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses.

12. Ecological Information

Ecotoxicity

Assessment of aquatic toxicity:

The product has not been tested. The statement has been derived from the structure of the product. There is a high probability that the product is not acutely harmful to aquatic organisms.

Mobility

Assessment transport between environmental compartments:

Adsorption to solid soil phase is not expected.

Persistence and degradability

Assessment biodegradation and elimination (H2O):

The product is virtually insoluble in water and can thus be separated from water mechanically in suitable effluent treatment plants.

Elimination information:

Poorly biodegradable.

BASF Safety data sheet
Date / Revised: 22.01.2025
Version: 1.1

Product: ULTRADUR® S 4090 G4 LS BLACK 15077 POLYBUTYLENE TEREPHTHALATE

(30036591/SDS_GEN_SG/EN)

Date of print: 14.10.2025

Assessment of stability in water:

According to structural properties, hydrolysis is not expected/probable.

Bioaccumulation potential

Assessment bioaccumulation potential:

Does not significantly accumulate in organisms.

Bioaccumulation potential:

The product will not be readily bioavailable due to its consistency and insolubility in water.

Other adverse effects

Adsorbable organically-bound halogen (AOX):

This product contains no organically-bound halogen.

Additional information

Other ecotoxicological advice:

The product is a polymeric compound.

13. Disposal Considerations

Check for possible recycling.

Incinerate in suitable incineration plant, observing local authority regulations.

Contaminated packaging:

Packs must be completely emptied.

Completely emptied packagings can be given for recycling.

14. Transport Information

Domestic transport:

Not classified as a dangerous good under transport regulations

UN number or ID number
UN proper shipping name:
Transport hazard class(es):
Packing group:
Environmental hazards:
Special precautions for

Not applicable
Not applicable
Not applicable
Not applicable
Not applicable
Not applicable

user

Sea transport

IMDG

Not classified as a dangerous good under transport regulations

UN number or ID number:
UN proper shipping name:
Transport hazard class(es):
Packing group:
Not applicable
Not applicable
Not applicable
Not applicable
Not applicable
Not applicable

Date / Revised: 22.01.2025 Version: 1.1

Product: ULTRADUR® S 4090 G4 LS BLACK 15077 POLYBUTYLENE TEREPHTHALATE

(30036591/SDS_GEN_SG/EN)

Date of print: 14.10.2025

Marine pollutant: no

Special precautions for

user

None known

Air transport

IATA/ICAO

Not classified as a dangerous good under transport regulations

UN number or ID number
Proper shipping name:
Transport hazard class(es):
Packing group:
Environmental hazards:
Special precautions for

Not applicable
Not applicable
Not applicable
Not applicable
Not applicable
Not applicable

user

Maritime transport in bulk according to IMO instruments

Maritime transport in bulk is not intended.

15. Regulatory Information

Other regulations

16. Other Information

Vertical lines in the left hand margin indicate an amendment from the previous version.

The data contained in this safety data sheet are based on our current knowledge and experience and describe the product only with regard to safety requirements. This safety data sheet is neither a Certificate of Analysis (CoA) nor technical data sheet and shall not be mistaken for a specification agreement. Identified uses in this safety data sheet do neither represent an agreement on the corresponding contractual quality of the substance/mixture nor a contractually designated use. It is the responsibility of the recipient of the product to ensure any proprietary rights and existing laws and legislation are observed.