

Formulation Additives

Technical Data Sheet

Hydropalat® WE 3323 (old: Starfactant® 30)



Product Description

Hydropalat® wetting agents are a new, novel line of nonionic surfactants that offer unique combinations of benefits to coating, adhesives and graphic art formulations. These benefits include excellent substrate wetting with defoaming, gloss improvement and pigment wetting.

Chemical Composition

A hyper-branched surfactant with a central hydrophile

Properties

Typical Properties

Appearance	clear yellow liquid
Specific gravity	~ 1.00

Typical Characteristics

Active Matter	100%
Color, Gardner	max 7.0

These typical values should not be interpreted as specifications.

Applications

Hydropalat® WE 3323 is a non-ionic, 100% active wetting agent effective in water borne inks, OPV's, and coatings intended for plastic, wood, and metal substrates. This new wetting agent is effective in a wide variety of emulsion types including acrylics, styrenated acrylics and PUD's. Hydropalat® WE 3323, in addition to its outstanding wetting properties, does not stabilize foam and can act as a defoamer in many coating and graphic art formulations. In addition, increasing levels of Hydropalat® WE 3323 wetting agents typically reduces foam content in coatings rather than increases it, as is typical of most competitive wetting agents. Hydropalat® WE 3323 will not reduce the corrosion resistance or recoat characteristics of coatings when used at the recommended level. The product is free of silicones, alkyl phenol ethoxylates (APE's), and solvent.

Hydropalat® WE 3323 is typically added to paint and coating formulations at 0.25 to 0.75%. Hydropalat® WE 3323 can be added at any stage of the manufacturing process. When added in the grind the product will aid the pigment wetting process.

Safety

General

The usual safety precautions when handling chemicals must be observed. These include the measures described in Federal, State, and Local health and safety regulations, thorough ventilation of the workplace, good skin care, and wearing of protective goggles.

Material Safety Data Sheet

All safety information is provided in the Material Safety Data Sheet for Hydropalat® WE 3323.

Storage

Hydropalat® WE 3323 is subject to appropriate storage under the usual storage and temperature conditions; our products are durable for at least 2 years.

Important

While the descriptions, designs, data and information contained herein are presented in good faith and believed to be accurate, they are provided for guidance only. Because many factors may affect processing or application/use, BASF recommends that the reader make tests to determine the suitability of a product for a particular purpose prior to use. **NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESCRIPTIONS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS.** In no case shall the descriptions, information, data or designs provided be considered a part of BASF's terms and conditions of sale. Further, the descriptions, designs, data, and information furnished by BASF hereunder are given gratis and BASF assumes no obligation or liability for the descriptions, designs, data or information given or results obtained all such being given and accepted at the reader's risk.

Hydropalat and Starfactant is a registered trademark of BASF Group.

© BASF Corporation, 2015



BASF Corporation is fully committed to the Responsible Care® initiative in the USA, Canada, and Mexico. For more information on Responsible Care® go to:
U.S.: www.basf.us/responsiblecare_usa
Canada: www.basf.us/responsiblecare_canada
México: www.basf.us/responsiblecare_mexico

BASF Corporation
Dispersions and Pigments
11501 Steele Creek Road
Charlotte, North Carolina 28273
Phone: (800) 251 – 0612
Email: edtech_info@basf.com
www.basf.us/dpsolutions