

Safety data sheet

Page: 1/13

BASF Safety data sheet according to the United Nations' Globally Harmonized System (UN GHS)

Date / Revised: 24.04.2024 Version: 6.2

Product: Kaurit® Impregnating Resin 210

(ID no. 30034943/SDS_GEN_00/EN)

Date of print 11.10.2025

1. Identification

Product identifier

Kaurit® Impregnating Resin 210

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses: Chemical

Recommended use: Chemical, for industrial and professional users

Details of the supplier of the safety data sheet

Company:
BASF SE
67056 Ludwigshafen
GERMANY
Division Monomers

Telephone: +49 621 60 42737

E-mail address: pss.monomers@basf.com

Emergency telephone number

International emergency number: Telephone: +49 180 2273-112

2. Hazards Identification

Classification of the substance or mixture

Date / Revised: 24.04.2024 Version: 6.2

Product: Kaurit® Impregnating Resin 210

(ID no. 30034943/SDS_GEN_00/EN)

Date of print 11.10.2025

According to UN GHS criteria

Skin Sens. 1 Carc. 1B

For the classifications not written out in full in this section the full text can be found in section 16.

Label elements

Globally Harmonized System (GHS)

Pictogram:





Signal Word: Danger

Hazard Statement:

H317 May cause an allergic skin reaction.

H350 May cause cancer.

Precautionary Statements (Prevention):

P280 Wear protective gloves, protective clothing and eye protection or face

protection.

P201 Obtain special instructions before use.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P202 Do not handle until all safety precautions have been read and

understood.

P272 Contaminated work clothing should not be allowed out of the workplace.

Precautionary Statements (Response):

P308 + P311 IF exposed or concerned: Call a POISON CENTER or physician.

P303 IF ON SKIN (or hair):

P361 Take off immediately all contaminated clothing.

P352 Wash with plenty of soap and water.
P363 Wash contaminated clothing before reuse.

Precautionary Statements (Storage): P405 Store locked up.

Precautionary Statements (Disposal):

P501 Dispose of contents and container to hazardous or special waste

collection point.

Other hazards

According to UN GHS criteria

No specific dangers known, if the regulations/notes for storage and handling are considered.

Date / Revised: 24.04.2024 Version: 6.2

Product: Kaurit® Impregnating Resin 210

(ID no. 30034943/SDS_GEN_00/EN)

Date of print 11.10.2025

3. Composition/Information on Ingredients

Substances

Not applicable

Mixtures

Chemical nature

Polymer based on: Urea, Formaldehyde

in water

Hazardous ingredients (GHS)

According to UN GHS criteria

Formaldehyde

Content (W/W): >= 0.4 % - <= 0.4 Flam. Liq. 4

%

CAS Number: 50-00-0 EC-Number: 200-001-8 INDEX-Number: 605-001-00-5 Acute Tox. 2 (Inhalation - vapour)

Acute Tox. 3 (oral)

Acute Tox. 3 (dermal)

Skin Corr. 1B

Eye Dam. 1 Skin Sens. 1A

Carc. 1B

Aquatic Acute 2

H227, H330, H317, H350, H314, H301 + H311,

H401

Specific concentration limit: Eye Dam./Irrit. 2: 5 - < 25 %

STOT SE 3, irr. to respiratory syst.: >= 5 %

Skin Sens. 1: >= 0,2 % Skin Corr./Irrit. 2: 5 - < 25 % Skin Corr./Irrit. 1B: >= 25 %

Methanol

Date / Revised: 24.04.2024 Version: 6.2

Product: Kaurit® Impregnating Resin 210

(ID no. 30034943/SDS_GEN_00/EN)

Date of print 11.10.2025

Content (W/W): >= 0.3 % - <= 0.3

CAS Number: 67-56-1 EC-Number: 200-659-6

INDEX-Number: 603-001-00-X

Acute Tox. 3 (Inhalation - vapour) Acute Tox. 3 (oral)

Acute Tox. 3 (dermal)

Flam. Liq. 2

STOT SE (Central nervous system, Optic nerve)

H225, H301 + H311 + H331, H370

Specific concentration limit: STOT SE 2: 3 - < 10 % STOT SE 1: >= 10 %

For the classifications not written out in full in this section the full text can be found in section 16.

4. First-Aid Measures

Description of first aid measures

Remove contaminated clothing.

After inhalation of decomposition products, remove the affected person to a source of fresh air and keep calm. Provide medical aid.

On skin contact:

Wash thoroughly with soap and water

On contact with eyes:

Immediately wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.

On ingestion:

Immediately rinse mouth and then drink 200-300 ml of water, seek medical attention.

Most important symptoms and effects, both acute and delayed

Symptoms: Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11., (Further) symptoms and / or effects are not known so far

Hazards: No hazard is expected under intended use and appropriate handling.

Indication of any immediate medical attention and special treatment needed

Treatment: Treat according to symptoms (decontamination, vital functions), no known specific antidote.

Date / Revised: 24.04.2024 Version: 6.2

Product: Kaurit® Impregnating Resin 210

(ID no. 30034943/SDS_GEN_00/EN)

Date of print 11.10.2025

5. Fire-Fighting Measures

Extinguishing media

Suitable extinguishing media: water spray, foam, carbon dioxide, dry powder

Special hazards arising from the substance or mixture

Formaldehyde, Methanol, Carbon monoxide, Carbon dioxide, nitrogen oxides The substances/groups of substances mentioned can be released in case of fire.

Advice for fire-fighters

Further information:

Fire debris must be disposed of in accordance with offical regulations. In case of combustion evolution of toxic gases/vapours possible. Do not allow to enter drains or waterways. Forms slippery surfaces with water.

6. Accidental Release Measures

Forms slippery surfaces with water.

Personal precautions, protective equipment and emergency procedures

Avoid contact with the skin, eyes and clothing. Handle in accordance with good industrial hygiene and safety practice. Information regarding personal protective measures, see section 8.

Environmental precautions

Do not allow to enter soil, waterways or waste water channels. Prevent entry into drains and surface waters. Ensure compliance with local regulations before discharging into effluent treatment plants.

Methods and material for containment and cleaning up

For large amounts: Sweep/shovel up.

For residues: Pick up with suitable absorbent material.

7. Handling and Storage

Precautions for safe handling

Handle in accordance with good industrial hygiene and safety practice.

Inform workers about possible hazards caused by the release of formaldehyde during processing.

Protection against fire and explosion:

No special precautions necessary.

Conditions for safe storage, including any incompatibilities

Segregate from acids and acid forming substances.

Date / Revised: 24.04.2024 Version: 6.2

Product: Kaurit® Impregnating Resin 210

(ID no. 30034943/SDS_GEN_00/EN)

Date of print 11.10.2025

Suitable materials for containers: Stainless steel 1.4401, Stainless steel 1.4301 (V2), Aluminium, Polyester resin, glass reinforced (Palatal A410), High density polyethylene (HDPE), Low density polyethylene (LDPE)

Further information on storage conditions: Keep in a cool place.

Protect from temperatures below: 0 °C

The packed product must be protected from temperatures below the indicated one.

Protect from temperatures above: 30 °C

The packed product must be protected against exceeding the indicated temperature.

Specific end use(s)

For the relevant identified use(s) listed in Section 1 the advice mentioned in this section 7 is to be observed.

8. Exposure Controls/Personal Protection

Control parameters

Components with occupational exposure limits

50-00-0: Formaldehyde

57-13-6: Urea 67-56-1: Methanol

Exposure controls

Personal protective equipment

Hand protection:

Chemical resistant protective gloves (EN ISO 374-1)

Eye protection:

Safety glasses with side-shields (frame goggles) (e.g. EN 166)

Body protection:

Body protection must be chosen depending on activity and possible exposure, e.g. apron, protecting boots, chemical-protection suit (according to EN 14605 in case of splashes or EN ISO 13982 in case of dust).

General safety and hygiene measures

Handle in accordance with good industrial hygiene and safety practice. Do not inhale vapours or dust.

9. Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

State of matter: liquid
Form: liquid
Colour: colourless
Odour: almost odourless

Date / Revised: 24.04.2024 Version: 6.2

Product: Kaurit® Impregnating Resin 210

(ID no. 30034943/SDS_GEN_00/EN)

Date of print 11.10.2025

Odour threshold:

No data available.

Melting point: 0 °C

(approx. 1.013 hPa)

Boiling point: approx. 100 °C

Flash point:

No flash point - Measurement made

up to the boiling point.

Auto-ignition temperature: > 600 °C (DIN 51794)
Thermal decomposition: No decomposition if correctly stored and handled.
pH value: approx. 7,5 (ISO 1148)

(20 °C)

Viscosity, kinematic:

No data available.

Viscosity, dynamic: 20 - 35 mPa.s (DIN 53018)

(20 °C)

Solubility in water: miscible

Partitioning coefficient n-octanol/water (log Kow): < 1,0

The statements are based on the properties of the individual

components.

Vapour pressure: approx. 23 mbar

(20 °C)

Relative density:

No data available.

Density: approx. 1,2 g/cm3 (DIN 51757)

(20 °C)

Particle characteristics

Particle size distribution: The substance / product is marketed or used in a non solid or granular

form. -

9.2. Other information

Information with regard to physical hazard classes

Explosives

Explosion hazard: not explosive

Oxidizing properties

Fire promoting properties: not fire-propagating

Other safety characteristics

Hygroscopy: Non-hygroscopic

Other Information: none

Evaporation rate:

Value can be approximated from Henry's Law Constant or vapor

pressure.

10. Stability and Reactivity

Reactivity

No hazardous reactions if stored and handled as prescribed/indicated.

Date / Revised: 24.04.2024 Version: 6.2

Product: Kaurit® Impregnating Resin 210

(ID no. 30034943/SDS_GEN_00/EN)

Date of print 11.10.2025

Chemical stability

The product is chemically stable.

Possibility of hazardous reactions

During processing with acids, water and / or heat formaldehyde will be released, which may act as a sensitizer.

Conditions to avoid

> 30 °C

Avoid heat. Avoid freezing. See SDS section 7 - Handling and storage.

Incompatible materials

Substances to avoid:

Organic Peroxides, strong bases, strong acids, acid anhydrides

Hazardous decomposition products

÷

Formaldehyde

11. Toxicological Information

Information on toxicological effects

Acute toxicity

Assessment of acute toxicity:

Virtually nontoxic after a single ingestion. The inhalation of a highly enriched/saturated vapor-air-mixture represents an unlikely acute hazard.

Experimental/calculated data: LD50 rat (oral): > 5.000 mg/kg

rat (by inhalation): 7 h (IRT)

No mortality within the stated exposition time as shown in animal studies.

Irritation

Assessment of irritating effects:

Not irritating to the skin. Not irritating to the eyes.

Experimental/calculated data:

Skin corrosion/irritation rabbit: non-irritant (BASF-Test)

Serious eye damage/irritation rabbit: non-irritant

Date / Revised: 24.04.2024 Version: 6.2

Product: Kaurit® Impregnating Resin 210

(ID no. 30034943/SDS_GEN_00/EN)

Date of print 11.10.2025

Serious eye damage/irritation rabbit: non-irritant (BASF-Test)

Respiratory/Skin sensitization

Assessment of sensitization:

After continuous contact with the skin, sensitization cannot be excluded. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Experimental/calculated data:

Guinea pig maximization test: Non-sensitizing.

This compound containing < 1% formaldehyde has no sensitizing effect (literature data).

Carcinogenicity

Information on: Formaldehyde Assessment of carcinogenicity:

After lifelong inhalation exposure to concentrations that were severely damaging to the nasal epithelium, nasal tumors were induced in rats; in other species these findings were not found or were considerably less pronounced. The International Agency for Research on Cancer (IARC) has classified formaldehyde as a Group 1 (known) human carcinogen based on epidemiological evidence linking formaldehyde exposure to occurrence of nasopharyngeal cancer and leukemia. No adverse health effects are anticipated if recommended personal protective equipment and industrial hydiene practices are used.

Reproductive toxicity

Assessment of reproduction toxicity: No reproductive toxic effects reported.

Developmental toxicity

Assessment of teratogenicity:

Not a teratogen.

Specific target organ toxicity (single exposure)

Assessment of STOT single:

Based on the available information there is no specific target organ toxicity to be expected after a single exposure.

Repeated dose toxicity and Specific target organ toxicity (repeated exposure)

Information on: Formaldehyde

Assessment of repeated dose toxicity:

After repeated exposure the prominent effect is local irritation.

Information on: Methanol

Assessment of repeated dose toxicity:

The substance may cause blindness after repeated ingestion. The substance may cause blindness

after repeated inhalation.

Page: 10/13

Safety data sheet according to the United Nations' Globally Harmonized System (UN GHS)

Date / Revised: 24.04.2024 Version: 6.2

Product: Kaurit® Impregnating Resin 210

(ID no. 30034943/SDS_GEN_00/EN)

Date of print 11.10.2025

Aspiration hazard

No aspiration hazard expected.

12. Ecological Information

Toxicity

Assessment of aquatic toxicity:

There is a high probability that the product is not acutely harmful to aquatic organisms. The inhibition of the degradation activity of activated sludge is not anticipated when introduced to biological treatment plants in appropriate low concentrations.

Toxicity to fish:

LC50 (48 h) > 100 mg/l, Leuciscus idus (static)

The product has low solubility in the test medium. An eluate has been tested.

Persistence and degradability

Elimination information:

No data available.

Bioaccumulative potential

Assessment bioaccumulation potential:

Based on its structural properties, the polymer is not biologically available. Accumulation in organisms is not to be expected.

Mobility in soil

Assessment transport between environmental compartments:

Volatility: The substance will not evaporate into the atmosphere from the water surface.

Information on: Formaldehyde

Assessment transport between environmental compartments:

Volatility: The substance will not evaporate into the atmosphere from the water surface.

Adsorption in soil: Adsorption to solid soil phase is not expected.

Information on: Methanol

Assessment transport between environmental compartments:

Volatility: The substance will not evaporate into the atmosphere from the water surface.

Adsorption in soil: Adsorption to solid soil phase is not expected.

Other adverse effects

The product does not contain substances that are listed in Regulation (EC) 1005/2009 on substances that deplete the ozone layer.

Date / Revised: 24.04.2024 Version: 6.2

Product: Kaurit® Impregnating Resin 210

(ID no. 30034943/SDS_GEN_00/EN)

Date of print 11.10.2025

Additional information

Other ecotoxicological advice:

Do not release untreated into natural waters. Inhibition of degradation activity in activated sludge is not to be anticipated during correct introduction of low concentrations. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

13. Disposal Considerations

Waste treatment methods

Incinerate in suitable incineration plant, observing local authority regulations.

14. Transport Information

Land transport

ADR

Not classified as a dangerous good under transport regulations

UN number or ID number:
UN proper shipping name:
Transport hazard class(es):
Packing group:
Environmental hazards:
Special precautions for

Not applicable
Not applicable
Not applicable
Not applicable
Not applicable
Not applicable

user

RID

Not classified as a dangerous good under transport regulations

UN number or ID number:
UN proper shipping name:
Transport hazard class(es):
Packing group:
Not applicable
Not applicable
Not applicable
Not applicable
Not applicable

Special precautions for N

user

Not applicable None known

Inland waterway transport

ADN

Not classified as a dangerous good under transport regulations

UN number or ID number:
UN proper shipping name:
Transport hazard class(es):
Packing group:

Not applicable
Not applicable
Not applicable

Packing group:

Environmental hazards:

Special precautions for

Not applicable

None known

Date / Revised: 24.04.2024 Version: 6.2

Product: Kaurit® Impregnating Resin 210

(ID no. 30034943/SDS_GEN_00/EN)

Date of print 11.10.2025

user:

Transport in inland waterway vessel

Not evaluated

Sea transport

IMDG

Not classified as a dangerous good under transport regulations

UN number or ID number:
UN proper shipping name:
Transport hazard class(es):
Packing group:
Environmental hazards:
Special precautions for

Not applicable
Not applicable
Not applicable
Not applicable
Not applicable

user

Air transport

IATA/ICAO

Not classified as a dangerous good under transport regulations

UN number or ID number
UN proper shipping name:
Transport hazard class(es):
Packing group:
Environmental hazards:
Special precautions for

Not applicable
Not applicable
Not applicable
Not applicable
Not applicable
Not applicable

user

Maritime transport in bulk according to IMO instruments

Maritime transport in bulk is not intended.

15. Regulatory Information

Safety, health and environmental regulations/legislation specific for the substance or mixture

If other regulatory information applies that is not already provided elsewhere in this safety data sheet, then it is described in this subsection.

16. Other Information

Full text of classifications, hazard symbols and hazard statements, if mentioned in section 2 or 3:

Skin Sens. Skin sensitization Carc. Carcinogenicity

Page: 13/13

Safety data sheet according to the United Nations' Globally Harmonized System (UN GHS)

Date / Revised: 24.04.2024 Version: 6.2

Product: Kaurit® Impregnating Resin 210

(ID no. 30034943/SDS_GEN_00/EN)

Date of print 11.10.2025

Flam. Liq. Flammable liquids
Acute Tox. Acute toxicity
Skin Corr. Skin corrosion
Eye Dam. Serious eye damage

Aquatic Acute Hazardous to the aquatic environment - acute STOT SE Specific target organ toxicity — single exposure

Eye Dam./Irrit. Serious eye damage/eye irritation

Skin Corr./Irrit. Skin corrosion/irritation H227 Combustible liquid. H330 Fatal if inhaled.

H317 May cause an allergic skin reaction.

H350 May cause cancer.

H314 Causes severe skin burns and eye damage. H301 + H311 Toxic if swallowed or in contact with skin.

H401 Toxic to aquatic life.

H225 Highly flammable liquid and vapour.

H301 + H311 + H331 Toxic if swallowed, in contact with skin or if inhaled.

H370 Causes damage to organs (Central nervous system, Optic nerve).

The data contained in this safety data sheet are based on our current knowledge and experience and describe the product only with regard to safety requirements. This safety data sheet is neither a Certificate of Analysis (CoA) nor technical data sheet and shall not be mistaken for a specification agreement. Identified uses in this safety data sheet do neither represent an agreement on the corresponding contractual quality of the substance/mixture nor a contractually designated use. It is the responsibility of the recipient of the product to ensure any proprietary rights and existing laws and legislation are observed.

Vertical lines in the left hand margin indicate an amendment from the previous version.