

Joncryl® HPD 696

Product Description	Joncryl HPD 696 is a high-performance acrylic resin for pigment dispersion applications.
Key Features & Benefits	<ul style="list-style-type: none">- High pigment concentrations at low viscosity- Viscosity stability- Color development and gloss
Chemical Composition	Styrene acrylic resin

Properties

Typical Properties	Appearance	clear flakes
	Acid number	220
	Molecular weight (Mw)	16,000
	Non-volatile	% 98.9
	Density at 25°C	g/cm ³ 1.16
	Softening point	°C 155
	Tg	°C 88
	Total VOC	% wt 1.1

These typical values should not be interpreted as specifications.

Application

Joncryl HPD 696 is a high molecular weight acrylic resin specifically designed to improve the color development and gloss of pigment dispersions without compromising ink stability. Dispersions formulated with Joncryl HPD 696 approach the quality of chip dispersions.


Joncryl HPD 696 is recommended for applications such as:

- Pigment dispersions

Joncryl HPD 696 provides improved pigment wetting, color strength, and gloss compared to conventional dispersion resins. This allows the formulation of high solids, low viscosity pigment dispersions that have excellent rheology, flow, and stability.

Processing

Dispersions with pigment loadings of 35 – 40% can often be achieved with Joncryl HPD 696. A pigment-to-binder ratio of 4:1 will generally yield good viscosity and shock stability.



Safety

General

The usual safety precautions when handling chemicals must be observed. These include the measures described in Federal, State and Local health and safety regulations, thorough ventilation of the workplace, good skin care and wearing of protective goggles.

Safety Data Sheet

All safety information is provided in the Safety Data Sheet for Joncryl HPD 696.

Storage

Please refer to the "Handling and Storage of Polymer Dispersions" brochure.

Important

WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, THEY ARE PROVIDED FOR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, BASF RECOMMENDS THAT THE READER MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR A PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESCRIPTIONS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF BASF'S TERMS AND CONDITIONS OF SALE. FURTHER, THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY BASF HEREUNDER ARE GIVEN GRATIS AND BASF ASSUMES NO OBLIGATION OR LIABILITY FOR THE DESCRIPTIONS, DESIGNS, DATA OR INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT THE READER'S RISK.

Joncryl is a registered trademark of BASF Group.

© BASF Corporation, 2023



BASF Corporation is fully committed to the Responsible Care® initiative in the USA, Canada, and Mexico.

For more information on Responsible Care® go to:

U.S.: www.basf.us/responsiblecare_usa

Canada: www.basf.us/responsiblecare_canada

México: www.basf.us/responsiblecare_mexico

BASF Corporation

Dispersions and Resins

11501 Steele Creek Road

Charlotte, North Carolina 28273

Phone: (800) 251 – 0612

Email: CustCare-Charlotte@basf.com

www.basf.us/dpsolutions