

## Safety data sheet

Page: 1/34

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 09.11.2023 Version: 7.0 Date previous version: 07.11.2022 Previous version: 6.0

Date / First version: 07.11.2011
Product: **PENTYLACETATE** 

(ID no. 30034749/SDS\_GEN\_IE/EN)

Date of print 08.10.2025

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

## 1.1. Product identifier

## **PENTYLACETATE**

Chemical name: Reaction mass of 2-methylbutyl acetate and pentyl acetate

REACH registration number: 01-2119491285-32-0000, 01-2119491285-32

## 1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses: Chemical, solvent(s)

For the detailed identified uses of the product see appendix of the safety data sheet.

#### 1.3. Details of the supplier of the safety data sheet

Company: BASF SE 67056 Ludwigshafen GERMANY Contact address:
BASF Ireland DAC
Asgard House, 19-20 City Quay
Dublin, D02 K744
Ireland

Telephone: +353 21 451-7100

E-mail address: product-safety-uk-and-ireland@basf.com

#### 1.4. Emergency telephone number

For products classified as hazardous in accordance with CLP: National Poisons Information Centre, Beaumont Hospital, Dublin 9

Emergency medical information: 8am-10pm (seven days)

Tel.: 01 8092566

International emergency number: Telephone: +49 180 2273-112

Date / Revised: 09.11.2023 Version: 7.0
Date previous version: 07.11.2022 Previous version: 6.0

Date / First version: 07.11.2011

Product: **PENTYLACETATE** 

(ID no. 30034749/SDS\_GEN\_IE/EN)

Date of print 08.10.2025

#### **SECTION 2: Hazards Identification**

## 2.1. Classification of the substance or mixture

According to Regulation (EC) No 1272/2008 [CLP]

Flam. Liq. 3 H226 Flammable liquid and vapour.

For the classifications not written out in full in this section the full text can be found in section 16.

#### 2.2. Label elements

According to Regulation (EC) No 1272/2008 [CLP]

Pictogram:



Signal Word:

Warning

Hazard Statement:

H226 Flammable liquid and vapour.

Precautionary Statements (Prevention):

P210 Keep away from heat, hot surfaces, sparks, open flames and other

ignition sources. No smoking.

P280 Wear protective gloves and eye protection or face protection.

P243 Take action to prevent static discharges.

Precautionary Statements (Response):

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing.

Rinse skin with water or shower.

Precautionary Statements (Storage):

P403 + P235 Store in a well-ventilated place. Keep cool.

Precautionary Statements (Disposal):

P501 Dispose of contents and container to hazardous or special waste

collection point.

Labeling of special preparations (GHS):

EUH066: Repeated exposure may cause skin dryness or cracking.

Hazard determining component(s) for labelling: pentyl acetate, 2-methylbutyl acetat

#### 2.3. Other hazards

#### According to Regulation (EC) No 1272/2008 [CLP]

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture. See section 12 - Results of PBT and vPvB assessment.

Date / Revised: 09.11.2023 Version: 7.0
Date previous version: 07.11.2022 Previous version: 6.0

Date / First version: 07.11.2011
Product: **PENTYLACETATE** 

(ID no. 30034749/SDS\_GEN\_IE/EN)

Date of print 08.10.2025

Product does not contain a substance above legal limits included in the list established in accordance with Article 59(1) of Regulation (EC) No 1907/2006 for having endocrine disrupting properties or is identified to have endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

## **SECTION 3: Composition/Information on Ingredients**

#### 3.1. Substances

Chemical nature

Reaction mass of 2-methylbutyl acetate and

pentyl acetate

Flam. Liq. 3 H226 EUH066

#### Regulatory relevant ingredients

isopentyl acetate

Content (W/W): >= 0 % - <= 4 % Flam. Liq. 3
CAS Number: 123-92-2 Aquatic Chronic 3
EC-Number: 204-662-3 H226, H412
INDEX-Number: 607-130-00-2 EUH066

For the classifications not written out in full in this section, including the hazard classes and the hazard statements, the full text is listed in section 16.

#### 3.2. Mixtures

Not applicable

#### **SECTION 4: First-Aid Measures**

#### 4.1. Description of first aid measures

Remove contaminated clothing.

If inhaled:

Keep patient calm, remove to fresh air, seek medical attention.

On skin contact:

Wash thoroughly with soap and water

On contact with eyes:

Wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.

Date / Revised: 09.11.2023 Version: 7.0
Date previous version: 07.11.2022 Previous version: 6.0

Date / First version: 07.11.2011
Product: PENTYLACETATE

(ID no. 30034749/SDS\_GEN\_IE/EN)

Date of print 08.10.2025

#### On ingestion:

Immediately rinse mouth and then drink 200-300 ml of water, seek medical attention.

## 4.2. Most important symptoms and effects, both acute and delayed

Symptoms: Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11.

## 4.3. Indication of any immediate medical attention and special treatment needed

Treatment: Treat according to symptoms (decontamination, vital functions), no known specific antidote.

## **SECTION 5: Fire-Fighting Measures**

## 5.1. Extinguishing media

Suitable extinguishing media:

dry powder, water spray, carbon dioxide, foam

Unsuitable extinguishing media for safety reasons:

water jet

Additional information:

Use extinguishing measures to suit surroundings.

#### 5.2. Special hazards arising from the substance or mixture

Advice: Flammable liquid Cool endangered containers with water-spray. See SDS section 7 - Handling and storage.

#### 5.3. Advice for fire-fighters

Special protective equipment:

Wear a self-contained breathing apparatus. Special protective equipment for firefighters

Further information:

Evacuate area of all unnecessary personnel. Fight fire from maximum distance.

Extend fire extinguishing measures to the surroundings. Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

#### **SECTION 6: Accidental Release Measures**

High risk of slipping due to leakage/spillage of product.

Shut off or stop source of leak. Shut off or stop released substance/product under safe conditions.

Date / Revised: 09.11.2023 Version: 7.0
Date previous version: 07.11.2022 Previous version: 6.0

Date / First version: 07.11.2011
Product: **PENTYLACETATE** 

(ID no. 30034749/SDS\_GEN\_IE/EN)

Date of print 08.10.2025

Pack in tightly closed containers for disposal.

## 6.1. Personal precautions, protective equipment and emergency procedures

Handle in accordance with good industrial hygiene and safety practice.

#### 6.2. Environmental precautions

Discharge into the environment must be avoided.

#### 6.3. Methods and material for containment and cleaning up

Pick up with suitable appliance and dispose of. Spills should be contained, solidified, and placed in suitable containers for disposal. Dispose of absorbed material in accordance with regulations.

#### 6.4. Reference to other sections

Information regarding exposure controls/personal protection and disposal considerations can be found in section 8 and 13.

## **SECTION 7: Handling and Storage**

#### 7.1. Precautions for safe handling

Handle in accordance with good industrial hygiene and safety practice.

Protection against fire and explosion:

Avoid all sources of ignition: heat, sparks, open flame. Ground all transfer equipment properly to prevent electrostatic discharge.

## 7.2. Conditions for safe storage, including any incompatibilities

Further information on storage conditions: Keep container tightly closed in a cool, well-ventilated place.

#### 7.3. Specific end use(s)

See exposure scenario(s) in the attachment to this safety data sheet.

## **SECTION 8: Exposure Controls/Personal Protection**

#### 8.1. Control parameters

Components with occupational exposure limits

123-92-2: isopentyl acetate

STEL value 540 mg/m3; 100 ppm (OEL (EU))

indicative

TWA value 270 mg/m3; 50 ppm (OEL (EU))

indicative

Date / Revised: 09.11.2023 Version: 7.0 Date previous version: 07.11.2022 Previous version: 6.0

Date / First version: 07.11.2011
Product: PENTYLACETATE

(ID no. 30034749/SDS\_GEN\_IE/EN)

Date of print 08.10.2025

TWA value 260 mg/m3; 50 ppm (OEL (IE))

Indicative OELV

STEL value 520 mg/m3; 100 ppm (OEL (IE))

Ceiling limit value/factor: 15 min

Indicative OELV

628-63-7: pentyl acetate

STEL value 540 mg/m3; 100 ppm (OEL (EU))

indicative

TWA value 270 mg/m3; 50 ppm (OEL (EU))

indicative

TWA value 270 mg/m3; 50 ppm (OEL (IE))

Indicative OELV

STEL value 540 mg/m3; 100 ppm (OEL (IE))

Ceiling limit value/factor: 15 min

Indicative OELV

**PNEC** 

freshwater: 0.041 mg/l

marine water: 0.0041 mg/l

STP: 72 mg/l

soil: 0.033 mg/kg

sediment (marine water): 0.0286 mg/kg

sediment (freshwater): 0.286 mg/kg

intermittent release: 0.41 mg/l

oral (secondary poisoning):

According to EU risk assessment risks are negligible

**DNEL** 

worker:

Long- and short-term exposure - local effects, Inhalation: 260 mg/m3

consumer:

Long- and short-term exposure - local effects, Inhalation: 130 mg/m3

## 8.2. Exposure controls

Appropriate engineering controls

Provide local exhaust ventilation to control vapours/mists.

Personal protective equipment

Respiratory protection:

Date / Revised: 09.11.2023 Version: 7.0
Date previous version: 07.11.2022 Previous version: 6.0

Date / First version: 07.11.2011 Product: **PENTYLACETATE** 

(ID no. 30034749/SDS\_GEN\_IE/EN)

Date of print 08.10.2025

Wear respiratory protection if ventilation is inadequate. Gas filter for gases/vapours of organic compounds (boiling point >65 °C, e. g. EN 14387 Type A)

#### Hand protection:

Chemical resistant protective gloves (EN ISO 374-1)

Suitable materials for short-term contact (recommended: At least protective index 2, corresponding > 30 minutes of permeation time according to EN ISO 374-1)

butyl rubber (butyl) - 0.7 mm coating thickness

Manufacturer's directions for use should be observed because of great diversity of types. Supplementary note: The specifications are based on tests, literature data and information of glove manufacturers or are derived from similar substances by analogy. Due to many conditions (e.g. temperature) it must be considered, that the practical usage of a chemical-protective glove in practice may be much shorter than the permeation time determined through testing.

#### Eye protection:

Safety glasses with side-shields (frame goggles) (e.g. EN 166)

#### Body protection:

Body protection must be chosen depending on activity and possible exposure, e.g. apron, protecting boots, chemical-protection suit (according to EN 14605 in case of splashes or EN ISO 13982 in case of dust).

## General safety and hygiene measures

Wearing of closed work clothing is required additionally to the stated personal protection equipment. Handle in accordance with good industrial hygiene and safety practice.

## Environmental exposure controls

All appropriate measures must be taken to prevent the release of this product to the environment and to limit the dispersion of any release when it occurs. Suitable risk management measures should be in place.

## **SECTION 9: Physical and Chemical Properties**

## 9.1. Information on basic physical and chemical properties

State of matter: liquid
Form: liquid
Colour: colourless
Odour: ester-like

Odour threshold:

not determined

glass transition temperature: -82 °C (OECD Guideline 102)

Boiling point: 144.86 °C (measured)

(1,013.25 hPa)

Flammability: Flammable. (derived from flash point)

Date / Revised: 09.11.2023 Version: 7.0
Date previous version: 07.11.2022 Previous version: 6.0

Date / First version: 07.11.2011
Product: **PENTYLACETATE** 

(ID no. 30034749/SDS\_GEN\_IE/EN)

Date of print 08.10.2025

Lower explosion limit:

For liquids not relevant for classification and labelling., The lower explosion point may be 5 - 15

°C below the flash point.

Upper explosion limit:

For liquids not relevant for classification and labelling.

Flash point: 40 °C (ISO 13736, closed cup)
Auto-ignition temperature: 374 °C (Directive 92/69/EEC, A.15)
Thermal decomposition: No decomposition if stored and handled as prescribed/indicated.

pH value: 7.3

3 (pH Meter)

(1 %(m), 20 °C)

Viscosity, dynamic: 0.96 mPa.s (OECD Guideline 114)

(17.8 °C) 0.77 mPa.s

.77 mPa.s (OECD Guideline 114)

(35.6 °C)

Thixotropy: not thixotropic

Solubility in water: (OECD Guideline 105)

1.60 g/l

(20 °C, pH 4.6 - 5.8)

Solubility (qualitative) solvent(s): organic solvents

soluble

Partitioning coefficient n-octanol/water (log Kow): 2.1 - 2.7 (OECD Guideline 117)

(25 °C; pH value: 6.3)

Vapour pressure: 4.91 hPa (measured)

(20 °C) static

Relative density: 0.879 (OECD Guideline 109)

(17 °C)

Density: 0.875 - 0.877 g/cm3 (DIN 51757)

(20 °C)

Relative vapour density (air):> 1 (estimated)

(20 °C)

Heavier than air.

Particle characteristics

Particle size distribution: The substance / product is marketed or used in a non solid or granular

form. -

9.2. Other information

Information with regard to physical hazard classes

**Explosives** 

Explosion hazard: Based on the chemical structure

there is no indication of explosive

properties.

Oxidizing properties

Fire promoting properties: Based on its structural properties

the product is not classified as

oxidizing.

Date / Revised: 09.11.2023 Version: 7.0
Date previous version: 07.11.2022 Previous version: 6.0

Date / First version: 07.11.2011
Product: **PENTYLACETATE** 

(ID no. 30034749/SDS\_GEN\_IE/EN)

Date of print 08.10.2025

Flammable liquids

Sustained combustibility:

not determined

Pyrophoric properties

Self-ignition temperature: Test type: Spontaneous self-ignition at room-temperature.

Based on its structural properties the product is not classified as self-

(calculated)

(calculated)

igniting.

Self-heating substances and mixtures

Self heating ability: not applicable, the product is a liquid

Substances and mixtures, which emit flammable gases in contact with water

Formation of flammable gases:

Forms no flammable gases in the presence of water.

Corrosion to metals

Corrosive effects to metal are not anticipated.

Other safety characteristics

pKA:

The substance does not dissociate.

Adsorption/water - soil: KOC: 33.79; log KOC: 1.53 (calculated)

Adsorption to solid soil phase is not

expected.

Adsorption/water - soil: KOC: 29.75; log KOC: 1.47

Adsorption to solid soil phase is not

expected.

Adsorption/water - soil: KOC: 28.42; log KOC: 1.45

Adsorption to solid soil phase is not

expected.

Surface tension:

Based on chemical structure, surface

activity is not to be expected.

SAPT-Temperature:

Study scientifically not justified.

Evaporation rate:

Value can be approximated from Henry's Law Constant or vapor

pressure.

## **SECTION 10: Stability and Reactivity**

10.1. Reactivity

Date / Revised: 09.11.2023 Version: 7.0
Date previous version: 07.11.2022 Previous version: 6.0

Date / First version: 07.11.2011
Product: **PENTYLACETATE** 

(ID no. 30034749/SDS\_GEN\_IE/EN)

Date of print 08.10.2025

Corrosion to metals: Corrosive effects to metal are not anticipated.

Formation of Remarks: Forms no flammable gases in the

flammable gases: presence of water.

## 10.2. Chemical stability

The product is stable if stored and handled as prescribed/indicated.

### 10.3. Possibility of hazardous reactions

No hazardous reactions when stored and handled according to instructions.

#### 10.4. Conditions to avoid

No special precautions other than good housekeeping of chemicals.

## 10.5. Incompatible materials

Substances to avoid: strong oxidizing agents

#### 10.6. Hazardous decomposition products

Hazardous decomposition products:

No hazardous decomposition products if stored and handled as prescribed/indicated.

## **SECTION 11: Toxicological Information**

## 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

Assessment of acute toxicity:

Virtually nontoxic after a single ingestion. Virtually nontoxic after a single skin contact. Virtually nontoxic by inhalation.

Experimental/calculated data:

LD50 rat (oral): > 5,000 mg/kg (similar to OECD guideline 401)

LC50 rat (by inhalation): > 19.25 mg/l 4 h (similar to OECD guideline 403)

No mortality was observed. The vapour was tested.

LD50 rabbit (dermal): 8,300 mg/kg (similar to OECD guideline 402) LD50 rabbit (dermal): > 14,000 mg/kg (similar to OECD guideline 402)

#### Irritation

Assessment of irritating effects:

Not irritating to the eyes. May cause slight irritation to the skin.

Date / Revised: 09.11.2023 Version: 7.0
Date previous version: 07.11.2022 Previous version: 6.0

Date / First version: 07.11.2011 Product: **PENTYLACETATE** 

(ID no. 30034749/SDS\_GEN\_IE/EN)

Date of print 08.10.2025

#### Experimental/calculated data:

Skin corrosion/irritation

rabbit: Slightly irritating. (similar to OECD guideline 404)

Serious eye damage/irritation

rabbit: non-irritant (similar to OECD guideline 405)

#### Respiratory/Skin sensitization

Assessment of sensitization:

Skin sensitizing effects were not observed in animal studies.

Experimental/calculated data:

Guinea pig maximization test guinea pig: Non-sensitizing. (OECD Guideline 406)

#### Germ cell mutagenicity

Assessment of mutagenicity:

The substance was not mutagenic in bacteria. The substance was not mutagenic in mammalian cell culture.

#### Carcinogenicity

Assessment of carcinogenicity:

No data available.

#### Reproductive toxicity

Assessment of reproduction toxicity:

The results of animal studies gave no indication of a fertility impairing effect. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition. The results were determined in a Screening test (OECD 421/422).

## **Developmental toxicity**

Assessment of teratogenicity:

No indications of a developmental toxic / teratogenic effect were seen in animal studies.

#### Experiences in humans

Experimental/calculated data:

Prolonged contact can result in drying of the skin.

Specific target organ toxicity (single exposure)

#### Assessment of STOT single:

Based on the available information there is no specific target organ toxicity to be expected after a single exposure.

#### Repeated dose toxicity and Specific target organ toxicity (repeated exposure)

Assessment of repeated dose toxicity:

No adverse effects were observed after repeated inhalative exposure in animal studies.

#### Aspiration hazard

Date / Revised: 09.11.2023 Version: 7.0
Date previous version: 07.11.2022 Previous version: 6.0

Date / First version: 07.11.2011
Product: **PENTYLACETATE** 

(ID no. 30034749/SDS\_GEN\_IE/EN)

Date of print 08.10.2025

not applicable

#### Interactive effects

No data available.

#### 11.2. Information on other hazards

#### Endocrine disrupting properties

The substance is not identified to have endocrine disrupting properties according to Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 nor is included in the Candidate List of substances of very high concern according to EU REACh Article 59 for having endocrine disrupting properties.

## **SECTION 12: Ecological Information**

## 12.1. Toxicity

#### Assessment of aquatic toxicity:

Acutely harmful for aquatic organisms. The inhibition of the degradation activity of activated sludge is not anticipated when introduced to biological treatment plants in appropriate low concentrations.

## Toxicity to fish:

LC50 (96 h) 69 mg/l, Pimephales promelas (APHA 1971, static)

The product has not been tested. The statement has been derived from substances/products of a similar structure or composition. The details of the toxic effect relate to the nominal concentration.

#### Aquatic invertebrates:

EC50 (48 h) 40.9 mg/l, Daphnia magna (OECD Guideline 202, part 1, static)

The product has not been tested. The statement has been derived from substances/products of a similar structure or composition. The statement of the toxic effect relates to the analytically determined concentration.

#### Aquatic plants:

EC50 (72 h) > 466 mg/l (growth rate), Pseudokirchneriella subcapitata (OECD Guideline 201, static) The product has not been tested. The statement has been derived from substances/products of a similar structure or composition. The statement of the toxic effect relates to the analytically determined concentration.

#### Microorganisms/Effect on activated sludge:

EC20 (30 min) > 1,000 mg/l, (OECD Guideline 209, aerobic)

The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

#### Chronic toxicity to fish:

No data available regarding toxicity to fish.

Chronic toxicity to aquatic invertebrates:

Date / Revised: 09.11.2023 Version: 7.0
Date previous version: 07.11.2022 Previous version: 6.0

Date / First version: 07.11.2011
Product: **PENTYLACETATE** 

(ID no. 30034749/SDS\_GEN\_IE/EN)

Date of print 08.10.2025

No data available regarding toxicity to daphnids.

Assessment of terrestrial toxicity:

No data available concerning terrestrial toxicity.

## 12.2. Persistence and degradability

Assessment biodegradation and elimination (H2O):

Readily biodegradable (according to OECD criteria).

The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

#### Elimination information:

87 % BOD of the ThOD (20 d) (APHA 'Standard Methods', No. 219, 1971) (aerobic, Seawater) The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

72 % BOD of the ThOD (20 d) (APHA 'Standard Methods', No. 219, 1971) (aerobic, predominantly domestic sewage, non-adapted)

The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

57 % BOD of the ThOD (28 d) (OECD 301D; 92/69/EWG, C.4-E) (aerobic, domestic sewage) The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Assessment of stability in water:

No data available.

Information on Stability in Water (Hydrolysis):

No data available.

#### 12.3. Bioaccumulative potential

Assessment bioaccumulation potential:

Because of the n-octanol/water distribution coefficient (log Pow) accumulation in organisms is not to be expected.

The product has not been tested. The statement has been derived from the properties of the individual components.

Bioaccumulation potential:

No data available.

#### 12.4. Mobility in soil

Assessment transport between environmental compartments:

Volatility: The substance will slowly evaporate into the atmosphere from the water surface.

Adsorption in soil: Adsorption to solid soil phase is not expected.

Date / Revised: 09.11.2023 Version: 7.0
Date previous version: 07.11.2022 Previous version: 6.0

Date / First version: 07.11.2011
Product: **PENTYLACETATE** 

(ID no. 30034749/SDS\_GEN\_IE/EN)

Date of print 08.10.2025

#### 12.5. Results of PBT and vPvB assessment

According to Annex XIII of Regulation (EC) No.1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH): The product does not fulfill the criteria for PBT (Persistent/bioaccumulative/toxic) and vPvB (very persistent/very bioaccumulative). Self classification

## 12.6. Endocrine disrupting properties

The substance is not identified to have endocrine disrupting properties according to Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 nor is included in the Candidate List of substances of very high concern according to EU REACh Article 59 for having endocrine disrupting properties.

#### 12.7. Other adverse effects

The substance is not listed in Regulation (EC) 1005/2009 on substances that deplete the ozone layer.

#### 12.8. Additional information

Adsorbable organically-bound halogen (AOX):

This product contains no organically-bound halogen.

Other ecotoxicological advice:

Do not release untreated into natural waters.

## **SECTION 13: Disposal Considerations**

## 13.1. Waste treatment methods

Dispose of in accordance with national, state and local regulations.

Contaminated packaging:

Disposal must be made according to official regulations.

## **SECTION 14: Transport Information**

#### **Land transport**

**ADR** 

UN number or ID number: UN1104

Date / Revised: 09.11.2023 Version: 7.0 Date previous version: 07.11.2022 Previous version: 6.0

Date / First version: 07.11.2011

Product: **PENTYLACETATE** 

(ID no. 30034749/SDS\_GEN\_IE/EN)

Date of print 08.10.2025

AMYL ACETATES UN proper shipping name:

Transport hazard class(es): 3 Packing group: Ш Environmental hazards: no

Special precautions for Tunnel code: D/E

user:

**RID** 

UN number or ID number: UN1104

UN proper shipping name: **AMYL ACETATES** 

Transport hazard class(es): 3 Packing group: Ш Environmental hazards: no

Special precautions for None known

user:

#### **Inland waterway transport**

ADN

UN number or ID number: UN1104

UN proper shipping name: **AMYL ACETATES** 

Transport hazard class(es): 3 Ш Packing group: Environmental hazards: no

Special precautions for

user:

None known

## Transport in inland waterway vessel

Not evaluated

#### Sea transport

**IMDG** 

UN number or ID number: UN 1104

UN proper shipping name: **AMYL ACETATES** 

Transport hazard class(es): 3 Ш Packing group: Environmental hazards:

Marine pollutant: NO

Special precautions for

user:

EmS: F-E; S-D

Date / Revised: 09.11.2023 Version: 7.0
Date previous version: 07.11.2022 Previous version: 6.0

Date / First version: 07.11.2011
Product: PENTYLACETATE

(ID no. 30034749/SDS\_GEN\_IE/EN)

Date of print 08.10.2025

#### Air transport

IATA/ICAO

UN number or ID number: UN 1104

UN proper shipping name: AMYL ACETATES

Transport hazard class(es): 3 Packing group: III

Environmental hazards: No Mark as dangerous for the environment is needed

Special precautions for None known

user:

#### 14.1. UN number or ID number

See corresponding entries for "UN number or ID number" for the respective regulations in the tables above.

#### 14.2. UN proper shipping name

See corresponding entries for "UN proper shipping name" for the respective regulations in the tables above.

#### 14.3. Transport hazard class(es)

See corresponding entries for "Transport hazard class(es)" for the respective regulations in the tables above.

## 14.4. Packing group

See corresponding entries for "Packing group" for the respective regulations in the tables above.

#### 14.5. Environmental hazards

See corresponding entries for "Environmental hazards" for the respective regulations in the tables above.

## 14.6. Special precautions for user

See corresponding entries for "Special precautions for user" for the respective regulations in the tables above.

## 14.7. Maritime transport in bulk according to IMO instruments

Maritime transport in bulk is not intended.

## **SECTION 15: Regulatory Information**

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Prohibitions, Restrictions and Authorizations

Annex XVII of Regulation (EC) No 1907/2006: Number on List: 3, 40

Page: 17/34

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 09.11.2023 Version: 7.0
Date previous version: 07.11.2022 Previous version: 6.0

Date / First version: 07.11.2011 Product: **PENTYLACETATE** 

(ID no. 30034749/SDS\_GEN\_IE/EN)

Date of print 08.10.2025

Directive 2012/18/EU - Control of Major Accident Hazards involving dangerous substances (EU):

List entry in regulation: P5a List entry in regulation: P5b List entry in regulation: P5c

If other regulatory information applies that is not already provided elsewhere in this safety data sheet, then it is described in this subsection.

#### 15.2. Chemical Safety Assessment

Chemical Safety Assessment performed

#### **SECTION 16: Other Information**

Assessment of the hazard classes according to UN GHS criteria (most recent version)

Flam. Liq. 3 Skin Corr./Irrit. 3 Aquatic Acute 3

Full text of the classifications, including the hazard classes and the hazard statements, if mentioned

in section 2 or 3:

Flam. Liq. Flammable liquids

Aquatic Chronic Hazardous to the aquatic environment - chronic

H226 Flammable liquid and vapour.

H412 Harmful to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

#### Abbreviations

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road. ADN = The European Agreement concerning the International Carriage of Dangerous Goods by Inland waterways. ATE = Acute Toxicity Estimates. CAO = Cargo Aircraft Only. CAS = Chemical Abstract Service. CLP = Classification, Labelling and Packaging of substances and mixtures. DIN = German national organization for standardization. DNEL = Derived No Effect Level. EC50 = Effective concentration median for 50% of the population. EC = European Community. EN = European Standards. IARC = International Agency for Research on Cancer. IATA = International Air Transport Association. IBC-Code = Intermediate Bulk Container code. IMDG = International Maritime Dangerous Goods Code. ISO = International Organization for Standardization. STEL = Short-Term Exposure Limit. LC50 = Lethal concentration median for 50% of the population. LD50 = Lethal dose median for 50% of the population. TLV = Threshold Limit Value. MARPOL = The International Convention for the Prevention of Pollution from Ships. NEN = Dutch Norm. NOEC = No Observed Effect Concentration. OEL = Occupational Exposure Limit. OECD = Organization for Economic Cooperation and Development. PBT = Persistent, Bioaccumulative and Toxic. PNEC = Predicted No Effect Level. PPM = Parts per million. RID = The European Agreement concerning the International Carriage of Dangerous Goods by Rail. TWA = Time Weight Average. UN-number = UN number at transport. vPvB = very Persistent and very Bioaccumulative.

The data contained in this safety data sheet are based on our current knowledge and experience and describe the product only with regard to safety requirements. This safety data sheet is neither a Certificate of Analysis (CoA) nor technical data sheet and shall not be mistaken for a specification

Page: 18/34

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 09.11.2023 Version: 7.0 Date previous version: 07.11.2022 Previous version: 6.0

Date / First version: 07.11.2011
Product: PENTYLACETATE

(ID no. 30034749/SDS\_GEN\_IE/EN)

Date of print 08.10.2025

agreement. Identified uses in this safety data sheet do neither represent an agreement on the corresponding contractual quality of the substance/mixture nor a contractually designated use. It is the responsibility of the recipient of the product to ensure any proprietary rights and existing laws and legislation are observed.

Vertical lines in the left hand margin indicate an amendment from the previous version.

Date / Revised: 09.11.2023 Version: 7.0
Date previous version: 07.11.2022 Previous version: 6.0

Date / First version: 07.11.2011
Product: PENTYLACETATE

(ID no. 30034749/SDS\_GEN\_IE/EN)

Date of print 08.10.2025

## **Annex: Exposure Scenarios**

#### Index

1. Formulation

ERC2; PROC3, PROC5, PROC8a, PROC9, PROC15, PROC19

2. Use as processing aid

ERC4; PROC1, PROC2, PROC3, PROC4, PROC8a, PROC9, PROC15

3. Use in Cleaning Agents

ERC4; PROC7, PROC10, PROC13

4. Use in Coatings

ERC4; PROC7, PROC10, PROC13

**5.** Use in Cleaning Agents, (use in professional settings)

ERC8a, ERC8d; PROC10, PROC11, PROC13

6. Use in Cleaning Agents, (consumer use)

ERC8a, ERC8d; PC4, PC24, PC35

7. Use in Coatings, (use in professional settings)

ERC8a, ERC8d; PROC10, PROC11, PROC13

**8.** Use in Coatings, (consumer use)

ERC8a, ERC8d; PC9a, PC15, PC18, PC23

\* \* \* \* \* \* \* \* \* \* \* \* \* \* \* \*

## 1. Short title of exposure scenario

Formulation

ERC2; PROC3, PROC5, PROC8a, PROC9, PROC15, PROC19

Contributing exposure scenario	
Use descriptors covered	ESVOC SpERC 2.2.v1: ESVOC SpERC 2.2.v1
Operational conditions	
Annual amount used in the EU	1,000,000 kg
Minimum emission days per year	300
Emission factor air	1 %
Emission factor water	0.5 %
Emission factor soil	0.01 %

Date / Revised: 09.11.2023 Version: 7.0
Date previous version: 07.11.2022 Previous version: 6.0

Date / First version: 07.11.2011
Product: PENTYLACETATE

(ID no. 30034749/SDS\_GEN\_IE/EN)

Date of print 08.10.2025

Receive Surf. Water (Flow Rate).	18,000 m3/d	
Dilution factor river	10	
Dilution factor coast	100	
Risk Management Measures		
Air treatment measures considered suitable are, e.g.		Wet scrubber - for dusts, Filtration, Waste gas treatment by thermal oxidation, Adsorption
Wastewater treatment measures considered suitable are, e.g.		Acclimated biological treatment, Distillation
Type of STP		Municipal STP
Assumed sewage treatment plant flow (m3/d)		2,000 m3/d
Exposure estimate and reference to	its source	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Environment	
Risk Characterization Ratio (RCR)	0.225825	
	Risk from environmental exposure is driven by freshwater.	
Maximum amount of safe use	1,476.1 kg/d	
Risk from environmental exposure is driven by freshwater.		

Contributing exposure scenario	
Use descriptors covered	PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition  As no toxicological hazard was identified no human related (worker/consumer) exposure assessment and risk characterization was performed.

Contributing exposure scenario	
Use descriptors covered	PROC5: Mixing or blending in batch processes As no toxicological hazard was identified no human related (worker/consumer) exposure assessment and risk characterization was performed.

Contributing exposure scenario	
Use descriptors covered	PROC8a: Transfer of substance or mixture (charging and discharging) at non-dedicated facilities As no toxicological hazard was identified no human related (worker/consumer) exposure assessment and risk characterization was performed.

Date / Revised: 09.11.2023 Version: 7.0
Date previous version: 07.11.2022 Previous version: 6.0

Date / First version: 07.11.2011
Product: PENTYLACETATE

(ID no. 30034749/SDS\_GEN\_IE/EN)

Date of print 08.10.2025

Contributing exposure scenario	
Use descriptors covered	PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing). As no toxicological hazard was identified no human related (worker/consumer) exposure assessment and risk characterization was performed.

Contributing exposure scenario	
Use descriptors covered	PROC15: Use a laboratory reagent. As no toxicological hazard was identified no human related (worker/consumer) exposure assessment and risk characterization was performed.

Contributing exposure scenario	
Use descriptors covered	PROC19: Manual activities involving hand contact As no toxicological hazard was identified no human related (worker/consumer) exposure assessment and risk characterization was performed.

\* \* \* \* \* \* \* \* \* \* \* \* \* \* \* \*

## 2. Short title of exposure scenario

Use as processing aid

ERC4; PROC1, PROC2, PROC3, PROC4, PROC8a, PROC9, PROC15

Contributing exposure scenario	
Use descriptors covered	ESVOC SpERC 4.3a.v1: ESVOC SpERC 4.3a.v1
Operational conditions	
Annual amount used in the EU	200,000 kg
Minimum emission days per year	300
Emission factor air	98 %
Emission factor water	2 %
Emission factor soil	0 %
Receive Surf. Water (Flow Rate).	18,000 m3/d
Dilution factor river	10
Dilution factor coast	100

Date / Revised: 09.11.2023 Version: 7.0
Date previous version: 07.11.2022 Previous version: 6.0

Date / First version: 07.11.2011
Product: **PENTYLACETATE** 

(ID no. 30034749/SDS\_GEN\_IE/EN)

Date of print 08.10.2025

Risk Management Measures		
Air treatment measures considered suitable are, e.g.		Wet scrubber - for dusts, Filtration, Waste gas treatment by thermal oxidation, Adsorption
Wastewater treatment measures considered suitable are, e.g.		Acclimated biological treatment, Distillation
Type of STP		Municipal STP
Assumed sewage treatment plant flow (m3/d)		2,000 m3/d
Exposure estimate and reference to its source		
Assessment method	EASY TRA v4.1, ECETO	C TRA v3.0, Environment
Risk Characterization Ratio (RCR)	0.180801	
	Risk from environmental exposure is driven by freshwater.	
Maximum amount of safe use	368.7 kg/d	
Risk from environmental exposure is driven by freshwater.		

Contributing exposure scenario	
Use descriptors covered	PROC1: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions.  As no toxicological hazard was identified no human related (worker/consumer) exposure assessment and risk characterization was performed.

Contributing exposure scenario	
Use descriptors covered	PROC2: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions As no toxicological hazard was identified no human related (worker/consumer) exposure assessment and risk characterization was performed.

Contributing exposure scenario	
Use descriptors covered	PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition As no toxicological hazard was identified no human related (worker/consumer) exposure assessment and risk characterization was performed.

Contributing exposure scenario	
Use descriptors covered	PROC4: Chemical production where opportunity for
	exposure arises

Date / Revised: 09.11.2023 Version: 7.0
Date previous version: 07.11.2022 Previous version: 6.0

Date / First version: 07.11.2011
Product: **PENTYLACETATE** 

(ID no. 30034749/SDS\_GEN\_IE/EN)

Date of print 08.10.2025

As no toxicological hazard was identified no human related (worker/consumer) exposure assessment and risk characterization was performed.

Contributing exposure scenario	
Use descriptors covered	PROC8a: Transfer of substance or mixture (charging and discharging) at non-dedicated facilities As no toxicological hazard was identified no human related (worker/consumer) exposure assessment and risk characterization was performed.

Contributing exposure scenario	
Use descriptors covered	PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing). As no toxicological hazard was identified no human related (worker/consumer) exposure assessment and risk characterization was performed.

Contributing exposure scenario	
Use descriptors covered	PROC15: Use a laboratory reagent. As no toxicological hazard was identified no human related (worker/consumer) exposure assessment and risk characterization was performed.

\* \* \* \* \* \* \* \* \* \* \* \* \* \* \* \*

## 3. Short title of exposure scenario

Use in Cleaning Agents

ERC4; PROC7, PROC10, PROC13

Contributing exposure scenario		
Use descriptors covered	ESVOC SpERC 4.4a.v1: ESVOC SpERC 4.4a.v1	
Operational conditions		
Annual amount used in the EU	100,000 kg	
Minimum emission days per year	20	
Emission factor air	30 %	
Emission factor water	0.01 %	
Emission factor soil	0 %	

Date / Revised: 09.11.2023 Version: 7.0
Date previous version: 07.11.2022 Previous version: 6.0

Date / First version: 07.11.2011
Product: **PENTYLACETATE** 

(ID no. 30034749/SDS\_GEN\_IE/EN)

Date of print 08.10.2025

Receive Surf. Water (Flow Rate).	18,000 m3/d		
Dilution factor river	10	10	
Dilution factor coast	100		
Risk Management Measures			
Air treatment measures considered suitable are, e.g.		Wet scrubber - for dusts, Waste gas treatment by thermal oxidation, Adsorption	
Wastewater treatment measures considered suitable are, e.g.		Acclimated biological treatment, Distillation	
Type of STP		Municipal STP	
Assumed sewage treatment plant flow (m3/d)		2,000 m3/d	
Exposure estimate and reference to	its source		
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Environment		
Risk Characterization Ratio (RCR)	0.012076		
	Risk from environmental exposure is driven by soil.		
Maximum amount of safe use	41,403 kg/d		
Risk from environmental exposure is driven by soil.			

Contributing exposure scenario	
Use descriptors covered	PROC7: Industrial spraying As no toxicological hazard was identified no human related (worker/consumer) exposure assessment and risk characterization was performed.

Contributing exposure scenario	
Use descriptors covered	PROC10: Roller application or brushing As no toxicological hazard was identified no human related (worker/consumer) exposure assessment and risk characterization was performed.

Contributing exposure scenario	
Use descriptors covered	PROC13: Treatment of articles by dipping and pouring. As no toxicological hazard was identified no human related (worker/consumer) exposure assessment and risk characterization was performed.

\* \* \* \* \* \* \* \* \* \* \* \* \* \* \* \*

## 4. Short title of exposure scenario

Use in Coatings

Date / Revised: 09.11.2023 Version: 7.0
Date previous version: 07.11.2022 Previous version: 6.0

Date / First version: 07.11.2011 Product: **PENTYLACETATE** 

(ID no. 30034749/SDS\_GEN\_IE/EN)

Date of print 08.10.2025

ERC4; PROC7, PROC10, PROC13

## Control of exposure and risk management measures

Contributing exposure scenario			
Use descriptors covered	ESVOC SpERC 4.3a.v1: ESVOC SpERC 4.3a.v1		
Operational conditions			
Annual amount used in the EU	600,000 kg	600,000 kg	
Minimum emission days per year	300	300	
Emission factor air	98 %		
Emission factor water	2 %	2 %	
Emission factor soil	0 %	0 %	
Receive Surf. Water (Flow Rate).	18,000 m3/d	18,000 m3/d	
Dilution factor river	10		
Dilution factor coast	100		
Risk Management Measures			
Air treatment measures considered suitable are, e.g.		Wet scrubber - for dusts, Filtration, Waste gas treatment by thermal oxidation, Adsorption	
Wastewater treatment measures considered suitable are, e.g.		Acclimated biological treatment, Distillation	
Type of STP		Municipal STP	
Assumed sewage treatment plant flow (m3/d)		2,000 m3/d	
Exposure estimate and reference to its source			
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Environment		
Risk Characterization Ratio (RCR)	0.540992		
	Risk from environmental exposure is driven by freshwater.		
Maximum amount of safe use	369.7 kg/d		
Risk from environmental exposure is driven by freshwater.			

Contributing exposure scenario	
Use descriptors covered	PROC7: Industrial spraying As no toxicological hazard was identified no human related (worker/consumer) exposure assessment and risk characterization was performed.

## Contributing exposure scenario

Date / Revised: 09.11.2023 Version: 7.0
Date previous version: 07.11.2022 Previous version: 6.0

Date / First version: 07.11.2011 Product: **PENTYLACETATE** 

(ID no. 30034749/SDS\_GEN\_IE/EN)

Date of print 08.10.2025

Use descriptors covered	PROC10: Roller application or brushing As no toxicological hazard was identified no human related (worker/consumer) exposure assessment and risk characterization was performed.
-------------------------	--

Contributing exposure scenario	
Use descriptors covered	PROC13: Treatment of articles by dipping and pouring. As no toxicological hazard was identified no human related (worker/consumer) exposure assessment and risk characterization was performed.

\* \* \* \* \* \* \* \* \* \* \* \* \* \* \* \*

## 5. Short title of exposure scenario

Use in Cleaning Agents, (use in professional settings) ERC8a, ERC8d; PROC10, PROC11, PROC13

Contributing exposure scenario		
Use descriptors covered	ESVOC SpERC 8.4b.v1: ESVOC SpERC 8.4b.v1	
Operational conditions		
Annual amount used in the EU	100,000 kg	
Minimum emission days per year	365	
Emission factor air	2 %	
Emission factor water	1 ppm	
Emission factor soil	0 %	
Receive Surf. Water (Flow Rate).	18,000 m3/d	
Dilution factor river	10	
Dilution factor coast	100	
Risk Management Measures		
Type of STP	no STP	
Exposure estimate and reference to its source		
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Environment	
Risk Characterization Ratio (RCR)	0.000706	
	Risk from environmental exposure is driven by freshwater.	
Maximum amount of safe use	388.2 kg/d	

Date / Revised: 09.11.2023 Version: 7.0 Date previous version: 07.11.2022 Previous version: 6.0

Date / First version: 07.11.2011
Product: PENTYLACETATE

(ID no. 30034749/SDS\_GEN\_IE/EN)

Date of print 08.10.2025

Risk from environmental exposure is driven by freshwater.

Contributing exposure scenario	
Use descriptors covered	ESVOC SpERC 8.4b.v1: ESVOC SpERC 8.4b.v1
Operational conditions	
Annual amount used in the EU	100,000 kg
Minimum emission days per year	365
Emission factor air	2 %
Emission factor water	1 ppm
Emission factor soil	0 %
Receive Surf. Water (Flow Rate).	18,000 m3/d
Dilution factor river	10
Dilution factor coast	100
Risk Management Measures	
Type of STP	no STP
Exposure estimate and reference to	o its source
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Environment
Risk Characterization Ratio (RCR)	0.000706
	Risk from environmental exposure is driven by freshwater.
	388.2
Maximum amount of safe use	kg/d
Risk from environmental exposure is o	driven by freshwater.

Contributing exposure scenario	
Use descriptors covered	PROC10: Roller application or brushing As no toxicological hazard was identified no human related (worker/consumer) exposure assessment and risk characterization was performed.

Contributing exposure scenario	
Use descriptors covered	PROC11: Non industrial spraying As no toxicological hazard was identified no human related (worker/consumer) exposure assessment and risk characterization was performed.

Contributing exposure scenario	
Use descriptors covered	PROC13: Treatment of articles by dipping and pouring.

Page: 28/34

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 09.11.2023 Version: 7.0
Date previous version: 07.11.2022 Previous version: 6.0

Date / First version: 07.11.2011
Product: **PENTYLACETATE** 

(ID no. 30034749/SDS\_GEN\_IE/EN)

Date of print 08.10.2025

	As no toxicological hazard was identified no human related (worker/consumer) exposure assessment and risk characterization was performed.
--	---

\* \* \* \* \* \* \* \* \* \* \* \* \* \* \*

## 6. Short title of exposure scenario

Use in Cleaning Agents, (consumer use) ERC8a, ERC8d; PC4, PC24, PC35

Contributing exposure scenario		
Use descriptors covered	ESVOC SpERC 8.4c.v1: ESVOC SpERC 8.4c.v1	
Operational conditions		
Annual amount used in the EU	50,000 kg	
Minimum emission days per year	365	
Emission factor air	95 %	
Emission factor water	2.5 %	
Emission factor soil	2.5 %	
Receive Surf. Water (Flow Rate).	18,000 m3/d	
Dilution factor river	10	
Dilution factor coast	100	
Risk Management Measures		
Type of STP	no STP	
Exposure estimate and reference to its source		
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Environment	
Risk Characterization Ratio (RCR)	0.004882	
	Risk from environmental exposure is driven by freshwater.	
	28.1	
Maximum amount of safe use	kg/d	
Risk from environmental exposure is driven by freshwater.		

Contributing exposure scenario	
Use descriptors covered	ESVOC SpERC 8.4c.v1: ESVOC SpERC 8.4c.v1
Operational conditions	
Annual amount used in the EU	50,000 kg

Date / Revised: 09.11.2023 Version: 7.0
Date previous version: 07.11.2022 Previous version: 6.0

Date / First version: 07.11.2011
Product: **PENTYLACETATE** 

(ID no. 30034749/SDS\_GEN\_IE/EN)

Date of print 08.10.2025

Minimum emission days per year	365	
Emission factor air	95 %	
Emission factor water	2.5 %	
Emission factor soil	2.5 %	
Receive Surf. Water (Flow Rate).	18,000 m3/d	
Dilution factor river	10	
Dilution factor coast	100	
Risk Management Measures	•	
Type of STP	no STP	
Exposure estimate and reference to its source		
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Environment	
Risk Characterization Ratio (RCR)	0.004882	
	Risk from environmental exposure is driven by freshwater.	
	28.1	
Maximum amount of safe use	kg/d	
Risk from environmental exposure is o	driven by freshwater.	

Contributing exposure scenario		
Use descriptors covered	PC4: Anti-Freeze and De-icing products. As no toxicological hazard was identified no human related (worker/consumer) exposure assessment and risk characterization was performed.	
Operational conditions		
Vapour pressure of the substance during use	491 Pa	
Process temperature	20 °C	

Contributing exposure scenario	
Use descriptors covered	PC24: Lubricants, Greases and Release Products As no toxicological hazard was identified no human related (worker/consumer) exposure assessment and risk characterization was performed.
Operational conditions	
Vapour pressure of the substance during use	491 Pa
Process temperature	20 °C

Date / Revised: 09.11.2023 Version: 7.0 Date previous version: 07.11.2022 Previous version: 6.0

Date / First version: 07.11.2011 Product: **PENTYLACETATE** 

(ID no. 30034749/SDS\_GEN\_IE/EN)

Date of print 08.10.2025

Contributing exposure scenario	
Use descriptors covered	PC35: Washing and Cleaning Products (including solvent based products). As no toxicological hazard was identified no human related (worker/consumer) exposure assessment and risk characterization was performed.
Operational conditions	
Vapour pressure of the substance during use	491 Pa
Process temperature	20 °C

**7. Short title of exposure scenario**Use in Coatings, (use in professional settings)
ERC8a, ERC8d; PROC10, PROC11, PROC13

Contributing exposure scenario		
Use descriptors covered	ESVOC SpERC 8.3b.v1: ESVOC SpERC 8.3b.v1	
Operational conditions		
Annual amount used in the EU	100,000 kg	
Minimum emission days per year	365	
Emission factor air	98 %	
Emission factor water	1 %	
Emission factor soil	1 %	
Receive Surf. Water (Flow Rate).	18,000 m3/d	
Dilution factor river	10	
Dilution factor coast	100	
Risk Management Measures		
Type of STP	no STP	
Exposure estimate and reference to its source		
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Environment	
Risk Characterization Ratio (RCR)	0.002376	
	Risk from environmental exposure is driven by freshwater.	
Maximum amount of safe use	57.7	
waxiiiiuiii aiiiuuiii ui sale use	kg/d	

Date / Revised: 09.11.2023 Version: 7.0
Date previous version: 07.11.2022 Previous version: 6.0

Date / First version: 07.11.2011
Product: PENTYLACETATE

(ID no. 30034749/SDS\_GEN\_IE/EN)

Date of print 08.10.2025

Risk from environmental exposure is driven by freshwater.

Contributing exposure scenario	
Use descriptors covered	ESVOC SpERC 8.3b.v1: ESVOC SpERC 8.3b.v1
Operational conditions	
Annual amount used in the EU	100,000 kg
Minimum emission days per year	365
Emission factor air	98 %
Emission factor water	1 %
Emission factor soil	1 %
Receive Surf. Water (Flow Rate).	18,000 m3/d
Dilution factor river	10
Dilution factor coast	100
Risk Management Measures	
Type of STP	no STP
Exposure estimate and reference to	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Environment
Risk Characterization Ratio (RCR)	0.002376
	Risk from environmental exposure is driven by freshwater.
Maximum amount of safe use	57.7 kg/d
Risk from environmental exposure is d	driven by freshwater.

Contributing exposure scenario	
Use descriptors covered	PROC10: Roller application or brushing As no toxicological hazard was identified no human related (worker/consumer) exposure assessment and risk characterization was performed.

Contributing exposure scenario	
Use descriptors covered	PROC11: Non industrial spraying As no toxicological hazard was identified no human related (worker/consumer) exposure assessment and risk characterization was performed.

Contributing exposure scenario	
Use descriptors covered	PROC13: Treatment of articles by dipping and pouring.

Page: 32/34

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 09.11.2023

Version: 7

Date / Revised: 09.11.2023 Version: 7.0
Date previous version: 07.11.2022 Previous version: 6.0

Date / First version: 07.11.2011
Product: **PENTYLACETATE** 

(ID no. 30034749/SDS\_GEN\_IE/EN)

Date of print 08.10.2025

	As no toxicological hazard was identified no human related (worker/consumer) exposure assessment and risk characterization was performed.
--	---

\* \* \* \* \* \* \* \* \* \* \* \* \* \* \*

## 8. Short title of exposure scenario

Use in Coatings, (consumer use) ERC8a, ERC8d; PC9a, PC15, PC18, PC23

Contributing exposure scenario	
Use descriptors covered	ESVOC SpERC 8.3c.v1: ESVOC SpERC 8.3c.v1
Operational conditions	
Annual amount used in the EU	50,000 kg
Minimum emission days per year	365
Emission factor air	98.5 %
Emission factor water	1 %
Emission factor soil	0.5 %
Receive Surf. Water (Flow Rate).	18,000 m3/d
Dilution factor river	10
Dilution factor coast	100
Risk Management Measures	
Type of STP	no STP
Exposure estimate and reference to	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Environment
Risk Characterization Ratio (RCR)	0.002376
	Risk from environmental exposure is driven by freshwater.
Maximum amount of safe use	57.7 kg/d
Risk from environmental exposure is driven by freshwater.	

Contributing exposure scenario	
Use descriptors covered	ESVOC SpERC 8.3c.v1: ESVOC SpERC 8.3c.v1
Operational conditions	
Annual amount used in the EU	50,000 kg

Date / Revised: 09.11.2023 Version: 7.0
Date previous version: 07.11.2022 Previous version: 6.0

Date / First version: 07.11.2011
Product: **PENTYLACETATE** 

(ID no. 30034749/SDS\_GEN\_IE/EN)

Date of print 08.10.2025

Minimum emission days per year	365		
Emission factor air	98.5 %		
Emission factor water	1 %		
Emission factor soil	0.5 %		
Receive Surf. Water (Flow Rate).	18,000 m3/d		
Dilution factor river	10		
Dilution factor coast	100		
Risk Management Measures			
Type of STP	no STP		
Exposure estimate and reference to	Exposure estimate and reference to its source		
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Environment		
Risk Characterization Ratio (RCR)	0.002376		
	Risk from environmental exposure is driven by freshwater.		
	57.7		
Maximum amount of safe use	kg/d		
Risk from environmental exposure is d	riven by freshwater.		

Contributing exposure scenario		
Use descriptors covered	PC9a: Coatings and paints, thinners, paint removers As no toxicological hazard was identified no human related (worker/consumer) exposure assessment and risk characterization was performed.	
Operational conditions		
Vapour pressure of the substance during use	491 Pa	
Process temperature	20 °C	

Contributing exposure scenario	
Use descriptors covered	PC15: Non-metal-surface treatment products. As no toxicological hazard was identified no human related (worker/consumer) exposure assessment and risk characterization was performed.
Operational conditions	
Vapour pressure of the substance during use	491 Pa
Process temperature	20 °C

Date / Revised: 09.11.2023 Version: 7.0
Date previous version: 07.11.2022 Previous version: 6.0

Date / First version: 07.11.2011
Product: **PENTYLACETATE** 

(ID no. 30034749/SDS\_GEN\_IE/EN)

Date of print 08.10.2025

Contributing exposure scenario		
Use descriptors covered	PC18: Ink and Toners. As no toxicological hazard was identified no human related (worker/consumer) exposure assessment and risk characterization was performed.	
Operational conditions		
Vapour pressure of the substance during use	491 Pa	
Process temperature	20 °C	

Contributing exposure scenario	
Use descriptors covered	PC23: Leather tanning, dye, finishing, impregnation and care products. As no toxicological hazard was identified no human related (worker/consumer) exposure assessment and risk characterization was performed.
Operational conditions	
Vapour pressure of the substance during use	491 Pa
Process temperature	20 °C

\* \* \* \* \* \* \* \* \* \* \* \* \* \* \* \*