

Safety data sheet

Page: 1/19

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 04.04.2024

Version: 3.1

Date / Previous version: 05.03.2024

Previous version: 3.0

Product: **Kaurit® Glue 270**

(ID no. 30034914/SDS_GEN_DE/EN)

Date of print 21.10.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Kaurit® Glue 270

UFI: 57J8-QFYE-S00J-0QQD

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses: Chemical

Recommended use: Chemical, for industrial and professional users

1.3. Details of the supplier of the safety data sheet

Company:

BASF SE

67056 Ludwigshafen

GERMANY

Division Monomers

Telephone: +49 621 60 42737

E-mail address: pss.monomers@basf.com

1.4. Emergency telephone number

International emergency number:

Telephone: +49 180 2273-112

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 04.04.2024

Version: 3.1

Date / Previous version: 05.03.2024

Previous version: 3.0

Product: **Kaurit® Glue 270**

(ID no. 30034914/SDS_GEN_DE/EN)

Date of print 21.10.2025

SECTION 2: Hazards Identification

2.1. Classification of the substance or mixture

For the classification of the mixture the following methods have been applied: extrapolation on the concentration levels of the hazardous substances, on basis of test results and after evaluation of experts. The methodologies used are mentioned at the respective test results.

According to Regulation (EC) No 1272/2008 [CLP]

Skin Sens. 1	H317 May cause an allergic skin reaction.
Muta. 2	H341 Suspected of causing genetic defects.
Carc. 1B	H350 May cause cancer.

For the classifications not written out in full in this section the full text can be found in section 16.

2.2. Label elements

According to Regulation (EC) No 1272/2008 [CLP]

Pictogram:



Signal Word:

Danger

Hazard Statement:

H317	May cause an allergic skin reaction.
H350	May cause cancer.
H341	Suspected of causing genetic defects.

Precautionary Statements (Prevention):

P280	Wear protective gloves, protective clothing and eye protection or face protection.
P201	Obtain special instructions before use.
P260	Do not breathe mist or vapour.
P202	Do not handle until all safety precautions have been read and understood.
P272	Contaminated work clothing should not be allowed out of the workplace.

Precautionary Statements (Response):

P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P308 + P311	IF exposed or concerned: Call a POISON CENTER or physician.
P303	IF ON SKIN (or hair):
P361	Take off immediately all contaminated clothing.
P353	Rinse skin with water [or shower].
P363	Wash contaminated clothing before reuse.

Precautionary Statements (Storage):

P405	Store locked up.
------	------------------

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 04.04.2024

Version: 3.1

Date / Previous version: 05.03.2024

Previous version: 3.0

Product: **Kaurit® Glue 270**

(ID no. 30034914/SDS_GEN_DE/EN)

Date of print 21.10.2025

Precautionary Statements (Disposal):

P501 Dispose of contents and container to hazardous or special waste collection point.

Labeling of special preparations (GHS):

Restricted to professional users.

2.3. Other hazards

According to Regulation (EC) No 1272/2008 [CLP]

No specific dangers known, if the regulations/notes for storage and handling are considered.

The product does not contain a substance above legal limits fulfilling the PBT

(persistent/bioaccumulative/toxic) criteria or the vPvB (very persistent/very bioaccumulative) criteria.

Product does not contain a substance above legal limits included in the list established in accordance with Article 59(1) of Regulation (EC) No 1907/2006 for having endocrine disrupting properties or is identified to have endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

SECTION 3: Composition/Information on Ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Chemical nature

Polymer based on: Urea, Formaldehyde
in water

Regulatory relevant ingredients

Formaldehyde

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 04.04.2024

Version: 3.1

Date / Previous version: 05.03.2024

Previous version: 3.0

Product: **Kaurit® Glue 270**

(ID no. 30034914/SDS_GEN_DE/EN)

Date of print 21.10.2025

Content (W/W): $\geq 1\%$ - $< 3\%$
CAS Number: 50-00-0
EC-Number: 200-001-8
REACH registration number: 01-2119488953-20
INDEX-Number: 605-001-00-5

Substance with EU occupational exposure limit

Acute Tox. 2 (Inhalation - vapour)
Acute Tox. 3 (oral)
Acute Tox. 3 (dermal)
Skin Corr. 1B
Eye Dam. 1
Skin Sens. 1
Muta. 2
Carc. 1B
H330, H317, H350, H341, H314, H301 + H311
Differing classification according to current knowledge and the criteria given in Annex I of Regulation (EC) No. 1272/2008
Acute Tox. 3 (dermal)
Acute Tox. 2 (Inhalation - vapour)
Acute Tox. 3 (oral)
Skin Sens. 1A
Muta. 2
Carc. 1B
Skin Corr. 1B
Eye Dam. 1
Specific concentration limit:
Eye Dam./Irrit. 2: $5 - < 25\%$
STOT SE 3, irr. to respiratory syst.: $\geq 5\%$
Skin Sens. 1: $\geq 0,2\%$
Skin Corr./Irrit. 2: $5 - < 25\%$
Skin Corr./Irrit. 1B: $\geq 25\%$

methanol

Content (W/W): $\geq 0,3\%$ - $< 1\%$
CAS Number: 67-56-1
EC-Number: 200-659-6
REACH registration number: 01-2119433307-44
INDEX-Number: 603-001-00-X

Flam. Liq. 2
Acute Tox. 3 (Inhalation - vapour)
Acute Tox. 3 (oral)
Acute Tox. 3 (dermal)
STOT SE (Central nervous system, Optic nerve)
1
H225, H301 + H311 + H331, H370
Specific concentration limit:
STOT SE 2: $3 - < 10\%$
STOT SE 1: $\geq 10\%$
Acute toxicity estimate:
oral: 100 mg/kg
Inhalation: 3 mg/l
dermal: 300 mg/kg

For the classifications not written out in full in this section, including the hazard classes and the hazard statements, the full text is listed in section 16.

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 04.04.2024

Version: 3.1

Date / Previous version: 05.03.2024

Previous version: 3.0

Product: **Kaurit® Glue 270**

(ID no. 30034914/SDS_GEN_DE/EN)

Date of print 21.10.2025

SECTION 4: First-Aid Measures

4.1. Description of first aid measures

Remove contaminated clothing.

If inhaled:

If difficulties occur after vapour/aerosol has been inhaled, remove to fresh air and seek medical attention.

On skin contact:

Wash thoroughly with soap and water

On contact with eyes:

Immediately wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.

On ingestion:

Immediately rinse mouth and then drink 200-300 ml of water, seek medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms: Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11., (Further) symptoms and / or effects are not known so far

Hazards: No hazard is expected under intended use and appropriate handling.

4.3. Indication of any immediate medical attention and special treatment needed

Treatment: Treat according to symptoms (decontamination, vital functions), no known specific antidote.

SECTION 5: Fire-Fighting Measures

5.1. Extinguishing media

Suitable extinguishing media:

water spray, foam, carbon dioxide, dry powder

5.2. Special hazards arising from the substance or mixture

Endangering substances: Formaldehyde, methanol, carbon monoxide, Carbon dioxide, nitrogen oxides

Advice: The substances/groups of substances mentioned can be released in case of fire.

5.3. Advice for fire-fighters

Further information:

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 04.04.2024

Version: 3.1

Date / Previous version: 05.03.2024

Previous version: 3.0

Product: **Kaurit® Glue 270**

(ID no. 30034914/SDS_GEN_DE/EN)

Date of print 21.10.2025

Fire debris must be disposed of in accordance with official regulations. In case of combustion evolution of toxic gases/vapours possible. Do not allow to enter drains or waterways. Forms slippery surfaces with water.

SECTION 6: Accidental Release Measures

Forms slippery surfaces with water.

6.1. Personal precautions, protective equipment and emergency procedures

Avoid contact with the skin, eyes and clothing. Handle in accordance with good industrial hygiene and safety practice. Information regarding personal protective measures, see section 8.

6.2. Environmental precautions

Do not allow to enter soil, waterways or waste water channels. Prevent entry into drains and surface waters. Ensure compliance with local regulations before discharging into effluent treatment plants.

6.3. Methods and material for containment and cleaning up

For large amounts: Sweep/shovel up.

For residues: Pick up with suitable absorbent material.

6.4. Reference to other sections

Information regarding exposure controls/personal protection and disposal considerations can be found in section 8 and 13.

SECTION 7: Handling and Storage

7.1. Precautions for safe handling

Handle in accordance with good industrial hygiene and safety practice.

Inform workers about possible hazards caused by the release of formaldehyde during processing.

Protection against fire and explosion:

No special precautions necessary.

7.2. Conditions for safe storage, including any incompatibilities

Suitable materials for containers: Carbon steel (Iron), Stainless steel 1.4401, Stainless steel 1.4301 (V2), glass

Unsuitable materials for containers: Aluminium, Paper/Fibreboard

Further information on storage conditions: Keep in a cool place.

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 04.04.2024

Version: 3.1

Date / Previous version: 05.03.2024

Previous version: 3.0

Product: **Kaurit® Glue 270**

(ID no. 30034914/SDS_GEN_DE/EN)

Date of print 21.10.2025

Storage class according to TRGS 510 (originally VCI, Germany): (6.1D) Non-combustible substances of acute toxicity, category 3 / hazardous substances that are toxic or produce chronic effects

7.3. Specific end use(s)

For the relevant identified use(s) listed in Section 1 the advice mentioned in this section 7 is to be observed.

SECTION 8: Exposure Controls/Personal Protection

8.1. Control parameters

Components with occupational exposure limits

The surveillance of the workplace by exposure measurements may be necessary, in order to prove the efficiency of safety measures, for example ventilation or the need of respiratory protection. Since this requires a specific competency, only accredited laboratories should be contracted. Regarding suitable methods to assess inhalation exposure, the European Standards EN 482, 689 and 14042 are to be considered. In addition, the TRGS 402 has to be observed in Germany.

50-00-0: Formaldehyde

STEL value 0,74 mg/m³ (Directive 2004/37/EC)

TWA value 0,62 mg/m³ ; 0,5 ppm (Directive 2004/37/EC)

TWA value 0,37 mg/m³ ; 0,3 ppm (Directive 2004/37/EC)

STEL value 0,6 ppm (Directive 2004/37/EC)

OEL 0,37 mg/m³ ; 0,3 ppm (TRGS 900 (DE))

Ceiling limit value/factor: 2

If the occupational exposure limit value (AGW) and the biological limit value (BGW) are complied with, there should be no risk of damage for the unborn child (see TRGS 900, Number 2.7)

Short Term Exposure Classification: (TRGS 900 (DE))

Category I: Substances for which the localized effect has an assigned exposure limit or for substances with a sensitizing effect in respiratory passages

HAZ_DES (TRGS 900 (DE))

Skin sensitization

HAZ_DES X (TRGS 900 (DE))

Carcinogenic substance(s) of category 1A/1B. For activities with this hazardous substance, § 10 of the Hazardous Substances Act (GefStoffV) must also be observed.

67-56-1: methanol

Skin Designation (OEL (EU))

The substance can be absorbed through the skin.

TWA value 260 mg/m³ ; 200 ppm (OEL (EU))

indicative

Skin Designation (TRGS 900 (DE))

The substance can be absorbed through the skin.

Short Term Exposure Classification: (TRGS 900 (DE))

Category II: Substances with a resorptive effect

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 04.04.2024

Version: 3.1

Date / Previous version: 05.03.2024

Previous version: 3.0

Product: **Kaurit® Glue 270**

(ID no. 30034914/SDS_GEN_DE/EN)

Date of print 21.10.2025

OEL 130 mg/m³ ; 100 ppm (TRGS 900 (DE))

Ceiling limit value/factor: 2

If the occupational exposure limit value (AGW) and the biological limit value (BGW) are complied with, there should be no risk of damage for the unborn child (see TRGS 900, Number 2.7)

Components with PNEC

50-00-0: Formaldehyde

freshwater: 0,132 mg/l

marine water: 0,132 mg/l

intermittent release: 0,49 mg/l

sediment (freshwater): 0,686 mg/l

sediment (marine water): 0,686 mg/l

soil: 0,059 mg/l

STP: 0,19 mg/l

air:

No PNEC value available.

67-56-1: methanol

freshwater:

No hazard identified.

marine water:

No hazard identified.

intermittent release:

No hazard identified.

STP:

No hazard identified.

sediment (freshwater):

No hazard identified.

sediment (marine water):

No hazard identified.

soil:

No hazard identified.

Components with DNEL

50-00-0: Formaldehyde

worker: Short-term exposure - systemic and local effects, Inhalation: 0,75 mg/m³, 0,6 ppm

worker: Long-term exposure - systemic and local effects, Inhalation: 0,375 mg/m³, 0,3 ppm

worker: Long-term exposure- systemic effects, dermal: 240 mg/kg

consumer: Long-term exposure- systemic effects, oral: 4,1 mg/kg

consumer: Long-term exposure- systemic effects, dermal: 102 mg/kg

consumer: Long-term exposure - local effects, dermal: 0,012 mg/cm²

consumer: Long-term exposure - systemic and local effects, Inhalation: 0,1 mg/m³

67-56-1: methanol

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 04.04.2024

Version: 3.1

Date / Previous version: 05.03.2024

Previous version: 3.0

Product: **Kaurit® Glue 270**

(ID no. 30034914/SDS_GEN_DE/EN)

Date of print 21.10.2025

worker: Long-term exposure- systemic effects, dermal: 20 mg/kg
worker: Short-term exposure - systemic effects, dermal: 20 mg/kg
worker: Long- and short-term exposure - local effects, dermal
No hazard identified.
worker: Long-term exposure- systemic effects, Inhalation: 130 mg/m³
worker: Short-term exposure - systemic effects, Inhalation: 130 mg/m³
worker: Long-term exposure - local effects, Inhalation: 130 mg/m³
worker: Short-term exposure - local effects, Inhalation: 130 mg/m³
consumer: Long-term exposure- systemic effects, oral: 4 mg/kg
consumer: Short-term exposure - systemic effects, oral: 4 mg/kg
consumer: Long-term exposure- systemic effects, dermal: 4 mg/kg
consumer: Short-term exposure - systemic effects, dermal: 4 mg/kg
consumer: Long- and short-term exposure - local effects, dermal
No hazard identified.
consumer: Long-term exposure- systemic effects, Inhalation: 26 mg/m³
consumer: Short-term exposure - systemic effects, Inhalation: 26 mg/m³
consumer: Long-term exposure - local effects, Inhalation: 26 mg/m³
consumer: Short-term exposure - local effects, Inhalation: 26 mg/m³

8.2. Exposure controls

Personal protective equipment

Respiratory protection:

Breathing protection if gases/vapours are formed. Gas filter for gases/vapours of inorganic compounds (e.g. EN 14387 Type B)

Hand protection:

Chemical resistant protective gloves (EN ISO 374-1)

Suitable materials also with prolonged, direct contact (Recommended: Protective index 6, corresponding > 480 minutes of permeation time according to EN ISO 374-1):

butyl rubber (butyl) - 0.7 mm coating thickness

nitrile rubber (NBR) - 0.4 mm coating thickness

Eye protection:

Safety glasses with side-shields (frame goggles) (e.g. EN 166)

Body protection:

Body protection must be chosen depending on activity and possible exposure, e.g. apron, protecting boots, chemical-protection suit (according to EN 14605 in case of splashes or EN ISO 13982 in case of dust).

General safety and hygiene measures

Handle in accordance with good industrial hygiene and safety practice. Do not inhale vapours or dust.

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 04.04.2024

Version: 3.1

Date / Previous version: 05.03.2024

Previous version: 3.0

Product: **Kaurit® Glue 270**

(ID no. 30034914/SDS_GEN_DE/EN)

Date of print 21.10.2025

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

State of matter:	liquid	
Form:	liquid	
Colour:	colourless	
Odour:	faint odour	
Odour threshold:	No data available.	
Melting point:	0 °C	
	(approx. 1.013 hPa)	
boiling temperature:	approx. 100 °C	
Flash point:	No flash point - Measurement made up to the boiling point.	
Auto-ignition temperature:	440 °C	(DIN 51794)
Thermal decomposition:	No decomposition if correctly stored and handled.	
pH value:	7,5 - 9	(DIN ISO 976)
	(20 °C)	
Viscosity, kinematic:	No data available.	
Viscosity, dynamic:	5.000 - 8.000 mPa.s	(DIN EN ISO 3219, Annex B)
	(20 °C)	
Solubility in water:	miscible	
Partitioning coefficient n-octanol/water (log Kow):	< 1,0	
	The statements are based on the properties of the individual components.	
Vapour pressure:	approx. 23 mbar	
	(20 °C)	
Relative density:	No data available.	
Density:	1,31 - 1,33 g/cm ³	(ISO 2811-3)
	(20 °C)	
Relative vapour density (air):	No data available.	

Particle characteristics

Particle size distribution: The substance / product is marketed or used in a non solid or granular form. -

9.2. Other information

Information with regard to physical hazard classes

Explosives

Explosion hazard: not explosive

Oxidizing properties

Fire promoting properties: not fire-propagating

Other safety characteristics

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 04.04.2024

Version: 3.1

Date / Previous version: 05.03.2024

Previous version: 3.0

Product: **Kaurit® Glue 270**

(ID no. 30034914/SDS_GEN_DE/EN)

Date of print 21.10.2025

Bulk density:

No data available.

Other Information:

none

Evaporation rate:

Value can be approximated from
Henry's Law Constant or vapor
pressure.

SECTION 10: Stability and Reactivity

10.1. Reactivity

No hazardous reactions if stored and handled as prescribed/indicated.

10.2. Chemical stability

The product is chemically stable.

10.3. Possibility of hazardous reactions

During processing with acids, water and / or heat formaldehyde will be released, which may act as a sensitizer.

10.4. Conditions to avoid

> 30 °C

Avoid heat. Avoid freezing. See SDS section 7 - Handling and storage.

10.5. Incompatible materials

Substances to avoid:

Organic Peroxides, strong bases, strong acids, acid anhydrides

10.6. Hazardous decomposition products

Formaldehyde

SECTION 11: Toxicological Information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Assessment of acute toxicity:

Virtually nontoxic after a single ingestion. The inhalation of a highly enriched/saturated vapor-air-mixture represents an unlikely acute hazard.

Experimental/calculated data:

LD50 rat (oral): > 5.000 mg/kg

rat (by inhalation): 7 h (IRT)

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 04.04.2024

Version: 3.1

Date / Previous version: 05.03.2024

Previous version: 3.0

Product: **Kaurit® Glue 270**

(ID no. 30034914/SDS_GEN_DE/EN)

Date of print 21.10.2025

No mortality within the stated exposition time as shown in animal studies.

Irritation

Assessment of irritating effects:

Not irritating to the skin. Not irritating to the eyes.

Experimental/calculated data:

Skin corrosion/irritation

rabbit: non-irritant (Draize test)

Serious eye damage/irritation

rabbit: non-irritant

Serious eye damage/irritation

rabbit: non-irritant (Draize test)

Respiratory/Skin sensitization

Assessment of sensitization:

May cause sensitization by skin contact. May produce an allergic reaction. The product has not been tested. The statement has been derived from the properties of the individual components.

Information on: Formaldehyde

Assessment of sensitization:

Caused skin sensitization in animal studies. Caused sensitization in humans.

Germ cell mutagenicity

Assessment of mutagenicity:

Mutagenic properties can not be excluded on the basis of experimental data. The product has not been tested. The statement has been derived from the properties of the individual components.

Information on: Formaldehyde

Assessment of mutagenicity:

Reliable studies did not give evidence for systemic genotoxicity in experimental animals or in humans. Although positive in various in vitro studies, the substance does not induce local mutagenic effects in the absence of chronic irritation based on today's knowledge.

Carcinogenicity

Assessment of carcinogenicity:

The substance caused cancer in animal studies. The product has not been tested. The statement has been derived from the properties of the individual components.

Information on: Formaldehyde

Assessment of carcinogenicity:

After lifelong inhalation exposure to concentrations that were severely damaging to the nasal epithelium, nasal tumors were induced in rats; in other species these findings were not found or were considerably less pronounced. The International Agency for Research on Cancer (IARC) has classified formaldehyde as a Group 1 (known) human carcinogen based on epidemiological evidence linking formaldehyde exposure to occurrence of nasopharyngeal cancer and leukemia. No

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 04.04.2024

Version: 3.1

Date / Previous version: 05.03.2024

Previous version: 3.0

Product: **Kaurit® Glue 270**

(ID no. 30034914/SDS_GEN_DE/EN)

Date of print 21.10.2025

adverse health effects are anticipated if recommended personal protective equipment and industrial hygiene practices are used.

Reproductive toxicity

Assessment of reproduction toxicity:

No reproductive toxic effects reported.

Developmental toxicity

Assessment of teratogenicity:

Not a teratogen.

Specific target organ toxicity (single exposure)

Assessment of STOT single:

Based on the available information there is no specific target organ toxicity to be expected after a single exposure.

Repeated dose toxicity and Specific target organ toxicity (repeated exposure)

Information on: Formaldehyde

Assessment of repeated dose toxicity:

After repeated exposure the prominent effect is local irritation.

Information on: methanol

Assessment of repeated dose toxicity:

The substance may cause blindness after repeated ingestion. The substance may cause blindness after repeated inhalation.

Aspiration hazard

No aspiration hazard expected.

Interactive effects

No data available.

11.2. Information on other hazards

Endocrine disrupting properties

Product does not contain a substance above legal limits included in the list established in accordance with Article 59(1) of Regulation (EC) No 1907/2006 for having endocrine disrupting properties or is identified to have endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 04.04.2024

Version: 3.1

Date / Previous version: 05.03.2024

Previous version: 3.0

Product: **Kaurit® Glue 270**

(ID no. 30034914/SDS_GEN_DE/EN)

Date of print 21.10.2025

SECTION 12: Ecological Information

12.1. Toxicity

Assessment of aquatic toxicity:

There is a high probability that the product is not acutely harmful to aquatic organisms.

Toxicity to fish:

LC50 (48 h) > 500 mg/l, *Leuciscus idus* (static)

Nominal concentration.

Microorganisms/Effect on activated sludge:

activated sludge, industrial (DIN EN ISO 8192-OECD 209-88/302/EEC, P. C, aerobic)

Inhibition of degradation activity in activated sludge is not to be anticipated during correct introduction of low concentrations. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

12.2. Persistence and degradability

Elimination information:

No data available.

12.3. Bioaccumulative potential

Assessment bioaccumulation potential:

Based on its structural properties, the polymer is not biologically available. Accumulation in organisms is not to be expected.

12.4. Mobility in soil

Assessment transport between environmental compartments:

Volatility: The substance will not evaporate into the atmosphere from the water surface.

Information on: Formaldehyde

Assessment transport between environmental compartments:

Volatility: The substance will not evaporate into the atmosphere from the water surface.

Adsorption in soil: Adsorption to solid soil phase is not expected.

Information on: methanol

Assessment transport between environmental compartments:

Volatility: The substance will not evaporate into the atmosphere from the water surface.

Adsorption in soil: Adsorption to solid soil phase is not expected.

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 04.04.2024

Version: 3.1

Date / Previous version: 05.03.2024

Previous version: 3.0

Product: **Kaurit® Glue 270**

(ID no. 30034914/SDS_GEN_DE/EN)

Date of print 21.10.2025

12.5. Results of PBT and vPvB assessment

According to Annex XIII of Regulation (EC) No.1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH): The product does not fulfill the criteria for PBT (Persistent/bioaccumulative/toxic) and vPvB (very persistent/very bioaccumulative).

12.6. Endocrine disrupting properties

Product does not contain a substance above legal limits included in the list established in accordance with Article 59(1) of Regulation (EC) No 1907/2006 for having endocrine disrupting properties or is identified to have endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

12.7. Other adverse effects

The product does not contain substances that are listed in Regulation (EC) 1005/2009 on substances that deplete the ozone layer.

Additional information

Other ecotoxicological advice:

Do not release untreated into natural waters. Inhibition of degradation activity in activated sludge is not to be anticipated during correct introduction of low concentrations. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

SECTION 13: Disposal Considerations

13.1. Waste treatment methods

Incinerate in suitable incineration plant, observing local authority regulations.

SECTION 14: Transport Information

Land transport

ADR

	Not classified as a dangerous good under transport regulations
UN number or ID number:	Not applicable
UN proper shipping name:	Not applicable
Transport hazard class(es):	Not applicable
Packing group:	Not applicable
Environmental hazards:	Not applicable
Special precautions for user	None known

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 04.04.2024

Version: 3.1

Date / Previous version: 05.03.2024

Previous version: 3.0

Product: **Kaurit® Glue 270**

(ID no. 30034914/SDS_GEN_DE/EN)

Date of print 21.10.2025

RID

	Not classified as a dangerous good under transport regulations
UN number or ID number:	Not applicable
UN proper shipping name:	Not applicable
Transport hazard class(es):	Not applicable
Packing group:	Not applicable
Environmental hazards:	Not applicable
Special precautions for user	None known

Inland waterway transport

ADN

	Not classified as a dangerous good under transport regulations
UN number or ID number:	Not applicable
UN proper shipping name:	Not applicable
Transport hazard class(es):	Not applicable
Packing group:	Not applicable
Environmental hazards:	Not applicable
Special precautions for user:	None known

Transport in inland waterway vessel

Not evaluated

Sea transport

IMDG

	Not classified as a dangerous good under transport regulations
UN number or ID number:	Not applicable
UN proper shipping name:	Not applicable
Transport hazard class(es):	Not applicable
Packing group:	Not applicable
Environmental hazards:	Not applicable
Special precautions for user	None known

Air transport

IATA/ICAO

	Not classified as a dangerous good under transport regulations
UN number or ID number:	Not applicable

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 04.04.2024

Version: 3.1

Date / Previous version: 05.03.2024

Previous version: 3.0

Product: **Kaurit® Glue 270**

(ID no. 30034914/SDS_GEN_DE/EN)

Date of print 21.10.2025

UN proper shipping name:	Not applicable
Transport hazard class(es):	Not applicable
Packing group:	Not applicable
Environmental hazards:	Not applicable
Special precautions for user	None known

14.1. UN number or ID number

See corresponding entries for "UN number or ID number" for the respective regulations in the tables above.

14.2. UN proper shipping name

See corresponding entries for "UN proper shipping name" for the respective regulations in the tables above.

14.3. Transport hazard class(es)

See corresponding entries for "Transport hazard class(es)" for the respective regulations in the tables above.

14.4. Packing group

See corresponding entries for "Packing group" for the respective regulations in the tables above.

14.5. Environmental hazards

See corresponding entries for "Environmental hazards" for the respective regulations in the tables above.

14.6. Special precautions for user

See corresponding entries for "Special precautions for user" for the respective regulations in the tables above.

14.7. Maritime transport in bulk according to IMO instruments

Maritime transport in bulk is not intended.

SECTION 15: Regulatory Information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Prohibitions, Restrictions and Authorizations

Chemical Prohibition Ordinance (DE): Annex 2

Restriction Type: Restricted substance

Annex XVII of Regulation (EC) No 1907/2006: Number on List: 3, 28, 69, 72, 75, 77

Hazardous Incident Ordinance (Germany):

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 04.04.2024

Version: 3.1

Date / Previous version: 05.03.2024

Previous version: 3.0

Product: **Kaurit® Glue 270**

(ID no. 30034914/SDS_GEN_DE/EN)

Date of print 21.10.2025

Listed in above regulation: no

Directive 2012/18/EU - Control of Major Accident Hazards involving dangerous substances (EU):

Listed in above regulation: no

Classification according to 'TA-Luft' (Germany):

Formaldehyde

methanol

Water hazard class (§8/§10 AwSV (Self-classification of the mixture according to calculation method)): (1) Weakly water polluting.

Occupational Exposure Limit Values (TRGS 900)

15.2. Chemical Safety Assessment

Advice on product handling can be found in sections 7 and 8 of this safety data sheet.

SECTION 16: Other Information

Full text of the classifications, including the hazard classes and the hazard statements, if mentioned in section 2 or 3:

Skin Sens.	Skin sensitization
Muta.	Germ cell mutagenicity
Carc.	Carcinogenicity
Acute Tox.	Acute toxicity
Skin Corr.	Skin corrosion
Eye Dam.	Serious eye damage
Flam. Liq.	Flammable liquids
STOT SE	Specific target organ toxicity — single exposure
Eye Dam./Irrit.	Serious eye damage/eye irritation
Skin Corr./Irrit.	Skin corrosion/irritation
H317	May cause an allergic skin reaction.
H350	May cause cancer.
H341	Suspected of causing genetic defects.
H330	Fatal if inhaled.
H314	Causes severe skin burns and eye damage.
H301 + H311	Toxic if swallowed or in contact with skin.
H225	Highly flammable liquid and vapour.
H301 + H311 + H331	Toxic if swallowed, in contact with skin or if inhaled.
H370	Causes damage to organs (Central nervous system, Optic nerve).

Abbreviations

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road.
 ADN = The European Agreement concerning the International Carriage of Dangerous Goods by Inland waterways. ATE = Acute Toxicity Estimates. CAO = Cargo Aircraft Only. CAS = Chemical Abstract Service. CLP = Classification, Labelling and Packaging of substances and mixtures. DIN = German national organization for standardization. DNEL = Derived No Effect Level. EC50 = Effective

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 04.04.2024

Version: 3.1

Date / Previous version: 05.03.2024

Previous version: 3.0

Product: **Kaurit® Glue 270**

(ID no. 30034914/SDS_GEN_DE/EN)

Date of print 21.10.2025

concentration median for 50% of the population. EC = European Community. EN = European Standards. IARC = International Agency for Research on Cancer. IATA = International Air Transport Association. IBC-Code = Intermediate Bulk Container code. IMDG = International Maritime Dangerous Goods Code. ISO = International Organization for Standardization. STEL = Short-Term Exposure Limit. LC50 = Lethal concentration median for 50% of the population. LD50 = Lethal dose median for 50% of the population. TLV = Threshold Limit Value. MARPOL = The International Convention for the Prevention of Pollution from Ships. NEN = Dutch Norm. NOEC = No Observed Effect Concentration. OEL = Occupational Exposure Limit. OECD = Organization for Economic Cooperation and Development. PBT = Persistent, Bioaccumulative and Toxic. PNEC = Predicted No Effect Level. PPM = Parts per million. RID = The European Agreement concerning the International Carriage of Dangerous Goods by Rail. TWA = Time Weight Average. UN-number = UN number at transport. vPvB = very Persistent and very Bioaccumulative.

The data contained in this safety data sheet are based on our current knowledge and experience and describe the product only with regard to safety requirements. This safety data sheet is neither a Certificate of Analysis (CoA) nor technical data sheet and shall not be mistaken for a specification agreement. Identified uses in this safety data sheet do neither represent an agreement on the corresponding contractual quality of the substance/mixture nor a contractually designated use. It is the responsibility of the recipient of the product to ensure any proprietary rights and existing laws and legislation are observed.

Vertical lines in the left hand margin indicate an amendment from the previous version.