

# Safety data sheet

Page: 1/21

---

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 22.09.2025

Version: 9.0

Date / Previous version: 03.08.2023

Previous version: 8.0

Product: **Luprosil®**

(ID no. 30041113/SDS\_GEN\_IE/EN)

Date of print 22.10.2025

---

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

#### Luprosil®

Chemical name: propionic acid

CAS Number: 79-09-4

REACH registration number: 01-2119486971-24-0000

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses: feed additive(s)

For the detailed identified uses of the product see appendix of the safety data sheet.

### 1.3. Details of the supplier of the safety data sheet

Company:BASF SE  
67056 Ludwigshafen  
GERMANYContact address:BASF Ireland DAC  
Asgard House, 19-20 City Quay  
Dublin, D02 K744  
Ireland

---

Telephone: +353 21 451-7100

E-mail address: product-safety-uk-and-ireland@basf.com

### 1.4. Emergency telephone number

For products classified as hazardous in accordance with CLP:

National Poisons Information Centre, Beaumont Hospital, Dublin 9

Emergency medical information: 8am-10pm (seven days)

Tel.: 01 8092566

International emergency number:

Telephone: +49 180 2273-112

---

## SECTION 2: Hazards Identification

### 2.1. Classification of the substance or mixture

According to Regulation (EC) No 1272/2008 [CLP]

Flam. Liq. 3	H226 Flammable liquid and vapour.
Skin Corr. 1B	H314 Causes severe skin burns and eye damage.
Eye Dam. 1	H318 Causes serious eye damage.
STOT SE 3	H335 May cause respiratory irritation.

Specific Concentration Limits According to Regulation (EC) No 1272/2008 [CLP]

STOT SE 3, irr. to respiratory syst.:  $\geq 10$  %

Skin Corr./Irrit. 2: 10 - < 25 %

Eye Dam./Irrit. 2: 10 - < 25 %

Skin Corr./Irrit. 1B:  $\geq 25$  %

For the classifications not written out in full in this section the full text can be found in section 16.

### 2.2. Label elements

According to Regulation (EC) No 1272/2008 [CLP]

Pictogram:



Signal Word:

Danger

Hazard Statement:

H226	Flammable liquid and vapour.
H335	May cause respiratory irritation.
H314	Causes severe skin burns and eye damage.

Precautionary Statements (Prevention):

P280	Wear protective gloves, protective clothing and eye protection or face protection.
P271	Use only outdoors or in a well-ventilated area.

Precautionary Statements (Response):

P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER or physician.

Precautionary Statements (Storage):

P233	Keep container tightly closed.
------	--------------------------------

Precautionary Statements (Disposal):

P501	Dispose of contents and container to hazardous or special waste collection point.
------	---

Hazard determining component(s) for labelling: propionic acid ... %

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 22.09.2025

Version: 9.0

Date / Previous version: 03.08.2023

Previous version: 8.0

Product: **Luprosil®**

(ID no. 30041113/SDS\_GEN\_IE/EN)

Date of print 22.10.2025

## 2.3. Other hazards

According to Regulation (EC) No 1272/2008 [CLP]

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture. Product does not contain a substance above legal limits included in the list established in accordance with Article 59(1) of Regulation (EC) No 1907/2006 for having endocrine disrupting properties or is identified to have endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605. The product does not fulfill the criteria for PBT (Persistent/bioaccumulative/toxic) and vPvB (very persistent/very bioaccumulative).

## SECTION 3: Composition/Information on Ingredients

### 3.1. Substances

Chemical nature

carboxylic acid

Regulatory relevant ingredients

propionic acid ... %

Content (W/W):  $\geq 99.5\%$  -  $\leq 100\%$

CAS Number: 79-09-4

EC-Number: 201-176-3

INDEX-Number: 607-089-00-0

Substance with EU occupational exposure limit

Flam. Liq. 3

Skin Corr. 1B

Eye Dam. 1

STOT SE 3 (irr. to respiratory syst.)

H226, H335, H314

Specific concentration limit:

Eye Dam./Irrit. 2:  $10 - < 25\%$

Skin Corr./Irrit. 1B:  $\geq 25\%$

Skin Corr./Irrit. 2:  $10 - < 25\%$

STOT SE 3, irr. to respiratory syst.:  $\geq 10\%$

acetic acid ... %

Content (W/W):  $\geq 0\%$  -  $\leq 0.2\%$

CAS Number: 64-19-7

EC-Number: 200-580-7

INDEX-Number: 607-002-00-6

Substance with EU occupational exposure limit

Flam. Liq. 3

Skin Corr. 1A

Eye Dam. 1

H226, H314

Specific concentration limit:

Eye Irrit. 2:  $10 - < 25\%$

Skin Irrit. 2:  $10 - < 25\%$

Skin Corr. 1B:  $25 - < 90\%$

Skin Corr. 1A:  $\geq 90\%$

For the classifications not written out in full in this section, including the hazard classes and the hazard statements, the full text is listed in section 16.

### 3.2. Mixtures

Not applicable

---

## SECTION 4: First-Aid Measures

### 4.1. Description of first aid measures

First aid personnel should pay attention to their own safety. If the patient is likely to become unconscious, place and transport in stable sideways position (recovery position). Immediately remove contaminated clothing.

If inhaled:

Immediately administer a corticosteroid from a controlled/metered dose inhaler. Keep patient calm, remove to fresh air, seek medical attention.

On skin contact:

Immediately wash thoroughly with plenty of water, apply sterile dressings, consult a skin specialist.

On contact with eyes:

Immediately wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.

On ingestion:

Immediately rinse mouth and then drink 200-300 ml of water, seek medical attention.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms: Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treatment: Treat according to symptoms (decontamination, vital functions), no known specific antidote.

---

## SECTION 5: Fire-Fighting Measures

### 5.1. Extinguishing media

Suitable extinguishing media:

water spray, dry powder, foam, carbon dioxide

### 5.2. Special hazards arising from the substance or mixture

Endangering substances: carbon oxides, nitrogen oxides

Advice: The substances/groups of substances mentioned can be released in case of fire.

### 5.3. Advice for fire-fighters

Special protective equipment:

Wear self-contained breathing apparatus and chemical-protective clothing.

Further information:

Collect contaminated extinguishing water separately, do not allow to reach sewage or effluent systems.

---

## SECTION 6: Accidental Release Measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Personal protection: wear a tightly closed chemical protection suit and a self-contained breathing apparatus. Wear acid-resistant boots.

### 6.2. Environmental precautions

Do not empty into drains.

### 6.3. Methods and material for containment and cleaning up

For large amounts: Pump off product.

For residues: Pick up with suitable absorbent material (e.g. sand, sawdust, general-purpose binder, kieselguhr). Dispose of absorbed material in accordance with regulations.

### 6.4. Reference to other sections

Information regarding exposure controls/personal protection and disposal considerations can be found in section 8 and 13.

---

## SECTION 7: Handling and Storage

### 7.1. Precautions for safe handling

Ensure thorough ventilation of stores and work areas. When using do not eat, drink or smoke. Hands and/or face should be washed before breaks and at the end of the shift. Change clothes immediately after contamination.

Protection against fire and explosion:

Prevent electrostatic charge - sources of ignition should be kept well clear - fire extinguishers should be kept handy.

### 7.2. Conditions for safe storage, including any incompatibilities

Segregate from alkalies and alkalizing substances.

Further information on storage conditions: Keep container tightly closed in a cool, well-ventilated place.

### 7.3. Specific end use(s)

See exposure scenario(s) in the attachment to this safety data sheet.

---

## SECTION 8: Exposure Controls/Personal Protection

### 8.1. Control parameters

Components with occupational exposure limits

64-19-7: acetic acid ... %

TWA value 25 mg/m<sup>3</sup> ; 10 ppm (OEL (EU))

indicative

TWA value 25 mg/m<sup>3</sup> ; 10 ppm (OEL (IE))

Indicative OELV

STEL value 50 mg/m<sup>3</sup> ; 20 ppm (OEL (IE))

Ceiling limit value/factor: 15 min

Indicative OELV

STEL value 50 mg/m<sup>3</sup> ; 20 ppm (EU SCOEL)

Ceiling limit value/factor: 15 min

TWA value 25 mg/m<sup>3</sup> ; 10 ppm (EU SCOEL)

Ceiling limit value/factor: 8HR

79-09-4: propionic acid ... %

TWA value 31 mg/m<sup>3</sup> ; 10 ppm (OEL (IE))

Indicative OELV

STEL value 62 mg/m<sup>3</sup> ; 20 ppm (OEL (EU))

indicative

TWA value 31 mg/m<sup>3</sup> ; 10 ppm (OEL (EU))

indicative

STEL value 62 mg/m<sup>3</sup> ; 20 ppm (OEL (IE))

Ceiling limit value/factor: 15 min

Indicative OELV

STEL value 62 mg/m<sup>3</sup> ; 20 ppm (EU SCOEL)

Ceiling limit value/factor: 15 min

TWA value 31 mg/m<sup>3</sup> ; 10 ppm (EU SCOEL)

Ceiling limit value/factor: 8HR

### PNEC

freshwater: 0.5 mg/l

marine water: 0.05 mg/l

intermittent release: 5 mg/l

sediment (freshwater): 1.86 mg/kg

sediment (marine water): 0.186 mg/kg

soil: 0.1258 mg/kg

STP: 5 mg/l

### DNEL

worker:

Long-term exposure- systemic effects, Inhalation: 73 mg/m<sup>3</sup>

---

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 22.09.2025

Version: 9.0

Date / Previous version: 03.08.2023

Previous version: 8.0

Product: **Luprosil®**

(ID no. 30041113/SDS\_GEN\_IE/EN)

Date of print 22.10.2025

---

worker:

Long-term exposure - local effects, Inhalation: 31 mg/m<sup>3</sup>

worker:

Short-term exposure - local effects, Inhalation: 62 mg/m<sup>3</sup>

consumer:

Long-term exposure- systemic effects, Inhalation: 18.3 mg/m<sup>3</sup>

worker:

Long-term exposure- systemic effects, dermal: 20.9 mg/kg

consumer:

Long-term exposure - local effects, Inhalation: 3.7 mg/m<sup>3</sup>

consumer:

Short-term exposure - local effects, Inhalation: 30.8 mg/m<sup>3</sup>

consumer:

Long-term exposure- systemic effects, dermal: 10.5 mg/kg

consumer:

Long-term exposure- systemic effects, oral: 10.5 mg/kg

## 8.2. Exposure controls

### Personal protective equipment

Respiratory protection:

Wear respiratory protection if ventilation is inadequate. Gas filter for gases/vapours of organic compounds (boiling point &gt;65 °C, e. g. EN 14387 Type A)

Consider the risk management measures as outlined in the exposure scenario.

Hand protection:

Chemical resistant protective gloves (EN ISO 374-1)

Suitable materials also with prolonged, direct contact (Recommended: Protective index 6, corresponding &gt; 480 minutes of permeation time according to EN ISO 374-1):

butyl rubber (butyl) - 0.7 mm coating thickness

Suitable materials for short-term contact (recommended: At least protective index 2, corresponding &gt; 30 minutes of permeation time according to EN ISO 374-1)

nitrile rubber (NBR) - 0.4 mm coating thickness

chloroprene rubber (CR) - 0.5 mm coating thickness

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 22.09.2025

Version: 9.0

Date / Previous version: 03.08.2023

Previous version: 8.0

Product: **Luprosil®**

(ID no. 30041113/SDS\_GEN\_IE/EN)

Date of print 22.10.2025

Eye protection:

Tightly fitting safety goggles (cage goggles) (e.g. EN 166) and face shield.

Body protection:

acid-proof chemical protection suit (f.e. according to EN 14605)

General safety and hygiene measures

Avoid contact with the skin, eyes and clothing. Avoid inhalation of vapour. Avoid contact with skin and eyes. Take off immediately all contaminated clothing.

**SECTION 9: Physical and Chemical Properties****9.1. Information on basic physical and chemical properties**

State of matter:	liquid	
Form:	liquid	
Colour:	colourless	
Odour:	pungent	
Odour threshold:	not determined	
Melting point:	-20 °C	
Boiling point:	140.7 - 141.6 °C	
Flammability:	Flammable liquid and vapour.	(derived from flash point)
Lower explosion limit:	2.1 %(V) (46.9 °C) The lower explosion point of the substance/mixture has been determined. The explosion point describes the temperature of a flammable liquid at which the concentration of the saturated vapour mixed with air equals the lower explosion limit.	
Upper explosion limit:	12.0 %(V)	
Flash point:	53 °C	(ISO 13736, closed cup)
Auto-ignition temperature:	485 °C	(DIN 51794)
Thermal decomposition:	not determined	
SADT:	Not a substance/mixture liable to self-decomposition according to GHS.	
pH value:	2.5 (100 g/l, 20 °C) Literature data.	
Viscosity, dynamic:	1.102 mPa.s (20 °C) Literature data.	
Solubility in water:	miscible (20 °C)	
Partitioning coefficient n-octanol/water (log Kow):	0.25 (25 °C) 0.33	(Calculation Hansch/Leo)



BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 22.09.2025

Version: 9.0

Date / Previous version: 03.08.2023

Previous version: 8.0

Product: **Luprosil®**

(ID no. 30041113/SDS\_GEN\_IE/EN)

Date of print 22.10.2025

Vapour pressure: 5 mbar  
(20 °C)  
approx. 23 hPa  
(50 °C)

Density: 0.993 g/cm<sup>3</sup>  
(20 °C)  
Literature data.  
0.957 g/cm<sup>3</sup>  
(55 °C)  
Literature data.  
0.9990 g/cm<sup>3</sup>  
(15 °C)  
0.9610 g/cm<sup>3</sup>  
(50 °C)

Relative vapour density (air): > 1 (estimated)  
(20 °C)  
Heavier than air.

## 9.2. Other information

### Information with regard to physical hazard classes

#### Explosives

Impact sensitivity: Based on the chemical structure there is no shock-sensitivity.

#### Oxidizing properties

Fire promoting properties: Based on its structural properties the product is not classified as oxidizing.

#### Flammable liquids

Sustained combustibility: not determined

#### Pyrophoric properties

Self-ignition temperature: Test type: Spontaneous self-ignition at room-temperature.

Based on its structural properties the product is not classified as self-igniting.

#### Self-heating substances and mixtures

Self heating ability: not applicable, the product is a liquid

#### Substances and mixtures, which emit flammable gases in contact with water

Formation of flammable gases: Forms no flammable gases in the presence of water.

#### Corrosion to metals

Corrosive effects to metal are not anticipated. - In the presence of water or moisture metal corrosion cannot be excluded.

### Other safety characteristics

---

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 22.09.2025

Version: 9.0

Date / Previous version: 03.08.2023

Previous version: 8.0

Product: **Luprosil®**

(ID no. 30041113/SDS\_GEN\_IE/EN)

Date of print 22.10.2025

---

pK <sub>A</sub> :	4.87 (20 °C)	
Adsorption/water - soil:	KOC: 1.201; log KOC: 0.08 The data refer to the uncharged form of the substance. Under environmental conditions, the substance will almost completely be in its charged form.	(calculated)
Surface tension:	Based on chemical structure, surface activity is not to be expected.	
Molar mass:	74.08 g/mol	
Conductance:	< 0.1 S, 20 °C	
SAPT-Temperature:	Study scientifically not justified.	
Evaporation rate:	Value can be approximated from Henry's Law Constant or vapor pressure.	

---

## SECTION 10: Stability and Reactivity

### 10.1. Reactivity

Corrosion to metals:	Corrosive effects to metal are not anticipated. In the presence of water or moisture metal corrosion cannot be excluded.	
Formation of flammable gases:	Remarks:	Forms no flammable gases in the presence of water.

### 10.2. Chemical stability

The product is chemically stable.

### 10.3. Possibility of hazardous reactions

Reacts with strong alkalies. Exothermic reaction.

### 10.4. Conditions to avoid

No conditions to avoid anticipated.

### 10.5. Incompatible materials

Substances to avoid:  
bases, non-coated metals, base metals

### 10.6. Hazardous decomposition products

No hazardous decomposition products known.

---

## SECTION 11: Toxicological Information

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

##### Assessment of acute toxicity:

Of low toxicity after single ingestion. Virtually nontoxic by inhalation. Of low toxicity after short-term skin contact. Inhalation-risk test (IRT): No mortality within 8 hours as shown in animal studies. The inhalation of a highly saturated vapor-air mixture represents no acute hazard.

##### Experimental/calculated data:

LD50 rat (oral): 3,455 mg/kg (similar to OECD guideline 401)

LC50 rat (by inhalation): > 19.7 mg/l 1 h (OECD Guideline 403)

The vapour was tested.

LC0 rat (by inhalation): 24.4 mg/l 8 h (IRT)

Literature data. No mortality within the stated exposition time as shown in animal studies. The vapour was tested.

LD50 rat (dermal): 3,235 mg/kg (similar to OECD guideline 402)

#### Irritation

##### Assessment of irritating effects:

Corrosive! Damages skin and eyes.

##### Experimental/calculated data:

##### Skin corrosion/irritation

rabbit: Corrosive. (BASF-Test)

##### Serious eye damage/irritation

rabbit: irreversible damage (Draize test)

Literature data.

#### Respiratory/Skin sensitization

##### Assessment of sensitization:

Skin sensitizing effects were not observed in animal studies.

##### Experimental/calculated data:

Guinea pig maximization test guinea pig: Non-sensitizing. (similar to OECD guideline 406)

The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

#### Germ cell mutagenicity

##### Assessment of mutagenicity:

The substance was not mutagenic in bacteria. The substance was not mutagenic in mammalian cell culture. The substance was not mutagenic in studies with mammals. The product has not been fully tested. The statements have been derived in parts from products of a similar structure or composition.

#### Carcinogenicity

##### Assessment of carcinogenicity:

---

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 22.09.2025

Version: 9.0

Date / Previous version: 03.08.2023

Previous version: 8.0

Product: **Luprosil®**

(ID no. 30041113/SDS\_GEN\_IE/EN)

Date of print 22.10.2025

---

In long-term animal studies in which the substance was given in high concentrations by feed, a carcinogenic effect was not observed.

#### Reproductive toxicity

Assessment of reproduction toxicity:

No data available. Study scientifically not justified.

#### Developmental toxicity

Assessment of teratogenicity:

No indications of a developmental toxic / teratogenic effect were seen in animal studies. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

#### Specific target organ toxicity (single exposure)

Assessment of STOT single:

Causes temporary irritation of the respiratory tract.

#### Repeated dose toxicity and Specific target organ toxicity (repeated exposure)

Assessment of repeated dose toxicity:

No substance-specific organotoxicity was observed after repeated administration to animals. After repeated administration the prominent effect is the induction of corrosion.

#### Aspiration hazard

No aspiration hazard expected.

#### Interactive effects

No data available.

## **11.2. Information on other hazards**

#### Endocrine disrupting properties

The substance is not identified to have endocrine disrupting properties according to Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 nor is included in the Candidate List of substances of very high concern according to EU REACH Article 59 for having endocrine disrupting properties.

---

## **SECTION 12: Ecological Information**

### **12.1. Toxicity**

Assessment of aquatic toxicity:

There is a high probability that the product is not acutely harmful to aquatic organisms. The inhibition of the degradation activity of activated sludge is not anticipated when introduced to biological treatment plants in appropriate low concentrations.

---

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 22.09.2025

Version: 9.0

Date / Previous version: 03.08.2023

Previous version: 8.0

Product: **Luprosil®**

(ID no. 30041113/SDS\_GEN\_IE/EN)

Date of print 22.10.2025

---

**Toxicity to fish:**

LC50 (96 h) > 10,000 mg/l, *Leuciscus idus* (DIN 38412 Part 15, static)

The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

**Aquatic invertebrates:**

EC50 (48 h) > 500 mg/l, *Daphnia magna* (Directive 84/449/EEC, C.2, static)

The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

**Aquatic plants:**

EC50 (72 h) > 500 mg/l (biomass), *Scenedesmus subspicatus* (OECD Guideline 201, static)

The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

**Microorganisms/Effect on activated sludge:**

EC20 (30 min) 500 - 1,040 mg/l, activated sludge, domestic (DIN EN ISO 8192, aquatic)

The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

**Chronic toxicity to fish:**

Study scientifically not justified.

**Chronic toxicity to aquatic invertebrates:**

Study scientifically not justified.

**Assessment of terrestrial toxicity:**

Toxic effects have been observed in studies with terrestrial plants.

**Soil living organisms:**

No data available.

**Terrestrial plants:**

EC50 (3 d) 125.8 mg/l 188.7 mg/kg, *Lactuca sativa*

Literature data.

**Other terrestrial non-mammals:**

No data available.

## **12.2. Persistence and degradability**

**Assessment biodegradation and elimination (H<sub>2</sub>O):**

Readily biodegradable (according to OECD criteria). Literature data.

**Elimination information:**

approx. 74 % BOD of the ThOD (30 d) (other) (aerobic, activated sludge, domestic)

**Assessment of stability in water:**

According to structural properties, hydrolysis is not expected/probable.

Information on Stability in Water (Hydrolysis):

The product has not been tested. The statement has been derived from the structure of the product.

### 12.3. Bioaccumulative potential

Assessment bioaccumulation potential:

Significant accumulation in organisms is not to be expected.

Bioaccumulation potential:

Accumulation in organisms is not to be expected.

### 12.4. Mobility in soil

Assessment transport between environmental compartments:

Volatility: The substance will not evaporate into the atmosphere from the water surface.

Adsorption in soil: Adsorption to solid soil phase is not expected.

### 12.5. Results of PBT and vPvB assessment

According to Annex XIII of Regulation (EC) No.1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH): The product does not fulfill the criteria for PBT (Persistent/bioaccumulative/toxic) and vPvB (very persistent/very bioaccumulative). Self classification

### 12.6. Endocrine disrupting properties

The substance is not identified to have endocrine disrupting properties according to Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 nor is included in the Candidate List of substances of very high concern according to EU REACH Article 59 for having endocrine disrupting properties.

### 12.7. Other adverse effects

#### Results of PMT and vPvM assessment

Substance is not included in the list established in accordance with Article 59(1) of Regulation (EC) No 1907/2006 for having PMT/vPvM properties.

#### Additional information

Sum parameter

Chemical oxygen demand (COD): 1,520 mg/g

---

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 22.09.2025

Version: 9.0

Date / Previous version: 03.08.2023

Previous version: 8.0

Product: **Luprosil®**

(ID no. 30041113/SDS\_GEN\_IE/EN)

Date of print 22.10.2025

---

Biochemical oxygen demand (BOD) Incubation period5 d: 1,300 mg/g

---

## SECTION 13: Disposal Considerations

### 13.1. Waste treatment methods

Incinerate in suitable incineration plant, observing local authority regulations.

Contaminated packaging:

Contaminated packaging should be emptied as far as possible; then it can be passed on for recycling after being thoroughly cleaned.

---

## SECTION 14: Transport Information

### Land transport

ADR

UN number or ID number: UN3463

UN proper shipping name: PROPIONIC ACID

Transport hazard class(es): 8, 3

Packing group: II

Environmental hazards: no

Special precautions for user: Tunnel code: D/E

RID

UN number or ID number: UN3463

UN proper shipping name: PROPIONIC ACID

Transport hazard class(es): 8, 3

Packing group: II

Environmental hazards: no

Special precautions for user: None known

### Inland waterway transport

ADN

UN number or ID number: UN3463

UN proper shipping name: PROPIONIC ACID

Transport hazard class(es): 8, 3

Packing group: II

Environmental hazards: no

Special precautions for user: None known

---

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 22.09.2025

Version: 9.0

Date / Previous version: 03.08.2023

Previous version: 8.0

Product: **Luprosil®**

(ID no. 30041113/SDS\_GEN\_IE/EN)

Date of print 22.10.2025

---

Transport in inland waterway vessel

UN number or ID number: UN3463

UN proper shipping name: PROPIONIC ACID

Transport hazard class(es): 8, 3, N3

Packing group: II

Environmental hazards: yes

Type of inland waterway

vessel: N

Cargo tank design: 3

Cargo tank type: 3

**Sea transport**

## IMDG

UN number or ID number: UN 3463

UN proper shipping name: PROPIONIC ACID

Transport hazard class(es): 8, 3

Packing group: II

Environmental hazards: no

Marine pollutant: NO

Special precautions for user: EmS: F-E; S-C

**Air transport**

## IATA/ICAO

UN number or ID number: UN 3463

UN proper shipping name: PROPIONIC ACID

Transport hazard class(es): 8, 3

Packing group: II

Environmental hazards: No Mark as dangerous for the environment is needed

Special precautions for user: None known

**14.1. UN number or ID number**

See corresponding entries for "UN number or ID number" for the respective regulations in the tables above.

**14.2. UN proper shipping name**

See corresponding entries for "UN proper shipping name" for the respective regulations in the tables above.



---

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 22.09.2025

Version: 9.0

Date / Previous version: 03.08.2023

Previous version: 8.0

Product: **Luprosil®**

(ID no. 30041113/SDS\_GEN\_IE/EN)

Date of print 22.10.2025

---

**14.3. Transport hazard class(es)**

See corresponding entries for "Transport hazard class(es)" for the respective regulations in the tables above.

**14.4. Packing group**

See corresponding entries for "Packing group" for the respective regulations in the tables above.

**14.5. Environmental hazards**

See corresponding entries for "Environmental hazards" for the respective regulations in the tables above.

**14.6. Special precautions for user**

See corresponding entries for "Special precautions for user" for the respective regulations in the tables above.

**14.7. Maritime transport in bulk according to IMO instruments**

Regulation: IBC-Code

Product name: Propionic acid

Pollution category: Y

Ship Type: 3

---

**SECTION 15: Regulatory Information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**Prohibitions, Restrictions and Authorizations

Annex XVII of Regulation (EC) No 1907/2006: Number on List: 3, 40, 75

Directive 2012/18/EU - Control of Major Accident Hazards involving dangerous substances (EU):

List entry in regulation: P5c

Classification applies for standard conditions of temperature and pressure.

If other regulatory information applies that is not already provided elsewhere in this safety data sheet, then it is described in this subsection.

**15.2. Chemical Safety Assessment**

Chemical Safety Assessment performed

---

**SECTION 16: Other Information**

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 22.09.2025

Version: 9.0

Date / Previous version: 03.08.2023

Previous version: 8.0

Product: **Luprosil®**

(ID no. 30041113/SDS\_GEN\_IE/EN)

Date of print 22.10.2025

#### Assessment of the hazard classes according to UN GHS criteria (most recent version)

Skin Corr. 1B  
Acute Tox. 5 (oral)  
Flam. Liq. 3  
Eye Dam. 1  
Acute Tox. 5 (dermal)  
STOT SE 3 (irritating to respiratory system)

#### Full text of the classifications, including the hazard classes and the hazard statements, if mentioned in section 2 or 3:

Flam. Liq.	Flammable liquids
Skin Corr.	Skin corrosion
Eye Dam.	Serious eye damage
STOT SE	Specific target organ toxicity — single exposure
Skin Corr./Irrit.	Skin corrosion/irritation
Eye Dam./Irrit.	Serious eye damage/eye irritation
Eye Irrit.	Eye irritation
Skin Irrit.	Skin irritation
H226	Flammable liquid and vapour.
H335	May cause respiratory irritation.
H314	Causes severe skin burns and eye damage.

#### Abbreviations

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road.  
ADN = The European Agreement concerning the International Carriage of Dangerous Goods by Inland waterways. ATE = Acute Toxicity Estimates. CAO = Cargo Aircraft Only. CAS = Chemical Abstract Service. CLP = Classification, Labelling and Packaging of substances and mixtures. DIN = German national organization for standardization. DNEL = Derived No Effect Level. EC50 = Effective concentration median for 50% of the population. EC = European Community. EN = European Standards. IARC = International Agency for Research on Cancer. IATA = International Air Transport Association. IBC-Code = Intermediate Bulk Container code. IMDG = International Maritime Dangerous Goods Code. ISO = International Organization for Standardization. STEL = Short-Term Exposure Limit. LC50 = Lethal concentration median for 50% of the population. LD50 = Lethal dose median for 50% of the population. TLV = Threshold Limit Value. MARPOL = The International Convention for the Prevention of Pollution from Ships. NEN = Dutch Norm. NOEC = No Observed Effect Concentration. OEL = Occupational Exposure Limit. OECD = Organization for Economic Cooperation and Development. PBT = Persistent, Bioaccumulative and Toxic. PNEC = Predicted No Effect Level. PPM = Parts per million. RID = The European Agreement concerning the International Carriage of Dangerous Goods by Rail. TWA = Time Weight Average. UN-number = UN number at transport. vPvB = very Persistent and very Bioaccumulative.

The data contained in this safety data sheet are based on our current knowledge and experience and describe the product only with regard to safety requirements. This safety data sheet is neither a Certificate of Analysis (CoA) nor technical data sheet and shall not be mistaken for a specification agreement. Identified uses in this safety data sheet do neither represent an agreement on the corresponding contractual quality of the substance/mixture nor a contractually designated use. It is the responsibility of the recipient of the product to ensure any proprietary rights and existing laws and legislation are observed.

Vertical lines in the left hand margin indicate an amendment from the previous version.

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 22.09.2025

Version: 9.0

Date / Previous version: 03.08.2023

Previous version: 8.0

Product: **Luprosil®**

(ID no. 30041113/SDS\_GEN\_IE/EN)

Date of print 22.10.2025

**Annex: Exposure Scenarios****Index****1. Animal nutrition**

PW; ERC8a, ERC8d; PROC5, PROC11

\*\*\*\*\*

**1. Short title of exposure scenario**

Animal nutrition

PW; ERC8a, ERC8d; PROC5, PROC11

**Control of exposure and risk management measures**

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	ERC8a: Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor) As no environmental hazard was identified no environmental-related exposure assessment and risk characterization was performed.
<b>Operational conditions</b>	
<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	ERC8d: Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor) As no environmental hazard was identified no environmental-related exposure assessment and risk characterization was performed.
<b>Operational conditions</b>	
<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC5: Mixing or blending in batch processes Use domain: professional
<b>Operational conditions</b>	
Concentration of the substance	propionic acid ... % Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	39 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
<b>Risk Management Measures</b>	

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 22.09.2025

Version: 9.0

Date / Previous version: 03.08.2023

Previous version: 8.0

Product: **Luprosil®**

(ID no. 30041113/SDS\_GEN\_IE/EN)

Date of print 22.10.2025

Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %
Use suitable chemically resistant gloves.	Effectiveness: 80 %
Wear suitable personal protective equipment., In case of potential exposure:, Wear suitable respiratory protection.	
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	2.7429 mg/kg bw/day
Risk Characterization Ratio (RCR)	0.131237
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	21.6067 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0.295982
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - local
Exposure estimate	21.6067 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0.696989
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC11: Non industrial spraying Use domain: professional
<b>Operational conditions</b>	
Concentration of the substance	propionic acid ... % Content: >= 0 % - <= 10 %
Physical state	liquid
Vapour pressure of the substance during use	39 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
<b>Risk Management Measures</b>	
Wear chemically resistant gloves in combination with 'basic' employee training.	Effectiveness: 90 %
Ensure doors and windows are opened (general ventilation). Regular inspection and maintenance of equipment and machines. Ensure that the task is being carried out outside the breathing zone of a worker	

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 22.09.2025

Version: 9.0

Date / Previous version: 03.08.2023

Previous version: 8.0

Product: **Luprosil®**

(ID no. 30041113/SDS\_GEN\_IE/EN)

Date of print 22.10.2025

(distance head-product greater than 1m). Ensure that the task is not carried out by more than one worker simultaneously.	
Wear suitable personal protective equipment., Reduce concentration to less than 10%	
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, worker, modified version, The concentration of the substance has been considered using a linear approach.
	Worker - dermal, long-term - systemic
Exposure estimate	1.0714 mg/kg bw/day
Risk Characterization Ratio (RCR)	0.051265
Assessment method	EASY TRA v4.1, Stoffenmanager v5.6
	Worker - inhalation, long-term - systemic
Exposure estimate	28.52 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0.390685
Assessment method	EASY TRA v4.1, Stoffenmanager v5.6
	Worker - inhalation, long-term - local
Exposure estimate	28.52 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0.92
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a> Please note that a modified version has been used (see exposure estimates)	

\*\*\*\*\*