

Revision date : 2024/05/07 Page: 1/12

Version: 3.0 (30034751/SDS_GEN_GT/EN)

1. Identification

Product identifier used on the label

METHOXYPROPYLACETATE

Recommended use of the chemical and restriction on use

Recommended use*: process chemical, solvent(s)

Recommended use*: process chemical

Unsuitable for use: Not intended for sale to or use by the general public.

Details of the supplier of the safety data sheet

Company:

BASF de Guatemala S.A. 15 calle 7-77 zona 10, Edificio Optima, oficina 203, 01010 Ciudad de Guatemala Guatemala

Telephone: 1 502 2445 -7600

Emergency telephone number

24 Hour Emergency Response Information

International emergency number: Telephone: +49 180 2273-112

Other means of identification

Molecular formula: CH3-O-CH2-CH(OOCCH3)-CH3

2. Hazards Identification

According to Regulation NOM-018-STPS-2015

Classification of the product

Flam. Liq. 3 Flammable liquids

STOT SE 3 (May cause Specific target organ toxicity — single exposure

^{*} The "Recommended use" identified for this product is provided solely to comply with a Federal requirement and is not part of the seller's published specification. The terms of this Safety Data Sheet (SDS) do not create or infer any warranty, express or implied, including by incorporation into or reference in the seller's sales agreement.

Revision date: 2024/05/07 Page: 2/12 Version: 3.0 (30034751/SDS GEN GT/EN)

drowsiness and dizziness.)

Label elements

Pictogram:





Signal Word: Warning

Hazard Statement:

H226 Flammable liquid and vapour.H336 May cause drowsiness or dizziness.

Precautionary Statements (Prevention):

P271 Use only outdoors or in a well-ventilated area.

P210 Keep away from heat, hot surfaces, sparks, open flames and other

ignition sources. No smoking.

P280 Wear protective gloves and eye protection or face protection.

P261 Avoid breathing mist or vapour or spray. P243 Take action to prevent static discharges.

P241 Use explosion-proof electrical, ventilating and lighting equipment.

P240 Ground and bond container and receiving equipment.

P242 Use non-sparking tools.

Precautionary Statements (Response):

P312 Call a POISON CENTER or physician if you feel unwell.

P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for

breathing.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing.

Rinse skin with water or shower.

P370 + P378 In case of fire: Use water spray, dry powder, foam or carbon dioxide for

extinction.

Precautionary Statements (Storage):

P233 Keep container tightly closed.

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

Precautionary Statements (Disposal):

P501 Dispose of contents/container in accordance with local regulations.

Hazards not otherwise classified

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture. See section 12 - Results of PBT and vPvB assessment.

3. Composition / Information on Ingredients

According to Regulation NOM-018-STPS-2015

Revision date: 2024/05/07 Page: 3/12

Version: 3.0 (30034751/SDS GEN GT/EN)

1-methoxy-2-propylacetate

CAS Number: 108-65-6

Content (W/W): >= 99.5 - < 100.0%

Synonym: 2-Methoxy-1-methylethyl acetate; 1-Methoxy-2-propyl acetate

2-methoxypropyl acetate

CAS Number: 70657-70-4 Content (W/W): >= 0.0 - < 0.3%Synonym: 2-Methoxypropyl acetate

4. First-Aid Measures

Description of first aid measures

General advice:

First aid personnel should pay attention to their own safety. If the patient is likely to become unconscious, place and transport in stable sideways position (recovery position). Immediately remove contaminated clothing.

If inhaled:

Keep patient calm, remove to fresh air, seek medical attention.

If on skin:

Wash thoroughly with soap and water

If in eyes:

Wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eve specialist.

If swallowed:

Immediately rinse mouth and then drink 200-300 ml of water, seek medical attention.

Most important symptoms and effects, both acute and delayed

Symptoms: Overexposure may cause:, nausea, vomiting, dizziness, diarrhea, abdominal cramps Hazards: Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11. (Further) symptoms and / or effects are not known so far

Indication of any immediate medical attention and special treatment needed

Note to physician

Treatment: Treat according to symptoms (decontamination, vital functions), no

known specific antidote.

5. Fire-Fighting Measures

Extinguishing media

Suitable extinguishing media:

dry powder, water spray, carbon dioxide, alcohol-resistant foam

Revision date: 2024/05/07 Page: 4/12 Version: 3.0 (30034751/SDS GEN GT/EN)

Unsuitable extinguishing media for safety reasons: water jet

Additional information:

Use extinguishing measures to suit surroundings.

Special hazards arising from the substance or mixture

Hazards during fire-fighting:

Flammable liquid Cool endangered containers with water-spray. See SDS section 7 - Handling and storage.

Advice for fire-fighters

Protective equipment for fire-fighting:

Wear a self-contained breathing apparatus. Special protective equipment for firefighters

Further information:

Evacuate area of all unnecessary personnel. Fight fire from maximum distance.

Extend fire extinguishing measures to the surroundings. Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

Impact Sensitivity:

Remarks: Based on the chemical structure there is no shock-sensitivity.

6. Accidental release measures

Further accidental release measures:

High risk of slipping due to leakage/spillage of product.

Release of substance/product can cause fire or explosion. Shut off or stop source of leak. Shut off or stop released substance/product under safe conditions.

Pack in tightly closed containers for disposal.

Personal precautions, protective equipment and emergency procedures

Handle in accordance with good industrial hygiene and safety practice.

Avoid all sources of ignition: heat, sparks, open flame. Use antistatic tools.

Environmental precautions

Discharge into the environment must be avoided.

Methods and material for containment and cleaning up

Pick up with suitable appliance and dispose of. Spills should be contained, solidified, and placed in suitable containers for disposal. Dispose of absorbed material in accordance with regulations.

7. Handling and Storage

Precautions for safe handling

Handle in accordance with good industrial hygiene and safety practice.

Revision date: 2024/05/07 Page: 5/12 Version: 3.0 (30034751/SDS GEN GT/EN)

Protection against fire and explosion:

Prevent electrostatic charge - sources of ignition should be kept well clear - fire extinguishers should be kept handy.

Conditions for safe storage, including any incompatibilities

Unsuitable materials for containers: Low density polyethylene (LDPE), Paper/Fibreboard

Further information on storage conditions: Containers should be stored tightly sealed in a dry place.

8. Exposure Controls/Personal Protection

No substance specific occupational exposure limits known.

Personal protective equipment

Respiratory protection:

Wear respiratory protection if ventilation is inadequate. Gas filter for gases/vapours of organic compounds (boiling point >65 °C, e. g. EN 14387 Type A)

Hand protection:

Chemical resistant protective gloves (EN ISO 374-1), Suitable materials also with prolonged, direct contact (Recommended: Protective index 6, corresponding > 480 minutes of permeation time according to EN ISO 374-1):, butyl rubber (butyl) - 0.7 mm coating thickness, Suitable materials for short-term contact (recommended: At least protective index 2, corresponding > 30 minutes of permeation time according to EN ISO 374-1), chloroprene rubber (CR) - 0.5 mm coating thickness, nitrile rubber (NBR) - 0.4 mm coating thickness, Manufacturer's directions for use should be observed because of great diversity of types., Supplementary note: The specifications are based on tests, literature data and information of glove manufacturers or are derived from similar substances by analogy. Due to many conditions (e.g. temperature) it must be considered, that the practical usage of a chemical-protective glove in practice may be much shorter than the permeation time determined through testing.

Eye protection:

Safety glasses with side-shields (frame goggles) (e.g. EN 166)

Body protection:

Body protection must be chosen depending on activity and possible exposure, e.g. apron, protecting boots, chemical-protection suit (according to EN 14605 in case of splashes or EN ISO 13982 in case of dust).

General safety and hygiene measures:

Avoid contact with eyes. Wearing of closed work clothing is required additionally to the stated personal protection equipment.

9. Physical and Chemical Properties

Form: liquid
Odour: ether-like
Odour threshold: not determined
Colour: colourless
pH value: not applicable

Revision date: 2024/05/07 Page: 6/12 Version: 3.0 (30034751/SDS_GEN_GT/EN)

Melting point: -66 °C (measured)

(1,013.25 hPa) Literature data.

Boiling point: 145.8 °C (OECD Guideline

(1,013.25 hPa) 103)

Extrapolated value

Flash point: 45.5 °C (ASTM D3278,

closed cup)

Flammability: Flammable. (derived from flash

point)

Lower explosion limit: For liquids not relevant for

classification and labelling. The lower explosion point may be 5 - 15 °C

below the flash point.

Upper explosion limit: For liquids not relevant for

classification and labelling.

Autoignition: 333 °C (DIN 51794)
Vapour pressure: 3.5997 hPa (OECD Guideline

(20 °C) 104)

dynamic

Density: 0.9677 g/cm3

(20 °C, 1,013 hPa) Literature data.

0.9286 g/cm3 (calculated)

(55°C)

Relative density: 0.967 (DIN 51757)

(20 °C, 1,013 hPa)

Vapour density: 4.55 (calculated)

(20 °C)

Heavier than air.

Partitioning coefficient n- 1.2 (OECD Guideline

octanol/water (log Pow): (20 °C) 117)

Self-ignition Based on its structural properties the temperature: product is not classified as self-

igniting

Thermal decomposition: No decomposition if stored and handled as

prescribed/indicated.

Viscosity, kinematic: 1.23 mm2/s (DIN 51562)

(20 °C)

Solubility in water: 198 g/l

(20 °C) soluble

solvent(s); ord

solvent(s): organic solvents,

Molar mass: 132.16 g/mol

Evaporation rate: Value can be approximated from

Henry's Law Constant or vapor

pressure.

10. Stability and Reactivity

Solubility (qualitative):

Reactivity

When heated can give off ignitable vapours.

Corrosion to metals:

No corrosive effect on metal.

Revision date: 2024/05/07 Page: 7/12 Version: 3.0 (30034751/SDS GEN GT/EN)

Oxidizing properties:

Based on its structural properties the product is not classified as oxidizing.

Formation of Remarks: Forms no flammable gases in the

flammable gases: presence of water.

Chemical stability

The product is stable if stored and handled as prescribed/indicated.

Possibility of hazardous reactions

Reacts with strong oxidizing agents.

Conditions to avoid

No special precautions other than good housekeeping of chemicals.

Incompatible materials

strong oxidizing agents

Hazardous decomposition products

Decomposition products:

Hazardous decomposition products: No hazardous decomposition products if stored and handled as prescribed/indicated.

Thermal decomposition:

No decomposition if stored and handled as prescribed/indicated.

11. Toxicological information

Primary routes of exposure

Routes of entry for solids and liquids are ingestion and inhalation, but may include eye or skin contact. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquefied gases.

Acute Toxicity/Effects

Acute toxicity

Assessment of acute toxicity: Virtually nontoxic after a single ingestion. Virtually nontoxic by inhalation. Virtually nontoxic after a single skin contact.

Oral

Type of value: LD50 Species: rat (male/female)

Value: > 5,000 mg/kg (similar to OECD guideline 401)

Inhalation

Type of value: LC50

Species: rat

Value: > 23.5 mg/l (similar to OECD guideline 403)

Exposure time: 6 h
The vapour was tested.
No mortality was observed.

Dermal

Revision date: 2024/05/07 Page: 8/12 Version: 3.0 (30034751/SDS GEN GT/EN)

Type of value: LD50

Species: rat

Value: > 2,000 mg/kg (similar to OECD guideline 402)

No mortality was observed.

Type of value: LD50 Species: rabbit

Value: > 5,000 mg/kg (similar to OECD guideline 402)

No mortality was observed.

Assessment other acute effects Assessment of STOT single:

Possible narcotic effects (drowsiness or dizziness).

Irritation / corrosion

Assessment of irritating effects: Not irritating to the skin. Not irritating to the eyes.

Skin

Species: rabbit Result: non-irritant

Method: similar to OECD guideline 404

Eye

Species: rabbit Result: non-irritant

Method: similar to OECD guideline 405

Sensitization

Assessment of sensitization: Skin sensitizing effects were not observed in animal studies.

Guinea pig maximization test

Species: guinea pig Result: Non-sensitizing. Method: OECD Guideline 406

Aspiration Hazard

No aspiration hazard expected.

Chronic Toxicity/Effects

Repeated dose toxicity

Assessment of repeated dose toxicity: Repeated dermal uptake of the substance did not cause substance-related effects. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition. The substance may cause damage to the olfactory epithelium after repeated inhalation. Repeated oral uptake of the substance did not cause substance-related effects.

Genetic toxicity

Assessment of mutagenicity: The substance was not mutagenic in bacteria. The substance was not mutagenic in mammalian cell culture. The substance was not genotoxic in mammalian cell culture. Genetic toxicity in vitro: similar to OECD guideline 471 Ames-test Salmonella typhimurium:with and without metabolic activation negative

similar to OECD guideline 473 Chromosomal Aberration Test CHO cells:with and without metabolic activation negative

Revision date: 2024/05/07 Page: 9/12 Version: 3.0 (30034751/SDS GEN GT/EN)

Carcinogenicity

Assessment of carcinogenicity: In long-term studies in rats and mice in which the substance was given by inhalation, a carcinogenic effect was not observed. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Reproductive toxicity

Assessment of reproduction toxicity: The results of animal studies gave no indication of a fertility impairing effect. The product has not been fully tested. The statements have been derived in parts from products of a similar structure or composition.

Teratogenicity

Assessment of teratogenicity: No indications of a developmental toxic / teratogenic effect were seen in animal studies.

12. Ecological Information

Toxicity

Aquatic toxicity

Assessment of aquatic toxicity:

There is a high probability that the product is not acutely harmful to aquatic organisms. The inhibition of the degradation activity of activated sludge is not anticipated when introduced to biological treatment plants in appropriate low concentrations.

Toxicity to fish

LC50 (96 h) 134 mg/l, Oncorhynchus mykiss (OECD Guideline 203, static)

The details of the toxic effect relate to the nominal concentration.

Aquatic invertebrates

EC50 (48 h) > 500 mg/l, Daphnia magna (Daphnia test acute, semistatic)

The details of the toxic effect relate to the nominal concentration.

Aquatic plants

EC50 (72 h) > 1,000 mg/l (growth rate), Selenastrum capricornutum (OECD Guideline 201, static) The details of the toxic effect relate to the nominal concentration.

Chronic toxicity to fish

No observed effect concentration (14 d) 47.5 mg/l, Oryzias latipes (OECD Guideline 204, Flow through.)

The details of the toxic effect relate to the nominal concentration.

Chronic toxicity to aquatic invertebrates

No observed effect concentration (21 d) >= 100 mg/l, Daphnia magna (OECD Guideline 202, part 2, semistatic)

Assessment of terrestrial toxicity

No data available concerning terrestrial toxicity.

Microorganisms/Effect on activated sludge

Toxicity to microorganisms

DIN EN ISO 8192-OECD 209-88/302/EEC,P. C aerobic activated sludge, industrial/EC10 (30 min): > 1,000 mg/l

The details of the toxic effect relate to the nominal concentration.

Revision date: 2024/05/07 Page: 10/12 Version: 3.0 (30034751/SDS GEN GT/EN)

Persistence and degradability

Assessment biodegradation and elimination (H2O)

Readily biodegradable (according to OECD criteria).

Elimination information

83 % BOD of the ThOD (28 d) (OECD 301F; ISO 9408; 92/69/EWG, C.4-D) (aerobic, activated sludge, domestic, non-adapted)

Assessment of stability in water

In contact with water the substance will hydrolyse slowly.

Information on Stability in Water (Hydrolysis)

 $t_{1/2} > 1$ a (25 °C, pH value 7), (OECD Guideline 111, pH 7)

Bioaccumulative potential

Assessment bioaccumulation potential

Because of the n-octanol/water distribution coefficient (log Pow) accumulation in organisms is not to be expected.

Bioaccumulation potential

No data available.

Mobility in soil

Assessment transport between environmental compartments

The substance will slowly evaporate into the atmosphere from the water surface.

Adsorption to solid soil phase is not expected.

Additional information

Adsorbable organically-bound halogen(AOX):

This product contains no organically-bound halogen.

13. Disposal considerations

Waste disposal of substance:

Dispose of in accordance with national, state and local regulations.

Container disposal:

WARNING: Empty containers may still contain hazardous residue. Uncleaned empties should be disposed of in the same manner as the contents.

14. Transport Information

Land transport

TDG

Hazard class: 3 Packing group: III

ID number: UN 1993

Revision date: 2024/05/07 Page: 11/12 Version: 3.0 (30034751/SDS_GEN_GT/EN)

Hazard label: 3

Proper shipping name: FLAMMABLE LIQUID, N.O.S. (contains 2-METHOXY-1-

METHYLETHYL ACETATE)

Sea transport

IMDG

Hazard class: 3 Packing group: III

ID number: UN 1993

Hazard label: 3 Marine pollutant: NO

Proper shipping name: FLAMMABLE LIQUID, N.O.S. (contains 2-METHOXY-1-

METHYLETHYL ACETATE)

Air transport

IATA/ICAO

Hazard class: 3
Packing group: III
ID number: UN 1993

ID number: U Hazard label: 3

Proper shipping name: FLAMMABLE LIQUID, N.O.S. (contains 2-METHOXY-1-

METHYLETHYL ACETATE)

15. Regulatory Information

Federal Regulations

Not applicable

NFPA Hazard codes:

Health: 1 Fire: 2 Reactivity: 0 Special:

HMIS III rating

Health: 2 Flammability: 2 Physical hazard: 0 1 2 0

Assessment of the hazard classes according to UN GHS criteria (most recent version):

Flam. Liq. 3 Flammable liquids

STOT SE 3 (May cause Specific target organ toxicity — single exposure

drowsiness and dizziness.)

16. Other Information

SDS Prepared by:

BASF NA Product Regulations SDS Prepared on: 2024/05/07

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our

Revision date: 2024/05/07 Page: 12/12 Version: 3.0 (30034751/SDS_GEN_GT/EN)

commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

This information is considered accurate but is not exhaustive and shall only be used as a guideline based on current knowledge of the chemical substance or mixture. Safety precautions suitable for the product must be applied.

END OF DATA SHEET