

Chimassorb® 81

Product Description

Chimassorb 81 is a solid UV absorber of the 2-hydroxy-benzophenone class.

Key Features & Benefits

- Low yellowing
- Good absorbance in the UV-B region
- Reduces failure of coatings resulting from exposure to sunlight including discoloration, cracking, and loss of adhesion

Chemical Structure

Methanone, 2-hydroxy-4-(octyloxy)-phenyl

Properties

Typical Properties

CAS No. 1843-05-6 Molecular weight g/mol 326.4

Appearance slightly yellow powder

Melting range °C 48 – 49

Solubility at 20 °C (g/100 g solution):

 acetone
 43

 ethanol
 3.5

 ethyl acetate
 44

 hexane
 12


 toluene
 > 50

 water
 < 0.01</td>

These typical values should not be interpreted as specifications.

Transmittance Spectrum

(in chloroform, cell thickness 1 cm)



Top line: 0.001% Chimassorb 81, corresponds to 0.25 % in a 40 μ m film Second Line: 0.002% Chimassorb 81, corresponds to 0.50 % in a 40 μ m film Third Line: 0.004% Chimassorb 81, corresponds to 1.00 % in a 40 μ m film 0.006% Chimassorb 81, corresponds to 1.50 % in a 40 μ m film

Applications

Processing

Chimassorb 81 significantly improves the resistance of clear coatings to failures upon exposure to sunlight such as discoloration, cracking, loss of gloss and loss of adhesion. Its performance in outdoor applications can be improved further by use in synergistic combination with a hindered amine light stabilizer (HALS) such as Tinuvin® 292, Tinuvin 249 or Tinuvin 123.

The use of Chimassorb 81 should be reserved for applications where expectations of the final coating's durability are moderate since the light stability of 2-hydroxy-benzophenone derivatives is known to be limited.

For better long-term performance use of UV absorbers of the benzotriazole class e.g. Tinuvin 1130 or Tinuvin 384-2 is recommended.

The amount of Chimassorb 81 required for optimum performance should be determined in trials covering a concentration range.

Recommended Concentrations

+0.5 – 2.0 % Tinuvin 292, Tinuvin 249 or Tinuvin 123

(concentrations are based on weight percent binder solids)

Safety

General

The usual safety precautions when handling chemicals must be observed. These include the measures described in Federal, State and Local health and safety regulations, thorough ventilation of the workplace, good skin care and wearing of protective goggles.

Safety Data Sheet

All safety information is provided in the Safety Data Sheet for Chimassorb 81.

Storage

Please refer to the "Handling and Storage of Polymer Dispersions" brochure.

Important

WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, THEY ARE PROVIDED FOR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, BASF RECOMMENDS THAT THE READER MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR A PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESCRIPTIONS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF BASF'S TERMS AND CONDITIONS OF SALE. FURTHER, THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY BASF HEREUNDER ARE GIVEN GRATIS AND BASF ASSUMES NO OBLIGATION OR LIABILITY FOR THE DESCRIPTIONS, DESIGNS, DATA OR INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT THE READER'S RISK.

Chimassorb is a registered trademark of BASF Group.

© BASF Corporation, 2022



BASF Corporation is fully committed to the Responsible Care® initiative in the USA, Canada, and Mexico.
For more information on Responsible Care® go to:
U.S.: www.basf.us/responsiblecare_usa
Canada: www.basf.us/responsiblecare_canada
México: www.basf.us/responsiblecare_mexico

page 3 of 3

BASF Corporation

Dispersions and Resins 11501 Steele Creek Road Charlotte, North Carolina 28273 Phone: (800) 251 – 0612 Email: CustCare-Charlotte@basf.com www.basf.us/dpsolutions

October 2022 Rev 6