

Safety data sheet

Page: 1/10

BASF Safety data sheet

Date / Revised: 28.07.2025 Version: 5.0

Product: Kollidon® CL

(30034964/SDS_GEN_VN/EN)

Date of print: 11.10.2025

1. Substance/preparation and manufacturer/supplier identification

Product name:

Kollidon® CL

Use: pharmaceutical excipient

Manufacturer/supplier:

BASF Vietnam Co. Ltd. Level 23, Deutsches Haus, 33 Le Duan, Sai Gon Ward, Ho Chi Minh City, Vietnam

Telephone: +84 28 3824 3833 Telefax number: +84 28 3824 3832

E-mail address: minh-triet.thieu@basf.com

Emergency information:

18001703 (Vietnam)

Telefax number: +84 28 3824 3832 International emergency number: Telephone: +49 180 2273-112

2. Hazard identification

Classification of the substance and mixture:

No need for classification according to GHS criteria for this product.

Label elements and precautionary statement:

The product does not require a hazard warning label in accordance with GHS criteria.

Other hazards which do not result in classification:

The product is under certain conditions capable of dust explosion.

Product: Kollidon® CL

(30034964/SDS_GEN_VN/EN)

Date of print: 11.10.2025

3. Composition/information on ingredients

Chemical nature

Substance nature: Substance

2-Pyrrolidinone, 1-ethenyl-, homopolymer CAS Number: 9003-39-8

crosslinked, Microgranule (MG)

No particular hazards known.

4. First-Aid Measures

General advice:

Remove contaminated clothing.

If inhaled:

Keep patient calm, remove to fresh air.

On skin contact:

Wash thoroughly with soap and water

On contact with eyes:

Wash affected eyes for at least 15 minutes under running water with eyelids held open.

On ingestion:

Rinse mouth and then drink 200-300 ml of water.

Note to physician:

Symptoms: (Further) symptoms and / or effects are not known so far Treatment: Symptomatic treatment (decontamination, vital functions).

5. Fire-Fighting Measures

Suitable extinguishing media:

water spray, foam, dry powder, carbon dioxide

Unsuitable extinguishing media for safety reasons: water jet

Specific hazards:

hydrogen cyanide, carbon oxides, nitrogen oxides, harmful vapours

The substances/groups of substances mentioned can be released in case of fire. Dust explosion hazard.

Special protective equipment:

Wear a self-contained breathing apparatus.

Product: Kollidon® CL

(30034964/SDS_GEN_VN/EN)

Date of print: 11.10.2025

Further information:

Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

6. Accidental Release Measures

Personal precautions:

Avoid dust formation. Information regarding personal protective measures, see section 8. Use personal protective clothing.

Environmental precautions:

Do not discharge into drains/surface waters/groundwater.

Methods for cleaning up or taking up:

For small amounts: Contain with dust binding material and dispose of.

For large amounts: Sweep/shovel up.

Dispose of absorbed material in accordance with regulations. Avoid raising dust.

<u>Additional information:</u> Avoid the formation and build-up of dust - danger of dust explosion. Dust in sufficient concentration can result in an explosive mixture in air. Handle to minimize dusting and eliminate open flame and other sources of ignition. Avoid dispersal of dust in the air (e.g. by clearing dusty surfaces with compressed air).

7. Handling and Storage

Handling

Handle in accordance with good industrial hygiene and safety practice. Avoid dust formation. Provide exhaust ventilation if dust is formed.

Protection against fire and explosion:

Avoid dust formation. The product is capable of dust explosion. Take precautionary measures against static discharges. Avoid all sources of ignition: heat, sparks, open flame. Prevent electrostatic charge - sources of ignition should be kept well clear - fire extinguishers should be kept handy.

Dust explosion class: Dust explosion class 2 (Kst-value 200 up to 300 bar m s-1).

Storage

Further information on storage conditions: Keep container tightly closed and dry.

8. Exposure controls and personal protection

Components with occupational exposure limits

No substance specific occupational exposure limits known.

Product: Kollidon® CL

(30034964/SDS_GEN_VN/EN)

Date of print: 11.10.2025

Personal protective equipment

Respiratory protection:

Breathing protection if dusts are formed. Particle filter with low efficiency for solid particles (e.g. EN 143 or 149, Type P1or FFP1)

Hand protection:

Wear chemical resistant protective gloves.

Eye protection:

Safety glasses with side-shields (frame goggles) (e.g. EN 166)

Body protection:

Body protection must be chosen based on level of activity and exposure.

General safety and hygiene measures:

Handle in accordance with good industrial hygiene and safety practice. Wearing of closed work clothing is recommended. No eating, drinking, smoking or tobacco use at the place of work. Hands and/or face should be washed before breaks and at the end of the shift. Store work clothing separately.

9. Physical and Chemical Properties

Form: powder

Colour: white to cream
Odour: almost odourless
Odour threshold: not determined

pH value: 5 - 7

(1 %(m), 20 °C)

(as aqueous suspension)

melting range: >= 130 °C

The substance / product

decomposes.

Boiling point:

not applicable

Flash point:

not applicable, the product is a solid

Evaporation rate:

The product is a non-volatile solid.

Flammability (solid/gas): not highly flammable (VDI 2263, sheet 1, 1.1 (May

1990))

Lower explosion limit:

For solids not relevant for classification and labelling.

Upper explosion limit:

For solids not relevant for classification and labelling.

Thermal decomposition: 150 °C (DSC (DIN 51007))

Product: Kollidon® CL

(30034964/SDS_GEN_VN/EN)

(UN Test N.4 (self heating

substances))

Date of print: 11.10.2025

Self heating ability: It is a substance capable of

spontaneous heating according to UN transport regulations class 4.2. Based on test results packaging < 450 I are exempted from the

classification.

Explosion hazard: Product is not explosive, however a

dust explosion could result from an

air / dust mixture.

Fire promoting properties: not fire-propagating

Vapour pressure:

dropped

Density:

Bulk density:

No information is available for the absolute density. Instead the bulk density was determined as a more

relevant value. approx. 330 kg/m3

Relative vapour density (air):

not relevant

Solubility in water: insoluble

Solubility (qualitative) solvent(s): organic solvents

insoluble

Partitioning coefficient n-octanol/water (log Pow):

not determined

Viscosity, dynamic:

not applicable, the product is a solid

10. Stability and Reactivity

Conditions to avoid:

Avoid dust formation. Avoid electro-static charge. Avoid all sources of ignition: heat, sparks, open flame. See SDS section 7 - Handling and storage.

Thermal decomposition: 150 °C (DSC (DIN 51007))

Substances to avoid: strong alkalies

Corrosion to metals: Corrosive effects to metal are not anticipated.

Hazardous reactions: Dust explosion hazard.

Hazardous decomposition products:

No hazardous decomposition products if stored and handled as prescribed/indicated.

Product: Kollidon® CL

(30034964/SDS_GEN_VN/EN)

Date of print: 11.10.2025

Chemical stability:

The product is stable if stored and handled as prescribed/indicated.

Reactivity:

No hazardous reactions if stored and handled as prescribed/indicated.

11. Toxicological Information

Routes of exposure

Acute oral toxicity

Experimental/calculated data:

LD50rat (oral): > 2,000 mg/kg (BASF-Test)

Acute inhalation toxicity

LC50 rat (by inhalation): > 5.2 mg/l 4 h (OECD Guideline 403)

Assessment of acute toxicity

Virtually nontoxic after a single ingestion. Virtually nontoxic by inhalation.

Symptoms

(Further) symptoms and / or effects are not known so far

Irritation

Assessment of irritating effects:

Not irritating to the skin. Not irritating to the eyes.

Experimental/calculated data:

Skin corrosion/irritation rabbit: non-irritant (Draize test)

Serious eye damage/irritation rabbit: non-irritant (Draize test)

Respiratory/Skin sensitization

Assessment of sensitization:

No data available.

Germ cell mutagenicity

Assessment of mutagenicity:

The substance was not mutagenic in studies with mammals.

Carcinogenicity

Assessment of carcinogenicity:

In long-term animal studies in which the substance was given in high doses by feed, a carcinogenic effect was not observed.

Reproductive toxicity

Assessment of reproduction toxicity:

Product: Kollidon® CL

(30034964/SDS_GEN_VN/EN)

Date of print: 11.10.2025

No data available.

Developmental toxicity

Assessment of teratogenicity:

No indications of a developmental toxic / teratogenic effect were seen in animal studies.

Specific target organ toxicity (single exposure)

Remarks: No data available.

Repeated dose toxicity and Specific target organ toxicity (repeated exposure)

Assessment of repeated dose toxicity:

No data available.

Aspiration hazard

not applicable

12. Ecological Information

Ecotoxicity

Assessment of aquatic toxicity:

There is a high probability that the product is not acutely harmful to aquatic organisms. The inhibition of the degradation activity of activated sludge is not anticipated when introduced to biological treatment plants in appropriate low concentrations.

Toxicity to fish:

LC50 (96 h) > 10,000 mg/l, Leuciscus idus (DIN 38412 Part 15, static)

Microorganisms/Effect on activated sludge:

EC20 (0.5 h) > 1,995 mg/l, activated sludge, industrial (OECD Guideline 209, aerobic)

Mobility

Assessment transport between environmental compartments:

No data available.

Persistence and degradability

Elimination information:

< 10 % DOC reduction (15 d) (OECD Guideline 302 B) (aerobic, activated sludge, industrial) Poorly eliminated from water.

Bioaccumulation potential

Bioaccumulation potential:

Based on its structural properties, the polymer is not biologically available. Accumulation in organisms is not to be expected.

Product: Kollidon® CL

(30034964/SDS_GEN_VN/EN)

Date of print: 11.10.2025

13. Disposal Considerations

Information on disposal regulations: Must comply with regulations on hazardous waste such as:

- Decree No. 08/2022/ND-CP of the Government: detailing a number of articles of the Law on Environmental Protection.
- Circular No. 02/2022/TT-BTNMT of the Ministry of Natural Resources and Environment: detailing a number of articles of the Law on Environmental Protection.

Observe national and local legal requirements.

Contaminated packaging:

Uncontaminated packaging can be re-used.

Packs that cannot be cleaned should be disposed of in the same manner as the contents.

14. Transport Information

Domestic transport:

UN number or ID number: UN 3088

UN proper shipping name: SELF-HEATING SOLID, ORGANIC, N.O.S. (1-ETHENYL-2-

PYRROLIDINONE, HOMOPOLYMER)

Transport hazard class(es): 4.2 Packing group: III Environmental hazards: no

Special precautions for

user:

Not dangerous goods of class 4.2 in packages up to 450 litres

capacity.

Sea transport

IMDG

UN number or ID number: UN 3088

UN proper shipping name: SELF-HEATING SOLID, ORGANIC, N.O.S. (1-ETHENYL-2-

PYRROLIDINONE, HOMOPOLYMER)

Transport hazard class(es): 4.2 Packing group: III Environmental hazards: no

Marine pollutant: NO

Special precautions for EmS: F-A; S-J

user: Not dangerous goods of class 4.2 in packages up to 450 litres

capacity.

Air transport

IATA/ICAO

UN number or ID number: UN 3088

UN proper shipping name: SELF-HEATING SOLID, ORGANIC, N.O.S. (1-ETHENYL-2-

Product: Kollidon® CL

(30034964/SDS_GEN_VN/EN)

Date of print: 11.10.2025

PYRROLIDINONE, HOMOPOLYMER)

Transport hazard class(es): 4.2 Packing group: III

Environmental hazards: No Mark as dangerous for the environment is needed

Special precautions for Not dangerous goods of class 4.2 in packages up to 450 litres

user: capacity.

Maritime transport in bulk according to IMO instruments

Maritime transport in bulk is not intended.

15. Regulatory Information

Other regulations

Legal information on safety, health and environment for chemicals: Law on Chemicals No. 06/2007/QH12

Chemical Safety Sheets (SDS) are compiled in accordance with international regulations on chemical classification and labelling (GHS) as well as relevant applicable legal regulations:

- QCVN 05A:2020/BCT National Technical Regulation on safety in production, trading, use, preservation and transportation of hazardous chemicals.
- Amendment 1:2024 QCVN 05A:2020/BCT National technical regulation on safety in production, trading, use, preservation and transportation of hazardous chemicals.
- Decree No. 113/2017/ND-CP dated 09/10/2017 of the Government detailing and guiding the implementation of a number of articles of the Law on Chemicals:
- Circular No. 32/2017/TT-BCT dated 28/12/2017 of the Ministry of Industry and Trade specifying and guiding the implementation of a number of articles of the Law on Chemicals and Decree No. 113/2017/ND-CP dated 09/10/2017 of the Government detailing and guiding the implementation of a number of articles of the Law on Chemicals;
- Decree No. 82/2022/ND-CP dated October 18, 2022 of the Government amending and supplementing a number of articles of the Government's Decree No. 113/2017/ND-CP dated October 09, 2017 detailing and guiding the implementation of a number of articles of the Law on Chemicals
- Circular No. 17/2022/TT-BCT dated October 27, 2022 of the Ministry of Industry and Trade amending and supplementing a number of articles of Circular No. 32/2017/TT-BCT dated December 28, 2017 of the Minister of Industry and Trade specifying and guiding the implementation of a number of articles of the Law on Chemicals and the Government's Decree No. 113/2017/ND-CP dated October 09, 2017 detailing and guiding the exam a number of articles of the Law on Chemicals
- Decree No. 161/2024 ND-CP dated December 18, 2024 of the Government regulating the list of dangerous goods, transportation of dangerous goods and the order and procedures for issuance of licenses and certificates of completion of training programs for drivers or escorts transporting dangerous goods on roads;
- Decree 34/2024/ND-CP dated 31/03/2024 regulating the list of dangerous goods, transporting dangerous goods by road motor vehicles and inland waterway vehicles
- Circular No. 37/2020/TT-BCT dated 30/11/2020 of the Ministry of Industry and Trade stipulating the list of dangerous goods that must be packed in the process of transporting and transporting dangerous goods by road, railway and inland waterway motor vehicles.

Version: 5.0

BASF Safety data sheet Date / Revised: 28.07.2025

Product: Kollidon® CL

(30034964/SDS_GEN_VN/EN)

Date of print: 11.10.2025

- Decree No. 71/2019/ND-CP dated August 30, 2019 of the Government stipulating the sanctioning of administrative violations in the field of chemicals and industrial explosives.

16. Other Information

Any other intended applications should be discussed with the manufacturer. Corresponding occupational protection measurements must be followed.

Vertical lines in the left hand margin indicate an amendment from the previous version.

The data contained in this safety data sheet are based on our current knowledge and experience and describe the product only with regard to safety requirements. This safety data sheet is neither a Certificate of Analysis (CoA) nor technical data sheet and shall not be mistaken for a specification agreement. Identified uses in this safety data sheet do neither represent an agreement on the corresponding contractual quality of the substance/mixture nor a contractually designated use. It is the responsibility of the recipient of the product to ensure any proprietary rights and existing laws and legislation are observed.