

## Safety data sheet

Page: 1/12

BASF Safety data sheet

Date / Revised: 23.06.2022 Version: 4.0

Product: Basonat® LR 9056

(30591253/SDS\_GEN\_TH/EN)

Date of print): 12.10.2025

## 1. Substance/preparation and manufacturer/supplier identification

## **Product name:**

Basonat® LR 9056

Use: Raw material, for industrial use only

## Manufacturer/supplier:

BASF (Thai) Limited

23rd Floor, Emporium Tower, 622, Sukhumvit 24 Rd., Klongton, Klongtoey, Bangkok 10110, THAILAND

Telephone: +66 2624-1999 Telefax number: +66 2664-9254

E-mail address: Thailand-SDS-info@basf.com

## **Emergency information:**

International emergency number: Telephone: +49 180 2273-112

#### 2. Hazard identification

#### Classification according to UN GHS 2009

Classification of the substance and mixture: Acute toxicity: Cat.4 (Inhalation - mist)

Acute toxicity: Cat.5 (oral) Skin sensitization: Cat.1

Specific target organ toxicity — single exposure: Cat.3 (irritating to respiratory system)

Hazardous to the aquatic environment - acute: Cat.3 Hazardous to the aquatic environment - chronic: Cat.3

Label elements and precautionary statement:

Pictogram:

Product: Basonat® LR 9056

(30591253/SDS\_GEN\_TH/EN)

Date of print): 12.10.2025



# Signal Word: Warning

#### Hazard Statement:

H332 Harmful if inhaled.

H303 May be harmful if swallowed.
H317 May cause an allergic skin reaction.
H335 May cause respiratory irritation.

H402 Harmful to aquatic life.

H412 Harmful to aquatic life with long lasting effects.

Precautionary Statements (Prevention):

P280 Wear protective gloves.

P271 Use only outdoors or in a well-ventilated area.

P260 Do not breathe mist or vapour. P273 Avoid release to the environment.

P272 Contaminated work clothing should not be allowed out of the workplace.

Precautionary Statements (Response):

P312 Call a POISON CENTER or physician if you feel unwell.

P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for

breathing.

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.
P333 + P313 If skin irritation or rash occurs: Get medical attention.
P362 + P364 Take off contaminated clothing and wash it before reuse.

Precautionary Statements (Storage):

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

Precautionary Statements (Disposal):

P501 Dispose of contents and container to hazardous or special waste

collection point.

Other hazards which do not result in classification:

No specific dangers known, if the regulations/notes for storage and handling are considered.

## 3. Composition/information on ingredients

## Chemical nature

Substance nature: mixture

polyfunctional polyisocyanate, aliphatic

#### **Hazardous ingredients**

Product: Basonat® LR 9056

(30591253/SDS\_GEN\_TH/EN)

Date of print): 12.10.2025

(OLIGOMER) Hexamethylene diisocyanate isocyanurate-type oligomers

Content (W/W): >= 60 % - <= 80 % Acute Tox.: Cat. 4 (Inhalation - mist)

CAS Number: 28182-81-2 Skin Sens.: Cat. 1

STOT SE: Cat. 3 (irr. to respiratory syst.)

Poly(oxy-1,2-ethanediyl), .alpha.-methyl-.omega.-hydroxy-, polymer with 1,6-diisocyanatohexane,

block

Content (W/W): >= 20 % - <= 35 % Acute Tox.: Cat. 4 (Inhalation - mist)

CAS Number: 143472-08-6 Skin Sens.: Cat. 1

STOT SE: Cat. 3 (irr. to respiratory syst.)

Aquatic Acute: Cat. 3 Aquatic Chronic: Cat. 3

1,6-hexamethylene diisocyanate

Content (W/W): < 0.1 % Acute Tox.: Cat. 4 (oral)

CAS Number: 822-06-0 Acute Tox.: Cat. 1 (Inhalation - mist)

Skin Corr./Irrit.: Cat. 2 Eye Dam./Irrit.: Cat. 2A Resp. Sens.: Cat. 1

Skin Sens.: Cat. 1

STOT SE: Cat. 3 (irr. to respiratory syst.)

#### 4. First-Aid Measures

General advice:

Immediately remove contaminated clothing.

If inhaled:

If difficulties occur after vapour/aerosol has been inhaled, remove to fresh air and seek medical attention.

On skin contact:

Wash thoroughly with soap and water

On contact with eyes:

Wash affected eyes for at least 15 minutes under running water with eyelids held open.

On ingestion:

Rinse mouth and then drink 200-300 ml of water. Do not induce vomiting unless told to by a poison control center or doctor.

Note to physician:

Symptoms: Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11., (Further) symptoms and / or effects are not known so far

Treatment: Treat according to symptoms (decontamination, vital functions), no known specific antidote.

Product: Basonat® LR 9056

(30591253/SDS\_GEN\_TH/EN)

Date of print): 12.10.2025

## 5. Fire-Fighting Measures

Suitable extinguishing media: water spray, dry powder, foam

Unsuitable extinguishing media for safety reasons: water jet

Specific hazards:

harmful vapours

Evolution of fumes/fog. The substances/groups of substances mentioned can be released in case of fire

Special protective equipment:

Wear a self-contained breathing apparatus.

Further information:

The degree of risk is governed by the burning substance and the fire conditions. Contaminated extinguishing water must be disposed of in accordance with official regulations.

#### 6. Accidental Release Measures

Personal precautions:

Use personal protective clothing. Breathing protection required.

Environmental precautions:

Contain contaminated water/firefighting water. Do not discharge into drains/surface waters/groundwater.

Methods for cleaning up or taking up:

For large amounts: Pump off product.

For residues: Pick up with suitable absorbent material. Dispose of absorbed material in accordance with regulations.

## 7. Handling and Storage

## **Handling**

Avoid handling of the substance in case of known skin complaints, hypersensitivity reactions, chronic respiratory disease, asthmatic attacks or bronchial attacks. Avoid contact with the skin, eyes and clothing. Avoid inhalation of dusts/mists/vapours. Avoid frequent and direct contact with substance. Ensure good work practices are implemented. Regular inspection and maintenance of equipment and machines. Clean equipment and the work area every day. Engineering controls have to be used to reduce exposures. Minimise exposure by partial enclosure of the operation or equipment and provide extract ventilation at openings. Workers should receive a pre-placement examination and subsequent periodic medical examinations, including a pulmonary function test. Wear suitable face shield Wear an impervious suit. Use suitable eye protection. Wear chemically resistant gloves in combination with 'basic' employee training. Change gloves, if duration of activity exceeds break through time Use a local exhaust ventilation with adequate effectiveness. In case of insufficient ventilation, wear suitable respiratory equipment.

Product: Basonat® LR 9056

(30591253/SDS\_GEN\_TH/EN)

Date of print): 12.10.2025

Protection against fire and explosion:

Take precautionary measures against static discharges.

#### Storage

Further information on storage conditions: Keep container tightly closed and in a cool place. Keep container dry.

Storage stability:

If moisture enters isocyanate containers, CO2 forms and pressure builds up.

Protect from temperatures above: 50 °C

## 8. Exposure controls and personal protection

Components with occupational exposure limits

1,6-hexamethylene diisocyanate, 822-06-0;

TWA value 0.005 ppm (ACGIHTLV) TWA value 0.005 ppm (OEL (TH))

## Personal protective equipment

#### Respiratory protection:

For short-term or slight exposure, use a respiratory mask with filter, for intensive or long-term exposure wear full respiratory protection apparatus Combination filter for gases/vapours of organic compounds and solid and liquid particles (f.e. EN 14387 Type A-P2)

#### Hand protection:

Chemical resistant protective gloves

Suitable materials for short-term contact (recommended: At least protective index 2, corresponding > 30 minutes of permeation time according to EN ISO 374-1)

nitrile rubber (NBR) - 0.4 mm coating thickness

fluoroelastomer (FKM) - 0.7 mm coating thickness

Supplementary note: The specifications are based on tests, literature data and information of glove manufacturers or are derived from similar substances by analogy. Due to many conditions (e.g. temperature) it must be considered, that the practical usage of a chemical-protective glove in practice may be much shorter than the permeation time determined through testing. Manufacturer's directions for use should be observed because of great diversity of types.

#### Eye protection:

Safety glasses with side-shields (frame goggles) (f.e. EN 166) and face shield

#### Body protection:

Body protection must be chosen depending on activity and possible exposure, e.g. apron, protecting boots, chemical-protection suit (according to EN 14605 in case of splashes or EN ISO 13982 in case of dust).

Product: Basonat® LR 9056

(30591253/SDS\_GEN\_TH/EN)

Date of print): 12.10.2025

General safety and hygiene measures:

Handle in accordance with good industrial hygiene and safety practice. Wearing of closed work clothing is required additionally to the stated personal protection equipment. Do not breathe vapour/aerosol/spray mists. Ensure adequate ventilation. Clean equipment, work area and clothing regularly.

## 9. Physical and Chemical Properties

Form: liquid

Colour: colourless to yellowish product specific Odour: not determined

Odour threshold:

pH value: not applicable

approx. -46 °C (DIN 51583) Melting point:

Boiling point:

not determined

Flash point: 168 °C (ISO 2719)

Evaporation rate:

not determined

Flammability (solid/gas): not flammable (derived from flash point)

Lower explosion limit:

As a result of our experience with this product and our knowledge of its composition we do not expect any hazard as long as the product is used appropriately and in accordance with

the intended use.

Upper explosion limit:

As a result of our experience with this product and our knowledge of its composition we do not expect any hazard as long as the product is used appropriately and in accordance with

the intended use.

Ignition temperature: 414 °C (DIN EN 14522)

Thermal decomposition: No decomposition if used correctly.

Self ignition: not self-igniting

It is not a substance capable of Self heating ability:

spontaneous heating.

Explosion hazard: not explosive

Fire promoting properties: not fire-propagating

Vapour pressure: < 0.0001 hPa

(20 °C)

Product: Basonat® LR 9056

(30591253/SDS\_GEN\_TH/EN)

Date of print): 12.10.2025

Density: 1.16 g/cm3

(20 °C) 1.14 g/cm3 (50 °C)

Relative density: 1.16

(20 °C)

Relative vapour density (air):

not determined

Solubility in water: Reacts with water.

Miscibility with water:

Reacts with water.

Hygroscopy: hygroscopic

Solubility (qualitative) solvent(s): polar solvents

soluble

Partitioning coefficient n-octanol/water (log Pow):

Study scientifically not justified.

Surface tension:

Based on chemical structure, surface

activity is not to be expected.

Viscosity, dynamic: 1.5 - 3.0 Pa.s (DIN EN ISO 3219)

(23 °C, 50 1/s)

## 10. Stability and Reactivity

Conditions to avoid:

Avoid moisture. Avoid humidity. Avoid direct contact with water.

Thermal decomposition: No decomposition if used correctly.

Substances to avoid: water, alcohols, amines

Hazardous reactions:

Reacts with alcohols. Reacts with amines. Reacts with substances which contain active hydrogen. Reacts with water, with formation of carbon dioxide. The formation of gaseous decomposition products builds up pressure in tightly closed containers.

Hazardous decomposition products:

No hazardous decomposition products if stored and handled as prescribed/indicated.

Chemical stability:

The product is stable if stored and handled as prescribed/indicated.

## 11. Toxicological Information

#### Routes of exposure

**Acute oral toxicity** 

Experimental/calculated data:

Product: Basonat® LR 9056

(30591253/SDS\_GEN\_TH/EN)

Date of print): 12.10.2025

LD50rat (oral): > 2,000 mg/kg

The product has not been tested. The statement has been derived from the properties of the individual components.

#### Acute inhalation toxicity

LC50 rat (by inhalation): > 1 - 5 mg/l 4 h

The substance from the isocyanate substance class has been tested in a form (respirable aerosol) that is different from the forms in which the product is placed on the market and used. Therefore, the test result is not adequate for the purpose of classification and labelling of the product. Based on expert judgement and available data, a modified classification and labeling for acute inhalation toxicity is justified. The generation of a respirable aerosol must be prevented! The product has not been tested. The statement has been derived from the properties of the individual components.

#### Acute dermal toxicity

LD50 rat (dermal): not determined

## Assessment of acute toxicity

Virtually nontoxic after a single ingestion. Of moderate toxicity after short-term inhalation. The product has not been tested. The statement has been derived from the properties of the individual components.

Information on: (OLIGOMER) Hexamethylene diisocyanate isocyanurate-type oligomers

#### Acute inhalation toxicity

Experimental/calculated data:

LC50 rat (by inhalation): 0.467 mg/l 4 h (OECD Guideline 403)

The test result applies only to the substance transferred into respirable aerosol (particles  $< 20 \ \mu m$ ). An aerosol was tested.

\_\_\_\_\_

#### **Symptoms**

Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11. (Further) symptoms and / or effects are not known so far

#### Irritation

Assessment of irritating effects:

Not irritating to eyes and skin. The product has not been tested. The statement has been derived from the properties of the individual components.

Experimental/calculated data:

Skin corrosion/irritation rabbit: non-irritant (OECD Guideline 404)

The product has not been tested. The statement has been derived from the properties of the individual components.

Serious eye damage/irritation rabbit: non-irritant (OECD Guideline 405)

The product has not been tested. The statement has been derived from the properties of the individual components.

#### Respiratory/Skin sensitization

Experimental/calculated data:

Guinea pig maximization test guinea pig: skin sensitizing

Product: Basonat® LR 9056

(30591253/SDS\_GEN\_TH/EN)

Date of print): 12.10.2025

Caused skin sensitization in animal studies. The product has not been tested. The statement has been derived from the properties of the individual components.

## Germ cell mutagenicity

Assessment of mutagenicity:

Based on the ingredients, there is no suspicion of a mutagenic effect.

## Carcinogenicity

Assessment of carcinogenicity:

No data available.

#### Reproductive toxicity

Assessment of reproduction toxicity:

No data available.

#### **Developmental toxicity**

Assessment of teratogenicity:

No data available.

## Specific target organ toxicity (single exposure)

Causes temporary irritation of the respiratory tract.

## Repeated dose toxicity and Specific target organ toxicity (repeated exposure)

Assessment of repeated dose toxicity:

No data available.

## **Aspiration hazard**

No aspiration hazard expected.

## 12. Ecological Information

## **Ecotoxicity**

Assessment of aquatic toxicity:

The inhibition of the degradation activity of activated sludge is not anticipated when introduced to biological treatment plants in appropriate low concentrations.

Toxicity to fish: LC50 (96 h), Fish not determined

Aquatic invertebrates:

EC50 (48 h) 10 - 100 mg/l, Daphnia magna

Product: Basonat® LR 9056

(30591253/SDS\_GEN\_TH/EN)

Date of print): 12.10.2025

The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Aquatic plants: EC50 (72 h), algae not determined

Microorganisms/Effect on activated sludge:

EC50 (3 h) > 1,000 mg/l, bacteria

The inhibition of the degradation activity of activated sludge is not anticipated when introduced to biological treatment plants in appropriate low concentrations.

Chronic toxicity to fish:

No data available.

Chronic toxicity to aquatic invertebrates:

No data available.

Assessment of terrestrial toxicity: Study scientifically not justified.

#### **Mobility**

Assessment transport between environmental compartments:

The substance will not evaporate into the atmosphere from the water surface.

No data available.

## Persistence and degradability

Elimination information:

Not readily biodegradable (by OECD criteria).

## **Bioaccumulation potential**

Assessment bioaccumulation potential:

The product has not been tested.

#### **Additional information**

Add. remarks environm. fate & pathway:

Treatment in biological waste water treatment plants has to be performed according to local and administrative regulations.

Other ecotoxicological advice:

Do not release untreated into natural waters. The local regulations on waste-water treatment must be followed.

#### 13. Disposal Considerations

Incinerate in suitable incineration plant, observing local authority regulations.

Contaminated packaging:

Uncontaminated packaging can be re-used.

Product: Basonat® LR 9056

(30591253/SDS\_GEN\_TH/EN)

Date of print): 12.10.2025

Packs that cannot be cleaned should be disposed of in the same manner as the contents. Refer to manufacturer/supplier for information on recovery/recycling.

## 14. Transport Information

#### **Domestic transport:**

Not classified as a dangerous good under transport regulations

UN number or ID number
UN proper shipping name:
Transport hazard class(es):
Packing group:
Environmental hazards:
Special precautions for

Not applicable

user

#### Sea transport

**IMDG** 

Not classified as a dangerous good under transport regulations

UN number or ID number:
UN proper shipping name:
Transport hazard class(es):
Packing group:
Environmental hazards:
Special precautions for

Not applicable
Not applicable
Not applicable
Not applicable
Not applicable
Not applicable

user

Air transport

Not classified as a dangerous good under transport regulations

UN number or ID number
Proper shipping name:
Transport hazard class(es):
Packing group:
Environmental hazards:
Special precautions for

Not applicable
Not applicable
Not applicable
Not applicable
Not applicable
Not applicable

user

## 15. Regulatory Information

Product: Basonat® LR 9056

(30591253/SDS\_GEN\_TH/EN)

Date of print): 12.10.2025

## **Other regulations**

#### 16. Other Information

Vertical lines in the left hand margin indicate an amendment from the previous version.

The data contained in this safety data sheet are based on our current knowledge and experience and describe the product only with regard to safety requirements. This safety data sheet is neither a Certificate of Analysis (CoA) nor technical data sheet and shall not be mistaken for a specification agreement. Identified uses in this safety data sheet do neither represent an agreement on the corresponding contractual quality of the substance/mixture nor a contractually designated use. It is the responsibility of the recipient of the product to ensure any proprietary rights and existing laws and legislation are observed.