

Safety Data Sheet Luwax® A Powder

Revision date : 2024/02/12 Page: 1/9

Version: 3.1 (30043686/SDS_GEN_US/EN)

1. Identification

Product identifier used on the label

Luwax® A Powder

Recommended use of the chemical and restriction on use

Recommended use*: wax for the chemical industry

Unsuitable for use: None known

Details of the supplier of the safety data sheet

Company:
BASF CORPORATION
100 Park Avenue

Florham Park, NJ 07932, USA

Telephone: +1 973 245-6000

Emergency telephone number

24 Hour Emergency Response Information

CHEMTREC: 1-800-424-9300

BASF HOTLINE: 1-800-832-HELP (4357)

Other means of identification

Chemical family: polyethylene wax

2. Hazards Identification

According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

Classification of the product

Combustible Dust Combustible Dust (1) Combustible Dust

Label elements

Signal Word:

^{*} The "Recommended use" identified for this product is provided solely to comply with a Federal requirement and is not part of the seller's published specification. The terms of this Safety Data Sheet (SDS) do not create or infer any warranty, express or implied, including by incorporation into or reference in the seller's sales agreement.

Luwax® A Powder

Revision date: 2024/02/12 Page: 2/9
Version: 3.1 (30043686/SDS GEN US/EN)

Warning

Hazard Statement:

May form combustible dust concentration in air.

Hazards not otherwise classified

The product is under certain conditions capable of dust explosion.

3. Composition / Information on Ingredients

According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

Polyethylene wax

CAS Number: 9002-88-4 Content (W/W): 100.0 % Synonym: Poly(ethylene)

4. First-Aid Measures

Description of first aid measures

General advice:

Remove contaminated clothing.

If inhaled:

Keep patient calm, remove to fresh air, seek medical attention.

If on skin:

Remove contaminated clothing. Rinse skin immediately with plenty of water for 15 - 20 minutes. If irritation develops, seek medical attention.

If in eyes:

Wash affected eyes for at least 15 minutes under running water with eyelids held open.

If irritation develops, seek medical attention.

If swallowed:

Rinse mouth and then drink 200-300 ml of water. Do not induce vomiting. Immediate medical attention required.

Most important symptoms and effects, both acute and delayed

Symptoms: Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11.

(Further) symptoms and / or effects are not known so far

Hazards: No applicable information available.

Indication of any immediate medical attention and special treatment needed

Luwax® A Powder

Revision date: 2024/02/12 Page: 3/9
Version: 3.1 (30043686/SDS GEN US/EN)

Note to physician

Treat according to symptoms (decontamination, vital functions), no

known specific antidote.

5. Fire-Fighting Measures

Extinguishing media

Suitable extinguishing media:

dry powder, foam

Unsuitable extinguishing media for safety reasons:

carbon dioxide

Additional information:

Avoid whirling up the material/product because of the danger of dust explosion.

Special hazards arising from the substance or mixture

Hazards during fire-fighting:

harmful vapours

Evolution of fumes/fog. The substances/groups of substances mentioned can be released in case of fire.

Advice for fire-fighters

Protective equipment for fire-fighting:

Firefighters should be equipped with self-contained breathing apparatus and turn-out gear.

Further information:

Dusty conditions may ignite explosively in the presence of an ignition source causing flash fire.

6. Accidental release measures

Further accidental release measures:

Avoid dispersal of dust in the air (e.g. by clearing dusty surfaces with compressed air). Avoid the formation and build-up of dust - danger of dust explosion. Dust in sufficient concentration can result in an explosive mixture in air. Handle to minimize dusting and eliminate open flame and other sources of ignition.

Personal precautions, protective equipment and emergency procedures

Avoid dust formation. Use personal protective clothing.

Environmental precautions

Contain contaminated water/firefighting water. Do not discharge into drains/surface waters/groundwater.

Methods and material for containment and cleaning up

Nonsparking tools should be used.

Luwax® A Powder

Revision date: 2024/02/12 Page: 4/9
Version: 3.1 (30043686/SDS_GEN_US/EN)

7. Handling and Storage

Precautions for safe handling

Breathing must be protected when large quantities are decanted without local exhaust ventilation.

Closed containers should only be opened in well-ventilated areas. Avoid dust formation. Do not use any sparking tools.

Protection against fire and explosion:

Avoid dust formation. Dust in sufficient concentration can result in an explosive mixture in air. Handle to minimize dusting and eliminate open flame and other sources of ignition. Routine housekeeping should be instituted to ensure that dusts do not accumulate on surfaces. Dry powders can build static electricity charges when subjected to the friction of transfer and mixing operations. Provide adequate precautions, such as electrical grounding and bonding, or inert atmospheres. Refer to NFPA 654, Standard for the Prevention of Fire and Dust Explosions from the Manufacturing, Processing, and Handling of Combustible Particulate Solids (2013 Edition) for safe handling.

Conditions for safe storage, including any incompatibilities

No applicable information available.

Suitable materials for containers: Low density polyethylene (LDPE), Stainless steel 1.4301 (V2), Stainless steel 1.4401, glass, Paper/Fibreboard, High density polyethylene (HDPE)

Further information on storage conditions: Keep container tightly closed and dry; store in a cool place.

Protect from temperatures below: -20 °C Protect from temperatures above: 50 °C

8. Exposure Controls/Personal Protection

Components with occupational exposure limits

Polyethylene wax	OSHA Z1: OSHA Z1:	PEL 5 mg/m3 Respirable fraction; PEL 15 mg/m3 Total dust;
polyethylene	OSHA Z1: OSHA Z1:	PEL 5 mg/m3 Respirable fraction; PEL 15 mg/m3 Total dust;

The nuisance dust limit value is to be kept.

Particles, not otherwise specified, respirable	ACGIH, US: OSHA Z3: OSHA Z3: OSHA Z3:	TWA value 3 mg/m3 Respirable particles; TWA value 5 mg/m3 Respirable fraction; TWA value 15 mg/m3 Total dust; TWA value 50 millions of particles per cubic foot of air Total dust;
	OSHA Z3:	TWA value 15 millions of particles per cubic foot of air Respirable fraction;
Particles, not otherwise specified, inhalable	ACGIH, US: OSHA Z3: OSHA Z3:	TWA value 10 mg/m3 Inhalable particles; TWA value 15 mg/m3 Total dust; TWA value 50 millions of particles per cubic foot of air Total dust;

Luwax® A Powder

Revision date: 2024/02/12 Page: 5/9
Version: 3.1 (30043686/SDS GEN US/EN)

Personal protective equipment

Respiratory protection:

Respiratory protection may not be required under normal operating conditions if adequate ventilation is provided. Breathing protection if dusts are formed.

Hand protection:

Wear chemical resistant protective gloves.

Eye protection:

Safety glasses with side-shields.

Body protection:

Body protection must be chosen depending on activity and possible exposure, e.g. head protection, apron, protective boots, chemical-protection suit.

General safety and hygiene measures:

Wear protective clothing as necessary to minimize contact. Handle in accordance with good industrial hygiene and safety practice. No eating, drinking, smoking or tobacco use at the place of work. Handle in accordance with good industrial hygiene and safety practice.

9. Physical and Chemical Properties

Form: powder

Odour: No data available.

Odour threshold: No applicable information available.

Colour: white

pH value: not applicable melting range: 101 - 109 °C solidification 94 - 100 °C

temperature:

Boiling point: not determined

Sublimation point: No applicable information available.

Flash point: 225 °C

Flammability: hardly combustible

Lower explosion limit: No applicable information available. Upper explosion limit: No applicable information available.

Autoignition: 390 °C

Vapour pressure: Study scientifically not justified.

Density: 0.91 - 0.93 g/cm3

(23°C)

Bulk density: 400 - 450 kg/m3

Vapour density: No applicable information available.

Partitioning coefficient n- not applicable

octanol/water (log Pow):

Self-ignition not self-igniting

temperature:

Thermal decomposition: No decomposition if used as directed.

Viscosity, kinematic: 950 - 1,550 mm2/s (DIN 51562)

(120 °C)

Solubility in water: insoluble Solubility (qualitative): soluble

solvent(s): non-polar solvents,

Luwax® A Powder

Revision date: 2024/02/12 Page: 6/9
Version: 3.1 (30043686/SDS GEN US/EN)

Molar mass: No applicable information available. Evaporation rate: No applicable information available.

10. Stability and Reactivity

Reactivity

No hazardous reactions if stored and handled as prescribed/indicated.

Corrosion to metals:

No corrosive effect on metal.

Oxidizing properties:

not fire-propagating

Minimum ignition energy:

> 30 - < 100 mJ, Inductivity: 1 mH

Chemical stability

The product is stable if stored and handled as prescribed/indicated.

Possibility of hazardous reactions

No hazardous reactions when stored and handled according to instructions.

The product is chemically stable.

Conditions to avoid

Avoid dust formation. Avoid deposition of dust. Avoid all sources of ignition: heat, sparks, open flame. Avoid electro-static charge.

Incompatible materials

strong acids, strong bases, strong oxidizing agents

Hazardous decomposition products

Decomposition products:

Hazardous decomposition products: No hazardous decomposition products if stored and handled as prescribed/indicated.

Thermal decomposition:

No decomposition if used as directed.

11. Toxicological information

Primary routes of exposure

Routes of entry for solids and liquids are ingestion and inhalation, but may include eye or skin contact. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquefied gases.

Acute Toxicity/Effects

Acute toxicity

Assessment of acute toxicity: Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses.

Luwax® A Powder

Revision date: 2024/02/12 Page: 7/9
Version: 3.1 (30043686/SDS_GEN_US/EN)

Oral

Type of value: ATE Value: > 2,000 mg/kg

Inhalation

No applicable information available.

Dermal

No applicable information available.

Assessment other acute effects

Assessment of STOT single:

Based on the available information there is no specific target organ toxicity to be expected after a single exposure.

Irritation / corrosion

Assessment of irritating effects: Not irritating to eyes and skin.

Sensitization

Assessment of sensitization: Based on the ingredients, there is no suspicion of a skin-sensitizing potential.

Aspiration Hazard

No aspiration hazard expected.

Chronic Toxicity/Effects

Repeated dose toxicity

Assessment of repeated dose toxicity: Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses.

Genetic toxicity

Assessment of mutagenicity: Based on the ingredients, there is no suspicion of a mutagenic effect.

Carcinogenicity

Assessment of carcinogenicity: Based on the ingredients there is no suspicion of a carcinogenic effect in humans.

Reproductive toxicity

Assessment of reproduction toxicity: Based on the ingredients, there is no suspicion of a toxic effect on reproduction.

Other Information

The product has not been tested. The statements on toxicology have been derived from products of a similar structure and composition.

12. Ecological Information

Toxicity

Aquatic toxicity

Luwax® A Powder

Revision date: 2024/02/12 Page: 8/9
Version: 3.1 (30043686/SDS GEN US/EN)

Assessment of aquatic toxicity:

There is a high probability that the product is not acutely harmful to aquatic organisms.

At the present state of knowledge, no negative ecological effects are expected.

Persistence and degradability

Assessment biodegradation and elimination (H2O)

Not readily biodegradable (by OECD criteria).

The product is virtually insoluble in water and can thus be separated from water mechanically in suitable effluent treatment plants.

Bioaccumulative potential

Assessment bioaccumulation potential

Accumulation in organisms is not to be expected.

Mobility in soil

Assessment transport between environmental compartments

The substance will not evaporate into the atmosphere from the water surface.

Adsorption to solid soil phase is possible.

Additional information

Other ecotoxicological advice:

Do not discharge product into the environment without control. The product has not been tested. The statements on ecotoxicology have been derived from products of a similar structure and composition.

13. Disposal considerations

Waste disposal of substance:

Do not discharge into drains/surface waters/groundwater. Dispose of in accordance with national, state and local regulations.

Container disposal:

Dispose of in accordance with national, state and local regulations. Recommend crushing, puncturing or other means to prevent unauthorized use of used containers.

RCRA: NONE

14. Transport Information

Land transport

USDOT

Not classified as a dangerous good under transport regulations

Sea transport

IMDG

Not classified as a dangerous good under transport regulations

Air transport IATA/ICAO

Not classified as a dangerous good under transport regulations

Luwax® A Powder

Revision date: 2024/02/12 Page: 9/9
Version: 3.1 (30043686/SDS GEN US/EN)

15. Regulatory Information

Federal Regulations

Registration status:

Chemical TSCA, US released / listed

EPCRA 311/312 (Hazard categories): Refer to SDS section 2 for GHS hazard classes applicable for this product.

NFPA Hazard codes:

Health: 1 Fire: 1 Reactivity: 0 Special:

HMIS III rating

Health: 1 Flammability: 1 Physical hazard: 0

16. Other Information

SDS Prepared by:

BASF NA Product Regulations SDS Prepared on: 2024/02/12

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

Luwax® A Powder is a registered trademark of BASF Corporation or BASF SE IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS. DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK. **END OF DATA SHEET**