

Safety data sheet

Page: 1/115

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 13.12.2023 Date / Previous version: not applicable Previous version: none

Product: METHOXYPROPYLACETATE

(ID no. 30034751/SDS_GEN_IT/EN)

Date of print 21.10.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

METHOXYPROPYLACETATE

Chemical name: 1-methoxy-2-propylacetate

INDEX-Number: 607-195-00-7 CAS Number: 108-65-6

REACH registration number: 01-2119475791-29

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses: process chemical, solvent(s)

For the detailed identified uses of the product see appendix of the safety data sheet.

1.3. Details of the supplier of the safety data sheet

Company: **BASF SE** 67056 Ludwigshafen **GERMANY**

Contact address: BASF Italia S.p.A. Via Marconato 8 20811 Cesano Maderno (MB)

ITALY

Telephone: +39 0362 512-1

E-mail address: Sicurezzaprodotti.BASF-Italia@basf.com

1.4. Emergency telephone number

International emergency number: Telephone: +49 180 2273-112

CAV "Osp. Pediatrico Bambino Gesù" Az. Osp. Univ. Foggia

Roma 06 68593726 Foggia 800183459

to Regulation (EC) No 1907/2006.

Date / Revised: 13.12.2023 Version: 1.0
Date / Previous version: not applicable Previous version: none

Product: METHOXYPROPYLACETATE

(ID no. 30034751/SDS_GEN_IT/EN)

Date of print 21.10.2025

Az. Osp. "A. Cardarelli"

CAV Policlinico "Umberto I"

CAV Policlinico "A. Gemelli"

Napoli 081-5453333

Roma 06-49978000

Roma 06-3054343

Az. Osp. "Careggi" U.O. Tossicologia Medica Firenze 055-7947819 CAV Centro Nazionale di Informazione Tossicologica Pavia 0382-24444 Osp. Niguarda Ca' Granda Milano 02-66101029

Azienda Ospedaliera Papa Giovanni XXII Bergamo 800883300

Azienda Ospedaliera Integrata Verona Verona 800011858

SECTION 2: Hazards Identification

2.1. Classification of the substance or mixture

According to Regulation (EC) No 1272/2008 [CLP]

Flam. Liq. 3 H226 Flammable liquid and vapour. STOT SE 3 H336 May cause drowsiness or dizziness.

For the classifications not written out in full in this section the full text can be found in section 16.

2.2. Label elements

According to Regulation (EC) No 1272/2008 [CLP]

Pictogram:





Signal Word:

Warning

Hazard Statement:

H226 Flammable liquid and vapour.H336 May cause drowsiness or dizziness.

Precautionary Statements (Prevention):

P271 Use only outdoors or in a well-ventilated area.

P210 Keep away from heat, hot surfaces, sparks, open flames and other

ignition sources. No smoking.

P280 Wear protective gloves and eye protection or face protection.

Precautionary Statements (Response):

P312 Call a POISON CENTER or physician if you feel unwell.

Precautionary Statements (Storage):

P233 Keep container tightly closed.

Precautionary Statements (Disposal):

P501 Dispose of contents and container to hazardous or special waste

collection point.

Date / Revised: 13.12.2023

Version: 1.0 Previous version: none

Date / Previous version: not applicable Product: **METHOXYPROPYLACETATE**

(ID no. 30034751/SDS_GEN_IT/EN)

Date of print 21.10.2025

2.3. Other hazards

According to Regulation (EC) No 1272/2008 [CLP]

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture. See section 12 - Results of PBT and vPvB assessment.

Product does not contain a substance above legal limits included in the list established in accordance with Article 59(1) of Regulation (EC) No 1907/2006 for having endocrine disrupting properties or is identified to have endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

SECTION 3: Composition/Information on Ingredients

3.1. Substances

Chemical nature

2-methoxy-1-methylethyl acetate

Content (W/W): >= 99,5 % Flam. Liq. 3

CAS Number: 108-65-6 STOT SE 3 (drowsiness and dizziness)

EC-Number: 203-603-9 H226, H336

INDEX-Number: 607-195-00-7

stabilized with:

2,6-di-tert-Butyl-p-cresol

Aquatic Acute 1
CAS Number: 128-37-0
EC-Number: 204-881-4
Aquatic Chronic 1
M-factor chronic: 1
H400, H410

Regulatory relevant ingredients

2-methoxy-1-methylethyl acetate

Content (W/W): >= 99,5 % - < 100 Flam. Liq. 3

% STOT SE 3 (drowsiness and dizziness)

CAS Number: 108-65-6 H226, H336

EC-Number: 203-603-9 INDEX-Number: 607-195-00-7

2-methoxypropyl acetate

Content (W/W): >= 0 % - < 0.3 % Flam. Liq. 3

CAS Number: 70657-70-4 Repr. 1B (unborn child)

EC-Number: 274-724-2 STOT SE 3 (irr. to respiratory syst.)

INDEX-Number: 607-251-00-0 H226, H335, H360D

Date / Revised: 13.12.2023

Version: 1.0 Previous version: none

Date / Previous version: not applicable Product: **METHOXYPROPYLACETATE**

(ID no. 30034751/SDS_GEN_IT/EN)

Date of print 21.10.2025

For the classifications not written out in full in this section, including the hazard classes and the hazard statements, the full text is listed in section 16.

3.2. Mixtures

Not applicable

SECTION 4: First-Aid Measures

4.1. Description of first aid measures

First aid personnel should pay attention to their own safety. If the patient is likely to become unconscious, place and transport in stable sideways position (recovery position). Immediately remove contaminated clothing.

If inhaled:

Keep patient calm, remove to fresh air, seek medical attention.

On skin contact:

Wash thoroughly with soap and water

On contact with eyes:

Wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.

On ingestion:

Immediately rinse mouth and then drink 200-300 ml of water, seek medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms: Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11.

Hazards: Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11. (Further) symptoms and / or effects are not known so far

4.3. Indication of any immediate medical attention and special treatment needed

Treatment: Treat according to symptoms (decontamination, vital functions), no known specific antidote.

SECTION 5: Fire-Fighting Measures

5.1. Extinguishing media

Suitable extinguishing media:

dry powder, water spray, carbon dioxide, alcohol-resistant foam

Date / Revised: 13.12.2023 Version: 1.0
Date / Previous version: not applicable Previous version: none

Product: METHOXYPROPYLACETATE

(ID no. 30034751/SDS_GEN_IT/EN)

Date of print 21.10.2025

Unsuitable extinguishing media for safety reasons: water jet

Additional information:

Use extinguishing measures to suit surroundings.

5.2. Special hazards arising from the substance or mixture

Advice: Flammable liquid Cool endangered containers with water-spray. See SDS section 7 - Handling and storage.

5.3. Advice for fire-fighters

Special protective equipment:

Wear a self-contained breathing apparatus. Special protective equipment for firefighters

Further information:

Evacuate area of all unnecessary personnel. Fight fire from maximum distance.

Extend fire extinguishing measures to the surroundings. Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

SECTION 6: Accidental Release Measures

High risk of slipping due to leakage/spillage of product.

Release of substance/product can cause fire or explosion. Shut off or stop source of leak. Shut off or stop released substance/product under safe conditions.

Pack in tightly closed containers for disposal.

6.1. Personal precautions, protective equipment and emergency procedures

Handle in accordance with good industrial hygiene and safety practice.

Avoid all sources of ignition: heat, sparks, open flame. Use antistatic tools.

6.2. Environmental precautions

Discharge into the environment must be avoided.

6.3. Methods and material for containment and cleaning up

Pick up with suitable appliance and dispose of. Spills should be contained, solidified, and placed in suitable containers for disposal. Dispose of absorbed material in accordance with regulations.

Date / Revised: 13.12.2023
Date / Previous version: not applicable

Wersion: 1.0 tapplicable Previous version: none

Product: METHOXYPROPYLACETATE

(ID no. 30034751/SDS_GEN_IT/EN)

Date of print 21.10.2025

6.4. Reference to other sections

Information regarding exposure controls/personal protection and disposal considerations can be found in section 8 and 13.

SECTION 7: Handling and Storage

7.1. Precautions for safe handling

Handle in accordance with good industrial hygiene and safety practice.

Protection against fire and explosion:

Prevent electrostatic charge - sources of ignition should be kept well clear - fire extinguishers should be kept handy.

7.2. Conditions for safe storage, including any incompatibilities

Unsuitable materials for containers: Low density polyethylene (LDPE), Paper/Fibreboard Further information on storage conditions: Containers should be stored tightly sealed in a dry place.

7.3. Specific end use(s)

See exposure scenario(s) in the attachment to this safety data sheet.

SECTION 8: Exposure Controls/Personal Protection

8.1. Control parameters

Components with occupational exposure limits

108-65-6: 2-methoxy-1-methylethyl acetate

STEL value 550 mg/m3; 100 ppm (OEL (EU))

indicative

Skin Designation (OEL (EU))

The substance can be absorbed through the skin. TWA value 275 mg/m3; 50 ppm (OEL (EU))

indicative

TWA value 275 mg/m3; 50 ppm (OEL (IT))

Skin Designation (OEL (IT))
Danger of cutaneous absorption
Skin Designation (OEL (IT))
Danger of cutaneous absorption

STEL value 550 mg/m3; 100 ppm (OEL (IT))

Ceiling limit value/factor: 15 min

PNEC

freshwater: 0,635 mg/l

marine water: 0,0635 mg/l

to Regulation (EC) No 1907/2006.

Date / Revised: 13.12.2023 Version: 1.0
Date / Previous version: not applicable Previous version: none

Product: METHOXYPROPYLACETATE

(ID no. 30034751/SDS_GEN_IT/EN)

Date of print 21.10.2025

intermittent release: 6,35 mg/l

sediment (freshwater): 3,29 mg/kg

sediment (marine water): 0,329 mg/kg

soil: 0,29 mg/kg

STP: 100 mg/l

DNEL

worker:

Long-term exposure- systemic effects, Inhalation: 275 mg/m3

worker:

Long-term exposure- systemic effects, dermal: 796 mg/kg

consumer:

Long-term exposure- systemic effects, oral: 36 mg/kg

consumer:

Long-term exposure - systemic and local effects, Inhalation: 33 mg/m3

consumer:

Long-term exposure- systemic effects, dermal: 320 mg/kg

worker:

Short-term exposure - local effects, Inhalation: 550 mg/m3

consumer:

Short-term exposure - systemic effects, oral: 500 mg/kg

8.2. Exposure controls

Personal protective equipment

Respiratory protection:

Wear respiratory protection if ventilation is inadequate. Gas filter for gases/vapours of organic compounds (boiling point >65 °C, e. g. EN 14387 Type A)

Hand protection:

Chemical resistant protective gloves (EN ISO 374-1)

Date / Revised: 13.12.2023 Version: 1.0
Date / Previous version: not applicable Previous version: none

Product: METHOXYPROPYLACETATE

(ID no. 30034751/SDS_GEN_IT/EN)

Date of print 21.10.2025

Suitable materials also with prolonged, direct contact (Recommended: Protective index 6, corresponding > 480 minutes of permeation time according to EN ISO 374-1):

butyl rubber (butyl) - 0.7 mm coating thickness

Suitable materials for short-term contact (recommended: At least protective index 2, corresponding > 30 minutes of permeation time according to EN ISO 374-1)

chloroprene rubber (CR) - 0.5 mm coating thickness

nitrile rubber (NBR) - 0.4 mm coating thickness

Manufacturer's directions for use should be observed because of great diversity of types. Supplementary note: The specifications are based on tests, literature data and information of glove manufacturers or are derived from similar substances by analogy. Due to many conditions (e.g. temperature) it must be considered, that the practical usage of a chemical-protective glove in practice may be much shorter than the permeation time determined through testing.

Eye protection:

Safety glasses with side-shields (frame goggles) (e.g. EN 166)

Body protection:

Body protection must be chosen depending on activity and possible exposure, e.g. apron, protecting boots, chemical-protection suit (according to EN 14605 in case of splashes or EN ISO 13982 in case of dust).

General safety and hygiene measures

Avoid contact with eyes. Wearing of closed work clothing is required additionally to the stated personal protection equipment.

Environmental exposure controls

All appropriate measures must be taken to prevent the release of this product to the environment and to limit the dispersion of any release when it occurs. Suitable risk management measures should be in place.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

State of matter: liquid
Form: liquid
Colour: colourless
Odour: ether-like

Odour threshold:

not determined

Melting point: -66 °C (measured)

(1.013,25 hPa) Literature data.

Boiling point: 145,8 °C (OECD Guideline 103)

(1.013,25 hPa) Extrapolated value

Flammability: Flammable. (derived from flash point)

Date / Revised: 13.12.2023 Version: 1.0 Date / Previous version: not applicable Previous version: none

Product: METHOXYPROPYLACETATE

(ID no. 30034751/SDS_GEN_IT/EN)

Date of print 21.10.2025

Lower explosion limit:

For liquids not relevant for classification and labelling., The lower explosion point may be 5 - 15

°C below the flash point.

Upper explosion limit:

For liquids not relevant for classification and labelling.

Flash point: 45,5 °C (ASTM D3278, closed cup)

Auto-ignition temperature: (DIN 51794)

Thermal decomposition: No decomposition if stored and handled as prescribed/indicated.

pH value:

not applicable

1,23 mm2/s Viscosity, kinematic: (DIN 51562)

(20 °C)

Thixotropy: not thixotropic

Solubility in water: (Directive 92/69/EEC, A.6)

198 g/l

(20 °C, pH 6,8)

Solubility (qualitative) solvent(s): organic solvents

soluble

Partitioning coefficient n-octanol/water (log Kow): 1,2 (OECD Guideline 117)

(20 °C; pH value: 6,8)

3,5997 hPa Vapour pressure: (OECD Guideline 104)

> (20 °C) dynamic

Relative density: 0,967 (DIN 51757)

(20 °C, 1.013 hPa)

Density: 0,9677 g/cm3

(20 °C, 1.013 hPa) Literature data.

0,9286 g/cm3 (calculated)

(55 °C)

Relative vapour density (air):4,55 (calculated)

(20 °C)

Heavier than air.

9.2. Other information

Information with regard to physical hazard classes

Explosives

Based on the chemical structure Explosion hazard:

there is no indication of explosive

properties.

Impact sensitivity: not shock-sensitive

Based on the chemical structure there is no shock-sensitivity.

Oxidizing properties

Fire promoting properties: Based on its structural properties

the product is not classified as

oxidizing.

to Regulation (EC) No 1907/2006.

Date / Revised: 13.12.2023 Version: 1.0
Date / Previous version: not applicable Previous version: none

Product: METHOXYPROPYLACETATE

(ID no. 30034751/SDS_GEN_IT/EN)

Date of print 21.10.2025

Flammable liquids

Sustained combustibility:

not determined

Pyrophoric properties

Self-ignition temperature: Test type: Spontaneous self-ignition at room-temperature.

Based on its structural properties the product is not classified as self-

(calculated)

igniting.

Self-heating substances and mixtures

Self heating ability: It is not a substance capable of

spontaneous heating.

Substances and mixtures, which emit flammable gases in contact with water

Formation of flammable gases:

Forms no flammable gases in the presence of water.

Corrosion to metals

No corrosive effect on metal.

Other safety characteristics

pKA:

The substance does not dissociate.

Adsorption/water - soil: KOC: 3,998; log KOC: 0,6

The data refer to the uncharged form

of the substance.

Surface tension:

Based on chemical structure, surface

activity is not to be expected.

Molar mass: 132,16 g/mol

SAPT-Temperature:

Study scientifically not justified.

Evaporation rate:

Value can be approximated from Henry's Law Constant or vapor

pressure.

SECTION 10: Stability and Reactivity

10.1. Reactivity

When heated can give off ignitable vapours.

Corrosion to metals: No corrosive effect on metal.

Formation of Remarks: Forms no flammable gases in the

flammable gases: presence of water.

Date / Revised: 13.12.2023 Version: 1.0
Date / Previous version: not applicable Previous version: none

Product: METHOXYPROPYLACETATE

(ID no. 30034751/SDS_GEN_IT/EN)

Date of print 21.10.2025

10.2. Chemical stability

The product is stable if stored and handled as prescribed/indicated.

10.3. Possibility of hazardous reactions

Reacts with strong oxidizing agents.

10.4. Conditions to avoid

No special precautions other than good housekeeping of chemicals.

10.5. Incompatible materials

Substances to avoid: strong oxidizing agents

10.6. Hazardous decomposition products

Hazardous decomposition products:

No hazardous decomposition products if stored and handled as prescribed/indicated.

SECTION 11: Toxicological Information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Assessment of acute toxicity:

Virtually nontoxic after a single ingestion. Virtually nontoxic by inhalation. Virtually nontoxic after a single skin contact.

Experimental/calculated data:

LD50 rat (oral): > 5.000 mg/kg (similar to OECD guideline 401)

LC50 rat (by inhalation): > 23,5 mg/l > 4345 ppm 6 h (similar to OECD guideline 403)

No mortality was observed. The vapour was tested.

LD50 rat (dermal): > 2.000 mg/kg (similar to OECD guideline 402)

No mortality was observed.

LD50 rabbit (dermal): > 5.000 mg/kg (similar to OECD guideline 402)

No mortality was observed.

<u>Irritation</u>

Assessment of irritating effects:

Not irritating to the skin. Not irritating to the eyes.

Experimental/calculated data:

Skin corrosion/irritation

rabbit: non-irritant (similar to OECD guideline 404)

Date / Revised: 13.12.2023 Version: 1.0
Date / Previous version: not applicable Previous version: none

Product: METHOXYPROPYLACETATE

(ID no. 30034751/SDS_GEN_IT/EN)

Date of print 21.10.2025

Serious eye damage/irritation

rabbit: non-irritant (similar to OECD guideline 405)

Respiratory/Skin sensitization

Assessment of sensitization:

Skin sensitizing effects were not observed in animal studies.

Experimental/calculated data:

Guinea pig maximization test guinea pig: Non-sensitizing. (OECD Guideline 406)

Germ cell mutagenicity

Assessment of mutagenicity:

The substance was not mutagenic in bacteria. The substance was not mutagenic in mammalian cell culture. The substance was not genotoxic in mammalian cell culture.

Carcinogenicity

Assessment of carcinogenicity:

In long-term studies in rats and mice in which the substance was given by inhalation, a carcinogenic effect was not observed. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Reproductive toxicity

Assessment of reproduction toxicity:

The results of animal studies gave no indication of a fertility impairing effect. The product has not been fully tested. The statements have been derived in parts from products of a similar structure or composition.

Developmental toxicity

Assessment of teratogenicity:

No indications of a developmental toxic / teratogenic effect were seen in animal studies.

Specific target organ toxicity (single exposure)

Assessment of STOT single:

Possible narcotic effects (drowsiness or dizziness).

Repeated dose toxicity and Specific target organ toxicity (repeated exposure)

Assessment of repeated dose toxicity:

Repeated dermal uptake of the substance did not cause substance-related effects. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition. The substance may cause damage to the olfactory epithelium after repeated inhalation. Repeated oral uptake of the substance did not cause substance-related effects.

Aspiration hazard

No aspiration hazard expected.

Date / Revised: 13.12.2023 Version: 1.0
Date / Previous version: not applicable Previous version: none

Product: METHOXYPROPYLACETATE

(ID no. 30034751/SDS_GEN_IT/EN)

Date of print 21.10.2025

Interactive effects

No data available.

11.2. Information on other hazards

Endocrine disrupting properties

The substance is not identified to have endocrine disrupting properties according to Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 nor is included in the Candidate List of substances of very high concern according to EU REACh Article 59 for having endocrine disrupting properties.

SECTION 12: Ecological Information

12.1. Toxicity

Assessment of aquatic toxicity:

There is a high probability that the product is not acutely harmful to aquatic organisms. The inhibition of the degradation activity of activated sludge is not anticipated when introduced to biological treatment plants in appropriate low concentrations.

Toxicity to fish:

LC50 (96 h) 134 mg/l, Oncorhynchus mykiss (OECD Guideline 203, static)

The details of the toxic effect relate to the nominal concentration.

Aquatic invertebrates:

EC50 (48 h) > 500 mg/l, Daphnia magna (Daphnia test acute, semistatic)

The details of the toxic effect relate to the nominal concentration.

Aquatic plants:

EC50 (72 h) > 1.000 mg/l (growth rate), Selenastrum capricornutum (OECD Guideline 201, static) The details of the toxic effect relate to the nominal concentration.

Microorganisms/Effect on activated sludge:

EC10 (30 min) > 1.000 mg/l, activated sludge, industrial (DIN EN ISO 8192-OECD 209-88/302/EEC,P. C, aerobic)

The details of the toxic effect relate to the nominal concentration.

Chronic toxicity to fish:

No observed effect concentration (14 d) 47,5 mg/l, Oryzias latipes (OECD Guideline 204, Flow through.)

The details of the toxic effect relate to the nominal concentration.

Chronic toxicity to aquatic invertebrates:

No observed effect concentration (21 d) >= 100 mg/l, Daphnia magna (OECD Guideline 202, part 2, semistatic)

Assessment of terrestrial toxicity:

Date / Revised: 13.12.2023 Version: 1.0
Date / Previous version: not applicable Previous version: none

Product: METHOXYPROPYLACETATE

(ID no. 30034751/SDS_GEN_IT/EN)

Date of print 21.10.2025

No data available concerning terrestrial toxicity.

12.2. Persistence and degradability

Assessment biodegradation and elimination (H2O): Readily biodegradable (according to OECD criteria).

Elimination information:

83 % BOD of the ThOD (28 d) (OECD 301F; ISO 9408; 92/69/EWG, C.4-D) (aerobic, activated sludge, domestic, non-adapted)

Assessment of stability in water:

In contact with water the substance will hydrolyse slowly.

Information on Stability in Water (Hydrolysis): $t_{1/2} > 1$ a (25 °C, pH value7), (OECD Guideline 111, pH 7)

12.3. Bioaccumulative potential

Assessment bioaccumulation potential:

Because of the n-octanol/water distribution coefficient (log Pow) accumulation in organisms is not to be expected.

Bioaccumulation potential:

No data available.

12.4. Mobility in soil

Assessment transport between environmental compartments:

Volatility: The substance will slowly evaporate into the atmosphere from the water surface.

Adsorption in soil: Adsorption to solid soil phase is not expected.

12.5. Results of PBT and vPvB assessment

According to Annex XIII of Regulation (EC) No.1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH): The product does not fulfill the criteria for PBT (Persistent/bioaccumulative/toxic) and vPvB (very persistent/very bioaccumulative). Self classification

12.6. Endocrine disrupting properties

The substance is not identified to have endocrine disrupting properties according to Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 nor is included in the Candidate List of substances of very high concern according to EU REACh Article 59 for having endocrine disrupting properties.

to Regulation (EC) No 1907/2006.

Date / Revised: 13.12.2023 Version: 1.0 Date / Previous version: not applicable Previous version: none

Product: METHOXYPROPYLACETATE

(ID no. 30034751/SDS_GEN_IT/EN)

Date of print 21.10.2025

12.7. Other adverse effects

The substance is not listed in Regulation (EC) 1005/2009 on substances that deplete the ozone layer.

12.8. Additional information

Adsorbable organically-bound halogen (AOX): This product contains no organically-bound halogen.

SECTION 13: Disposal Considerations

13.1. Waste treatment methods

Must be disposed of or incinerated in accordance with local regulations.

Contaminated packaging:

Contaminated packaging should be emptied as far as possible; then it can be passed on for recycling after being thoroughly cleaned.

SECTION 14: Transport Information

Land transport

ADR

UN number or ID number: UN1993

UN proper shipping name: FLAMMABLE LIQUID, N.O.S. (2-METHOXY-1-METHYLETHYL

ACETATE)

Transport hazard class(es): 3 Ш Packing group: Environmental hazards: no

Special precautions for Tunnel code: D/E

user:

RID

UN number or ID number: UN1993

UN proper shipping name: FLAMMABLE LIQUID, N.O.S. (2-METHOXY-1-METHYLETHYL

ACETATE)

Transport hazard class(es): 3 Ш Packing group: Environmental hazards: no

Special precautions for None known

Date / Revised: 13.12.2023 Version: 1.0
Date / Previous version: not applicable Previous version: none

Product: METHOXYPROPYLACETATE

(ID no. 30034751/SDS_GEN_IT/EN)

Date of print 21.10.2025

user:

Inland waterway transport

ADN

UN number or ID number: UN1993

UN proper shipping name: FLAMMABLE LIQUID, N.O.S. (2-METHOXY-1-METHYLETHYL

ACETATE)

Transport hazard class(es): 3
Packing group: III
Environmental hazards: no

Special precautions for

None known

user:

Transport in inland waterway vessel

UN number or ID number: UN1993

UN proper shipping name: FLAMMABLE LIQUID, N.O.S. (2-METHOXY-1-METHYLETHYL

ACETATE)

Transport hazard class(es): 3
Packing group: III
Environmental hazards: no
Type of inland waterway N

vessel:

Cargo tank design: 3 Cargo tank type: 2

Sea transport

IMDG

UN number or ID number: UN 1993

UN proper shipping name: FLAMMABLE LIQUID, N.O.S. (2-METHOXY-1-METHYLETHYL

ACETATE)

Transport hazard class(es): 3
Packing group: III
Environmental hazards: no

Marine pollutant: NO

Special precautions for

user:

EmS: F-E; S-E

Air transport

Date / Revised: 13.12.2023 Version: 1.0
Date / Previous version: not applicable Previous version: none

Product: METHOXYPROPYLACETATE

(ID no. 30034751/SDS_GEN_IT/EN)

Date of print 21.10.2025

IATA/ICAO

UN number or ID number: UN 1993

UN proper shipping name: FLAMMABLE LIQUID, N.O.S. (2-METHOXY-1-METHYLETHYL

ACETATE)

Transport hazard class(es): 3 Packing group: III

Environmental hazards: No Mark as dangerous for the environment is needed

Special precautions for None known

user:

14.1. UN number or ID number

See corresponding entries for "UN number or ID number" for the respective regulations in the tables above.

14.2. UN proper shipping name

See corresponding entries for "UN proper shipping name" for the respective regulations in the tables above.

14.3. Transport hazard class(es)

See corresponding entries for "Transport hazard class(es)" for the respective regulations in the tables above.

14.4. Packing group

See corresponding entries for "Packing group" for the respective regulations in the tables above.

14.5. Environmental hazards

See corresponding entries for "Environmental hazards" for the respective regulations in the tables above.

14.6. Special precautions for user

See corresponding entries for "Special precautions for user" for the respective regulations in the tables above.

14.7. Maritime transport in bulk according to IMO instruments

Regulation: IBC-Code

Product name: Propylene glycol methyl ether acetate

Pollution category: Z Ship Type: 3

Date / Revised: 13.12.2023

Version: 1.0 Date / Previous version: not applicable Previous version: none

Product: METHOXYPROPYLACETATE

(ID no. 30034751/SDS_GEN_IT/EN)

Date of print 21.10.2025

SECTION 15: Regulatory Information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Prohibitions, Restrictions and Authorizations

Annex XVII of Regulation (EC) No 1907/2006: Number on List: 3, 40

Directive 2012/18/EU - Control of Major Accident Hazards involving dangerous substances (EU):

List entry in regulation: P5a List entry in regulation: P5b List entry in regulation: P5c

Regulations (Italy): 1) 1272/2008/CE Regulation and subsequent amendments; 2) 2012/18/EU Directive (Seveso III) and Legislative Decree 105/2015; 3) Legislative Decree 81/2008 and

Legislative Decree 152/2006.

15.2. Chemical Safety Assessment

Chemical Safety Assessment performed

SECTION 16: Other Information

Assessment of the hazard classes according to UN GHS criteria (most recent version)

Flam. Liq. 3

STOT SE 3 (May cause drowsiness and dizziness.)

Full text of the classifications, including the hazard classes and the hazard statements, if mentioned

in section 2 or 3:

Flam. Liq. Flammable liquids

STOT SE Specific target organ toxicity — single exposure

Reproductive toxicity Repr.

Flammable liquid and vapour. H226 H336 May cause drowsiness or dizziness. H335 May cause respiratory irritation. H360D May damage the unborn child.

Abbreviations

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road. ADN = The European Agreement concerning the International Carriage of Dangerous Goods by Inland waterways. ATE = Acute Toxicity Estimates. CAO = Cargo Aircraft Only. CAS = Chemical Abstract Service. CLP = Classification, Labelling and Packaging of substances and mixtures. DIN = German national organization for standardization. DNEL = Derived No Effect Level. EC50 = Effective concentration median for 50% of the population. EC = European Community. EN = European Standards. IARC = International Agency for Research on Cancer. IATA = International Air Transport Association. IBC-Code = Intermediate Bulk Container code. IMDG = International Maritime Dangerous Goods Code. ISO = International Organization for Standardization. STEL = Short-Term Exposure Limit. LC50 = Lethal

Date / Revised: 13.12.2023 Version: 1.0
Date / Previous version: not applicable Previous version: none

Product: METHOXYPROPYLACETATE

(ID no. 30034751/SDS_GEN_IT/EN)

Date of print 21.10.2025

concentration median for 50% of the population. LD50 = Lethal dose median for 50% of the population. TLV = Threshold Limit Value. MARPOL = The International Convention for the Prevention of Pollution from Ships. NEN = Dutch Norm. NOEC = No Observed Effect Concentration. OEL = Occupational Exposure Limit. OECD = Organization for Economic Cooperation and Development. PBT = Persistent, Bioaccumulative and Toxic. PNEC = Predicted No Effect Level. PPM = Parts per million. RID = The European Agreement concerning the International Carriage of Dangerous Goods by Rail. TWA = Time Weight Average. UN-number = UN number at transport. vPvB = very Persistent and very Bioaccumulative.

The data contained in this safety data sheet are based on our current knowledge and experience and describe the product only with regard to safety requirements. This safety data sheet is neither a Certificate of Analysis (CoA) nor technical data sheet and shall not be mistaken for a specification agreement. Identified uses in this safety data sheet do neither represent an agreement on the corresponding contractual quality of the substance/mixture nor a contractually designated use. It is the responsibility of the recipient of the product to ensure any proprietary rights and existing laws and legislation are observed.

Vertical lines in the left hand margin indicate an amendment from the previous version.

Date / Revised: 13.12.2023 Version: 1.0
Date / Previous version: not applicable Previous version: none

Product: METHOXYPROPYLACETATE

(ID no. 30034751/SDS_GEN_IT/EN)

Date of print 21.10.2025

Annex: Exposure Scenarios

Index

1. Manufacture of substance

ERC1; PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC9, PROC15, PROC28

2. Use as a Process chemical

ERC4; PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC15, PROC28

3. Formulation & (re)packing of substances and mixtures

ERC2; PROC1, PROC2, PROC3, PROC4, PROC5, PROC8a, PROC8b, PROC9, PROC14, PROC28

4. Use in Coatings, (use in industrial settings)

ERC4; PROC1, PROC2, PROC3, PROC4, PROC5, PROC7, PROC8a, PROC8b, PROC9, PROC10, PROC13, PROC14, PROC15, PROC28

5. Use in Coatings, (use in professional settings)

ERC8a, ERC8d; PROC1, PROC2, PROC3, PROC4, PROC5, PROC8a, PROC8b, PROC9, PROC10, PROC11, PROC13, PROC14, PROC15, PROC19, PROC28

6. Use in Coatings, (consumer use)

ERC8a, ERC8d; PC9a, PC18

7. Cleaning agents, (use in industrial settings)

ERC4; PROC1, PROC2, PROC3, PROC4, PROC7, PROC8a, PROC8b, PROC10, PROC13, PROC28

8. Cleaning agents, (use in professional settings)

ERC8a, ERC8d; PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC10, PROC11, PROC13, PROC19

9. Cleaning agents, (consumer use)

ERC8a, ERC8d; PC35

10.Use in Agrochemicals, (use in professional settings)

ERC8a, ERC8d; PROC1, PROC2, PROC4, PROC8a, PROC8b, PROC11, PROC13, PROC28

11. Use in Agrochemicals, (consumer use)

ERC8a, ERC8d; PC27

12.Use in Printing inks, (use in industrial settings)

ERC4; PROC1, PROC2, PROC3, PROC4, PROC5, PROC7, PROC8a, PROC8b, PROC9, PROC10, PROC13, PROC15, PROC28

13. Use in Coatings, (coil), (use in industrial settings)

ERC4; PROC1, PROC2, PROC3, PROC4, PROC5, PROC7, PROC8a, PROC8b, PROC9, PROC10, PROC13, PROC15, PROC28

* * * * * * * * * * * * * * * *

Date / Revised: 13.12.2023

Version: 1.0 Date / Previous version: not applicable Previous version: none

Product: METHOXYPROPYLACETATE

(ID no. 30034751/SDS_GEN_IT/EN)

Date of print 21.10.2025

1. Short title of exposure scenario

Manufacture of substance

ERC1; PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC9, PROC15, PROC28

Control of exposure and risk management measures

Contributing exposure scenario		
Use descriptors covered	ESVOC SpERC 1.1.o.v2	
Operational conditions		
Annual amount used in the EU	25.000.000 kg	
Minimum emission days per year	300	
Emission factor air	1 %	
Emission factor water	1 %	
Emission factor soil	0,01 %	
Receive Surf. Water (Flow Rate).	43.541 m3/min	
Dilution factor river	187,67	
Dilution factor coast	100	
Risk Management Measures		
		No application of sludge to soil
Type of STP		Municipal STP
Assumed sewage treatment plant flow (m3/d)		335.890 m3/d
Exposure estimate and reference to its source		
Assessment method		
Risk Characterization Ratio (RCR)	0,134997	
	Risk from environmental exposure is driven by soil.	
	617.299,9	
Maximum amount of safe use	kg/d	
Risk from environmental exposure is driven by soil.		

Contributing exposure scenario	
Use descriptors covered	PROC1: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions. Use domain: industrial
Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 100 %

Date / Revised: 13.12.2023 Version: 1.0
Date / Previous version: not applicable Previous version: none

Product: METHOXYPROPYLACETATE

(ID no. 30034751/SDS_GEN_IT/EN)

Date of print 21.10.2025

Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Exposure estimate and reference to	its source
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	0,0343 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,000043
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	0,0551 mg/m ³
Risk Characterization Ratio (RCR)	0,0002
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/	/tra

Contributing exposure scenario	
Use descriptors covered	PROC2: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions Use domain: industrial
Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Exposure estimate and reference to	its source
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	1,3714 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,001723
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	27,5312 mg/m³
Risk Characterization Ratio (RCR)	0,100114
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	

Date / Revised: 13.12.2023

Version: 1.0 Date / Previous version: not applicable Previous version: none

Product: METHOXYPROPYLACETATE

(ID no. 30034751/SDS_GEN_IT/EN)

Date of print 21.10.2025

For scaling see: http://www.ecetoc.org/tra

Contributing exposure scenario	
Use descriptors covered	PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition Use domain: industrial
Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Exposure estimate and reference to	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	0,6857 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,000861
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	55,0625 mg/m³
Risk Characterization Ratio (RCR)	0,200227
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/	ira

Contributing exposure scenario	
Use descriptors covered	PROC4: Chemical production where opportunity for exposure arises Use domain: industrial
Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 13.12.2023
Date / Previous version: not applicable

Product: METHOXYPROPYLACETATE

(ID no. 30034751/SDS_GEN_IT/EN)

Date of print 21.10.2025

Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	6,8571 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,008615
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	110,125 mg/m³
Risk Characterization Ratio (RCR)	0,400455
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC8a: Transfer of substance or mixture (charging and discharging) at non-dedicated facilities Use domain: industrial
Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Risk Management Measures	
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %
Exposure estimate and reference to	its source
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	13,7143 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,017229
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	192,7187 mg/m³
Risk Characterization Ratio (RCR)	0,700795
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/	tra

Contributing exposure scenario	
Use descriptors covered	PROC8b: Transfer of substance or mixture (charging and
	discharging) at dedicated facilities

Date / Revised: 13.12.2023 Version: 1.0
Date / Previous version: not applicable Previous version: none

Product: METHOXYPROPYLACETATE

(ID no. 30034751/SDS_GEN_IT/EN)

Date of print 21.10.2025

	Use domain: industrial
Operational conditions	
	2-methoxy-1-methylethyl acetate
Concentration of the substance	Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Exposure estimate and reference to	its source
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	13,7143 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,017229
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	137,6562 mg/m³
Risk Characterization Ratio (RCR)	0,500568
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/t	ra

Contributing exposure scenario		
Use descriptors covered	PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing). Use domain: industrial	
Operational conditions		
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 100 %	
Physical state	liquid	
Vapour pressure of the substance during use	502 Pa	
Duration and Frequency of activity	480 min 5 days per week	
Indoor/Outdoor	Indoor	
	Assumes activities are at ambient temperature.	
Risk Management Measures		
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %	
Exposure estimate and reference to its source		
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker	
	Worker - dermal, long-term - systemic	

Date / Revised: 13.12.2023

Version: 1.0 Previous version: none

Date / Previous version: not applicable Product: METHOXYPROPYLACETATE

(ID no. 30034751/SDS_GEN_IT/EN)

Date of print 21.10.2025

Exposure estimate	6,8571 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,008615
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	192,7187 mg/m³
Risk Characterization Ratio (RCR)	0,700795
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org	/tra

Contributing exposure scenario	
	PROC15: Use a laboratory reagent.
Use descriptors covered	Use domain: industrial
Operational conditions	1
	2-methoxy-1-methylethyl acetate
Concentration of the substance	Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Exposure estimate and reference to	its source
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	0,3429 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,000431
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	55,0625 mg/m³
Risk Characterization Ratio (RCR)	0,200227
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/	'tra

Contributing exposure scenario	
Use descriptors covered	PROC28: Manual maintenance (cleaning and repair) of machinery covered by PROC8a

* * * * * * * * * * * * * * * *

2. Short title of exposure scenario

Use as a Process chemical

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 13.12.2023
Date / Previous version: not applicable

Product: METHOXYPROPYLACETATE

(ID no. 30034751/SDS_GEN_IT/EN)

Date of print 21.10.2025

Previous version: none

ERC4; PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC15, PROC28

Control of exposure and risk management measures

Contributing exposure scenario		
Use descriptors covered	ESVOC SpERC 4.23.v1: ESVOC SpERC 4.23.v1	
Operational conditions		
Annual amount used in the EU	660.000 kg	
Minimum emission days per year	300	
Emission factor air	0,2 %	
Emission factor water	1 %	
Emission factor soil	0,01 %	
Receive Surf. Water (Flow Rate).	18.000 m3/d	
Dilution factor river	10	
Dilution factor coast	100	
Risk Management Measures		
Type of STP	Municipal STP	
Assumed sewage treatment plant flow ((m3/d) 2.000 m3/d	
Exposure estimate and reference to its source		
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Environment	
Risk Characterization Ratio (RCR)	0,433591	
	Risk from environmental exposure is driven by soil.	
	5.073,9	
Maximum amount of safe use	kg/d	
Risk from environmental exposure is driven by soil.		

Contributing exposure scenario	
Use descriptors covered	PROC1: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions. Use domain: industrial
Operational conditions	
	2-methoxy-1-methylethyl acetate
Concentration of the substance	Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance	502 Pa
during use	302 i d

Page: 28/115

Version: 1.0

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 13.12.2023
Date / Previous version: not applicable

Product: METHOXYPROPYLACETATE

(ID no. 30034751/SDS_GEN_IT/EN)

Date of print 21.10.2025

Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	0,0343 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,000043
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	0,0551 mg/m ³
Risk Characterization Ratio (RCR)	0,0002
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC2: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions Use domain: industrial
Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Exposure estimate and reference to	its source
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	1,3714 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,001723
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	27,5312 mg/m³
Risk Characterization Ratio (RCR)	0,100114
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/t	tra

Contributing exposure scenario	
Use descriptors covered	PROC3: Manufacture or formulation in the chemical

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 13.12.2023
Date / Previous version: not applicable

Product: METHOXYPROPYLACETATE

(ID no. 30034751/SDS_GEN_IT/EN)

Date of print 21.10.2025

	industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition Use domain: industrial
Operational conditions	
	2-methoxy-1-methylethyl acetate
Concentration of the substance	Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Exposure estimate and reference to	o its source
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	0,6857 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,000861
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	55,0625 mg/m³
Risk Characterization Ratio (RCR)	0,200227
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org	g/tra

Contributing exposure scenario	Contributing exposure scenario	
Use descriptors covered	PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition Use domain: industrial	
Operational conditions		
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 100 %	
Physical state	liquid	
Vapour pressure of the substance during use	502 Pa	
Duration and Frequency of activity	480 min 5 days per week	
Indoor/Outdoor	Indoor	
	Assumes activities are at ambient temperature.	
Exposure estimate and reference to its source		
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker	

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 13.12.2023 Date / Previous version: not applicable

Product: METHOXYPROPYLACETATE

(ID no. 30034751/SDS_GEN_IT/EN)

Date of print 21.10.2025

	Worker - dermal, long-term - systemic
Exposure estimate	0,6857 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,000861
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	55,0625 mg/m³
Risk Characterization Ratio (RCR)	0,200227
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC4: Chemical production where opportunity for exposure arises Use domain: industrial
Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Exposure estimate and reference to	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	6,8571 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,008615
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	110,125 mg/m³
Risk Characterization Ratio (RCR)	0,400455
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org	/tra

Contributing exposure scenario		
Use descriptors covered	PROC8a: Transfer of substance or mixture (charging and discharging) at non-dedicated facilities Use domain: industrial	
Operational conditions		
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 100 %	

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 13.12.2023
Date / Previous version: not applicable

Product: METHOXYPROPYLACETATE

(ID no. 30034751/SDS_GEN_IT/EN)

Date of print 21.10.2025

Physical state	liquid	
Vapour pressure of the substance	502 Pa	
during use		
Duration and Frequency of activity	480 min 5 days per week	
Indoor/Outdoor	Indoor	
	Assumes activities are at ambient temperature.	
Risk Management Measures		
Provide a good standard of general		
ventilation (not less than 3 - 5 air	Effectiveness: 30 %	
changes per hour)		
Exposure estimate and reference to its source		
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker	
	Worker - dermal, long-term - systemic	
Exposure estimate	13,7143 mg/kg bw/day	
Risk Characterization Ratio (RCR)	0,017229	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker	
	Worker - inhalation, long-term - systemic	
Exposure estimate	192,7187 mg/m³	
Risk Characterization Ratio (RCR)	0,700795	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker	
Guidance to Downstream Users		
For scaling see: http://www.ecetoc.org/t	ra	

Contributing exposure scenario	
Use descriptors covered	PROC8b: Transfer of substance or mixture (charging and discharging) at dedicated facilities Use domain: industrial
Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Exposure estimate and reference to	its source
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	13,7143 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,017229
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	137,6562 mg/m³
Risk Characterization Ratio (RCR)	0,500568

Date / Revised: 13.12.2023 Version: 1.0
Date / Previous version: not applicable Previous version: none

Product: METHOXYPROPYLACETATE

(ID no. 30034751/SDS_GEN_IT/EN)

Date of print 21.10.2025

Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tr	a

Contributing exposure scenario		
<u> </u>	PROC15: Use a laboratory reagent.	
Use descriptors covered	Use domain: industrial	
•		
Operational conditions		
	2-methoxy-1-methylethyl acetate	
Concentration of the substance	Content: >= 0 % - <= 100 %	
Physical state	liquid	
Vapour pressure of the substance	502 Pa	
during use		
Duration and Frequency of activity	480 min 5 days per week	
Indoor/Outdoor	Indoor	
	Assumes activities are at ambient temperature.	
Exposure estimate and reference to its source		
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker	
	Worker - dermal, long-term - systemic	
Exposure estimate	0,3429 mg/kg bw/day	
Risk Characterization Ratio (RCR)	0,000431	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker	
	Worker - inhalation, long-term - systemic	
Exposure estimate	55,0625 mg/m³	
Risk Characterization Ratio (RCR)	0,200227	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker	
Guidance to Downstream Users		
For scaling see: http://www.ecetoc.org	/tra	

Contributing exposure scenario	
Use descriptors covered	PROC28: Manual maintenance (cleaning and repair) of machinery covered by PROC8a

3. Short title of exposure scenario

Formulation & (re)packing of substances and mixtures ERC2; PROC1, PROC2, PROC3, PROC4, PROC5, PROC8a, PROC8b, PROC9, PROC14, PROC28

Control of exposure and risk management measures

Contributing exposure scenario	
Use descriptors covered	CEPE SPERC 2.1a.v2

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 13.12.2023
Date / Previous version: not applicable
Product: METHOXYPROPYLACETATE

(ID no. 30034751/SDS_GEN_IT/EN)

Date of print 21.10.2025

Operational conditions		
Annual amount used in the EU	25.000.000 kg	
Minimum emission days per year	225	
Emission factor air	1,8 %	
Emission factor water	0 %	
Emission factor soil	0 %	
Receive Surf. Water (Flow Rate).	18.000 m3/d	
Dilution factor river	10	
Dilution factor coast	100	
Risk Management Measures		
Type of STP		
Assumed sewage treatment plant flow	(m3/d)	2.000 m3/d
Exposure estimate and reference to	its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Environment	
Risk Characterization Ratio (RCR)	0,226704	
	Risk from environmental exposure is driven by soil.	
	490.115,3	
Maximum amount of safe use	kg/d	
Risk from environmental exposure is dr	iven by soil.	

Contributing exposure scenario	
Use descriptors covered	PROC1: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions. Use domain: industrial
Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Exposure estimate and reference to	o its source
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 13.12.2023 Date / Previous version: not applicable

Product: METHOXYPROPYLACETATE

(ID no. 30034751/SDS_GEN_IT/EN)

Date of print 21.10.2025

	Worker - dermal, long-term - systemic
Exposure estimate	0,0343 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,000043
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	0,0551 mg/m³
Risk Characterization Ratio (RCR)	0,0002
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/	tra

Contributing exposure scenario	
Use descriptors covered	PROC2: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions Use domain: industrial
Operational conditions	1
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Exposure estimate and reference to	o its source
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	1,3714 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,001723
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	27,5312 mg/m³
Risk Characterization Ratio (RCR)	0,100114
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org	g/tra

Contributing exposure scenario	
Use descriptors covered	PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition Use domain: industrial
Operational conditions	

Date / Revised: 13.12.2023 Version: 1.0
Date / Previous version: not applicable
Product: METHOXYPROPYLACETATE

(ID no. 30034751/SDS_GEN_IT/EN)

Date of print 21.10.2025

Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Exposure estimate and reference to	its source
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	0,6857 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,000861
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	55,0625 mg/m ³
Risk Characterization Ratio (RCR)	0,200227
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org	/tra

Contributing exposure scenario		
Use descriptors covered	PROC4: Chemical production where opportunity for exposure arises Use domain: industrial	
Operational conditions		
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 100 %	
Physical state	liquid	
Vapour pressure of the substance during use	502 Pa	
Duration and Frequency of activity	480 min 5 days per week	
Indoor/Outdoor	Indoor	
	Assumes activities are at ambient temperature.	
Exposure estimate and reference to its source		
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker	
	Worker - dermal, long-term - systemic	
Exposure estimate	6,8571 mg/kg bw/day	
Risk Characterization Ratio (RCR)	0,008615	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker	
	Worker - inhalation, long-term - systemic	
Exposure estimate	110,125 mg/m³	
Risk Characterization Ratio (RCR)	0,400455	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker	

Date / Revised: 13.12.2023 Version: 1.0
Date / Previous version: not applicable Previous version: none

Product: METHOXYPROPYLACETATE

(ID no. 30034751/SDS_GEN_IT/EN)

Date of print 21.10.2025

Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario		
Use descriptors covered	PROC5: Mixing or blending in batch processes Use domain: industrial	
Operational conditions		
	2-methoxy-1-methylethyl acetate	
Concentration of the substance	Content: >= 0 % - <= 100 %	
Physical state	liquid	
Vapour pressure of the substance during use	502 Pa	
Duration and Frequency of activity	480 min 5 days per week	
Indoor/Outdoor	Indoor	
	Assumes activities are at ambient temperature.	
Risk Management Measures		
Provide a good standard of general		
ventilation (not less than 3 - 5 air	Effectiveness: 30 %	
changes per hour)		
Exposure estimate and reference to its source		
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker	
	Worker - dermal, long-term - systemic	
Exposure estimate	13,7143 mg/kg bw/day	
Risk Characterization Ratio (RCR)	0,017229	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker	
	Worker - inhalation, long-term - systemic	
Exposure estimate	192,7187 mg/m ³	
Risk Characterization Ratio (RCR)	0,700795	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker	
Guidance to Downstream Users		
For scaling see: http://www.ecetoc.org/	′tra	

Contributing exposure scenario		
Use descriptors covered	PROC8a: Transfer of substance or mixture (charging and discharging) at non-dedicated facilities Use domain: industrial	
Operational conditions		
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 100 %	
Physical state	liquid	
Vapour pressure of the substance during use	502 Pa	
Duration and Frequency of activity	480 min 5 days per week	

Date / Revised: 13.12.2023

Version: 1.0 Date / Previous version: not applicable Previous version: none

Product: METHOXYPROPYLACETATE

(ID no. 30034751/SDS_GEN_IT/EN)

Date of print 21.10.2025

Indoor/Outdoor	Indoor	
	Assumes activities are at ambient temperature.	
Risk Management Measures		
Provide a good standard of general		
ventilation (not less than 3 - 5 air	Effectiveness: 30 %	
changes per hour)		
Exposure estimate and reference to its source		
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker	
	Worker - dermal, long-term - systemic	
Exposure estimate	13,7143 mg/kg bw/day	
Risk Characterization Ratio (RCR)	0,017229	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker	
	Worker - inhalation, long-term - systemic	
Exposure estimate	192,7187 mg/m³	
Risk Characterization Ratio (RCR)	0,700795	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker	
Guidance to Downstream Users		
For scaling see: http://www.ecetoc.org/tra		

Contributing exposure scenario	
Use descriptors covered	PROC8b: Transfer of substance or mixture (charging and discharging) at dedicated facilities Use domain: industrial
Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	13,7143 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,017229
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	137,6562 mg/m³
Risk Characterization Ratio (RCR)	0,500568
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org	/tra

Contributing exposure scenario

Date / Revised: 13.12.2023

Version: 1.0 Date / Previous version: not applicable Previous version: none

Product: METHOXYPROPYLACETATE

(ID no. 30034751/SDS_GEN_IT/EN)

Use descriptors covered	PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing). Use domain: industrial	
Operational conditions		
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 100 %	
Physical state	liquid	
Vapour pressure of the substance during use	502 Pa	
Duration and Frequency of activity	480 min 5 days per week	
Indoor/Outdoor	Indoor	
	Assumes activities are at ambient temperature.	
Risk Management Measures		
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %	
Exposure estimate and reference to its source		
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker	
	Worker - dermal, long-term - systemic	
Exposure estimate	6,8571 mg/kg bw/day	
Risk Characterization Ratio (RCR)	0,008615	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker	
	Worker - inhalation, long-term - systemic	
Exposure estimate	192,7187 mg/m³	
Risk Characterization Ratio (RCR)	0,700795	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker	
Guidance to Downstream Users		
For scaling see: http://www.ecetoc.org/	'tra	

Contributing exposure scenario	
Use descriptors covered	PROC14: Tabletting, compression, extrusion, pelletisation, granulation Use domain: industrial
Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Risk Management Measures	

Date / Revised: 13.12.2023 Version: 1.0
Date / Previous version: not applicable Previous version: none

Product: METHOXYPROPYLACETATE

(ID no. 30034751/SDS_GEN_IT/EN)

Date of print 21.10.2025

Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	3,4286 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,004307
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	192,7187 mg/m³
Risk Characterization Ratio (RCR)	0,700795
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC28: Manual maintenance (cleaning and repair) of machinery covered by PROC8a

* * * * * * * * * * * * * * * *

4. Short title of exposure scenario

Use in Coatings, (use in industrial settings)

ERC4; PROC1, PROC2, PROC3, PROC4, PROC5, PROC7, PROC8a, PROC8b, PROC9, PROC10, PROC13, PROC14, PROC15, PROC28

Control of exposure and risk management measures

Contributing exposure scenario	
Use descriptors covered	ESVOC SpERC 4.4a.v1: ESVOC SpERC 4.4a.v1
Operational conditions	
Annual amount used in the EU	5.500.000 kg
Minimum emission days per year	300
Emission factor air	98 %
Emission factor water	2 %
Emission factor soil	0 %
Receive Surf. Water (Flow Rate).	18.000 m3/d
Dilution factor river	10

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 13.12.2023
Date / Previous version: not applicable

Product: METHOXYPROPYLACETATE

(ID no. 30034751/SDS_GEN_IT/EN)

Date of print 21.10.2025

	400	
Dilution factor coast	100	
Risk Management Measures		
Air treatment measures considered suitable are, e.g.		Wet scrubber - for dusts, Filtration, Waste gas treatment by thermal oxidation, Adsorption
Wastewater treatment measures considered suitable are, e.g.		Acclimated biological treatment, Distillation
Type of STP		Municipal STP
Assumed sewage treatment plant flow (m3/d)		2.000 m3/d
Exposure estimate and reference to its source		
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Environment	
Risk Characterization Ratio (RCR)	0,955519	
	Risk from environmental exposure is driven by soil.	
Maximum amount of safe use	1.918,7 kg/d	
Risk from environmental exposure is driven by soil.		

Contributing exposure scenario	
Use descriptors covered	PROC1: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions. Use domain: industrial
Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Exposure estimate and reference to	its source
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	0,0343 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,000043
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	0,0551 mg/m³
Risk Characterization Ratio (RCR)	0,0002
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	

Date / Revised: 13.12.2023

Version: 1.0 Date / Previous version: not applicable Previous version: none Product: METHOXYPROPYLACETATE

(ID no. 30034751/SDS_GEN_IT/EN)

Date of print 21.10.2025

For scaling see: http://www.ecetoc.org/tra

Contributing exposure scenario		
Use descriptors covered	PROC2: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions Use domain: industrial	
Operational conditions		
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 100 %	
Physical state	liquid	
Vapour pressure of the substance during use	502 Pa	
Duration and Frequency of activity	480 min 5 days per week	
Indoor/Outdoor	Indoor	
	Assumes activities are at ambient temperature.	
Exposure estimate and reference to	its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker	
	Worker - dermal, long-term - systemic	
Exposure estimate	1,3714 mg/kg bw/day	
Risk Characterization Ratio (RCR)	0,001723	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker	
	Worker - inhalation, long-term - systemic	
Exposure estimate	27,5312 mg/m³	
Risk Characterization Ratio (RCR)	0,100114	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker	
Guidance to Downstream Users		
For scaling see: http://www.ecetoc.org/	tra	

Contributing exposure scenario		
Use descriptors covered	PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition Use domain: industrial	
Operational conditions		
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 100 %	
Physical state	liquid	
Vapour pressure of the substance during use	502 Pa	
Duration and Frequency of activity	480 min 5 days per week	
Indoor/Outdoor	Indoor	

Date / Revised: 13.12.2023 Version: 1.0
Date / Previous version: not applicable Previous version: none

Product: METHOXYPROPYLACETATE

(ID no. 30034751/SDS_GEN_IT/EN)

	Assumes activities are at ambient temperature.
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	0,6857 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,000861
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	55,0625 mg/m ³
Risk Characterization Ratio (RCR)	0,200227
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC4: Chemical production where opportunity for exposure arises Use domain: industrial
Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Exposure estimate and reference to	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	6,8571 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,008615
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	110,125 mg/m³
Risk Characterization Ratio (RCR)	0,400455
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org	/tra

Contributing exposure scenario	
Use descriptors covered	PROC5: Mixing or blending in batch processes Use domain: industrial
Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 13.12.2023 Date / Previous version: not applicable

Product: METHOXYPROPYLACETATE

(ID no. 30034751/SDS_GEN_IT/EN)

Date of print 21.10.2025

	Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Risk Management Measures	
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %
Exposure estimate and reference to	its source
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	13,7143 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,017229
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	192,7187 mg/m³
Risk Characterization Ratio (RCR)	0,700795
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/	′tra

Contributing exposure scenario	Contributing exposure scenario	
Use descriptors covered	PROC7: Industrial spraying Use domain: industrial	
Operational conditions	1	
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 90 %	
Physical state	liquid	
Vapour pressure of the substance during use	502 Pa	
Duration and Frequency of activity	240 min 5 days per week	
Indoor/Outdoor	Indoor	
	Assumes activities are at ambient temperature.	
	Any sized room	
Application rate	< 3 l/min	
Risk Management Measures		
Wear suitable respiratory protection.	Effectiveness: 90 %	
Surface spraying with no or low		
compressed air use.		
Provide extract ventilation to points		
where emissions occur (LEV).		

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 13.12.2023 Date / Previous version: not applicable

Previous version: none

Product: METHOXYPROPYLACETATE

(ID no. 30034751/SDS_GEN_IT/EN)

Ensure that general housekeeping is in place	
Provide a good standard of controlled ventilation (10 to 15 air changes per hour)	
Exposure estimate and reference to it	its source
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, worker, modified version, The concentration of the substance has been considered using a linear approach.
	Worker - dermal, long-term - systemic
Exposure estimate	23,1429 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,029074
Assessment method	EASY TRA v5.2, Advanced REACH Tool v1.5
	Worker - inhalation, long-term - systemic
Exposure estimate	190 mg/m ³
Risk Characterization Ratio (RCR)	0,690909
Assessment method	EASY TRA v5.2, Advanced REACH Tool v1.5
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra For scaling see: http://www.advancedreachtool.com Please note that a modified version has been used (see exposure estimates)	

Contributing exposure scenario	
Contains exposure socilario	PROC7: Industrial spraying
Use descriptors covered	Use domain: industrial
	See demain induction
	Surface spraying of liquids
Operational conditions	
	2-methoxy-1-methylethyl acetate
Concentration of the substance	Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance	502 Pa
during use	302 T a
during use	480 min 5 days per week
Duration and Frequency of activity	400 min 3 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Application rate	< 3 l/min
Risk Management Measures	
Ensure that general housekeeping is	
in place	
Provide a good standard of controlled	
ventilation (10 to 15 air changes per	
hour)	
Ensure that the task is being carried	
out outside the breathing zone of a	
worker (distance head-product greater	
than 1m).	

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 13.12.2023
Date / Previous version: not applicable

Product: METHOXYPROPYLACETATE

(ID no. 30034751/SDS_GEN_IT/EN)

Date of print 21.10.2025

Ensure that the worker is in a seperated (control) room with independent air supply	
Exposure estimate and reference to	its source
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	42,8571 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,053841
Assessment method	EASY TRA v5.2, Advanced REACH Tool v1.5
	Worker - inhalation, long-term - systemic
Exposure estimate	180 mg/m³
Risk Characterization Ratio (RCR)	0,654545
Assessment method	EASY TRA v5.2, Advanced REACH Tool v1.5
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/t	ra For scaling see: http://www.advancedreachtool.com

Contributing exposure scenario	
Use descriptors covered	PROC8a: Transfer of substance or mixture (charging and discharging) at non-dedicated facilities Use domain: industrial
Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Risk Management Measures	
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %
Exposure estimate and reference to	its source
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	13,7143 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,017229
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	192,7187 mg/m³
Risk Characterization Ratio (RCR)	0,700795
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org	g/tra

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 13.12.2023
Date / Previous version: not applicable

Product: METHOXYPROPYLACETATE

(ID no. 30034751/SDS_GEN_IT/EN)

Date of print 21.10.2025

Contributing exposure scenario	
Use descriptors covered	PROC8b: Transfer of substance or mixture (charging and discharging) at dedicated facilities Use domain: industrial
Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Exposure estimate and reference to	its source
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	13,7143 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,017229
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	137,6562 mg/m³
Risk Characterization Ratio (RCR)	0,500568
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/	′tra

Contributing exposure scenario	
Use descriptors covered	PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing). Use domain: industrial
Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Risk Management Measures	
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %

Date / Revised: 13.12.2023 Version: 1.0
Date / Previous version: not applicable Previous version: none

Product: METHOXYPROPYLACETATE

(ID no. 30034751/SDS_GEN_IT/EN)

Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	6,8571 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,008615
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	192,7187 mg/m³
Risk Characterization Ratio (RCR)	0,700795
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
<u> </u>	PROC10: Roller application or brushing
Use descriptors covered	Use domain: industrial
Operational conditions	
	2-methoxy-1-methylethyl acetate
Concentration of the substance	Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance	502 Pa
during use	
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Risk Management Measures	·
Provide a good standard of general	
ventilation (not less than 3 - 5 air	Effectiveness: 30 %
changes per hour)	
Exposure estimate and reference to	its source
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	27,4286 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,034458
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	192,7187 mg/m³
Risk Characterization Ratio (RCR)	0,700795
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org	/tra

Contributing exposure scenario	
Use descriptors covered	PROC13: Treatment of articles by dipping and pouring. Use domain: industrial

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 13.12.2023

Date / Previous version: not applicable Product: **METHOXYPROPYLACETATE**

(ID no. 30034751/SDS_GEN_IT/EN)

Date of print 21.10.2025

Operational conditions		
	2-methoxy-1-methylethyl acetate	
Concentration of the substance	Content: >= 0 % - <= 100 %	
Physical state	liquid	
Vapour pressure of the substance during use	502 Pa	
Duration and Frequency of activity	480 min 5 days per week	
Indoor/Outdoor	Indoor	
	Assumes activities are at ambient temperature.	
Risk Management Measures		
Provide a good standard of general		
ventilation (not less than 3 - 5 air	Effectiveness: 30 %	
changes per hour)		
Exposure estimate and reference to		
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker	
	Worker - dermal, long-term - systemic	
Exposure estimate	13,7143 mg/kg bw/day	
Risk Characterization Ratio (RCR)	0,017229	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker	
	Worker - inhalation, long-term - systemic	
Exposure estimate	192,7187 mg/m³	
Risk Characterization Ratio (RCR)	0,700795	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker	
Guidance to Downstream Users		
For scaling see: http://www.ecetoc.org/t	ra	

Contributing exposure scenario	
Use descriptors covered	PROC14: Tabletting, compression, extrusion, pelletisation, granulation Use domain: industrial
Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Risk Management Measures	
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %
Exposure estimate and reference to its source	

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 13.12.2023 Date / Previous version: not applicable

Product: METHOXYPROPYLACETATE

(ID no. 30034751/SDS_GEN_IT/EN)

Date of print 21.10.2025

Previous version: none

Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	3,4286 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,004307
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	192,7187 mg/m ³
Risk Characterization Ratio (RCR)	0,700795
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org	/tra

Contributing exposure scenario		
•	PROC15: Use a laboratory reagent.	
Use descriptors covered	Use domain: industrial	
Operational conditions		
	2-methoxy-1-methylethyl acetate	
Concentration of the substance	Content: >= 0 % - <= 100 %	
Physical state	liquid	
Vapour pressure of the substance during use	502 Pa	
Duration and Frequency of activity	480 min 5 days per week	
Indoor/Outdoor	Indoor	
	Assumes activities are at ambient temperature.	
Exposure estimate and reference to its source		
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker	
	Worker - dermal, long-term - systemic	
Exposure estimate	0,3429 mg/kg bw/day	
Risk Characterization Ratio (RCR)	0,000431	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker	
	Worker - inhalation, long-term - systemic	
Exposure estimate	55,0625 mg/m³	
Risk Characterization Ratio (RCR)	0,200227	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker	
Guidance to Downstream Users		
For scaling see: http://www.ecetoc.org/	/tra	

Contributing exposure scenario	
Use descriptors covered	PROC28: Manual maintenance (cleaning and repair) of machinery covered by PROC8a

* * * * * * * * * * * * * * * *

Date / Revised: 13.12.2023 Version: 1.0
Date / Previous version: not applicable Previous version: none

Product: METHOXYPROPYLACETATE

(ID no. 30034751/SDS_GEN_IT/EN)

Date of print 21.10.2025

5. Short title of exposure scenario

Use in Coatings, (use in professional settings)
ERC8a, ERC8d; PROC1, PROC2, PROC3, PROC4, PROC5, PROC8a, PROC8b, PROC9, PROC10, PROC11, PROC13, PROC14, PROC15, PROC19, PROC28

Control of exposure and risk management measures

Contributing exposure scenario			
Use descriptors covered	ESVOC SpERC 8.3b.v2		
Operational conditions			
Annual amount used in the EU	25.000.000 kg		
Minimum emission days per year	365		
Emission factor air	98 %		
Emission factor water	1 %		
Emission factor soil	1 %		
Receive Surf. Water (Flow Rate).	18.000 m3/d		
Dilution factor river	10		
Dilution factor coast	100		
Risk Management Measures	Risk Management Measures		
Type of STP	Municipal STP		
Assumed sewage treatment plant flow (v (m3/d) 2.000 m3/d		
Exposure estimate and reference to its source			
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Environment		
Risk Characterization Ratio (RCR)	0,022771		
	Risk from environmental exposure is driven by soil.		
Maximum amount of safe use	601,6		
	kg/d		
Risk from environmental exposure is driven by soil.			

Contributing exposure scenario		
Use descriptors covered	ESVOC SpERC 8.3b.v2	
Operational conditions		
Annual amount used in the EU	25.000.000 kg	
Minimum emission days per year	365	
Emission factor air	98 %	

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 13.12.2023
Date / Previous version: not applicable

Product: METHOXYPROPYLACETATE

(ID no. 30034751/SDS_GEN_IT/EN)

Date of print 21.10.2025

Emission factor water	1 %	
Emission factor soil	1 %	
Receive Surf. Water (Flow Rate).	18.000 m3/d	
Dilution factor river	10	
Dilution factor coast	100	
Risk Management Measures		
Type of STP		Municipal STP
Assumed sewage treatment plant flow (m3/d)		2.000 m3/d
Exposure estimate and reference to its source		
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Environment	
Risk Characterization Ratio (RCR)	0,022771	
	Risk from environmental exposure is driven by soil.	
	601,6	
Maximum amount of safe use	kg/d	
Risk from environmental exposure is driven by soil.		

Contributing exposure scenario		
Use descriptors covered	PROC1: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions. Use domain: professional	
Operational conditions		
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 100 %	
Physical state	liquid	
Vapour pressure of the substance during use	502 Pa	
Duration and Frequency of activity	480 min 5 days per week	
Indoor/Outdoor	Indoor	
	Assumes activities are at ambient temperature.	
Exposure estimate and reference to	its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker	
	Worker - dermal, long-term - systemic	
Exposure estimate	0,0343 mg/kg bw/day	
Risk Characterization Ratio (RCR)	0,000043	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker	
	Worker - inhalation, long-term - systemic	
Exposure estimate	0,0551 mg/m³	
Risk Characterization Ratio (RCR)	0,0002	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker	

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 13.12.2023 Date / Previous version: not applicable

Product: METHOXYPROPYLACETATE

(ID no. 30034751/SDS_GEN_IT/EN)

Date of print 21.10.2025

Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario		
Use descriptors covered	PROC2: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions Use domain: professional	
Operational conditions		
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 100 %	
Physical state	liquid	
Vapour pressure of the substance during use	502 Pa	
Duration and Frequency of activity	480 min 5 days per week	
Indoor/Outdoor	Indoor	
	Assumes activities are at ambient temperature.	
Exposure estimate and reference to	its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker	
	Worker - dermal, long-term - systemic	
Exposure estimate	1,3714 mg/kg bw/day	
Risk Characterization Ratio (RCR)	0,001723	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker	
	Worker - inhalation, long-term - systemic	
Exposure estimate	110,125 mg/m ³	
Risk Characterization Ratio (RCR)	0,400455	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker	
Guidance to Downstream Users		
For scaling see: http://www.ecetoc.org/	tra	

Contributing exposure scenario			
Use descriptors covered	PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition Use domain: professional		
Operational conditions	Operational conditions		
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 100 %		
Physical state	liquid		
Vapour pressure of the substance during use	502 Pa		
Duration and Frequency of activity	480 min 5 days per week		

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 13.12.2023
Date / Previous version: not applicable

Product: METHOXYPROPYLACETATE

(ID no. 30034751/SDS_GEN_IT/EN)

Date of print 21.10.2025

Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	0,6857 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,000861
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	137,6562 mg/m³
Risk Characterization Ratio (RCR)	0,500568
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/t	tra

Contributing exposure scenario	
Use descriptors covered	PROC4: Chemical production where opportunity for exposure arises Use domain: professional
Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Outdoor
	Assumes activities are at ambient temperature.
Exposure estimate and reference to	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	6,8571 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,008615
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	192,7187 mg/m ³
Risk Characterization Ratio (RCR)	0,700795
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org	ı/tra

Contributing exposure scenario	
Use descriptors covered	PROC4: Chemical production where opportunity for exposure arises Use domain: professional

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 13.12.2023
Date / Previous version: not applicable

Product: METHOXYPROPYLACETATE

(ID no. 30034751/SDS_GEN_IT/EN)

Date of print 21.10.2025

Operational conditions	
	2-methoxy-1-methylethyl acetate
Concentration of the substance	Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Risk Management Measures	
Provide a good standard of general	
ventilation (not less than 3 - 5 air	Effectiveness: 30 %
changes per hour)	
Exposure estimate and reference to	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	6,8571 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,008615
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	192,7187 mg/m³
Risk Characterization Ratio (RCR)	0,700795
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/t	tra

Contributing exposure scenario		
Use descriptors covered	PROC5: Mixing or blending in batch processes Use domain: professional	
Operational conditions		
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 100 %	
Physical state	liquid	
Vapour pressure of the substance during use	502 Pa	
Duration and Frequency of activity	480 min 5 days per week	
Indoor/Outdoor	Indoor	
	Assumes activities are at ambient temperature.	
Risk Management Measures		
Provide a good standard of general or controlled ventilation (5 to 10 air changes per hour)	Effectiveness: 70 %	
Exposure estimate and reference to its source		
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker	

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 13.12.2023 Date / Previous version: not applicable

Product: METHOXYPROPYLACETATE

(ID no. 30034751/SDS_GEN_IT/EN)

Date of print 21.10.2025

	Worker - dermal, long-term - systemic
Exposure estimate	13,7143 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,017229
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	165,1875 mg/m³
Risk Characterization Ratio (RCR)	0,600682
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/	tra

Contributing exposure scenario	
Use descriptors covered	PROC5: Mixing or blending in batch processes Use domain: professional
Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	240 min 5 days per week
Indoor/Outdoor	Outdoor
	Assumes activities are at ambient temperature.
Exposure estimate and reference to	o its source
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	8,2286 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,010337
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	231,2625 mg/m³
Risk Characterization Ratio (RCR)	0,840955
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org	g/tra

Contributing exposure scenario	
Use descriptors covered	PROC8a: Transfer of substance or mixture (charging and discharging) at non-dedicated facilities Use domain: professional
Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid

Date / Revised: 13.12.2023 Version: 1.0
Date / Previous version: not applicable Previous version: none

Product: METHOXYPROPYLACETATE

(ID no. 30034751/SDS_GEN_IT/EN)

Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Risk Management Measures	
Provide a good standard of general or	
controlled ventilation (5 to 10 air	Effectiveness: 70 %
changes per hour)	
Exposure estimate and reference to it	its source
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	13,7143 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,017229
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	165,1875 mg/m³
Risk Characterization Ratio (RCR)	0,600682
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/t	ra

Contributing exposure scenario	
Use descriptors covered	PROC8b: Transfer of substance or mixture (charging and discharging) at dedicated facilities Use domain: professional
Operational conditions	1
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Risk Management Measures	
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	13,7143 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,017229
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 13.12.2023 Date / Previous version: not applicable

Previous version: none

Product: METHOXYPROPYLACETATE

(ID no. 30034751/SDS_GEN_IT/EN)

	Worker - inhalation, long-term - systemic
Exposure estimate	192,7187 mg/m³
Risk Characterization Ratio (RCR)	0,700795
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario			
Use descriptors covered	PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing). Use domain: professional		
Operational conditions			
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 100 %		
Physical state	liquid		
Vapour pressure of the substance during use	502 Pa		
Duration and Frequency of activity	480 min 5 days per week		
Indoor/Outdoor	Indoor		
	Assumes activities are at ambient temperature.		
Risk Management Measures			
Provide a good standard of general or controlled ventilation (5 to 10 air changes per hour)	Effectiveness: 70 %		
Exposure estimate and reference to	Exposure estimate and reference to its source		
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker		
	Worker - dermal, long-term - systemic		
Exposure estimate	6,8571 mg/kg bw/day		
Risk Characterization Ratio (RCR)	0,008615		
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker		
	Worker - inhalation, long-term - systemic		
Exposure estimate	165,1875 mg/m³		
Risk Characterization Ratio (RCR)	0,600682		
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker		
Guidance to Downstream Users			
For scaling see: http://www.ecetoc.org/t	ra		

Contributing exposure scenario	
Use descriptors covered	PROC10: Roller application or brushing Use domain: professional
Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 13.12.2023
Date / Previous version: not applicable

Product: METHOXYPROPYLACETATE

(ID no. 30034751/SDS_GEN_IT/EN)

Date of print 21.10.2025

Vapour pressure of the substance during use	502 Pa		
Duration and Frequency of activity	480 min 5 days per week		
Indoor/Outdoor	Indoor		
	Assumes activities are at ambient temperature.		
Risk Management Measures	·		
Provide a good standard of general or			
controlled ventilation (5 to 10 air	Effectiveness: 70 %		
changes per hour)			
Exposure estimate and reference to it	Exposure estimate and reference to its source		
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker		
	Worker - dermal, long-term - systemic		
Exposure estimate	27,4286 mg/kg bw/day		
Risk Characterization Ratio (RCR)	0,034458		
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker		
	Worker - inhalation, long-term - systemic		
Exposure estimate	165,1875 mg/m³		
Risk Characterization Ratio (RCR)	0,600682		
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker		
Guidance to Downstream Users			
For scaling see: http://www.ecetoc.org/tra			

Contributing exposure scenario	
	PROC10: Roller application or brushing
Use descriptors covered	Use domain: professional
Operational conditions	
	2-methoxy-1-methylethyl acetate
Concentration of the substance	Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance	502 Pa
during use	
Duration and Frequency of activity	240 min 5 days per week
Indoor/Outdoor	Outdoor
	Assumes activities are at ambient temperature.
Exposure estimate and reference to	its source
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	16,4571 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,020675
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	231,2625 mg/m³
Risk Characterization Ratio (RCR)	0,840955
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	

Page: 59/115

Version: 1.0

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 13.12.2023
Date / Previous version: not applicable

Product: METHOXYPROPYLACETATE

(ID no. 30034751/SDS_GEN_IT/EN)

Date of print 21.10.2025

Previous version: none

For scaling see: http://www.ecetoc.org/tra

Contributing exposure scenario	
	PROC11: Non industrial spraying
Use descriptors covered	Use domain: professional
, and a second	
Operational conditions	
•	2-methoxy-1-methylethyl acetate
Concentration of the substance	Content: >= 0 % - <= 90 %
Physical state	liquid
Vapour pressure of the substance	502 Pa
during use	
Duration and Fraguency of activity	240 min 5 days per week
Duration and Frequency of activity	
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
	Any sized room
Application rate	< 3 l/min
Risk Management Measures	
Wear suitable respiratory protection.	Effectiveness: 90 %
Surface spraying with no or low	
compressed air use.	
Provide extract ventilation to points	
where emissions occur (LEV).	
Ensure that general housekeeping is	
in place	
Provide a good standard of controlled	
ventilation (10 to 15 air changes per	
hour)	
Exposure estimate and reference to	
	EASY TRA v5.2, ECETOC TRA v3.0, worker, modified
Assessment method	version, The concentration of the substance has been
	considered using a linear approach.
	Worker - dermal, long-term - systemic
Exposure estimate	57,8571 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,072685
Assessment method	EASY TRA v5.2, Advanced REACH Tool v1.5
	Worker - inhalation, long-term - systemic
Exposure estimate	190 mg/m³
Risk Characterization Ratio (RCR)	0,690909
Assessment method	EASY TRA v5.2, Advanced REACH Tool v1.5
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra For scaling see: http://www.advancedreachtool.com	
Please note that a modified version has been used (see exposure estimates)	

Contributing exposure scenario	
Use descriptors covered	PROC11: Non industrial spraying
	Use domain: professional

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 13.12.2023
Date / Previous version: not applicable

Product: METHOXYPROPYLACETATE

(ID no. 30034751/SDS_GEN_IT/EN)

Date of print 21.10.2025

Operational conditions	
	2-methoxy-1-methylethyl acetate
Concentration of the substance	Content: >= 0 % - <= 90 %
Physical state	liquid
Vapour pressure of the substance	502 Pa
during use	
Duration and Frequency of activity	240 min 5 days per week
Duration and Frequency of activity	
Indoor/Outdoor	Outdoor
	Assumes activities are at ambient temperature.
Application rate	< 3 l/min
Risk Management Measures	
Wear suitable respiratory protection.	Effectiveness: 95 %
Surface spraying with no or low	
compressed air use.	
Ensure that general housekeeping is	
in place	
Exposure estimate and reference to	its source
	EASY TRA v5.2, ECETOC TRA v3.0, worker, modified
Assessment method	version, The concentration of the substance has been
	considered using a linear approach.
	Worker - dermal, long-term - systemic
Exposure estimate	57,8571 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,072685
Assessment method	EASY TRA v5.2, Advanced REACH Tool v1.5
	Worker - inhalation, long-term - systemic
Exposure estimate	190 mg/m³
Risk Characterization Ratio (RCR)	0,690909
Assessment method	EASY TRA v5.2, Advanced REACH Tool v1.5
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra For scaling see: http://www.advancedreachtool.com	
Please note that a modified version has been used (see exposure estimates)	

Contributing exposure scenario	
Use descriptors covered	PROC13: Treatment of articles by dipping and pouring. Use domain: professional
Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor

Date / Revised: 13.12.2023 Version: 1.0
Date / Previous version: not applicable Previous version: none

Product: METHOXYPROPYLACETATE

(ID no. 30034751/SDS_GEN_IT/EN)

	Assumes activities are at ambient temperature.	
Risk Management Measures		
Provide a good standard of general or controlled ventilation (5 to 10 air	Effectiveness: 70 %	
changes per hour)		
Exposure estimate and reference to its source		
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker	
	Worker - dermal, long-term - systemic	
Exposure estimate	13,7143 mg/kg bw/day	
Risk Characterization Ratio (RCR)	0,017229	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker	
	Worker - inhalation, long-term - systemic	
Exposure estimate	165,1875 mg/m³	
Risk Characterization Ratio (RCR)	0,600682	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker	
Guidance to Downstream Users		
For scaling see: http://www.ecetoc.org/tra		

Contributing exposure scenario	
Use descriptors covered	PROC13: Treatment of articles by dipping and pouring. Use domain: professional
Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	240 min 5 days per week
Indoor/Outdoor	Outdoor
	Assumes activities are at ambient temperature.
Exposure estimate and reference to	its source
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	8,2286 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,010337
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	231,2625 mg/m³
Risk Characterization Ratio (RCR)	0,840955
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org	ı/tra

Contributing exposure scenario	
Use descriptors covered	PROC14: Tabletting, compression, extrusion, pelletisation,
	granulation

Date / Revised: 13.12.2023

Version: 1.0 Previous version: none

Date / Previous version: not applicable Product: METHOXYPROPYLACETATE

(ID no. 30034751/SDS_GEN_IT/EN)

	Use domain: professional
Operational conditions	<u> </u>
	2-methoxy-1-methylethyl acetate
Concentration of the substance	Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance	502 Pa
during use	302 Fa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Risk Management Measures	
Provide a good standard of general or	
controlled ventilation (5 to 10 air	Effectiveness: 70 %
changes per hour)	
Exposure estimate and reference to it	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	3,4286 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,004307
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	165,1875 mg/m³
Risk Characterization Ratio (RCR)	0,600682
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/t	ra

Contributing exposure scenario	
	PROC15: Use a laboratory reagent.
Use descriptors covered	Use domain: professional
Operational conditions	
-	2-methoxy-1-methylethyl acetate
Concentration of the substance	Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	0,3429 mg/kg bw/day

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 13.12.2023
Date / Previous version: not applicable

Product: METHOXYPROPYLACETATE

(ID no. 30034751/SDS_GEN_IT/EN)

Date of print 21.10.2025

Risk Characterization Ratio (RCR)	0,000431
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	55,0625 mg/m³
Risk Characterization Ratio (RCR)	0,200227
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/	tra

Contributing exposure scenario		
	PROC19: Manual activities involving hand contact	
Use descriptors covered	Use domain: professional	
Operational conditions		
	2-methoxy-1-methylethyl acetate	
Concentration of the substance	Content: >= 0 % - <= 100 %	
Physical state	liquid	
Vapour pressure of the substance	502 Pa	
during use		
Duration and Frequency of activity	480 min 5 days per week	
Indoor/Outdoor	Indoor	
	Assumes activities are at ambient temperature.	
Risk Management Measures		
Wear suitable respiratory protection.	Effectiveness: 90 %	
Exposure estimate and reference to	its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker	
	Worker - dermal, long-term - systemic	
Exposure estimate	141,4286 mg/kg bw/day	
Risk Characterization Ratio (RCR)	0,177674	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker	
	Worker - inhalation, long-term - systemic	
Exposure estimate	55,0625 mg/m³	
Risk Characterization Ratio (RCR)	0,200227	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker	
Guidance to Downstream Users		
For scaling see: http://www.ecetoc.org/	tra	

Contributing exposure scenario	
Use descriptors covered	PROC19: Manual activities involving hand contact Use domain: professional
Operational conditions	
	2-methoxy-1-methylethyl acetate
Concentration of the substance	Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance	502 Pa

Date / Revised: 13.12.2023 Version: 1.0
Date / Previous version: not applicable
Product: METHOXYPROPYLACETATE

Version: 1.0
Previous version: none

(ID no. 30034751/SDS_GEN_IT/EN)

Date of print 21.10.2025

during use	
Duration and Frequency of activity	240 min 5 days per week
Indoor/Outdoor	Outdoor
	Assumes activities are at ambient temperature.
Exposure estimate and reference to	its source
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	84,8571 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,106604
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	231,2625 mg/m³
Risk Characterization Ratio (RCR)	0,840955
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/t	tra

Contributing exposure scenario	
Use descriptors covered	PROC28: Manual maintenance (cleaning and repair) of machinery covered by PROC8a

* * * * * * * * * * * * * * *

6. Short title of exposure scenario

Use in Coatings, (consumer use) ERC8a, ERC8d; PC9a, PC18

Control of exposure and risk management measures

Contributing exposure scenario	
Use descriptors covered	ESVOC SpERC 8.3c.v2
Operational conditions	
Annual amount used in the EU	5.280.000 kg
Minimum emission days per year	365
Emission factor air	98,5 %
Emission factor water	1 %
Emission factor soil	0,5 %
Receive Surf. Water (Flow Rate).	18.000 m3/d

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 13.12.2023
Date / Previous version: not applicable
Product: METHOXYPROPYLACETATE

...

(ID no. 30034751/SDS_GEN_IT/EN)

Date of print 21.10.2025

Previous version: none

Dilution factor river	10	
Dilution factor coast	100	
Risk Management Measures		
Type of STP		Municipal STP
Assumed sewage treatment plant flow (m3/d)	2.000 m3/d
Exposure estimate and reference to its source		
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Environment	
Risk Characterization Ratio (RCR)	0,020744	
	Risk from environmental exposure is driven by soil.	
	139,5	
Maximum amount of safe use	kg/d	
Risk from environmental exposure is driven by soil.		

Contributing exposure scenario		
Use descriptors covered	ESVOC SpERC 8.3c.v2	
Operational conditions	1	
Annual amount used in the EU	5.280.000 kg	
Minimum emission days per year	365	
Emission factor air	98,5 %	
Emission factor water	1 %	
Emission factor soil	0,5 %	
Receive Surf. Water (Flow Rate).	18.000 m3/d	
Dilution factor river	10	
Dilution factor coast	100	
Risk Management Measures		
Type of STP		Municipal STP
Assumed sewage treatment plant flow (m3/d) 2.000 m3/d		2.000 m3/d
Exposure estimate and reference to its source		
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Environment	
Risk Characterization Ratio (RCR)	0,020744	
	Risk from environmental ex	cposure is driven by soil.
	139,5	
Maximum amount of safe use	kg/d	
Risk from environmental exposure is driven by soil.		

Contributing exposure scenario

Date / Revised: 13.12.2023 Version: 1.0

Date / Previous version: not applicable Previous version: none

Product: METHOXYPROPYLACETATE

(ID no. 30034751/SDS_GEN_IT/EN)

Use descriptors covered	PC9a_2, PC15_2: Subcategory: Solvent rich, high solid, water borne paint	
Operational conditions	,	
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 10 %	
Vapour pressure of the substance during use	502 Pa	
Duration and Frequency of activity	Exposure duration: 2,2 h 2 uses per year	
Room size	20 m3	
Indoor/Outdoor	Indoor	
Ventilation rate per hour	0,6	
Exposed skin area	Palm of both hands (480 cm²)	
Uptake fraction dermal	100 %	
Uptake fraction inhalation	100 %	
	Amount per use 1.000 g Relevant for inhalative exposure estimates	
Exposure estimate and reference to its source		
Assessment method	EASY TRA v5.2, ECETOC TRA, Consumer	
	Consumer - dermal, long-term - systemic	
Exposure estimate	0,0715 mg/kg bw/day	
Risk Characterization Ratio (RCR)	0,000223	
Assessment method	EASY TRA v5.2, ECETOC TRA, Consumer	
	Consumer - inhalation, long-term - systemic	
Exposure estimate	21,5517 mg/m³	
Risk Characterization Ratio (RCR)	0,653083	
Guidance to Downstream Users		
For scaling see: http://www.ecetoc.org/	/tra	

Contributing exposure scenario	
Use descriptors covered	PC18: Ink and Toners.
Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 45 %
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	Exposure duration: 5 min Relevant for inhalative exposure estimates
Duration and Frequency of activity	Application duration: 5 min Relevant for inhalative exposure estimates
Duration and Frequency of activity	156 uses per year
Room size	1 m3

Date / Revised: 13.12.2023

Version: 1.0

Date / Previous version: not applicable

Previous version: none

Product: METHOXYPROPYLACETATE

(ID no. 30034751/SDS_GEN_IT/EN)

Date of print 21.10.2025

Ventilation rate per hour	1
Temperature (Application)	20 °C
body weight	61 kg
Lintaka fraction darmal	100 %
Uptake fraction dermal	Relevant for dermal exposure estimates
	Relevant for dermal exposure estimates
	Amount per use 0,05 g Relevant for dermal exposure
	estimates
Release area	19 cm ²
	Release area is constant
Release duration	5 min
	Relevant for inhalative exposure estimates
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ConsExpo v4.1, Dermal model: instant
Assessment method	application, Uptake model: Uptake fraction
	Consumer - dermal, long-term - systemic
Exposure estimate	0,1576 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,000493
	The calculation is based on the internal chronic dose.
Assessment method	EASY TRA v5.2, ConsExpo v4.1, Inhalation model:
Assessment method	exposure to vapour - evaporation
	Consumer - inhalation, long-term - systemic
Exposure estimate	0,1517 mg/m³
Risk Characterization Ratio (RCR)	0,004597
	The exposure calculation is based on the mean
	concentration per year.
Guidance to Downstream Users	
For scaling see: http://www.rivm.nl/en/l	nealthanddisease/productsafety/ConsExpo.jsp

* * * * * * * * * * * * * * * *

7. Short title of exposure scenario

Cleaning agents, (use in industrial settings)

ERC4; PROC1, PROC2, PROC3, PROC4, PROC7, PROC8a, PROC8b, PROC10, PROC13, PROC28

Control of exposure and risk management measures

Contributing exposure scenario		
Use descriptors covered	ESVOC SpERC 4.6a.v1: ESVOC SpERC 4.6a.v1	
Operational conditions		
Annual amount used in the EU	8.415.000 kg	
Minimum emission days per year	20	
Emission factor air	30 %	

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 13.12.2023
Date / Previous version: not applicable
Product: METHOXYPROPYLACETATE

(ID no. 30034751/SDS_GEN_IT/EN)

Date of print 21.10.2025

Emission factor water	0,01 %	
Emission factor soil	0 %	
Receive Surf. Water (Flow Rate).	18.000 m3/d	
Dilution factor river	10	
Dilution factor coast	100	
Risk Management Measures		
Air treatment measures considered suitable are, e.g.		Wet scrubber - for dusts, Waste gas treatment by thermal oxidation, Adsorption
Wastewater treatment measures consid	lered suitable are, e.g.	Acclimated biological treatment, Distillation
Type of STP		Municipal STP
Assumed sewage treatment plant flow (m3/d)	2.000 m3/d
Exposure estimate and reference to its source		
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Environment	
Risk Characterization Ratio (RCR)	0,043349	
	Risk from environmental exposure is driven by soil.	
	115.342	
Maximum amount of safe use	kg/d	
Risk from environmental exposure is driven by soil.		

Contributing exposure scenario		
Use descriptors covered	PROC1: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions. Use domain: industrial	
Operational conditions		
	2-methoxy-1-methylethyl acetate	
Concentration of the substance	Content: >= 0 % - <= 100 %	
Physical state	liquid	
Vapour pressure of the substance during use	502 Pa	
Duration and Frequency of activity	480 min 5 days per week	
Indoor/Outdoor	Indoor	
	Assumes activities are at ambient temperature.	
Exposure estimate and reference to its source		
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker	
	Worker - dermal, long-term - systemic	
Exposure estimate	0,0343 mg/kg bw/day	
Risk Characterization Ratio (RCR)	0,000043	

Date / Revised: 13.12.2023 Version: 1.0
Date / Previous version: not applicable Previous version: none

Product: METHOXYPROPYLACETATE

(ID no. 30034751/SDS_GEN_IT/EN)

Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	0,0551 mg/m³
Risk Characterization Ratio (RCR)	0,0002
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario		
Use descriptors covered	PROC2: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions Use domain: industrial	
Operational conditions		
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 100 %	
Physical state	liquid	
Vapour pressure of the substance during use	502 Pa	
Duration and Frequency of activity	480 min 5 days per week	
Indoor/Outdoor	Indoor	
	Assumes activities are at ambient temperature.	
Exposure estimate and reference to its source		
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker	
	Worker - dermal, long-term - systemic	
Exposure estimate	1,3714 mg/kg bw/day	
Risk Characterization Ratio (RCR)	0,001723	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker	
	Worker - inhalation, long-term - systemic	
Exposure estimate	27,5312 mg/m³	
Risk Characterization Ratio (RCR)	0,100114	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker	
Guidance to Downstream Users		
For scaling see: http://www.ecetoc.org/t	ra	

Contributing exposure scenario	
Use descriptors covered	PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition Use domain: industrial
Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 100 %

Date / Revised: 13.12.2023

Version: 1.0 Date / Previous version: not applicable Previous version: none

Product: METHOXYPROPYLACETATE

(ID no. 30034751/SDS_GEN_IT/EN)

Physical state	liquid
Vapour pressure of the substance	502 Pa
during use	
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	0,6857 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,000861
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	55,0625 mg/m³
Risk Characterization Ratio (RCR)	0,200227
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing expecuse cooperie		
Contributing exposure scenario		
	PROC4: Chemical production where opportunity for	
Use descriptors covered	exposure arises	
	Use domain: industrial	
Operational conditions		
	2-methoxy-1-methylethyl acetate	
Concentration of the substance	Content: >= 0 % - <= 100 %	
Physical state	liquid	
Vapour pressure of the substance	502 Pa	
during use		
Duration and Frequency of activity	480 min 5 days per week	
• • •		
Indoor/Outdoor	Indoor	
	Assumes activities are at ambient temperature.	
Exposure estimate and reference to		
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker	
	Worker - dermal, long-term - systemic	
Exposure estimate	6,8571 mg/kg bw/day	
Risk Characterization Ratio (RCR)	0,008615	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker	
	Worker - inhalation, long-term - systemic	
Exposure estimate	110,125 mg/m ³	
Risk Characterization Ratio (RCR)	0,400455	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker	
Guidance to Downstream Users		
For scaling see: http://www.ecetoc.org	/tra	

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 13.12.2023 Date / Previous version: not applicable

Product: METHOXYPROPYLACETATE

(ID no. 30034751/SDS_GEN_IT/EN)

Date of print 21.10.2025

	PPOC7: Industrial enraving
Use descriptors covered	PROC7: Industrial spraying Use domain: industrial
Operational conditions	
	2-methoxy-1-methylethyl acetate
Concentration of the substance	Content: >= 0 % - <= 90 %
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	240 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
	Any sized room
Application rate	< 3 l/min
Risk Management Measures	
Wear suitable respiratory protection.	Effectiveness: 90 %
Surface spraying with no or low	
compressed air use.	
Provide extract ventilation to points	
where emissions occur (LEV).	
Ensure that general housekeeping is in place	
Provide a good standard of controlled	
ventilation (10 to 15 air changes per	
hour)	
Exposure estimate and reference to	
	EASY TRA v5.2, ECETOC TRA v3.0, worker, modified
Assessment method	version, The concentration of the substance has been
	considered using a linear approach.
	Worker - dermal, long-term - systemic
Exposure estimate	23,1429 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,029074
Assessment method	EASY TRA v5.2, Advanced REACH Tool v1.5
	Worker - inhalation, long-term - systemic
Exposure estimate	190 mg/m³
Risk Characterization Ratio (RCR)	0,690909
Assessment method	EASY TRA v5.2, Advanced REACH Tool v1.5
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/ Please note that a modified version has	tra For scaling see: http://www.advancedreachtool.com

Contributing exposure scenario	
Use descriptors covered	PROC8a: Transfer of substance or mixture (charging and discharging) at non-dedicated facilities Use domain: industrial

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 13.12.2023 Date / Previous version: not applicable

Product: METHOXYPROPYLACETATE

(ID no. 30034751/SDS_GEN_IT/EN)

Date of print 21.10.2025

Operational conditions		
	2-methoxy-1-methylethyl acetate	
Concentration of the substance	Content: >= 0 % - <= 100 %	
Physical state	liquid	
Vapour pressure of the substance during use	502 Pa	
Duration and Frequency of activity	480 min 5 days per week	
Indoor/Outdoor	Indoor	
	Assumes activities are at ambient temperature.	
Risk Management Measures		
Provide a good standard of general		
ventilation (not less than 3 - 5 air	Effectiveness: 30 %	
changes per hour)		
Exposure estimate and reference to		
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker	
	Worker - dermal, long-term - systemic	
Exposure estimate	13,7143 mg/kg bw/day	
Risk Characterization Ratio (RCR)	0,017229	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker	
	Worker - inhalation, long-term - systemic	
Exposure estimate	192,7187 mg/m³	
Risk Characterization Ratio (RCR)	0,700795	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker	
Guidance to Downstream Users		
For scaling see: http://www.ecetoc.org/tra		

Contributing exposure scenario	
Use descriptors covered	PROC8b: Transfer of substance or mixture (charging and discharging) at dedicated facilities Use domain: industrial
Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
_	Worker - dermal, long-term - systemic
Exposure estimate	13,7143 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,017229

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 13.12.2023 Date / Previous version: not applicable

Previous version: none

Product: METHOXYPROPYLACETATE

(ID no. 30034751/SDS_GEN_IT/EN)

Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker	
	Worker - inhalation, long-term - systemic	
Exposure estimate	137,6562 mg/m ³	
Risk Characterization Ratio (RCR)	0,500568	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker	
Guidance to Downstream Users		
For scaling see: http://www.ecetoc.org/tra		

Contributing exposure scenario	
<u> </u>	PROC10: Roller application or brushing
Use descriptors covered	Use domain: industrial
Operational conditions	
	2-methoxy-1-methylethyl acetate
Concentration of the substance	Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
	480 min 5 days per week
Duration and Frequency of activity	
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Risk Management Measures	
Provide a good standard of general	
ventilation (not less than 3 - 5 air	Effectiveness: 30 %
changes per hour)	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	27,4286 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,034458
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	192,7187 mg/m³
Risk Characterization Ratio (RCR)	0,700795
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario		
Use descriptors covered	PROC13: Treatment of articles by dipping and pouring. Use domain: industrial	
Operational conditions		
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 100 %	
Physical state	liquid	

Date / Revised: 13.12.2023 Version: 1.0
Date / Previous version: not applicable Previous version: none

Product: METHOXYPROPYLACETATE

(ID no. 30034751/SDS_GEN_IT/EN)

Date of print 21.10.2025

Vapour pressure of the substance during use	502 Pa		
Duration and Frequency of activity	480 min 5 days per week		
Indoor/Outdoor	Indoor		
	Assumes activities are at ambient temperature.		
Risk Management Measures			
Provide a good standard of general			
ventilation (not less than 3 - 5 air	Effectiveness: 30 %		
changes per hour)			
Exposure estimate and reference to	Exposure estimate and reference to its source		
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker		
	Worker - dermal, long-term - systemic		
Exposure estimate	13,7143 mg/kg bw/day		
Risk Characterization Ratio (RCR)	0,017229		
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker		
	Worker - inhalation, long-term - systemic		
Exposure estimate	192,7187 mg/m³		
Risk Characterization Ratio (RCR)	0,700795		
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker		
Guidance to Downstream Users			
For scaling see: http://www.ecetoc.org/tra			

Contributing exposure scenario	
Use descriptors covered	PROC28: Manual maintenance (cleaning and repair) of machinery covered by PROC8a

* * * * * * * * * * * * * * * *

8. Short title of exposure scenario

Cleaning agents, (use in professional settings)

ERC8a, ERC8d; PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC10, PROC11, PROC13, PROC19

Control of exposure and risk management measures

Contributing exposure scenario		
Use descriptors covered	ESVOC SpERC 8.4b.v3	
Operational conditions		
Annual amount used in the EU	8.415.000 kg	
Minimum emission days per year	365	
Emission factor air	4 %	

Date / Revised: 13.12.2023 Version: 1.0
Date / Previous version: not applicable Previous version: none

Product: METHOXYPROPYLACETATE

(ID no. 30034751/SDS_GEN_IT/EN)

Emission factor water	1 ppm	
Emission factor soil	0,2 ppm	
Receive Surf. Water (Flow Rate).	18.000 m3/d	
Dilution factor river	10	
Dilution factor coast	100	
Risk Management Measures		
Type of STP		Municipal STP
Assumed sewage treatment plant flow (ssumed sewage treatment plant flow (m3/d)	
Exposure estimate and reference to its source		
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Environment	
Risk Characterization Ratio (RCR)	0,020201	
	Risk from environmental exposure is driven by soil.	
	228,3	
Maximum amount of safe use	kg/d	
Risk from environmental exposure is driven by soil.		

Contributing exposure scenario			
Use descriptors covered	ESVOC SpERC 8.4b.v3		
Operational conditions	Operational conditions		
Annual amount used in the EU	8.415.000 kg		
Minimum emission days per year	365		
Emission factor air	4 %		
Emission factor water	1 ppm		
Emission factor soil	0,2 ppm		
Receive Surf. Water (Flow Rate).	18.000 m3/d		
Dilution factor river	10		
Dilution factor coast	100		
Risk Management Measures			
Type of STP Mui		Municipal STP	
Assumed sewage treatment plant flow (m3/d) 2.000 m		2.000 m3/d	
Exposure estimate and reference to its source			
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Environment		
Risk Characterization Ratio (RCR)	0,020201		
	Risk from environmental ex	kposure is driven by soil.	

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 13.12.2023 Date / Previous version: not applicable

Product: METHOXYPROPYLACETATE

(ID no. 30034751/SDS_GEN_IT/EN)

Date of print 21.10.2025

Maximum am	ount of safe use	228,3 kg/d
Risk from environmental exposure is driven by soil.		

Contributing exposure scenario	
Use descriptors covered	PROC1: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions. Use domain: professional
Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Exposure estimate and reference to	its source
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	0,0343 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,000043
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	0,0551 mg/m³
Risk Characterization Ratio (RCR)	0,0002
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/	ira

Contributing exposure scenario		
Use descriptors covered	PROC2: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions Use domain: professional	
Operational conditions		
	2-methoxy-1-methylethyl acetate	
Concentration of the substance	Content: >= 0 % - <= 100 %	
Physical state	liquid	
Vapour pressure of the substance	502 Pa	
during use		
Duration and Frequency of activity	480 min 5 days per week	

Page: 77/115

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 13.12.2023 Version: 1.0
Date / Previous version: not applicable Previous version: none

Product: METHOXYPROPYLACETATE

(ID no. 30034751/SDS_GEN_IT/EN)

Indoor/Outdoor	Indoor	
	Assumes activities are at ambient temperature.	
Exposure estimate and reference to	its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker	
	Worker - dermal, long-term - systemic	
Exposure estimate	1,3714 mg/kg bw/day	
Risk Characterization Ratio (RCR)	0,001723	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker	
	Worker - inhalation, long-term - systemic	
Exposure estimate	110,125 mg/m³	
Risk Characterization Ratio (RCR)	0,400455	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker	
Guidance to Downstream Users		
For scaling see: http://www.ecetoc.org/tra		

Contributing exposure scenario		
Use descriptors covered	PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition Use domain: professional	
Operational conditions		
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 100 %	
Physical state	liquid	
Vapour pressure of the substance during use	502 Pa	
Duration and Frequency of activity	480 min 5 days per week	
Indoor/Outdoor	Indoor	
	Assumes activities are at ambient temperature.	
Exposure estimate and reference to its source		
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker	
	Worker - dermal, long-term - systemic	
Exposure estimate	0,6857 mg/kg bw/day	
Risk Characterization Ratio (RCR)	0,000861	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker	
	Worker - inhalation, long-term - systemic	
Exposure estimate	137,6562 mg/m³	
Risk Characterization Ratio (RCR)	0,500568	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker	
Guidance to Downstream Users		
For scaling see: http://www.ecetoc.org/	tra	

Contributing exposure scenario	
Use descriptors covered	PROC4: Chemical production where opportunity for

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 13.12.2023
Date / Previous version: not applicable
Product: METHOXYPROPYLACETATE

(ID no. 30034751/SDS_GEN_IT/EN)

Date of print 21.10.2025

	exposure arises
	Use domain: professional
Operational conditions	
	2-methoxy-1-methylethyl acetate
Concentration of the substance	Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Risk Management Measures	
Provide a good standard of general	
ventilation (not less than 3 - 5 air	Effectiveness: 30 %
changes per hour)	
Exposure estimate and reference to	its source
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	6,8571 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,008615
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	192,7187 mg/m³
Risk Characterization Ratio (RCR)	0,700795
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/	/tra

Contributing exposure scenario	
Use descriptors covered	PROC8a: Transfer of substance or mixture (charging and discharging) at non-dedicated facilities Use domain: professional
Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	240 min 5 days per week
Indoor/Outdoor	Outdoor
	Assumes activities are at ambient temperature.
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 13.12.2023 Date / Previous version: not applicable

Product: METHOXYPROPYLACETATE

(ID no. 30034751/SDS_GEN_IT/EN)

Date of print 21.10.2025

	Worker - dermal, long-term - systemic
Exposure estimate	8,2286 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,010337
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	231,2625 mg/m³
Risk Characterization Ratio (RCR)	0,840955
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/	tra

Contributing exposure scenario		
Use descriptors covered	PROC8b: Transfer of substance or mixture (charging and discharging) at dedicated facilities Use domain: professional	
Operational conditions		
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 100 %	
Physical state	liquid	
Vapour pressure of the substance during use	502 Pa	
Duration and Frequency of activity	480 min 5 days per week	
Indoor/Outdoor	Indoor	
	Assumes activities are at ambient temperature.	
Risk Management Measures		
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %	
Exposure estimate and reference to its source		
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker	
	Worker - dermal, long-term - systemic	
Exposure estimate	13,7143 mg/kg bw/day	
Risk Characterization Ratio (RCR)	0,017229	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker	
	Worker - inhalation, long-term - systemic	
Exposure estimate	192,7187 mg/m³	
Risk Characterization Ratio (RCR)	0,700795	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker	
Guidance to Downstream Users		
For scaling see: http://www.ecetoc.org	/tra	

Contributing exposure scenario	
Use descriptors covered	PROC10: Roller application or brushing Use domain: professional
Operational conditions	

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 13.12.2023
Date / Previous version: not applicable

Product: METHOXYPROPYLACETATE

(ID no. 30034751/SDS_GEN_IT/EN)

Date of print 21.10.2025

Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 100 %		
Physical state	liquid		
Vapour pressure of the substance during use	502 Pa		
Duration and Frequency of activity	480 min 5 days per week		
Indoor/Outdoor	Indoor		
	Assumes activities are at ambient temperature.		
Risk Management Measures			
Provide a good standard of general or controlled ventilation (5 to 10 air changes per hour)	Effectiveness: 70 %		
	Exposure estimate and reference to its source		
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker		
	Worker - dermal, long-term - systemic		
Exposure estimate	27,4286 mg/kg bw/day		
Risk Characterization Ratio (RCR)	0,034458		
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker		
	Worker - inhalation, long-term - systemic		
Exposure estimate	165,1875 mg/m³		
Risk Characterization Ratio (RCR)	0,600682		
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker		
Guidance to Downstream Users			
For scaling see: http://www.ecetoc.org/t	ra		

Contributing exposure scenario	
	PROC11: Non industrial spraying
Use descriptors covered	Use domain: professional
Operational conditions	
	2-methoxy-1-methylethyl acetate
Concentration of the substance	Content: >= 0 % - <= 90 %
Physical state	liquid
Vapour pressure of the substance	502 Pa
during use	
Duration and Frequency of activity	240 min 5 days per week
, , ,	
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
	Any sized room
Application rate	< 3 l/min
Risk Management Measures	
Wear suitable respiratory protection.	Effectiveness: 90 %
Surface spraying with no or low	
compressed air use.	
Provide extract ventilation to points	

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 13.12.2023 Date / Previous version: not applicable

Product: METHOXYPROPYLACETATE

(ID no. 30034751/SDS_GEN_IT/EN)

Date of print 21.10.2025

where emissions occur (LEV).	
Ensure that general housekeeping is	
in place	
Provide a good standard of controlled	
ventilation (10 to 15 air changes per	
hour)	
Exposure estimate and reference to it	ts source
	EASY TRA v5.2, ECETOC TRA v3.0, worker, modified
Assessment method	version, The concentration of the substance has been
	considered using a linear approach.
	Worker - dermal, long-term - systemic
Exposure estimate	57,8571 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,072685
Assessment method	EASY TRA v5.2, Advanced REACH Tool v1.5
	Worker - inhalation, long-term - systemic
Exposure estimate	190 mg/m³
Risk Characterization Ratio (RCR)	0,690909
Assessment method	EASY TRA v5.2, Advanced REACH Tool v1.5
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra For scaling see: http://www.advancedreachtool.com	
Please note that a modified version has	been used (see exposure estimates)

Contributing exposure scenario	
<u> </u>	PROC11: Non industrial spraying
Use descriptors covered	Use domain: professional
Operational conditions	<u> </u>
-	2-methoxy-1-methylethyl acetate
Concentration of the substance	Content: >= 0 % - <= 90 %
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	240 min 5 days per week
Indoor/Outdoor	Outdoor
	Assumes activities are at ambient temperature.
Application rate	< 3 l/min
Risk Management Measures	
Wear suitable respiratory protection.	Effectiveness: 95 %
Surface spraying with no or low compressed air use.	
Ensure that general housekeeping is	
in place	
Exposure estimate and reference to its source	
	EASY TRA v5.2, ECETOC TRA v3.0, worker, modified
Assessment method	version, The concentration of the substance has been
	considered using a linear approach.
	Worker - dermal, long-term - systemic

Date / Revised: 13.12.2023 Version: 1.0
Date / Previous version: not applicable Previous version: none

Product: METHOXYPROPYLACETATE

(ID no. 30034751/SDS_GEN_IT/EN)

Date of print 21.10.2025

Exposure estimate	57,8571 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,072685
Assessment method	EASY TRA v5.2, Advanced REACH Tool v1.5
	Worker - inhalation, long-term - systemic
Exposure estimate	190 mg/m ³
Risk Characterization Ratio (RCR)	0,690909
Assessment method	EASY TRA v5.2, Advanced REACH Tool v1.5
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra For scaling see: http://www.advancedreachtool.com	
Please note that a modified version has been used (see exposure estimates)	

Contributing exposure scenario PROC13: Treatment of articles by dipping and pouring. Use descriptors covered Use domain: professional Operational conditions 2-methoxy-1-methylethyl acetate Concentration of the substance Content: >= 0 % - <= 100 % Physical state liquid Vapour pressure of the substance 502 Pa during use 480 min 5 days per week **Duration and Frequency of activity** Indoor/Outdoor Assumes activities are at ambient temperature. Risk Management Measures Provide a good standard of general or controlled ventilation (5 to 10 air Effectiveness: 70 % changes per hour) Exposure estimate and reference to its source EASY TRA v5.2, ECETOC TRA v3.0, Worker Assessment method Worker - dermal, long-term - systemic Exposure estimate 13,7143 mg/kg bw/day Risk Characterization Ratio (RCR) 0,017229 EASY TRA v5.2, ECETOC TRA v3.0, Worker Assessment method Worker - inhalation, long-term - systemic Exposure estimate 165,1875 mg/m³ Risk Characterization Ratio (RCR) 0,600682 Assessment method EASY TRA v5.2, ECETOC TRA v3.0, Worker Guidance to Downstream Users For scaling see: http://www.ecetoc.org/tra

Contributing exposure scenario	
Use descriptors covered	PROC19: Manual activities involving hand contact Use domain: professional
Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 13.12.2023 Date / Previous version: not applicable

Product: METHOXYPROPYLACETATE

(ID no. 30034751/SDS_GEN_IT/EN)

Date of print 21.10.2025

Previous version: none

	Content: >= 0 % - <= 100 %	
Physical state	liquid	
Vapour pressure of the substance during use	502 Pa	
Duration and Frequency of activity	480 min 5 days per week	
Indoor/Outdoor	Indoor	
	Assumes activities are at ambient temperature.	
Risk Management Measures		
Wear suitable respiratory protection.	Effectiveness: 90 %	
Exposure estimate and reference to its source		
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker	
	Worker - dermal, long-term - systemic	
Exposure estimate	141,4286 mg/kg bw/day	
Risk Characterization Ratio (RCR)	0,177674	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker	
	Worker - inhalation, long-term - systemic	
Exposure estimate	55,0625 mg/m ³	
Risk Characterization Ratio (RCR)	0,200227	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker	
Guidance to Downstream Users		
For scaling see: http://www.ecetoc.org/tra		

9. Short title of exposure scenario

Cleaning agents, (consumer use) ERC8a, ERC8d; PC35

Control of exposure and risk management measures

Contributing exposure scenario	
Use descriptors covered	ESVOC SpERC 8.4c.v2
Operational conditions	
Annual amount used in the EU	168.000 kg
Minimum emission days per year	365
Emission factor air	95 %
Emission factor water	2,5 %
Emission factor soil	2,5 %
Receive Surf. Water (Flow Rate).	18.000 m3/d

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 13.12.2023 Date / Previous version: not applicable

Product: METHOXYPROPYLACETATE

(ID no. 30034751/SDS_GEN_IT/EN)

Date of print 21.10.2025

Previous version: none

Dilution factor river	10	
Dilution factor coast	100	
Risk Management Measures		
Type of STP Municipal S		Municipal STP
Assumed sewage treatment plant flow (m3/d)		2.000 m3/d
Exposure estimate and reference to its source		
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Environment	
Risk Characterization Ratio (RCR)	0,020244	
	Risk from environmental exposure is driven by soil.	
	4,5	
Maximum amount of safe use	kg/d	
Risk from environmental exposure is driven by soil.		

Contributing exposure scenario		
Use descriptors covered	ESVOC SpERC 8.4c.v2	
Operational conditions		
Annual amount used in the EU	168.000 kg	
Minimum emission days per year	365	
Emission factor air	95 %	
Emission factor water	2,5 %	
Emission factor soil	2,5 %	
Receive Surf. Water (Flow Rate).	18.000 m3/d	
Dilution factor river	10	
Dilution factor coast	100	
Risk Management Measures		
Type of STP Municipal STP		Municipal STP
Assumed sewage treatment plant flow (Assumed sewage treatment plant flow (m3/d) 2.000 m3/d	
Exposure estimate and reference to its source		
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Environment	
Risk Characterization Ratio (RCR)	0,020244	
	Risk from environmental ex	rposure is driven by soil.
	4,5	
Maximum amount of safe use	kg/d	
Risk from environmental exposure is dri	iven by soil.	

Contributing exposure scenario

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 13.12.2023
Date / Previous version: not applicable

Product: METHOXYPROPYLACETATE

(ID no. 30034751/SDS_GEN_IT/EN)

Date of print 21.10.2025

Previous version: none

Use descriptors covered	PC8_3, PC35_3: Subcategory: Cleaners, trigger sprays (all purpose cleaners, sanitary products, glass cleaners)	
Operational conditions		
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 10 %	
Vapour pressure of the substance during use	502 Pa	
Duration and Frequency of activity	Exposure duration: 4 h 365 uses per year	
Room size	20 m3	
Indoor/Outdoor	Indoor	
Ventilation rate per hour	0,6	
Exposed skin area	Both hands (820 cm ²)	
Uptake fraction dermal	100 %	
Uptake fraction inhalation	100 %	
	Amount per use 16 g Relevant for inhalative exposure estimates	
Exposure estimate and reference to its source		
Assessment method	EASY TRA v5.2, ECETOC TRA, Consumer	
	Consumer - dermal, long-term - systemic	
Exposure estimate	14,2917 mg/kg bw/day	
Risk Characterization Ratio (RCR)	0,044661	
Assessment method	EASY TRA v5.2, ECETOC TRA, Consumer	
	Consumer - inhalation, long-term - systemic	
Exposure estimate	23,5294 mg/m³	
Risk Characterization Ratio (RCR)	0,713012	
Guidance to Downstream Users		
For scaling see: http://www.ecetoc.org/	tra	

10. Short title of exposure scenario

Use in Agrochemicals, (use in professional settings)

ERC8a, ERC8d; PROC1, PROC2, PROC4, PROC8a, PROC8b, PROC11, PROC13, PROC28

Control of exposure and risk management measures

Contributing exposure scenario	
Use descriptors covered	ECPA SPERC 8d.2.v2
Operational conditions	
Annual amount used in the EU	660.000 kg
Minimum emission days per year	365

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 13.12.2023
Date / Previous version: not applicable

Product: METHOXYPROPYLACETATE

(ID no. 30034751/SDS_GEN_IT/EN)

Date of print 21.10.2025

Emission factor air	100 %	
Emission factor water	0 %	
Emission factor soil	0 %	
Receive Surf. Water (Flow Rate).	18.000 m3/d	
Dilution factor river	10	
Dilution factor coast	100	
Risk Management Measures		
Type of STP no STP		
Exposure estimate and reference to its source		
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Environment	
Risk Characterization Ratio (RCR)	0,020201	
	Risk from environmental exposure is driven by soil.	
	17,9	
Maximum amount of safe use	kg/d	
Risk from environmental exposure is driven by soil.		

Contributing exposure scenario		
Use descriptors covered	ECPA SPERC 8d.2.v2	
Operational conditions		
Annual amount used in the EU	660.000 kg	
Minimum emission days per year	365	
Emission factor air	100 %	
Emission factor water	0 %	
Emission factor soil	0 %	
Receive Surf. Water (Flow Rate).	18.000 m3/d	
Dilution factor river	10	
Dilution factor coast	100	
Risk Management Measures		
Type of STP	no STP	
Exposure estimate and reference to	its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Environment	
Risk Characterization Ratio (RCR)	0,020201	

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 13.12.2023
Date / Previous version: not applicable

Product: METHOXYPROPYLACETATE

(ID no. 30034751/SDS_GEN_IT/EN)

Date of print 21.10.2025

Maximum amount of safe use	Risk from environmental exposure is driven by soil. 17,9 kg/d
Risk from environmental exposure is dri	ven by soil.

Contributing exposure scenario		
Use descriptors covered	PROC1: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions. Use domain: professional	
Operational conditions		
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 100 %	
Physical state	liquid	
Vapour pressure of the substance during use	502 Pa	
Duration and Frequency of activity	480 min 5 days per week	
Indoor/Outdoor	Indoor	
	Assumes activities are at ambient temperature.	
Exposure estimate and reference to		
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker	
	Worker - dermal, long-term - systemic	
Exposure estimate	0,0343 mg/kg bw/day	
Risk Characterization Ratio (RCR)	0,000043	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker	
	Worker - inhalation, long-term - systemic	
Exposure estimate	0,0551 mg/m³	
Risk Characterization Ratio (RCR)	0,0002	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker	
Guidance to Downstream Users		
For scaling see: http://www.ecetoc.org/	tra	

Contributing exposure scenario		
Use descriptors covered	PROC2: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions Use domain: professional	
Operational conditions		
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 100 %	
Concentration of the substance	Contont. >= 0 /0 <= 100 /0	
Physical state	liquid	
Vapour pressure of the substance during use	502 Pa	

Page: 88/115

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 13.12.2023 Version: 1.0
Date / Previous version: not applicable Previous version: none

Product: METHOXYPROPYLACETATE

(ID no. 30034751/SDS_GEN_IT/EN)

Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Outdoor
	Assumes activities are at ambient temperature.
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	1,3714 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,001723
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	77,0875 mg/m³
Risk Characterization Ratio (RCR)	0,280318
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC4: Chemical production where opportunity for exposure arises Use domain: professional
Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Outdoor
	Assumes activities are at ambient temperature.
Exposure estimate and reference to	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	6,8571 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,008615
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	192,7187 mg/m³
Risk Characterization Ratio (RCR)	0,700795
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org	/tra

Contributing exposure scenario	
Use descriptors covered	PROC8a: Transfer of substance or mixture (charging and discharging) at non-dedicated facilities

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 13.12.2023
Date / Previous version: not applicable
Product: METHOXYPROPYLACETATE

(ID no. 30034751/SDS_GEN_IT/EN)

Date of print 21.10.2025

	Use domain: professional
Operational conditions	<u> </u>
	2-methoxy-1-methylethyl acetate
Concentration of the substance	Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	240 min 5 days per week
Indoor/Outdoor	Outdoor
	Assumes activities are at ambient temperature.
Exposure estimate and reference to	its source
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	8,2286 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,010337
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	231,2625 mg/m³
Risk Characterization Ratio (RCR)	0,840955
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/t	ra

Contributing exposure scenario		
Use descriptors covered	PROC8a: Transfer of substance or mixture (charging and discharging) at non-dedicated facilities Use domain: professional	
Operational conditions		
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 100 %	
Physical state	liquid	
Vapour pressure of the substance during use	502 Pa	
Duration and Frequency of activity	240 min 5 days per week	
Indoor/Outdoor	Indoor	
	Assumes activities are at ambient temperature.	
Risk Management Measures		
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %	
Exposure estimate and reference to its source		
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker	
	Worker - dermal, long-term - systemic	

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 13.12.2023 Date / Previous version: not applicable

Product: METHOXYPROPYLACETATE

(ID no. 30034751/SDS_GEN_IT/EN)

Date of print 21.10.2025

Exposure estimate	8,2286 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,010337
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	231,2625 mg/m ³
Risk Characterization Ratio (RCR)	0,840955
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC8b: Transfer of substance or mixture (charging and discharging) at dedicated facilities Use domain: professional
Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Risk Management Measures	
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %
Exposure estimate and reference to	its source
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	13,7143 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,017229
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	192,7187 mg/m³
Risk Characterization Ratio (RCR)	0,700795
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org	/tra

Contributing exposure scenario	
Use descriptors covered	PROC11: Non industrial spraying Use domain: professional
	Surface spraying of liquids

Date / Revised: 13.12.2023 Version: 1.0
Date / Previous version: not applicable Previous version: none

Product: METHOXYPROPYLACETATE

(ID no. 30034751/SDS_GEN_IT/EN)

Operational conditions	Operational conditions	
	2-methoxy-1-methylethyl acetate	
Concentration of the substance	Content: >= 0 % - <= 100 %	
Physical state	liquid	
Vapour pressure of the substance during use	502 Pa	
during use	480 min 5 days per week	
Duration and Frequency of activity	400 min 3 days per week	
Indoor/Outdoor	outdoor, away from buildings	
	Assumes activities are at ambient temperature.	
Application rate	< 3 l/min	
Risk Management Measures		
Ensure that the distance from worker		
to emission source is greater than 4		
m.		
Ensure that the task is being carried		
out outside the breathing zone of a		
worker (distance head-product greater		
than 1m).		
Ensure that the worker is in a		
personal enclosure		
Exposure estimate and reference to		
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker	
	Worker - dermal, long-term - systemic	
Exposure estimate	107,1429 mg/kg bw/day	
Risk Characterization Ratio (RCR)	0,134602	
Assessment method	EASY TRA v5.2, Advanced REACH Tool v1.5	
	Worker - inhalation, long-term - systemic	
Exposure estimate	16 mg/m³	
Risk Characterization Ratio (RCR)	0,058182	
Assessment method	EASY TRA v5.2, Advanced REACH Tool v1.5	
Guidance to Downstream Users		
For scaling see: http://www.ecetoc.org/t	ra For scaling see: http://www.advancedreachtool.com	

Contributing exposure scenario	
Use descriptors covered	PROC11: Non industrial spraying Use domain: professional
Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 90 %
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	240 min 5 days per week
Indoor/Outdoor	Outdoor

Date / Revised: 13.12.2023 Version: 1.0
Date / Previous version: not applicable Previous version: none

Product: METHOXYPROPYLACETATE

(ID no. 30034751/SDS_GEN_IT/EN)

	Assumes activities are at ambient temperature.	
Application rate	< 3 l/min	
Risk Management Measures		
Wear suitable respiratory protection.	Effectiveness: 95 %	
Surface spraying with no or low compressed air use.		
Ensure that general housekeeping is in place		
Exposure estimate and reference to its source		
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, worker, modified version, The concentration of the substance has been considered using a linear approach.	
	Worker - dermal, long-term - systemic	
Exposure estimate	57,8571 mg/kg bw/day	
Risk Characterization Ratio (RCR)	0,072685	
Assessment method	EASY TRA v5.2, Advanced REACH Tool v1.5	
	Worker - inhalation, long-term - systemic	
Exposure estimate	190 mg/m³	
Risk Characterization Ratio (RCR)	0,690909	
Assessment method	EASY TRA v5.2, Advanced REACH Tool v1.5	
Guidance to Downstream Users		
For scaling see: http://www.ecetoc.org/tra For scaling see: http://www.advancedreachtool.com Please note that a modified version has been used (see exposure estimates)		

Contributing exposure scenario		
Use descriptors covered	PROC13: Treatment of articles by dipping and pouring. Use domain: professional	
Operational conditions		
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 100 %	
Physical state	liquid	
Vapour pressure of the substance during use	502 Pa	
Duration and Frequency of activity	240 min 5 days per week	
Indoor/Outdoor	Indoor	
	Assumes activities are at ambient temperature.	
Risk Management Measures		
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %	
Exposure estimate and reference to its source		
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker	
	Worker - dermal, long-term - systemic	
Exposure estimate	8,2286 mg/kg bw/day	
Risk Characterization Ratio (RCR)	0,010337	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker	

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 13.12.2023 Date / Previous version: not applicable Previous version: none

Product: METHOXYPROPYLACETATE

(ID no. 30034751/SDS_GEN_IT/EN)

Date of print 21.10.2025

	Worker - inhalation, long-term - systemic
Exposure estimate	231,2625 mg/m ³
Risk Characterization Ratio (RCR)	0,840955
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC28: Manual maintenance (cleaning and repair) of machinery covered by PROC8a

11. Short title of exposure scenario

Use in Agrochemicals, (consumer use) ERC8a, ERC8d; PC27

Control of exposure and risk management measures

Contributing exposure scenario		
Use descriptors covered	ECPA SPERC 8d.2.v2	
Operational conditions		
Annual amount used in the EU	660.000 kg	
Minimum emission days per year	365	
Emission factor air	100 %	
Emission factor water	0 %	
Emission factor soil	0 %	
Receive Surf. Water (Flow Rate).	18.000 m3/d	
Dilution factor river	10	
Dilution factor coast	100	
Risk Management Measures		
Type of STP no STP		
Exposure estimate and reference to its source		
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Environment	
Risk Characterization Ratio (RCR)	0,020201	
	Risk from environmental exposure is driven by soil.	
Maximum amount of safe use	17,9	

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 13.12.2023
Date / Previous version: not applicable
Product: METHOXYPROPYLACETATE

Previous version: none

(ID no. 30034751/SDS_GEN_IT/EN)
Date of print 21.10.2025

k	xg/d
Risk from environmental exposure is driver	en by soil.

Contributing exposure scenario		
Use descriptors covered	ECPA SPERC 8d.2.v2	
Operational conditions		
Annual amount used in the EU	660.000 kg	
Minimum emission days per year	365	
Emission factor air	100 %	
Emission factor water	0 %	
Emission factor soil	0 %	
Receive Surf. Water (Flow Rate).	18.000 m3/d	
Dilution factor river	10	
Dilution factor coast	100	
Risk Management Measures		
Type of STP	no STP	
Exposure estimate and reference to its source		
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Environment	
Risk Characterization Ratio (RCR)	0,020201	
	Risk from environmental exposure is driven by soil.	
	17,9	
Maximum amount of safe use	kg/d	
Risk from environmental exposure is driven by soil.		

Contributing exposure scenario		
Use descriptors covered	PC27: Plant Protection products.	
Operational conditions	-	
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 70 %	
Vapour pressure of the substance during use	502 Pa	
Duration and Frequency of activity	Exposure duration: 240 min Relevant for inhalative exposure estimates	
Duration and Frequency of activity	9 uses per year	
Room size	58 m3	

Date / Revised: 13.12.2023 Version: 1.0
Date / Previous version: not applicable Previous version: none

Product: METHOXYPROPYLACETATE

(ID no. 30034751/SDS_GEN_IT/EN)

Date of print 21.10.2025

Ventilation rate per hour	0,5	
body weight	65 kg	
Uptake fraction dermal	100 %	
optano naotion donnai	Relevant for dermal exposure estimates	
	Relevant for dermal exposure estimates	
Spray duration	600 sec	
Contact rate	100 mg/min	
Release duration	10 min	
	Relevant for dermal exposure estimates	
Risk Management Measures		
Consumer Measures	Ensure spraying away from persons.	
Exposure estimate and reference to its source		
Assessment method	EASY TRA v5.2, ConsExpo v4.1, Dermal model: constant	
Assessment method	application rate, Uptake model: Uptake fraction	
	Consumer - dermal, long-term - systemic	
Exposure estimate	0,2655 mg/kg bw/day	
Risk Characterization Ratio (RCR)	0,00083	
	The calculation is based on the internal chronic dose.	
Assessment method	EASY TRA v5.2, ConsExpo v4.1, Inhalation model:	
Assessment method	Exposure to spray/dust	
	Consumer - inhalation, long-term - systemic	
Exposure estimate	1,1628 mg/m³	
Risk Characterization Ratio (RCR)	0,035235	
	The exposure calculation is based on the mean	
	concentration per year.	
Guidance to Downstream Users		
For scaling see: http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp		

12. Short title of exposure scenario

Use in Printing inks, (use in industrial settings)

ERC4; PROC1, PROC2, PROC3, PROC4, PROC5, PROC7, PROC8a, PROC8b, PROC9, PROC10, PROC13, PROC15, PROC28

Control of exposure and risk management measures

Contributing exposure scenario	
Use descriptors covered	CEPE SPERC 4.1b.v2
Operational conditions	
Annual amount used in the EU	3.300.000 kg
Minimum emission days per year	225
Emission factor air	95 %

Date / Revised: 13.12.2023 Version: 1.0
Date / Previous version: not applicable Previous version: none

Product: METHOXYPROPYLACETATE

(ID no. 30034751/SDS_GEN_IT/EN)

Emission factor water	0 %	
Emission factor soil	0 %	
Receive Surf. Water (Flow Rate).	18.000 m3/d	
Dilution factor river	10	
Dilution factor coast	100	
Risk Management Measures		
Type of STP		Municipal STP
Assumed sewage treatment plant flow ((m3/d)	2.000 m3/d
Exposure estimate and reference to its source		
Assessment method	EASY TRA v5.2, ECETOC	TRA v3.0, Environment
Risk Characterization Ratio (RCR)	0,164065	
	Risk from environmental ex	rposure is driven by soil.
	8.939,6	
Maximum amount of safe use	kg/d	
Risk from environmental exposure is driven by soil.		

Contributing exposure scenario		
Use descriptors covered	PROC1: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions. Use domain: industrial	
Operational conditions		
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 100 %	
Physical state	liquid	
Vapour pressure of the substance during use	502 Pa	
Duration and Frequency of activity	480 min 5 days per week	
Indoor/Outdoor	Indoor	
	Assumes activities are at ambient temperature.	
Exposure estimate and reference to its source		
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker	
	Worker - dermal, long-term - systemic	
Exposure estimate	0,0343 mg/kg bw/day	
Risk Characterization Ratio (RCR)	0,000043	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker	
	Worker - inhalation, long-term - systemic	
Exposure estimate	0,0551 mg/m³	
Risk Characterization Ratio (RCR)	0,0002	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker	

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 13.12.2023
Date / Previous version: not applicable
Product: METHOXYPROPYLACETATE

Previous version: none

(ID no. 30034751/SDS_GEN_IT/EN)

Date of print 21.10.2025

Guidance to Downstream Users For scaling see: http://www.ecetoc.org/tra

Contributing exposure scenario		
Use descriptors covered	PROC2: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions Use domain: industrial	
Operational conditions		
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 100 %	
Physical state	liquid	
Vapour pressure of the substance during use	502 Pa	
Duration and Frequency of activity	480 min 5 days per week	
Indoor/Outdoor	Indoor	
	Assumes activities are at ambient temperature.	
Exposure estimate and reference to its source		
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker	
	Worker - dermal, long-term - systemic	
Exposure estimate	1,3714 mg/kg bw/day	
Risk Characterization Ratio (RCR)	0,001723	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker	
	Worker - inhalation, long-term - systemic	
Exposure estimate	27,5312 mg/m³	
Risk Characterization Ratio (RCR)	0,100114	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker	
Guidance to Downstream Users		
For scaling see: http://www.ecetoc.org/tra		

Contributing exposure scenario		
Use descriptors covered	PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition Use domain: industrial	
Operational conditions		
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 100 %	
Physical state	liquid	
Vapour pressure of the substance during use	502 Pa	
Duration and Frequency of activity	480 min 5 days per week	

Date / Revised: 13.12.2023 Version: 1.0
Date / Previous version: not applicable
Product: METHOXYPROPYLACETATE

(ID no. 30034751/SDS_GEN_IT/EN)

Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	0,6857 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,000861
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	55,0625 mg/m ³
Risk Characterization Ratio (RCR)	0,200227
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario		
Use descriptors covered	PROC4: Chemical production where opportunity for exposure arises Use domain: industrial	
Operational conditions		
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 100 %	
Physical state	liquid	
Vapour pressure of the substance during use	502 Pa	
Duration and Frequency of activity	480 min 5 days per week	
Indoor/Outdoor	Indoor	
	Assumes activities are at ambient temperature.	
Exposure estimate and reference to its source		
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker	
	Worker - dermal, long-term - systemic	
Exposure estimate	6,8571 mg/kg bw/day	
Risk Characterization Ratio (RCR)	0,008615	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker	
·	Worker - inhalation, long-term - systemic	
Exposure estimate	110,125 mg/m³	
Risk Characterization Ratio (RCR)	0,400455	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker	
Guidance to Downstream Users		
For scaling see: http://www.ecetoc.org	/tra	

Contributing exposure scenario	
Use descriptors covered	PROC5: Mixing or blending in batch processes Use domain: industrial
Operational conditions	

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 13.12.2023
Date / Previous version: not applicable

Product: METHOXYPROPYLACETATE

(ID no. 30034751/SDS_GEN_IT/EN)

Date of print 21.10.2025

Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 100 %	
Physical state	liquid	
Vapour pressure of the substance during use	502 Pa	
Duration and Frequency of activity	480 min 5 days per week	
Indoor/Outdoor	Indoor	
	Assumes activities are at ambient temperature.	
Risk Management Measures		
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %	
Exposure estimate and reference to its source		
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker	
	Worker - dermal, long-term - systemic	
Exposure estimate	13,7143 mg/kg bw/day	
Risk Characterization Ratio (RCR)	0,017229	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker	
	Worker - inhalation, long-term - systemic	
Exposure estimate	192,7187 mg/m³	
Risk Characterization Ratio (RCR)	0,700795	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker	
Guidance to Downstream Users		
For scaling see: http://www.ecetoc.org	/tra	

Contributing exposure scenario	
	PROC7: Industrial spraying
Use descriptors covered	Use domain: industrial
Operational conditions	
	2-methoxy-1-methylethyl acetate
Concentration of the substance	Content: >= 0 % - <= 90 %
Physical state	liquid
Vapour pressure of the substance	502 Pa
during use	
Duration and Frequency of activity	240 min 5 days per week
, , ,	
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
	Any sized room
Application rate	< 3 l/min
Risk Management Measures	
Wear suitable respiratory protection.	Effectiveness: 90 %
Surface spraying with no or low	
compressed air use.	
Provide extract ventilation to points	

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 13.12.2023 Date / Previous version: not applicable

Previous version: none Product: METHOXYPROPYLACETATE

(ID no. 30034751/SDS_GEN_IT/EN)

where emissions occur (LEV).	
Ensure that general housekeeping is	
in place	
Provide a good standard of controlled	
ventilation (10 to 15 air changes per	
hour)	
Exposure estimate and reference to it	ts source
	EASY TRA v5.2, ECETOC TRA v3.0, worker, modified
Assessment method	version, The concentration of the substance has been
	considered using a linear approach.
	Worker - dermal, long-term - systemic
Exposure estimate	23,1429 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,029074
Assessment method	EASY TRA v5.2, Advanced REACH Tool v1.5
	Worker - inhalation, long-term - systemic
Exposure estimate	190 mg/m³
Risk Characterization Ratio (RCR)	0,690909
Assessment method	EASY TRA v5.2, Advanced REACH Tool v1.5
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra For scaling see: http://www.advancedreachtool.com	
Please note that a modified version has been used (see exposure estimates)	

Contributing exposure scenario	
<u> </u>	PROC7: Industrial spraying
Use descriptors covered	Use domain: industrial
	Surface spraying of liquids
Operational conditions	<u> </u>
	2-methoxy-1-methylethyl acetate
Concentration of the substance	Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance	502 Pa
during use	
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Application rate	< 3 l/min
Risk Management Measures	
Ensure that general housekeeping is	
in place	
Provide a good standard of controlled	
ventilation (10 to 15 air changes per	
hour)	
Ensure that the task is being carried	
out outside the breathing zone of a	
worker (distance head-product greater	

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 13.12.2023
Date / Previous version: not applicable
Product: METHOXYPROPYLACETATE

(ID no. 30034751/SDS_GEN_IT/EN)

Date of print 21.10.2025

than 1m).	
Ensure that the worker is in a	
seperated (control) room with	
independent air supply	
Ensure good work practices are	
implemented.	
Provide a good standard of general or	
controlled ventilation (5 to 10 air	
changes per hour) Carry out in a fully	
closed cabin with independent	
exhaust ventilation	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	42,8571 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,053841
Assessment method	EASY TRA v5.2, Advanced REACH Tool v1.5
	Worker - inhalation, long-term - systemic
Exposure estimate	180 mg/m ³
Risk Characterization Ratio (RCR)	0,654545
Assessment method	EASY TRA v5.2, Advanced REACH Tool v1.5
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/t	ra For scaling see: http://www.advancedreachtool.com

Contributing exposure scenario		
Use descriptors covered	PROC8a: Transfer of substance or mixture (charging and discharging) at non-dedicated facilities Use domain: industrial	
Operational conditions		
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 100 %	
Physical state	liquid	
Vapour pressure of the substance during use	502 Pa	
Duration and Frequency of activity	480 min 5 days per week	
Indoor/Outdoor	Indoor	
	Assumes activities are at ambient temperature.	
Risk Management Measures		
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %	
Exposure estimate and reference to its source		
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker	
	Worker - dermal, long-term - systemic	
Exposure estimate	13,7143 mg/kg bw/day	
Risk Characterization Ratio (RCR)	0,017229	

Date / Revised: 13.12.2023 Version: 1.0
Date / Previous version: not applicable Previous version: none

Product: METHOXYPROPYLACETATE

(ID no. 30034751/SDS_GEN_IT/EN)

Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	192,7187 mg/m ³
Risk Characterization Ratio (RCR)	0,700795
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/	/tra

Contributing exposure scenario	
Use descriptors covered	PROC8b: Transfer of substance or mixture (charging and discharging) at dedicated facilities Use domain: industrial
Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Exposure estimate and reference to	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	13,7143 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,017229
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	137,6562 mg/m³
Risk Characterization Ratio (RCR)	0,500568
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org	/tra

Contributing exposure scenario		
Use descriptors covered	PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing). Use domain: industrial	
Operational conditions		
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 100 %	
Physical state	liquid	
Vapour pressure of the substance during use	502 Pa	

Date / Revised: 13.12.2023 Version: 1.0
Date / Previous version: not applicable Previous version: none

Product: METHOXYPROPYLACETATE

(ID no. 30034751/SDS_GEN_IT/EN)

Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Risk Management Measures	
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	6,8571 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,008615
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	192,7187 mg/m³
Risk Characterization Ratio (RCR)	0,700795
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario		
Use descriptors covered	PROC10: Roller application or brushing Use domain: industrial	
Operational conditions		
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 100 %	
Physical state	liquid	
Vapour pressure of the substance during use	502 Pa	
Duration and Frequency of activity	480 min 5 days per week	
Indoor/Outdoor	Indoor	
	Assumes activities are at ambient temperature.	
Risk Management Measures		
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %	
Exposure estimate and reference to	its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker, Reduction factor for local exhaust ventilation (LEV) has been used for the calculation of dermal exposure estimates. Worker - dermal, long-term - systemic	
Exposure estimate	27,4286 mg/kg bw/day	
Risk Characterization Ratio (RCR)	0,034458	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker	
	Worker - inhalation, long-term - systemic	

Date / Revised: 13.12.2023 Version: 1.0
Date / Previous version: not applicable Previous version: none

Product: METHOXYPROPYLACETATE

(ID no. 30034751/SDS_GEN_IT/EN)

Exposure estimate	192,7187 mg/m³
Risk Characterization Ratio (RCR)	0,700795
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario		
Use descriptors covered	PROC13: Treatment of articles by dipping and pouring. Use domain: industrial	
Operational conditions		
	2-methoxy-1-methylethyl acetate	
Concentration of the substance	Content: >= 0 % - <= 100 %	
Physical state	liquid	
Vapour pressure of the substance during use	502 Pa	
Duration and Frequency of activity	480 min 5 days per week	
Indoor/Outdoor	Indoor	
	Assumes activities are at ambient temperature.	
Risk Management Measures		
Provide a good standard of general		
ventilation (not less than 3 - 5 air	Effectiveness: 30 %	
changes per hour)		
Exposure estimate and reference to	its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker	
	Worker - dermal, long-term - systemic	
Exposure estimate	13,7143 mg/kg bw/day	
Risk Characterization Ratio (RCR)	0,017229	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker	
	Worker - inhalation, long-term - systemic	
Exposure estimate	192,7187 mg/m³	
Risk Characterization Ratio (RCR)	0,700795	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker	
Guidance to Downstream Users		
For scaling see: http://www.ecetoc.org	ı/tra	

Contributing exposure scenario		
Use descriptors covered	PROC15: Use a laboratory reagent. Use domain: industrial	
Operational conditions		
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 100 %	
Physical state	liquid	
Vapour pressure of the substance during use	502 Pa	

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 13.12.2023 Date / Previous version: not applicable

Product: METHOXYPROPYLACETATE

(ID no. 30034751/SDS_GEN_IT/EN)

Date of print 21.10.2025

Previous version: none

Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	0,3429 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,000431
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	55,0625 mg/m ³
Risk Characterization Ratio (RCR)	0,200227
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC28: Manual maintenance (cleaning and repair) of machinery covered by PROC8a

* * * * * * * * * * * * * * * *

13. Short title of exposure scenario

Use in Coatings, (coil), (use in industrial settings) ERC4; PROC1, PROC2, PROC3, PROC4, PROC5, PROC7, PROC8a, PROC8b, PROC9, PROC10, PROC13, PROC15, PROC28

Control of exposure and risk management measures

Contributing exposure scenario	
Use descriptors covered	CEPE SPERC 4.1a.v2
Operational conditions	
Annual amount used in the EU	25.000.000 kg
Minimum emission days per year	225
Emission factor air	20,8 %
Emission factor water	0 %
Emission factor soil	0 %
Receive Surf. Water (Flow Rate).	18.000 m3/d

Page: 106/115

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 13.12.2023 Version: 1.0
Date / Previous version: not applicable Previous version: none

Product: METHOXYPROPYLACETATE

(ID no. 30034751/SDS_GEN_IT/EN)

Dilution factor river	10	
Dilution factor coast	100	
Risk Management Measures		
		Municipal STP
Assumed sewage treatment plant flow (m3/d)		2.000 m3/d
Exposure estimate and reference to its source		
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Environment	
Risk Characterization Ratio (RCR)	0,258827	
	Risk from environmental exposure is driven by soil.	
	42.928,8	
Maximum amount of safe use	kg/d	
Risk from environmental exposure is driven by soil.		

Contributing exposure scenario	
Use descriptors covered	PROC1: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions. Use domain: industrial
Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Exposure estimate and reference to	its source
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	0,0343 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,000043
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	0,0551 mg/m³
Risk Characterization Ratio (RCR)	0,0002
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org	/tra

Contributing exposure scenario	
Use descriptors covered	PROC2: Chemical production or refinery in closed
	continuous process with occasional controlled exposure or

Date / Revised: 13.12.2023

Version: 1.0 Previous version: none

Date / Previous version: not applicable Product: METHOXYPROPYLACETATE

(ID no. 30034751/SDS_GEN_IT/EN)

	processes with equivalent containment conditions Use domain: industrial
Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Exposure estimate and reference to	its source
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	1,3714 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,001723
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	27,5312 mg/m³
Risk Characterization Ratio (RCR)	0,100114
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/	'tra

Contributing avacaure cooperie	
Contributing exposure scenario	
Use descriptors covered	PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition Use domain: industrial
Operational conditions	
	2-methoxy-1-methylethyl acetate
Concentration of the substance	Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	0,6857 mg/kg bw/day

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 13.12.2023 Date / Previous version: not applicable

Date / Previous version: not applicable Previous version: none Product: **METHOXYPROPYLACETATE**

(ID no. 30034751/SDS_GEN_IT/EN)

Risk Characterization Ratio (RCR)	0,000861
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	55,0625 mg/m ³
Risk Characterization Ratio (RCR)	0,200227
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/	tra

Contributing exposure scenario		
Use descriptors covered	PROC4: Chemical production where opportunity for exposure arises Use domain: industrial	
Operational conditions		
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 100 %	
Physical state	liquid	
Vapour pressure of the substance during use	502 Pa	
Duration and Frequency of activity	480 min 5 days per week	
Indoor/Outdoor	Indoor	
	Assumes activities are at ambient temperature.	
Exposure estimate and reference to		
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker	
	Worker - dermal, long-term - systemic	
Exposure estimate	6,8571 mg/kg bw/day	
Risk Characterization Ratio (RCR)	0,008615	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker	
	Worker - inhalation, long-term - systemic	
Exposure estimate	110,125 mg/m³	
Risk Characterization Ratio (RCR)	0,400455	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker	
Guidance to Downstream Users		
For scaling see: http://www.ecetoc.org/	/tra	

Contributing exposure scenario		
Use descriptors covered	PROC5: Mixing or blending in batch processes Use domain: industrial	
Operational conditions		
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 100 %	
Physical state	liquid	
Vapour pressure of the substance during use	502 Pa	

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 13.12.2023
Date / Previous version: not applicable

Product: METHOXYPROPYLACETATE

(ID no. 30034751/SDS_GEN_IT/EN)

Date of print 21.10.2025

Duration and Frequency of activity	480 min 5 days per week	
Indoor/Outdoor	Indoor	
	Assumes activities are at ambient temperature.	
Risk Management Measures		
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %	
Exposure estimate and reference to its source		
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker	
	Worker - dermal, long-term - systemic	
Exposure estimate	13,7143 mg/kg bw/day	
Risk Characterization Ratio (RCR)	0,017229	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker	
	Worker - inhalation, long-term - systemic	
Exposure estimate	192,7187 mg/m³	
Risk Characterization Ratio (RCR)	0,700795	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker	
Guidance to Downstream Users		
For scaling see: http://www.ecetoc.org/tra		

Contributing exposure scenario		
Use descriptors covered	PROC7: Industrial spraying Use domain: industrial	
Operational conditions		
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 90 %	
Physical state	liquid	
Vapour pressure of the substance during use	502 Pa	
Duration and Frequency of activity	240 min 5 days per week	
Indoor/Outdoor	Indoor	
	Assumes activities are at ambient temperature.	
	Any sized room	
Application rate	< 3 l/min	
Risk Management Measures		
Wear suitable respiratory protection.	Effectiveness: 90 %	
Surface spraying with no or low		
compressed air use.		
Provide extract ventilation to points		
where emissions occur (LEV).		
Ensure that general housekeeping is in place		
Provide a good standard of controlled ventilation (10 to 15 air changes per hour)		

Date / Revised: 13.12.2023

Version: 1.0 Previous version: none

Date / Previous version: not applicable Product: **METHOXYPROPYLACETATE**

(ID no. 30034751/SDS_GEN_IT/EN)

Exposure estimate and reference to its source	
	EASY TRA v5.2, ECETOC TRA v3.0, worker, modified
Assessment method	version, The concentration of the substance has been
	considered using a linear approach.
	Worker - dermal, long-term - systemic
Exposure estimate	23,1429 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,029074
Assessment method	EASY TRA v5.2, Advanced REACH Tool v1.5
	Worker - inhalation, long-term - systemic
Exposure estimate	190 mg/m ³
Risk Characterization Ratio (RCR)	0,690909
Assessment method	EASY TRA v5.2, Advanced REACH Tool v1.5
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra For scaling see: http://www.advancedreachtool.com	
Please note that a modified version has been used (see exposure estimates)	

Contributing exposure scenario	
·	PROC7: Industrial spraying
Use descriptors covered	Use domain: industrial
	Surface spraying of liquids
Operational conditions	
-	2-methoxy-1-methylethyl acetate
Concentration of the substance	Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Application rate	< 3 l/min
Risk Management Measures	
Ensure that general housekeeping is	
in place	
Provide a good standard of controlled	
ventilation (10 to 15 air changes per	
hour)	
Ensure that the task is being carried	
out outside the breathing zone of a	
worker (distance head-product greater	
than 1m).	
Ensure that the worker is in a	
seperated (control) room with	
independent air supply	<u> </u>
Exposure estimate and reference to	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker

Date / Revised: 13.12.2023 Version: 1.0
Date / Previous version: not applicable
Product: METHOXYPROPYLACETATE

Version: 1.0
Previous version: none

(ID no. 30034751/SDS_GEN_IT/EN)

	Worker - dermal, long-term - systemic
Exposure estimate	42,8571 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,053841
Assessment method	EASY TRA v5.2, Advanced REACH Tool v1.5
	Worker - inhalation, long-term - systemic
Exposure estimate	180 mg/m³
Risk Characterization Ratio (RCR)	0,654545
Assessment method	EASY TRA v5.2, Advanced REACH Tool v1.5
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra For scaling see: http://www.advancedreachtool.com	

Contributing exposure scenario		
Use descriptors covered	PROC8a: Transfer of substance or mixture (charging and discharging) at non-dedicated facilities Use domain: industrial	
Operational conditions		
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 100 %	
Physical state	liquid	
Vapour pressure of the substance during use	502 Pa	
Duration and Frequency of activity	480 min 5 days per week	
Indoor/Outdoor	Indoor	
	Assumes activities are at ambient temperature.	
Risk Management Measures		
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %	
Exposure estimate and reference to	its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker	
	Worker - dermal, long-term - systemic	
Exposure estimate	13,7143 mg/kg bw/day	
Risk Characterization Ratio (RCR)	0,017229	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker	
	Worker - inhalation, long-term - systemic	
Exposure estimate	192,7187 mg/m³	
Risk Characterization Ratio (RCR)	0,700795	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker	
Guidance to Downstream Users		
For scaling see: http://www.ecetoc.org/tra		

Contributing exposure scenario	
Use descriptors covered	PROC8b: Transfer of substance or mixture (charging and discharging) at dedicated facilities Use domain: industrial

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 13.12.2023
Date / Previous version: not applicable

Product: METHOXYPROPYLACETATE

(ID no. 30034751/SDS_GEN_IT/EN)

Date of print 21.10.2025

Operational conditions	
	2-methoxy-1-methylethyl acetate
Concentration of the substance	Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance	502 Pa
during use	
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	13,7143 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,017229
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	137,6562 mg/m³
Risk Characterization Ratio (RCR)	0,500568
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/	′tra

Contributing exposure scenario	
Use descriptors covered	PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing). Use domain: industrial
Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Risk Management Measures	
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %
Exposure estimate and reference to	its source
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	6,8571 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,008615

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 13.12.2023
Date / Previous version: not applicable
Product: METHOXYPROPYLACETATE

Previous version: none

(ID no. 30034751/SDS_GEN_IT/EN)

Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	192,7187 mg/m ³
Risk Characterization Ratio (RCR)	0,700795
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario		
-	PROC10: Roller application or brushing	
Use descriptors covered	Use domain: industrial	
Operational conditions		
	2-methoxy-1-methylethyl acetate	
Concentration of the substance	Content: >= 0 % - <= 100 %	
Physical state	liquid	
Vapour pressure of the substance	502 Pa	
during use		
Duration and Frequency of activity	480 min 5 days per week	
Indoor/Outdoor	Indoor	
	Assumes activities are at ambient temperature.	
Risk Management Measures		
Provide a good standard of general		
ventilation (not less than 3 - 5 air	Effectiveness: 30 %	
changes per hour)		
Exposure estimate and reference to		
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker	
	Worker - dermal, long-term - systemic	
Exposure estimate	27,4286 mg/kg bw/day	
Risk Characterization Ratio (RCR)	0,034458	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker	
	Worker - inhalation, long-term - systemic	
Exposure estimate	192,7187 mg/m³	
Risk Characterization Ratio (RCR)	0,700795	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker	
Guidance to Downstream Users		
For scaling see: http://www.ecetoc.org/tra		

Contributing exposure scenario	
Use descriptors covered	PROC13: Treatment of articles by dipping and pouring. Use domain: industrial
Operational conditions	·
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid

Date / Revised: 13.12.2023 Version: 1.0
Date / Previous version: not applicable Previous version: none

Product: METHOXYPROPYLACETATE

(ID no. 30034751/SDS_GEN_IT/EN)

Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Risk Management Measures	
Provide a good standard of general	
ventilation (not less than 3 - 5 air	Effectiveness: 30 %
changes per hour)	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	13,7143 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,017229
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	192,7187 mg/m³
Risk Characterization Ratio (RCR)	0,700795
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario		
Use descriptors covered	PROC15: Use a laboratory reagent. Use domain: industrial	
Operational conditions		
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 100 %	
Physical state	liquid	
Vapour pressure of the substance during use	502 Pa	
Duration and Frequency of activity	480 min 5 days per week	
Indoor/Outdoor	Indoor	
	Assumes activities are at ambient temperature.	
Exposure estimate and reference to		
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker	
	Worker - dermal, long-term - systemic	
Exposure estimate	0,3429 mg/kg bw/day	
Risk Characterization Ratio (RCR)	0,000431	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker	
	Worker - inhalation, long-term - systemic	
Exposure estimate	55,0625 mg/m³	
Risk Characterization Ratio (RCR)	0,200227	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker	
Guidance to Downstream Users		

Page: 115/115

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 13.12.2023

Version: 1.0

Date / Previous version: not applicable Product: **METHOXYPROPYLACETATE**

Previous version: none

(ID no. 30034751/SDS_GEN_IT/EN)

Date of print 21.10.2025

For scaling see: http://www.ecetoc.org/tra

Contributing exposure scenario	
Use descriptors covered	PROC28: Manual maintenance (cleaning and repair) of machinery covered by PROC8a

* * * * * * * * * * * * * * * *