

# Safety data sheet

Page: 1/78

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 18.10.2023

Version: 1.0

Date previous version: not applicable

Previous version: none

Date / First version: 18.10.2023

Product: **n-HEXYL GLYCOL**

(ID no. 30034797/SDS\_GEN\_AT/EN)

Date of print 19.10.2025

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

## n-HEXYL GLYCOL

Chemical name: 2-hexyloxyethanol

INDEX-Number: 603-178-00-3

CAS Number: 112-25-4

REACH registration number: 01-2119486575-24-0001, 01-2119486575-24-0004

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses: Chemical

For the detailed identified uses of the product see appendix of the safety data sheet.

### 1.3. Details of the supplier of the safety data sheet

Company:

BASF SE

67056 Ludwigshafen

GERMANY

Contact address:

BASF Oesterreich GmbH

Handelskai 94-96

1200 Wien

AUSTRIA

Telephone: +43 (0)664 8396135

E-mail address: product-safety-oesterreich@basf.com

### 1.4. Emergency telephone number

VergiftungsInformationsZentrale Österreich:

+43 1 406 43 43

International emergency number:

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 18.10.2023

Version: 1.0

Date previous version: not applicable

Previous version: none

Date / First version: 18.10.2023

Product: **n-HEXYL GLYCOL**

(ID no. 30034797/SDS\_GEN\_AT/EN)

Date of print 19.10.2025

Telephone: +49 180 2273-112

## SECTION 2: Hazards Identification

### 2.1. Classification of the substance or mixture

According to Regulation (EC) No 1272/2008 [CLP]

Acute Tox. 4 (oral)	H302 Harmful if swallowed.
Acute Tox. 3 (dermal)	H311 Toxic in contact with skin.
Skin Corr./Irrit. 1B	H314 Causes severe skin burns and eye damage.
Eye Dam./Irrit. 1	H318 Causes serious eye damage.

For the classifications not written out in full in this section the full text can be found in section 16.

### 2.2. Label elements

According to Regulation (EC) No 1272/2008 [CLP]

Pictogram:



Signal Word:

Danger

Hazard Statement:

H311	Toxic in contact with skin.
H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.

Precautionary Statements (Prevention):

P280	Wear protective gloves, protective clothing and eye protection or face protection.
------	--

Precautionary Statements (Response):

P310	Immediately call a POISON CENTER or physician.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.

Precautionary Statements (Storage):

P405	Store locked up.
------	------------------

Precautionary Statements (Disposal):

P501	Dispose of contents and container to hazardous or special waste collection point.
------	---

Hazard determining component(s) for labelling: 2-hexyloxyethanol, 2-(2-hexyloxyethoxy)ethanol

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 18.10.2023

Version: 1.0

Date previous version: not applicable

Previous version: none

Date / First version: 18.10.2023

Product: **n-HEXYL GLYCOL**

(ID no. 30034797/SDS\_GEN\_AT/EN)

Date of print 19.10.2025

## 2.3. Other hazards

According to Regulation (EC) No 1272/2008 [CLP]

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

See section 12 - Results of PBT and vPvB assessment.

Product does not contain a substance above legal limits included in the list established in accordance with Article 59(1) of Regulation (EC) No 1907/2006 for having endocrine disrupting properties or is identified to have endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605. Product does not contain a substance above legal limits included in the list established in accordance with Article 59(1) of Regulation (EC) No 1907/2006 for having endocrine disrupting properties or is identified to have endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605. The product does not fulfill the criteria for PBT (Persistent/bioaccumulative/toxic) and vPvB (very persistent/very bioaccumulative).

## SECTION 3: Composition/Information on Ingredients

### 3.1. Substances

#### Chemical nature

#### 2-hexyloxyethanol

Content (W/W): > 98,5 %

CAS Number: 112-25-4

EC-Number: 203-951-1

INDEX-Number: 603-178-00-3

Acute Tox. 4 (oral)

Acute Tox. 3 (dermal)

Skin Corr./Irrit. 1B

Eye Dam./Irrit. 1

H311, H302, H314

#### Regulatory relevant ingredients

#### 2-hexyloxyethanol

Content (W/W): > 98,5 % - < 99,1 %

CAS Number: 112-25-4

EC-Number: 203-951-1

INDEX-Number: 603-178-00-3

Acute Tox. 4 (oral)

Acute Tox. 3 (dermal)

Skin Corr./Irrit. 1B

Eye Dam./Irrit. 1

H311, H302, H314

#### 2-(2-hexyloxyethoxy)ethanol

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 18.10.2023

Version: 1.0

Date previous version: not applicable

Previous version: none

Date / First version: 18.10.2023

Product: **n-HEXYL GLYCOL**

(ID no. 30034797/SDS\_GEN\_AT/EN)

Date of print 19.10.2025

Content (W/W):  $\geq 0,03\%$  -  $\leq 0,28\%$

CAS Number: 112-59-4

EC-Number: 203-988-3

INDEX-Number: 603-175-00-7

Acute Tox. 4 (dermal)

Eye Dam./Irrit. 1

STOT SE 3 (drowsiness and dizziness)

H318, H312, H336

For the classifications not written out in full in this section, including the hazard classes and the hazard statements, the full text is listed in section 16.

### 3.2. Mixtures

Not applicable

---

## SECTION 4: First-Aid Measures

### 4.1. Description of first aid measures

If not breathing, give artificial respiration.

First aid personnel should pay attention to their own safety. If the patient is likely to become unconscious, place and transport in stable sideways position (recovery position). Immediately remove contaminated clothing.

If inhaled:

Keep patient calm, remove to fresh air, seek medical attention. Immediately administer a corticosteroid from a controlled/metered dose inhaler.

On skin contact:

Immediately wash thoroughly with plenty of water, apply sterile dressings, consult a skin specialist.

On contact with eyes:

Immediately wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.

On ingestion:

Do not induce vomiting. Immediately rinse mouth and then drink 200-300 ml of water, seek medical attention.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms: Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11.

Hazards: Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11. (Further) symptoms and / or effects are not known so far

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 18.10.2023

Version: 1.0

Date previous version: not applicable

Previous version: none

Date / First version: 18.10.2023

Product: **n-HEXYL GLYCOL**

(ID no. 30034797/SDS\_GEN\_AT/EN)

Date of print 19.10.2025

### 4.3. Indication of any immediate medical attention and special treatment needed

Treatment: Treat according to symptoms (decontamination, vital functions), no known specific antidote.

---

## SECTION 5: Fire-Fighting Measures

### 5.1. Extinguishing media

Suitable extinguishing media:  
dry powder, water spray, carbon dioxide, foam

Unsuitable extinguishing media for safety reasons:  
water jet

Additional information:  
Use extinguishing measures to suit surroundings.

### 5.2. Special hazards arising from the substance or mixture

Advice: Flammable liquid Cool endangered containers with water-spray. See SDS section 7 - Handling and storage.

### 5.3. Advice for fire-fighters

Special protective equipment:  
Wear a self-contained breathing apparatus. Special protective equipment for firefighters

Further information:  
Evacuate area of all unnecessary personnel. Fight fire from maximum distance.

Extend fire extinguishing measures to the surroundings. Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

---

## SECTION 6: Accidental Release Measures

High risk of slipping due to leakage/spillage of product.

Release of substance/product can cause fire or explosion. Shut off or stop source of leak. Shut off or stop released substance/product under safe conditions.

Pack in tightly closed containers for disposal.

### 6.1. Personal precautions, protective equipment and emergency procedures

Handle in accordance with good industrial hygiene and safety practice.

Avoid all sources of ignition: heat, sparks, open flame. Use antistatic tools.

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 18.10.2023

Version: 1.0

Date previous version: not applicable

Previous version: none

Date / First version: 18.10.2023

Product: **n-HEXYL GLYCOL**

(ID no. 30034797/SDS\_GEN\_AT/EN)

Date of print 19.10.2025

## 6.2. Environmental precautions

Discharge into the environment must be avoided.

## 6.3. Methods and material for containment and cleaning up

Pick up with suitable appliance and dispose of. Spills should be contained, solidified, and placed in suitable containers for disposal. Dispose of absorbed material in accordance with regulations.

## 6.4. Reference to other sections

Information regarding exposure controls/personal protection and disposal considerations can be found in section 8 and 13.

---

# SECTION 7: Handling and Storage

## 7.1. Precautions for safe handling

Handle in accordance with good industrial hygiene and safety practice.

Protection against fire and explosion:

Avoid all sources of ignition: heat, sparks, open flame. Ground all transfer equipment properly to prevent electrostatic discharge.

## 7.2. Conditions for safe storage, including any incompatibilities

Further information on storage conditions: Containers should be stored tightly sealed in a dry place.

## 7.3. Specific end use(s)

See exposure scenario(s) in the attachment to this safety data sheet.

---

# SECTION 8: Exposure Controls/Personal Protection

## 8.1. Control parameters

Components with occupational exposure limits

No substance specific occupational exposure limits known.

### PNEC

freshwater: 0,14 mg/l

marine water: 0,014 mg/l

intermittent release: 1,4 mg/l

sediment (freshwater): 0,644 mg/kg

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 18.10.2023

Version: 1.0

Date previous version: not applicable

Previous version: none

Date / First version: 18.10.2023

Product: **n-HEXYL GLYCOL**

(ID no. 30034797/SDS\_GEN\_AT/EN)

Date of print 19.10.2025

sediment (marine water): 0,0644 mg/kg

soil: 0,0467 mg/kg

STP: 75 mg/l

#### DNEL

worker:

Long-term exposure- systemic effects, dermal: 9,3 mg/kg

worker:

Long-term exposure- systemic effects, Inhalation: 18,4 mg/m<sup>3</sup>, 3,1 ppm

consumer:

Long-term exposure- systemic effects, dermal: 4,63 mg/kg

consumer:

Long-term exposure- systemic effects, Inhalation: 2,9 mg/m<sup>3</sup>, 0,5 ppm

worker:

Short-term exposure - systemic effects, dermal: 18,5 mg/kg

consumer:

Short-term exposure - systemic effects, dermal: 9,25 mg/kg

## **8.2. Exposure controls**

### Personal protective equipment

Respiratory protection:

Wear respiratory protection if ventilation is inadequate. Gas filter for gases/vapours of organic compounds (boiling point >65 °C, e. g. EN 14387 Type A)

Hand protection:

Chemical resistant protective gloves (EN ISO 374-1)

Suitable materials also with prolonged, direct contact (Recommended: Protective index 6, corresponding > 480 minutes of permeation time according to EN ISO 374-1):

butyl rubber (butyl) - 0.7 mm coating thickness

Manufacturer's directions for use should be observed because of great diversity of types.

Supplementary note: The specifications are based on tests, literature data and information of glove manufacturers or are derived from similar substances by analogy. Due to many conditions (e.g. temperature) it must be considered, that the practical usage of a chemical-protective glove in practice may be much shorter than the permeation time determined through testing.

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 18.10.2023

Version: 1.0

Date previous version: not applicable

Previous version: none

Date / First version: 18.10.2023

Product: **n-HEXYL GLYCOL**

(ID no. 30034797/SDS\_GEN\_AT/EN)

Date of print 19.10.2025

Eye protection:

Tightly fitting safety goggles (splash goggles) (e.g. EN 166)

Body protection:

Body protection must be chosen depending on activity and possible exposure, e.g. apron, protecting boots, chemical-protection suit (according to EN 14605 in case of splashes or EN ISO 13982 in case of dust).

#### General safety and hygiene measures

Avoid contact with the skin, eyes and clothing. Wearing of closed work clothing is required additionally to the stated personal protection equipment.

#### Environmental exposure controls

All appropriate measures must be taken to prevent the release of this product to the environment and to limit the dispersion of any release when it occurs. Suitable risk management measures should be in place.

## **SECTION 9: Physical and Chemical Properties**

### **9.1. Information on basic physical and chemical properties**

State of matter:	liquid	
Form:	liquid	
Colour:	colourless, clear	
Odour:	ether-like	
Odour threshold:		
	not determined	
Melting point:	-42 °C (1.013 hPa)	
Boiling range:	200 - 212 °C (1.013,3 hPa)	
Flammability:	Combustible liquid.	(derived from flash point)
Lower explosion limit:	0,9 %(V) (82,85 °C) The lower explosion point of the substance/mixture has been determined. The explosion point describes the temperature of a flammable liquid at which the concentration of the saturated vapour mixed with air equals the lower explosion limit., Literature data.	
Upper explosion limit:		
	For liquids not relevant for classification and labelling.	
Flash point:	91,5 °C	(ISO 2719, closed cup)



BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 18.10.2023

Version: 1.0

Date previous version: not applicable

Previous version: none

Date / First version: 18.10.2023

Product: **n-HEXYL GLYCOL**

(ID no. 30034797/SDS\_GEN\_AT/EN)

Date of print 19.10.2025

Auto-ignition temperature:	225 °C	(DIN 51794)
Thermal decomposition:	No decomposition if stored and handled as prescribed/indicated.	
pH value:	neutral	
Viscosity, dynamic:	4,4 mPa.s	
	(20 °C)	
Thixotropy:	not thixotropic	
Solubility in water:	9,460 g/l	
	(20 °C)	
Solubility (qualitative) solvent(s):	organic solvents	
	soluble	
Partitioning coefficient n-octanol/water (log Kow):	1,97	
	(25 °C)	
Vapour pressure:	0,1 hPa	(OECD Guideline 104)
	(22,9 °C)	
	dynamic	
Relative density:	0,8875	
	(20 °C)	
Density:	0,8875 g/cm <sup>3</sup>	
	(20 °C)	
	Literature data.	
Relative vapour density (air):	5,04	(calculated)
	(20 °C)	
	Heavier than air.	

#### Particle characteristics

Particle size distribution: The substance / product is marketed or used in a non solid or granular form. -

## **9.2. Other information**

### **Information with regard to physical hazard classes**

#### Explosives

Explosion hazard: Based on the chemical structure there is no indication of explosive properties.

Impact sensitivity: Based on the chemical structure there is no shock-sensitivity.

#### Oxidizing properties

Fire promoting properties: Based on its structural properties the product is not classified as oxidizing.

#### Pyrophoric properties

Self-ignition temperature: Test type: Spontaneous self-ignition at room-temperature.

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 18.10.2023

Version: 1.0

Date previous version: not applicable

Previous version: none

Date / First version: 18.10.2023

Product: **n-HEXYL GLYCOL**

(ID no. 30034797/SDS\_GEN\_AT/EN)

Date of print 19.10.2025

Based on its structural properties the product is not classified as self-igniting.

#### Self-heating substances and mixtures

Self heating ability: not applicable, the product is a liquid

#### Substances and mixtures, which emit flammable gases in contact with water

Formation of flammable gases:

Forms no flammable gases in the presence of water.

#### Corrosion to metals

No corrosive effect on metal.

#### **Other safety characteristics**

Miscibility with water:

partly miscible

pKA:

The substance does not dissociate.

Adsorption/water - soil:

KOC: 10; log KOC: 1 (calculated)

Surface tension:

Based on chemical structure, surface activity is not to be expected.

Molar mass:

146,23 g/mol

SAPT-Temperature:

Study scientifically not justified.

Evaporation rate:

Value can be approximated from Henry's Law Constant or vapor pressure.

## **SECTION 10: Stability and Reactivity**

### **10.1. Reactivity**

When heated can give off ignitable vapours.

Corrosion to metals: No corrosive effect on metal.

Formation of

Remarks:

flammable gases:

Forms no flammable gases in the presence of water.

### **10.2. Chemical stability**

The product is stable if stored and handled as prescribed/indicated.

### **10.3. Possibility of hazardous reactions**

Reacts with light metals, with evolution of hydrogen. Reacts with strong oxidizing agents.

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 18.10.2023

Version: 1.0

Date previous version: not applicable

Previous version: none

Date / First version: 18.10.2023

Product: **n-HEXYL GLYCOL**

(ID no. 30034797/SDS\_GEN\_AT/EN)

Date of print 19.10.2025

#### 10.4. Conditions to avoid

No special precautions other than good housekeeping of chemicals.

#### 10.5. Incompatible materials

Substances to avoid:  
strong oxidizing agents

#### 10.6. Hazardous decomposition products

Hazardous decomposition products:  
No hazardous decomposition products if stored and handled as prescribed/indicated.

---

### SECTION 11: Toxicological Information

#### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

##### Acute toxicity

Assessment of acute toxicity:

Of moderate toxicity after single ingestion. Of pronounced toxicity after short-term skin contact.  
Virtually nontoxic by inhalation.

Experimental/calculated data:

LD50 rat (oral): 738 mg/kg (other)

LC0 rat (by inhalation): > 131,58 ppm 6 h (other)

No mortality within the stated exposition time as shown in animal studies. The vapour was tested.

LD50 rabbit (dermal): 757,35 mg/kg (other)

##### Irritation

Assessment of irritating effects:

Corrosive! Damages skin and eyes.

Experimental/calculated data:

Skin corrosion/irritation

rabbit: Corrosive. (other)

The European Union (EU) has classified this substance with 'Causes burns.'

Serious eye damage/irritation

rabbit: irreversible damage (OECD Guideline 405)

##### Respiratory/Skin sensitization

Assessment of sensitization:

As the substance is corrosive, conducting sensitization studies is not feasible.

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 18.10.2023

Version: 1.0

Date previous version: not applicable

Previous version: none

Date / First version: 18.10.2023

Product: **n-HEXYL GLYCOL**

(ID no. 30034797/SDS\_GEN\_AT/EN)

Date of print 19.10.2025

#### Germ cell mutagenicity

Assessment of mutagenicity:

The substance was not mutagenic in bacteria. The substance was not mutagenic in mammalian cell culture.

#### Carcinogenicity

Assessment of carcinogenicity:

The whole of the information assessable provides no indication of a carcinogenic effect.

#### Reproductive toxicity

Assessment of reproduction toxicity:

The results of animal studies gave no indication of a fertility impairing effect. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

#### Developmental toxicity

Assessment of teratogenicity:

No indications of a developmental toxic / teratogenic effect were seen in animal studies.

#### Specific target organ toxicity (single exposure)

Assessment of STOT single:

not applicable

#### Repeated dose toxicity and Specific target organ toxicity (repeated exposure)

Assessment of repeated dose toxicity:

After repeated exposure the prominent effect is local irritation. The substance may cause damage to the liver after repeated inhalation of high doses.

#### Aspiration hazard

not applicable

#### Interactive effects

No data available.

## **11.2. Information on other hazards**

#### Endocrine disrupting properties

The substance is not identified to have endocrine disrupting properties according to Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 nor is included in the Candidate List of substances of very high concern according to EU REACH Article 59 for having endocrine disrupting properties.

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 18.10.2023

Version: 1.0

Date previous version: not applicable

Previous version: none

Date / First version: 18.10.2023

Product: **n-HEXYL GLYCOL**

(ID no. 30034797/SDS\_GEN\_AT/EN)

Date of print 19.10.2025

---

## SECTION 12: Ecological Information

### 12.1. Toxicity

Assessment of aquatic toxicity:

There is a high probability that the product is not acutely harmful to aquatic organisms. The inhibition of the degradation activity of activated sludge is not anticipated when introduced to biological treatment plants in appropriate low concentrations.

Toxicity to fish:

LC50 (96 h) 140 mg/l, *Pimephales promelas* (OECD Guideline 203, static)

Nominal concentration.

Aquatic invertebrates:

EC50 (48 h) 145 mg/l, *Daphnia magna* (DIN 38412 Part 11, static)

Nominal concentration.

Aquatic plants:

EC50 (72 h) 198 mg/l (growth rate), *Scenedesmus subspicatus* (DIN 38412 Part 9, static)

Nominal concentration.

Microorganisms/Effect on activated sludge:

EC20 (30 min) 750 mg/l, activated sludge, domestic, non-adapted (DIN EN ISO 8192-OECD 209-88/302/EEC, P. C, aquatic)

Nominal concentration.

Chronic toxicity to fish:

Study scientifically not justified.

Chronic toxicity to aquatic invertebrates:

Study scientifically not justified.

Assessment of terrestrial toxicity:

No data available concerning terrestrial toxicity.

### 12.2. Persistence and degradability

Assessment biodegradation and elimination (H<sub>2</sub>O):

Readily biodegradable (according to OECD criteria).

Elimination information:

97 % CO<sub>2</sub> formation relative to the theoretical value (20 d) (OECD 301B; ISO 9439; 92/69/EWG, C.4-C) (aerobic)

Assessment of stability in water:

Substance is readily biodegradable, therefore hydrolysis is not expected to be relevant.

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 18.10.2023

Version: 1.0

Date previous version: not applicable

Previous version: none

Date / First version: 18.10.2023

Product: **n-HEXYL GLYCOL**

(ID no. 30034797/SDS\_GEN\_AT/EN)

Date of print 19.10.2025

### 12.3. Bioaccumulative potential

Assessment bioaccumulation potential:

No significant accumulation in organisms is expected as a result of the distribution coefficient of n-octanol/water (log Pow).

Bioaccumulation potential:

No data available.

### 12.4. Mobility in soil

Assessment transport between environmental compartments:

Volatility: The substance will not evaporate into the atmosphere from the water surface.

Adsorption in soil: Adsorption to solid soil phase is not expected.

### 12.5. Results of PBT and vPvB assessment

According to Annex XIII of Regulation (EC) No.1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH): The product does not fulfill the criteria for PBT (Persistent/bioaccumulative/toxic) and vPvB (very persistent/very bioaccumulative). Self classification

### 12.6. Endocrine disrupting properties

The substance is not identified to have endocrine disrupting properties according to Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 nor is included in the Candidate List of substances of very high concern according to EU REACH Article 59 for having endocrine disrupting properties.

### 12.7. Other adverse effects

The substance is not listed in Regulation (EC) 1005/2009 on substances that deplete the ozone layer.

### 12.8. Additional information

Adsorbable organically-bound halogen (AOX):

This product contains no organically-bound halogen.

Other ecotoxicological advice:

Do not release untreated into natural waters.

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 18.10.2023

Version: 1.0

Date previous version: not applicable

Previous version: none

Date / First version: 18.10.2023

Product: **n-HEXYL GLYCOL**

(ID no. 30034797/SDS\_GEN\_AT/EN)

Date of print 19.10.2025

## SECTION 13: Disposal Considerations

### 13.1. Waste treatment methods

Must be disposed of or incinerated in accordance with local regulations.

Waste code (regional specific) (Austria):

55356 glycol ether

Contaminated packaging:

Contaminated packaging should be emptied as far as possible; then it can be passed on for recycling after being thoroughly cleaned.

## SECTION 14: Transport Information

### Land transport

ADR

UN number or ID number: UN2922

UN proper shipping name: CORROSIVE LIQUID, TOXIC, N.O.S. (ETHYLENEGLYCOL MONOHEXYLETHYER)

Transport hazard class(es): 8, 6.1

Packing group: II

Environmental hazards: no

Special precautions for user: Tunnel code: E

RID

UN number or ID number: UN2922

UN proper shipping name: CORROSIVE LIQUID, TOXIC, N.O.S. (ETHYLENEGLYCOL MONOHEXYLETHYER)

Transport hazard class(es): 8, 6.1

Packing group: II

Environmental hazards: no

Special precautions for user: None known

### Inland waterway transport

ADN

UN number or ID number: UN2922

UN proper shipping name: CORROSIVE LIQUID, TOXIC, N.O.S. (ETHYLENEGLYCOL MONOHEXYLETHYER)

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 18.10.2023

Version: 1.0

Date previous version: not applicable

Previous version: none

Date / First version: 18.10.2023

Product: **n-HEXYL GLYCOL**

(ID no. 30034797/SDS\_GEN\_AT/EN)

Date of print 19.10.2025

Transport hazard class(es): 8, 6.1  
Packing group: II  
Environmental hazards: no  
Special precautions for user: None known

Transport in inland waterway vessel  
Not evaluated

### **Sea transport**

IMDG

UN number or ID number: UN 2922  
UN proper shipping name: CORROSIVE LIQUID, TOXIC, N.O.S. (ETHYLENEGLYCOL MONOHEXYLETHYER)

Transport hazard class(es): 8, 6.1  
Packing group: II  
Environmental hazards: no  
Marine pollutant: NO  
Special precautions for user: EmS: F-A; S-B

### **Air transport**

IATA/ICAO

UN number or ID number: UN 2922  
UN proper shipping name: CORROSIVE LIQUID, TOXIC, N.O.S. (ETHYLENEGLYCOL MONOHEXYLETHYER)

Transport hazard class(es): 8, 6.1  
Packing group: II  
Environmental hazards: No Mark as dangerous for the environment is needed  
Special precautions for user: None known

#### **14.1. UN number or ID number**

See corresponding entries for "UN number or ID number" for the respective regulations in the tables above.

#### **14.2. UN proper shipping name**



BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 18.10.2023

Version: 1.0

Date previous version: not applicable

Previous version: none

Date / First version: 18.10.2023

Product: **n-HEXYL GLYCOL**

(ID no. 30034797/SDS\_GEN\_AT/EN)

Date of print 19.10.2025

See corresponding entries for "UN proper shipping name" for the respective regulations in the tables above.

#### **14.3. Transport hazard class(es)**

See corresponding entries for "Transport hazard class(es)" for the respective regulations in the tables above.

#### **14.4. Packing group**

See corresponding entries for "Packing group" for the respective regulations in the tables above.

#### **14.5. Environmental hazards**

See corresponding entries for "Environmental hazards" for the respective regulations in the tables above.

#### **14.6. Special precautions for user**

See corresponding entries for "Special precautions for user" for the respective regulations in the tables above.

#### **14.7. Maritime transport in bulk according to IMO instruments**

Maritime transport in bulk is not intended.

---

### **SECTION 15: Regulatory Information**

#### **15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

##### Prohibitions, Restrictions and Authorizations

Annex XVII of Regulation (EC) No 1907/2006: Number on List: 3, 75

Directive 2012/18/EU - Control of Major Accident Hazards involving dangerous substances (EU):  
Listed in above regulation: no

Water hazard class (§6 AwSV para.4 (Legal binding announcement of the substance in the Federal Gazette)): (1) Weakly water polluting. ID-No.: 8497

The regulations of the 'Arbeitnehmer/Innenschutzgesetz' (Austria) and associated ordinances have to be observed.

#### **15.2. Chemical Safety Assessment**

Chemical Safety Assessment performed

---

### **SECTION 16: Other Information**

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 18.10.2023

Version: 1.0

Date previous version: not applicable

Previous version: none

Date / First version: 18.10.2023

Product: **n-HEXYL GLYCOL**

(ID no. 30034797/SDS\_GEN\_AT/EN)

Date of print 19.10.2025

#### Assessment of the hazard classes according to UN GHS criteria (most recent version)

Acute Tox. 4 (oral)  
Skin Corr./Irrit. 1B  
Flam. Liq. 4  
Eye Dam./Irrit. 1  
Acute Tox. 3 (dermal)

#### Full text of the classifications, including the hazard classes and the hazard statements, if mentioned in section 2 or 3:

Acute Tox.	Acute toxicity
Skin Corr./Irrit.	Skin corrosion/irritation
Eye Dam./Irrit.	Serious eye damage/eye irritation
STOT SE	Specific target organ toxicity — single exposure
H311	Toxic in contact with skin.
H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H312	Harmful in contact with skin.
H336	May cause drowsiness or dizziness.

#### Abbreviations

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road.  
ADN = The European Agreement concerning the International Carriage of Dangerous Goods by Inland waterways. ATE = Acute Toxicity Estimates. CAO = Cargo Aircraft Only. CAS = Chemical Abstract Service. CLP = Classification, Labelling and Packaging of substances and mixtures. DIN = German national organization for standardization. DNEL = Derived No Effect Level. EC50 = Effective concentration median for 50% of the population. EC = European Community. EN = European Standards. IARC = International Agency for Research on Cancer. IATA = International Air Transport Association. IBC-Code = Intermediate Bulk Container code. IMDG = International Maritime Dangerous Goods Code. ISO = International Organization for Standardization. STEL = Short-Term Exposure Limit. LC50 = Lethal concentration median for 50% of the population. LD50 = Lethal dose median for 50% of the population. TLV = Threshold Limit Value. MARPOL = The International Convention for the Prevention of Pollution from Ships. NEN = Dutch Norm. NOEC = No Observed Effect Concentration. OEL = Occupational Exposure Limit. OECD = Organization for Economic Cooperation and Development. PBT = Persistent, Bioaccumulative and Toxic. PNEC = Predicted No Effect Level. PPM = Parts per million. RID = The European Agreement concerning the International Carriage of Dangerous Goods by Rail. TWA = Time Weight Average. UN-number = UN number at transport. vPvB = very Persistent and very Bioaccumulative.

The data contained in this safety data sheet are based on our current knowledge and experience and describe the product only with regard to safety requirements. This safety data sheet is neither a Certificate of Analysis (CoA) nor technical data sheet and shall not be mistaken for a specification agreement. Identified uses in this safety data sheet do neither represent an agreement on the corresponding contractual quality of the substance/mixture nor a contractually designated use. It is the responsibility of the recipient of the product to ensure any proprietary rights and existing laws and legislation are observed.

Vertical lines in the left hand margin indicate an amendment from the previous version.

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 18.10.2023

Version: 1.0

Date previous version: not applicable

Previous version: none

Date / First version: 18.10.2023

Product: **n-HEXYL GLYCOL**

(ID no. 30034797/SDS\_GEN\_AT/EN)

Date of print 19.10.2025

## Annex: Exposure Scenarios

### Index

#### 1. Formulation

ERC2; PROC1, PROC2, PROC3, PROC4, PROC5, PROC8a, PROC8b, PROC9, PROC14, PROC15

#### 2. Use in Coatings, (waterborne), (use in industrial settings)

ERC4; PROC1, PROC2, PROC3, PROC4, PROC5, PROC7, PROC8a, PROC8b, PROC9, PROC10, PROC13, PROC15

#### 3. Use in laboratories, (use in industrial settings)

ERC4; PROC10, PROC15

#### 4. Distribution of substance

ERC7; PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC9, PROC15

#### 5. Use in laboratories, (use in professional settings)

ERC8a; PROC10, PROC15

#### 6. Use in Cleaning Agents, (consumer use)

ERC8a, ERC8d; PC20, PC35

#### 7. Use in Coatings, (waterborne), (use in professional settings)

ERC8a, ERC8d; PROC1, PROC2, PROC3, PROC4, PROC5, PROC8a, PROC8b, PROC10, PROC11, PROC13, PROC15

#### 8. Use in Cleaning Agents, (use in professional settings)

ERC8a, ERC8d; PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC10, PROC11, PROC13

#### 9. Use in Coatings, (consumer use)

ERC8a, ERC8c, ERC8d, ERC8f; PC1, PC9a, PC9b, PC24, PC31

\*\*\*\*\*

### 1. Short title of exposure scenario

Formulation

ERC2; PROC1, PROC2, PROC3, PROC4, PROC5, PROC8a, PROC8b, PROC9, PROC14, PROC15

### Control of exposure and risk management measures

Contributing exposure scenario	
Use descriptors covered	ESVOC SpERC 2.2.o.v2
Operational conditions	
Annual amount used in the EU	100.000 kg

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 18.10.2023

Version: 1.0

Date previous version: not applicable

Previous version: none

Date / First version: 18.10.2023

Product: **n-HEXYL GLYCOL**

(ID no. 30034797/SDS\_GEN\_AT/EN)

Date of print 19.10.2025

Minimum emission days per year	10
Emission factor air	0,5 %
Emission factor water	0,5 %
Emission factor soil	0,01 %
Receive Surf. Water (Flow Rate).	18.000 m3/d
Dilution factor river	10
Dilution factor coast	100
<b>Risk Management Measures</b>	
Type of STP	Municipal STP
Assumed sewage treatment plant flow (m3/d)	2.000 m3/d
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Environment
Risk Characterization Ratio (RCR)	0,142743
	Risk from environmental exposure is driven by marine water.
Maximum amount of safe use	7.005,6 kg/d
Risk from environmental exposure is driven by marine water.	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC1: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions. Use domain: industrial
<b>Operational conditions</b>	
Concentration of the substance	2-hexyloxyethanol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	10 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Assumes activities are at ambient temperature.	
<b>Risk Management Measures</b>	
Personal measures have to be applied in case of potential exposure only.	

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 18.10.2023

Version: 1.0

Date previous version: not applicable

Previous version: none

Date / First version: 18.10.2023

Product: **n-HEXYL GLYCOL**

(ID no. 30034797/SDS\_GEN\_AT/EN)

Date of print 19.10.2025

Use suitable eye protection.	
Wear chemically resistant gloves in combination with 'basic' employee training.	
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	0,0609 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,003311
Assessment method	Qualitative assessment
	Worker - dermal
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC2: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions Use domain: industrial
<b>Operational conditions</b>	
Concentration of the substance	2-hexyloxyethanol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	10 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
<b>Risk Management Measures</b>	
Personal measures have to be applied in case of potential exposure only.	
Use suitable eye protection.	
Wear chemically resistant gloves in combination with 'basic' employee training.	
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	6,0917 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,331069
Assessment method	Qualitative assessment
	Worker - dermal
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 18.10.2023

Version: 1.0

Date previous version: not applicable

Previous version: none

Date / First version: 18.10.2023

Product: **n-HEXYL GLYCOL**

(ID no. 30034797/SDS\_GEN\_AT/EN)

Date of print 19.10.2025

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition Use domain: industrial
<b>Operational conditions</b>	
Concentration of the substance	2-hexyloxyethanol Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	10 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
<b>Risk Management Measures</b>	
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %
Personal measures have to be applied in case of potential exposure only.	
Use suitable eye protection.	
Wear chemically resistant gloves in combination with 'basic' employee training.	
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	12,7925 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,695245
Assessment method	Qualitative assessment
	Worker - dermal
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC4: Chemical production where opportunity for exposure arises Use domain: industrial
<b>Operational conditions</b>	
Concentration of the substance	2-hexyloxyethanol Content: $\geq 0\%$ - $\leq 100\%$

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 18.10.2023

Version: 1.0

Date previous version: not applicable

Previous version: none

Date / First version: 18.10.2023

Product: **n-HEXYL GLYCOL**

(ID no. 30034797/SDS\_GEN\_AT/EN)

Date of print 19.10.2025

Physical state	liquid
Vapour pressure of the substance during use	10 Pa
Duration and Frequency of activity	240 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
<b>Risk Management Measures</b>	
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %
Personal measures have to be applied in case of potential exposure only.	
Use suitable eye protection.	
Wear chemically resistant gloves in combination with 'basic' employee training.	
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	12,7925 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,695245
Assessment method	Qualitative assessment
	Worker - dermal
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC5: Mixing or blending in batch processes Use domain: industrial
<b>Operational conditions</b>	
Concentration of the substance	2-hexyloxyethanol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	10 Pa
Duration and Frequency of activity	240 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
<b>Risk Management Measures</b>	
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 18.10.2023

Version: 1.0

Date previous version: not applicable

Previous version: none

Date / First version: 18.10.2023

Product: **n-HEXYL GLYCOL**

(ID no. 30034797/SDS\_GEN\_AT/EN)

Date of print 19.10.2025

Personal measures have to be applied in case of potential exposure only.	
Use suitable eye protection.	
Wear chemically resistant gloves in combination with 'basic' employee training.	
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	12,7925 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,695245
Assessment method	Qualitative assessment
	Worker - dermal
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC8a: Transfer of substance or mixture (charging and discharging) at non-dedicated facilities Use domain: industrial
<b>Operational conditions</b>	
Concentration of the substance	2-hexyloxyethanol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	10 Pa
Duration and Frequency of activity	240 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
<b>Risk Management Measures</b>	
Provide a good standard of general or controlled ventilation (5 to 10 air changes per hour)	Effectiveness: 70 %
Personal measures have to be applied in case of potential exposure only.	
Use suitable eye protection.	
Wear chemically resistant gloves in combination with 'basic' employee training.	
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	10,965 mg/m <sup>3</sup>



BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 18.10.2023

Version: 1.0

Date previous version: not applicable

Previous version: none

Date / First version: 18.10.2023

Product: **n-HEXYL GLYCOL**

(ID no. 30034797/SDS\_GEN\_AT/EN)

Date of print 19.10.2025

Risk Characterization Ratio (RCR)	0,595924
Assessment method	Qualitative assessment
	Worker - dermal
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC8b: Transfer of substance or mixture (charging and discharging) at dedicated facilities Use domain: industrial
<b>Operational conditions</b>	
Concentration of the substance	2-hexyloxyethanol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	10 Pa
Duration and Frequency of activity	240 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
<b>Risk Management Measures</b>	
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %
Personal measures have to be applied in case of potential exposure only.	
Use suitable eye protection.	
Wear chemically resistant gloves in combination with 'basic' employee training.	
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	12,7925 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,695245
Assessment method	Qualitative assessment
	Worker - dermal
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing). Use domain: industrial

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 18.10.2023

Version: 1.0

Date previous version: not applicable

Previous version: none

Date / First version: 18.10.2023

Product: **n-HEXYL GLYCOL**

(ID no. 30034797/SDS\_GEN\_AT/EN)

Date of print 19.10.2025

<b>Operational conditions</b>	
Concentration of the substance	2-hexyloxyethanol Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	10 Pa
Duration and Frequency of activity	240 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
<b>Risk Management Measures</b>	
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %
Personal measures have to be applied in case of potential exposure only.	
Use suitable eye protection.	
Wear chemically resistant gloves in combination with 'basic' employee training.	
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	12,7925 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,695245
Assessment method	Qualitative assessment
	Worker - dermal
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC14: Tableting, compression, extrusion, pelletisation, granulation Use domain: industrial
<b>Operational conditions</b>	
Concentration of the substance	2-hexyloxyethanol Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	10 Pa
Duration and Frequency of activity	240 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 18.10.2023

Version: 1.0

Date previous version: not applicable

Previous version: none

Date / First version: 18.10.2023

Product: **n-HEXYL GLYCOL**

(ID no. 30034797/SDS\_GEN\_AT/EN)

Date of print 19.10.2025

<b>Risk Management Measures</b>	
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %
Personal measures have to be applied in case of potential exposure only.	
Use suitable eye protection.	
Wear chemically resistant gloves in combination with 'basic' employee training.	
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	12,7925 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,695245
Assessment method	Qualitative assessment
	Worker - dermal
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC15: Use a laboratory reagent. Use domain: industrial
<b>Operational conditions</b>	
Concentration of the substance	2-hexyloxyethanol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	10 Pa
Duration and Frequency of activity	240 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
<b>Risk Management Measures</b>	
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %
Personal measures have to be applied in case of potential exposure only.	
Use suitable eye protection.	
Wear chemically resistant gloves in combination with 'basic' employee training.	
<b>Exposure estimate and reference to its source</b>	

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 18.10.2023

Version: 1.0

Date previous version: not applicable

Previous version: none

Date / First version: 18.10.2023

Product: **n-HEXYL GLYCOL**

(ID no. 30034797/SDS\_GEN\_AT/EN)

Date of print 19.10.2025

Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	12,7925 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,695245
Assessment method	Qualitative assessment
	Worker - dermal
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

\*\*\*\*\*

## 2. Short title of exposure scenario

Use in Coatings, (waterborne), (use in industrial settings)

ERC4; PROC1, PROC2, PROC3, PROC4, PROC5, PROC7, PROC8a, PROC8b, PROC9, PROC10, PROC13, PROC15

## Control of exposure and risk management measures

<b>Contributing exposure scenario</b>	
Use descriptors covered	ESVOC SpERC 1.1.v1: ESVOC SpERC 1.1.v1
<b>Operational conditions</b>	
Annual amount used in the EU	10.000 kg
Minimum emission days per year	20
Emission factor air	2,5 %
Emission factor water	2 %
Emission factor soil	0,01 %
Receive Surf. Water (Flow Rate).	18.000 m3/d
Dilution factor river	10
Dilution factor coast	100
<b>Risk Management Measures</b>	
Type of STP	Municipal STP
Assumed sewage treatment plant flow (m3/d)	2.000 m3/d
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Environment
Risk Characterization Ratio (RCR)	0,028658
	Risk from environmental exposure is driven by marine water.
Maximum amount of safe use	1.744,7

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 18.10.2023

Version: 1.0

Date previous version: not applicable

Previous version: none

Date / First version: 18.10.2023

Product: **n-HEXYL GLYCOL**

(ID no. 30034797/SDS\_GEN\_AT/EN)

Date of print 19.10.2025

	kg/d
Risk from environmental exposure is driven by marine water.	

Contributing exposure scenario	
<b>Use descriptors covered</b>	PROC1: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions. Use domain: industrial
Operational conditions	
Concentration of the substance	2-hexyloxyethanol Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	10 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Risk Management Measures	
Personal measures have to be applied in case of potential exposure only.	
Use suitable eye protection.	
Wear chemically resistant gloves in combination with 'basic' employee training.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	0,0609 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,003311
Assessment method	Qualitative assessment
	Worker - dermal
Guidance to Downstream Users	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

Contributing exposure scenario	
<b>Use descriptors covered</b>	PROC2: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions Use domain: industrial
Operational conditions	
Concentration of the substance	2-hexyloxyethanol Content: $\geq 0\%$ - $\leq 100\%$

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 18.10.2023

Version: 1.0

Date previous version: not applicable

Previous version: none

Date / First version: 18.10.2023

Product: **n-HEXYL GLYCOL**

(ID no. 30034797/SDS\_GEN\_AT/EN)

Date of print 19.10.2025

Physical state	liquid
Vapour pressure of the substance during use	10 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
<b>Risk Management Measures</b>	
Personal measures have to be applied in case of potential exposure only.	
Use suitable eye protection.	
Wear chemically resistant gloves in combination with 'basic' employee training.	
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	6,0917 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,331069
Assessment method	Qualitative assessment
	Worker - dermal
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition Use domain: industrial
<b>Operational conditions</b>	
Concentration of the substance	2-hexyloxyethanol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	10 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
<b>Risk Management Measures</b>	
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 18.10.2023

Version: 1.0

Date previous version: not applicable

Previous version: none

Date / First version: 18.10.2023

Product: **n-HEXYL GLYCOL**

(ID no. 30034797/SDS\_GEN\_AT/EN)

Date of print 19.10.2025

Personal measures have to be applied in case of potential exposure only.	
Use suitable eye protection.	
Wear chemically resistant gloves in combination with 'basic' employee training.	
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	12,7925 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,695245
Assessment method	Qualitative assessment
	Worker - dermal
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC4: Chemical production where opportunity for exposure arises Use domain: industrial
<b>Operational conditions</b>	
Concentration of the substance	2-hexyloxyethanol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	10 Pa
Duration and Frequency of activity	240 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
<b>Risk Management Measures</b>	
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %
Personal measures have to be applied in case of potential exposure only.	
Use suitable eye protection.	
Wear chemically resistant gloves in combination with 'basic' employee training.	
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	12,7925 mg/m <sup>3</sup>

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 18.10.2023

Version: 1.0

Date previous version: not applicable

Previous version: none

Date / First version: 18.10.2023

Product: **n-HEXYL GLYCOL**

(ID no. 30034797/SDS\_GEN\_AT/EN)

Date of print 19.10.2025

Risk Characterization Ratio (RCR)	0,695245
Assessment method	Qualitative assessment
	Worker - dermal
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC5: Mixing or blending in batch processes Use domain: industrial
<b>Operational conditions</b>	
Concentration of the substance	2-hexyloxyethanol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	10 Pa
Duration and Frequency of activity	240 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
<b>Risk Management Measures</b>	
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %
Personal measures have to be applied in case of potential exposure only.	
Use suitable eye protection.	
Wear chemically resistant gloves in combination with 'basic' employee training.	
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	12,7925 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,695245
Assessment method	Qualitative assessment
	Worker - dermal
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC7: Industrial spraying Use domain: industrial
	Surface spraying of liquids



BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 18.10.2023

Version: 1.0

Date previous version: not applicable

Previous version: none

Date / First version: 18.10.2023

Product: **n-HEXYL GLYCOL**

(ID no. 30034797/SDS\_GEN\_AT/EN)

Date of print 19.10.2025

<b>Operational conditions</b>	
Concentration of the substance	2-hexyloxyethanol Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	10 Pa
Duration and Frequency of activity	240 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
	Any sized room
Application rate	$> 3$ l/min
<b>Risk Management Measures</b>	
Wear suitable respiratory protection.	Effectiveness: 90 %
Ensure that the task is not carried out overhead.	
Ensure that general housekeeping is in place	
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	
Personal measures have to be applied in case of potential exposure only.	
Use suitable eye protection.	
Wear chemically resistant gloves in combination with 'basic' employee training.	
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v4.2, Advanced REACH Tool v1.5
	Worker - inhalation, long-term - systemic
Exposure estimate	11 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,597826
Assessment method	Qualitative assessment
	Worker - dermal

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC8a: Transfer of substance or mixture (charging and discharging) at non-dedicated facilities Use domain: industrial
<b>Operational conditions</b>	
Concentration of the substance	2-hexyloxyethanol Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance	10 Pa

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 18.10.2023

Version: 1.0

Date previous version: not applicable

Previous version: none

Date / First version: 18.10.2023

Product: **n-HEXYL GLYCOL**

(ID no. 30034797/SDS\_GEN\_AT/EN)

Date of print 19.10.2025

during use	
Duration and Frequency of activity	240 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
<b>Risk Management Measures</b>	
Provide a good standard of general or controlled ventilation (5 to 10 air changes per hour)	Effectiveness: 70 %
Personal measures have to be applied in case of potential exposure only.	
Use suitable eye protection.	
Wear chemically resistant gloves in combination with 'basic' employee training.	
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	10,965 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,595924
Assessment method	Qualitative assessment
	Worker - dermal
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC8b: Transfer of substance or mixture (charging and discharging) at dedicated facilities Use domain: industrial
<b>Operational conditions</b>	
Concentration of the substance	2-hexyloxyethanol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	10 Pa
Duration and Frequency of activity	240 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
<b>Risk Management Measures</b>	
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %
Personal measures have to be applied in case of potential exposure	

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 18.10.2023

Version: 1.0

Date previous version: not applicable

Previous version: none

Date / First version: 18.10.2023

Product: **n-HEXYL GLYCOL**

(ID no. 30034797/SDS\_GEN\_AT/EN)

Date of print 19.10.2025

only.	
Use suitable eye protection.	
Wear chemically resistant gloves in combination with 'basic' employee training.	
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	12,7925 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,695245
Assessment method	Qualitative assessment
	Worker - dermal
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing). Use domain: industrial
<b>Operational conditions</b>	
Concentration of the substance	2-hexyloxyethanol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	10 Pa
Duration and Frequency of activity	240 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
<b>Risk Management Measures</b>	
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %
Personal measures have to be applied in case of potential exposure only.	
Use suitable eye protection.	
Wear chemically resistant gloves in combination with 'basic' employee training.	
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	12,7925 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,695245
Assessment method	Qualitative assessment

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 18.10.2023

Version: 1.0

Date previous version: not applicable

Previous version: none

Date / First version: 18.10.2023

Product: **n-HEXYL GLYCOL**

(ID no. 30034797/SDS\_GEN\_AT/EN)

Date of print 19.10.2025

	Worker - dermal
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC10: Roller application or brushing Use domain: industrial
<b>Operational conditions</b>	
Concentration of the substance	2-hexyloxyethanol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	10 Pa
Duration and Frequency of activity	240 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
<b>Risk Management Measures</b>	
Provide a good standard of general or controlled ventilation (5 to 10 air changes per hour)	Effectiveness: 70 %
Personal measures have to be applied in case of potential exposure only.	
Use suitable eye protection.	
Wear chemically resistant gloves in combination with 'basic' employee training.	
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	10,965 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,595924
Assessment method	Qualitative assessment
	Worker - dermal
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC13: Treatment of articles by dipping and pouring. Use domain: industrial
<b>Operational conditions</b>	
Concentration of the substance	2-hexyloxyethanol Content: >= 0 % - <= 100 %

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 18.10.2023

Version: 1.0

Date previous version: not applicable

Previous version: none

Date / First version: 18.10.2023

Product: **n-HEXYL GLYCOL**

(ID no. 30034797/SDS\_GEN\_AT/EN)

Date of print 19.10.2025

Physical state	liquid
Vapour pressure of the substance during use	10 Pa
Duration and Frequency of activity	240 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
<b>Risk Management Measures</b>	
Provide a good standard of general or controlled ventilation (5 to 10 air changes per hour)	Effectiveness: 70 %
Personal measures have to be applied in case of potential exposure only.	
Use suitable eye protection.	
Wear chemically resistant gloves in combination with 'basic' employee training.	
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	10,965 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,595924
Assessment method	Qualitative assessment
	Worker - dermal
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC15: Use a laboratory reagent. Use domain: industrial
<b>Operational conditions</b>	
Concentration of the substance	2-hexyloxyethanol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	10 Pa
Duration and Frequency of activity	240 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
<b>Risk Management Measures</b>	
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %
Personal measures have to be	

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 18.10.2023

Version: 1.0

Date previous version: not applicable

Previous version: none

Date / First version: 18.10.2023

Product: **n-HEXYL GLYCOL**

(ID no. 30034797/SDS\_GEN\_AT/EN)

Date of print 19.10.2025

applied in case of potential exposure only.	
Use suitable eye protection.	
Wear chemically resistant gloves in combination with 'basic' employee training.	
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	12,7925 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,695245
Assessment method	Qualitative assessment
	Worker - dermal
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

\*\*\*\*\*

### 3. Short title of exposure scenario

Use in laboratories, (use in industrial settings)

ERC4; PROC10, PROC15

### Control of exposure and risk management measures

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	ESVOC SpERC 1.1.v1: ESVOC SpERC 1.1.v1
<b>Operational conditions</b>	
Annual amount used in the EU	1.000 kg
Minimum emission days per year	20
Emission factor air	2,5 %
Emission factor water	2 %
Emission factor soil	0,01 %
Receive Surf. Water (Flow Rate).	18.000 m3/d
Dilution factor river	10
Dilution factor coast	100
<b>Risk Management Measures</b>	
Type of STP	Municipal STP
Assumed sewage treatment plant flow (m3/d)	2.000 m3/d

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 18.10.2023

Version: 1.0

Date previous version: not applicable

Previous version: none

Date / First version: 18.10.2023

Product: **n-HEXYL GLYCOL**

(ID no. 30034797/SDS\_GEN\_AT/EN)

Date of print 19.10.2025

<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Environment
Risk Characterization Ratio (RCR)	0,003127
	Risk from environmental exposure is driven by soil.
Maximum amount of safe use	1.598,9 kg/d
	Risk from environmental exposure is driven by soil.

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC10: Roller application or brushing Use domain: industrial
<b>Operational conditions</b>	
Concentration of the substance	2-hexyloxyethanol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	10 Pa
Duration and Frequency of activity	240 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
<b>Risk Management Measures</b>	
Provide a good standard of general or controlled ventilation (5 to 10 air changes per hour)	Effectiveness: 70 %
Personal measures have to be applied in case of potential exposure only.	
Use suitable eye protection.	
Wear chemically resistant gloves in combination with 'basic' employee training.	
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	10,965 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,595924
Assessment method	Qualitative assessment
	Worker - dermal
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC15: Use a laboratory reagent. Use domain: industrial

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 18.10.2023

Version: 1.0

Date previous version: not applicable

Previous version: none

Date / First version: 18.10.2023

Product: **n-HEXYL GLYCOL**

(ID no. 30034797/SDS\_GEN\_AT/EN)

Date of print 19.10.2025

<b>Operational conditions</b>	
Concentration of the substance	2-hexyloxyethanol Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	10 Pa
Duration and Frequency of activity	240 min 5 days per week
Indoor/Outdoor	Indoor
Assumes activities are at ambient temperature.	
<b>Risk Management Measures</b>	
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %
Personal measures have to be applied in case of potential exposure only.	
Use suitable eye protection.	
Wear chemically resistant gloves in combination with 'basic' employee training.	
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	12,7925 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,695245
Assessment method	Qualitative assessment
	Worker - dermal
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

\*\*\*\*\*

#### 4. Short title of exposure scenario

Distribution of substance

ERC7; PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC9, PROC15

#### Control of exposure and risk management measures

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	ESVOC SpERC 2.2.v1: ESVOC SpERC 2.2.v1
<b>Operational conditions</b>	
Annual amount used in the EU	100.000 kg



BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 18.10.2023

Version: 1.0

Date previous version: not applicable

Previous version: none

Date / First version: 18.10.2023

Product: **n-HEXYL GLYCOL**

(ID no. 30034797/SDS\_GEN\_AT/EN)

Date of print 19.10.2025

Minimum emission days per year	300
Emission factor air	0,001 %
Emission factor water	0,001 %
Emission factor soil	0 %
Receive Surf. Water (Flow Rate).	18.000 m3/d
Dilution factor river	10
Dilution factor coast	100
<b>Risk Management Measures</b>	
Air treatment measures considered suitable are, e.g.	Adsorption
Wastewater treatment measures considered suitable are, e.g.	Acclimated biological treatment
Type of STP	Municipal STP
Assumed sewage treatment plant flow (m3/d)	2.000 m3/d
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Environment
Risk Characterization Ratio (RCR)	0,000652
	Risk from environmental exposure is driven by soil.
Maximum amount of safe use	102,3 kg/d
Risk from environmental exposure is driven by soil.	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC1: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions. Use domain: industrial
<b>Operational conditions</b>	
Concentration of the substance	2-hexyloxyethanol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	10 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
<b>Risk Management Measures</b>	
Personal measures have to be	

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 18.10.2023

Version: 1.0

Date previous version: not applicable

Previous version: none

Date / First version: 18.10.2023

Product: **n-HEXYL GLYCOL**

(ID no. 30034797/SDS\_GEN\_AT/EN)

Date of print 19.10.2025

applied in case of potential exposure only.	
Use suitable eye protection.	
Wear chemically resistant gloves in combination with 'basic' employee training.	
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	0,0609 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,003311
Assessment method	Qualitative assessment
	Worker - dermal
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC2: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions Use domain: industrial
<b>Operational conditions</b>	
Concentration of the substance	2-hexyloxyethanol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	10 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
<b>Risk Management Measures</b>	
Personal measures have to be applied in case of potential exposure only.	
Use suitable eye protection.	
Wear chemically resistant gloves in combination with 'basic' employee training.	
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	6,0917 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,331069
Assessment method	Qualitative assessment
	Worker - dermal

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 18.10.2023

Version: 1.0

Date previous version: not applicable

Previous version: none

Date / First version: 18.10.2023

Product: **n-HEXYL GLYCOL**

(ID no. 30034797/SDS\_GEN\_AT/EN)

Date of print 19.10.2025

### **Guidance to Downstream Users**

For scaling see: <http://www.ecetoc.org/tra>

### **Contributing exposure scenario**

<b>Use descriptors covered</b>	PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition Use domain: industrial
--------------------------------	---

### **Operational conditions**

Concentration of the substance	2-hexyloxyethanol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	10 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.

### **Risk Management Measures**

Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %
Personal measures have to be applied in case of potential exposure only.	
Use suitable eye protection.	
Wear chemically resistant gloves in combination with 'basic' employee training.	

### **Exposure estimate and reference to its source**

Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	12,7925 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,695245
Assessment method	Qualitative assessment
	Worker - dermal

### **Guidance to Downstream Users**

For scaling see: <http://www.ecetoc.org/tra>

### **Contributing exposure scenario**

<b>Use descriptors covered</b>	PROC4: Chemical production where opportunity for exposure arises Use domain: industrial
--------------------------------	--

### **Operational conditions**

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 18.10.2023

Version: 1.0

Date previous version: not applicable

Previous version: none

Date / First version: 18.10.2023

Product: **n-HEXYL GLYCOL**

(ID no. 30034797/SDS\_GEN\_AT/EN)

Date of print 19.10.2025

Concentration of the substance	2-hexyloxyethanol Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	10 Pa
Duration and Frequency of activity	240 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
<b>Risk Management Measures</b>	
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %
Personal measures have to be applied in case of potential exposure only.	
Use suitable eye protection.	
Wear chemically resistant gloves in combination with 'basic' employee training.	
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	12,7925 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,695245
Assessment method	Qualitative assessment
	Worker - dermal
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC8a: Transfer of substance or mixture (charging and discharging) at non-dedicated facilities Use domain: industrial
<b>Operational conditions</b>	
Concentration of the substance	2-hexyloxyethanol Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	10 Pa
Duration and Frequency of activity	240 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
<b>Risk Management Measures</b>	

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 18.10.2023

Version: 1.0

Date previous version: not applicable

Previous version: none

Date / First version: 18.10.2023

Product: **n-HEXYL GLYCOL**

(ID no. 30034797/SDS\_GEN\_AT/EN)

Date of print 19.10.2025

Provide a good standard of general or controlled ventilation (5 to 10 air changes per hour)	Effectiveness: 70 %
Personal measures have to be applied in case of potential exposure only.	
Use suitable eye protection.	
Wear chemically resistant gloves in combination with 'basic' employee training.	
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	10,965 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,595924
Assessment method	Qualitative assessment
	Worker - dermal
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC8b: Transfer of substance or mixture (charging and discharging) at dedicated facilities Use domain: industrial
<b>Operational conditions</b>	
Concentration of the substance	2-hexyloxyethanol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	10 Pa
Duration and Frequency of activity	240 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
<b>Risk Management Measures</b>	
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %
Personal measures have to be applied in case of potential exposure only.	
Use suitable eye protection.	
Wear chemically resistant gloves in combination with 'basic' employee training.	
<b>Exposure estimate and reference to its source</b>	

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 18.10.2023

Version: 1.0

Date previous version: not applicable

Previous version: none

Date / First version: 18.10.2023

Product: **n-HEXYL GLYCOL**

(ID no. 30034797/SDS\_GEN\_AT/EN)

Date of print 19.10.2025

Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	12,7925 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,695245
Assessment method	Qualitative assessment
	Worker - dermal
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing). Use domain: industrial
<b>Operational conditions</b>	
Concentration of the substance	2-hexyloxyethanol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	10 Pa
Duration and Frequency of activity	240 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
<b>Risk Management Measures</b>	
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %
Personal measures have to be applied in case of potential exposure only.	
Use suitable eye protection.	
Wear chemically resistant gloves in combination with 'basic' employee training.	
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	12,7925 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,695245
Assessment method	Qualitative assessment
	Worker - dermal
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC15: Use a laboratory reagent.

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 18.10.2023

Version: 1.0

Date previous version: not applicable

Previous version: none

Date / First version: 18.10.2023

Product: **n-HEXYL GLYCOL**

(ID no. 30034797/SDS\_GEN\_AT/EN)

Date of print 19.10.2025

	Use domain: industrial
<b>Operational conditions</b>	
Concentration of the substance	2-hexyloxyethanol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	10 Pa
Duration and Frequency of activity	240 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
<b>Risk Management Measures</b>	
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %
Personal measures have to be applied in case of potential exposure only.	
Use suitable eye protection.	
Wear chemically resistant gloves in combination with 'basic' employee training.	
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	12,7925 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,695245
Assessment method	Qualitative assessment
	Worker - dermal
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

\*\*\*\*\*

## 5. Short title of exposure scenario

Use in laboratories, (use in professional settings)

ERC8a; PROC10, PROC15

## Control of exposure and risk management measures

<b>Contributing exposure scenario</b>	
Use descriptors covered	ESVOC SpERC 8.17.v2
<b>Operational conditions</b>	
Annual amount used in the EU	1.000 kg

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 18.10.2023

Version: 1.0

Date previous version: not applicable

Previous version: none

Date / First version: 18.10.2023

Product: **n-HEXYL GLYCOL**

(ID no. 30034797/SDS\_GEN\_AT/EN)

Date of print 19.10.2025

Minimum emission days per year	365
Emission factor air	50 %
Emission factor water	50 %
Emission factor soil	0 %
Receive Surf. Water (Flow Rate).	18.000 m3/d
Dilution factor river	10
Dilution factor coast	100
<b>Risk Management Measures</b>	
Type of STP	Municipal STP
Assumed sewage treatment plant flow (m3/d)	2.000 m3/d
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Environment
Risk Characterization Ratio (RCR)	0,000659
	Risk from environmental exposure is driven by soil.
Maximum amount of safe use	0,831804 kg/d
Risk from environmental exposure is driven by soil.	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC10: Roller application or brushing Use domain: professional
<b>Operational conditions</b>	
Concentration of the substance	2-hexyloxyethanol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	10 Pa
Duration and Frequency of activity	60 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
<b>Risk Management Measures</b>	
Provide a good standard of general or controlled ventilation (5 to 10 air changes per hour)	Effectiveness: 70 %
Personal measures have to be applied in case of potential exposure	



BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 18.10.2023

Version: 1.0

Date previous version: not applicable

Previous version: none

Date / First version: 18.10.2023

Product: **n-HEXYL GLYCOL**

(ID no. 30034797/SDS\_GEN\_AT/EN)

Date of print 19.10.2025

only.	
Use suitable eye protection.	
Wear chemically resistant gloves in combination with 'basic' employee training.	
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	9,1375 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,496603
Assessment method	Qualitative assessment
	Worker - dermal
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC15: Use a laboratory reagent. Use domain: professional
<b>Operational conditions</b>	
Concentration of the substance	2-hexyloxyethanol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	10 Pa
Duration and Frequency of activity	240 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
<b>Risk Management Measures</b>	
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %
Personal measures have to be applied in case of potential exposure only.	
Use suitable eye protection.	
Wear chemically resistant gloves in combination with 'basic' employee training.	
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	12,7925 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,695245
Assessment method	Qualitative assessment
	Worker - dermal

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 18.10.2023

Version: 1.0

Date previous version: not applicable

Previous version: none

Date / First version: 18.10.2023

Product: **n-HEXYL GLYCOL**

(ID no. 30034797/SDS\_GEN\_AT/EN)

Date of print 19.10.2025

### **Guidance to Downstream Users**

For scaling see: <http://www.ecetoc.org/tra>

\*\*\*\*\*

## **6. Short title of exposure scenario**

Use in Cleaning Agents, (consumer use)

ERC8a, ERC8d; PC20, PC35

## **Control of exposure and risk management measures**

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	ESVOC SpERC 8.4c.v2
<b>Operational conditions</b>	
Annual amount used in the EU	50.000 kg
Minimum emission days per year	365
Emission factor air	95 %
Emission factor water	2,5 %
Emission factor soil	2,5 %
Receive Surf. Water (Flow Rate).	18.000 m3/d
Dilution factor river	10
Dilution factor coast	100
<b>Risk Management Measures</b>	
Type of STP	Municipal STP
Assumed sewage treatment plant flow (m3/d)	2.000 m3/d
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Environment
Risk Characterization Ratio (RCR)	0,000669
	Risk from environmental exposure is driven by soil.
Maximum amount of safe use	41 kg/d
Risk from environmental exposure is driven by soil.	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	ESVOC SpERC 8.4c.v2
<b>Operational conditions</b>	

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 18.10.2023

Version: 1.0

Date previous version: not applicable

Previous version: none

Date / First version: 18.10.2023

Product: **n-HEXYL GLYCOL**

(ID no. 30034797/SDS\_GEN\_AT/EN)

Date of print 19.10.2025

Annual amount used in the EU	50.000 kg
Minimum emission days per year	365
Emission factor air	95 %
Emission factor water	2,5 %
Emission factor soil	2,5 %
Receive Surf. Water (Flow Rate).	18.000 m3/d
Dilution factor river	10
Dilution factor coast	100
<b>Risk Management Measures</b>	
Type of STP	Municipal STP
Assumed sewage treatment plant flow (m3/d)	2.000 m3/d
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Environment
Risk Characterization Ratio (RCR)	0,000669
	Risk from environmental exposure is driven by soil.
Maximum amount of safe use	41 kg/d
Risk from environmental exposure is driven by soil.	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PC20: Products such as ph-regulators, flocculants, precipitants, neutralisation agents.
<b>Operational conditions</b>	
Concentration of the substance	2-hexyloxyethanol Content: >= 0 % - <= 100 %
Vapour pressure of the substance during use	10 Pa
Duration and Frequency of activity	Exposure duration: 0,75 min Relevant for inhalative exposure estimates
Duration and Frequency of activity	Application duration: 60 min Relevant for inhalative exposure estimates
Duration and Frequency of activity	197 uses per year
Room size	1 m3
Ventilation rate per hour	0,5
Temperature (Application)	20 °C
body weight	68,8 kg

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 18.10.2023

Version: 1.0

Date previous version: not applicable

Previous version: none

Date / First version: 18.10.2023

Product: **n-HEXYL GLYCOL**

(ID no. 30034797/SDS\_GEN\_AT/EN)

Date of print 19.10.2025

	Amount per use 0,01 g Relevant for dermal exposure estimates
Release area	20 cm <sup>2</sup>
	Release area is constant
Release duration	60 min
	Relevant for inhalative exposure estimates
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v4.2, ConsExpo v4.1, Dermal model: instant application
	Consumer - dermal, short-term - systemic
Exposure estimate	0,1453 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,015713
	The calculation is based on the external dose.
Assessment method	EASY TRA v4.2, ConsExpo v4.1, Inhalation model: exposure to vapour - evaporation
	Consumer - inhalation, long-term - systemic
Exposure estimate	0,0001 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,000013
	The exposure calculation is based on the mean concentration on the day of exposure.
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp">http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PC35: Washing and Cleaning Products (including solvent based products).
<b>Operational conditions</b>	
Concentration of the substance	2-hexyloxyethanol Content: >= 0 % - <= 25 %
Vapour pressure of the substance during use	10 Pa
Duration and Frequency of activity	Exposure duration: 240 min Relevant for inhalative exposure estimates
Duration and Frequency of activity	Application duration: 20 min Relevant for inhalative exposure estimates
Duration and Frequency of activity	197 uses per year
Room size	58 m <sup>3</sup>
Ventilation rate per hour	0,5
Temperature (Application)	20 °C
body weight	68,8 kg
	Amount per use 0,286 g Relevant for dermal exposure estimates
Release area	320000 cm <sup>2</sup>

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 18.10.2023

Version: 1.0

Date previous version: not applicable

Previous version: none

Date / First version: 18.10.2023

Product: **n-HEXYL GLYCOL**

(ID no. 30034797/SDS\_GEN\_AT/EN)

Date of print 19.10.2025

	Release area increases over time
Release duration	20 min
	Relevant for inhalative exposure estimates
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v4.2, ConsExpo v4.1, Dermal model: instant application
	Consumer - dermal, short-term - systemic
Exposure estimate	1,0392 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,112351
	The calculation is based on the external dose.
Assessment method	EASY TRA v4.2, ConsExpo v4.1, Inhalation model: exposure to vapour - evaporation
	Consumer - inhalation, long-term - systemic
Exposure estimate	1,7981 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,620047
	The exposure calculation is based on the mean concentration per year.
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp">http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp</a>	

\*\*\*\*\*

## 7. Short title of exposure scenario

Use in Coatings, (waterborne), (use in professional settings)

ERC8a, ERC8d; PROC1, PROC2, PROC3, PROC4, PROC5, PROC8a, PROC8b, PROC10, PROC11, PROC13, PROC15

## Control of exposure and risk management measures

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	ESVOC SpERC 8.3b.v2
<b>Operational conditions</b>	
Annual amount used in the EU	50.000 kg
Minimum emission days per year	365
Emission factor air	98 %
Emission factor water	1 %
Emission factor soil	1 %
Receive Surf. Water (Flow Rate).	18.000 m3/d
Dilution factor river	10

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 18.10.2023

Version: 1.0

Date previous version: not applicable

Previous version: none

Date / First version: 18.10.2023

Product: **n-HEXYL GLYCOL**

(ID no. 30034797/SDS\_GEN\_AT/EN)

Date of print 19.10.2025

Dilution factor coast	100
<b>Risk Management Measures</b>	
Type of STP	Municipal STP
Assumed sewage treatment plant flow (m3/d)	2.000 m3/d
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Environment
Risk Characterization Ratio (RCR)	0,000659
	Risk from environmental exposure is driven by soil.
Maximum amount of safe use	41,6 kg/d
Risk from environmental exposure is driven by soil.	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	ESVOC SpERC 8.3b.v2
<b>Operational conditions</b>	
Annual amount used in the EU	50.000 kg
Minimum emission days per year	365
Emission factor air	98 %
Emission factor water	1 %
Emission factor soil	1 %
Receive Surf. Water (Flow Rate).	18.000 m3/d
Dilution factor river	10
Dilution factor coast	100
<b>Risk Management Measures</b>	
Type of STP	Municipal STP
Assumed sewage treatment plant flow (m3/d)	2.000 m3/d
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Environment
Risk Characterization Ratio (RCR)	0,000659
	Risk from environmental exposure is driven by soil.
Maximum amount of safe use	41,6 kg/d
Risk from environmental exposure is driven by soil.	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC1: Chemical production or refinery in closed process

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 18.10.2023

Version: 1.0

Date previous version: not applicable

Previous version: none

Date / First version: 18.10.2023

Product: **n-HEXYL GLYCOL**

(ID no. 30034797/SDS\_GEN\_AT/EN)

Date of print 19.10.2025

	without likelihood of exposure or processes with equivalent containment conditions. Use domain: professional
<b>Operational conditions</b>	
Concentration of the substance	2-hexyloxyethanol Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	10 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
<b>Risk Management Measures</b>	
Personal measures have to be applied in case of potential exposure only.	
Use suitable eye protection.	
Wear chemically resistant gloves in combination with 'basic' employee training.	
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	0,0609 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,003311
Assessment method	Qualitative assessment
	Worker - dermal
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC2: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions Use domain: professional
<b>Operational conditions</b>	
Concentration of the substance	2-hexyloxyethanol Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	10 Pa
Duration and Frequency of activity	480 min 5 days per week

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 18.10.2023

Version: 1.0

Date previous version: not applicable

Previous version: none

Date / First version: 18.10.2023

Product: **n-HEXYL GLYCOL**

(ID no. 30034797/SDS\_GEN\_AT/EN)

Date of print 19.10.2025

Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
<b>Risk Management Measures</b>	
Provide a good standard of general or controlled ventilation (5 to 10 air changes per hour)	Effectiveness: 70 %
Personal measures have to be applied in case of potential exposure only.	
Use suitable eye protection.	
Wear chemically resistant gloves in combination with 'basic' employee training.	
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	9,1375 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,496603
Assessment method	Qualitative assessment
	Worker - dermal
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition Use domain: professional
<b>Operational conditions</b>	
Concentration of the substance	2-hexyloxyethanol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	10 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
<b>Risk Management Measures</b>	
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %
Personal measures have to be applied in case of potential exposure only.	



BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 18.10.2023

Version: 1.0

Date previous version: not applicable

Previous version: none

Date / First version: 18.10.2023

Product: **n-HEXYL GLYCOL**

(ID no. 30034797/SDS\_GEN\_AT/EN)

Date of print 19.10.2025

Use suitable eye protection.	
Wear chemically resistant gloves in combination with 'basic' employee training.	
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	12,7925 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,695245
Assessment method	Qualitative assessment
	Worker - dermal
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC4: Chemical production where opportunity for exposure arises Use domain: professional
<b>Operational conditions</b>	
Concentration of the substance	2-hexyloxyethanol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	10 Pa
Duration and Frequency of activity	240 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
<b>Risk Management Measures</b>	
Provide a good standard of general or controlled ventilation (5 to 10 air changes per hour)	Effectiveness: 70 %
Personal measures have to be applied in case of potential exposure only.	
Use suitable eye protection.	
Wear chemically resistant gloves in combination with 'basic' employee training.	
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	10,965 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,595924
Assessment method	Qualitative assessment
	Worker - dermal

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 18.10.2023

Version: 1.0

Date previous version: not applicable

Previous version: none

Date / First version: 18.10.2023

Product: **n-HEXYL GLYCOL**

(ID no. 30034797/SDS\_GEN\_AT/EN)

Date of print 19.10.2025

### **Guidance to Downstream Users**

For scaling see: <http://www.ecetoc.org/tra>

### **Contributing exposure scenario**

<b>Use descriptors covered</b>	PROC5: Mixing or blending in batch processes Use domain: professional
<b>Operational conditions</b>	
Concentration of the substance	2-hexyloxyethanol Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	10 Pa
Duration and Frequency of activity	240 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.

### **Risk Management Measures**

Provide a good standard of general or controlled ventilation (5 to 10 air changes per hour)	Effectiveness: 70 %
Personal measures have to be applied in case of potential exposure only.	
Use suitable eye protection.	
Wear chemically resistant gloves in combination with 'basic' employee training.	

### **Exposure estimate and reference to its source**

Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	10,965 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,595924
Assessment method	Qualitative assessment
	Worker - dermal

### **Guidance to Downstream Users**

For scaling see: <http://www.ecetoc.org/tra>

### **Contributing exposure scenario**

<b>Use descriptors covered</b>	PROC8a: Transfer of substance or mixture (charging and discharging) at non-dedicated facilities Use domain: professional
<b>Operational conditions</b>	
Concentration of the substance	2-hexyloxyethanol Content: $\geq 0\%$ - $\leq 100\%$

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 18.10.2023

Version: 1.0

Date previous version: not applicable

Previous version: none

Date / First version: 18.10.2023

Product: **n-HEXYL GLYCOL**

(ID no. 30034797/SDS\_GEN\_AT/EN)

Date of print 19.10.2025

Physical state	liquid
Vapour pressure of the substance during use	10 Pa
Duration and Frequency of activity	60 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
<b>Risk Management Measures</b>	
Provide a good standard of general or controlled ventilation (5 to 10 air changes per hour)	Effectiveness: 70 %
Personal measures have to be applied in case of potential exposure only.	
Use suitable eye protection.	
Wear chemically resistant gloves in combination with 'basic' employee training.	
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	9,1375 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,496603
Assessment method	Qualitative assessment
	Worker - dermal
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC8b: Transfer of substance or mixture (charging and discharging) at dedicated facilities Use domain: professional
<b>Operational conditions</b>	
Concentration of the substance	2-hexyloxyethanol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	10 Pa
Duration and Frequency of activity	240 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
<b>Risk Management Measures</b>	
Provide a good standard of general or controlled ventilation (5 to 10 air changes per hour)	Effectiveness: 70 %

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 18.10.2023

Version: 1.0

Date previous version: not applicable

Previous version: none

Date / First version: 18.10.2023

Product: **n-HEXYL GLYCOL**

(ID no. 30034797/SDS\_GEN\_AT/EN)

Date of print 19.10.2025

Personal measures have to be applied in case of potential exposure only.	
Use suitable eye protection.	
Wear chemically resistant gloves in combination with 'basic' employee training.	
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	10,965 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,595924
Assessment method	Qualitative assessment
	Worker - dermal
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC10: Roller application or brushing Use domain: professional
<b>Operational conditions</b>	
Concentration of the substance	2-hexyloxyethanol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	10 Pa
Duration and Frequency of activity	240 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
<b>Risk Management Measures</b>	
Local exhaust ventilation	Effectiveness: 80 %
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %
Personal measures have to be applied in case of potential exposure only.	
Use suitable eye protection.	
Wear chemically resistant gloves in combination with 'basic' employee training.	
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	12,7925 mg/m <sup>3</sup>

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 18.10.2023

Version: 1.0

Date previous version: not applicable

Previous version: none

Date / First version: 18.10.2023

Product: **n-HEXYL GLYCOL**

(ID no. 30034797/SDS\_GEN\_AT/EN)

Date of print 19.10.2025

Risk Characterization Ratio (RCR)	0,695245
Assessment method	Qualitative assessment
	Worker - dermal
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC11: Non industrial spraying Use domain: professional
	Surface spraying of liquids
<b>Operational conditions</b>	
Concentration of the substance	2-hexyloxyethanol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	10 Pa
Duration and Frequency of activity	240 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
	Any sized room
Application rate	> 3 l/min
<b>Risk Management Measures</b>	
Wear suitable respiratory protection.	Effectiveness: 90 %
Ensure that the task is not carried out overhead.	
Ensure that general housekeeping is in place	
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	
Personal measures have to be applied in case of potential exposure only.	
Use suitable eye protection.	
Wear chemically resistant gloves in combination with 'basic' employee training.	
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v4.2, Advanced REACH Tool v1.5
	Worker - inhalation, long-term - systemic
Exposure estimate	11 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,597826
Assessment method	Qualitative assessment
	Worker - dermal

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 18.10.2023

Version: 1.0

Date previous version: not applicable

Previous version: none

Date / First version: 18.10.2023

Product: **n-HEXYL GLYCOL**

(ID no. 30034797/SDS\_GEN\_AT/EN)

Date of print 19.10.2025

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC13: Treatment of articles by dipping and pouring. Use domain: professional
<b>Operational conditions</b>	
Concentration of the substance	2-hexyloxyethanol Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	10 Pa
Duration and Frequency of activity	240 min 5 days per week
Indoor/Outdoor	Indoor
Assumes activities are at ambient temperature.	
<b>Risk Management Measures</b>	
Provide a good standard of general or controlled ventilation (5 to 10 air changes per hour)	Effectiveness: 70 %
Personal measures have to be applied in case of potential exposure only.	
Use suitable eye protection.	
Wear chemically resistant gloves in combination with 'basic' employee training.	
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	10,965 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,595924
Assessment method	Qualitative assessment
	Worker - dermal
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC15: Use a laboratory reagent. Use domain: professional
<b>Operational conditions</b>	
Concentration of the substance	2-hexyloxyethanol Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	10 Pa

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 18.10.2023

Version: 1.0

Date previous version: not applicable

Previous version: none

Date / First version: 18.10.2023

Product: **n-HEXYL GLYCOL**

(ID no. 30034797/SDS\_GEN\_AT/EN)

Date of print 19.10.2025

Duration and Frequency of activity	240 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
<b>Risk Management Measures</b>	
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %
Personal measures have to be applied in case of potential exposure only.	
Use suitable eye protection.	
Wear chemically resistant gloves in combination with 'basic' employee training.	
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	12,7925 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,695245
Assessment method	Qualitative assessment
	Worker - dermal
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

\*\*\*\*\*

## 8. Short title of exposure scenario

Use in Cleaning Agents, (use in professional settings)

ERC8a, ERC8d; PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC10, PROC11, PROC13

## Control of exposure and risk management measures

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	ESVOC SpERC 8.4b.v3
<b>Operational conditions</b>	
Annual amount used in the EU	50.000 kg
Minimum emission days per year	365
Emission factor air	4 %
Emission factor water	1 ppm
Emission factor soil	0,2 ppm

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 18.10.2023

Version: 1.0

Date previous version: not applicable

Previous version: none

Date / First version: 18.10.2023

Product: **n-HEXYL GLYCOL**

(ID no. 30034797/SDS\_GEN\_AT/EN)

Date of print 19.10.2025

Receive Surf. Water (Flow Rate).	18.000 m3/d
Dilution factor river	10
Dilution factor coast	100
<b>Risk Management Measures</b>	
Type of STP	Municipal STP
Assumed sewage treatment plant flow (m3/d)	2.000 m3/d
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Environment
Risk Characterization Ratio (RCR)	0,000652
	Risk from environmental exposure is driven by soil.
Maximum amount of safe use	42 kg/d
Risk from environmental exposure is driven by soil.	

<b>Contributing exposure scenario</b>	
Use descriptors covered	ESVOC SpERC 8.4b.v3
<b>Operational conditions</b>	
Annual amount used in the EU	50.000 kg
Minimum emission days per year	365
Emission factor air	4 %
Emission factor water	1 ppm
Emission factor soil	0,2 ppm
Receive Surf. Water (Flow Rate).	18.000 m3/d
Dilution factor river	10
Dilution factor coast	100
<b>Risk Management Measures</b>	
Type of STP	Municipal STP
Assumed sewage treatment plant flow (m3/d)	2.000 m3/d
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Environment
Risk Characterization Ratio (RCR)	0,000652
	Risk from environmental exposure is driven by soil.
Maximum amount of safe use	42 kg/d



BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 18.10.2023

Version: 1.0

Date previous version: not applicable

Previous version: none

Date / First version: 18.10.2023

Product: **n-HEXYL GLYCOL**

(ID no. 30034797/SDS\_GEN\_AT/EN)

Date of print 19.10.2025

Risk from environmental exposure is driven by soil.

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC2: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions Use domain: professional
<b>Operational conditions</b>	
Concentration of the substance	2-hexyloxyethanol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	10 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Assumes activities are at ambient temperature.	
<b>Risk Management Measures</b>	
Provide a good standard of general or controlled ventilation (5 to 10 air changes per hour)	Effectiveness: 70 %
Personal measures have to be applied in case of potential exposure only.	
Use suitable eye protection.	
Wear chemically resistant gloves in combination with 'basic' employee training.	
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	9,1375 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,496603
Assessment method	Qualitative assessment
	Worker - dermal
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition Use domain: professional
<b>Operational conditions</b>	

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 18.10.2023

Version: 1.0

Date previous version: not applicable

Previous version: none

Date / First version: 18.10.2023

Product: **n-HEXYL GLYCOL**

(ID no. 30034797/SDS\_GEN\_AT/EN)

Date of print 19.10.2025

Concentration of the substance	2-hexyloxyethanol Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	10 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
<b>Risk Management Measures</b>	
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %
Personal measures have to be applied in case of potential exposure only.	
Use suitable eye protection.	
Wear chemically resistant gloves in combination with 'basic' employee training.	
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	12,7925 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,695245
Assessment method	Qualitative assessment
	Worker - dermal
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC4: Chemical production where opportunity for exposure arises Use domain: professional
<b>Operational conditions</b>	
Concentration of the substance	2-hexyloxyethanol Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	10 Pa
Duration and Frequency of activity	240 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
<b>Risk Management Measures</b>	

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 18.10.2023

Version: 1.0

Date previous version: not applicable

Previous version: none

Date / First version: 18.10.2023

Product: **n-HEXYL GLYCOL**

(ID no. 30034797/SDS\_GEN\_AT/EN)

Date of print 19.10.2025

Provide a good standard of general or controlled ventilation (5 to 10 air changes per hour)	Effectiveness: 70 %
Personal measures have to be applied in case of potential exposure only.	
Use suitable eye protection.	
Wear chemically resistant gloves in combination with 'basic' employee training.	
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	10,965 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,595924
Assessment method	Qualitative assessment
	Worker - dermal
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC8a: Transfer of substance or mixture (charging and discharging) at non-dedicated facilities Use domain: professional
<b>Operational conditions</b>	
Concentration of the substance	2-hexyloxyethanol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	10 Pa
Duration and Frequency of activity	60 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
<b>Risk Management Measures</b>	
Provide a good standard of general or controlled ventilation (5 to 10 air changes per hour)	Effectiveness: 70 %
Personal measures have to be applied in case of potential exposure only.	
Use suitable eye protection.	
Wear chemically resistant gloves in combination with 'basic' employee training.	
<b>Exposure estimate and reference to its source</b>	

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 18.10.2023

Version: 1.0

Date previous version: not applicable

Previous version: none

Date / First version: 18.10.2023

Product: **n-HEXYL GLYCOL**

(ID no. 30034797/SDS\_GEN\_AT/EN)

Date of print 19.10.2025

Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	9,1375 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,496603
Assessment method	Qualitative assessment
	Worker - dermal
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC8b: Transfer of substance or mixture (charging and discharging) at dedicated facilities Use domain: professional
<b>Operational conditions</b>	
Concentration of the substance	2-hexyloxyethanol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	10 Pa
Duration and Frequency of activity	240 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
<b>Risk Management Measures</b>	
Provide a good standard of general or controlled ventilation (5 to 10 air changes per hour)	Effectiveness: 70 %
Personal measures have to be applied in case of potential exposure only.	
Use suitable eye protection.	
Wear chemically resistant gloves in combination with 'basic' employee training.	
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	10,965 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,595924
Assessment method	Qualitative assessment
	Worker - dermal
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC10: Roller application or brushing

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 18.10.2023

Version: 1.0

Date previous version: not applicable

Previous version: none

Date / First version: 18.10.2023

Product: **n-HEXYL GLYCOL**

(ID no. 30034797/SDS\_GEN\_AT/EN)

Date of print 19.10.2025

	Use domain: professional
<b>Operational conditions</b>	
Concentration of the substance	2-hexyloxyethanol Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	10 Pa
Duration and Frequency of activity	60 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
<b>Risk Management Measures</b>	
Local exhaust ventilation	Effectiveness: 80 %
Personal measures have to be applied in case of potential exposure only.	
Use suitable eye protection.	
Wear chemically resistant gloves in combination with 'basic' employee training.	
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	6,0917 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,331069
Assessment method	Qualitative assessment
	Worker - dermal
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC11: Non industrial spraying Use domain: professional
	Surface spraying of liquids
<b>Operational conditions</b>	
Concentration of the substance	2-hexyloxyethanol Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	10 Pa
Duration and Frequency of activity	240 min 5 days per week
Indoor/Outdoor	Indoor

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 18.10.2023

Version: 1.0

Date previous version: not applicable

Previous version: none

Date / First version: 18.10.2023

Product: **n-HEXYL GLYCOL**

(ID no. 30034797/SDS\_GEN\_AT/EN)

Date of print 19.10.2025

	Assumes activities are at ambient temperature.
	Any sized room
Application rate	> 3 l/min
<b>Risk Management Measures</b>	
Wear suitable respiratory protection.	Effectiveness: 90 %
Ensure that the task is not carried out overhead.	
Ensure that general housekeeping is in place	
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	
Personal measures have to be applied in case of potential exposure only.	
Use suitable eye protection.	
Wear chemically resistant gloves in combination with 'basic' employee training.	
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v4.2, Advanced REACH Tool v1.5
	Worker - inhalation, long-term - systemic
Exposure estimate	11 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,597826
Assessment method	Qualitative assessment
	Worker - dermal

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC13: Treatment of articles by dipping and pouring. Use domain: professional
<b>Operational conditions</b>	
Concentration of the substance	2-hexyloxyethanol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	10 Pa
Duration and Frequency of activity	240 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
<b>Risk Management Measures</b>	
Provide a good standard of general or controlled ventilation (5 to 10 air changes per hour)	Effectiveness: 70 %
Personal measures have to be applied in case of potential exposure	

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 18.10.2023

Version: 1.0

Date previous version: not applicable

Previous version: none

Date / First version: 18.10.2023

Product: **n-HEXYL GLYCOL**

(ID no. 30034797/SDS\_GEN\_AT/EN)

Date of print 19.10.2025

only.	
Use suitable eye protection.	
Wear chemically resistant gloves in combination with 'basic' employee training.	
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	10,965 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,595924
Assessment method	Qualitative assessment
	Worker - dermal
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

\*\*\*\*\*

## 9. Short title of exposure scenario

Use in Coatings, (consumer use)

ERC8a, ERC8c, ERC8d, ERC8f; PC1, PC9a, PC9b, PC24, PC31

## Control of exposure and risk management measures

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	ESVOC SpERC 8.3c.v2
<b>Operational conditions</b>	
Annual amount used in the EU	50.000 kg
Minimum emission days per year	365
Emission factor air	98,5 %
Emission factor water	1 %
Emission factor soil	0,5 %
Receive Surf. Water (Flow Rate).	18.000 m3/d
Dilution factor river	10
Dilution factor coast	100
<b>Risk Management Measures</b>	
Type of STP	Municipal STP
Assumed sewage treatment plant flow (m3/d)	2.000 m3/d
<b>Exposure estimate and reference to its source</b>	

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 18.10.2023

Version: 1.0

Date previous version: not applicable

Previous version: none

Date / First version: 18.10.2023

Product: **n-HEXYL GLYCOL**

(ID no. 30034797/SDS\_GEN\_AT/EN)

Date of print 19.10.2025

Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Environment
Risk Characterization Ratio (RCR)	0,000659
	Risk from environmental exposure is driven by soil.
Maximum amount of safe use	41,6 kg/d
	Risk from environmental exposure is driven by soil.

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	ERC8c: Widespread use leading to inclusion into/onto article (indoor)
<b>Operational conditions</b>	
Annual amount used in the EU	50.000 kg
Minimum emission days per year	365
Emission factor air	15 %
Emission factor water	1 %
Emission factor soil	0 %
Receive Surf. Water (Flow Rate).	18.000 m3/d
Dilution factor river	10
Dilution factor coast	100
<b>Risk Management Measures</b>	
Type of STP	Municipal STP
Assumed sewage treatment plant flow (m3/d)	2.000 m3/d
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Environment
Risk Characterization Ratio (RCR)	0,00072
	Risk from environmental exposure is driven by soil.
Maximum amount of safe use	380,7 kg/d
	Risk from environmental exposure is driven by soil.

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	ESVOC SpERC 8.3c.v2
<b>Operational conditions</b>	
Annual amount used in the EU	50.000 kg
Minimum emission days per year	365



BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 18.10.2023

Version: 1.0

Date previous version: not applicable

Previous version: none

Date / First version: 18.10.2023

Product: **n-HEXYL GLYCOL**

(ID no. 30034797/SDS\_GEN\_AT/EN)

Date of print 19.10.2025

Emission factor air	98,5 %
Emission factor water	1 %
Emission factor soil	0,5 %
Receive Surf. Water (Flow Rate).	18.000 m3/d
Dilution factor river	10
Dilution factor coast	100
<b>Risk Management Measures</b>	
Type of STP	Municipal STP
Assumed sewage treatment plant flow (m3/d)	2.000 m3/d
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Environment
Risk Characterization Ratio (RCR)	0,000659
	Risk from environmental exposure is driven by soil.
Maximum amount of safe use	41,6 kg/d
Risk from environmental exposure is driven by soil.	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	ERC8f: Widespread use leading to inclusion into/onto article (outdoor)
<b>Operational conditions</b>	
Annual amount used in the EU	50.000 kg
Minimum emission days per year	365
Emission factor air	15 %
Emission factor water	1 %
Emission factor soil	0,5 %
Receive Surf. Water (Flow Rate).	18.000 m3/d
Dilution factor river	10
Dilution factor coast	100
<b>Risk Management Measures</b>	
Type of STP	Municipal STP

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 18.10.2023

Version: 1.0

Date previous version: not applicable

Previous version: none

Date / First version: 18.10.2023

Product: **n-HEXYL GLYCOL**

(ID no. 30034797/SDS\_GEN\_AT/EN)

Date of print 19.10.2025

Assumed sewage treatment plant flow (m3/d)	2.000 m3/d
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Environment
Risk Characterization Ratio (RCR)	0,00072
	Risk from environmental exposure is driven by soil.
Maximum amount of safe use	380,7 kg/d
	Risk from environmental exposure is driven by soil.

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PC1: Adhesives, Sealants
<b>Operational conditions</b>	
Concentration of the substance	2-hexyloxyethanol Content: >= 0 % - <= 2 %
Vapour pressure of the substance during use	10 Pa
Duration and Frequency of activity	Exposure duration: 45 min Relevant for inhalative exposure estimates
Duration and Frequency of activity	Application duration: 30 min Relevant for inhalative exposure estimates
Duration and Frequency of activity	3 uses per year
Room size	10 m3
Ventilation rate per hour	2
Temperature (Application)	20 °C
body weight	65 kg
Release area	250 cm <sup>2</sup>
	Release area increases over time
Release duration	30 min
	Relevant for inhalative exposure estimates
Contact rate	50 mg/min
Release duration	30 min
	Relevant for dermal exposure estimates
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v4.2, ConsExpo v4.1, Dermal model: constant application rate
	Consumer - dermal, short-term - systemic
Exposure estimate	0,4615 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,049896
	The calculation is based on the external dose.
Assessment method	EASY TRA v4.2, ConsExpo v4.1, Inhalation model: exposure to vapour - evaporation
	Consumer - inhalation, long-term - systemic
Exposure estimate	0,0176 mg/m <sup>3</sup>

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 18.10.2023

Version: 1.0

Date previous version: not applicable

Previous version: none

Date / First version: 18.10.2023

Product: **n-HEXYL GLYCOL**

(ID no. 30034797/SDS\_GEN\_AT/EN)

Date of print 19.10.2025

Risk Characterization Ratio (RCR)	0,006072
	The exposure calculation is based on the mean concentration on the day of exposure.
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.rivm.nl/en/healthandddisease/productsafety/ConsExpo.jsp">http://www.rivm.nl/en/healthandddisease/productsafety/ConsExpo.jsp</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PC9a: Coatings and paints, thinners, paint removers
<b>Operational conditions</b>	
Concentration of the substance	2-hexyloxyethanol Content: >= 0 % - <= 7 %
Vapour pressure of the substance during use	10 Pa
Duration and Frequency of activity	Exposure duration: 132 min Relevant for inhalative exposure estimates
Duration and Frequency of activity	Application duration: 120 min Relevant for inhalative exposure estimates
Duration and Frequency of activity	1 uses per year
Room size	20 m <sup>3</sup>
Ventilation rate per hour	0,6
Temperature (Application)	20 °C
body weight	65 kg
Release area	100000 cm <sup>2</sup>
	Release area increases over time
Release duration	120 min
	Relevant for inhalative exposure estimates
Contact rate	30 mg/min
Release duration	120 min
	Relevant for dermal exposure estimates
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v4.2, ConsExpo v4.1, Dermal model: constant application rate
	Consumer - dermal, short-term - systemic
Exposure estimate	3,8769 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,419127
	The calculation is based on the external dose.
Assessment method	EASY TRA v4.2, ConsExpo v4.1, Inhalation model: exposure to vapour - evaporation
	Consumer - inhalation, long-term - systemic
Exposure estimate	0,697 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,240337
	The exposure calculation is based on the mean concentration on the day of exposure.
<b>Guidance to Downstream Users</b>	

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 18.10.2023

Version: 1.0

Date previous version: not applicable

Previous version: none

Date / First version: 18.10.2023

Product: **n-HEXYL GLYCOL**

(ID no. 30034797/SDS\_GEN\_AT/EN)

Date of print 19.10.2025

For scaling see: <http://www.rivm.nl/en/healthandddisease/productsafety/ConsExpo.jsp>

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PC9b: Fillers, putties, plasters, modelling clay
<b>Operational conditions</b>	
Concentration of the substance	2-hexyloxyethanol Content: $\geq 0\%$ - $\leq 2\%$
Vapour pressure of the substance during use	10 Pa
Duration and Frequency of activity	Exposure duration: 240 min Relevant for inhalative exposure estimates
Duration and Frequency of activity	Application duration: 20 min Relevant for inhalative exposure estimates
Duration and Frequency of activity	3 uses per year
Room size	20 m <sup>3</sup>
Ventilation rate per hour	0,6
Temperature (Application)	20 °C
body weight	65 kg
	Amount per use 0,05 g Relevant for dermal exposure estimates
Release area	200 cm <sup>2</sup>
	Release area increases over time
Release duration	20 min
	Relevant for inhalative exposure estimates
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v4.2, ConsExpo v4.1, Dermal model: instant application
	Consumer - dermal, short-term - systemic
Exposure estimate	0,0154 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,001663
	The calculation is based on the external dose.
Assessment method	EASY TRA v4.2, ConsExpo v4.1, Inhalation model: exposure to vapour - evaporation
	Consumer - inhalation, long-term - systemic
Exposure estimate	0,2845 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,098095
	The exposure calculation is based on the mean concentration on the day of exposure.
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.rivm.nl/en/healthandddisease/productsafety/ConsExpo.jsp">http://www.rivm.nl/en/healthandddisease/productsafety/ConsExpo.jsp</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PC24: Lubricants, Greases and Release Products

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 18.10.2023

Version: 1.0

Date previous version: not applicable

Previous version: none

Date / First version: 18.10.2023

Product: **n-HEXYL GLYCOL**

(ID no. 30034797/SDS\_GEN\_AT/EN)

Date of print 19.10.2025

<b>Operational conditions</b>	
Concentration of the substance	2-hexyloxyethanol Content: $\geq 0\%$ - $\leq 0,5\%$
Vapour pressure of the substance during use	10 Pa
Duration and Frequency of activity	Exposure duration: 60 min Relevant for inhalative exposure estimates
Duration and Frequency of activity	Application duration: 60 min Relevant for inhalative exposure estimates
Duration and Frequency of activity	< 1 uses per year
Room size	34 m <sup>3</sup>
Ventilation rate per hour	1,5
Temperature (Application)	20 °C
body weight	65 kg
	Amount per use 0,25 g Relevant for dermal exposure estimates
Release area	150000 cm <sup>2</sup>
	Release area increases over time
Release duration	60 min
	Relevant for inhalative exposure estimates
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v4.2, ConsExpo v4.1, Dermal model: instant application
	Consumer - dermal, short-term - systemic
Exposure estimate	0,0192 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,002079
	The calculation is based on the external dose.
Assessment method	EASY TRA v4.2, ConsExpo v4.1, Inhalation model: exposure to vapour - evaporation
	Consumer - inhalation, long-term - systemic
Exposure estimate	0,7813 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,269426
	The exposure calculation is based on the mean concentration on the day of exposure.
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.rivm.nl/en/healthandddisease/productsafety/ConsExpo.jsp">http://www.rivm.nl/en/healthandddisease/productsafety/ConsExpo.jsp</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PC31: Polishes and Wax Blends.
<b>Operational conditions</b>	
Concentration of the substance	2-hexyloxyethanol Content: $\geq 0\%$ - $\leq 15\%$
Vapour pressure of the substance	10 Pa

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 18.10.2023

Version: 1.0

Date previous version: not applicable

Previous version: none

Date / First version: 18.10.2023

Product: **n-HEXYL GLYCOL**

(ID no. 30034797/SDS\_GEN\_AT/EN)

Date of print 19.10.2025

during use	
Duration and Frequency of activity	Exposure duration: 240 min Relevant for inhalative exposure estimates
Duration and Frequency of activity	Application duration: 20 min Relevant for inhalative exposure estimates
Duration and Frequency of activity	197 uses per year
Room size	58 m <sup>3</sup>
Ventilation rate per hour	0,5
Temperature (Application)	20 °C
body weight	68,8 kg
	Amount per use 0,286 g Relevant for dermal exposure estimates
Release area	320000 cm <sup>2</sup>
	Release area increases over time
Release duration	20 min
	Relevant for inhalative exposure estimates
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v4.2, ConsExpo v4.1, Dermal model: instant application
	Consumer - dermal, short-term - systemic
Exposure estimate	0,6235 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,06741
	The calculation is based on the external dose.
Assessment method	EASY TRA v4.2, ConsExpo v4.1, Inhalation model: exposure to vapour - evaporation
	Consumer - inhalation, long-term - systemic
Exposure estimate	1,7971 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,619694
	The exposure calculation is based on the mean concentration on the day of exposure.
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp">http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp</a>	

\*\*\*\*\*