

Safety data sheet

Page: 1/115

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 12.12.2023

Version: 2.0

Date / Previous version: 02.07.2021

Previous version: 1.0

Product: **METHOXYPROPYLACETATE**

(ID no. 30034751/SDS_GEN_ES/EN)

Date of print 19.10.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

METHOXYPROPYLACETATE

Chemical name: 1-methoxy-2-propylacetate

INDEX-Number: 607-195-00-7

CAS Number: 108-65-6

REACH registration number: 01-2119475791-29

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses: process chemical, solvent(s)

For the detailed identified uses of the product see appendix of the safety data sheet.

1.3. Details of the supplier of the safety data sheet

Company:

BASF SE
67056 Ludwigshafen
GERMANY

Contact address:

BASF Española S. L. Unipersonal
C/ Can Rabia, 3/5
08017 Barcelona
SPAIN

Telephone: +34 93 496-4214

E-mail address: Seguridad-de-Producto.Iberia@basf.com

1.4. Emergency telephone number

Instituto Nacional de Toxicología y Ciencias Forenses (INTCF)

Tel.: 915 620 420

Número internacional de emergencia (24h) con respuesta local

Telephone: +49 180 2273-112

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 12.12.2023

Version: 2.0

Date / Previous version: 02.07.2021

Previous version: 1.0

Product: **METHOXYPROPYLACETATE**

(ID no. 30034751/SDS_GEN_ES/EN)

Date of print 19.10.2025

SECTION 2: Hazards Identification

2.1. Classification of the substance or mixture

According to Regulation (EC) No 1272/2008 [CLP]

Flam. Liq. 3	H226 Flammable liquid and vapour.
STOT SE 3	H336 May cause drowsiness or dizziness.

For the classifications not written out in full in this section the full text can be found in section 16.

2.2. Label elements

According to Regulation (EC) No 1272/2008 [CLP]

Pictogram:



Signal Word:

Warning

Hazard Statement:

H226	Flammable liquid and vapour.
H336	May cause drowsiness or dizziness.

Precautionary Statements (Prevention):

P271	Use only outdoors or in a well-ventilated area.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P280	Wear protective gloves and eye protection or face protection.

Precautionary Statements (Response):

P312	Call a POISON CENTER or physician if you feel unwell.
------	---

Precautionary Statements (Storage):

P233	Keep container tightly closed.
------	--------------------------------

Precautionary Statements (Disposal):

P501	Dispose of contents and container to hazardous or special waste collection point.
------	---

2.3. Other hazards

According to Regulation (EC) No 1272/2008 [CLP]

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

See section 12 - Results of PBT and vPvB assessment.

Product does not contain a substance above legal limits included in the list established in accordance with Article 59(1) of Regulation (EC) No 1907/2006 for having endocrine disrupting

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 12.12.2023

Version: 2.0

Date / Previous version: 02.07.2021

Previous version: 1.0

Product: **METHOXYPROPYLACETATE**

(ID no. 30034751/SDS_GEN_ES/EN)

Date of print 19.10.2025

properties or is identified to have endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

SECTION 3: Composition/Information on Ingredients

3.1. Substances

Chemical nature

2-methoxy-1-methylethyl acetate Content (W/W): $\geq 99,5 \%$ CAS Number: 108-65-6 EC-Number: 203-603-9 INDEX-Number: 607-195-00-7	Flam. Liq. 3 STOT SE 3 (drowsiness and dizziness) H226, H336
--	--

stabilized with:

2,6-di-tert-Butyl-p-cresol

CAS Number: 128-37-0 EC-Number: 204-881-4	Aquatic Acute 1 Aquatic Chronic 1 M-factor chronic: 1 H400, H410
--	---

Regulatory relevant ingredients

2-methoxy-1-methylethyl acetate Content (W/W): $\geq 99,5 \%$ - $< 100 \%$ CAS Number: 108-65-6 EC-Number: 203-603-9 INDEX-Number: 607-195-00-7	Flam. Liq. 3 STOT SE 3 (drowsiness and dizziness) H226, H336
---	--

2-methoxypropyl acetate Content (W/W): $\geq 0 \%$ - $< 0,3 \%$ CAS Number: 70657-70-4 EC-Number: 274-724-2 INDEX-Number: 607-251-00-0	Flam. Liq. 3 Repr. 1B (unborn child) STOT SE 3 (irr. to respiratory syst.) H226, H335, H360D
--	---

For the classifications not written out in full in this section, including the hazard classes and the hazard statements, the full text is listed in section 16.

3.2. Mixtures

Not applicable

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 12.12.2023

Version: 2.0

Date / Previous version: 02.07.2021

Previous version: 1.0

Product: **METHOXYPROPYLACETATE**

(ID no. 30034751/SDS_GEN_ES/EN)

Date of print 19.10.2025

SECTION 4: First-Aid Measures

4.1. Description of first aid measures

First aid personnel should pay attention to their own safety. If the patient is likely to become unconscious, place and transport in stable sideways position (recovery position). Immediately remove contaminated clothing.

If inhaled:

Keep patient calm, remove to fresh air, seek medical attention.

On skin contact:

Wash thoroughly with soap and water

On contact with eyes:

Wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.

On ingestion:

Immediately rinse mouth and then drink 200-300 ml of water, seek medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms: Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11.

Hazards: Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11. (Further) symptoms and / or effects are not known so far

4.3. Indication of any immediate medical attention and special treatment needed

Treatment: Treat according to symptoms (decontamination, vital functions), no known specific antidote.

SECTION 5: Fire-Fighting Measures

5.1. Extinguishing media

Suitable extinguishing media:

dry powder, water spray, carbon dioxide, alcohol-resistant foam

Unsuitable extinguishing media for safety reasons:

water jet

Additional information:

Use extinguishing measures to suit surroundings.

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 12.12.2023

Version: 2.0

Date / Previous version: 02.07.2021

Previous version: 1.0

Product: **METHOXYPROPYLACETATE**

(ID no. 30034751/SDS_GEN_ES/EN)

Date of print 19.10.2025

5.2. Special hazards arising from the substance or mixture

Advice: Flammable liquid Cool endangered containers with water-spray. See SDS section 7 - Handling and storage.

5.3. Advice for fire-fighters

Special protective equipment:

Wear a self-contained breathing apparatus. Special protective equipment for firefighters

Further information:

Evacuate area of all unnecessary personnel. Fight fire from maximum distance.

Extend fire extinguishing measures to the surroundings. Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

SECTION 6: Accidental Release Measures

High risk of slipping due to leakage/spillage of product.

Release of substance/product can cause fire or explosion. Shut off or stop source of leak. Shut off or stop released substance/product under safe conditions.

Pack in tightly closed containers for disposal.

6.1. Personal precautions, protective equipment and emergency procedures

Handle in accordance with good industrial hygiene and safety practice.

Avoid all sources of ignition: heat, sparks, open flame. Use antistatic tools.

6.2. Environmental precautions

Discharge into the environment must be avoided.

6.3. Methods and material for containment and cleaning up

Pick up with suitable appliance and dispose of. Spills should be contained, solidified, and placed in suitable containers for disposal. Dispose of absorbed material in accordance with regulations.

6.4. Reference to other sections

Information regarding exposure controls/personal protection and disposal considerations can be found in section 8 and 13.

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 12.12.2023

Version: 2.0

Date / Previous version: 02.07.2021

Previous version: 1.0

Product: **METHOXYPROPYLACETATE**

(ID no. 30034751/SDS_GEN_ES/EN)

Date of print 19.10.2025

SECTION 7: Handling and Storage

7.1. Precautions for safe handling

| Handle in accordance with good industrial hygiene and safety practice.

Protection against fire and explosion:

Prevent electrostatic charge - sources of ignition should be kept well clear - fire extinguishers should be kept handy.

7.2. Conditions for safe storage, including any incompatibilities

Unsuitable materials for containers: Low density polyethylene (LDPE), Paper/Fibreboard

Further information on storage conditions: Containers should be stored tightly sealed in a dry place.

7.3. Specific end use(s)

See exposure scenario(s) in the attachment to this safety data sheet.

SECTION 8: Exposure Controls/Personal Protection

8.1. Control parameters

Components with occupational exposure limits

108-65-6: 2-methoxy-1-methylethyl acetate	STEL value 550 mg/m ³ ; 100 ppm (OEL (EU))
	indicative
	Skin Designation (OEL (EU))
	The substance can be absorbed through the skin.
	TWA value 275 mg/m ³ ; 50 ppm (OEL (EU))
	indicative
70657-70-4: 2-methoxypropyl acetate	Skin Designation (OEL (ES))
	The substance can be absorbed through the skin.
	STEL value 550 mg/m ³ ; 100 ppm (OEL (ES))
	TWA value 275 mg/m ³ ; 50 ppm (OEL (ES))
70657-70-4: 2-methoxypropyl acetate	TWA value 28 mg/m ³ ; 5 ppm (OEL (ES))
	STEL value 220 mg/m ³ ; 40 ppm (OEL (ES))

PNEC

freshwater: 0,635 mg/l

marine water: 0,0635 mg/l

intermittent release: 6,35 mg/l

sediment (freshwater): 3,29 mg/kg

sediment (marine water): 0,329 mg/kg

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 12.12.2023

Version: 2.0

Date / Previous version: 02.07.2021

Previous version: 1.0

Product: **METHOXYPROPYLACETATE**

(ID no. 30034751/SDS_GEN_ES/EN)

Date of print 19.10.2025

soil: 0,29 mg/kg

STP: 100 mg/l

DNEL

worker:

Long-term exposure- systemic effects, Inhalation: 275 mg/m³

worker:

Long-term exposure- systemic effects, dermal: 796 mg/kg

consumer:

Long-term exposure- systemic effects, oral: 36 mg/kg

consumer:

Long-term exposure - systemic and local effects, Inhalation: 33 mg/m³

consumer:

Long-term exposure- systemic effects, dermal: 320 mg/kg

worker:

Short-term exposure - local effects, Inhalation: 550 mg/m³

consumer:

Short-term exposure - systemic effects, oral: 500 mg/kg

8.2. Exposure controls

Personal protective equipment

Respiratory protection:

Wear respiratory protection if ventilation is inadequate. Gas filter for gases/vapours of organic compounds (boiling point >65 °C, e. g. EN 14387 Type A)

Hand protection:

Chemical resistant protective gloves (EN ISO 374-1)

Suitable materials also with prolonged, direct contact (Recommended: Protective index 6, corresponding > 480 minutes of permeation time according to EN ISO 374-1):

butyl rubber (butyl) - 0.7 mm coating thickness

Suitable materials for short-term contact (recommended: At least protective index 2, corresponding > 30 minutes of permeation time according to EN ISO 374-1)

chloroprene rubber (CR) - 0.5 mm coating thickness

nitrile rubber (NBR) - 0.4 mm coating thickness

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 12.12.2023

Version: 2.0

Date / Previous version: 02.07.2021

Previous version: 1.0

Product: **METHOXYPROPYLACETATE**

(ID no. 30034751/SDS_GEN_ES/EN)

Date of print 19.10.2025

Manufacturer's directions for use should be observed because of great diversity of types.

Supplementary note: The specifications are based on tests, literature data and information of glove manufacturers or are derived from similar substances by analogy. Due to many conditions (e.g. temperature) it must be considered, that the practical usage of a chemical-protective glove in practice may be much shorter than the permeation time determined through testing.

Eye protection:

Safety glasses with side-shields (frame goggles) (e.g. EN 166)

Body protection:

Body protection must be chosen depending on activity and possible exposure, e.g. apron, protecting boots, chemical-protection suit (according to EN 14605 in case of splashes or EN ISO 13982 in case of dust).

General safety and hygiene measures

Avoid contact with eyes. Wearing of closed work clothing is required additionally to the stated personal protection equipment.

Environmental exposure controls

All appropriate measures must be taken to prevent the release of this product to the environment and to limit the dispersion of any release when it occurs. Suitable risk management measures should be in place.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

State of matter:	liquid	
Form:	liquid	
Colour:	colourless	
Odour:	ether-like	
Odour threshold:		
	not determined	
Melting point:	-66 °C	(measured)
	(1.013,25 hPa)	
	Literature data.	
Boiling point:	145,8 °C	(OECD Guideline 103)
	(1.013,25 hPa)	
	Extrapolated value	
Flammability:	Flammable.	(derived from flash point)
Lower explosion limit:		
	For liquids not relevant for classification and labelling., The lower explosion point may be 5 - 15 °C below the flash point.	
Upper explosion limit:		
	For liquids not relevant for classification and labelling.	

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 12.12.2023

Version: 2.0

Date / Previous version: 02.07.2021

Previous version: 1.0

Product: **METHOXYPROPYLACETATE**

(ID no. 30034751/SDS_GEN_ES/EN)

Date of print 19.10.2025

Flash point:	45,5 °C	(ASTM D3278, closed cup)
Auto-ignition temperature:	333 °C	(DIN 51794)
Thermal decomposition:	No decomposition if stored and handled as prescribed/indicated.	
pH value:		
	not applicable	
Viscosity, kinematic:	1,23 mm ² /s (20 °C)	(DIN 51562)
Thixotropy:	not thixotropic	
Solubility in water:		(Directive 92/69/EEC, A.6)
	198 g/l (20 °C, pH 6,8)	
Solubility (qualitative) solvent(s):	organic solvents soluble	
Partitioning coefficient n-octanol/water (log K _{ow}):	1,2 (20 °C; pH value: 6,8)	(OECD Guideline 117)
Vapour pressure:	3,5997 hPa (20 °C)	(OECD Guideline 104)
	dynamic	
Relative density:	0,967 (20 °C, 1.013 hPa)	(DIN 51757)
Density:	0,9677 g/cm ³ (20 °C, 1.013 hPa)	
	Literature data.	
	0,9286 g/cm ³ (55 °C)	(calculated)
Relative vapour density (air):	4,55 (20 °C)	(calculated)
	Heavier than air.	

9.2. Other information

Information with regard to physical hazard classes

Explosives

Explosion hazard:	Based on the chemical structure there is no indication of explosive properties.
Impact sensitivity:	not shock-sensitive Based on the chemical structure there is no shock-sensitivity.

Oxidizing properties

Fire promoting properties:	Based on its structural properties the product is not classified as oxidizing.
----------------------------	--

Flammable liquids

Sustained combustibility:	not determined
---------------------------	----------------

Pyrophoric properties

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 12.12.2023

Version: 2.0

Date / Previous version: 02.07.2021

Previous version: 1.0

Product: **METHOXYPROPYLACETATE**

(ID no. 30034751/SDS_GEN_ES/EN)

Date of print 19.10.2025

Self-ignition temperature:

Test type: Spontaneous self-ignition at room-temperature.

Based on its structural properties the product is not classified as self-igniting.

Self-heating substances and mixtures

Self heating ability: It is not a substance capable of spontaneous heating.

Substances and mixtures, which emit flammable gases in contact with water

Formation of flammable gases: Forms no flammable gases in the presence of water.

Corrosion to metals

No corrosive effect on metal.

Other safety characteristics

pKA:

The substance does not dissociate.

Adsorption/water - soil: KOC: 3,998; log KOC: 0,6 (calculated)
The data refer to the uncharged form of the substance.

Surface tension:

Based on chemical structure, surface activity is not to be expected.

Molar mass:

132,16 g/mol

SAPT-Temperature:

Study scientifically not justified.

Evaporation rate:

Value can be approximated from Henry's Law Constant or vapor pressure.

SECTION 10: Stability and Reactivity

10.1. Reactivity

| When heated can give off ignitable vapours.

Corrosion to metals: No corrosive effect on metal.

Formation of flammable gases: Remarks:

Forms no flammable gases in the presence of water.

10.2. Chemical stability

The product is stable if stored and handled as prescribed/indicated.

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 12.12.2023

Version: 2.0

Date / Previous version: 02.07.2021

Previous version: 1.0

Product: **METHOXYPROPYLACETATE**

(ID no. 30034751/SDS_GEN_ES/EN)

Date of print 19.10.2025

10.3. Possibility of hazardous reactions

Reacts with strong oxidizing agents.

10.4. Conditions to avoid

No special precautions other than good housekeeping of chemicals.

10.5. Incompatible materials

Substances to avoid:
strong oxidizing agents

10.6. Hazardous decomposition products

Hazardous decomposition products:
No hazardous decomposition products if stored and handled as prescribed/indicated.

SECTION 11: Toxicological Information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Assessment of acute toxicity:

Virtually nontoxic after a single ingestion. Virtually nontoxic by inhalation. Virtually nontoxic after a single skin contact.

Experimental/calculated data:

LD50 rat (oral): > 5.000 mg/kg (similar to OECD guideline 401)

LC50 rat (by inhalation): > 23,5 mg/l > 4345 ppm 6 h (similar to OECD guideline 403)

No mortality was observed. The vapour was tested.

LD50 rat (dermal): > 2.000 mg/kg (similar to OECD guideline 402)

No mortality was observed.

LD50 rabbit (dermal): > 5.000 mg/kg (similar to OECD guideline 402)

No mortality was observed.

Irritation

Assessment of irritating effects:

Not irritating to the skin. Not irritating to the eyes.

Experimental/calculated data:

Skin corrosion/irritation

rabbit: non-irritant (similar to OECD guideline 404)

Serious eye damage/irritation

rabbit: non-irritant (similar to OECD guideline 405)

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 12.12.2023

Version: 2.0

Date / Previous version: 02.07.2021

Previous version: 1.0

Product: **METHOXYPROPYLACETATE**

(ID no. 30034751/SDS_GEN_ES/EN)

Date of print 19.10.2025

Respiratory/Skin sensitization

Assessment of sensitization:

Skin sensitizing effects were not observed in animal studies.

Experimental/calculated data:

Guinea pig maximization test guinea pig: Non-sensitizing. (OECD Guideline 406)

Germ cell mutagenicity

Assessment of mutagenicity:

The substance was not mutagenic in bacteria. The substance was not mutagenic in mammalian cell culture. The substance was not genotoxic in mammalian cell culture.

Carcinogenicity

Assessment of carcinogenicity:

In long-term studies in rats and mice in which the substance was given by inhalation, a carcinogenic effect was not observed. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Reproductive toxicity

Assessment of reproduction toxicity:

The results of animal studies gave no indication of a fertility impairing effect. The product has not been fully tested. The statements have been derived in parts from products of a similar structure or composition.

Developmental toxicity

Assessment of teratogenicity:

No indications of a developmental toxic / teratogenic effect were seen in animal studies.

Specific target organ toxicity (single exposure)

Assessment of STOT single:

Possible narcotic effects (drowsiness or dizziness).

Repeated dose toxicity and Specific target organ toxicity (repeated exposure)

Assessment of repeated dose toxicity:

Repeated dermal uptake of the substance did not cause substance-related effects. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition. The substance may cause damage to the olfactory epithelium after repeated inhalation. Repeated oral uptake of the substance did not cause substance-related effects.

Aspiration hazard

No aspiration hazard expected.

Interactive effects

No data available.

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 12.12.2023

Version: 2.0

Date / Previous version: 02.07.2021

Previous version: 1.0

Product: **METHOXYPROPYLACETATE**

(ID no. 30034751/SDS_GEN_ES/EN)

Date of print 19.10.2025

11.2. Information on other hazards

Endocrine disrupting properties

The substance is not identified to have endocrine disrupting properties according to Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 nor is included in the Candidate List of substances of very high concern according to EU REACH Article 59 for having endocrine disrupting properties.

SECTION 12: Ecological Information

12.1. Toxicity

Assessment of aquatic toxicity:

There is a high probability that the product is not acutely harmful to aquatic organisms. The inhibition of the degradation activity of activated sludge is not anticipated when introduced to biological treatment plants in appropriate low concentrations.

Toxicity to fish:

LC50 (96 h) 134 mg/l, *Oncorhynchus mykiss* (OECD Guideline 203, static)

The details of the toxic effect relate to the nominal concentration.

Aquatic invertebrates:

EC50 (48 h) > 500 mg/l, *Daphnia magna* (Daphnia test acute, semistatic)

The details of the toxic effect relate to the nominal concentration.

Aquatic plants:

EC50 (72 h) > 1.000 mg/l (growth rate), *Selenastrum capricornutum* (OECD Guideline 201, static)

The details of the toxic effect relate to the nominal concentration.

Microorganisms/Effect on activated sludge:

EC10 (30 min) > 1.000 mg/l, activated sludge, industrial (DIN EN ISO 8192-OECD 209-88/302/EEC, P. C, aerobic)

The details of the toxic effect relate to the nominal concentration.

Chronic toxicity to fish:

No observed effect concentration (14 d) 47,5 mg/l, *Oryzias latipes* (OECD Guideline 204, Flow through.)

The details of the toxic effect relate to the nominal concentration.

Chronic toxicity to aquatic invertebrates:

No observed effect concentration (21 d) \geq 100 mg/l, *Daphnia magna* (OECD Guideline 202, part 2, semistatic)

Assessment of terrestrial toxicity:

No data available concerning terrestrial toxicity.

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 12.12.2023

Version: 2.0

Date / Previous version: 02.07.2021

Previous version: 1.0

Product: **METHOXYPROPYLACETATE**

(ID no. 30034751/SDS_GEN_ES/EN)

Date of print 19.10.2025

12.2. Persistence and degradability

Assessment biodegradation and elimination (H₂O):
Readily biodegradable (according to OECD criteria).

Elimination information:

83 % BOD of the ThOD (28 d) (OECD 301F; ISO 9408; 92/69/EWG, C.4-D) (aerobic, activated sludge, domestic, non-adapted)

Assessment of stability in water:

In contact with water the substance will hydrolyse slowly.

Information on Stability in Water (Hydrolysis):

$t_{1/2} > 1$ a (25 °C, pH value 7), (OECD Guideline 111, pH 7)

12.3. Bioaccumulative potential

Assessment bioaccumulation potential:

Because of the n-octanol/water distribution coefficient (log Pow) accumulation in organisms is not to be expected.

Bioaccumulation potential:

No data available.

12.4. Mobility in soil

Assessment transport between environmental compartments:

Volatility: The substance will slowly evaporate into the atmosphere from the water surface.

Adsorption in soil: Adsorption to solid soil phase is not expected.

12.5. Results of PBT and vPvB assessment

According to Annex XIII of Regulation (EC) No.1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH): The product does not fulfill the criteria for PBT (Persistent/bioaccumulative/toxic) and vPvB (very persistent/very bioaccumulative). Self classification

12.6. Endocrine disrupting properties

The substance is not identified to have endocrine disrupting properties according to Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 nor is included in the Candidate List of substances of very high concern according to EU REACH Article 59 for having endocrine disrupting properties.

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 12.12.2023

Version: 2.0

Date / Previous version: 02.07.2021

Previous version: 1.0

Product: **METHOXYPROPYLACETATE**

(ID no. 30034751/SDS_GEN_ES/EN)

Date of print 19.10.2025

12.7. Other adverse effects

The substance is not listed in Regulation (EC) 1005/2009 on substances that deplete the ozone layer.

12.8. Additional information

Adsorbable organically-bound halogen (AOX):
This product contains no organically-bound halogen.

SECTION 13: Disposal Considerations

13.1. Waste treatment methods

Must be disposed of or incinerated in accordance with local regulations.

Contaminated packaging:

Contaminated packaging should be emptied as far as possible; then it can be passed on for recycling after being thoroughly cleaned.

SECTION 14: Transport Information

Land transport

ADR

UN number or ID number: UN1993

UN proper shipping name: FLAMMABLE LIQUID, N.O.S. (2-METHOXY-1-METHYLETHYL ACETATE)

Transport hazard class(es): 3

Packing group: III

Environmental hazards: no

Special precautions for user: Tunnel code: D/E

RID

UN number or ID number: UN1993

UN proper shipping name: FLAMMABLE LIQUID, N.O.S. (2-METHOXY-1-METHYLETHYL ACETATE)

Transport hazard class(es): 3

Packing group: III

Environmental hazards: no

Special precautions for user: None known

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 12.12.2023

Version: 2.0

Date / Previous version: 02.07.2021

Previous version: 1.0

Product: **METHOXYPROPYLACETATE**

(ID no. 30034751/SDS_GEN_ES/EN)

Date of print 19.10.2025

user:

Inland waterway transport

ADN

UN number or ID number: UN1993

UN proper shipping name: FLAMMABLE LIQUID, N.O.S. (2-METHOXY-1-METHYLETHYL ACETATE)

Transport hazard class(es): 3

Packing group: III

Environmental hazards: no

Special precautions for user: None known

Transport in inland waterway vessel

UN number or ID number: UN1993

UN proper shipping name: FLAMMABLE LIQUID, N.O.S. (2-METHOXY-1-METHYLETHYL ACETATE)

Transport hazard class(es): 3

Packing group: III

Environmental hazards: no

Type of inland waterway vessel: N

Cargo tank design: 3

Cargo tank type: 2

Sea transport

IMDG

UN number or ID number: UN 1993

UN proper shipping name: FLAMMABLE LIQUID, N.O.S. (2-METHOXY-1-METHYLETHYL ACETATE)

Transport hazard class(es): 3

Packing group: III

Environmental hazards: no

Marine pollutant: NO

Special precautions for user: EmS: F-E; S-E

Air transport

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 12.12.2023

Version: 2.0

Date / Previous version: 02.07.2021

Previous version: 1.0

Product: **METHOXYPROPYLACETATE**

(ID no. 30034751/SDS_GEN_ES/EN)

Date of print 19.10.2025

IATA/ICAO

UN number or ID number: UN 1993
UN proper shipping name: FLAMMABLE LIQUID, N.O.S. (2-METHOXY-1-METHYLETHYL ACETATE)

Transport hazard class(es): 3
Packing group: III
Environmental hazards: No Mark as dangerous for the environment is needed
Special precautions for user: None known

14.1. UN number or ID number

See corresponding entries for "UN number or ID number" for the respective regulations in the tables above.

14.2. UN proper shipping name

See corresponding entries for "UN proper shipping name" for the respective regulations in the tables above.

14.3. Transport hazard class(es)

See corresponding entries for "Transport hazard class(es)" for the respective regulations in the tables above.

14.4. Packing group

See corresponding entries for "Packing group" for the respective regulations in the tables above.

14.5. Environmental hazards

See corresponding entries for "Environmental hazards" for the respective regulations in the tables above.

14.6. Special precautions for user

See corresponding entries for "Special precautions for user" for the respective regulations in the tables above.

14.7. Maritime transport in bulk according to IMO instruments

Regulation: IBC-Code
Product name: Propylene glycol methyl ether acetate
Pollution category: Z
Ship Type: 3

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 12.12.2023

Version: 2.0

Date / Previous version: 02.07.2021

Previous version: 1.0

Product: **METHOXYPROPYLACETATE**

(ID no. 30034751/SDS_GEN_ES/EN)

Date of print 19.10.2025

SECTION 15: Regulatory Information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Prohibitions, Restrictions and Authorizations

Annex XVII of Regulation (EC) No 1907/2006: Number on List: 3, 40

Directive 2012/18/EU - Control of Major Accident Hazards involving dangerous substances (EU):

List entry in regulation: P5a

List entry in regulation: P5b

List entry in regulation: P5c

If other regulatory information applies that is not already provided elsewhere in this safety data sheet, then it is described in this subsection.

15.2. Chemical Safety Assessment

Chemical Safety Assessment performed

SECTION 16: Other Information

Assessment of the hazard classes according to UN GHS criteria (most recent version)

Flam. Liq. 3

STOT SE 3 (May cause drowsiness and dizziness.)

Full text of the classifications, including the hazard classes and the hazard statements, if mentioned in section 2 or 3:

Flam. Liq.

Flammable liquids

STOT SE

Specific target organ toxicity — single exposure

Repr.

Reproductive toxicity

H226

Flammable liquid and vapour.

H336

May cause drowsiness or dizziness.

H335

May cause respiratory irritation.

H360D

May damage the unborn child.

Abbreviations

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road.
 ADN = The European Agreement concerning the International Carriage of Dangerous Goods by Inland waterways. ATE = Acute Toxicity Estimates. CAO = Cargo Aircraft Only. CAS = Chemical Abstract Service. CLP = Classification, Labelling and Packaging of substances and mixtures. DIN = German national organization for standardization. DNEL = Derived No Effect Level. EC50 = Effective concentration median for 50% of the population. EC = European Community. EN = European Standards. IARC = International Agency for Research on Cancer. IATA = International Air Transport Association. IBC-Code = Intermediate Bulk Container code. IMDG = International Maritime Dangerous Goods Code. ISO = International Organization for Standardization. STEL = Short-Term Exposure Limit. LC50 = Lethal concentration median for 50% of the population. LD50 = Lethal dose median for 50% of the population.

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 12.12.2023

Version: 2.0

Date / Previous version: 02.07.2021

Previous version: 1.0

Product: **METHOXYPROPYLACETATE**

(ID no. 30034751/SDS_GEN_ES/EN)

Date of print 19.10.2025

TLV = Threshold Limit Value. MARPOL = The International Convention for the Prevention of Pollution from Ships. NEN = Dutch Norm. NOEC = No Observed Effect Concentration. OEL = Occupational Exposure Limit. OECD = Organization for Economic Cooperation and Development. PBT = Persistent, Bioaccumulative and Toxic. PNEC = Predicted No Effect Level. PPM = Parts per million. RID = The European Agreement concerning the International Carriage of Dangerous Goods by Rail. TWA = Time Weight Average. UN-number = UN number at transport. vPvB = very Persistent and very Bioaccumulative.

The data contained in this safety data sheet are based on our current knowledge and experience and describe the product only with regard to safety requirements. This safety data sheet is neither a Certificate of Analysis (CoA) nor technical data sheet and shall not be mistaken for a specification agreement. Identified uses in this safety data sheet do neither represent an agreement on the corresponding contractual quality of the substance/mixture nor a contractually designated use. It is the responsibility of the recipient of the product to ensure any proprietary rights and existing laws and legislation are observed.

Vertical lines in the left hand margin indicate an amendment from the previous version.

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 12.12.2023

Version: 2.0

Date / Previous version: 02.07.2021

Previous version: 1.0

Product: **METHOXYPROPYLACETATE**

(ID no. 30034751/SDS_GEN_ES/EN)

Date of print 19.10.2025

Annex: Exposure Scenarios

Index

1. Manufacture of substance

ERC1; PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC9, PROC15, PROC28

2. Use as a Process chemical

ERC4; PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC15, PROC28

3. Formulation & (re)packing of substances and mixtures

ERC2; PROC1, PROC2, PROC3, PROC4, PROC5, PROC8a, PROC8b, PROC9, PROC14, PROC28

4. Use in Coatings, (use in industrial settings)

ERC4; PROC1, PROC2, PROC3, PROC4, PROC5, PROC7, PROC8a, PROC8b, PROC9, PROC10, PROC13, PROC14, PROC15, PROC28

5. Use in Coatings, (use in professional settings)

ERC8a, ERC8d; PROC1, PROC2, PROC3, PROC4, PROC5, PROC8a, PROC8b, PROC9, PROC10, PROC11, PROC13, PROC14, PROC15, PROC19, PROC28

6. Use in Coatings, (consumer use)

ERC8a, ERC8d; PC9a, PC18

7. Cleaning agents, (use in industrial settings)

ERC4; PROC1, PROC2, PROC3, PROC4, PROC7, PROC8a, PROC8b, PROC10, PROC13, PROC28

8. Cleaning agents, (use in professional settings)

ERC8a, ERC8d; PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC10, PROC11, PROC13, PROC19

9. Cleaning agents, (consumer use)

ERC8a, ERC8d; PC35

10. Use in Agrochemicals, (use in professional settings)

ERC8a, ERC8d; PROC1, PROC2, PROC4, PROC8a, PROC8b, PROC11, PROC13, PROC28

11. Use in Agrochemicals, (consumer use)

ERC8a, ERC8d; PC27

12. Use in Printing inks, (use in industrial settings)

ERC4; PROC1, PROC2, PROC3, PROC4, PROC5, PROC7, PROC8a, PROC8b, PROC9, PROC10, PROC13, PROC15, PROC28

13. Use in Coatings, (coil), (use in industrial settings)

ERC4; PROC1, PROC2, PROC3, PROC4, PROC5, PROC7, PROC8a, PROC8b, PROC9, PROC10, PROC13, PROC15, PROC28

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 12.12.2023

Version: 2.0

Date / Previous version: 02.07.2021

Previous version: 1.0

Product: **METHOXYPROPYLACETATE**

(ID no. 30034751/SDS_GEN_ES/EN)

Date of print 19.10.2025

1. Short title of exposure scenario

Manufacture of substance

ERC1; PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC9, PROC15, PROC28

Control of exposure and risk management measures

Contributing exposure scenario	
Use descriptors covered	ESVOC SpERC 1.1.o.v2
Operational conditions	
Annual amount used in the EU	25.000.000 kg
Minimum emission days per year	300
Emission factor air	1 %
Emission factor water	1 %
Emission factor soil	0,01 %
Receive Surf. Water (Flow Rate).	43.541 m3/min
Dilution factor river	187,67
Dilution factor coast	100
Risk Management Measures	
Soil treatment measures considered suitable are, e.g.	No application of sludge to soil
Type of STP	Municipal STP
Assumed sewage treatment plant flow (m3/d)	335.890 m3/d
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Environment
Risk Characterization Ratio (RCR)	0,134997
	Risk from environmental exposure is driven by soil.
Maximum amount of safe use	617.299,9 kg/d
Risk from environmental exposure is driven by soil.	

Contributing exposure scenario	
Use descriptors covered	PROC1: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions. Use domain: industrial
Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 100 %

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 12.12.2023

Version: 2.0

Date / Previous version: 02.07.2021

Previous version: 1.0

Product: **METHOXYPROPYLACETATE**

(ID no. 30034751/SDS_GEN_ES/EN)

Date of print 19.10.2025

Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	0,0343 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,000043
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	0,0551 mg/m ³
Risk Characterization Ratio (RCR)	0,0002
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC2: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions Use domain: industrial
Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	1,3714 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,001723
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	27,5312 mg/m ³
Risk Characterization Ratio (RCR)	0,100114
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 12.12.2023

Version: 2.0

Date / Previous version: 02.07.2021

Previous version: 1.0

Product: **METHOXYPROPYLACETATE**

(ID no. 30034751/SDS_GEN_ES/EN)

Date of print 19.10.2025

For scaling see: <http://www.ecetoc.org/tra>

Contributing exposure scenario	
Use descriptors covered	PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition Use domain: industrial
Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	0,6857 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,000861
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	55,0625 mg/m ³
Risk Characterization Ratio (RCR)	0,200227
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC4: Chemical production where opportunity for exposure arises Use domain: industrial
Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 12.12.2023

Version: 2.0

Date / Previous version: 02.07.2021

Previous version: 1.0

Product: **METHOXYPROPYLACETATE**

(ID no. 30034751/SDS_GEN_ES/EN)

Date of print 19.10.2025

Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	6,8571 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,008615
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	110,125 mg/m ³
Risk Characterization Ratio (RCR)	0,400455
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC8a: Transfer of substance or mixture (charging and discharging) at non-dedicated facilities Use domain: industrial
Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.

Risk Management Measures	
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	13,7143 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,017229
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	192,7187 mg/m ³
Risk Characterization Ratio (RCR)	0,700795
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC8b: Transfer of substance or mixture (charging and discharging) at dedicated facilities

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 12.12.2023

Version: 2.0

Date / Previous version: 02.07.2021

Previous version: 1.0

Product: **METHOXYPROPYLACETATE**

(ID no. 30034751/SDS_GEN_ES/EN)

Date of print 19.10.2025

	Use domain: industrial
Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	13,7143 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,017229
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	137,6562 mg/m ³
Risk Characterization Ratio (RCR)	0,500568
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing). Use domain: industrial
Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Risk Management Measures	
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 12.12.2023

Version: 2.0

Date / Previous version: 02.07.2021

Previous version: 1.0

Product: **METHOXYPROPYLACETATE**

(ID no. 30034751/SDS_GEN_ES/EN)

Date of print 19.10.2025

Exposure estimate	6,8571 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,008615
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	192,7187 mg/m ³
Risk Characterization Ratio (RCR)	0,700795
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC15: Use a laboratory reagent. Use domain: industrial
Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	0,3429 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,000431
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	55,0625 mg/m ³
Risk Characterization Ratio (RCR)	0,200227
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC28: Manual maintenance (cleaning and repair) of machinery covered by PROC8a

2. Short title of exposure scenario

Use as a Process chemical

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 12.12.2023

Version: 2.0

Date / Previous version: 02.07.2021

Previous version: 1.0

Product: **METHOXYPROPYLACETATE**

(ID no. 30034751/SDS_GEN_ES/EN)

Date of print 19.10.2025

ERC4; PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC15, PROC28

Control of exposure and risk management measures

Contributing exposure scenario	
Use descriptors covered	ESVOC SpERC 4.23.v1: ESVOC SpERC 4.23.v1
Operational conditions	
Annual amount used in the EU	660.000 kg
Minimum emission days per year	300
Emission factor air	0,2 %
Emission factor water	1 %
Emission factor soil	0,01 %
Receive Surf. Water (Flow Rate).	18.000 m3/d
Dilution factor river	10
Dilution factor coast	100
Risk Management Measures	
Type of STP	Municipal STP
Assumed sewage treatment plant flow (m3/d)	2.000 m3/d
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Environment
Risk Characterization Ratio (RCR)	0,433591
	Risk from environmental exposure is driven by soil.
Maximum amount of safe use	5.073,9 kg/d
Risk from environmental exposure is driven by soil.	

Contributing exposure scenario	
Use descriptors covered	PROC1: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions. Use domain: industrial
Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	502 Pa

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 12.12.2023

Version: 2.0

Date / Previous version: 02.07.2021

Previous version: 1.0

Product: **METHOXYPROPYLACETATE**

(ID no. 30034751/SDS_GEN_ES/EN)

Date of print 19.10.2025

Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	0,0343 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,000043
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	0,0551 mg/m ³
Risk Characterization Ratio (RCR)	0,0002
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC2: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions Use domain: industrial
Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	1,3714 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,001723
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	27,5312 mg/m ³
Risk Characterization Ratio (RCR)	0,100114
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC3: Manufacture or formulation in the chemical

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 12.12.2023

Version: 2.0

Date / Previous version: 02.07.2021

Previous version: 1.0

Product: **METHOXYPROPYLACETATE**

(ID no. 30034751/SDS_GEN_ES/EN)

Date of print 19.10.2025

	industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition Use domain: industrial
Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	0,6857 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,000861
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	55,0625 mg/m ³
Risk Characterization Ratio (RCR)	0,200227
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition Use domain: industrial
Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 12.12.2023

Version: 2.0

Date / Previous version: 02.07.2021

Previous version: 1.0

Product: **METHOXYPROPYLACETATE**

(ID no. 30034751/SDS_GEN_ES/EN)

Date of print 19.10.2025

	Worker - dermal, long-term - systemic
Exposure estimate	0,6857 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,000861
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	55,0625 mg/m ³
Risk Characterization Ratio (RCR)	0,200227
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC4: Chemical production where opportunity for exposure arises Use domain: industrial
Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	6,8571 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,008615
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	110,125 mg/m ³
Risk Characterization Ratio (RCR)	0,400455
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC8a: Transfer of substance or mixture (charging and discharging) at non-dedicated facilities Use domain: industrial
Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 100 %

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 12.12.2023

Version: 2.0

Date / Previous version: 02.07.2021

Previous version: 1.0

Product: **METHOXYPROPYLACETATE**

(ID no. 30034751/SDS_GEN_ES/EN)

Date of print 19.10.2025

Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Risk Management Measures	
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	13,7143 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,017229
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	192,7187 mg/m ³
Risk Characterization Ratio (RCR)	0,700795
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC8b: Transfer of substance or mixture (charging and discharging) at dedicated facilities Use domain: industrial
Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	13,7143 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,017229
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	137,6562 mg/m ³
Risk Characterization Ratio (RCR)	0,500568

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 12.12.2023

Version: 2.0

Date / Previous version: 02.07.2021

Previous version: 1.0

Product: **METHOXYPROPYLACETATE**

(ID no. 30034751/SDS_GEN_ES/EN)

Date of print 19.10.2025

Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC15: Use a laboratory reagent. Use domain: industrial
Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Assumes activities are at ambient temperature.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	0,3429 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,000431
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	55,0625 mg/m ³
Risk Characterization Ratio (RCR)	0,200227
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC28: Manual maintenance (cleaning and repair) of machinery covered by PROC8a

3. Short title of exposure scenario

Formulation & (re)packing of substances and mixtures

ERC2; PROC1, PROC2, PROC3, PROC4, PROC5, PROC8a, PROC8b, PROC9, PROC14, PROC28

Control of exposure and risk management measures

Contributing exposure scenario	
Use descriptors covered	CEPE SPERC 2.1a.v2

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 12.12.2023

Version: 2.0

Date / Previous version: 02.07.2021

Previous version: 1.0

Product: **METHOXYPROPYLACETATE**

(ID no. 30034751/SDS_GEN_ES/EN)

Date of print 19.10.2025

Operational conditions	
Annual amount used in the EU	25.000.000 kg
Minimum emission days per year	225
Emission factor air	1,8 %
Emission factor water	0 %
Emission factor soil	0 %
Receive Surf. Water (Flow Rate).	18.000 m3/d
Dilution factor river	10
Dilution factor coast	100
Risk Management Measures	
Type of STP	Municipal STP
Assumed sewage treatment plant flow (m3/d)	2.000 m3/d
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Environment
Risk Characterization Ratio (RCR)	0,226704
	Risk from environmental exposure is driven by soil.
Maximum amount of safe use	490.115,3 kg/d
Risk from environmental exposure is driven by soil.	
Contributing exposure scenario	
Use descriptors covered	PROC1: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions. Use domain: industrial
Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 12.12.2023

Version: 2.0

Date / Previous version: 02.07.2021

Previous version: 1.0

Product: **METHOXYPROPYLACETATE**

(ID no. 30034751/SDS_GEN_ES/EN)

Date of print 19.10.2025

	Worker - dermal, long-term - systemic
Exposure estimate	0,0343 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,000043
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	0,0551 mg/m ³
Risk Characterization Ratio (RCR)	0,0002
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC2: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions Use domain: industrial
Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	1,3714 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,001723
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	27,5312 mg/m ³
Risk Characterization Ratio (RCR)	0,100114
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition Use domain: industrial
Operational conditions	

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 12.12.2023

Version: 2.0

Date / Previous version: 02.07.2021

Previous version: 1.0

Product: **METHOXYPROPYLACETATE**

(ID no. 30034751/SDS_GEN_ES/EN)

Date of print 19.10.2025

Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	0,6857 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,000861
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	55,0625 mg/m ³
Risk Characterization Ratio (RCR)	0,200227
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC4: Chemical production where opportunity for exposure arises Use domain: industrial
Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	6,8571 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,008615
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	110,125 mg/m ³
Risk Characterization Ratio (RCR)	0,400455
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 12.12.2023

Version: 2.0

Date / Previous version: 02.07.2021

Previous version: 1.0

Product: **METHOXYPROPYLACETATE**

(ID no. 30034751/SDS_GEN_ES/EN)

Date of print 19.10.2025

Guidance to Downstream Users

For scaling see: <http://www.ecetoc.org/tra>

Contributing exposure scenario

Use descriptors covered	PROC5: Mixing or blending in batch processes Use domain: industrial
--------------------------------	--

Operational conditions

Concentration of the substance	2-methoxy-1-methylethyl acetate Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.

Risk Management Measures

Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %
---	---------------------

Exposure estimate and reference to its source

Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	13,7143 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,017229
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	192,7187 mg/m ³
Risk Characterization Ratio (RCR)	0,700795
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker

Guidance to Downstream Users

For scaling see: <http://www.ecetoc.org/tra>

Contributing exposure scenario

Use descriptors covered	PROC8a: Transfer of substance or mixture (charging and discharging) at non-dedicated facilities Use domain: industrial
--------------------------------	---

Operational conditions

Concentration of the substance	2-methoxy-1-methylethyl acetate Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	480 min 5 days per week

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 12.12.2023

Version: 2.0

Date / Previous version: 02.07.2021

Previous version: 1.0

Product: **METHOXYPROPYLACETATE**

(ID no. 30034751/SDS_GEN_ES/EN)

Date of print 19.10.2025

Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Risk Management Measures	
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	13,7143 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,017229
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	192,7187 mg/m ³
Risk Characterization Ratio (RCR)	0,700795
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC8b: Transfer of substance or mixture (charging and discharging) at dedicated facilities Use domain: industrial
Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	13,7143 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,017229
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	137,6562 mg/m ³
Risk Characterization Ratio (RCR)	0,500568
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 12.12.2023

Version: 2.0

Date / Previous version: 02.07.2021

Previous version: 1.0

Product: **METHOXYPROPYLACETATE**

(ID no. 30034751/SDS_GEN_ES/EN)

Date of print 19.10.2025

Use descriptors covered	PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing). Use domain: industrial
Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Risk Management Measures	
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	6,8571 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,008615
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	192,7187 mg/m ³
Risk Characterization Ratio (RCR)	0,700795
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC14: Tableting, compression, extrusion, pelletisation, granulation Use domain: industrial
Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Risk Management Measures	

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 12.12.2023

Version: 2.0

Date / Previous version: 02.07.2021

Previous version: 1.0

Product: **METHOXYPROPYLACETATE**

(ID no. 30034751/SDS_GEN_ES/EN)

Date of print 19.10.2025

Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	3,4286 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,004307
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	192,7187 mg/m ³
Risk Characterization Ratio (RCR)	0,700795
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC28: Manual maintenance (cleaning and repair) of machinery covered by PROC8a

4. Short title of exposure scenario

Use in Coatings, (use in industrial settings)

ERC4; PROC1, PROC2, PROC3, PROC4, PROC5, PROC7, PROC8a, PROC8b, PROC9, PROC10, PROC13, PROC14, PROC15, PROC28

Control of exposure and risk management measures

Contributing exposure scenario	
Use descriptors covered	ESVOC SpERC 4.4a.v1: ESVOC SpERC 4.4a.v1
Operational conditions	
Annual amount used in the EU	5.500.000 kg
Minimum emission days per year	300
Emission factor air	98 %
Emission factor water	2 %
Emission factor soil	0 %
Receive Surf. Water (Flow Rate).	18.000 m3/d
Dilution factor river	10

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 12.12.2023

Version: 2.0

Date / Previous version: 02.07.2021

Previous version: 1.0

Product: **METHOXYPROPYLACETATE**

(ID no. 30034751/SDS_GEN_ES/EN)

Date of print 19.10.2025

Dilution factor coast	100
Risk Management Measures	
Air treatment measures considered suitable are, e.g.	Wet scrubber - for dusts, Filtration, Waste gas treatment by thermal oxidation, Adsorption
Wastewater treatment measures considered suitable are, e.g.	Acclimated biological treatment, Distillation
Type of STP	Municipal STP
Assumed sewage treatment plant flow (m3/d)	2.000 m3/d
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Environment
Risk Characterization Ratio (RCR)	0,955519
	Risk from environmental exposure is driven by soil.
Maximum amount of safe use	1.918,7 kg/d
Risk from environmental exposure is driven by soil.	
Contributing exposure scenario	
Use descriptors covered	PROC1: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions. Use domain: industrial
Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	0,0343 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,000043
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	0,0551 mg/m ³
Risk Characterization Ratio (RCR)	0,0002
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 12.12.2023

Version: 2.0

Date / Previous version: 02.07.2021

Previous version: 1.0

Product: **METHOXYPROPYLACETATE**

(ID no. 30034751/SDS_GEN_ES/EN)

Date of print 19.10.2025

For scaling see: <http://www.ecetoc.org/tra>

Contributing exposure scenario	
Use descriptors covered	PROC2: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions Use domain: industrial
Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	1,3714 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,001723
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	27,5312 mg/m ³
Risk Characterization Ratio (RCR)	0,100114
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition Use domain: industrial
Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 12.12.2023

Version: 2.0

Date / Previous version: 02.07.2021

Previous version: 1.0

Product: **METHOXYPROPYLACETATE**

(ID no. 30034751/SDS_GEN_ES/EN)

Date of print 19.10.2025

	Assumes activities are at ambient temperature.
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	0,6857 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,000861
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	55,0625 mg/m ³
Risk Characterization Ratio (RCR)	0,200227
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC4: Chemical production where opportunity for exposure arises Use domain: industrial
Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	6,8571 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,008615
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	110,125 mg/m ³
Risk Characterization Ratio (RCR)	0,400455
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC5: Mixing or blending in batch processes Use domain: industrial
Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 12.12.2023

Version: 2.0

Date / Previous version: 02.07.2021

Previous version: 1.0

Product: **METHOXYPROPYLACETATE**

(ID no. 30034751/SDS_GEN_ES/EN)

Date of print 19.10.2025

	Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Risk Management Measures	
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	13,7143 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,017229
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	192,7187 mg/m ³
Risk Characterization Ratio (RCR)	0,700795
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC7: Industrial spraying Use domain: industrial
Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: $\geq 0\%$ - $\leq 90\%$
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	240 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
	Any sized room
Application rate	< 3 l/min
Risk Management Measures	
Wear suitable respiratory protection.	Effectiveness: 90 %
Surface spraying with no or low compressed air use.	
Provide extract ventilation to points where emissions occur (LEV).	

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 12.12.2023

Version: 2.0

Date / Previous version: 02.07.2021

Previous version: 1.0

Product: **METHOXYPROPYLACETATE**

(ID no. 30034751/SDS_GEN_ES/EN)

Date of print 19.10.2025

Ensure that general housekeeping is in place	
Provide a good standard of controlled ventilation (10 to 15 air changes per hour)	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, worker, modified version, The concentration of the substance has been considered using a linear approach.
	Worker - dermal, long-term - systemic
Exposure estimate	23,1429 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,029074
Assessment method	EASY TRA v5.2, Advanced REACH Tool v1.5
	Worker - inhalation, long-term - systemic
Exposure estimate	190 mg/m ³
Risk Characterization Ratio (RCR)	0,690909
Assessment method	EASY TRA v5.2, Advanced REACH Tool v1.5
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra For scaling see: http://www.advancedreachtool.com Please note that a modified version has been used (see exposure estimates)	

Contributing exposure scenario	
Use descriptors covered	PROC7: Industrial spraying Use domain: industrial
	Surface spraying of liquids
Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Application rate	< 3 l/min
Risk Management Measures	
Ensure that general housekeeping is in place	
Provide a good standard of controlled ventilation (10 to 15 air changes per hour)	
Ensure that the task is being carried out outside the breathing zone of a worker (distance head-product greater than 1m).	

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 12.12.2023

Version: 2.0

Date / Previous version: 02.07.2021

Previous version: 1.0

Product: **METHOXYPROPYLACETATE**

(ID no. 30034751/SDS_GEN_ES/EN)

Date of print 19.10.2025

Ensure that the worker is in a separated (control) room with independent air supply	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	42,8571 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,053841
Assessment method	EASY TRA v5.2, Advanced REACH Tool v1.5
	Worker - inhalation, long-term - systemic
Exposure estimate	180 mg/m ³
Risk Characterization Ratio (RCR)	0,654545
Assessment method	EASY TRA v5.2, Advanced REACH Tool v1.5
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra For scaling see: http://www.advancedreachtool.com	
Contributing exposure scenario	
Use descriptors covered	PROC8a: Transfer of substance or mixture (charging and discharging) at non-dedicated facilities Use domain: industrial
Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Risk Management Measures	
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	13,7143 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,017229
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	192,7187 mg/m ³
Risk Characterization Ratio (RCR)	0,700795
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 12.12.2023

Version: 2.0

Date / Previous version: 02.07.2021

Previous version: 1.0

Product: **METHOXYPROPYLACETATE**

(ID no. 30034751/SDS_GEN_ES/EN)

Date of print 19.10.2025

Contributing exposure scenario	
Use descriptors covered	PROC8b: Transfer of substance or mixture (charging and discharging) at dedicated facilities Use domain: industrial
Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	13,7143 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,017229
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	137,6562 mg/m ³
Risk Characterization Ratio (RCR)	0,500568
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing). Use domain: industrial
Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Risk Management Measures	
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 12.12.2023

Version: 2.0

Date / Previous version: 02.07.2021

Previous version: 1.0

Product: **METHOXYPROPYLACETATE**

(ID no. 30034751/SDS_GEN_ES/EN)

Date of print 19.10.2025

Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	6,8571 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,008615
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	192,7187 mg/m ³
Risk Characterization Ratio (RCR)	0,700795
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC10: Roller application or brushing Use domain: industrial
Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.

Risk Management Measures	
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	27,4286 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,034458
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	192,7187 mg/m ³
Risk Characterization Ratio (RCR)	0,700795
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC13: Treatment of articles by dipping and pouring. Use domain: industrial

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 12.12.2023

Version: 2.0

Date / Previous version: 02.07.2021

Previous version: 1.0

Product: **METHOXYPROPYLACETATE**

(ID no. 30034751/SDS_GEN_ES/EN)

Date of print 19.10.2025

Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Risk Management Measures	
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	13,7143 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,017229
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	192,7187 mg/m ³
Risk Characterization Ratio (RCR)	0,700795
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC14: Tableting, compression, extrusion, pelletisation, granulation Use domain: industrial
Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Risk Management Measures	
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %
Exposure estimate and reference to its source	

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 12.12.2023

Version: 2.0

Date / Previous version: 02.07.2021

Previous version: 1.0

Product: **METHOXYPROPYLACETATE**

(ID no. 30034751/SDS_GEN_ES/EN)

Date of print 19.10.2025

Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	3,4286 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,004307
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	192,7187 mg/m ³
Risk Characterization Ratio (RCR)	0,700795
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC15: Use a laboratory reagent. Use domain: industrial
Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	0,3429 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,000431
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	55,0625 mg/m ³
Risk Characterization Ratio (RCR)	0,200227
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC28: Manual maintenance (cleaning and repair) of machinery covered by PROC8a

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 12.12.2023

Version: 2.0

Date / Previous version: 02.07.2021

Previous version: 1.0

Product: **METHOXYPROPYLACETATE**

(ID no. 30034751/SDS_GEN_ES/EN)

Date of print 19.10.2025

5. Short title of exposure scenario

Use in Coatings, (use in professional settings)

ERC8a, ERC8d; PROC1, PROC2, PROC3, PROC4, PROC5, PROC8a, PROC8b, PROC9, PROC10, PROC11, PROC13, PROC14, PROC15, PROC19, PROC28

Control of exposure and risk management measures

Contributing exposure scenario	
Use descriptors covered	ESVOC SpERC 8.3b.v2
Operational conditions	
Annual amount used in the EU	25.000.000 kg
Minimum emission days per year	365
Emission factor air	98 %
Emission factor water	1 %
Emission factor soil	1 %
Receive Surf. Water (Flow Rate).	18.000 m3/d
Dilution factor river	10
Dilution factor coast	100
Risk Management Measures	
Type of STP	Municipal STP
Assumed sewage treatment plant flow (m3/d)	2.000 m3/d
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Environment
Risk Characterization Ratio (RCR)	0,022771
	Risk from environmental exposure is driven by soil.
Maximum amount of safe use	601,6 kg/d
Risk from environmental exposure is driven by soil.	

Contributing exposure scenario	
Use descriptors covered	ESVOC SpERC 8.3b.v2
Operational conditions	
Annual amount used in the EU	25.000.000 kg
Minimum emission days per year	365
Emission factor air	98 %

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 12.12.2023

Version: 2.0

Date / Previous version: 02.07.2021

Previous version: 1.0

Product: **METHOXYPROPYLACETATE**

(ID no. 30034751/SDS_GEN_ES/EN)

Date of print 19.10.2025

Emission factor water	1 %
Emission factor soil	1 %
Receive Surf. Water (Flow Rate).	18.000 m3/d
Dilution factor river	10
Dilution factor coast	100
Risk Management Measures	
Type of STP	Municipal STP
Assumed sewage treatment plant flow (m3/d)	2.000 m3/d
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Environment
Risk Characterization Ratio (RCR)	0,022771
	Risk from environmental exposure is driven by soil.
Maximum amount of safe use	601,6 kg/d
Risk from environmental exposure is driven by soil.	

Contributing exposure scenario	
Use descriptors covered	PROC1: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions. Use domain: professional
Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	0,0343 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,000043
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	0,0551 mg/m ³
Risk Characterization Ratio (RCR)	0,0002
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 12.12.2023

Version: 2.0

Date / Previous version: 02.07.2021

Previous version: 1.0

Product: **METHOXYPROPYLACETATE**

(ID no. 30034751/SDS_GEN_ES/EN)

Date of print 19.10.2025

Guidance to Downstream Users

For scaling see: <http://www.ecetoc.org/tra>

Contributing exposure scenario

Use descriptors covered	PROC2: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions Use domain: professional
--------------------------------	---

Operational conditions

Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.

Exposure estimate and reference to its source

Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	1,3714 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,001723
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	110,125 mg/m ³
Risk Characterization Ratio (RCR)	0,400455
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker

Guidance to Downstream Users

For scaling see: <http://www.ecetoc.org/tra>

Contributing exposure scenario

Use descriptors covered	PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition Use domain: professional
--------------------------------	---

Operational conditions

Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	480 min 5 days per week

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 12.12.2023

Version: 2.0

Date / Previous version: 02.07.2021

Previous version: 1.0

Product: **METHOXYPROPYLACETATE**

(ID no. 30034751/SDS_GEN_ES/EN)

Date of print 19.10.2025

Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	0,6857 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,000861
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	137,6562 mg/m ³
Risk Characterization Ratio (RCR)	0,500568
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC4: Chemical production where opportunity for exposure arises Use domain: professional
Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Outdoor
	Assumes activities are at ambient temperature.
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	6,8571 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,008615
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	192,7187 mg/m ³
Risk Characterization Ratio (RCR)	0,700795
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC4: Chemical production where opportunity for exposure arises Use domain: professional

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 12.12.2023

Version: 2.0

Date / Previous version: 02.07.2021

Previous version: 1.0

Product: **METHOXYPROPYLACETATE**

(ID no. 30034751/SDS_GEN_ES/EN)

Date of print 19.10.2025

Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Risk Management Measures	
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	6,8571 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,008615
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	192,7187 mg/m ³
Risk Characterization Ratio (RCR)	0,700795
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC5: Mixing or blending in batch processes Use domain: professional
Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Risk Management Measures	
Provide a good standard of general or controlled ventilation (5 to 10 air changes per hour)	Effectiveness: 70 %
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 12.12.2023

Version: 2.0

Date / Previous version: 02.07.2021

Previous version: 1.0

Product: **METHOXYPROPYLACETATE**

(ID no. 30034751/SDS_GEN_ES/EN)

Date of print 19.10.2025

	Worker - dermal, long-term - systemic
Exposure estimate	13,7143 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,017229
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	165,1875 mg/m ³
Risk Characterization Ratio (RCR)	0,600682
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC5: Mixing or blending in batch processes Use domain: professional
Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	240 min 5 days per week
Indoor/Outdoor	Outdoor
	Assumes activities are at ambient temperature.
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	8,2286 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,010337
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	231,2625 mg/m ³
Risk Characterization Ratio (RCR)	0,840955
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC8a: Transfer of substance or mixture (charging and discharging) at non-dedicated facilities Use domain: professional
Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 12.12.2023

Version: 2.0

Date / Previous version: 02.07.2021

Previous version: 1.0

Product: **METHOXYPROPYLACETATE**

(ID no. 30034751/SDS_GEN_ES/EN)

Date of print 19.10.2025

Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Risk Management Measures	
Provide a good standard of general or controlled ventilation (5 to 10 air changes per hour)	Effectiveness: 70 %
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	13,7143 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,017229
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	165,1875 mg/m ³
Risk Characterization Ratio (RCR)	0,600682
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC8b: Transfer of substance or mixture (charging and discharging) at dedicated facilities Use domain: professional
Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Risk Management Measures	
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	13,7143 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,017229
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 12.12.2023

Version: 2.0

Date / Previous version: 02.07.2021

Previous version: 1.0

Product: **METHOXYPROPYLACETATE**

(ID no. 30034751/SDS_GEN_ES/EN)

Date of print 19.10.2025

	Worker - inhalation, long-term - systemic
Exposure estimate	192,7187 mg/m ³
Risk Characterization Ratio (RCR)	0,700795
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing). Use domain: professional
Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Risk Management Measures	
Provide a good standard of general or controlled ventilation (5 to 10 air changes per hour)	Effectiveness: 70 %
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	6,8571 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,008615
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	165,1875 mg/m ³
Risk Characterization Ratio (RCR)	0,600682
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC10: Roller application or brushing Use domain: professional
Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 12.12.2023

Version: 2.0

Date / Previous version: 02.07.2021

Previous version: 1.0

Product: **METHOXYPROPYLACETATE**

(ID no. 30034751/SDS_GEN_ES/EN)

Date of print 19.10.2025

Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Risk Management Measures	
Provide a good standard of general or controlled ventilation (5 to 10 air changes per hour)	Effectiveness: 70 %
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	27,4286 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,034458
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	165,1875 mg/m ³
Risk Characterization Ratio (RCR)	0,600682
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC10: Roller application or brushing Use domain: professional
Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	240 min 5 days per week
Indoor/Outdoor	Outdoor
	Assumes activities are at ambient temperature.
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	16,4571 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,020675
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	231,2625 mg/m ³
Risk Characterization Ratio (RCR)	0,840955
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 12.12.2023

Version: 2.0

Date / Previous version: 02.07.2021

Previous version: 1.0

Product: **METHOXYPROPYLACETATE**

(ID no. 30034751/SDS_GEN_ES/EN)

Date of print 19.10.2025

For scaling see: <http://www.ecetoc.org/tra>

Contributing exposure scenario	
Use descriptors covered	PROC11: Non industrial spraying Use domain: professional
Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 90 %
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	240 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
	Any sized room
Application rate	< 3 l/min
Risk Management Measures	
Wear suitable respiratory protection.	Effectiveness: 90 %
Surface spraying with no or low compressed air use.	
Provide extract ventilation to points where emissions occur (LEV).	
Ensure that general housekeeping is in place	
Provide a good standard of controlled ventilation (10 to 15 air changes per hour)	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, worker, modified version, The concentration of the substance has been considered using a linear approach.
	Worker - dermal, long-term - systemic
Exposure estimate	57,8571 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,072685
Assessment method	EASY TRA v5.2, Advanced REACH Tool v1.5
	Worker - inhalation, long-term - systemic
Exposure estimate	190 mg/m ³
Risk Characterization Ratio (RCR)	0,690909
Assessment method	EASY TRA v5.2, Advanced REACH Tool v1.5
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra For scaling see: http://www.advancedreachtool.com Please note that a modified version has been used (see exposure estimates)	

Contributing exposure scenario	
Use descriptors covered	PROC11: Non industrial spraying Use domain: professional

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 12.12.2023

Version: 2.0

Date / Previous version: 02.07.2021

Previous version: 1.0

Product: **METHOXYPROPYLACETATE**

(ID no. 30034751/SDS_GEN_ES/EN)

Date of print 19.10.2025

Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: $\geq 0\%$ - $\leq 90\%$
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	240 min 5 days per week
Indoor/Outdoor	Outdoor
	Assumes activities are at ambient temperature.
Application rate	< 3 l/min
Risk Management Measures	
Wear suitable respiratory protection.	Effectiveness: 95 %
Surface spraying with no or low compressed air use.	
Ensure that general housekeeping is in place	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, worker, modified version, The concentration of the substance has been considered using a linear approach.
	Worker - dermal, long-term - systemic
Exposure estimate	57,8571 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,072685
Assessment method	EASY TRA v5.2, Advanced REACH Tool v1.5
	Worker - inhalation, long-term - systemic
Exposure estimate	190 mg/m ³
Risk Characterization Ratio (RCR)	0,690909
Assessment method	EASY TRA v5.2, Advanced REACH Tool v1.5
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra For scaling see: http://www.advancedreachtool.com Please note that a modified version has been used (see exposure estimates)	

Contributing exposure scenario	
Use descriptors covered	PROC13: Treatment of articles by dipping and pouring. Use domain: professional
Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 12.12.2023

Version: 2.0

Date / Previous version: 02.07.2021

Previous version: 1.0

Product: **METHOXYPROPYLACETATE**

(ID no. 30034751/SDS_GEN_ES/EN)

Date of print 19.10.2025

	Assumes activities are at ambient temperature.
Risk Management Measures	
Provide a good standard of general or controlled ventilation (5 to 10 air changes per hour)	Effectiveness: 70 %
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	13,7143 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,017229
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	165,1875 mg/m ³
Risk Characterization Ratio (RCR)	0,600682
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC13: Treatment of articles by dipping and pouring. Use domain: professional
Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	240 min 5 days per week
Indoor/Outdoor	Outdoor
	Assumes activities are at ambient temperature.
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	8,2286 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,010337
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	231,2625 mg/m ³
Risk Characterization Ratio (RCR)	0,840955
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC14: Tableting, compression, extrusion, pelletisation, granulation

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 12.12.2023

Version: 2.0

Date / Previous version: 02.07.2021

Previous version: 1.0

Product: **METHOXYPROPYLACETATE**

(ID no. 30034751/SDS_GEN_ES/EN)

Date of print 19.10.2025

	Use domain: professional
Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Risk Management Measures	
Provide a good standard of general or controlled ventilation (5 to 10 air changes per hour)	Effectiveness: 70 %
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	3,4286 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,004307
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	165,1875 mg/m ³
Risk Characterization Ratio (RCR)	0,600682
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC15: Use a laboratory reagent. Use domain: professional
Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	0,3429 mg/kg bw/day

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 12.12.2023

Version: 2.0

Date / Previous version: 02.07.2021

Previous version: 1.0

Product: **METHOXYPROPYLACETATE**

(ID no. 30034751/SDS_GEN_ES/EN)

Date of print 19.10.2025

Risk Characterization Ratio (RCR)	0,000431
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	55,0625 mg/m ³
Risk Characterization Ratio (RCR)	0,200227
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC19: Manual activities involving hand contact Use domain: professional
Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Risk Management Measures	
Wear suitable respiratory protection.	Effectiveness: 90 %
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	141,4286 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,177674
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	55,0625 mg/m ³
Risk Characterization Ratio (RCR)	0,200227
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC19: Manual activities involving hand contact Use domain: professional
Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance	502 Pa

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 12.12.2023

Version: 2.0

Date / Previous version: 02.07.2021

Previous version: 1.0

Product: **METHOXYPROPYLACETATE**

(ID no. 30034751/SDS_GEN_ES/EN)

Date of print 19.10.2025

during use	
Duration and Frequency of activity	240 min 5 days per week
Indoor/Outdoor	Outdoor
	Assumes activities are at ambient temperature.
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	84,8571 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,106604
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	231,2625 mg/m ³
Risk Characterization Ratio (RCR)	0,840955
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	
Contributing exposure scenario	
Use descriptors covered	PROC28: Manual maintenance (cleaning and repair) of machinery covered by PROC8a

6. Short title of exposure scenario

Use in Coatings, (consumer use)

ERC8a, ERC8d; PC9a, PC18

Control of exposure and risk management measures

Contributing exposure scenario	
Use descriptors covered	ESVOC SpERC 8.3c.v2
Operational conditions	
Annual amount used in the EU	5.280.000 kg
Minimum emission days per year	365
Emission factor air	98,5 %
Emission factor water	1 %
Emission factor soil	0,5 %
Receive Surf. Water (Flow Rate).	18.000 m3/d

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 12.12.2023

Version: 2.0

Date / Previous version: 02.07.2021

Previous version: 1.0

Product: **METHOXYPROPYLACETATE**

(ID no. 30034751/SDS_GEN_ES/EN)

Date of print 19.10.2025

Dilution factor river	10
Dilution factor coast	100
Risk Management Measures	
Type of STP	Municipal STP
Assumed sewage treatment plant flow (m3/d)	2.000 m3/d
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Environment
Risk Characterization Ratio (RCR)	0,020744
	Risk from environmental exposure is driven by soil.
Maximum amount of safe use	139,5 kg/d
	Risk from environmental exposure is driven by soil.

Contributing exposure scenario	
Use descriptors covered	ESVOC SpERC 8.3c.v2
Operational conditions	
Annual amount used in the EU	5.280.000 kg
Minimum emission days per year	365
Emission factor air	98,5 %
Emission factor water	1 %
Emission factor soil	0,5 %
Receive Surf. Water (Flow Rate).	18.000 m3/d
Dilution factor river	10
Dilution factor coast	100
Risk Management Measures	
Type of STP	Municipal STP
Assumed sewage treatment plant flow (m3/d)	2.000 m3/d
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Environment
Risk Characterization Ratio (RCR)	0,020744
	Risk from environmental exposure is driven by soil.
Maximum amount of safe use	139,5 kg/d
	Risk from environmental exposure is driven by soil.
Contributing exposure scenario	

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 12.12.2023

Version: 2.0

Date / Previous version: 02.07.2021

Previous version: 1.0

Product: **METHOXYPROPYLACETATE**

(ID no. 30034751/SDS_GEN_ES/EN)

Date of print 19.10.2025

Use descriptors covered	PC9a_2, PC15_2: Subcategory: Solvent rich, high solid, water borne paint
Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 10 %
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	Exposure duration: 2,2 h 2 uses per year
Room size	20 m3
Indoor/Outdoor	Indoor
Ventilation rate per hour	0,6
Exposed skin area	Palm of both hands (480 cm ²)
Uptake fraction dermal	100 %
Uptake fraction inhalation	100 %
	Amount per use 1.000 g Relevant for inhalative exposure estimates
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA, Consumer
	Consumer - dermal, long-term - systemic
Exposure estimate	0,0715 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,000223
Assessment method	EASY TRA v5.2, ECETOC TRA, Consumer
	Consumer - inhalation, long-term - systemic
Exposure estimate	21,5517 mg/m ³
Risk Characterization Ratio (RCR)	0,653083
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PC18: Ink and Toners.
Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 45 %
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	Exposure duration: 5 min Relevant for inhalative exposure estimates
Duration and Frequency of activity	Application duration: 5 min Relevant for inhalative exposure estimates
Duration and Frequency of activity	156 uses per year
Room size	1 m3

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 12.12.2023

Version: 2.0

Date / Previous version: 02.07.2021

Previous version: 1.0

Product: **METHOXYPROPYLACETATE**

(ID no. 30034751/SDS_GEN_ES/EN)

Date of print 19.10.2025

Ventilation rate per hour	1
Temperature (Application)	20 °C
body weight	61 kg
Uptake fraction dermal	100 % Relevant for dermal exposure estimates
	Relevant for dermal exposure estimates
	Amount per use 0,05 g Relevant for dermal exposure estimates
Release area	19 cm ²
	Release area is constant
Release duration	5 min
	Relevant for inhalative exposure estimates
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ConsExpo v4.1, Dermal model: instant application, Uptake model: Uptake fraction
	Consumer - dermal, long-term - systemic
Exposure estimate	0,1576 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,000493
	The calculation is based on the internal chronic dose.
Assessment method	EASY TRA v5.2, ConsExpo v4.1, Inhalation model: exposure to vapour - evaporation
	Consumer - inhalation, long-term - systemic
Exposure estimate	0,1517 mg/m ³
Risk Characterization Ratio (RCR)	0,004597
	The exposure calculation is based on the mean concentration per year.
Guidance to Downstream Users	
For scaling see: http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp	

7. Short title of exposure scenario

Cleaning agents, (use in industrial settings)

ERC4; PROC1, PROC2, PROC3, PROC4, PROC7, PROC8a, PROC8b, PROC10, PROC13, PROC28

Control of exposure and risk management measures

Contributing exposure scenario	
Use descriptors covered	ESVOC SpERC 4.6a.v1: ESVOC SpERC 4.6a.v1
Operational conditions	
Annual amount used in the EU	8.415.000 kg
Minimum emission days per year	20
Emission factor air	30 %

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 12.12.2023

Version: 2.0

Date / Previous version: 02.07.2021

Previous version: 1.0

Product: **METHOXYPROPYLACETATE**

(ID no. 30034751/SDS_GEN_ES/EN)

Date of print 19.10.2025

Emission factor water	0,01 %
Emission factor soil	0 %
Receive Surf. Water (Flow Rate).	18.000 m3/d
Dilution factor river	10
Dilution factor coast	100

Risk Management Measures

Air treatment measures considered suitable are, e.g.	Wet scrubber - for dusts, Waste gas treatment by thermal oxidation, Adsorption
Wastewater treatment measures considered suitable are, e.g.	Acclimated biological treatment, Distillation
Type of STP	Municipal STP
Assumed sewage treatment plant flow (m3/d)	2.000 m3/d

Exposure estimate and reference to its source

Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Environment
Risk Characterization Ratio (RCR)	0,043349
	Risk from environmental exposure is driven by soil.
Maximum amount of safe use	115.342 kg/d

Risk from environmental exposure is driven by soil.

Contributing exposure scenario

Use descriptors covered	PROC1: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions. Use domain: industrial
--------------------------------	--

Operational conditions

Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.

Exposure estimate and reference to its source

Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	0,0343 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,000043

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 12.12.2023

Version: 2.0

Date / Previous version: 02.07.2021

Previous version: 1.0

Product: **METHOXYPROPYLACETATE**

(ID no. 30034751/SDS_GEN_ES/EN)

Date of print 19.10.2025

Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	0,0551 mg/m ³
Risk Characterization Ratio (RCR)	0,0002
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC2: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions Use domain: industrial
Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	1,3714 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,001723
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	27,5312 mg/m ³
Risk Characterization Ratio (RCR)	0,100114
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition Use domain: industrial
Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 100 %

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 12.12.2023

Version: 2.0

Date / Previous version: 02.07.2021

Previous version: 1.0

Product: **METHOXYPROPYLACETATE**

(ID no. 30034751/SDS_GEN_ES/EN)

Date of print 19.10.2025

Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	0,6857 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,000861
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	55,0625 mg/m ³
Risk Characterization Ratio (RCR)	0,200227
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC4: Chemical production where opportunity for exposure arises Use domain: industrial
Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	6,8571 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,008615
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	110,125 mg/m ³
Risk Characterization Ratio (RCR)	0,400455
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 12.12.2023

Version: 2.0

Date / Previous version: 02.07.2021

Previous version: 1.0

Product: **METHOXYPROPYLACETATE**

(ID no. 30034751/SDS_GEN_ES/EN)

Date of print 19.10.2025

Contributing exposure scenario	
Use descriptors covered	PROC7: Industrial spraying Use domain: industrial
Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 90 %
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	240 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
	Any sized room
Application rate	< 3 l/min
Risk Management Measures	
Wear suitable respiratory protection.	Effectiveness: 90 %
Surface spraying with no or low compressed air use.	
Provide extract ventilation to points where emissions occur (LEV).	
Ensure that general housekeeping is in place	
Provide a good standard of controlled ventilation (10 to 15 air changes per hour)	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, worker, modified version, The concentration of the substance has been considered using a linear approach.
	Worker - dermal, long-term - systemic
Exposure estimate	23,1429 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,029074
Assessment method	EASY TRA v5.2, Advanced REACH Tool v1.5
	Worker - inhalation, long-term - systemic
Exposure estimate	190 mg/m ³
Risk Characterization Ratio (RCR)	0,690909
Assessment method	EASY TRA v5.2, Advanced REACH Tool v1.5
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra For scaling see: http://www.advancedreachtool.com Please note that a modified version has been used (see exposure estimates)	

Contributing exposure scenario	
Use descriptors covered	PROC8a: Transfer of substance or mixture (charging and discharging) at non-dedicated facilities Use domain: industrial

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 12.12.2023

Version: 2.0

Date / Previous version: 02.07.2021

Previous version: 1.0

Product: **METHOXYPROPYLACETATE**

(ID no. 30034751/SDS_GEN_ES/EN)

Date of print 19.10.2025

Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Risk Management Measures	
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	13,7143 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,017229
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	192,7187 mg/m ³
Risk Characterization Ratio (RCR)	0,700795
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC8b: Transfer of substance or mixture (charging and discharging) at dedicated facilities Use domain: industrial
Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	13,7143 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,017229

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 12.12.2023

Version: 2.0

Date / Previous version: 02.07.2021

Previous version: 1.0

Product: **METHOXYPROPYLACETATE**

(ID no. 30034751/SDS_GEN_ES/EN)

Date of print 19.10.2025

Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	137,6562 mg/m ³
Risk Characterization Ratio (RCR)	0,500568
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC10: Roller application or brushing Use domain: industrial
Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Risk Management Measures	
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	27,4286 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,034458
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	192,7187 mg/m ³
Risk Characterization Ratio (RCR)	0,700795
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC13: Treatment of articles by dipping and pouring. Use domain: industrial
Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 12.12.2023

Version: 2.0

Date / Previous version: 02.07.2021

Previous version: 1.0

Product: **METHOXYPROPYLACETATE**

(ID no. 30034751/SDS_GEN_ES/EN)

Date of print 19.10.2025

Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Risk Management Measures	
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	13,7143 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,017229
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	192,7187 mg/m ³
Risk Characterization Ratio (RCR)	0,700795
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC28: Manual maintenance (cleaning and repair) of machinery covered by PROC8a

8. Short title of exposure scenario

Cleaning agents, (use in professional settings)

ERC8a, ERC8d; PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC10, PROC11, PROC13, PROC19

Control of exposure and risk management measures

Contributing exposure scenario	
Use descriptors covered	ESVOC SpERC 8.4b.v3
Operational conditions	
Annual amount used in the EU	8.415.000 kg
Minimum emission days per year	365
Emission factor air	4 %

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 12.12.2023

Version: 2.0

Date / Previous version: 02.07.2021

Previous version: 1.0

Product: **METHOXYPROPYLACETATE**

(ID no. 30034751/SDS_GEN_ES/EN)

Date of print 19.10.2025

Emission factor water	1 ppm
Emission factor soil	0,2 ppm
Receive Surf. Water (Flow Rate).	18.000 m3/d
Dilution factor river	10
Dilution factor coast	100
Risk Management Measures	
Type of STP	Municipal STP
Assumed sewage treatment plant flow (m3/d)	2.000 m3/d
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Environment
Risk Characterization Ratio (RCR)	0,020201
	Risk from environmental exposure is driven by soil.
Maximum amount of safe use	228,3 kg/d
Risk from environmental exposure is driven by soil.	

Contributing exposure scenario	
Use descriptors covered	ESVOC SpERC 8.4b.v3
Operational conditions	
Annual amount used in the EU	8.415.000 kg
Minimum emission days per year	365
Emission factor air	4 %
Emission factor water	1 ppm
Emission factor soil	0,2 ppm
Receive Surf. Water (Flow Rate).	18.000 m3/d
Dilution factor river	10
Dilution factor coast	100
Risk Management Measures	
Type of STP	Municipal STP
Assumed sewage treatment plant flow (m3/d)	2.000 m3/d
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Environment
Risk Characterization Ratio (RCR)	0,020201
	Risk from environmental exposure is driven by soil.

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 12.12.2023

Version: 2.0

Date / Previous version: 02.07.2021

Previous version: 1.0

Product: **METHOXYPROPYLACETATE**

(ID no. 30034751/SDS_GEN_ES/EN)

Date of print 19.10.2025

Maximum amount of safe use	228,3 kg/d
Risk from environmental exposure is driven by soil.	

Contributing exposure scenario	
Use descriptors covered	PROC1: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions. Use domain: professional
Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Assumes activities are at ambient temperature.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	0,0343 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,000043
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	0,0551 mg/m ³
Risk Characterization Ratio (RCR)	0,0002
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC2: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions Use domain: professional
Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	480 min 5 days per week

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 12.12.2023

Version: 2.0

Date / Previous version: 02.07.2021

Previous version: 1.0

Product: **METHOXYPROPYLACETATE**

(ID no. 30034751/SDS_GEN_ES/EN)

Date of print 19.10.2025

Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	1,3714 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,001723
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	110,125 mg/m ³
Risk Characterization Ratio (RCR)	0,400455
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition Use domain: professional
Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	0,6857 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,000861
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	137,6562 mg/m ³
Risk Characterization Ratio (RCR)	0,500568
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC4: Chemical production where opportunity for

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 12.12.2023

Version: 2.0

Date / Previous version: 02.07.2021

Previous version: 1.0

Product: **METHOXYPROPYLACETATE**

(ID no. 30034751/SDS_GEN_ES/EN)

Date of print 19.10.2025

	exposure arises Use domain: professional
Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Risk Management Measures	
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	6,8571 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,008615
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	192,7187 mg/m ³
Risk Characterization Ratio (RCR)	0,700795
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC8a: Transfer of substance or mixture (charging and discharging) at non-dedicated facilities Use domain: professional
Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	240 min 5 days per week
Indoor/Outdoor	Outdoor
	Assumes activities are at ambient temperature.
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 12.12.2023

Version: 2.0

Date / Previous version: 02.07.2021

Previous version: 1.0

Product: **METHOXYPROPYLACETATE**

(ID no. 30034751/SDS_GEN_ES/EN)

Date of print 19.10.2025

	Worker - dermal, long-term - systemic
Exposure estimate	8,2286 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,010337
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	231,2625 mg/m ³
Risk Characterization Ratio (RCR)	0,840955
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC8b: Transfer of substance or mixture (charging and discharging) at dedicated facilities Use domain: professional
Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Risk Management Measures	
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	13,7143 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,017229
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	192,7187 mg/m ³
Risk Characterization Ratio (RCR)	0,700795
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC10: Roller application or brushing Use domain: professional
Operational conditions	

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 12.12.2023

Version: 2.0

Date / Previous version: 02.07.2021

Previous version: 1.0

Product: **METHOXYPROPYLACETATE**

(ID no. 30034751/SDS_GEN_ES/EN)

Date of print 19.10.2025

Concentration of the substance	2-methoxy-1-methylethyl acetate Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Risk Management Measures	
Provide a good standard of general or controlled ventilation (5 to 10 air changes per hour)	Effectiveness: 70 %
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	27,4286 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,034458
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	165,1875 mg/m ³
Risk Characterization Ratio (RCR)	0,600682
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC11: Non industrial spraying Use domain: professional
Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: $\geq 0\%$ - $\leq 90\%$
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	240 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
	Any sized room
Application rate	< 3 l/min
Risk Management Measures	
Wear suitable respiratory protection.	Effectiveness: 90 %
Surface spraying with no or low compressed air use.	
Provide extract ventilation to points	

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 12.12.2023

Version: 2.0

Date / Previous version: 02.07.2021

Previous version: 1.0

Product: **METHOXYPROPYLACETATE**

(ID no. 30034751/SDS_GEN_ES/EN)

Date of print 19.10.2025

where emissions occur (LEV).	
Ensure that general housekeeping is in place	
Provide a good standard of controlled ventilation (10 to 15 air changes per hour)	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, worker, modified version, The concentration of the substance has been considered using a linear approach.
	Worker - dermal, long-term - systemic
Exposure estimate	57,8571 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,072685
Assessment method	EASY TRA v5.2, Advanced REACH Tool v1.5
	Worker - inhalation, long-term - systemic
Exposure estimate	190 mg/m ³
Risk Characterization Ratio (RCR)	0,690909
Assessment method	EASY TRA v5.2, Advanced REACH Tool v1.5
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra For scaling see: http://www.advancedreachtool.com	
Please note that a modified version has been used (see exposure estimates)	

Contributing exposure scenario	
Use descriptors covered	PROC11: Non industrial spraying Use domain: professional
Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 90 %
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	240 min 5 days per week
Indoor/Outdoor	Outdoor
	Assumes activities are at ambient temperature.
Application rate	< 3 l/min
Risk Management Measures	
Wear suitable respiratory protection.	Effectiveness: 95 %
Surface spraying with no or low compressed air use.	
Ensure that general housekeeping is in place	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, worker, modified version, The concentration of the substance has been considered using a linear approach.
	Worker - dermal, long-term - systemic

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 12.12.2023

Version: 2.0

Date / Previous version: 02.07.2021

Previous version: 1.0

Product: **METHOXYPROPYLACETATE**

(ID no. 30034751/SDS_GEN_ES/EN)

Date of print 19.10.2025

Exposure estimate	57,8571 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,072685
Assessment method	EASY TRA v5.2, Advanced REACH Tool v1.5
	Worker - inhalation, long-term - systemic
Exposure estimate	190 mg/m ³
Risk Characterization Ratio (RCR)	0,690909
Assessment method	EASY TRA v5.2, Advanced REACH Tool v1.5
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra For scaling see: http://www.advancedreachtool.com	
Please note that a modified version has been used (see exposure estimates)	

Contributing exposure scenario	
Use descriptors covered	PROC13: Treatment of articles by dipping and pouring. Use domain: professional
Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Risk Management Measures	
Provide a good standard of general or controlled ventilation (5 to 10 air changes per hour)	Effectiveness: 70 %
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	13,7143 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,017229
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	165,1875 mg/m ³
Risk Characterization Ratio (RCR)	0,600682
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC19: Manual activities involving hand contact Use domain: professional
Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 12.12.2023

Version: 2.0

Date / Previous version: 02.07.2021

Previous version: 1.0

Product: **METHOXYPROPYLACETATE**

(ID no. 30034751/SDS_GEN_ES/EN)

Date of print 19.10.2025

	Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Risk Management Measures	
Wear suitable respiratory protection.	Effectiveness: 90 %
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	141,4286 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,177674
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	55,0625 mg/m ³
Risk Characterization Ratio (RCR)	0,200227
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

9. Short title of exposure scenario

Cleaning agents, (consumer use)

ERC8a, ERC8d; PC35

Control of exposure and risk management measures

Contributing exposure scenario	
Use descriptors covered	ESVOC SpERC 8.4c.v2
Operational conditions	
Annual amount used in the EU	168.000 kg
Minimum emission days per year	365
Emission factor air	95 %
Emission factor water	2,5 %
Emission factor soil	2,5 %
Receive Surf. Water (Flow Rate).	18.000 m3/d

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 12.12.2023

Version: 2.0

Date / Previous version: 02.07.2021

Previous version: 1.0

Product: **METHOXYPROPYLACETATE**

(ID no. 30034751/SDS_GEN_ES/EN)

Date of print 19.10.2025

Dilution factor river	10
Dilution factor coast	100
Risk Management Measures	
Type of STP	Municipal STP
Assumed sewage treatment plant flow (m3/d)	2.000 m3/d
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Environment
Risk Characterization Ratio (RCR)	0,020244
	Risk from environmental exposure is driven by soil.
Maximum amount of safe use	4,5 kg/d
Risk from environmental exposure is driven by soil.	

Contributing exposure scenario	
Use descriptors covered	ESVOC SpERC 8.4c.v2
Operational conditions	
Annual amount used in the EU	168.000 kg
Minimum emission days per year	365
Emission factor air	95 %
Emission factor water	2,5 %
Emission factor soil	2,5 %
Receive Surf. Water (Flow Rate).	18.000 m3/d
Dilution factor river	10
Dilution factor coast	100
Risk Management Measures	
Type of STP	Municipal STP
Assumed sewage treatment plant flow (m3/d)	2.000 m3/d
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Environment
Risk Characterization Ratio (RCR)	0,020244
	Risk from environmental exposure is driven by soil.
Maximum amount of safe use	4,5 kg/d
Risk from environmental exposure is driven by soil.	
Contributing exposure scenario	

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 12.12.2023

Version: 2.0

Date / Previous version: 02.07.2021

Previous version: 1.0

Product: **METHOXYPROPYLACETATE**

(ID no. 30034751/SDS_GEN_ES/EN)

Date of print 19.10.2025

Use descriptors covered	PC8_3, PC35_3: Subcategory: Cleaners, trigger sprays (all purpose cleaners, sanitary products, glass cleaners)
Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 10 %
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	Exposure duration: 4 h 365 uses per year
Room size	20 m3
Indoor/Outdoor	Indoor
Ventilation rate per hour	0,6
Exposed skin area	Both hands (820 cm ²)
Uptake fraction dermal	100 %
Uptake fraction inhalation	100 %
	Amount per use 16 g Relevant for inhalative exposure estimates
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA, Consumer
	Consumer - dermal, long-term - systemic
Exposure estimate	14,2917 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,044661
Assessment method	EASY TRA v5.2, ECETOC TRA, Consumer
	Consumer - inhalation, long-term - systemic
Exposure estimate	23,5294 mg/m ³
Risk Characterization Ratio (RCR)	0,713012
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

10. Short title of exposure scenario

Use in Agrochemicals, (use in professional settings)

ERC8a, ERC8d; PROC1, PROC2, PROC4, PROC8a, PROC8b, PROC11, PROC13, PROC28

Control of exposure and risk management measures

Contributing exposure scenario	
Use descriptors covered	ECPA SPERC 8d.2.v2
Operational conditions	
Annual amount used in the EU	660.000 kg
Minimum emission days per year	365

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 12.12.2023

Version: 2.0

Date / Previous version: 02.07.2021

Previous version: 1.0

Product: **METHOXYPROPYLACETATE**

(ID no. 30034751/SDS_GEN_ES/EN)

Date of print 19.10.2025

Emission factor air	100 %
Emission factor water	0 %
Emission factor soil	0 %
Receive Surf. Water (Flow Rate).	18.000 m3/d
Dilution factor river	10
Dilution factor coast	100
Risk Management Measures	
Type of STP	no STP
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Environment
Risk Characterization Ratio (RCR)	0,020201
	Risk from environmental exposure is driven by soil.
Maximum amount of safe use	17,9 kg/d
Risk from environmental exposure is driven by soil.	

Contributing exposure scenario	
Use descriptors covered	ECPA SPERC 8d.2.v2
Operational conditions	
Annual amount used in the EU	660.000 kg
Minimum emission days per year	365
Emission factor air	100 %
Emission factor water	0 %
Emission factor soil	0 %
Receive Surf. Water (Flow Rate).	18.000 m3/d
Dilution factor river	10
Dilution factor coast	100
Risk Management Measures	
Type of STP	no STP
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Environment
Risk Characterization Ratio (RCR)	0,020201

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 12.12.2023

Version: 2.0

Date / Previous version: 02.07.2021

Previous version: 1.0

Product: **METHOXYPROPYLACETATE**

(ID no. 30034751/SDS_GEN_ES/EN)

Date of print 19.10.2025

	Risk from environmental exposure is driven by soil.
Maximum amount of safe use	17,9 kg/d
Risk from environmental exposure is driven by soil.	

Contributing exposure scenario	
Use descriptors covered	PROC1: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions. Use domain: professional
Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Assumes activities are at ambient temperature.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	0,0343 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,000043
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	0,0551 mg/m ³
Risk Characterization Ratio (RCR)	0,0002
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC2: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions Use domain: professional
Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	502 Pa

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 12.12.2023

Version: 2.0

Date / Previous version: 02.07.2021

Previous version: 1.0

Product: **METHOXYPROPYLACETATE**

(ID no. 30034751/SDS_GEN_ES/EN)

Date of print 19.10.2025

Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Outdoor
	Assumes activities are at ambient temperature.
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	1,3714 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,001723
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	77,0875 mg/m ³
Risk Characterization Ratio (RCR)	0,280318
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC4: Chemical production where opportunity for exposure arises Use domain: professional
Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Outdoor
	Assumes activities are at ambient temperature.
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	6,8571 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,008615
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	192,7187 mg/m ³
Risk Characterization Ratio (RCR)	0,700795
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC8a: Transfer of substance or mixture (charging and discharging) at non-dedicated facilities

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 12.12.2023

Version: 2.0

Date / Previous version: 02.07.2021

Previous version: 1.0

Product: **METHOXYPROPYLACETATE**

(ID no. 30034751/SDS_GEN_ES/EN)

Date of print 19.10.2025

	Use domain: professional
Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	240 min 5 days per week
Indoor/Outdoor	Outdoor
	Assumes activities are at ambient temperature.
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	8,2286 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,010337
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	231,2625 mg/m ³
Risk Characterization Ratio (RCR)	0,840955
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC8a: Transfer of substance or mixture (charging and discharging) at non-dedicated facilities Use domain: professional
Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	240 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Risk Management Measures	
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 12.12.2023

Version: 2.0

Date / Previous version: 02.07.2021

Previous version: 1.0

Product: **METHOXYPROPYLACETATE**

(ID no. 30034751/SDS_GEN_ES/EN)

Date of print 19.10.2025

Exposure estimate	8,2286 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,010337
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	231,2625 mg/m ³
Risk Characterization Ratio (RCR)	0,840955
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC8b: Transfer of substance or mixture (charging and discharging) at dedicated facilities Use domain: professional
Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Risk Management Measures	
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	13,7143 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,017229
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	192,7187 mg/m ³
Risk Characterization Ratio (RCR)	0,700795
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC11: Non industrial spraying Use domain: professional
	Surface spraying of liquids

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 12.12.2023

Version: 2.0

Date / Previous version: 02.07.2021

Previous version: 1.0

Product: **METHOXYPROPYLACETATE**

(ID no. 30034751/SDS_GEN_ES/EN)

Date of print 19.10.2025

Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	outdoor, away from buildings
	Assumes activities are at ambient temperature.
Application rate	< 3 l/min
Risk Management Measures	
Ensure that the distance from worker to emission source is greater than 4 m.	
Ensure that the task is being carried out outside the breathing zone of a worker (distance head-product greater than 1m).	
Ensure that the worker is in a personal enclosure	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	107,1429 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,134602
Assessment method	EASY TRA v5.2, Advanced REACH Tool v1.5
	Worker - inhalation, long-term - systemic
Exposure estimate	16 mg/m ³
Risk Characterization Ratio (RCR)	0,058182
Assessment method	EASY TRA v5.2, Advanced REACH Tool v1.5
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra For scaling see: http://www.advancedreachtool.com	

Contributing exposure scenario	
Use descriptors covered	PROC11: Non industrial spraying Use domain: professional
Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: $\geq 0\%$ - $\leq 90\%$
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	240 min 5 days per week
Indoor/Outdoor	Outdoor

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 12.12.2023

Version: 2.0

Date / Previous version: 02.07.2021

Previous version: 1.0

Product: **METHOXYPROPYLACETATE**

(ID no. 30034751/SDS_GEN_ES/EN)

Date of print 19.10.2025

	Assumes activities are at ambient temperature.
Application rate	< 3 l/min
Risk Management Measures	
Wear suitable respiratory protection.	Effectiveness: 95 %
Surface spraying with no or low compressed air use.	
Ensure that general housekeeping is in place	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, worker, modified version, The concentration of the substance has been considered using a linear approach.
	Worker - dermal, long-term - systemic
Exposure estimate	57,8571 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,072685
Assessment method	EASY TRA v5.2, Advanced REACH Tool v1.5
	Worker - inhalation, long-term - systemic
Exposure estimate	190 mg/m ³
Risk Characterization Ratio (RCR)	0,690909
Assessment method	EASY TRA v5.2, Advanced REACH Tool v1.5
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra For scaling see: http://www.advancedreachtool.com Please note that a modified version has been used (see exposure estimates)	

Contributing exposure scenario	
Use descriptors covered	PROC13: Treatment of articles by dipping and pouring. Use domain: professional
Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	240 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Risk Management Measures	
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	8,2286 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,010337
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 12.12.2023

Version: 2.0

Date / Previous version: 02.07.2021

Previous version: 1.0

Product: **METHOXYPROPYLACETATE**

(ID no. 30034751/SDS_GEN_ES/EN)

Date of print 19.10.2025

	Worker - inhalation, long-term - systemic
Exposure estimate	231,2625 mg/m ³
Risk Characterization Ratio (RCR)	0,840955
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC28: Manual maintenance (cleaning and repair) of machinery covered by PROC8a

11. Short title of exposure scenario

Use in Agrochemicals, (consumer use)

ERC8a, ERC8d; PC27

Control of exposure and risk management measures

Contributing exposure scenario	
Use descriptors covered	ECPA SPERC 8d.2.v2
Operational conditions	
Annual amount used in the EU	660.000 kg
Minimum emission days per year	365
Emission factor air	100 %
Emission factor water	0 %
Emission factor soil	0 %
Receive Surf. Water (Flow Rate).	18.000 m ³ /d
Dilution factor river	10
Dilution factor coast	100
Risk Management Measures	
Type of STP	no STP
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Environment
Risk Characterization Ratio (RCR)	0,020201
	Risk from environmental exposure is driven by soil.
Maximum amount of safe use	17,9

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 12.12.2023

Version: 2.0

Date / Previous version: 02.07.2021

Previous version: 1.0

Product: **METHOXYPROPYLACETATE**

(ID no. 30034751/SDS_GEN_ES/EN)

Date of print 19.10.2025

	kg/d
Risk from environmental exposure is driven by soil.	

Contributing exposure scenario	
Use descriptors covered	ECPA SPERC 8d.2.v2
Operational conditions	
Annual amount used in the EU	660.000 kg
Minimum emission days per year	365
Emission factor air	100 %
Emission factor water	0 %
Emission factor soil	0 %
Receive Surf. Water (Flow Rate).	18.000 m3/d
Dilution factor river	10
Dilution factor coast	100
Risk Management Measures	
Type of STP	no STP
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Environment
Risk Characterization Ratio (RCR)	0,020201
	Risk from environmental exposure is driven by soil.
Maximum amount of safe use	17,9 kg/d
Risk from environmental exposure is driven by soil.	

Contributing exposure scenario	
Use descriptors covered	PC27: Plant Protection products.
Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 70 %
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	Exposure duration: 240 min Relevant for inhalative exposure estimates
Duration and Frequency of activity	9 uses per year
Room size	58 m3

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 12.12.2023

Version: 2.0

Date / Previous version: 02.07.2021

Previous version: 1.0

Product: **METHOXYPROPYLACETATE**

(ID no. 30034751/SDS_GEN_ES/EN)

Date of print 19.10.2025

Ventilation rate per hour	0,5
body weight	65 kg
Uptake fraction dermal	100 % Relevant for dermal exposure estimates
	Relevant for dermal exposure estimates
Spray duration	600 sec
Contact rate	100 mg/min
Release duration	10 min
	Relevant for dermal exposure estimates
Risk Management Measures	
Consumer Measures	Ensure spraying away from persons.
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ConsExpo v4.1, Dermal model: constant application rate, Uptake model: Uptake fraction
	Consumer - dermal, long-term - systemic
Exposure estimate	0,2655 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,00083
	The calculation is based on the internal chronic dose.
Assessment method	EASY TRA v5.2, ConsExpo v4.1, Inhalation model: Exposure to spray/dust
	Consumer - inhalation, long-term - systemic
Exposure estimate	1,1628 mg/m ³
Risk Characterization Ratio (RCR)	0,035235
	The exposure calculation is based on the mean concentration per year.
Guidance to Downstream Users	
For scaling see: http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp	

12. Short title of exposure scenario

Use in Printing inks, (use in industrial settings)

ERC4; PROC1, PROC2, PROC3, PROC4, PROC5, PROC7, PROC8a, PROC8b, PROC9, PROC10, PROC13, PROC15, PROC28

Control of exposure and risk management measures

Contributing exposure scenario	
Use descriptors covered	CEPE SPERC 4.1b.v2
Operational conditions	
Annual amount used in the EU	3.300.000 kg
Minimum emission days per year	225
Emission factor air	95 %

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 12.12.2023

Version: 2.0

Date / Previous version: 02.07.2021

Previous version: 1.0

Product: **METHOXYPROPYLACETATE**

(ID no. 30034751/SDS_GEN_ES/EN)

Date of print 19.10.2025

Emission factor water	0 %
Emission factor soil	0 %
Receive Surf. Water (Flow Rate).	18.000 m3/d
Dilution factor river	10
Dilution factor coast	100
Risk Management Measures	
Type of STP	Municipal STP
Assumed sewage treatment plant flow (m3/d)	2.000 m3/d
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Environment
Risk Characterization Ratio (RCR)	0,164065
	Risk from environmental exposure is driven by soil.
Maximum amount of safe use	8.939,6 kg/d
Risk from environmental exposure is driven by soil.	

Contributing exposure scenario	
Use descriptors covered	PROC1: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions. Use domain: industrial
Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	0,0343 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,000043
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	0,0551 mg/m ³
Risk Characterization Ratio (RCR)	0,0002
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 12.12.2023

Version: 2.0

Date / Previous version: 02.07.2021

Previous version: 1.0

Product: **METHOXYPROPYLACETATE**

(ID no. 30034751/SDS_GEN_ES/EN)

Date of print 19.10.2025

Guidance to Downstream Users

For scaling see: <http://www.ecetoc.org/tra>

Contributing exposure scenario

Use descriptors covered	PROC2: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions Use domain: industrial
--------------------------------	---

Operational conditions

Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.

Exposure estimate and reference to its source

Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	1,3714 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,001723
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	27,5312 mg/m ³
Risk Characterization Ratio (RCR)	0,100114
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker

Guidance to Downstream Users

For scaling see: <http://www.ecetoc.org/tra>

Contributing exposure scenario

Use descriptors covered	PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition Use domain: industrial
--------------------------------	---

Operational conditions

Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	480 min 5 days per week

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 12.12.2023

Version: 2.0

Date / Previous version: 02.07.2021

Previous version: 1.0

Product: **METHOXYPROPYLACETATE**

(ID no. 30034751/SDS_GEN_ES/EN)

Date of print 19.10.2025

Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	0,6857 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,000861
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	55,0625 mg/m ³
Risk Characterization Ratio (RCR)	0,200227
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC4: Chemical production where opportunity for exposure arises Use domain: industrial
Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	6,8571 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,008615
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	110,125 mg/m ³
Risk Characterization Ratio (RCR)	0,400455
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC5: Mixing or blending in batch processes Use domain: industrial
Operational conditions	

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 12.12.2023

Version: 2.0

Date / Previous version: 02.07.2021

Previous version: 1.0

Product: **METHOXYPROPYLACETATE**

(ID no. 30034751/SDS_GEN_ES/EN)

Date of print 19.10.2025

Concentration of the substance	2-methoxy-1-methylethyl acetate Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Risk Management Measures	
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	13,7143 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,017229
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	192,7187 mg/m ³
Risk Characterization Ratio (RCR)	0,700795
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC7: Industrial spraying Use domain: industrial
Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: $\geq 0\%$ - $\leq 90\%$
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	240 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
	Any sized room
Application rate	< 3 l/min
Risk Management Measures	
Wear suitable respiratory protection.	Effectiveness: 90 %
Surface spraying with no or low compressed air use.	
Provide extract ventilation to points	

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 12.12.2023

Version: 2.0

Date / Previous version: 02.07.2021

Previous version: 1.0

Product: **METHOXYPROPYLACETATE**

(ID no. 30034751/SDS_GEN_ES/EN)

Date of print 19.10.2025

where emissions occur (LEV).	
Ensure that general housekeeping is in place	
Provide a good standard of controlled ventilation (10 to 15 air changes per hour)	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, worker, modified version, The concentration of the substance has been considered using a linear approach.
	Worker - dermal, long-term - systemic
Exposure estimate	23,1429 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,029074
Assessment method	EASY TRA v5.2, Advanced REACH Tool v1.5
	Worker - inhalation, long-term - systemic
Exposure estimate	190 mg/m ³
Risk Characterization Ratio (RCR)	0,690909
Assessment method	EASY TRA v5.2, Advanced REACH Tool v1.5
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra For scaling see: http://www.advancedreachtool.com	
Please note that a modified version has been used (see exposure estimates)	

Contributing exposure scenario	
Use descriptors covered	PROC7: Industrial spraying Use domain: industrial
	Surface spraying of liquids
Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Application rate	< 3 l/min
Risk Management Measures	
Ensure that general housekeeping is in place	
Provide a good standard of controlled ventilation (10 to 15 air changes per hour)	
Ensure that the task is being carried out outside the breathing zone of a worker (distance head-product greater	

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 12.12.2023

Version: 2.0

Date / Previous version: 02.07.2021

Previous version: 1.0

Product: **METHOXYPROPYLACETATE**

(ID no. 30034751/SDS_GEN_ES/EN)

Date of print 19.10.2025

than 1m).	
Ensure that the worker is in a separated (control) room with independent air supply	
Ensure good work practices are implemented.	
Provide a good standard of general or controlled ventilation (5 to 10 air changes per hour) Carry out in a fully closed cabin with independent exhaust ventilation	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	42,8571 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,053841
Assessment method	EASY TRA v5.2, Advanced REACH Tool v1.5
	Worker - inhalation, long-term - systemic
Exposure estimate	180 mg/m ³
Risk Characterization Ratio (RCR)	0,654545
Assessment method	EASY TRA v5.2, Advanced REACH Tool v1.5
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra For scaling see: http://www.advancedreachtool.com	

Contributing exposure scenario	
Use descriptors covered	PROC8a: Transfer of substance or mixture (charging and discharging) at non-dedicated facilities Use domain: industrial
Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Risk Management Measures	
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	13,7143 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,017229

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 12.12.2023

Version: 2.0

Date / Previous version: 02.07.2021

Previous version: 1.0

Product: **METHOXYPROPYLACETATE**

(ID no. 30034751/SDS_GEN_ES/EN)

Date of print 19.10.2025

Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	192,7187 mg/m ³
Risk Characterization Ratio (RCR)	0,700795
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC8b: Transfer of substance or mixture (charging and discharging) at dedicated facilities Use domain: industrial
Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	13,7143 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,017229
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	137,6562 mg/m ³
Risk Characterization Ratio (RCR)	0,500568
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing). Use domain: industrial
Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	502 Pa

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 12.12.2023

Version: 2.0

Date / Previous version: 02.07.2021

Previous version: 1.0

Product: **METHOXYPROPYLACETATE**

(ID no. 30034751/SDS_GEN_ES/EN)

Date of print 19.10.2025

Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Risk Management Measures	
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	6,8571 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,008615
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	192,7187 mg/m ³
Risk Characterization Ratio (RCR)	0,700795
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC10: Roller application or brushing Use domain: industrial
Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Risk Management Measures	
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker, Reduction factor for local exhaust ventilation (LEV) has been used for the calculation of dermal exposure estimates.
	Worker - dermal, long-term - systemic
Exposure estimate	27,4286 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,034458
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 12.12.2023

Version: 2.0

Date / Previous version: 02.07.2021

Previous version: 1.0

Product: **METHOXYPROPYLACETATE**

(ID no. 30034751/SDS_GEN_ES/EN)

Date of print 19.10.2025

Exposure estimate	192,7187 mg/m ³
Risk Characterization Ratio (RCR)	0,700795
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC13: Treatment of articles by dipping and pouring. Use domain: industrial
Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Assumes activities are at ambient temperature.	
Risk Management Measures	
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	13,7143 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,017229
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	192,7187 mg/m ³
Risk Characterization Ratio (RCR)	0,700795
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC15: Use a laboratory reagent. Use domain: industrial
Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	502 Pa

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 12.12.2023

Version: 2.0

Date / Previous version: 02.07.2021

Previous version: 1.0

Product: **METHOXYPROPYLACETATE**

(ID no. 30034751/SDS_GEN_ES/EN)

Date of print 19.10.2025

Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	0,3429 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,000431
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	55,0625 mg/m ³
Risk Characterization Ratio (RCR)	0,200227
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC28: Manual maintenance (cleaning and repair) of machinery covered by PROC8a

13. Short title of exposure scenario

Use in Coatings, (coil), (use in industrial settings)

ERC4; PROC1, PROC2, PROC3, PROC4, PROC5, PROC7, PROC8a, PROC8b, PROC9, PROC10, PROC13, PROC15, PROC28

Control of exposure and risk management measures

Contributing exposure scenario	
Use descriptors covered	CEPE SPERC 4.1a.v2
Operational conditions	
Annual amount used in the EU	25.000.000 kg
Minimum emission days per year	225
Emission factor air	20,8 %
Emission factor water	0 %
Emission factor soil	0 %
Receive Surf. Water (Flow Rate).	18.000 m3/d

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 12.12.2023

Version: 2.0

Date / Previous version: 02.07.2021

Previous version: 1.0

Product: **METHOXYPROPYLACETATE**

(ID no. 30034751/SDS_GEN_ES/EN)

Date of print 19.10.2025

Dilution factor river	10
Dilution factor coast	100
Risk Management Measures	
Type of STP	Municipal STP
Assumed sewage treatment plant flow (m3/d)	2.000 m3/d
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Environment
Risk Characterization Ratio (RCR)	0,258827
	Risk from environmental exposure is driven by soil.
Maximum amount of safe use	42.928,8 kg/d
	Risk from environmental exposure is driven by soil.

Contributing exposure scenario	
Use descriptors covered	PROC1: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions. Use domain: industrial
Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	0,0343 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,000043
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	0,0551 mg/m ³
Risk Characterization Ratio (RCR)	0,0002
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC2: Chemical production or refinery in closed continuous process with occasional controlled exposure or

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 12.12.2023

Version: 2.0

Date / Previous version: 02.07.2021

Previous version: 1.0

Product: **METHOXYPROPYLACETATE**

(ID no. 30034751/SDS_GEN_ES/EN)

Date of print 19.10.2025

	processes with equivalent containment conditions Use domain: industrial
Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	1,3714 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,001723
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	27,5312 mg/m ³
Risk Characterization Ratio (RCR)	0,100114
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition Use domain: industrial
Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	0,6857 mg/kg bw/day

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 12.12.2023

Version: 2.0

Date / Previous version: 02.07.2021

Previous version: 1.0

Product: **METHOXYPROPYLACETATE**

(ID no. 30034751/SDS_GEN_ES/EN)

Date of print 19.10.2025

Risk Characterization Ratio (RCR)	0,000861
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	55,0625 mg/m ³
Risk Characterization Ratio (RCR)	0,200227
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC4: Chemical production where opportunity for exposure arises Use domain: industrial
Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	6,8571 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,008615
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	110,125 mg/m ³
Risk Characterization Ratio (RCR)	0,400455
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC5: Mixing or blending in batch processes Use domain: industrial
Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	502 Pa

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 12.12.2023

Version: 2.0

Date / Previous version: 02.07.2021

Previous version: 1.0

Product: **METHOXYPROPYLACETATE**

(ID no. 30034751/SDS_GEN_ES/EN)

Date of print 19.10.2025

Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Risk Management Measures	
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	13,7143 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,017229
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	192,7187 mg/m ³
Risk Characterization Ratio (RCR)	0,700795
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC7: Industrial spraying Use domain: industrial
Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 90 %
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	240 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
	Any sized room
Application rate	< 3 l/min
Risk Management Measures	
Wear suitable respiratory protection.	Effectiveness: 90 %
Surface spraying with no or low compressed air use.	
Provide extract ventilation to points where emissions occur (LEV).	
Ensure that general housekeeping is in place	
Provide a good standard of controlled ventilation (10 to 15 air changes per hour)	

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 12.12.2023

Version: 2.0

Date / Previous version: 02.07.2021

Previous version: 1.0

Product: **METHOXYPROPYLACETATE**

(ID no. 30034751/SDS_GEN_ES/EN)

Date of print 19.10.2025

Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, worker, modified version, The concentration of the substance has been considered using a linear approach.
	Worker - dermal, long-term - systemic
Exposure estimate	23,1429 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,029074
Assessment method	EASY TRA v5.2, Advanced REACH Tool v1.5
	Worker - inhalation, long-term - systemic
Exposure estimate	190 mg/m ³
Risk Characterization Ratio (RCR)	0,690909
Assessment method	EASY TRA v5.2, Advanced REACH Tool v1.5
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra For scaling see: http://www.advancedreachtool.com Please note that a modified version has been used (see exposure estimates)	
Contributing exposure scenario	
Use descriptors covered	PROC7: Industrial spraying Use domain: industrial
	Surface spraying of liquids
Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Application rate	< 3 l/min
Risk Management Measures	
Ensure that general housekeeping is in place	
Provide a good standard of controlled ventilation (10 to 15 air changes per hour)	
Ensure that the task is being carried out outside the breathing zone of a worker (distance head-product greater than 1m).	
Ensure that the worker is in a separated (control) room with independent air supply	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 12.12.2023

Version: 2.0

Date / Previous version: 02.07.2021

Previous version: 1.0

Product: **METHOXYPROPYLACETATE**

(ID no. 30034751/SDS_GEN_ES/EN)

Date of print 19.10.2025

	Worker - dermal, long-term - systemic
Exposure estimate	42,8571 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,053841
Assessment method	EASY TRA v5.2, Advanced REACH Tool v1.5
	Worker - inhalation, long-term - systemic
Exposure estimate	180 mg/m ³
Risk Characterization Ratio (RCR)	0,654545
Assessment method	EASY TRA v5.2, Advanced REACH Tool v1.5
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra For scaling see: http://www.advancedreachtool.com	

Contributing exposure scenario	
Use descriptors covered	PROC8a: Transfer of substance or mixture (charging and discharging) at non-dedicated facilities Use domain: industrial
Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Risk Management Measures	
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	13,7143 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,017229
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	192,7187 mg/m ³
Risk Characterization Ratio (RCR)	0,700795
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC8b: Transfer of substance or mixture (charging and discharging) at dedicated facilities Use domain: industrial

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 12.12.2023

Version: 2.0

Date / Previous version: 02.07.2021

Previous version: 1.0

Product: **METHOXYPROPYLACETATE**

(ID no. 30034751/SDS_GEN_ES/EN)

Date of print 19.10.2025

Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	13,7143 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,017229
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	137,6562 mg/m ³
Risk Characterization Ratio (RCR)	0,500568
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing). Use domain: industrial
Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Risk Management Measures	
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	6,8571 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,008615

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 12.12.2023

Version: 2.0

Date / Previous version: 02.07.2021

Previous version: 1.0

Product: **METHOXYPROPYLACETATE**

(ID no. 30034751/SDS_GEN_ES/EN)

Date of print 19.10.2025

Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	192,7187 mg/m ³
Risk Characterization Ratio (RCR)	0,700795
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC10: Roller application or brushing Use domain: industrial
Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Risk Management Measures	
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	27,4286 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,034458
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	192,7187 mg/m ³
Risk Characterization Ratio (RCR)	0,700795
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC13: Treatment of articles by dipping and pouring. Use domain: industrial
Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 12.12.2023

Version: 2.0

Date / Previous version: 02.07.2021

Previous version: 1.0

Product: **METHOXYPROPYLACETATE**

(ID no. 30034751/SDS_GEN_ES/EN)

Date of print 19.10.2025

Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Risk Management Measures	
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	13,7143 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,017229
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	192,7187 mg/m ³
Risk Characterization Ratio (RCR)	0,700795
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC15: Use a laboratory reagent. Use domain: industrial
Operational conditions	
Concentration of the substance	2-methoxy-1-methylethyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	502 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	0,3429 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,000431
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	55,0625 mg/m ³
Risk Characterization Ratio (RCR)	0,200227
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
Guidance to Downstream Users	

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 12.12.2023

Version: 2.0

Date / Previous version: 02.07.2021

Previous version: 1.0

Product: **METHOXYPROPYLACETATE**

(ID no. 30034751/SDS_GEN_ES/EN)

Date of print 19.10.2025

For scaling see: <http://www.ecetoc.org/tra>

Contributing exposure scenario	
Use descriptors covered	PROC28: Manual maintenance (cleaning and repair) of machinery covered by PROC8a
