

# Foamaster® MO 2159

**Product Description** Foamaster® MO 2159 is an emulsified defoamer, designed for water-based systems, especially high PVC decorative paints.

**Key Benefits**

- Excellent defoamer action in High PVC paints
- Excellent de-aeration action
- Good substrate wetting
- Helps levelling
- Easy incorporation
- Excellent price/performance

**Chemical Composition** Blend of emulsified mineral oil, hydrophobic solids and foam killer polymers.

---

## Properties

**Appearance** Opaque, white liquid

**Typical properties  
(no supply  
specification)**

Density	25 °C	0,900 – 0,980 g/cm <sup>3</sup>
pH (as is)	25 °C	7.50 – 9,50
Viscosity (Brookfield)	RVT, f3, 20rpm, 25°C	300 – 1500 mPa.s

---

## Application

Foamaster® MO 2159 is an emulsified defoamer especially developed to decorative paints with high PVC, as economic paints and texture and plasters also.

## Dosage

0,2 – 0,8% on the total formulation. Despite of the recommended dosage, laboratory tests are advised. The addition could be in grind stage or in letdown portion, however, for better grinding efficiency, it is advisable to add a portion (~ 70%) of the total defoamer in the grinding and the rest in the letdown stage.

---

## Storage

Foamaster® MO 2159 is subject to appropriate storage under the usual storage and temperature conditions, our products are durable for at least 1 year. Keep it at original package (preferably between 5 and 45°C) in a dry place, under protection from the weather. Foamaster® MO 2159 can show a slight phase separation with time. Stir well before using. This does not change the characteristics and performance of the product.

### Contacts worldwide

Asia  
BASF East Asia Regional Headquarters Ltd  
45/F, Jardine House  
No. 1 Connaught Place  
Central Hong Kong  
China  
[formulation-additives-asia@basf.com](mailto:formulation-additives-asia@basf.com)

Europe  
BASF SE  
Formulation Additives  
67056 Ludwigshafen  
Germany  
[formulation-additives-europe@basf.com](mailto:formulation-additives-europe@basf.com)

North America  
BASF Corporation  
11501 Steele Creek Road  
Charlotte, NC 28273  
USA  
[formulation-additives-nafta@basf.com](mailto:formulation-additives-nafta@basf.com)

South America  
BASF S.A  
Rochaverá - Crystal Tower  
Av. das Nações Unidas, 14.171  
Morumbi - São Paulo-SP  
Brasil  
[formulation-additives-south-america@basf.com](mailto:formulation-additives-south-america@basf.com)

### Safety

When handling this product please comply with the advice and information given in the safety data sheet and observe protective and workplace hygiene measures

#### Note

The data contained in this publication are based on our current knowledge and experience. In view of the many factors that may affect processing and application of our product, these data do not relieve processors from carrying out their own investigations and tests; do these data imply neither any guarantee of certain properties, nor the suitability of the product for a specific purpose. Any descriptions, drawings, photographs, data, proportions, weights, etc. given herein may change without prior information and do not constitute the agreed contractual quality of the product. The agreed contractual quality of the product results exclusively from the statements made in the product specification. It is the responsibility of the recipient of our product to ensure that any proprietary rights and existing laws and legislation are observed.

\* = registered trademark, ™ = trademark of BASF Group, unless otherwise noted

[www.basf.com/formulation-additives](http://www.basf.com/formulation-additives)