

Safety data sheet

Page: 1/16

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 25.08.2025 Version: 2.0
Date / Previous version: 22.12.2022 Previous version: 1.1

Product: Styrofan® D 422

(ID no. 30041944/SDS_GEN_DE/EN)

Date of print 14.10.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Styrofan® D 422

UFI: P6D6-6K1N-700X-VYKN

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses: Raw material, for industrial use only

1.3. Details of the supplier of the safety data sheet

Company:
BASF SE
67056 Ludwigshafen
GERMANY
Regional Business Unit Dispersions Europe

Telephone: +49 621 60-0

E-mail address: ed-psr@basf.com

1.4. Emergency telephone number

International emergency number: Telephone: +49 180 2273-112

to Regulation (EC) No 1907/2006.

Date / Revised: 25.08.2025 Version: 2.0 Date / Previous version: 22.12.2022 Previous version: 1.1

Product: Styrofan® D 422

(ID no. 30041944/SDS_GEN_DE/EN)

Date of print 14.10.2025

SECTION 2: Hazards Identification

2.1. Classification of the substance or mixture

For the classification of the mixture the following methods have been applied: extrapolation on the concentration levels of the hazardous substances, on basis of test results and after evaluation of experts. The methodologies used are mentioned at the respective test results.

According to Regulation (EC) No 1272/2008 [CLP]

Skin Sens. 1 H317 May cause an allergic skin reaction.

For the classifications not written out in full in this section the full text can be found in section 16.

2.2. Label elements

According to Regulation (EC) No 1272/2008 [CLP]

Pictogram:



Signal Word:

Warning

Hazard Statement:

H317 May cause an allergic skin reaction.

Precautionary Statements (Prevention):

P280 Wear protective gloves.

P261 Avoid breathing mist or vapour or spray.

Precautionary Statements (Response):

P302 + P352 IF ON SKIN: Wash with plenty of soap and water. P333 + P313 If skin irritation or rash occurs: Get medical attention. P362 + P364 Take off contaminated clothing and wash it before reuse.

Precautionary Statements (Disposal):

P501 Dispose of contents and container to hazardous or special waste

collection point.

According to Regulation (EC) No 1272/2008 [CLP]

Labeling of special preparations (GHS):

EUH208: May produce an allergic reaction. Contains: mixture of: 5-chloro-2-methyl-2H-isothiazol-3one and 2-methyl-2H-isothiazol-3-one, 1,2-benzisothiazol-3(2H)-one, Phenol, 4-methyl-, reaction products with dicyclopentadiene and isobutylene

Hazard determining component(s) for labelling: 1,2-benzisothiazol-3(2H)-one

to Regulation (EC) No 1907/2006.

Date / Revised: 25.08.2025 Version: 2.0
Date / Previous version: 22.12.2022 Previous version: 1.1

Product: Styrofan® D 422

(ID no. 30041944/SDS_GEN_DE/EN)

Date of print 14.10.2025

2.3. Other hazards

According to Regulation (EC) No 1272/2008 [CLP]

Product does not contain a substance above legal limits included in the list established in accordance with Article 59(1) of Regulation (EC) No 1907/2006 for having endocrine disrupting properties or is identified to have endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605. The product does not contain a substance above legal limits fulfilling the PBT (persistent/bioaccumulative/toxic) criteria or the vPvB (very persistent/very bioaccumulative) criteria.

SECTION 3: Composition/Information on Ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Chemical nature

Aqueous dispersion of a polymer based on:styrene, 1,3-butadiene

Regulatory relevant ingredients

Phenol, 4-methyl-, reaction products with dicyclopentadiene and isobutylene

Content (W/W): > 0 % - < 0,2 % Skin Sens. 1B
CAS Number: 68610-51-5 Repr. 2 (unborn child)
EC-Number: 271-867-2 Aquatic Chronic 4
REACH registration number: 01-

2119496062-39

1,2-benzisothiazol-3(2H)-one

Content (W/W): > 0 PPM - < 450 Acute Tox. 2 (Inhalation - dust)

PPM Acute Tox. 4 (oral)

CAS Number: 2634-33-5 Skin Irrit. 2
EC-Number: 220-120-9 Eye Dam. 1
REACH registration number: 01- Skin Sens. 1A
2120761540-60 Aguatic Acute 1

20761540-60

Aquatic Acute 1

Aquatic Chronic 1

M-factor acute: 1

M-factor chronic: 1

H318, H315, H330, H302, H317, H400, H410

Specific concentration limit: Skin Sens. 1A: >= 0,036 %

Acute toxicity estimate:

oral: 450 mg/kg

Inhalation: 0,21 mg/l (dust/mist)

mixture of: 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one

Date / Revised: 25.08.2025 Version: 2.0
Date / Previous version: 22.12.2022 Previous version: 1.1

Product: Styrofan® D 422

(ID no. 30041944/SDS_GEN_DE/EN)

Date of print 14.10.2025

Content (W/W): > 0 PPM - < 15 Acute

PPM

CAS Number: 55965-84-9 REACH registration number: 01-

2120764691-48

INDEX-Number: 613-167-00-5

Acute Tox. 3 (oral)

Acute Tox. 2 (Inhalation - mist)

Acute Tox. 2 (dermal) Skin Corr./Irrit. 1C Eye Dam./Irrit. 1

Skin Sens. 1A
Aquatic Acute 1
Aquatic Chronic 1
M-factor acute: 100
M-factor chronic: 100

H301, H317, H314, H310 + H330, H400, H410

EUH071

Specific concentration limit:

Skin Corr./Irrit. 1C: >= 0,6 % Skin Sens. 1A: >= 0,0015 % Eye Dam./Irrit. 1: >= 0,6 % Skin Corr./Irrit. 2: 0,06 - < 0,6 % Eye Dam./Irrit. 2: 0,06 - < 0,6 %

For the classifications not written out in full in this section, including the hazard classes and the hazard statements, the full text is listed in section 16.

SECTION 4: First-Aid Measures

4.1. Description of first aid measures

Remove contaminated clothing.

If inhaled:

Keep patient calm, remove to fresh air, seek medical attention.

On skin contact:

Wash thoroughly with soap and water

On contact with eyes:

Immediately wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.

On ingestion:

Rinse mouth and then drink 200-300 ml of water. Do not induce vomiting unless told to by a poison control center or doctor.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms: Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11.

to Regulation (EC) No 1907/2006. Date / Revised: 25.08.2025

Product: Styrofan® D 422

Version: 2.0 Previous version: 1.1

Date / Previous version: 22.12.2022

(ID no. 30041944/SDS_GEN_DE/EN)

Date of print 14.10.2025

Hazards: No hazards anticipated.

4.3. Indication of any immediate medical attention and special treatment needed

Treatment: Symptomatic treatment (decontamination, vital functions).

SECTION 5: Fire-Fighting Measures

5.1. Extinguishing media

Suitable extinguishing media: water spray, dry powder, foam, carbon dioxide

5.2. Special hazards arising from the substance or mixture

Advice: No particular hazards known.

5.3. Advice for fire-fighters

Special protective equipment:

No data available.

Further information:

Dispose of fire debris and contaminated extinguishing water in accordance with official regulations. Product itself is non-combustible; fire extinguishing method of surrounding areas must be considered.

SECTION 6: Accidental Release Measures

6.1. Personal precautions, protective equipment and emergency procedures

Use personal protective clothing. Avoid contact with skin and eyes.

6.2. Environmental precautions

Do not release untreated into natural waters.

6.3. Methods and material for containment and cleaning up

For small amounts: Pick up with suitable absorbent material (e.g. sand, sawdust, general-purpose

binder, kieselguhr). Dispose of absorbed material in accordance with regulations.

For large amounts: Pump off product.

6.4. Reference to other sections

Information regarding exposure controls/personal protection and disposal considerations can be found in section 8 and 13.

Date / Revised: 25.08.2025 Version: 2.0
Date / Previous version: 22.12.2022 Previous version: 1.1

Product: Styrofan® D 422

(ID no. 30041944/SDS_GEN_DE/EN)

Date of print 14.10.2025

SECTION 7: Handling and Storage

7.1. Precautions for safe handling

Handle in accordance with good industrial hygiene and safety practice. After long storage, slight quantities of carbon monoxide may be formed. To our best knowledge, the occupational exposure limit (OEL) is not exceeded during use. Entering of tanks must only be performed after intensive cleaning and when it is ensured that residual vapours have been removed. Consideration of national laws and international standards for confined space entry should be taken in to account. In case of doubt, the concentration of Carbon monoxide must be determined.

Implement proper technical protective measures to prevent product release during handling and processing.

7.2. Conditions for safe storage, including any incompatibilities

Further information on storage conditions: Store protected against freezing.

Storage class according to TRGS 510 (originally VCI, Germany): (12) Non-combustible liquids

Protect from temperatures below:5 °C Protect from temperatures above:60 °C

7.3. Specific end use(s)

For the relevant identified use(s) listed in Section 1 the advice mentioned in this section 7 is to be observed.

SECTION 8: Exposure Controls/Personal Protection

8.1. Control parameters

Components with occupational exposure limits

No substance specific occupational exposure limits known.

8.2. Exposure controls

Personal protective equipment

Hand protection:

Suitable chemical resistant safety gloves (EN ISO 374-1) also with prolonged, direct contact (Recommended: Protective index 6, corresponding > 480 minutes of permeation time according to EN ISO 374-1): E.g. nitrile rubber (0.4 mm), chloroprene rubber (0.5 mm), butyl rubber (0.7 mm) etc. Supplementary note: The specifications are based on tests, literature data and information of glove manufacturers or are derived from similar substances by analogy. Due to many conditions (e.g. temperature) it must be considered, that the practical usage of a chemical-protective glove in practice may be much shorter than the permeation time determined through testing.

Eye protection:

Safety glasses with side-shields (frame goggles) (e.g. EN 166)

Date / Revised: 25.08.2025

Version: 2.0 Date / Previous version: 22.12.2022 Previous version: 1.1

Product: Styrofan® D 422

(ID no. 30041944/SDS_GEN_DE/EN)

Date of print 14.10.2025

General safety and hygiene measures

Hands and/or face should be washed before breaks and at the end of the shift. Avoid contact with skin and eyes.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

State of matter: liquid

liquid, dispersion Form:

Colour: white Odour: aromatic

Odour threshold:

No data available.

Information on: Water

Melting point: 0°C

Information on: Water

100 °C Boiling point:

Flammability: not flammable (derived from flash - and boiling

point)

(DIN EN ISO 2555 (RVT))

Lower explosion limit:

For liquids not relevant for classification and labelling.

Upper explosion limit:

For liquids not relevant for classification and labelling.

Flash point:

not applicable

Auto-ignition temperature:

No data available.

Thermal decomposition: No decomposition if used correctly.

pH value: (DIN ISO 976) 7,3 - 8,330 - 150 mPa.s (DIN EN ISO 3219) Viscosity, dynamic:

(23 °C, 100 1/s)

60 - 300 mPa.s (23 °C)

partly soluble

(15 °C)

Solubility (qualitative):

Solubility in water:

No data available.

Partitioning coefficient n-octanol/water (log Kow):

No data available.

Information on: Water

23.4 hPa Vapour pressure:

(20 °C) Literature data.

Date / Revised: 25.08.2025 Version: 2.0
Date / Previous version: 22.12.2022 Previous version: 1.1

Product: Styrofan® D 422

(ID no. 30041944/SDS_GEN_DE/EN)

Date of print 14.10.2025

Relative density:

No data available.

Density: approx. 1,01 g/cm3 (ISO 2811-1)

(20 °C)

Relative vapour density (air):

Water content greater than 10%.

9.2. Other information

Information with regard to physical hazard classes

Explosives

Explosion hazard: not explosive

Oxidizing properties

Fire promoting properties: not fire-propagating

Self-heating substances and mixtures

Self heating ability: It is not a substance capable of

spontaneous heating.

Other safety characteristics

Miscibility with water:

miscible

Solids content: 49,0 - 51,0 % (DIN EN ISO 3251)

Other Information: Range of particle size: $< 0.1 \mu m - 10 \mu m$

SAPT-Temperature:

Product does not fulfil criteria for polymerizing substances according to

transport regulations.

Evaporation rate:

Value can be approximated from Henry's Law Constant or vapor

pressure.

SECTION 10: Stability and Reactivity

10.1. Reactivity

No hazardous reactions if stored and handled as prescribed/indicated.

Reactions with Reaction with: air water/air:

Flammable gases: no Toxic gases: no Corrosive gases: no Smoke or fog: no Peroxides: no

10.2. Chemical stability

The product is stable if stored and handled as prescribed/indicated.

Date / Revised: 25.08.2025 Version: 2.0
Date / Previous version: 22.12.2022 Previous version: 1.1

Product: Styrofan® D 422

(ID no. 30041944/SDS_GEN_DE/EN)

Date of print 14.10.2025

Peroxides: The product does not contain peroxides. The product/the substance has

not a tendency towards the formation of peroxide.

10.3. Possibility of hazardous reactions

No hazardous reactions when stored and handled according to instructions. After long storage, slight quantities of carbon monoxide may be formed.

10.4. Conditions to avoid

Avoid extreme temperatures.

10.5. Incompatible materials

Substances to avoid:

No substances known that should be avoided.

10.6. Hazardous decomposition products

No hazardous decomposition products if stored and handled as prescribed/indicated.

SECTION 11: Toxicological Information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Assessment of acute toxicity:

Virtually nontoxic after a single ingestion. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Experimental/calculated data:

LD50 rat (oral): > 2.000 - 10.000 mg/kg

Irritation

Assessment of irritating effects:

If the product adheres to skin, irritation may occur when it dries.

Not irritating to the eyes. Not irritating to the skin. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Experimental/calculated data:

Skin corrosion/irritation

rabbit: non-irritant (OECD Guideline 404)

Serious eye damage/irritation

rabbit: non-irritant (OECD Guideline 405)

Date / Revised: 25.08.2025 Version: 2.0
Date / Previous version: 22.12.2022 Previous version: 1.1

Product: Styrofan® D 422

(ID no. 30041944/SDS_GEN_DE/EN)

Date of print 14.10.2025

Respiratory/Skin sensitization

Assessment of sensitization:

May cause sensitization by skin contact.

Germ cell mutagenicity

Assessment of mutagenicity:

The substance was not mutagenic in bacteria. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Carcinogenicity

Assessment of carcinogenicity:

The whole of the information assessable provides no indication of a carcinogenic effect.

Reproductive toxicity

No data available.

Developmental toxicity

Assessment of teratogenicity:

The data available for an assessment of the effect of the substance on developmental toxicity are not sufficient for a proper evaluation.

Specific target organ toxicity (single exposure)

Assessment of STOT single:

Based on the available information there is no specific target organ toxicity to be expected after a single exposure.

Repeated dose toxicity and Specific target organ toxicity (repeated exposure)

Assessment of repeated dose toxicity:

No adverse effects were observed after repeated inhalative exposure in animal studies. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Aspiration hazard

not applicable

Interactive effects

No data available.

11.2. Information on other hazards

Endocrine disrupting properties

Date / Revised: 25.08.2025 Version: 2.0
Date / Previous version: 22.12.2022 Previous version: 1.1

Product: Styrofan® D 422

(ID no. 30041944/SDS_GEN_DE/EN)

Date of print 14.10.2025

Product does not contain a substance above legal limits included in the list established in accordance with Article 59(1) of Regulation (EC) No 1907/2006 for having endocrine disrupting properties or is identified to have endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

Other information

Other relevant toxicity information

Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses. The statement was derived from products of similar composition.

SECTION 12: Ecological Information

12.1. Toxicity

Toxicity to fish:

LC50 (96 h) > 100 mg/l, Brachydanio rerio (OECD Guideline 203, static)

Aquatic invertebrates:

EC50 (48 h) > 100 mg/l, Daphnia magna (OECD Guideline 202, part 1, static)

Aquatic plants:

EC50 (72 h) > 100 mg/l, Scenedesmus subspicatus (OECD Guideline 201)

Nominal concentration.

Microorganisms/Effect on activated sludge:

EC20 (0.5 h) > 100 mg/l, activated sludge, domestic (DIN EN ISO 8192-OECD 209-88/302/EEC,P. C)

The inhibition of the degradation activity of activated sludge is not anticipated when introduced to biological treatment plants in appropriate low concentrations.

12.2. Persistence and degradability

Assessment biodegradation and elimination (H2O):

The product can be virtually eliminated from water by abiotic processes e.g. adsorption onto activated sludge.

Elimination information:

> 70 % DOC reduction (OECD 302B; ISO 9888; 88/302/EWG, Teil C) Easily eliminated from water.

12.3. Bioaccumulative potential

Bioaccumulation potential:

Date / Revised: 25.08.2025 Version: 2.0
Date / Previous version: 22.12.2022 Previous version: 1.1

Product: Styrofan® D 422

(ID no. 30041944/SDS_GEN_DE/EN)

Date of print 14.10.2025

Based on its structural properties, the polymer is not biologically available. Accumulation in organisms is not to be expected.

12.4. Mobility in soil

Assessment transport between environmental compartments: Volatility: No data available.

12.5. Results of PBT and vPvB assessment

According to Annex XIII of Regulation (EC) No.1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH): The product does not contain a substance fulfilling the PBT (persistent/bioaccumulative/toxic) criteria or the vPvB (very persistent/very bioaccumulative) criteria.

12.6. Endocrine disrupting properties

Product does not contain a substance above legal limits included in the list established in accordance with Article 59(1) of Regulation (EC) No 1907/2006 for having endocrine disrupting properties or is identified to have endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

12.7. Other adverse effects

The product does not contain substances that are listed in Regulation (EU) 2024/590 on substances that deplete the ozone layer.

Additional information

Adsorbable organically-bound halogen (AOX):

No data available.

Other ecotoxicological advice:

Do not release untreated into natural waters. At the present state of knowledge, no negative ecological effects are expected.

Ecological data are determined by analogy.

SECTION 13: Disposal Considerations

13.1. Waste treatment methods

Must be disposed of or incinerated in accordance with local regulations.

Do not discharge into drains/surface waters/groundwater.

A waste code in accordance with the European waste catalog (EWC) cannot be specified, due to dependence on the usage.

Date / Revised: 25.08.2025 Version: 2.0 Date / Previous version: 22.12.2022 Previous version: 1.1

Product: Styrofan® D 422

(ID no. 30041944/SDS_GEN_DE/EN)

Date of print 14.10.2025

Observe national and local legal requirements.

SECTION 14: Transport Information

Land transport

ADR

Not classified as a dangerous good under transport regulations

UN number or ID number: Not applicable Not applicable UN proper shipping name: Transport hazard class(es): Not applicable Packing group: Not applicable Environmental hazards: Not applicable Special precautions for None known

user

RID

Not classified as a dangerous good under transport regulations

UN number or ID number: Not applicable Not applicable UN proper shipping name: Not applicable Transport hazard class(es): Packing group: Not applicable Environmental hazards: Not applicable Special precautions for

user

None known

Inland waterway transport

ADN

Not classified as a dangerous good under transport regulations

UN number or ID number: Not applicable UN proper shipping name: Not applicable Transport hazard class(es): Not applicable Packing group: Not applicable Environmental hazards: Not applicable Special precautions for None known

user:

Transport in inland waterway vessel

Not evaluated

Sea transport

to Regulation (EC) No 1907/2006.

Date / Revised: 25.08.2025 Version: 2.0
Date / Previous version: 22.12.2022 Previous version: 1.1

Product: Styrofan® D 422

(ID no. 30041944/SDS_GEN_DE/EN)

Date of print 14.10.2025

IMDG

Not classified as a dangerous good under transport regulations

UN number or ID number:
UN proper shipping name:
Transport hazard class(es):
Packing group:
Environmental hazards:
Special precautions for

Not applicable
Not applicable
Not applicable
Not applicable
Not applicable
Not applicable

user

Air transport

IATA/ICAO

Not classified as a dangerous good under transport regulations

UN number or ID number:
UN proper shipping name:
Transport hazard class(es):
Packing group:
Environmental hazards:
Special precautions for

Not applicable
Not applicable
Not applicable
Not applicable
Not applicable
Not applicable

user

14.1. UN number or ID number

See corresponding entries for "UN number or ID number" for the respective regulations in the tables above.

14.2. UN proper shipping name

See corresponding entries for "UN proper shipping name" for the respective regulations in the tables above.

14.3. Transport hazard class(es)

See corresponding entries for "Transport hazard class(es)" for the respective regulations in the tables above.

14.4. Packing group

See corresponding entries for "Packing group" for the respective regulations in the tables above.

14.5. Environmental hazards

See corresponding entries for "Environmental hazards" for the respective regulations in the tables above.

14.6. Special precautions for user

See corresponding entries for "Special precautions for user" for the respective regulations in the tables above.

Date / Revised: 25.08.2025 Version: 2.0
Date / Previous version: 22.12.2022 Previous version: 1.1

Product: Styrofan® D 422

(ID no. 30041944/SDS_GEN_DE/EN)

Date of print 14.10.2025

14.7. Maritime transport in bulk according to IMO instruments

Maritime transport in bulk is not intended.

SECTION 15: Regulatory Information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Hazardous Incident Ordinance (Germany):

Listed in above regulation: no

Classification applies for standard conditions of temperature and pressure.

Directive 2012/18/EU - Control of Major Accident Hazards involving dangerous substances (EU):

Listed in above regulation: no

Classification applies for standard conditions of temperature and pressure.

Water hazard class (§8/§10 AwSV (Self-classification of the mixture according to calculation method)): (1) Weakly water polluting.

Law on the Protection of Working Youth

German Regulation TA Luft (Technical Instruction on Air Quality Control, i.e. first Directive to the Federal Immission Control Ordinance)

15.2. Chemical Safety Assessment

Assessment of safe use has been performed for the mixture and the result is documented in section 7 and 8 of the SDS

SECTION 16: Other Information

Any other intended applications should be discussed with the manufacturer.

Full text of the classifications, including the hazard classes and the hazard statements, if mentioned

in section 2 or 3:

Skin Sens. Skin sensitization Repr. Reproductive toxicity

Aquatic Chronic Hazardous to the aquatic environment - chronic

Acute Tox. Acute toxicity
Skin Irrit. Skin irritation
Eye Dam. Serious eye damage

Aquatic Acute Hazardous to the aquatic environment - acute

Skin Corr./Irrit. Skin corrosion/irritation

Eye Dam./Irrit. Serious eye damage/eye irritation H317 May cause an allergic skin reaction.

Date / Revised: 25.08.2025 Version: 2.0
Date / Previous version: 22.12.2022 Previous version: 1.1

Product: Styrofan® D 422

(ID no. 30041944/SDS_GEN_DE/EN)

Date of print 14.10.2025

H361d	Suspected of damaging the unborn child.
H413	May cause long lasting harmful effects to aquatic life.
H318	Causes serious eye damage.
H315	Causes skin irritation.
H330	Fatal if inhaled.
H302	Harmful if swallowed.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H301	Toxic if swallowed.
H314	Causes severe skin burns and eye damage.
H310 + H330	Fatal in contact with skin or if inhaled.
EUH071	Corrosive to the respiratory tract.

Abbreviations

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road. ADN = The European Agreement concerning the International Carriage of Dangerous Goods by Inland waterways. ATE = Acute Toxicity Estimates. CAO = Cargo Aircraft Only. CAS = Chemical Abstract Service. CLP = Classification, Labelling and Packaging of substances and mixtures. DIN = German national organization for standardization. DNEL = Derived No Effect Level. EC50 = Effective concentration median for 50% of the population, EC = European Community, EN = European Standards. IARC = International Agency for Research on Cancer. IATA = International Air Transport Association. IBC-Code = Intermediate Bulk Container code. IMDG = International Maritime Dangerous Goods Code. ISO = International Organization for Standardization. STEL = Short-Term Exposure Limit. LC50 = Lethal concentration median for 50% of the population. LD50 = Lethal dose median for 50% of the population. TLV = Threshold Limit Value. MARPOL = The International Convention for the Prevention of Pollution from Ships. NEN = Dutch Norm. NOEC = No Observed Effect Concentration. OEL = Occupational Exposure Limit. OECD = Organization for Economic Cooperation and Development. PBT = Persistent, Bioaccumulative and Toxic. PNEC = Predicted No Effect Level. PPM = Parts per million. RID = The European Agreement concerning the International Carriage of Dangerous Goods by Rail. TWA = Time Weight Average. UN-number = UN number at transport. vPvB = very Persistent and very Bioaccumulative.

The data contained in this safety data sheet are based on our current knowledge and experience and describe the product only with regard to safety requirements. This safety data sheet is neither a Certificate of Analysis (CoA) nor technical data sheet and shall not be mistaken for a specification agreement. Identified uses in this safety data sheet do neither represent an agreement on the corresponding contractual quality of the substance/mixture nor a contractually designated use. It is the responsibility of the recipient of the product to ensure any proprietary rights and existing laws and legislation are observed.

Vertical lines in the left hand margin indicate an amendment from the previous version.