

Acronal[®] NX 4787

Chemical Nature

Aqueous styrene-acrylate copolymer dispersion for the manufacture of ceramic tile adhesives

Properties

Typical Properties

Solids content	%	~ 50.0
Viscosity at 23 °C (Brookfield RV, Spindle #2, at 20 rpm)	cps	900 – 1600
pH		~ 8.0

Other properties of the dispersion

Density at 23 °C	g/cm ³	1.04
Type of dispersion		anionic
Freeze/thaw stability		not stable

Properties of the film

* The above values should not be taken as specification.

Application

Features

Acronal NX 4787 is an APEO-free, low odor, aqueous copolymer dispersion for the manufacture of coatings, ceramic tile mastics, primers and other construction adhesives.

Acronal NX 4787 exhibits superior water resistance, strength and adhesion to mineral substrates. This polymer is also deodorized to reduce the volatile organic compounds (VOC), enabling the compounder to formulate environmentally friendly adhesives.

Processing

Although Acronal NX 4787 is protected from attack by microorganisms, preservatives must be added to the produced formulations in order to ensure that their quality remains unimpaired over long storage periods. Prior experiment is essential for checking their compatibility and efficiency.

With its low viscosity, Acronal NX 4787 is also well suited for applications such as paper and architectural coatings.

Safety

General

The usual safety precautions when handling chemicals must be observed. These include the measures described in Federal, State and Local health and safety regulations, thorough ventilation of the workplace, good skin care and wearing of protective goggles.

Safety Data Sheet

All safety information is provided in the Safety Data Sheet for Acronal NX 4787.

Storage

Please refer to the "Handling and Storage of Polymer Dispersions" brochure.

Important

The descriptions, designs, and data contained herein are presented for your guidance only. Because there are many factors under your control which may affect processing or application/use it is necessary for you to make appropriate tests to determine whether the product is suitable for your particular purpose prior to use. **NO WARRANTIES OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, OR DATA MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, DATA OR DESIGNS PROVIDED BE PRESUMED TO BE A PART OF OUR TERMS AND CONDITIONS OF SALE.** Further, you expressly understand and agree that the descriptions, designs, and data furnished by BASF hereunder are given gratis and BASF assumes no obligation or liability for same or results obtained from use thereof, all such being given to you and accepted by you at your risk.

Acronal is a registered trademark of BASF Group.

© BASF Corporation, 2025



BASF Corporation is fully committed to the Responsible Care® initiative in the USA, Canada, and Mexico.

For more information on Responsible Care® go to:

U.S.: www.basf.us/responsiblecare_usa

Canada: www.basf.us/responsiblecare_canada

México: www.basf.us/responsiblecare_mexico

BASF Corporation
Dispersions and Resins
11501 Steele Creek Road
Charlotte, North Carolina 28273
Phone: (800) 251 – 0612
Email: CustCare-Charlotte@basf.com
Email: edtech-info@basf.com
www.basf.us/formulation-additives