

Safety data sheet

Page: 1/45

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 14.05.2025

Version: 14.0

Date / Previous version: 03.11.2023

Previous version: 13.0

Product: **NA-ETHYLATE SOL. 21 %**

(ID no. 30036708/SDS_GEN_GB/EN)

Date of print 21.10.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

NA-ETHYLATE SOL. 21 %

UFI: U8JU-MFES-N009-PPER

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses: Chemical

Recommended use: Raw material, process chemical, initial product for chemical syntheses

For the detailed identified uses of the product see appendix of the safety data sheet.

1.3. Details of the supplier of the safety data sheet

Company:

BASF SE
67056 Ludwigshafen
GERMANY

Contact address:

BASF plc
4th and 5th Floors, 2 Stockport Exchange
Railway Road, Stockport, SK1 3GG
UNITED KINGDOM

Telephone: +44 161 475 3000

E-mail address: product-safety-uk-and-ireland@basf.com

1.4. Emergency telephone number

International emergency number:

Telephone: +49 180 2273-112

SECTION 2: Hazards Identification

2.1. Classification of the substance or mixture

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 14.05.2025

Version: 14.0

Date / Previous version: 03.11.2023

Previous version: 13.0

Product: **NA-ETHYLATE SOL. 21 %**

(ID no. 30036708/SDS_GEN_GB/EN)

Date of print 21.10.2025

For the classification of the mixture the following methods have been applied: extrapolation on the concentration levels of the hazardous substances, on basis of test results and after evaluation of experts. The methodologies used are mentioned at the respective test results.

According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567

Flam. Liq. 3	H226 Flammable liquid and vapour.
Met. Corr. 1	H290 May be corrosive to metals.
Skin Corr. 1A	H314 Causes severe skin burns and eye damage.
Eye Dam. 1	H318 Causes serious eye damage.

For the classifications not written out in full in this section the full text can be found in section 16.

2.2. Label elements

According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567

Pictogram:



Signal Word:

Danger

Hazard Statement:

H226	Flammable liquid and vapour.
H290	May be corrosive to metals.
H314	Causes severe skin burns and eye damage.

Precautionary Statements (Prevention):

P280	Wear protective gloves, protective clothing and eye protection or face protection.
------	--

Precautionary Statements (Response):

P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER or physician.
P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.

Precautionary Statements (Storage):

P405	Store locked up.
------	------------------

Precautionary Statements (Disposal):

P501	Dispose of contents and container to hazardous or special waste collection point.
------	---

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 14.05.2025

Version: 14.0

Date / Previous version: 03.11.2023

Previous version: 13.0

Product: **NA-ETHYLATE SOL. 21 %**

(ID no. 30036708/SDS_GEN_GB/EN)

Date of print 21.10.2025

Hazard determining component(s) for labelling: sodium ethanolate

2.3. Other hazards

According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

Possible risk by inhalation of aerosols.

The product does not contain a substance above legal limits fulfilling the PBT (persistent/bioaccumulative/toxic) criteria or the vPvB (very persistent/very bioaccumulative) criteria.

SECTION 3: Composition/Information on Ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Chemical nature

Preparation based on: sodium ethanolate, ethanol

Hazardous ingredients (GHS)

ethanol

Content (W/W): $\geq 75\%$ - $\leq 100\%$	Flam. Liq. 2
CAS Number: 64-17-5	Eye Irrit. 2
EC-Number: 200-578-6	H225, H319
REACH registration number: 01-2119457610-43	<u>Specific concentration limit:</u>
INDEX-Number: 603-002-00-5	Eye Dam./Irrit. 2: $\geq 50\%$

sodium ethanolate

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 14.05.2025

Version: 14.0

Date / Previous version: 03.11.2023

Previous version: 13.0

Product: **NA-ETHYLATE SOL. 21 %**

(ID no. 30036708/SDS_GEN_GB/EN)

Date of print 21.10.2025

<p>Content (W/W): $\geq 15\%$ - $< 25\%$ CAS Number: 141-52-6 EC-Number: 205-487-5 REACH registration number: 01-2119972296-27 INDEX-Number: 603-041-00-8</p>	<p>Flam. Sol. 1 Self-heat. 1 Acute Tox. 4 (oral) Eye Dam. 1 Skin Corr. 1B H228, H251, H314, H302 EUH014 EUH071</p>
--	---

Differing classification according to current knowledge and the criteria given in Annex I of Regulation (EC) No. 1272/2008

Flam. Sol. 1
Self-heat. 1
Skin Corr. 1A
Eye Dam. 1
Acute Tox. 4 (oral)
EUH014
EUH071

sodium hydroxide

<p>Content (W/W): $\geq 0.2\%$ - $< 1\%$ CAS Number: 1310-73-2 EC-Number: 215-185-5 REACH registration number: 01-2119457892-27 INDEX-Number: 011-002-00-6</p>	<p>Met. Corr. 1 Skin Corr. 1A Eye Dam. 1 H290, H314</p> <p><u>Specific concentration limit:</u> Eye Irrit. 2: $0.5 - < 2\%$ Skin Corr. 1B: $2 - < 5\%$ Skin Corr. 1A: $\geq 5\%$ Skin Irrit. 2: $0.5 - < 2\%$</p>
---	---

For the classifications not written out in full in this section, including the hazard classes and the hazard statements, the full text is listed in section 16.

SECTION 4: First-Aid Measures

4.1. Description of first aid measures

First aid personnel should pay attention to their own safety. Immediately remove contaminated clothing. If the patient is likely to become unconscious, place and transport in stable sideways position (recovery position).

If inhaled:

Keep patient calm, remove to fresh air, seek medical attention.

On skin contact:

Immediately wash thoroughly with plenty of water, apply sterile dressings, consult a skin specialist.

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 14.05.2025

Version: 14.0

Date / Previous version: 03.11.2023

Previous version: 13.0

Product: **NA-ETHYLATE SOL. 21 %**

(ID no. 30036708/SDS_GEN_GB/EN)

Date of print 21.10.2025

On contact with eyes:

Immediately wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.

On ingestion:

Immediately rinse mouth and then drink 200 - 300 ml water, do not induce vomiting, seek medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms: skin corrosion, Eye irritation

Hazards: No hazard is expected under intended use and appropriate handling.

4.3. Indication of any immediate medical attention and special treatment needed

Treatment: Treat according to symptoms (decontamination, vital functions), no known specific antidote.

SECTION 5: Fire-Fighting Measures

5.1. Extinguishing media

Suitable extinguishing media:

dry powder, Dry sand, alcohol-resistant foam

Unsuitable extinguishing media for safety reasons:

water, carbon dioxide

5.2. Special hazards arising from the substance or mixture

Advice: Risk of exothermic reaction.

5.3. Advice for fire-fighters

Special protective equipment:

Wear self-contained breathing apparatus and chemical-protective clothing.

Further information:

Vapours are heavier than air and may accumulate in low areas and travel a considerable distance up to the source of ignition. Collect contaminated extinguishing water separately, do not allow to reach sewage or effluent systems. Sealed containers should be protected against heat as this results in pressure build-up.

SECTION 6: Accidental Release Measures

Release of substance/product can cause fire or explosion.

6.1. Personal precautions, protective equipment and emergency procedures

Sources of ignition should be kept well clear. Use personal protective clothing. Avoid inhalation. Avoid contact with skin and eyes.

6.2. Environmental precautions

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 14.05.2025

Version: 14.0

Date / Previous version: 03.11.2023

Previous version: 13.0

Product: **NA-ETHYLATE SOL. 21 %**

(ID no. 30036708/SDS_GEN_GB/EN)

Date of print 21.10.2025

Do not discharge into drains/surface waters/groundwater. Contain contaminated water/firefighting water.

6.3. Methods and material for containment and cleaning up

For large amounts: Pump off product.

For residues: Pick up with suitable absorbent material (e.g. sand, sawdust, general-purpose binder, kieselguhr). Dispose of absorbed material in accordance with regulations.

6.4. Reference to other sections

Information regarding exposure controls/personal protection and disposal considerations can be found in section 8 and 13.

SECTION 7: Handling and Storage

7.1. Precautions for safe handling

Ensure thorough ventilation of stores and work areas. Protect against moisture. Protect against heat.

Protection against fire and explosion:

Avoid all sources of ignition: heat, sparks, open flame. Take precautionary measures against static discharges. Use antistatic tools. Render equipment and apparatus inert (nitrogen, inert gases) and ground before putting into operation. Fire extinguishers should be kept handy.

7.2. Conditions for safe storage, including any incompatibilities

Segregate from acids and acid forming substances. Keep away from water.

Suitable materials for containers: Carbon steel (Iron), Stainless steel 1.4401, Stainless steel 1.4301 (V2), High density polyethylene (HDPE), Low density polyethylene (LDPE), enamelled, glass
Further information on storage conditions: Keep container tightly closed in a cool, well-ventilated place. Keep under dry nitrogen. Protect against moisture. Protect against heat. Keep away from sources of ignition - No smoking.

Protect from temperatures below: 0 °C

The product crystallizes below the limit temperature.

7.3. Specific end use(s)

See exposure scenario(s) in the attachment to this safety data sheet.

SECTION 8: Exposure Controls/Personal Protection

8.1. Control parameters

Components with occupational exposure limits

64-17-5: ethanol

TWA value 1,920 mg/m³ ; 1,000 ppm (WEL/EH 40 (UK))

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 14.05.2025

Version: 14.0

Date / Previous version: 03.11.2023

Previous version: 13.0

Product: **NA-ETHYLATE SOL. 21 %**

(ID no. 30036708/SDS_GEN_GB/EN)

Date of print 21.10.2025

1310-73-2: sodium hydroxide

STEL value 2 mg/m³ (WEL/EH 40 (UK))

Ceiling limit value/factor: 15 min

Components with PNEC

64-17-5: ethanol

freshwater: 0.96 mg/l

marine water: 0.79 mg/l

intermittent release: 2.75 mg/l

STP: 580 mg/l

sediment (freshwater): 3.6 mg/kg

soil: 0.63 mg/kg

sediment (marine water): 2.9 mg/kg

oral (secondary poisoning): 0.38 mg/kg

141-52-6: sodium ethanolate

freshwater: 0.96 mg/l

marine water: 0.79 mg/l

intermittent release: 2.75 mg/l

STP: 584 mg/l

sediment (freshwater): 3.6 mg/kg

sediment (marine water): 2.9 mg/kg

soil: 0.63 mg/kg

oral (secondary poisoning): 0.38 g/kg

Components with DNEL

64-17-5: ethanol

worker: Long-term exposure- systemic effects, dermal: 343 mg/kg

worker: Long-term exposure- systemic effects, Inhalation: 950 mg/m³

141-52-6: sodium ethanolate

worker: Long-term exposure - systemic and local effects, Inhalation: 1 mg/m³

8.2. Exposure controls

Personal protective equipment

Respiratory protection:

Wear respiratory protection if ventilation is inadequate. Gas filter for gases/vapours of organic compounds (boiling point >65 °C, e. g. EN 14387 Type A)

Hand protection:

Chemical resistant protective gloves (EN ISO 374-1)

Suitable materials also with prolonged, direct contact (Recommended: Protective index 6, corresponding > 480 minutes of permeation time according to EN ISO 374-1):

fluoroelastomer (FKM) - 0.7 mm coating thickness

butyl rubber (butyl) - 0.7 mm coating thickness

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 14.05.2025

Version: 14.0

Date / Previous version: 03.11.2023

Previous version: 13.0

Product: **NA-ETHYLATE SOL. 21 %**

(ID no. 30036708/SDS_GEN_GB/EN)

Date of print 21.10.2025

Suitable materials for short-term contact (recommended: At least protective index 2, corresponding > 30 minutes of permeation time according to EN ISO 374-1)

nitrile rubber (NBR) - 0.4 mm coating thickness

polyvinylchloride (PVC) - 0.7 mm coating thickness

chloroprene rubber (CR) - 0.5 mm coating thickness

Supplementary note: The specifications are based on tests, literature data and information of glove manufacturers or are derived from similar substances by analogy. Due to many conditions (e.g. temperature) it must be considered, that the practical usage of a chemical-protective glove in practice may be much shorter than the permeation time determined through testing.

Manufacturer's directions for use should be observed because of great diversity of types.

Eye protection:

Safety glasses with side-shields (frame goggles) (f.e. EN 166) and face shield

Body protection:

Body protection must be chosen depending on activity and possible exposure, e.g. apron, protecting boots, chemical-protection suit (according to EN 14605 in case of splashes or EN ISO 13982 in case of dust).

General safety and hygiene measures

Avoid contact with the skin, eyes and clothing. Do not breathe vapour/spray. Handle in accordance with good industrial hygiene and safety practice.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Form:	liquid	
Colour:	yellow to brown	
Odour:	perceptible, of ethanol	
Odour threshold:	Not determined due to potential health hazard by inhalation.	
pH value:	approx. 11	(ISO 1148)
crystallization temperature:	-5 °C	
Boiling point:	approx. 91 °C	
Flash point:	23 °C	(DIN 51755)
Evaporation rate:	not determined, Value can be approximated from Henry's Law Constant or vapor pressure.	
Flammability:	Flammable liquid and vapour.	(other)
Lower explosion limit:	2.6 %(V) Information applies to the solvent.	(DIN 51649-1)
Upper explosion limit:	For liquids not relevant for classification and labelling. 19.0 %(V) Information applies to the solvent.	(DIN 51649-1)

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 14.05.2025

Version: 14.0

Date / Previous version: 03.11.2023

Previous version: 13.0

Product: **NA-ETHYLATE SOL. 21 %**

(ID no. 30036708/SDS_GEN_GB/EN)

Date of print 21.10.2025

	For liquids not relevant for classification and labelling.	
Ignition temperature:	420 °C	(DIN 51794)
Vapour pressure:	approx. 31 mbar (20 °C)	(measured)
	approx. 165 mbar (50 °C)	(measured)
Density:	0.878 g/cm ³ (20 °C)	(ISO 2811-3)
	0.855 g/cm ³ (50 °C)	(ISO 2811-3)
Relative vapour density (air):	combustible vapours	
Solubility in water:	hydrolyzes (20 °C)	
Partitioning coefficient n-octanol/water (log K _{ow}):	not applicable	
<i>Information on: ethanol</i>		
Partitioning coefficient n-octanol/water (log K _{ow}):	-0.31 (25 °C)	(measured)
	Literature data.	

Self ignition:	not self-igniting	
Thermal decomposition:	It is not a self-decompositionable substance.	
Viscosity, dynamic:	24 mPa.s (20 °C)	(DIN 51562)
Viscosity, kinematic:	approx. 27 mm ² /s (20 °C)	
Explosion hazard:	not explosive	
Fire promoting properties:	not fire-propagating	

9.2. Other information

Hygroscopy:	hygroscopic
Grain size distribution:	The substance / product is marketed or used in a non solid or granular form.

SECTION 10: Stability and Reactivity

10.1. Reactivity

Corrosion to metals: Corrosive effect on: Aluminium

10.2. Chemical stability

The product is stable if stored and handled as prescribed/indicated.

10.3. Possibility of hazardous reactions

Exothermic reaction. Reacts with water and acids.

10.4. Conditions to avoid

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 14.05.2025

Version: 14.0

Date / Previous version: 03.11.2023

Previous version: 13.0

Product: **NA-ETHYLATE SOL. 21 %**

(ID no. 30036708/SDS_GEN_GB/EN)

Date of print 21.10.2025

Avoid all sources of ignition: heat, sparks, open flame. Avoid contact with air. Avoid moisture.

10.5. Incompatible materials

Substances to avoid:
water, acids

10.6. Hazardous decomposition products

Hazardous decomposition products:
sodium hydroxide, ethanol

SECTION 11: Toxicological Information

11.1. Information on toxicological effects

Acute toxicity

Assessment of acute toxicity:
The toxicity of the product is based on its corrosivity.

Experimental/calculated data:
rat (by inhalation): 8 h (IRT)

No mortality within the stated exposition time as shown in animal studies. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Information on: ethanol

Assessment of acute toxicity:

Virtually nontoxic after a single ingestion. Virtually nontoxic by inhalation.

Irritation

Assessment of irritating effects:
The break through time determined in the in-vitro membrane barrier test indicates that the test substance is expected to cause skin necrosis in vivo within 14 days after a 1-hour exposure.

Experimental/calculated data:
Skin corrosion/irritation
: Corrosive. (OECD Guideline 435)

Serious eye damage/irritation
rabbit: irreversible damage (BASF-Test)

The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Information on: sodium hydroxide

Assessment of irritating effects:

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 14.05.2025

Version: 14.0

Date / Previous version: 03.11.2023

Previous version: 13.0

Product: **NA-ETHYLATE SOL. 21 %**

(ID no. 30036708/SDS_GEN_GB/EN)

Date of print 21.10.2025

Highly corrosive! Damages skin and eyes.

Information on: sodium hydroxide

Experimental/calculated data:

Skin corrosion/irritation

rabbit: Corrosive.

Data refer to a diluted aqueous solution of the substance.

Respiratory/Skin sensitization

Experimental/calculated data:

Non-sensitizing. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Information on: ethanol

Assessment of sensitization:

Skin sensitizing effects were not observed in animal studies.

Germ cell mutagenicity

Information on: ethanol

Assessment of mutagenicity:

The substance was not mutagenic in bacteria. The substance was not mutagenic in mammalian cell culture. The substance was not mutagenic in a test with mammals.

Information on: sodium methanolate

Assessment of mutagenicity:

The substance was not mutagenic in bacteria. The substance was not mutagenic in mammalian cell culture. The substance was not mutagenic in a test with mammals. The product has not been fully tested. The statements have been derived in parts from products of a similar structure or composition.

Carcinogenicity

Information on: ethanol

Assessment of carcinogenicity:

The International Agency for Research on Cancer (IARC) has classified this substance as a Group 1 (known) human carcinogen. The whole of the information assessable provides no indication of a carcinogenic effect.

Information on: sodium ethanolate

Assessment of carcinogenicity:

The whole of the information assessable provides no indication of a carcinogenic effect.

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 14.05.2025

Version: 14.0

Date / Previous version: 03.11.2023

Previous version: 13.0

Product: **NA-ETHYLATE SOL. 21 %**

(ID no. 30036708/SDS_GEN_GB/EN)

Date of print 21.10.2025

Reproductive toxicity

Information on: sodium ethanolate

Assessment of reproduction toxicity:

The results of animal studies suggest a fertility impairing effect with high doses. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Information on: ethanol

Assessment of reproduction toxicity:

The potential to impair fertility cannot be excluded when given at high doses.

Developmental toxicity

Information on: ethanol

Assessment of teratogenicity:

At high doses there are indications of a developmental effect.

Specific target organ toxicity (single exposure)

No data available.

Repeated dose toxicity and Specific target organ toxicity (repeated exposure)

Information on: ethanol

Assessment of repeated dose toxicity:

The substance may cause damage to the liver after repeated ingestion. Repeated inhalative uptake of the substance did not cause substance-related effects. The substance may cause damage to the peripheral nervous system after repeated ingestion of high doses. The substance may cause damage to the central nervous system after repeated ingestion of high doses. Based on the chemical structure a neurotoxic effect by repeated administration cannot be excluded.

Aspiration hazard

No data available.

SECTION 12: Ecological Information

12.1. Toxicity

Information on: sodium hydroxide

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 14.05.2025

Version: 14.0

Date / Previous version: 03.11.2023

Previous version: 13.0

Product: **NA-ETHYLATE SOL. 21 %**

(ID no. 30036708/SDS_GEN_GB/EN)

Date of print 21.10.2025

Assessment of aquatic toxicity:

Depending on local conditions and existing concentrations, disturbances in the biodegradation process of activated sludge are possible. There is a high probability that the product is not acutely harmful to aquatic organisms.

The effect strongly depends on the pH-value. The data refers to the dissociated form of the substance.

Information on: ethanol

Assessment of aquatic toxicity:

There is a high probability that the product is not acutely harmful to aquatic organisms. The inhibition of the degradation activity of activated sludge is not anticipated when introduced to biological treatment plants in appropriate low concentrations.

Information on: sodium hydroxide

Toxicity to fish:

LC50 (96 h) 125 mg/l, Gambusia affinis (other, static)

The product will cause changes in the pH value of the test system. The result refers to an unneutralized sample. Literature data.

Information on: ethanol

Toxicity to fish:

LC50 (96 h) 13,000 mg/l, Salmo gairdneri, syn. O. mykiss (Fish test acute, static)

The details of the toxic effect relate to the nominal concentration. Literature data.

Information on: sodium hydroxide

Aquatic invertebrates:

EC50 (48 h) 40.4 mg/l, Ceriodaphnia sp. (other, static)

Literature data.

Information on: ethanol

Aquatic invertebrates:

LC50 (48 h) 12,340 mg/l, Daphnia magna (Daphnia test acute, static)

The details of the toxic effect relate to the nominal concentration. Literature data.

(48 h) 5,012 mg/l, Ceriodaphnia dubia (Daphnia test acute)

The details of the toxic effect relate to the nominal concentration. Literature data.

Information on: ethanol

Aquatic plants:

EC50 (4 d) 675 mg/l (growth rate), Chlorella vulgaris (Algal growth inhibition test)

The details of the toxic effect relate to the nominal concentration. Literature data.

Information on: ethanol

Microorganisms/Effect on activated sludge:

Toxic limit concentration (16 h) 6,500 mg/l, Pseudomonas putida (other, aquatic)

The details of the toxic effect relate to the nominal concentration. Literature data.

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 14.05.2025

Version: 14.0

Date / Previous version: 03.11.2023

Previous version: 13.0

Product: **NA-ETHYLATE SOL. 21 %**

(ID no. 30036708/SDS_GEN_GB/EN)

Date of print 21.10.2025

12.2. Persistence and degradability

Assessment biodegradation and elimination (H₂O):

The product is unstable in water. The elimination data also refer to products of hydrolysis. The organic component of the product is biodegradable.

Information on: sodium hydroxide

Assessment biodegradation and elimination (H₂O):

Inorganic product which cannot be eliminated from water by biological purification processes.

Information on: ethanol

Assessment biodegradation and elimination (H₂O):

Readily biodegradable (according to OECD criteria).

Information on: ethanol

Elimination information:

89 % BOD of the ThOD (14 d) (OECD 301C; ISO 9408; 92/69/EEG, C.4-F) (aerobic, Inoculum conforming to MITI requirements (OECD 301C))

Literature data.

84 % BOD of the ThOD (20 d) (other) (aerobic, activated sludge, domestic, non-adapted)

Literature data.

12.3. Bioaccumulative potential

Information on: ethanol

Assessment bioaccumulation potential:

No significant accumulation in organisms is expected as a result of the distribution coefficient of n-octanol/water (log Pow).

12.4. Mobility in soil

Assessment transport between environmental compartments:

Adsorption in soil: Due to the product characteristics the test is impossible.

12.5. Results of PBT and vPvB assessment

The product does not fulfill the criteria for PBT (Persistent/bioaccumulative/toxic) and vPvB (very persistent/very bioaccumulative).

12.6. Other adverse effects

The product does not contain substances that are listed in Regulation (EC) 1005/2009 on substances that deplete the ozone layer.

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 14.05.2025

Version: 14.0

Date / Previous version: 03.11.2023

Previous version: 13.0

Product: **NA-ETHYLATE SOL. 21 %**

(ID no. 30036708/SDS_GEN_GB/EN)

Date of print 21.10.2025

12.7. Additional information

Other ecotoxicological advice:

Due to the pH-value of the product, neutralization is generally required before discharging sewage into treatment plants. The inhibition of the degradation activity of activated sludge is not anticipated when introduced to biological treatment plants in appropriate low concentrations. Do not release untreated into natural waters.

SECTION 13: Disposal Considerations

13.1. Waste treatment methods

Obtain the consent of pollution control authorities before discharging to wastewater treatment plants.

The UK Environmental Protection (Duty of Care) Regulations (EP) and amendments should be noted (United Kingdom).

This product and any uncleaned containers must be disposed of as hazardous waste in accordance with the 2005 Hazardous Waste Regulations and amendments (United Kingdom)

Contaminated packaging:

Contaminated packaging should be emptied as far as possible; then it can be passed on for recycling after being thoroughly cleaned.

SECTION 14: Transport Information

Land transport

ADR

UN number or ID number: UN2920
UN proper shipping name: CORROSIVE LIQUID, FLAMMABLE, N.O.S. (contains SODIUM ETHYLATE/SODIUM ETHANOLATE, ETHANOL)
Transport hazard class(es): 8, 3
Packing group: II
Environmental hazards: no
Special precautions for user: Tunnel code: D/E

RID

UN number or ID number: UN2920
UN proper shipping name: CORROSIVE LIQUID, FLAMMABLE, N.O.S. (contains SODIUM ETHYLATE/SODIUM ETHANOLATE, ETHANOL)
Transport hazard class(es): 8, 3
Packing group: II
Environmental hazards: no

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 14.05.2025

Version: 14.0

Date / Previous version: 03.11.2023

Previous version: 13.0

Product: **NA-ETHYLATE SOL. 21 %**

(ID no. 30036708/SDS_GEN_GB/EN)

Date of print 21.10.2025

Special precautions for user: None known

Inland waterway transport

ADN

UN number or ID number: UN2920
UN proper shipping name: CORROSIVE LIQUID, FLAMMABLE, N.O.S. (contains SODIUM ETHYLATE/SODIUM ETHANOLATE, ETHANOL)
Transport hazard class(es): 8, 3
Packing group: II
Environmental hazards: no
Special precautions for user: None known

Transport in inland waterway vessel

Not evaluated

Sea transport

IMDG

UN number or ID number: UN 2920
UN proper shipping name: CORROSIVE LIQUID, FLAMMABLE, N.O.S. (contains SODIUM ETHYLATE/SODIUM ETHANOLATE, ETHANOL)
Transport hazard class(es): 8, 3
Packing group: II
Environmental hazards: no
Marine pollutant: NO
Special precautions for user:

Air transport

IATA/ICAO

UN number or ID number: UN 2920
UN proper shipping name: CORROSIVE LIQUID, FLAMMABLE, N.O.S. (contains SODIUM ETHYLATE/SODIUM ETHANOLATE, ETHANOL)
Transport hazard class(es): 8, 3
Packing group: II
Environmental hazards: No Mark as dangerous for the environment is needed
Special precautions for user: None known

14.1. UN number or ID number

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 14.05.2025

Version: 14.0

Date / Previous version: 03.11.2023

Previous version: 13.0

Product: **NA-ETHYLATE SOL. 21 %**

(ID no. 30036708/SDS_GEN_GB/EN)

Date of print 21.10.2025

See corresponding entries for "UN number or ID number" for the respective regulations in the tables above.

14.2. UN proper shipping name

See corresponding entries for "UN proper shipping name" for the respective regulations in the tables above.

14.3. Transport hazard class(es)

See corresponding entries for "Transport hazard class(es)" for the respective regulations in the tables above.

14.4. Packing group

See corresponding entries for "Packing group" for the respective regulations in the tables above.

14.5. Environmental hazards

See corresponding entries for "Environmental hazards" for the respective regulations in the tables above.

14.6. Special precautions for user

See corresponding entries for "Special precautions for user" for the respective regulations in the tables above.

14.7. Maritime transport in bulk according to IMO instruments

Maritime transport in bulk is not intended.

Further information

This product is subject to the most recent edition of "The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment Regulations" and their amendments (United Kingdom).

SECTION 15: Regulatory Information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Prohibitions, Restrictions and Authorizations

UK REACH SI, Annex XVII, Marketing and Use Restrictions
Number on List: 3

UK REACH SI, Annex XVII, Marketing and Use Restrictions
Number on List: 40

Directive 2012/18/EU - Control of Major Accident Hazards involving dangerous substances (EU):
List entry in regulation: P5c
Classification applies for standard conditions of temperature and pressure.

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 14.05.2025

Version: 14.0

Date / Previous version: 03.11.2023

Previous version: 13.0

Product: **NA-ETHYLATE SOL. 21 %**

(ID no. 30036708/SDS_GEN_GB/EN)

Date of print 21.10.2025

The data should be considered when making any assessment under the Control of Substances Hazardous to Health Regulations (COSHH), and related guidance, for example, 'COSHH Essentials' (United Kingdom).

This product may be subject to the Control of Major Accident Hazards Regulations (COMAH), and amendments if specific threshold tonnages are exceeded (United Kingdom).

If other regulatory information applies that is not already provided elsewhere in this safety data sheet, then it is described in this subsection.

The product contains a substance (Schedule 1A) regulated under United Kingdom Poisons Act 1972. This may result in obligations for your company according to the statutory requirements of the aforementioned regulation and the respective national implementing regulations.

15.2. Chemical Safety Assessment

Chemical Safety Assessment performed

SECTION 16: Other Information

Full text of the classifications, including the hazard classes and the hazard statements, if mentioned in section 2 or 3:

Flam. Liq.	Flammable liquids
Met. Corr.	Corrosive to metals
Skin Corr.	Skin corrosion
Eye Dam.	Serious eye damage
Eye Irrit.	Eye irritation
Flam. Sol.	Flammable solids
Self-heat.	Self-heating substances and mixtures
Acute Tox.	Acute toxicity
Eye Dam./Irrit.	Serious eye damage/eye irritation
Skin Irrit.	Skin irritation
H226	Flammable liquid and vapour.
H290	May be corrosive to metals.
H314	Causes severe skin burns and eye damage.
H225	Highly flammable liquid and vapour.
H319	Causes serious eye irritation.
H228	Flammable solid.
H251	Self-heating: may catch fire.
H302	Harmful if swallowed.
EUH014	Reacts violently with water.
EUH071	Corrosive to the respiratory tract.

Abbreviations

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road.
 ADN = The European Agreement concerning the International Carriage of Dangerous Goods by Inland waterways. ATE = Acute Toxicity Estimates. CAO = Cargo Aircraft Only. CAS = Chemical Abstract Service. CLP = Classification, Labelling and Packaging of substances and mixtures. DIN = German

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 14.05.2025

Version: 14.0

Date / Previous version: 03.11.2023

Previous version: 13.0

Product: **NA-ETHYLATE SOL. 21 %**

(ID no. 30036708/SDS_GEN_GB/EN)

Date of print 21.10.2025

national organization for standardization. DNEL = Derived No Effect Level. EC50 = Effective concentration median for 50% of the population. EC = European Community. EN = European Standards. IARC = International Agency for Research on Cancer. IATA = International Air Transport Association. IBC-Code = Intermediate Bulk Container code. IMDG = International Maritime Dangerous Goods Code. ISO = International Organization for Standardization. STEL = Short-Term Exposure Limit. LC50 = Lethal concentration median for 50% of the population. LD50 = Lethal dose median for 50% of the population. TLV = Threshold Limit Value. MARPOL = The International Convention for the Prevention of Pollution from Ships. NEN = Dutch Norm. NOEC = No Observed Effect Concentration. OEL = Occupational Exposure Limit. OECD = Organization for Economic Cooperation and Development. PBT = Persistent, Bioaccumulative and Toxic. PNEC = Predicted No Effect Level. PPM = Parts per million. RID = The European Agreement concerning the International Carriage of Dangerous Goods by Rail. TWA = Time Weight Average. UN-number = UN number at transport. vPvB = very Persistent and very Bioaccumulative.

The data contained in this safety data sheet are based on our current knowledge and experience and describe the product only with regard to safety requirements. This safety data sheet is neither a Certificate of Analysis (CoA) nor technical data sheet and shall not be mistaken for a specification agreement. Identified uses in this safety data sheet do neither represent an agreement on the corresponding contractual quality of the substance/mixture nor a contractually designated use. It is the responsibility of the recipient of the product to ensure any proprietary rights and existing laws and legislation are observed.

Vertical lines in the left hand margin indicate an amendment from the previous version.

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 14.05.2025

Version: 14.0

Date / Previous version: 03.11.2023

Previous version: 13.0

Product: **NA-ETHYLATE SOL. 21 %**

(ID no. 30036708/SDS_GEN_GB/EN)

Date of print 21.10.2025

Annex: Exposure Scenarios

Index

1. Manufacture of substance, Formulation of solutions

IS; IS; ERC1; PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC9, PROC15

2. Formulation & (re)packing of substances and mixtures, (liquid products)

IS; IS; ERC2; PROC3, PROC8a, PROC8b, PROC9, PROC15

3. Use in chemical synthesis, (liquid products)

IS; IS; ERC4, ERC6b; PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC9, PROC15

4. Use as an intermediate

IS; IS; ERC6b; PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC9, PROC15

5. Use in laboratories, Use as laboratory reagent/agent

PW; PW; ERC8a, ERC8b; PROC15

1. Short title of exposure scenario

Manufacture of substance, Formulation of solutions

IS; IS; ERC1; PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC9, PROC15

Control of exposure and risk management measures

Contributing exposure scenario	
Use descriptors covered	ERC1: Manufacture of the substance As no environmental hazard was identified no environmental-related exposure assessment and risk characterization was performed.
Operational conditions	
Contributing exposure scenario	
Use descriptors covered	PROC1: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions. Use domain: industrial
Operational conditions	
Concentration of the substance	sodium ethanolate Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	0.000275 Pa
Process temperature	20 °C

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 14.05.2025

Version: 14.0

Date / Previous version: 03.11.2023

Previous version: 13.0

Product: **NA-ETHYLATE SOL. 21 %**

(ID no. 30036708/SDS_GEN_GB/EN)

Date of print 21.10.2025

Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Avoid skin contact. Supervision in place to check that the RMMs in place are being used correctly and OCs followed. Avoid contact with eyes. Provide specific employee training to prevent/minimize exposures. Avoid frequent and direct contact with substance.	
Wear suitable working clothes.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	0.0284 mg/m ³
Risk Characterization Ratio (RCR)	0.028354
Assessment method	Qualitative assessment
	Worker - dermal
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra Please note that a modified version has been used (see exposure estimates)	

Contributing exposure scenario	
Use descriptors covered	PROC2: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions Use domain: industrial
Operational conditions	
Concentration of the substance	sodium ethanolate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	0.000275 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Avoid skin contact. Supervision in place to check that the RMMs in place are being used correctly and OCs followed. Avoid contact with eyes. Provide specific employee training to prevent/minimize exposures. Avoid frequent and direct contact with	

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 14.05.2025

Version: 14.0

Date / Previous version: 03.11.2023

Previous version: 13.0

Product: **NA-ETHYLATE SOL. 21 %**

(ID no. 30036708/SDS_GEN_GB/EN)

Date of print 21.10.2025

substance.	
Wear suitable working clothes., Use suitable chemically resistant gloves.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	0.2835 mg/m ³
Risk Characterization Ratio (RCR)	0.283543
Assessment method	Qualitative assessment
	Worker - dermal
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra Please note that a modified version has been used (see exposure estimates)	

Contributing exposure scenario	
Use descriptors covered	PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition Use domain: industrial
Operational conditions	
Concentration of the substance	sodium ethanolate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	0.000275 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Avoid skin contact. Supervision in place to check that the RMMs in place are being used correctly and OCs followed. Avoid contact with eyes. Provide specific employee training to prevent/minimize exposures. Avoid frequent and direct contact with substance.	
Wear suitable working clothes., Use suitable chemically resistant gloves.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	0.2835 mg/m ³
Risk Characterization Ratio (RCR)	0.283543
Assessment method	Qualitative assessment

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 14.05.2025

Version: 14.0

Date / Previous version: 03.11.2023

Previous version: 13.0

Product: **NA-ETHYLATE SOL. 21 %**

(ID no. 30036708/SDS_GEN_GB/EN)

Date of print 21.10.2025

	Worker - dermal
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra Please note that a modified version has been used (see exposure estimates)	

Contributing exposure scenario	
Use descriptors covered	PROC4: Chemical production where opportunity for exposure arises Use domain: industrial
Operational conditions	
Concentration of the substance	sodium ethanolate Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	0.000275 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Avoid skin contact. Supervision in place to check that the RMMs in place are being used correctly and OCs followed. Avoid contact with eyes. Provide specific employee training to prevent/minimize exposures. Avoid frequent and direct contact with substance.	
Wear suitable working clothes., Use suitable chemically resistant gloves.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	0.2835 mg/m ³
Risk Characterization Ratio (RCR)	0.283543
Assessment method	Qualitative assessment
	Worker - dermal
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra Please note that a modified version has been used (see exposure estimates)	

Contributing exposure scenario	
Use descriptors covered	PROC8a: Transfer of substance or mixture (charging and discharging) at non-dedicated facilities Use domain: industrial
Operational conditions	

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 14.05.2025

Version: 14.0

Date / Previous version: 03.11.2023

Previous version: 13.0

Product: **NA-ETHYLATE SOL. 21 %**

(ID no. 30036708/SDS_GEN_GB/EN)

Date of print 21.10.2025

Concentration of the substance	sodium ethanolate Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	0.000275 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Avoid skin contact. Supervision in place to check that the RMMs in place are being used correctly and OCs followed. Avoid contact with eyes. Provide specific employee training to prevent/minimize exposures. Avoid frequent and direct contact with substance.	
Wear suitable working clothes., Use suitable chemically resistant gloves.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	0.2835 mg/m ³
Risk Characterization Ratio (RCR)	0.283543
Assessment method	Qualitative assessment
	Worker - dermal
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra Please note that a modified version has been used (see exposure estimates)	

Contributing exposure scenario	
Use descriptors covered	PROC8b: Transfer of substance or mixture (charging and discharging) at dedicated facilities Use domain: industrial
Operational conditions	
Concentration of the substance	sodium ethanolate Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	0.000275 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 14.05.2025

Version: 14.0

Date / Previous version: 03.11.2023

Previous version: 13.0

Product: **NA-ETHYLATE SOL. 21 %**

(ID no. 30036708/SDS_GEN_GB/EN)

Date of print 21.10.2025

Risk Management Measures	
Avoid skin contact. Supervision in place to check that the RMMs in place are being used correctly and OCs followed. Avoid contact with eyes. Provide specific employee training to prevent/minimize exposures. Avoid frequent and direct contact with substance.	
Wear suitable working clothes., Use suitable chemically resistant gloves.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	0.2835 mg/m ³
Risk Characterization Ratio (RCR)	0.283543
Assessment method	Qualitative assessment
	Worker - dermal
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra Please note that a modified version has been used (see exposure estimates)	

Contributing exposure scenario	
Use descriptors covered	PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing). Use domain: industrial
Operational conditions	
Concentration of the substance	sodium ethanolate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	0.000275 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Avoid skin contact. Supervision in place to check that the RMMs in place are being used correctly and OCs followed. Avoid contact with eyes. Provide specific employee training to prevent/minimize exposures. Avoid frequent and direct contact with substance.	
Wear suitable working clothes., Use suitable chemically resistant gloves.	

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 14.05.2025

Version: 14.0

Date / Previous version: 03.11.2023

Previous version: 13.0

Product: **NA-ETHYLATE SOL. 21 %**

(ID no. 30036708/SDS_GEN_GB/EN)

Date of print 21.10.2025

Exposure estimate and reference to its source	
Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	0.2835 mg/m ³
Risk Characterization Ratio (RCR)	0.283543
Assessment method	Qualitative assessment
	Worker - dermal
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra Please note that a modified version has been used (see exposure estimates)	

Contributing exposure scenario	
Use descriptors covered	PROC15: Use a laboratory reagent. Use domain: industrial
Operational conditions	
Concentration of the substance	sodium ethanolate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	0.000275 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Avoid skin contact. Supervision in place to check that the RMMs in place are being used correctly and OCs followed. Avoid contact with eyes. Provide specific employee training to prevent/minimize exposures. Avoid frequent and direct contact with substance.	
Wear suitable working clothes., Use suitable chemically resistant gloves.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	0.2835 mg/m ³
Risk Characterization Ratio (RCR)	0.283543
Assessment method	Qualitative assessment
	Worker - dermal
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra Please note that a modified version has been used (see exposure estimates)	

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 14.05.2025

Version: 14.0

Date / Previous version: 03.11.2023

Previous version: 13.0

Product: **NA-ETHYLATE SOL. 21 %**

(ID no. 30036708/SDS_GEN_GB/EN)

Date of print 21.10.2025

2. Short title of exposure scenario

Formulation & (re)packing of substances and mixtures, (liquid products)

IS; IS; ERC2; PROC3, PROC8a, PROC8b, PROC9, PROC15

Control of exposure and risk management measures

Contributing exposure scenario	
Use descriptors covered	ERC2: Formulation into mixture As no environmental hazard was identified no environmental-related exposure assessment and risk characterization was performed.
Operational conditions	
Contributing exposure scenario	
Use descriptors covered	PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition Use domain: industrial
Operational conditions	
Concentration of the substance	sodium ethanolate Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	0.000275 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Avoid skin contact. Supervision in place to check that the RMMs in place are being used correctly and OCs followed. Avoid contact with eyes. Provide specific employee training to prevent/minimize exposures. Avoid frequent and direct contact with substance.	
Wear suitable working clothes., Use suitable chemically resistant gloves.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	0.2835 mg/m ³
Risk Characterization Ratio (RCR)	0.283543

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 14.05.2025

Version: 14.0

Date / Previous version: 03.11.2023

Previous version: 13.0

Product: **NA-ETHYLATE SOL. 21 %**

(ID no. 30036708/SDS_GEN_GB/EN)

Date of print 21.10.2025

Assessment method	Qualitative assessment
	Worker - dermal
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra Please note that a modified version has been used (see exposure estimates)	

Contributing exposure scenario	
Use descriptors covered	PROC8a: Transfer of substance or mixture (charging and discharging) at non-dedicated facilities Use domain: industrial
Operational conditions	
Concentration of the substance	sodium ethanolate Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	0.000275 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Avoid skin contact. Supervision in place to check that the RMMs in place are being used correctly and OCs followed. Avoid contact with eyes. Provide specific employee training to prevent/minimize exposures. Avoid frequent and direct contact with substance.	
Wear suitable working clothes., Use suitable chemically resistant gloves.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	0.2835 mg/m ³
Risk Characterization Ratio (RCR)	0.283543
Assessment method	Qualitative assessment
	Worker - dermal
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra Please note that a modified version has been used (see exposure estimates)	

Contributing exposure scenario	
Use descriptors covered	PROC8b: Transfer of substance or mixture (charging and discharging) at dedicated facilities Use domain: industrial

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 14.05.2025

Version: 14.0

Date / Previous version: 03.11.2023

Previous version: 13.0

Product: **NA-ETHYLATE SOL. 21 %**

(ID no. 30036708/SDS_GEN_GB/EN)

Date of print 21.10.2025

Operational conditions	
Concentration of the substance	sodium ethanolate Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	0.000275 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Avoid skin contact. Supervision in place to check that the RMMs in place are being used correctly and OCs followed. Avoid contact with eyes. Provide specific employee training to prevent/minimize exposures. Avoid frequent and direct contact with substance.	
Wear suitable working clothes., Use suitable chemically resistant gloves.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	0.2835 mg/m ³
Risk Characterization Ratio (RCR)	0.283543
Assessment method	Qualitative assessment
	Worker - dermal
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra Please note that a modified version has been used (see exposure estimates)	

Contributing exposure scenario	
Use descriptors covered	PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing). Use domain: industrial
Operational conditions	
Concentration of the substance	sodium ethanolate Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	0.000275 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 14.05.2025

Version: 14.0

Date / Previous version: 03.11.2023

Previous version: 13.0

Product: **NA-ETHYLATE SOL. 21 %**

(ID no. 30036708/SDS_GEN_GB/EN)

Date of print 21.10.2025

Indoor/Outdoor	Indoor
Risk Management Measures	
Avoid skin contact. Supervision in place to check that the RMMs in place are being used correctly and OCs followed. Avoid contact with eyes. Provide specific employee training to prevent/minimize exposures. Avoid frequent and direct contact with substance.	
Wear suitable working clothes., Use suitable chemically resistant gloves.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	0.2835 mg/m ³
Risk Characterization Ratio (RCR)	0.283543
Assessment method	Qualitative assessment
	Worker - dermal
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra Please note that a modified version has been used (see exposure estimates)	

Contributing exposure scenario	
Use descriptors covered	PROC15: Use a laboratory reagent. Use domain: industrial
Operational conditions	
Concentration of the substance	sodium ethanolate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	0.000275 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Avoid skin contact. Supervision in place to check that the RMMs in place are being used correctly and OCs followed. Avoid contact with eyes. Provide specific employee training to prevent/minimize exposures. Avoid frequent and direct contact with substance.	
Wear suitable working clothes., Use suitable chemically resistant gloves.	

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 14.05.2025

Version: 14.0

Date / Previous version: 03.11.2023

Previous version: 13.0

Product: **NA-ETHYLATE SOL. 21 %**

(ID no. 30036708/SDS_GEN_GB/EN)

Date of print 21.10.2025

Exposure estimate and reference to its source	
Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	0.2835 mg/m ³
Risk Characterization Ratio (RCR)	0.283543
Assessment method	Qualitative assessment
	Worker - dermal
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra Please note that a modified version has been used (see exposure estimates)	

3. Short title of exposure scenario

Use in chemical synthesis, (liquid products)

IS; IS; ERC4, ERC6b; PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC9, PROC15

Control of exposure and risk management measures

Contributing exposure scenario	
Use descriptors covered	ERC4: Use of non-reactive processing aid at industrial site (no inclusion into or onto article) As no environmental hazard was identified no environmental-related exposure assessment and risk characterization was performed.
Operational conditions	
Contributing exposure scenario	
Use descriptors covered	ERC6b: Use of reactive processing aid at industrial site (no inclusion into or onto article) As no environmental hazard was identified no environmental-related exposure assessment and risk characterization was performed.
Operational conditions	
Contributing exposure scenario	
Use descriptors covered	PROC1: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions. Use domain: industrial
Operational conditions	
Concentration of the substance	sodium ethanolate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	0.000275 Pa

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 14.05.2025

Version: 14.0

Date / Previous version: 03.11.2023

Previous version: 13.0

Product: **NA-ETHYLATE SOL. 21 %**

(ID no. 30036708/SDS_GEN_GB/EN)

Date of print 21.10.2025

Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Avoid skin contact. Supervision in place to check that the RMMs in place are being used correctly and OCs followed. Avoid contact with eyes. Provide specific employee training to prevent/minimize exposures. Avoid frequent and direct contact with substance.	
Wear suitable working clothes.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	0.0284 mg/m ³
Risk Characterization Ratio (RCR)	0.028354
Assessment method	Qualitative assessment
	Worker - dermal
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra Please note that a modified version has been used (see exposure estimates)	

Contributing exposure scenario	
Use descriptors covered	PROC2: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions Use domain: industrial
Operational conditions	
Concentration of the substance	sodium ethanolate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	0.000275 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Avoid skin contact. Supervision in place to check that the RMMs in place are being used correctly and OCs followed. Avoid contact with eyes. Provide specific employee training to	

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 14.05.2025

Version: 14.0

Date / Previous version: 03.11.2023

Previous version: 13.0

Product: **NA-ETHYLATE SOL. 21 %**

(ID no. 30036708/SDS_GEN_GB/EN)

Date of print 21.10.2025

prevent/minimize exposures. Avoid frequent and direct contact with substance.	
Wear suitable working clothes., Use suitable chemically resistant gloves.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	0.2835 mg/m ³
Risk Characterization Ratio (RCR)	0.283543
Assessment method	Qualitative assessment
	Worker - dermal
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra Please note that a modified version has been used (see exposure estimates)	

Contributing exposure scenario	
Use descriptors covered	PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition Use domain: industrial
Operational conditions	
Concentration of the substance	sodium ethanolate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	0.000275 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Avoid skin contact. Supervision in place to check that the RMMs in place are being used correctly and OCs followed. Avoid contact with eyes. Provide specific employee training to prevent/minimize exposures. Avoid frequent and direct contact with substance.	
Wear suitable working clothes., Use suitable chemically resistant gloves.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	0.2835 mg/m ³

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 14.05.2025

Version: 14.0

Date / Previous version: 03.11.2023

Previous version: 13.0

Product: **NA-ETHYLATE SOL. 21 %**

(ID no. 30036708/SDS_GEN_GB/EN)

Date of print 21.10.2025

Risk Characterization Ratio (RCR)	0.283543
Assessment method	Qualitative assessment
	Worker - dermal
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra Please note that a modified version has been used (see exposure estimates)	

Contributing exposure scenario	
Use descriptors covered	PROC4: Chemical production where opportunity for exposure arises Use domain: industrial
Operational conditions	
Concentration of the substance	sodium ethanolate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	0.000275 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Avoid skin contact. Supervision in place to check that the RMMs in place are being used correctly and OCs followed. Avoid contact with eyes. Provide specific employee training to prevent/minimize exposures. Avoid frequent and direct contact with substance.	
Wear suitable working clothes., Use suitable chemically resistant gloves.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	0.2835 mg/m ³
Risk Characterization Ratio (RCR)	0.283543
Assessment method	Qualitative assessment
	Worker - dermal
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra Please note that a modified version has been used (see exposure estimates)	

Contributing exposure scenario	
Use descriptors covered	PROC8a: Transfer of substance or mixture (charging and discharging) at non-dedicated facilities Use domain: industrial

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 14.05.2025

Version: 14.0

Date / Previous version: 03.11.2023

Previous version: 13.0

Product: **NA-ETHYLATE SOL. 21 %**

(ID no. 30036708/SDS_GEN_GB/EN)

Date of print 21.10.2025

Operational conditions	
Concentration of the substance	sodium ethanolate Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	0.000275 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Avoid skin contact. Supervision in place to check that the RMMs in place are being used correctly and OCs followed. Avoid contact with eyes. Provide specific employee training to prevent/minimize exposures. Avoid frequent and direct contact with substance.	
Wear suitable working clothes., Use suitable chemically resistant gloves.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	0.2835 mg/m ³
Risk Characterization Ratio (RCR)	0.283543
Assessment method	Qualitative assessment
	Worker - dermal
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra Please note that a modified version has been used (see exposure estimates)	

Contributing exposure scenario	
Use descriptors covered	PROC8b: Transfer of substance or mixture (charging and discharging) at dedicated facilities Use domain: industrial
Operational conditions	
Concentration of the substance	sodium ethanolate Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	0.000275 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 14.05.2025

Version: 14.0

Date / Previous version: 03.11.2023

Previous version: 13.0

Product: **NA-ETHYLATE SOL. 21 %**

(ID no. 30036708/SDS_GEN_GB/EN)

Date of print 21.10.2025

Indoor/Outdoor	Indoor
Risk Management Measures	
Avoid skin contact. Supervision in place to check that the RMMs in place are being used correctly and OCs followed. Avoid contact with eyes. Provide specific employee training to prevent/minimize exposures. Avoid frequent and direct contact with substance.	
Wear suitable working clothes., Use suitable chemically resistant gloves.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	0.2835 mg/m ³
Risk Characterization Ratio (RCR)	0.283543
Assessment method	Qualitative assessment
	Worker - dermal
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra Please note that a modified version has been used (see exposure estimates)	

Contributing exposure scenario	
Use descriptors covered	PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing). Use domain: industrial
Operational conditions	
Concentration of the substance	sodium ethanolate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	0.000275 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Avoid skin contact. Supervision in place to check that the RMMs in place are being used correctly and OCs followed. Avoid contact with eyes. Provide specific employee training to prevent/minimize exposures. Avoid frequent and direct contact with substance.	

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 14.05.2025

Version: 14.0

Date / Previous version: 03.11.2023

Previous version: 13.0

Product: **NA-ETHYLATE SOL. 21 %**

(ID no. 30036708/SDS_GEN_GB/EN)

Date of print 21.10.2025

Wear suitable working clothes., Use suitable chemically resistant gloves.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	0.2835 mg/m ³
Risk Characterization Ratio (RCR)	0.283543
Assessment method	Qualitative assessment
	Worker - dermal
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra Please note that a modified version has been used (see exposure estimates)	

Contributing exposure scenario	
Use descriptors covered	PROC15: Use a laboratory reagent. Use domain: industrial
Operational conditions	
Concentration of the substance	sodium ethanolate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	0.000275 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Avoid skin contact. Supervision in place to check that the RMMs in place are being used correctly and OCs followed. Avoid contact with eyes. Provide specific employee training to prevent/minimize exposures. Avoid frequent and direct contact with substance.	
Wear suitable working clothes., Use suitable chemically resistant gloves.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	0.2835 mg/m ³
Risk Characterization Ratio (RCR)	0.283543
Assessment method	Qualitative assessment
	Worker - dermal
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra Please note that a modified version has been used (see exposure estimates)	

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 14.05.2025

Version: 14.0

Date / Previous version: 03.11.2023

Previous version: 13.0

Product: **NA-ETHYLATE SOL. 21 %**

(ID no. 30036708/SDS_GEN_GB/EN)

Date of print 21.10.2025

4. Short title of exposure scenario

Use as an intermediate

IS; IS; ERC6b; PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC9, PROC15

Control of exposure and risk management measures

Contributing exposure scenario	
Use descriptors covered	ERC6a: Use of intermediate As no environmental hazard was identified no environmental-related exposure assessment and risk characterization was performed.
Operational conditions	
Contributing exposure scenario	
Use descriptors covered	PROC1: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions. Use domain: industrial
Operational conditions	
Concentration of the substance	sodium ethanolate Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	0.000275 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Avoid skin contact. Supervision in place to check that the RMMs in place are being used correctly and OCs followed. Avoid contact with eyes. Provide specific employee training to prevent/minimize exposures. Avoid frequent and direct contact with substance.	
Wear suitable working clothes.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	0.0284 mg/m ³
Risk Characterization Ratio (RCR)	0.028354

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 14.05.2025

Version: 14.0

Date / Previous version: 03.11.2023

Previous version: 13.0

Product: **NA-ETHYLATE SOL. 21 %**

(ID no. 30036708/SDS_GEN_GB/EN)

Date of print 21.10.2025

Assessment method	Qualitative assessment
	Worker - dermal
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra Please note that a modified version has been used (see exposure estimates)	

Contributing exposure scenario	
Use descriptors covered	PROC2: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions Use domain: industrial
Operational conditions	
Concentration of the substance	sodium ethanolate Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	0.000275 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Avoid skin contact. Supervision in place to check that the RMMs in place are being used correctly and OCs followed. Avoid contact with eyes. Provide specific employee training to prevent/minimize exposures. Avoid frequent and direct contact with substance.	
Wear suitable working clothes., Use suitable chemically resistant gloves.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	0.2835 mg/m ³
Risk Characterization Ratio (RCR)	0.283543
Assessment method	Qualitative assessment
	Worker - dermal
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra Please note that a modified version has been used (see exposure estimates)	

Contributing exposure scenario	
Use descriptors covered	PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 14.05.2025

Version: 14.0

Date / Previous version: 03.11.2023

Previous version: 13.0

Product: **NA-ETHYLATE SOL. 21 %**

(ID no. 30036708/SDS_GEN_GB/EN)

Date of print 21.10.2025

	containment condition Use domain: industrial
Operational conditions	
Concentration of the substance	sodium ethanolate Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	0.000275 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Avoid skin contact. Supervision in place to check that the RMMs in place are being used correctly and OCs followed. Avoid contact with eyes. Provide specific employee training to prevent/minimize exposures. Avoid frequent and direct contact with substance.	
Wear suitable working clothes., Use suitable chemically resistant gloves.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	0.2835 mg/m ³
Risk Characterization Ratio (RCR)	0.283543
Assessment method	Qualitative assessment
	Worker - dermal
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra Please note that a modified version has been used (see exposure estimates)	

Contributing exposure scenario	
Use descriptors covered	PROC4: Chemical production where opportunity for exposure arises Use domain: industrial
Operational conditions	
Concentration of the substance	sodium ethanolate Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	0.000275 Pa
Process temperature	20 °C

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 14.05.2025

Version: 14.0

Date / Previous version: 03.11.2023

Previous version: 13.0

Product: **NA-ETHYLATE SOL. 21 %**

(ID no. 30036708/SDS_GEN_GB/EN)

Date of print 21.10.2025

Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Avoid skin contact. Supervision in place to check that the RMMs in place are being used correctly and OCs followed. Avoid contact with eyes. Provide specific employee training to prevent/minimize exposures. Avoid frequent and direct contact with substance.	
Wear suitable working clothes., Use suitable chemically resistant gloves.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	0.2835 mg/m ³
Risk Characterization Ratio (RCR)	0.283543
Assessment method	Qualitative assessment
	Worker - dermal
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra Please note that a modified version has been used (see exposure estimates)	

Contributing exposure scenario	
Use descriptors covered	PROC8a: Transfer of substance or mixture (charging and discharging) at non-dedicated facilities Use domain: industrial
Operational conditions	
Concentration of the substance	sodium ethanolate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	0.000275 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Avoid skin contact. Supervision in place to check that the RMMs in place are being used correctly and OCs followed. Avoid contact with eyes. Provide specific employee training to prevent/minimize exposures. Avoid	

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 14.05.2025

Version: 14.0

Date / Previous version: 03.11.2023

Previous version: 13.0

Product: **NA-ETHYLATE SOL. 21 %**

(ID no. 30036708/SDS_GEN_GB/EN)

Date of print 21.10.2025

frequent and direct contact with substance.	
Wear suitable working clothes., Use suitable chemically resistant gloves.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	0.2835 mg/m ³
Risk Characterization Ratio (RCR)	0.283543
Assessment method	Qualitative assessment
	Worker - dermal
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra Please note that a modified version has been used (see exposure estimates)	

Contributing exposure scenario	
Use descriptors covered	PROC8b: Transfer of substance or mixture (charging and discharging) at dedicated facilities Use domain: industrial
Operational conditions	
Concentration of the substance	sodium ethanolate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	0.000275 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Avoid skin contact. Supervision in place to check that the RMMs in place are being used correctly and OCs followed. Avoid contact with eyes. Provide specific employee training to prevent/minimize exposures. Avoid frequent and direct contact with substance.	
Wear suitable working clothes., Use suitable chemically resistant gloves.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	0.2835 mg/m ³
Risk Characterization Ratio (RCR)	0.283543
Assessment method	Qualitative assessment
	Worker - dermal

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 14.05.2025

Version: 14.0

Date / Previous version: 03.11.2023

Previous version: 13.0

Product: **NA-ETHYLATE SOL. 21 %**

(ID no. 30036708/SDS_GEN_GB/EN)

Date of print 21.10.2025

Guidance to Downstream Users

For scaling see: <http://www.ecetoc.org/tra> Please note that a modified version has been used (see exposure estimates)

Contributing exposure scenario

Use descriptors covered	PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing). Use domain: industrial
--------------------------------	---

Operational conditions

Concentration of the substance	sodium ethanolate Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	0.000275 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor

Risk Management Measures

Avoid skin contact. Supervision in place to check that the RMMs in place are being used correctly and OCs followed. Avoid contact with eyes. Provide specific employee training to prevent/minimize exposures. Avoid frequent and direct contact with substance.

Wear suitable working clothes., Use suitable chemically resistant gloves.

Exposure estimate and reference to its source

Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	0.2835 mg/m ³
Risk Characterization Ratio (RCR)	0.283543
Assessment method	Qualitative assessment
	Worker - dermal

Guidance to Downstream Users

For scaling see: <http://www.ecetoc.org/tra> Please note that a modified version has been used (see exposure estimates)

Contributing exposure scenario

Use descriptors covered	PROC15: Use a laboratory reagent. Use domain: industrial
--------------------------------	---

Operational conditions

Concentration of the substance	sodium ethanolate Content: $\geq 0\%$ - $\leq 100\%$
--------------------------------	---

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 14.05.2025

Version: 14.0

Date / Previous version: 03.11.2023

Previous version: 13.0

Product: **NA-ETHYLATE SOL. 21 %**

(ID no. 30036708/SDS_GEN_GB/EN)

Date of print 21.10.2025

Physical state	liquid
Vapour pressure of the substance during use	0.000275 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Avoid skin contact. Supervision in place to check that the RMMs in place are being used correctly and OCs followed. Avoid contact with eyes. Provide specific employee training to prevent/minimize exposures. Avoid frequent and direct contact with substance.	
Wear suitable working clothes., Use suitable chemically resistant gloves.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	0.2835 mg/m ³
Risk Characterization Ratio (RCR)	0.283543
Assessment method	Qualitative assessment
	Worker - dermal
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra Please note that a modified version has been used (see exposure estimates)	

5. Short title of exposure scenario

Use in laboratories, Use as laboratory reagent/agent

PW; PW; ERC8a, ERC8b; PROC15

Control of exposure and risk management measures

Contributing exposure scenario	
Use descriptors covered	ERC8a: Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor) As no environmental hazard was identified no environmental-related exposure assessment and risk characterization was performed.
Operational conditions	
Contributing exposure scenario	
Use descriptors covered	ERC8b: Widespread use of reactive processing aid (no

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 14.05.2025

Version: 14.0

Date / Previous version: 03.11.2023

Previous version: 13.0

Product: **NA-ETHYLATE SOL. 21 %**

(ID no. 30036708/SDS_GEN_GB/EN)

Date of print 21.10.2025

	inclusion into or onto article, indoor) As no environmental hazard was identified no environmental-related exposure assessment and risk characterization was performed.
Operational conditions	
Contributing exposure scenario	
Use descriptors covered	PROC15: Use a laboratory reagent. Use domain: professional
Operational conditions	
Concentration of the substance	sodium ethanolate Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	0.000275 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Avoid skin contact. Supervision in place to check that the RMMs in place are being used correctly and OCs followed. Avoid contact with eyes. Provide specific employee training to prevent/minimize exposures. Avoid frequent and direct contact with substance.	
Wear suitable working clothes., Use suitable chemically resistant gloves.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v3.6, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	0.2835 mg/m ³
Risk Characterization Ratio (RCR)	0.283543
Assessment method	Qualitative assessment
	Worker - dermal
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra Please note that a modified version has been used (see exposure estimates)	
