

Safety data sheet

Page: 1/10

BASF Safety data sheet
Date / Revised: 03.02.2025
Product: **Kollidon® 30 Origin Germany**

Version: 6.1

(30034974/SDS_GEN_SG/EN)

Date of print: 14.10.2025

1. Substance/preparation and manufacturer/supplier identification

Product name:
Kollidon® 30 Origin Germany

Use: Polymer, pharmaceutical excipient

Manufacturer/supplier:
BASF South East Asia Pte Ltd.
128 Beach Road #18-01
Guoco Midtown, 189773, Singapore
Telephone: +65 8322 4420
Telefax number: +65 6 334-0330
E-mail address: benny.zou@basf.com

Emergency information:
Singapore Emergency Toll-Free Number:
Telephone: 1800-723-1361
International emergency number:
Telephone: +49 180 2273-112

2. Hazard identification

Classification of the substance and mixture:
No need for classification according to GHS criteria for this product.

Label elements and precautionary statement:

The product does not require a hazard warning label in accordance with GHS criteria.

Other hazards which do not result in classification:
The product is under certain conditions capable of dust explosion.
May form explosible dust-air mixture if dispersed

BASF Safety data sheet
Date / Revised: 03.02.2025
Product: **Kollidon® 30 Origin Germany**

Version: 6.1

(30034974/SDS_GEN_SG/EN)

Date of print: 14.10.2025

3. Composition/information on ingredients

Chemical nature

Substance nature: Substance

2-Pyrrolidinone, 1-ethenyl-, homopolymer
CAS Number: 9003-39-8

4. First-Aid Measures

General advice:
Remove contaminated clothing.

If inhaled:
Keep patient calm, remove to fresh air.

On skin contact:
Wash thoroughly with soap and water

On contact with eyes:
Wash affected eyes for at least 15 minutes under running water with eyelids held open.

On ingestion:
Rinse mouth and then drink 200-300 ml of water.

Note to physician:
Symptoms: (Further) symptoms and / or effects are not known so far
Treatment: Symptomatic treatment (decontamination, vital functions).

5. Fire-Fighting Measures

Suitable extinguishing media:
water spray, foam, dry powder, carbon dioxide

Specific hazards:
carbon dioxide, nitrogen oxides
The substances/groups of substances mentioned can be released in case of fire.

Special protective equipment:
Wear a self-contained breathing apparatus.

Further information:
Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

6. Accidental Release Measures

Personal precautions:

Avoid dust formation. Use personal protective clothing. Information regarding personal protective measures, see section 8.

Environmental precautions:

Do not discharge into drains/surface waters/groundwater.

Methods for cleaning up or taking up:

For small amounts: Sweep/shovel up.

For large amounts: Sweep/shovel up.

Dispose of absorbed material in accordance with regulations. Avoid raising dust.

Additional information: Avoid the formation and build-up of dust - danger of dust explosion. Dust in sufficient concentration can result in an explosive mixture in air. Handle to minimize dusting and eliminate open flame and other sources of ignition. Avoid dispersal of dust in the air (e.g. by clearing dusty surfaces with compressed air).

7. Handling and Storage

Handling

Handle in accordance with good industrial hygiene and safety practice. Avoid dust formation.

Protection against fire and explosion:

The product is capable of dust explosion. Avoid dust formation. Prevent electrostatic charge - sources of ignition should be kept well clear - fire extinguishers should be kept handy. Avoid all sources of ignition: heat, sparks, open flame.

Storage

Further information on storage conditions: Keep container tightly closed and dry.

8. Exposure controls and personal protection

Components with occupational exposure limits

No substance specific occupational exposure limits known.

Personal protective equipment

Respiratory protection:

Breathing protection if breathable aerosols/dust are formed. Particle filter with low efficiency for solid particles (e.g. EN 143 or 149, Type P1 or FFP1)

Hand protection:

Suitable chemical resistant safety gloves (EN ISO 374-1) also with prolonged, direct contact (Recommended: Protective index 6, corresponding > 480 minutes of permeation time according to EN ISO 374-1): E.g. nitrile rubber (0.4 mm), chloroprene rubber (0.5 mm), butyl rubber (0.7 mm) etc. Supplementary note: The specifications are based on tests, literature data and information of glove manufacturers or are derived from similar substances by analogy. Due to many conditions (e.g. temperature) it must be considered, that the practical usage of a chemical-protective glove in practice may be much shorter than the permeation time determined through testing. Manufacturer's directions for use should be observed because of great diversity of types.

Eye protection:

Safety glasses with side-shields (frame goggles) (e.g. EN 166)

Body protection:

Body protection must be chosen depending on activity and possible exposure, e.g. apron, protecting boots, chemical-protection suit (according to EN 14605 in case of splashes or EN ISO 13982 in case of dust).

General safety and hygiene measures:

Handle in accordance with good industrial hygiene and safety practice. Wearing of closed work clothing is recommended. Avoid contact with the skin, eyes and clothing. No eating, drinking, smoking or tobacco use at the place of work. Hands and/or face should be washed before breaks and at the end of the shift. Store work clothing separately.

9. Physical and Chemical Properties

Form: powder
Colour: white to cream
Odour: almost odourless
Odour threshold: not determined

pH value: 3 - 5
(10 %(m), 20 °C)

onset of melting: 131 °C
The substance / product
decomposes.

Boiling point:
not applicable

Flash point:
not applicable, the product is a solid

Evaporation rate:
The product is a non-volatile solid.

Flammability (solid/gas): not highly flammable (VDI 2263, sheet 1, 1.1 (May 1990))

Lower explosion limit:
For solids not relevant for
classification and labelling.

Upper explosion limit:
For solids not relevant for
classification and labelling.

BASF Safety data sheet
 Date / Revised: 03.02.2025
 Product: **Kollidon® 30 Origin Germany**

Version: 6.1

(30034974/SDS_GEN_SG/EN)

Date of print: 14.10.2025

Ignition temperature: No data available.

Thermal decomposition: 150 °C (DSC (DIN 51007))
 It is not a self-decomposable substance.

Self heating ability: 150 °C , > 230 kJ/kg (DSC (DIN 51007))
 It is a substance capable of spontaneous heating according to UN transport regulations class 4.2. Based on test results packaging < 3m³ are exempted from the classification. (UN Test N.4 (self heating substances))

SADT: No data available.

Minimum ignition energy: The product is capable of dust explosion.

Explosion hazard: Product is not explosive, however a dust explosion could result from an air / dust mixture.

Fire promoting properties: not fire-propagating

Vapour pressure: dropped

Density: No information is available for the absolute density. Instead the bulk density was determined as a more relevant value.

Relative density: No data available.

Bulk density: 400 - 600 kg/m³

Relative vapour density (air): The product is a non-volatile solid.

Solubility in water: fully soluble

Hygroscopy: hygroscopic

Solubility (qualitative) solvent(s): organic solvents
 soluble

Partitioning coefficient n-octanol/water (log Pow): not determined

Viscosity, kinematic: not applicable, the product is a solid

Particle characteristics

Particle size distribution: No data available. -

Specific Surface Area: No data available.

Particle Shape: No data available.

BASF Safety data sheet
Date / Revised: 03.02.2025
Product: **Kollidon® 30 Origin Germany**

Version: 6.1

(30034974/SDS_GEN_SG/EN)

Date of print: 14.10.2025

Dustiness:
No data available.

10. Stability and Reactivity

Conditions to avoid:
See SDS section 7 - Handling and storage. Avoid dust formation. Avoid electro-static charge.

Thermal decomposition: 150 °C (DSC (DIN 51007))
It is not a self-decomposable substance.

Thermal decomposition: 150 °C, > 230 kJ/kg (DSC (DIN 51007))

Substances to avoid:
strong alkalies

Corrosion to metals: Corrosive effects to metal are not anticipated.

Hazardous reactions:
Dust explosion hazard.

Hazardous decomposition products:
No hazardous decomposition products if stored and handled as prescribed/indicated.

Chemical stability:
The product is stable if stored and handled as prescribed/indicated.

Reactivity:
No hazardous reactions if stored and handled as prescribed/indicated.

11. Toxicological Information

Routes of exposure

Acute oral toxicity

Experimental/calculated data:
LD50rat (oral): > 2,000 mg/kg (BASF-Test)

Acute inhalation toxicity

LC50 rat (by inhalation): > 5.2 mg/l 4 h (OECD Guideline 403)

Acute dermal toxicity

(dermal): No data available.

Assessment of acute toxicity

Virtually nontoxic after a single ingestion. Virtually nontoxic by inhalation.

Symptoms

(Further) symptoms and / or effects are not known so far

Irritation

Assessment of irritating effects:
Not irritating to the skin. Not irritating to the eyes.

Experimental/calculated data:
Skin corrosion/irritation rabbit: non-irritant (Draize test)

Serious eye damage/irritation rabbit: non-irritant (Draize test)

Respiratory/Skin sensitization

Assessment of sensitization:
No data available.

Experimental/calculated data:
No data available.

Germ cell mutagenicity

Assessment of mutagenicity:
The substance was not mutagenic in studies with mammals.

Carcinogenicity

Assessment of carcinogenicity:
In long-term animal studies in which the substance was given in high doses by feed, a carcinogenic effect was not observed.

Experimental/calculated data:
No data available.

Reproductive toxicity

Assessment of reproduction toxicity:
No data available.

Experimental/calculated data:
No data available.

Developmental toxicity

Assessment of teratogenicity:
No indications of a developmental toxic / teratogenic effect were seen in animal studies.

Specific target organ toxicity (single exposure)

Remarks: No data available.

Repeated dose toxicity and Specific target organ toxicity (repeated exposure)

Assessment of repeated dose toxicity:
No data available.

Experimental/calculated data:

No data available.

Aspiration hazard

not applicable

12. Ecological Information

Ecotoxicity

Assessment of aquatic toxicity:

There is a high probability that the product is not acutely harmful to aquatic organisms. The inhibition of the degradation activity of activated sludge is not anticipated when introduced to biological treatment plants in appropriate low concentrations.

Toxicity to fish:

LC50 (96 h) > 10,000 mg/l, *Leuciscus idus* (DIN 38412 Part 15, static)

Aquatic invertebrates:

No data available.

Aquatic plants:

No data available.

Microorganisms/Effect on activated sludge:

EC20 (0.5 h) > 1,995 mg/l, activated sludge, industrial (OECD Guideline 209, aerobic)

Chronic toxicity to fish:

No data available.

Chronic toxicity to aquatic invertebrates:

No data available.

Mobility

Assessment transport between environmental compartments:

No data available.

Persistence and degradability

Elimination information:

< 10 % DOC reduction (15 d) (OECD Guideline 302 B) (aerobic, activated sludge, industrial) Poorly eliminated from water.

Bioaccumulation potential

Assessment bioaccumulation potential:

No data available.

Bioaccumulation potential:

Based on its structural properties, the polymer is not biologically available. Accumulation in organisms is not to be expected.

13. Disposal Considerations

Observe national and local legal requirements.

Contaminated packaging:

Uncontaminated packaging can be re-used.

Packs that cannot be cleaned should be disposed of in the same manner as the contents.

14. Transport Information

Domestic transport:

UN number or ID number: UN 3088

UN proper shipping name: SELF-HEATING SOLID, ORGANIC, N.O.S. (1-ETHENYL-2-PYRROLIDINONE, HOMOPOLYMER)

Transport hazard class(es): 4.2

Packing group: III

Environmental hazards: no

Special precautions for user: Not dangerous goods of class 4.2 in packages up to 3000 litres capacity.

Sea transport

IMDG

UN number or ID number: UN 3088

UN proper shipping name: SELF-HEATING SOLID, ORGANIC, N.O.S. (1-ETHENYL-2-PYRROLIDINONE, HOMOPOLYMER)

Transport hazard class(es): 4.2

Packing group: III

Environmental hazards: no

Marine pollutant: NO

Special precautions for user: EmS: F-A; S-J

Not dangerous goods of class 4.2 in packages up to 3000 litres capacity.

Air transport

IATA/ICAO

UN number or ID number: UN 3088

UN proper shipping name: SELF-HEATING SOLID, ORGANIC, N.O.S. (1-ETHENYL-2-PYRROLIDINONE, HOMOPOLYMER)

Transport hazard class(es): 4.2

Packing group: III

Environmental hazards: No Mark as dangerous for the environment is needed

Special precautions for user: Not dangerous goods of class 4.2 in packages up to 3000 litres capacity.

Maritime transport in bulk according to IMO instruments

Maritime transport in bulk is not intended.

Further information

Not dangerous goods of class 4.2 in packages up to 3000 litres capacity.

15. Regulatory Information

Other regulations

If other regulatory information applies that is not already provided elsewhere in this safety data sheet, then it is described in this subsection.

16. Other Information

Any other intended applications should be discussed with the manufacturer. Corresponding occupational protection measurements must be followed.

Vertical lines in the left hand margin indicate an amendment from the previous version.

The data contained in this safety data sheet are based on our current knowledge and experience and describe the product only with regard to safety requirements. This safety data sheet is neither a Certificate of Analysis (CoA) nor technical data sheet and shall not be mistaken for a specification agreement. Identified uses in this safety data sheet do neither represent an agreement on the corresponding contractual quality of the substance/mixture nor a contractually designated use. It is the responsibility of the recipient of the product to ensure any proprietary rights and existing laws and legislation are observed.