

Safety data sheet

Page: 1/103

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 27.05.2025

Version: 8.0

Date / Previous version: 19.09.2023

Previous version: 7.0

Product: **BUTYLGLYCOL**

(ID no. 30034845/SDS_GEN_RO/EN)

Date of print 13.10.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

BUTYLGLYCOL

Chemical name: 2-butoxyethanol; ethylene glycol monobutyl ether butyl cellosolve

INDEX-Number: 603-014-00-0

CAS Number: 111-76-2

REACH registration number: 01-2119475108-36-0005, 01-2119475108-36-0037, 01-2119475108-36

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses: process chemical, solvent(s)

For the detailed identified uses of the product see appendix of the safety data sheet.

1.3. Details of the supplier of the safety data sheet

Company:

BASF SE
67056 Ludwigshafen
GERMANY

Contact address:

BASF SRL
Floreasca Park
Sos.Pipera nr.43, corp A, etaj 1
014254 Bucharest
ROMANIA

Telephone: +40 21 5299-029

E-mail address: product-safety-romania@basf.com

1.4. Emergency telephone number

Numar national pentru cazuri de urgenta:

+40 21 599 23 00 Centrul de Informatii Toxicologice – Spitalul Clinic de Urgenta Bucuresti

International emergency number:

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 27.05.2025

Version: 8.0

Date / Previous version: 19.09.2023

Previous version: 7.0

Product: **BUTYLGLYCOL**

(ID no. 30034845/SDS_GEN_RO/EN)

Date of print 13.10.2025

Telephone: +49 180 2273-112

SECTION 2: Hazards Identification

2.1. Classification of the substance or mixture

According to Regulation (EC) No 1272/2008 [CLP]

Acute Tox. 4 (oral)	H302 Harmful if swallowed.
Skin Irrit. 2	H315 Causes skin irritation.
Eye Irrit. 2	H319 Causes serious eye irritation.
Acute Tox. 3 (Inhalation - vapour)	H331 Toxic if inhaled.

For the classifications not written out in full in this section the full text can be found in section 16.

2.2. Label elements

According to Regulation (EC) No 1272/2008 [CLP]

Pictogram:



Signal Word:

Danger

Hazard Statement:

H319	Causes serious eye irritation.
H315	Causes skin irritation.
H331	Toxic if inhaled.
H302	Harmful if swallowed.

Precautionary Statements (Prevention):

P271	Use only outdoors or in a well-ventilated area.
P260	Do not breathe mist or vapour.

Precautionary Statements (Response):

P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Precautionary Statements (Storage):

P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
-------------	--

Precautionary Statements (Disposal):

P501	Dispose of contents and container to hazardous or special waste collection point.
------	---

Hazard determining component(s) for labelling: 2-butoxyethanol

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 27.05.2025

Version: 8.0

Date / Previous version: 19.09.2023

Previous version: 7.0

Product: **BUTYLGLYCOL**

(ID no. 30034845/SDS_GEN_RO/EN)

Date of print 13.10.2025

2.3. Other hazards

According to Regulation (EC) No 1272/2008 [CLP]

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture. See section 12 - Results of PBT and vPvB assessment.

Product does not contain a substance above legal limits included in the list established in accordance with Article 59(1) of Regulation (EC) No 1907/2006 for having endocrine disrupting properties or is identified to have endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

SECTION 3: Composition/Information on Ingredients

3.1. Substances

Chemical nature

2-butoxyethanol

Content (W/W): > 99 %

CAS Number: 111-76-2

EC-Number: 203-905-0

INDEX-Number: 603-014-00-0

Substance with EU occupational exposure limit

Acute Tox. 4 (oral)

Skin Irrit. 2

Eye Irrit. 2

Acute Tox. 3 (Inhalation - vapour)

H319, H315, H331, H302

Acute toxicity estimate:

oral: 1.200 mg/kg

Inhalation: 3 mg/l (vapour)

Regulatory relevant ingredients

2-butoxyethanol

Content (W/W): > 99 % - < 100 %

CAS Number: 111-76-2

EC-Number: 203-905-0

INDEX-Number: 603-014-00-0

Substance with EU occupational exposure limit

Acute Tox. 4 (oral)

Skin Irrit. 2

Eye Irrit. 2

Acute Tox. 3 (Inhalation - vapour)

H319, H315, H331, H302

Acute toxicity estimate:

oral: 1.200 mg/kg

Inhalation: 3 mg/l (vapour)

For the classifications not written out in full in this section, including the hazard classes and the hazard statements, the full text is listed in section 16.

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 27.05.2025

Version: 8.0

Date / Previous version: 19.09.2023

Previous version: 7.0

Product: **BUTYLGLYCOL**

(ID no. 30034845/SDS_GEN_RO/EN)

Date of print 13.10.2025

3.2. Mixtures

Not applicable

SECTION 4: First-Aid Measures

4.1. Description of first aid measures

Remove contaminated clothing. If the patient is likely to become unconscious, place and transport in stable sideways position (recovery position). If not breathing, give artificial respiration. First aid personnel should pay attention to their own safety.

If inhaled:

Keep patient calm, remove to fresh air, seek medical attention.

On skin contact:

Immediately wash thoroughly with soap and water, seek medical attention.

On contact with eyes:

Wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.

On ingestion:

Immediately rinse mouth and then drink 200-300 ml of water, seek medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms: Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11.

Hazards: Skin resorption hazard.

Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11.
(Further) symptoms and / or effects are not known so far

4.3. Indication of any immediate medical attention and special treatment needed

Treatment: Treat according to symptoms (decontamination, vital functions), no known specific antidote.

SECTION 5: Fire-Fighting Measures

5.1. Extinguishing media

Suitable extinguishing media:

dry powder, water spray, carbon dioxide, alcohol-resistant foam

Unsuitable extinguishing media for safety reasons:

water jet

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 27.05.2025

Version: 8.0

Date / Previous version: 19.09.2023

Previous version: 7.0

Product: **BUTYLGLYCOL**

(ID no. 30034845/SDS_GEN_RO/EN)

Date of print 13.10.2025

Additional information:

Use extinguishing measures to suit surroundings.

5.2. Special hazards arising from the substance or mixture

Advice: Flammable liquid Cool endangered containers with water-spray. See SDS section 7 - Handling and storage.

5.3. Advice for fire-fighters

Special protective equipment:

Wear a self-contained breathing apparatus. Special protective equipment for firefighters

Further information:

Evacuate area of all unnecessary personnel. Fight fire from maximum distance.

Extend fire extinguishing measures to the surroundings. Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

SECTION 6: Accidental Release Measures

High risk of slipping due to leakage/spillage of product.

Release of substance/product can cause fire or explosion. Shut off or stop source of leak. Shut off or stop released substance/product under safe conditions.

Pack in tightly closed containers for disposal.

6.1. Personal precautions, protective equipment and emergency procedures

Handle in accordance with good industrial hygiene and safety practice.

Avoid all sources of ignition: heat, sparks, open flame. Use antistatic tools.

6.2. Environmental precautions

Discharge into the environment must be avoided.

6.3. Methods and material for containment and cleaning up

For large amounts: Pump off product.

For residues: Pick up with suitable absorbent material (e.g. sand, sawdust, general-purpose binder, kieselguhr). Dispose of absorbed material in accordance with regulations.

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 27.05.2025

Version: 8.0

Date / Previous version: 19.09.2023

Previous version: 7.0

Product: **BUTYLGLYCOL**

(ID no. 30034845/SDS_GEN_RO/EN)

Date of print 13.10.2025

6.4. Reference to other sections

Information regarding exposure controls/personal protection and disposal considerations can be found in section 8 and 13.

SECTION 7: Handling and Storage

7.1. Precautions for safe handling

Ensure thorough ventilation of stores and work areas. Prevent contact with air/oxygen (formation of peroxide).

Protection against fire and explosion:

Prevent electrostatic charge - sources of ignition should be kept well clear - fire extinguishers should be kept handy.

7.2. Conditions for safe storage, including any incompatibilities

Further information on storage conditions: Keep container tightly closed in a cool, well-ventilated place.

Storage stability:

Storage temperature: $\leq 35^{\circ}\text{C}$

The stability data given is only valid when stored under oxygen free inert gases or in containers that are impermeable to oxygen.

7.3. Specific end use(s)

See exposure scenario(s) in the attachment to this safety data sheet.

SECTION 8: Exposure Controls/Personal Protection

8.1. Control parameters

Components with occupational exposure limits

111-76-2: 2-butoxyethanol

Skin Designation (OEL (RO))

The substance can be absorbed through the skin.

TWA value 98 mg/m³ ; 20 ppm (OEL (RO))

Skin Designation (OEL (EU))

The substance can be absorbed through the skin.

STEL value 246 mg/m³ ; 50 ppm (OEL (EU))

indicative

TWA value 98 mg/m³ ; 20 ppm (OEL (EU))

indicative

STEL value 246 mg/m³ ; 50 ppm (OEL (RO))

Ceiling limit value/factor: 15 min

STEL value 246 mg/m³ ; 50 ppm (EU SCOEL)

Ceiling limit value/factor: 15 min

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 27.05.2025

Version: 8.0

Date / Previous version: 19.09.2023

Previous version: 7.0

Product: **BUTYLGLYCOL**

(ID no. 30034845/SDS_GEN_RO/EN)

Date of print 13.10.2025

TWA value 98 mg/m³ ; 20 ppm (EU SCOEL)
Ceiling limit value/factor: 8HR
Skin Designation (EU SCOEL)
The substance can be absorbed through the skin.

PNEC

freshwater: 8,8 mg/l

marine water: 0,88 mg/l

intermittent release: 9,1 mg/l

sediment (freshwater): 34,6 mg/kg

sediment (marine water): 3,46 mg/kg

soil: 2,33 mg/kg

STP: 463 mg/l

oral (secondary poisoning): 20 mg/kg

DNEL

worker:

Long-term exposure- systemic effects, Inhalation: 98 mg/m³, 20 ppm

worker:

Short-term exposure - systemic effects, Inhalation: 1091 mg/m³

worker:

Short-term exposure - local effects, Inhalation: 246 mg/m³

consumer:

Long-term exposure- systemic effects, oral: 6,3 mg/kg

consumer:

Short-term exposure - systemic effects, oral: 26,7 mg/kg

consumer:

Long-term exposure- systemic effects, Inhalation: 59 mg/m³

consumer:

Short-term exposure - systemic effects, Inhalation: 426 mg/m³

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 27.05.2025

Version: 8.0

Date / Previous version: 19.09.2023

Previous version: 7.0

Product: **BUTYLGLYCOL**

(ID no. 30034845/SDS_GEN_RO/EN)

Date of print 13.10.2025

consumer:

Short-term exposure - local effects, Inhalation: 147 mg/m³

8.2. Exposure controls

Personal protective equipment

Respiratory protection:

Gas filter for gases/vapours of organic compounds (boiling point >65 °C, e. g. EN 14387 Type A)

Hand protection:

Chemical resistant protective gloves (EN ISO 374-1)

Suitable materials also with prolonged, direct contact (Recommended: Protective index 6, corresponding > 480 minutes of permeation time according to EN ISO 374-1):

butyl rubber (butyl) - 0.7 mm coating thickness

Manufacturer's directions for use should be observed because of great diversity of types.

Supplementary note: The specifications are based on tests, literature data and information of glove manufacturers or are derived from similar substances by analogy. Due to many conditions (e.g. temperature) it must be considered, that the practical usage of a chemical-protective glove in practice may be much shorter than the permeation time determined through testing.

Eye protection:

Safety glasses with side-shields (frame goggles) (e.g. EN 166)

Body protection:

chemical-protection suit (f.e. according to EN 14605)

General safety and hygiene measures

Avoid contact with the skin, eyes and clothing. Avoid inhalation of vapour. Wearing of closed work clothing is required additionally to the stated personal protection equipment.

Environmental exposure controls

All appropriate measures must be taken to prevent the release of this product to the environment and to limit the dispersion of any release when it occurs. Suitable risk management measures should be in place.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

State of matter:	liquid
Form:	liquid
Colour:	colourless
Odour:	ether-like
Odour threshold:	not determined

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 27.05.2025

Version: 8.0

Date / Previous version: 19.09.2023

Previous version: 7.0

Product: **BUTYLGLYCOL**

(ID no. 30034845/SDS_GEN_RO/EN)

Date of print 13.10.2025

Melting point:	-74,8 °C	
	Literature data.	
Boiling point:	173,5 °C	(other)
	(1.013 hPa)	
Flammability:	Combustible liquid.	(derived from flash point)
Lower explosion limit:	1,1 %(V)	
	For liquids not relevant for classification and labelling., The lower explosion point may be 5 - 15 °C below the flash point.	
Upper explosion limit:	10,6 %(V)	
	For liquids not relevant for classification and labelling.	
Flash point:	67 °C	(DIN 51758, closed cup)
Auto-ignition temperature:	232 °C	(DIN EN 14522)
Thermal decomposition:	No decomposition if stored and handled as prescribed/indicated.	
pH value:	(20 °C)	
	miscible, neutral	
Viscosity, kinematic:	3,642 mm ² /s	(Capillary viscometer)
	(20 °C)	
Viscosity, dynamic:	3,3 mPa.s	(calculated (from kinematic viscosity))
	(20 °C)	
	The value was determined by calculation from the detected kinematic viscosity.	
Thixotropy:	not thixotropic	
Solubility in water:	Literature data.	(other)
	900 g/l	
	(20 °C, pH 7)	
Solubility (qualitative) solvent(s):	organic solvents	
	soluble	
Partitioning coefficient n-octanol/water (log Kow):	0,81	(measured)
	(25 °C)	
	The data refers to the undissociated form of the substance.	
Vapour pressure:	0,8 hPa	(measured)
	(20 °C)	
	Literature data.	
	1,17 hPa	(measured)
	(25 °C)	
	Literature data.	
Relative density:	0,9000	
	(20 °C)	
Density:	0,9000 g/cm ³	(DIN 51757)
	(20 °C, 1.013 hPa)	
Relative vapour density (air):	4,08	(calculated)
	(20 °C)	
	Heavier than air.	

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 27.05.2025

Version: 8.0

Date / Previous version: 19.09.2023

Previous version: 7.0

Product: **BUTYLGLYCOL**

(ID no. 30034845/SDS_GEN_RO/EN)

Date of print 13.10.2025

9.2. Other information

Information with regard to physical hazard classes

Explosives

Explosion hazard: Based on the chemical structure there is no indication of explosive properties.

Impact sensitivity: not shock-sensitive
Based on the chemical structure there is no shock-sensitivity.

Oxidizing properties

Fire promoting properties: Based on its structural properties the product is not classified as oxidizing.

Pyrophoric properties

Self-ignition temperature: Temperature: 20 °C
Test type: Spontaneous self-ignition at room-temperature.

Based on its structural properties the product is not classified as self-igniting.

Self-heating substances and mixtures

Self heating ability: not applicable, the product is a liquid

Substances and mixtures, which emit flammable gases in contact with water

Formation of flammable gases:
Forms no flammable gases in the presence of water.

Corrosion to metals

No corrosive effect on metal.

Other safety characteristics

pKA:	15 (20 °C)	(calculated)
	The substance does not dissociate.	
Adsorption/water - soil:	KOC: 2,82; log KOC: 0,45	(calculated)
Surface tension:	65 mN/m (20 °C; 2 g/l)	(other, other)
Molar mass:	118,18 g/mol	
SAPT-Temperature:	Study scientifically not justified.	
Evaporation rate:	Value can be approximated from Henry's Law Constant or vapor pressure.	

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 27.05.2025

Version: 8.0

Date / Previous version: 19.09.2023

Previous version: 7.0

Product: **BUTYLGLYCOL**

(ID no. 30034845/SDS_GEN_RO/EN)

Date of print 13.10.2025

SECTION 10: Stability and Reactivity

10.1. Reactivity

No hazardous reactions if stored and handled as prescribed/indicated., When heated can give off ignitable vapours.

Corrosion to metals: No corrosive effect on metal.

Formation of Remarks:

flammable gases:

Forms no flammable gases in the presence of water.

10.2. Chemical stability

The product is stable if stored and handled as prescribed/indicated.

10.3. Possibility of hazardous reactions

Reacts with light metals, with evolution of hydrogen. Reacts with strong oxidizing agents.

10.4. Conditions to avoid

No special precautions other than good housekeeping of chemicals.

10.5. Incompatible materials

Substances to avoid:

strong oxidizing agents

10.6. Hazardous decomposition products

Hazardous decomposition products:

No hazardous decomposition products if stored and handled as prescribed/indicated.

SECTION 11: Toxicological Information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Assessment of acute toxicity:

Of moderate toxicity after single ingestion. The inhalation of a highly enriched/saturated vapor-air-mixture represents an unlikely acute hazard. Virtually nontoxic after a single skin contact.

Experimental/calculated data:

LD50 guinea pig (oral): 1.200 mg/kg (similar to OECD guideline 401)

ATE (oral): 1.200 mg/kg

LC0 guinea pig (by inhalation): > 2,25 mg/l 4 h (similar to OECD guideline 403)

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 27.05.2025

Version: 8.0

Date / Previous version: 19.09.2023

Previous version: 7.0

Product: **BUTYLGLYCOL**

(ID no. 30034845/SDS_GEN_RO/EN)

Date of print 13.10.2025

No mortality was observed. The European Union (EU) has classified this substance as 'toxic' (Cat. 3). The vapour was tested.

ATE (by inhalation): 3 mg/l

vapour

LD50 guinea pig (dermal): > 2.000 mg/kg (OECD Guideline 402)

LD50 mouse (intraperitoneal): 1.174 mg/kg

Irritation

Assessment of irritating effects:

Eye contact causes irritation. Skin contact causes irritation.

Experimental/calculated data:

Skin corrosion/irritation

rabbit: Irritant. (BASF-Test)

Serious eye damage/irritation

rabbit: Irritant. (OECD Guideline 405)

Respiratory/Skin sensitization

Assessment of sensitization:

Skin sensitizing effects were not observed in animal studies.

Experimental/calculated data:

Guinea pig maximization test guinea pig: Non-sensitizing. (OECD Guideline 406)

Germ cell mutagenicity

Assessment of mutagenicity:

The substance was not mutagenic in bacteria. The substance was not mutagenic in mammalian cell culture. The substance was not mutagenic in studies with mammals.

Carcinogenicity

Assessment of carcinogenicity:

Indication of possible carcinogenic effect in animal tests. A clear indication of an increased risk of cancer in humans has so far not been shown. IARC Group 3 (not classifiable as to human carcinogenicity).

Reproductive toxicity

Assessment of reproduction toxicity:

The results of animal studies gave no indication of a fertility impairing effect.

Developmental toxicity

Assessment of teratogenicity:

In animal studies the substance did not cause malformations.

Specific target organ toxicity (single exposure)

Assessment of STOT single:

Based on the available information there is no specific target organ toxicity to be expected after a single exposure.

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 27.05.2025

Version: 8.0

Date / Previous version: 19.09.2023

Previous version: 7.0

Product: **BUTYLGLYCOL**

(ID no. 30034845/SDS_GEN_RO/EN)

Date of print 13.10.2025

Repeated dose toxicity and Specific target organ toxicity (repeated exposure)

Assessment of repeated dose toxicity:

Damages blood cells. Due to the species specific mode of action, the effects are not expected to occur in humans.

Aspiration hazard

not applicable

Interactive effects

No data available.

11.2. Information on other hazards

Endocrine disrupting properties

The substance is not identified to have endocrine disrupting properties according to Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 nor is included in the Candidate List of substances of very high concern according to EU REACH Article 59 for having endocrine disrupting properties.

Other information

Other relevant toxicity information

Skin resorption hazard.

SECTION 12: Ecological Information

12.1. Toxicity

Assessment of aquatic toxicity:

There is a high probability that the product is not acutely harmful to aquatic organisms. Based on long-term (chronic) toxicity study data, the product is very likely not harmful to aquatic organisms. The inhibition of the degradation activity of activated sludge is not anticipated when introduced to biological treatment plants in appropriate low concentrations.

Toxicity to fish:

LC50 (96 h) 1.474 mg/l, *Oncorhynchus mykiss* (OECD Guideline 203, static)
Nominal concentration. Literature data.

Aquatic invertebrates:

EC50 (48 h) 1.550 mg/l, *Daphnia magna* (OECD Guideline 202, part 1, static)
Nominal concentration. Literature data.

Aquatic plants:

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 27.05.2025

Version: 8.0

Date / Previous version: 19.09.2023

Previous version: 7.0

Product: **BUTYLGLYCOL**

(ID no. 30034845/SDS_GEN_RO/EN)

Date of print 13.10.2025

EC50 (72 h) 1.840 mg/l (growth rate), *Pseudokirchneriella subcapitata* (OECD Guideline 201, static)
Nominal concentration. Literature data.

Microorganisms/Effect on activated sludge:

Toxic limit concentration (16 h) > 700 mg/l, *Pseudomonas putida* (DIN 38412 Part 8, static)

Nominal concentration. Literature data.

Chronic toxicity to fish:

No observed effect concentration (21 d) > 100 mg/l, *Brachydanio rerio* (OECD Guideline 204, semistatic)

Nominal concentration. Literature data. Limit concentration test only (LIMIT test).

Chronic toxicity to aquatic invertebrates:

No observed effect concentration (21 d) 100 mg/l, *Daphnia magna* (OECD Guideline 211, semistatic)

Nominal concentration. Literature data.

Assessment of terrestrial toxicity:

No data available concerning terrestrial toxicity.

12.2. Persistence and degradability

Assessment biodegradation and elimination (H₂O):

Readily biodegradable (according to OECD criteria).

Elimination information:

90 % CO₂ formation relative to the theoretical value (28 d) (OECD 301B; ISO 9439; 92/69/EWG, C.4-C) (aerobic, activated sludge)

Assessment of stability in water:

Substance is readily biodegradable, therefore hydrolysis is not expected to be relevant.

12.3. Bioaccumulative potential

Assessment bioaccumulation potential:

Because of the n-octanol/water distribution coefficient (log Pow) accumulation in organisms is not to be expected.

Bioaccumulation potential:

No data available.

12.4. Mobility in soil

Assessment transport between environmental compartments:

Volatility: The substance will not evaporate into the atmosphere from the water surface.

Adsorption in soil: Adsorption to solid soil phase is not expected.

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 27.05.2025

Version: 8.0

Date / Previous version: 19.09.2023

Previous version: 7.0

Product: **BUTYLGLYCOL**

(ID no. 30034845/SDS_GEN_RO/EN)

Date of print 13.10.2025

12.5. Results of PBT and vPvB assessment

According to Annex XIII of Regulation (EC) No.1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH): The product does not fulfill the criteria for PBT (Persistent/bioaccumulative/toxic) and vPvB (very persistent/very bioaccumulative). Self classification

12.6. Endocrine disrupting properties

The substance is not identified to have endocrine disrupting properties according to Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 nor is included in the Candidate List of substances of very high concern according to EU REACH Article 59 for having endocrine disrupting properties.

12.7. Other adverse effects

The substance is not listed in Regulation (EC) 1005/2009 on substances that deplete the ozone layer.

Results of PMT and vPvM assessment

The substance does not fulfill the PMT criteria. The substance does not fulfill the vPvM criteria.

Additional information

Adsorbable organically-bound halogen (AOX):
This product contains no organically-bound halogen.

SECTION 13: Disposal Considerations

13.1. Waste treatment methods

Must be disposed of or incinerated in accordance with local regulations.

National legislation regarding waste disposal:

GD 856/2002 on waste management records and approving the list of wastes, including hazardous waste.

GEO 92/ 2021 related to the waste regime

GD 1061/2008 on hazardous waste transport in Romania.

Contaminated packaging:

Contaminated packaging should be emptied as far as possible; then it can be passed on for recycling after being thoroughly cleaned. Disposal must be made according to official regulations.

SECTION 14: Transport Information

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 27.05.2025

Version: 8.0

Date / Previous version: 19.09.2023

Previous version: 7.0

Product: **BUTYLGLYCOL**

(ID no. 30034845/SDS_GEN_RO/EN)

Date of print 13.10.2025

Land transport

ADR

	Not classified as a dangerous good under transport regulations
UN number or ID number:	Not applicable
UN proper shipping name:	Not applicable
Transport hazard class(es):	Not applicable
Packing group:	Not applicable
Environmental hazards:	Not applicable
Special precautions for user	None known

RID

	Not classified as a dangerous good under transport regulations
UN number or ID number:	Not applicable
UN proper shipping name:	Not applicable
Transport hazard class(es):	Not applicable
Packing group:	Not applicable
Environmental hazards:	Not applicable
Special precautions for user	None known

Inland waterway transport

ADN

	Not classified as a dangerous good under transport regulations
UN number or ID number:	Not applicable
UN proper shipping name:	Not applicable
Transport hazard class(es):	Not applicable
Packing group:	Not applicable
Environmental hazards:	Not applicable
Special precautions for user:	None known

Transport in inland waterway vessel

UN number or ID number:	ID9003
UN proper shipping name:	SSUBSTANCES WITH FLASH-POINT BETWEEN 60°C - 100°C (ETHYLENE GLYCOL MONOBUTYL ETHER)

Transport hazard class(es):	9, N3, F
Packing group:	Not applicable
Environmental hazards:	yes
Type of inland waterway vessel:	N
Cargo tank design:	4
Cargo tank type:	3

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 27.05.2025

Version: 8.0

Date / Previous version: 19.09.2023

Previous version: 7.0

Product: **BUTYLGLYCOL**

(ID no. 30034845/SDS_GEN_RO/EN)

Date of print 13.10.2025

Sea transport

IMDG

	Not classified as a dangerous good under transport regulations
UN number or ID number:	Not applicable
UN proper shipping name:	Not applicable
Transport hazard class(es):	Not applicable
Packing group:	Not applicable
Environmental hazards:	Not applicable
Special precautions for user	None known

Air transport

IATA/ICAO

	Not classified as a dangerous good under transport regulations
UN number or ID number:	Not applicable
UN proper shipping name:	Not applicable
Transport hazard class(es):	Not applicable
Packing group:	Not applicable
Environmental hazards:	Not applicable
Special precautions for user	None known

14.1. UN number or ID number

See corresponding entries for "UN number or ID number" for the respective regulations in the tables above.

14.2. UN proper shipping name

See corresponding entries for "UN proper shipping name" for the respective regulations in the tables above.

14.3. Transport hazard class(es)

See corresponding entries for "Transport hazard class(es)" for the respective regulations in the tables above.

14.4. Packing group

See corresponding entries for "Packing group" for the respective regulations in the tables above.

14.5. Environmental hazards

See corresponding entries for "Environmental hazards" for the respective regulations in the tables above.

14.6. Special precautions for user

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 27.05.2025

Version: 8.0

Date / Previous version: 19.09.2023

Previous version: 7.0

Product: **BUTYLGLYCOL**

(ID no. 30034845/SDS_GEN_RO/EN)

Date of print 13.10.2025

See corresponding entries for "Special precautions for user" for the respective regulations in the tables above.

14.7. Maritime transport in bulk according to IMO instruments

Regulation:	IBC-Code
Product name:	Ethylene glycol monoalkyl ethers
Pollution category:	Y
Ship Type:	3

SECTION 15: Regulatory Information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Prohibitions, Restrictions and Authorizations

Annex XVII of Regulation (EC) No 1907/2006: Number on List: 3, 75

If other regulatory information applies that is not already provided elsewhere in this safety data sheet, then it is described in this subsection.

15.2. Chemical Safety Assessment

Chemical Safety Assessment performed

SECTION 16: Other Information

Assessment of the hazard classes according to UN GHS criteria (most recent version)

Acute Tox. 4 (oral)
 Eye Irrit. 2A
 Skin Irrit. 2
 Flam. Liq. 4

Full text of the classifications, including the hazard classes and the hazard statements, if mentioned in section 2 or 3:

Acute Tox.	Acute toxicity
Skin Irrit.	Skin irritation
Eye Irrit.	Eye irritation
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H331	Toxic if inhaled.

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 27.05.2025

Version: 8.0

Date / Previous version: 19.09.2023

Previous version: 7.0

Product: **BUTYLGLYCOL**

(ID no. 30034845/SDS_GEN_RO/EN)

Date of print 13.10.2025

H302

Harmful if swallowed.

Abbreviations

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road.
ADN = The European Agreement concerning the International Carriage of Dangerous Goods by Inland waterways. ATE = Acute Toxicity Estimates. CAO = Cargo Aircraft Only. CAS = Chemical Abstract Service. CLP = Classification, Labelling and Packaging of substances and mixtures. DIN = German national organization for standardization. DNEL = Derived No Effect Level. EC50 = Effective concentration median for 50% of the population. EC = European Community. EN = European Standards. IARC = International Agency for Research on Cancer. IATA = International Air Transport Association. IBC-Code = Intermediate Bulk Container code. IMDG = International Maritime Dangerous Goods Code. ISO = International Organization for Standardization. STEL = Short-Term Exposure Limit. LC50 = Lethal concentration median for 50% of the population. LD50 = Lethal dose median for 50% of the population. TLV = Threshold Limit Value. MARPOL = The International Convention for the Prevention of Pollution from Ships. NEN = Dutch Norm. NOEC = No Observed Effect Concentration. OEL = Occupational Exposure Limit. OECD = Organization for Economic Cooperation and Development. PBT = Persistent, Bioaccumulative and Toxic. PNEC = Predicted No Effect Level. PPM = Parts per million. RID = The European Agreement concerning the International Carriage of Dangerous Goods by Rail. TWA = Time Weight Average. UN-number = UN number at transport. vPvB = very Persistent and very Bioaccumulative.

The data contained in this safety data sheet are based on our current knowledge and experience and describe the product only with regard to safety requirements. This safety data sheet is neither a Certificate of Analysis (CoA) nor technical data sheet and shall not be mistaken for a specification agreement. Identified uses in this safety data sheet do neither represent an agreement on the corresponding contractual quality of the substance/mixture nor a contractually designated use. It is the responsibility of the recipient of the product to ensure any proprietary rights and existing laws and legislation are observed.

Vertical lines in the left hand margin indicate an amendment from the previous version.

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 27.05.2025

Version: 8.0

Date / Previous version: 19.09.2023

Previous version: 7.0

Product: **BUTYLGLYCOL**

(ID no. 30034845/SDS_GEN_RO/EN)

Date of print 13.10.2025

Annex: Exposure Scenarios

Index

1. Production

ERC1; PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC15

2. Distribution of substance

ERC2; PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC9, PROC15

3. Formulation

SU10; ERC2; PROC1, PROC2, PROC3, PROC4, PROC5, PROC8a, PROC8b, PROC9, PROC15

4. Use as an intermediate

ERC6a; PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC15

5. Use in Cleaning Agents, (use in industrial settings)

ERC4; PROC1, PROC2, PROC3, PROC4, PROC7, PROC8a, PROC8b, PROC10, PROC13

6. Use in Coatings, (use in industrial settings)

ERC4; PROC1, PROC2, PROC3, PROC4, PROC5, PROC7, PROC8a, PROC8b, PROC9, PROC10, PROC13, PROC15

7. Use in Coatings, (use in professional settings)

ERC8a, ERC8d; PROC1, PROC2, PROC3, PROC4, PROC5, PROC8a, PROC8b, PROC10, PROC11, PROC13, PROC15, PROC19

8. Use in Coatings, (consumer use)

ERC8a, ERC8d; PC9a

9. Use in Cleaning Agents, (use in professional settings)

ERC8a, ERC8d; PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC10, PROC11, PROC13

10. Use in Cleaning Agents, (consumer use)

ERC8a, ERC8d; PC35

11. Road and construction applications

ERC8d; PROC8a, PROC8b, PROC10, PROC11, PROC13

12. Use in Oilfield drilling and production operations

ERC8d; PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b

13. Fire foam

ERC8d; PROC1, PROC3, PROC8a, PROC8b, PROC11

1. Short title of exposure scenario

Production

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 27.05.2025

Version: 8.0

Date / Previous version: 19.09.2023

Previous version: 7.0

Product: **BUTYLGLYCOL**

(ID no. 30034845/SDS_GEN_RO/EN)

Date of print 13.10.2025

ERC1; PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC15

Control of exposure and risk management measures

Contributing exposure scenario	
Use descriptors covered	ERC1: Manufacture of the substance
Operational conditions	
Annual amount used in the EU	45.000.000 kg
Minimum emission days per year	300
Emission factor air	5 %
Emission factor water	6 %
Emission factor soil	0,01 %
Receive Surf. Water (Flow Rate).	43.541 m3/min
Dilution factor river	187,67
Dilution factor coast	100
Risk Management Measures	
Soil treatment measures considered suitable are, e.g.	No application of sludge to soil
Type of STP	Municipal STP
Assumed sewage treatment plant flow (m3/d)	335.890 m3/d
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Environment
Risk Characterization Ratio (RCR)	0,185488
	Risk from environmental exposure is driven by soil.
Maximum amount of safe use	808.677,8 kg/d
Risk from environmental exposure is driven by soil.	

Contributing exposure scenario	
Use descriptors covered	PROC1: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions. Use domain: industrial
Operational conditions	
Concentration of the substance	2-butoxyethanol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance	117 Pa

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 27.05.2025

Version: 8.0

Date / Previous version: 19.09.2023

Previous version: 7.0

Product: **BUTYLGLYCOL**

(ID no. 30034845/SDS_GEN_RO/EN)

Date of print 13.10.2025

during use	
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	0,0343 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,000274
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	0,0492 mg/m ³
Risk Characterization Ratio (RCR)	0,000502
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC2: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions Use domain: industrial
Operational conditions	
Concentration of the substance	2-butoxyethanol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	117 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Use suitable chemically resistant gloves.	Effectiveness: 80 %
Use suitable eye protection., Personal measures have to be applied in case of potential exposure only.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	0,2743 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,002194
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 27.05.2025

Version: 8.0

Date / Previous version: 19.09.2023

Previous version: 7.0

Product: **BUTYLGLYCOL**

(ID no. 30034845/SDS_GEN_RO/EN)

Date of print 13.10.2025

Exposure estimate	4,9239 mg/m ³
Risk Characterization Ratio (RCR)	0,050244
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition Use domain: industrial
Operational conditions	
Concentration of the substance	2-butoxyethanol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	117 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Use suitable chemically resistant gloves.	Effectiveness: 80 %
Use suitable eye protection., Personal measures have to be applied in case of potential exposure only.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	0,1371 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,001097
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	14,7718 mg/m ³
Risk Characterization Ratio (RCR)	0,150732
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC4: Chemical production where opportunity for exposure arises Use domain: industrial
Operational conditions	
Concentration of the substance	2-butoxyethanol

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 27.05.2025

Version: 8.0

Date / Previous version: 19.09.2023

Previous version: 7.0

Product: **BUTYLGLYCOL**

(ID no. 30034845/SDS_GEN_RO/EN)

Date of print 13.10.2025

	Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	117 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Use suitable chemically resistant gloves.	Effectiveness: 80 %
Use suitable eye protection., Personal measures have to be applied in case of potential exposure only.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	1,3714 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,010971
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	24,6196 mg/m ³
Risk Characterization Ratio (RCR)	0,251221
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC8a: Transfer of substance or mixture (charging and discharging) at non-dedicated facilities Use domain: industrial
Operational conditions	
Concentration of the substance	2-butoxyethanol Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	117 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Use suitable chemically resistant gloves.	Effectiveness: 80 %
Use suitable eye protection.	

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 27.05.2025

Version: 8.0

Date / Previous version: 19.09.2023

Previous version: 7.0

Product: **BUTYLGLYCOL**

(ID no. 30034845/SDS_GEN_RO/EN)

Date of print 13.10.2025

Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	2,7429 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,021943
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	49,2393 mg/m ³
Risk Characterization Ratio (RCR)	0,502441
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC8b: Transfer of substance or mixture (charging and discharging) at dedicated facilities Use domain: industrial
Operational conditions	
Concentration of the substance	2-butoxyethanol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	117 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Use suitable chemically resistant gloves.	Effectiveness: 80 %
Use suitable eye protection.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	2,7429 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,021943
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	24,6196 mg/m ³
Risk Characterization Ratio (RCR)	0,251221
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC15: Use a laboratory reagent. Use domain: industrial

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 27.05.2025

Version: 8.0

Date / Previous version: 19.09.2023

Previous version: 7.0

Product: **BUTYLGLYCOL**

(ID no. 30034845/SDS_GEN_RO/EN)

Date of print 13.10.2025

Operational conditions	
Concentration of the substance	2-butoxyethanol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	117 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Use suitable chemically resistant gloves.	Effectiveness: 80 %
Use suitable eye protection.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	0,0686 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,000549
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	24,6196 mg/m ³
Risk Characterization Ratio (RCR)	0,251221
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

2. Short title of exposure scenario

Distribution of substance

ERC2; PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC9, PROC15

Control of exposure and risk management measures

Contributing exposure scenario	
Use descriptors covered	ESVOC SpERC 1.1b.v1: ESVOC SpERC 1.1b.v1
Operational conditions	
Annual amount used in the EU	45.000.000 kg
Minimum emission days per year	300
Emission factor air	0,01 %
Emission factor water	0,001 %

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 27.05.2025

Version: 8.0

Date / Previous version: 19.09.2023

Previous version: 7.0

Product: **BUTYLGLYCOL**

(ID no. 30034845/SDS_GEN_RO/EN)

Date of print 13.10.2025

Emission factor soil	0 %
Receive Surf. Water (Flow Rate).	18.000 m3/d
Dilution factor river	10
Dilution factor coast	100
Risk Management Measures	
Air treatment measures considered suitable are, e.g.	Adsorption
Wastewater treatment measures considered suitable are, e.g.	Acclimated biological treatment
Type of STP	Municipal STP
Assumed sewage treatment plant flow (m3/d)	2.000 m3/d
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Environment
Risk Characterization Ratio (RCR)	0,018685
	Risk from environmental exposure is driven by soil.
Maximum amount of safe use	16.055,5 kg/d
Risk from environmental exposure is driven by soil.	

Contributing exposure scenario	
Use descriptors covered	PROC1: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions. Use domain: industrial
Operational conditions	
Concentration of the substance	2-butoxyethanol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	117 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	0,0343 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,000274
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	0,0492 mg/m ³

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 27.05.2025

Version: 8.0

Date / Previous version: 19.09.2023

Previous version: 7.0

Product: **BUTYLGLYCOL**

(ID no. 30034845/SDS_GEN_RO/EN)

Date of print 13.10.2025

Risk Characterization Ratio (RCR)	0,000502
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC2: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions Use domain: industrial
Operational conditions	
Concentration of the substance	2-butoxyethanol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	117 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Use suitable chemically resistant gloves.	Effectiveness: 80 %
Use suitable eye protection., Personal measures have to be applied in case of potential exposure only.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	0,2743 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,002194
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	4,9239 mg/m ³
Risk Characterization Ratio (RCR)	0,050244
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition Use domain: industrial
Operational conditions	
Concentration of the substance	2-butoxyethanol

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 27.05.2025

Version: 8.0

Date / Previous version: 19.09.2023

Previous version: 7.0

Product: **BUTYLGLYCOL**

(ID no. 30034845/SDS_GEN_RO/EN)

Date of print 13.10.2025

	Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	117 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Use suitable chemically resistant gloves.	Effectiveness: 80 %
Use suitable eye protection., Personal measures have to be applied in case of potential exposure only.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	0,1371 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,001097
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	14,7718 mg/m ³
Risk Characterization Ratio (RCR)	0,150732
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC4: Chemical production where opportunity for exposure arises Use domain: industrial
Operational conditions	
Concentration of the substance	2-butoxyethanol Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	117 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Use suitable chemically resistant gloves.	Effectiveness: 80 %
Use suitable eye protection., Personal	

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 27.05.2025

Version: 8.0

Date / Previous version: 19.09.2023

Previous version: 7.0

Product: **BUTYLGLYCOL**

(ID no. 30034845/SDS_GEN_RO/EN)

Date of print 13.10.2025

measures have to be applied in case of potential exposure only.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	1,3714 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,010971
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	24,6196 mg/m ³
Risk Characterization Ratio (RCR)	0,251221
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC8a: Transfer of substance or mixture (charging and discharging) at non-dedicated facilities Use domain: industrial
Operational conditions	
Concentration of the substance	2-butoxyethanol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	117 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Use suitable chemically resistant gloves.	Effectiveness: 80 %
Use suitable eye protection.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	2,7429 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,021943
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	49,2393 mg/m ³
Risk Characterization Ratio (RCR)	0,502441
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC8b: Transfer of substance or mixture (charging and

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 27.05.2025

Version: 8.0

Date / Previous version: 19.09.2023

Previous version: 7.0

Product: **BUTYLGLYCOL**

(ID no. 30034845/SDS_GEN_RO/EN)

Date of print 13.10.2025

	discharging) at dedicated facilities Use domain: industrial
Operational conditions	
Concentration of the substance	2-butoxyethanol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	117 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Use suitable chemically resistant gloves.	Effectiveness: 80 %
Use suitable eye protection.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	2,7429 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,021943
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	24,6196 mg/m ³
Risk Characterization Ratio (RCR)	0,251221
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing). Use domain: industrial
Operational conditions	
Concentration of the substance	2-butoxyethanol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	117 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 27.05.2025

Version: 8.0

Date / Previous version: 19.09.2023

Previous version: 7.0

Product: **BUTYLGLYCOL**

(ID no. 30034845/SDS_GEN_RO/EN)

Date of print 13.10.2025

Use suitable chemically resistant gloves.	Effectiveness: 80 %
Use suitable eye protection.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	1,3714 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,010971
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	24,6196 mg/m ³
Risk Characterization Ratio (RCR)	0,251221
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC15: Use a laboratory reagent. Use domain: industrial
Operational conditions	
Concentration of the substance	2-butoxyethanol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	117 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Use suitable chemically resistant gloves.	Effectiveness: 80 %
Use suitable eye protection.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	0,0686 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,000549
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	24,6196 mg/m ³
Risk Characterization Ratio (RCR)	0,251221
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 27.05.2025

Version: 8.0

Date / Previous version: 19.09.2023

Previous version: 7.0

Product: **BUTYLGLYCOL**

(ID no. 30034845/SDS_GEN_RO/EN)

Date of print 13.10.2025

3. Short title of exposure scenario

Formulation

SU10; ERC2; PROC1, PROC2, PROC3, PROC4, PROC5, PROC8a, PROC8b, PROC9, PROC15

Control of exposure and risk management measures

Contributing exposure scenario	
Use descriptors covered	ESVOC SpERC 2.2.v1: ESVOC SpERC 2.2.v1
Operational conditions	
Annual amount used in the EU	25.000.000 kg
Minimum emission days per year	300
Emission factor air	1 %
Emission factor water	0,5 %
Emission factor soil	0,01 %
Receive Surf. Water (Flow Rate).	18.000 m3/d
Dilution factor river	10
Dilution factor coast	100
Risk Management Measures	
Air treatment measures considered suitable are, e.g.	Wet scrubber - for dusts, Filtration, Waste gas treatment by thermal oxidation, Adsorption
Wastewater treatment measures considered suitable are, e.g.	Acclimated biological treatment, Distillation
Type of STP	Municipal STP
Assumed sewage treatment plant flow (m3/d)	2.000 m3/d
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Environment
Risk Characterization Ratio (RCR)	0,656739
	Risk from environmental exposure is driven by soil.
Maximum amount of safe use	126.889,5 kg/d
Risk from environmental exposure is driven by soil.	
Contributing exposure scenario	
Use descriptors covered	PROC1: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions.

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 27.05.2025

Version: 8.0

Date / Previous version: 19.09.2023

Previous version: 7.0

Product: **BUTYLGLYCOL**

(ID no. 30034845/SDS_GEN_RO/EN)

Date of print 13.10.2025

	Use domain: industrial
Operational conditions	
Concentration of the substance	2-butoxyethanol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	117 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	0,0343 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,000274
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	0,0492 mg/m ³
Risk Characterization Ratio (RCR)	0,000502
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC2: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions Use domain: industrial
Operational conditions	
Concentration of the substance	2-butoxyethanol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	117 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Use suitable chemically resistant gloves.	Effectiveness: 80 %
Use suitable eye protection., Personal measures have to be applied in case	

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 27.05.2025

Version: 8.0

Date / Previous version: 19.09.2023

Previous version: 7.0

Product: **BUTYLGLYCOL**

(ID no. 30034845/SDS_GEN_RO/EN)

Date of print 13.10.2025

of potential exposure only.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	0,2743 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,002194
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	4,9239 mg/m ³
Risk Characterization Ratio (RCR)	0,050244
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition Use domain: industrial
Operational conditions	
Concentration of the substance	2-butoxyethanol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	117 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Use suitable chemically resistant gloves.	Effectiveness: 80 %
Use suitable eye protection., Personal measures have to be applied in case of potential exposure only.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	0,1371 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,001097
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	14,7718 mg/m ³
Risk Characterization Ratio (RCR)	0,150732
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 27.05.2025

Version: 8.0

Date / Previous version: 19.09.2023

Previous version: 7.0

Product: **BUTYLGLYCOL**

(ID no. 30034845/SDS_GEN_RO/EN)

Date of print 13.10.2025

Contributing exposure scenario	
Use descriptors covered	PROC4: Chemical production where opportunity for exposure arises Use domain: industrial
Operational conditions	
Concentration of the substance	2-butoxyethanol Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	117 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Use suitable chemically resistant gloves.	Effectiveness: 80 %
Use suitable eye protection., Personal measures have to be applied in case of potential exposure only.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	1,3714 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,010971
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	24,6196 mg/m ³
Risk Characterization Ratio (RCR)	0,251221
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC5: Mixing or blending in batch processes Use domain: industrial
Operational conditions	
Concentration of the substance	2-butoxyethanol Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	117 Pa
Process temperature	20 °C

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 27.05.2025

Version: 8.0

Date / Previous version: 19.09.2023

Previous version: 7.0

Product: **BUTYLGLYCOL**

(ID no. 30034845/SDS_GEN_RO/EN)

Date of print 13.10.2025

Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Use suitable chemically resistant gloves.	Effectiveness: 80 %
Use suitable eye protection.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	2,7429 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,021943
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	24,6196 mg/m ³
Risk Characterization Ratio (RCR)	0,251221
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC8a: Transfer of substance or mixture (charging and discharging) at non-dedicated facilities Use domain: industrial
Operational conditions	
Concentration of the substance	2-butoxyethanol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	117 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Use suitable chemically resistant gloves.	Effectiveness: 80 %
Use suitable eye protection.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	2,7429 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,021943
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	49,2393 mg/m ³
Risk Characterization Ratio (RCR)	0,502441

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 27.05.2025

Version: 8.0

Date / Previous version: 19.09.2023

Previous version: 7.0

Product: **BUTYLGLYCOL**

(ID no. 30034845/SDS_GEN_RO/EN)

Date of print 13.10.2025

Guidance to Downstream Users

For scaling see: <http://www.ecetoc.org/tra>

Contributing exposure scenario

Use descriptors covered	PROC8b: Transfer of substance or mixture (charging and discharging) at dedicated facilities Use domain: industrial
--------------------------------	---

Operational conditions

Concentration of the substance	2-butoxyethanol Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	117 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor

Risk Management Measures

Use suitable chemically resistant gloves.	Effectiveness: 80 %
Use suitable eye protection.	

Exposure estimate and reference to its source

Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	2,7429 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,021943
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	24,6196 mg/m ³
Risk Characterization Ratio (RCR)	0,251221

Guidance to Downstream Users

For scaling see: <http://www.ecetoc.org/tra>

Contributing exposure scenario

Use descriptors covered	PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing). Use domain: industrial
--------------------------------	---

Operational conditions

Concentration of the substance	2-butoxyethanol Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	117 Pa
Process temperature	20 °C

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 27.05.2025

Version: 8.0

Date / Previous version: 19.09.2023

Previous version: 7.0

Product: **BUTYLGLYCOL**

(ID no. 30034845/SDS_GEN_RO/EN)

Date of print 13.10.2025

Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Use suitable chemically resistant gloves.	Effectiveness: 80 %
Use suitable eye protection.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	1,3714 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,010971
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	24,6196 mg/m ³
Risk Characterization Ratio (RCR)	0,251221
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC15: Use a laboratory reagent. Use domain: industrial
Operational conditions	
Concentration of the substance	2-butoxyethanol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	117 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Use suitable chemically resistant gloves.	Effectiveness: 80 %
Use suitable eye protection.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	0,0686 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,000549
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	24,6196 mg/m ³
Risk Characterization Ratio (RCR)	0,251221

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 27.05.2025

Version: 8.0

Date / Previous version: 19.09.2023

Previous version: 7.0

Product: **BUTYLGLYCOL**

(ID no. 30034845/SDS_GEN_RO/EN)

Date of print 13.10.2025

Guidance to Downstream Users

For scaling see: <http://www.ecetoc.org/tra>

4. Short title of exposure scenario

Use as an intermediate

ERC6a; PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC15

Control of exposure and risk management measures

Contributing exposure scenario	
Use descriptors covered	ESVOC SpERC 6.1a.v1: ESVOC SpERC 6.1a.v1
Operational conditions	
Annual amount used in the EU	5.000.000 kg
Minimum emission days per year	300
Emission factor air	0,02 %
Emission factor water	1 %
Emission factor soil	0,1 %
Receive Surf. Water (Flow Rate).	18.000 m3/d
Dilution factor river	10
Dilution factor coast	100
Risk Management Measures	
Air treatment measures considered suitable are, e.g.	Wet scrubber - for dusts, Adsorption
Wastewater treatment measures considered suitable are, e.g.	Acclimated biological treatment
Type of STP	Municipal STP
Assumed sewage treatment plant flow (m3/d)	2.000 m3/d
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Environment
Risk Characterization Ratio (RCR)	0,266564
	Risk from environmental exposure is driven by soil.
Maximum amount of safe use	62.524 kg/d
Risk from environmental exposure is driven by soil.	

Contributing exposure scenario

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 27.05.2025

Version: 8.0

Date / Previous version: 19.09.2023

Previous version: 7.0

Product: **BUTYLGLYCOL**

(ID no. 30034845/SDS_GEN_RO/EN)

Date of print 13.10.2025

Use descriptors covered	PROC1: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions. Use domain: industrial
Operational conditions	
Concentration of the substance	2-butoxyethanol Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	117 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	0,0343 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,000274
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	0,0492 mg/m ³
Risk Characterization Ratio (RCR)	0,000502
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC2: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions Use domain: industrial
Operational conditions	
Concentration of the substance	2-butoxyethanol Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	117 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Use suitable chemically resistant	Effectiveness: 80 %

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 27.05.2025

Version: 8.0

Date / Previous version: 19.09.2023

Previous version: 7.0

Product: **BUTYLGLYCOL**

(ID no. 30034845/SDS_GEN_RO/EN)

Date of print 13.10.2025

gloves.	
Use suitable eye protection., Personal measures have to be applied in case of potential exposure only.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	0,2743 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,002194
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	4,9239 mg/m ³
Risk Characterization Ratio (RCR)	0,050244
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition Use domain: industrial
Operational conditions	
Concentration of the substance	2-butoxyethanol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	117 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Use suitable chemically resistant gloves.	Effectiveness: 80 %
Use suitable eye protection., Personal measures have to be applied in case of potential exposure only.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	0,1371 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,001097
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	14,7718 mg/m ³

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 27.05.2025

Version: 8.0

Date / Previous version: 19.09.2023

Previous version: 7.0

Product: **BUTYLGLYCOL**

(ID no. 30034845/SDS_GEN_RO/EN)

Date of print 13.10.2025

Risk Characterization Ratio (RCR)	0,150732
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC4: Chemical production where opportunity for exposure arises Use domain: industrial
Operational conditions	
Concentration of the substance	2-butoxyethanol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	117 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Use suitable chemically resistant gloves.	Effectiveness: 80 %
Use suitable eye protection., Personal measures have to be applied in case of potential exposure only.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	1,3714 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,010971
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	24,6196 mg/m ³
Risk Characterization Ratio (RCR)	0,251221
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC8a: Transfer of substance or mixture (charging and discharging) at non-dedicated facilities Use domain: industrial
Operational conditions	
Concentration of the substance	2-butoxyethanol Content: >= 0 % - <= 100 %
Physical state	liquid

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 27.05.2025

Version: 8.0

Date / Previous version: 19.09.2023

Previous version: 7.0

Product: **BUTYLGLYCOL**

(ID no. 30034845/SDS_GEN_RO/EN)

Date of print 13.10.2025

Vapour pressure of the substance during use	117 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Use suitable chemically resistant gloves.	Effectiveness: 80 %
Use suitable eye protection.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	2,7429 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,021943
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	49,2393 mg/m ³
Risk Characterization Ratio (RCR)	0,502441
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC8b: Transfer of substance or mixture (charging and discharging) at dedicated facilities Use domain: industrial
Operational conditions	
Concentration of the substance	2-butoxyethanol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	117 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Use suitable chemically resistant gloves.	Effectiveness: 80 %
Use suitable eye protection.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	2,7429 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,021943

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 27.05.2025

Version: 8.0

Date / Previous version: 19.09.2023

Previous version: 7.0

Product: **BUTYLGLYCOL**

(ID no. 30034845/SDS_GEN_RO/EN)

Date of print 13.10.2025

Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	24,6196 mg/m ³
Risk Characterization Ratio (RCR)	0,251221
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC15: Use a laboratory reagent. Use domain: industrial
Operational conditions	
Concentration of the substance	2-butoxyethanol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	117 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Use suitable chemically resistant gloves.	Effectiveness: 80 %
Use suitable eye protection.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	0,0686 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,000549
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	24,6196 mg/m ³
Risk Characterization Ratio (RCR)	0,251221
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

5. Short title of exposure scenario

Use in Cleaning Agents, (use in industrial settings)

ERC4; PROC1, PROC2, PROC3, PROC4, PROC7, PROC8a, PROC8b, PROC10, PROC13

Control of exposure and risk management measures

Contributing exposure scenario

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 27.05.2025

Version: 8.0

Date / Previous version: 19.09.2023

Previous version: 7.0

Product: **BUTYLGLYCOL**

(ID no. 30034845/SDS_GEN_RO/EN)

Date of print 13.10.2025

Use descriptors covered	ESVOC SpERC 4.4a.v1: ESVOC SpERC 4.4a.v1	
Operational conditions		
Annual amount used in the EU	12.000.000 kg	
Minimum emission days per year	20	
Emission factor air	30 %	
Emission factor water	0,01 %	
Emission factor soil	0 %	
Receive Surf. Water (Flow Rate).	18.000 m3/d	
Dilution factor river	10	
Dilution factor coast	100	
Risk Management Measures		
Air treatment measures considered suitable are, e.g.	Wet scrubber - for dusts, Waste gas treatment by thermal oxidation, Adsorption	
Wastewater treatment measures considered suitable are, e.g.	Acclimated biological treatment, Distillation	
Type of STP	Municipal STP	
Assumed sewage treatment plant flow (m3/d)	2.000 m3/d	
Exposure estimate and reference to its source		
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Environment	
Risk Characterization Ratio (RCR)	0,021648	
	Risk from environmental exposure is driven by soil.	
Maximum amount of safe use	230.973,3 kg/d	
Risk from environmental exposure is driven by soil.		

Contributing exposure scenario	
Use descriptors covered	PROC1: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions. Use domain: industrial
Operational conditions	
Concentration of the substance	2-butoxyethanol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	117 Pa

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 27.05.2025

Version: 8.0

Date / Previous version: 19.09.2023

Previous version: 7.0

Product: **BUTYLGLYCOL**

(ID no. 30034845/SDS_GEN_RO/EN)

Date of print 13.10.2025

Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	0,0343 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,000274
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	0,0492 mg/m ³
Risk Characterization Ratio (RCR)	0,000502
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC2: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions Use domain: industrial
Operational conditions	
Concentration of the substance	2-butoxyethanol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	117 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Use suitable chemically resistant gloves.	Effectiveness: 80 %
Use suitable eye protection., Personal measures have to be applied in case of potential exposure only.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	0,2743 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,002194
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	4,9239 mg/m ³

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 27.05.2025

Version: 8.0

Date / Previous version: 19.09.2023

Previous version: 7.0

Product: **BUTYLGLYCOL**

(ID no. 30034845/SDS_GEN_RO/EN)

Date of print 13.10.2025

Risk Characterization Ratio (RCR)	0,050244
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition Use domain: industrial
Operational conditions	
Concentration of the substance	2-butoxyethanol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	117 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Use suitable chemically resistant gloves.	Effectiveness: 80 %
Use suitable eye protection., Personal measures have to be applied in case of potential exposure only.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	0,1371 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,001097
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	14,7718 mg/m ³
Risk Characterization Ratio (RCR)	0,150732
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC4: Chemical production where opportunity for exposure arises Use domain: industrial
Operational conditions	
Concentration of the substance	2-butoxyethanol Content: >= 0 % - <= 100 %

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 27.05.2025

Version: 8.0

Date / Previous version: 19.09.2023

Previous version: 7.0

Product: **BUTYLGLYCOL**

(ID no. 30034845/SDS_GEN_RO/EN)

Date of print 13.10.2025

Physical state	liquid
Vapour pressure of the substance during use	117 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Use suitable chemically resistant gloves.	Effectiveness: 80 %
Use suitable eye protection., Personal measures have to be applied in case of potential exposure only.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	1,3714 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,010971
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	24,6196 mg/m ³
Risk Characterization Ratio (RCR)	0,251221
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC7: Industrial spraying Use domain: industrial
Operational conditions	
Concentration of the substance	2-butoxyethanol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	117 Pa
Process temperature	20 °C
Duration and Frequency of activity	240 min 5 days per week
Indoor/Outdoor	Indoor
Application rate	< 3 l/min
Risk Management Measures	
Wear suitable respiratory protection.	Effectiveness: 95 %
Use suitable chemically resistant gloves.	Effectiveness: 80 %
Ensure that the task is not carried out	

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 27.05.2025

Version: 8.0

Date / Previous version: 19.09.2023

Previous version: 7.0

Product: **BUTYLGLYCOL**

(ID no. 30034845/SDS_GEN_RO/EN)

Date of print 13.10.2025

overhead. Provide specific employee training to prevent/minimize exposures. Regular inspection and maintenance of equipment and machines.	
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	
Use suitable eye protection.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	8,5714 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,068571
Assessment method	EASY TRA v4.2, Advanced REACH Tool v1.5
	Worker - inhalation, long-term - systemic
Exposure estimate	55 mg/m ³
Risk Characterization Ratio (RCR)	0,561224
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra For scaling see: http://www.advancedreachtool.com	

Contributing exposure scenario	
Use descriptors covered	PROC7: Industrial spraying Use domain: industrial
Operational conditions	
Concentration of the substance	2-butoxyethanol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	117 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Use suitable chemically resistant gloves.	Effectiveness: 80 %
Regular inspection and maintenance of equipment and machines.	
Ensure containment of the emission source and provide extract ventilation to points where emission occur	
Use suitable eye protection.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 27.05.2025

Version: 8.0

Date / Previous version: 19.09.2023

Previous version: 7.0

Product: **BUTYLGLYCOL**

(ID no. 30034845/SDS_GEN_RO/EN)

Date of print 13.10.2025

Exposure estimate	8,5714 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,068571
Assessment method	EASY TRA v4.2, Advanced REACH Tool v1.5
	Worker - inhalation, long-term - systemic
Exposure estimate	42 mg/m ³
Risk Characterization Ratio (RCR)	0,428571
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra For scaling see: http://www.advancedreachtool.com	

Contributing exposure scenario	
Use descriptors covered	PROC8a: Transfer of substance or mixture (charging and discharging) at non-dedicated facilities Use domain: industrial
Operational conditions	
Concentration of the substance	2-butoxyethanol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	117 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Use suitable chemically resistant gloves.	Effectiveness: 80 %
Use suitable eye protection.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	2,7429 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,021943
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	49,2393 mg/m ³
Risk Characterization Ratio (RCR)	0,502441
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC8b: Transfer of substance or mixture (charging and discharging) at dedicated facilities Use domain: industrial
Operational conditions	
Concentration of the substance	2-butoxyethanol

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 27.05.2025

Version: 8.0

Date / Previous version: 19.09.2023

Previous version: 7.0

Product: **BUTYLGLYCOL**

(ID no. 30034845/SDS_GEN_RO/EN)

Date of print 13.10.2025

	Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	117 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Use suitable chemically resistant gloves.	Effectiveness: 80 %
Use suitable eye protection.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	2,7429 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,021943
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	24,6196 mg/m ³
Risk Characterization Ratio (RCR)	0,251221
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC10: Roller application or brushing Use domain: industrial
Operational conditions	
Concentration of the substance	2-butoxyethanol Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	117 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Use suitable chemically resistant gloves.	Effectiveness: 80 %
Use suitable eye protection.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 27.05.2025

Version: 8.0

Date / Previous version: 19.09.2023

Previous version: 7.0

Product: **BUTYLGLYCOL**

(ID no. 30034845/SDS_GEN_RO/EN)

Date of print 13.10.2025

Exposure estimate	5,4857 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,043886
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	49,2393 mg/m ³
Risk Characterization Ratio (RCR)	0,502441
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC13: Treatment of articles by dipping and pouring. Use domain: industrial
Operational conditions	
Concentration of the substance	2-butoxyethanol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	117 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Use suitable chemically resistant gloves.	Effectiveness: 80 %
Use suitable eye protection.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	2,7429 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,021943
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	49,2393 mg/m ³
Risk Characterization Ratio (RCR)	0,502441
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

6. Short title of exposure scenario

Use in Coatings, (use in industrial settings)

ERC4; PROC1, PROC2, PROC3, PROC4, PROC5, PROC7, PROC8a, PROC8b, PROC9, PROC10, PROC13, PROC15

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 27.05.2025

Version: 8.0

Date / Previous version: 19.09.2023

Previous version: 7.0

Product: **BUTYLGLYCOL**

(ID no. 30034845/SDS_GEN_RO/EN)

Date of print 13.10.2025

Control of exposure and risk management measures

Contributing exposure scenario	
Use descriptors covered	ESVOC SpERC 4.3a.v1: ESVOC SpERC 4.3a.v1
Operational conditions	
Annual amount used in the EU	12.000.000 kg
Minimum emission days per year	300
Emission factor air	98 %
Emission factor water	2 %
Emission factor soil	0 %
Receive Surf. Water (Flow Rate).	18.000 m3/d
Dilution factor river	10
Dilution factor coast	100
Risk Management Measures	
Air treatment measures considered suitable are, e.g.	Wet scrubber - for dusts, Filtration, Waste gas treatment by thermal oxidation, Adsorption
Wastewater treatment measures considered suitable are, e.g.	Acclimated biological treatment, Distillation
Type of STP	Municipal STP
Assumed sewage treatment plant flow (m3/d)	2.000 m3/d
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Environment
Risk Characterization Ratio (RCR)	0,224811
	Risk from environmental exposure is driven by soil.
Maximum amount of safe use	17.792,7 kg/d
Risk from environmental exposure is driven by soil.	

Contributing exposure scenario	
Use descriptors covered	PROC1: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions. Use domain: industrial
Operational conditions	
Concentration of the substance	2-butoxyethanol Content: >= 0 % - <= 100 %

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 27.05.2025

Version: 8.0

Date / Previous version: 19.09.2023

Previous version: 7.0

Product: **BUTYLGLYCOL**

(ID no. 30034845/SDS_GEN_RO/EN)

Date of print 13.10.2025

Physical state	liquid
Vapour pressure of the substance during use	117 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	0,0343 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,000274
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	0,0492 mg/m ³
Risk Characterization Ratio (RCR)	0,000502
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC2: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions Use domain: industrial
Operational conditions	
Concentration of the substance	2-butoxyethanol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	117 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Use suitable chemically resistant gloves.	Effectiveness: 80 %
Use suitable eye protection., Personal measures have to be applied in case of potential exposure only.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	0,2743 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,002194

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 27.05.2025

Version: 8.0

Date / Previous version: 19.09.2023

Previous version: 7.0

Product: **BUTYLGLYCOL**

(ID no. 30034845/SDS_GEN_RO/EN)

Date of print 13.10.2025

Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	4,9239 mg/m ³
Risk Characterization Ratio (RCR)	0,050244
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition Use domain: industrial
Operational conditions	
Concentration of the substance	2-butoxyethanol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	117 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Use suitable chemically resistant gloves.	Effectiveness: 80 %
Use suitable eye protection., Personal measures have to be applied in case of potential exposure only.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	0,1371 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,001097
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	14,7718 mg/m ³
Risk Characterization Ratio (RCR)	0,150732
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC4: Chemical production where opportunity for exposure arises Use domain: industrial

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 27.05.2025

Version: 8.0

Date / Previous version: 19.09.2023

Previous version: 7.0

Product: **BUTYLGLYCOL**

(ID no. 30034845/SDS_GEN_RO/EN)

Date of print 13.10.2025

Operational conditions	
Concentration of the substance	2-butoxyethanol Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	117 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Use suitable chemically resistant gloves.	Effectiveness: 80 %
Use suitable eye protection., Personal measures have to be applied in case of potential exposure only.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	1,3714 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,010971
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	24,6196 mg/m ³
Risk Characterization Ratio (RCR)	0,251221
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC5: Mixing or blending in batch processes Use domain: industrial
Operational conditions	
Concentration of the substance	2-butoxyethanol Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	117 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Use suitable chemically resistant gloves.	Effectiveness: 80 %

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 27.05.2025

Version: 8.0

Date / Previous version: 19.09.2023

Previous version: 7.0

Product: **BUTYLGLYCOL**

(ID no. 30034845/SDS_GEN_RO/EN)

Date of print 13.10.2025

Use suitable eye protection.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	2,7429 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,021943
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	24,6196 mg/m ³
Risk Characterization Ratio (RCR)	0,251221
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC7: Industrial spraying Use domain: industrial
Operational conditions	
Concentration of the substance	2-butoxyethanol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	117 Pa
Process temperature	20 °C
Duration and Frequency of activity	240 min 5 days per week
Indoor/Outdoor	Indoor
Application rate	< 3 l/min
Risk Management Measures	
Wear suitable respiratory protection.	Effectiveness: 95 %
Use suitable chemically resistant gloves.	Effectiveness: 80 %
Ensure that the task is not carried out overhead. Provide specific employee training to prevent/minimize exposures. Regular inspection and maintenance of equipment and machines.	
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	
Use suitable eye protection.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	8,5714 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,068571

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 27.05.2025

Version: 8.0

Date / Previous version: 19.09.2023

Previous version: 7.0

Product: **BUTYLGLYCOL**

(ID no. 30034845/SDS_GEN_RO/EN)

Date of print 13.10.2025

Assessment method	EASY TRA v4.2, Advanced REACH Tool v1.5
	Worker - inhalation, long-term - systemic
Exposure estimate	55 mg/m ³
Risk Characterization Ratio (RCR)	0,561224
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra For scaling see: http://www.advancedreachtool.com	

Contributing exposure scenario	
Use descriptors covered	PROC7: Industrial spraying Use domain: industrial
Operational conditions	
Concentration of the substance	2-butoxyethanol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	117 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Use suitable chemically resistant gloves.	Effectiveness: 80 %
Regular inspection and maintenance of equipment and machines.	
Ensure containment of the emission source and provide extract ventilation to points where emission occur	
Use suitable eye protection.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	8,5714 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,068571
Assessment method	EASY TRA v4.2, Advanced REACH Tool v1.5
	Worker - inhalation, long-term - systemic
Exposure estimate	42 mg/m ³
Risk Characterization Ratio (RCR)	0,428571
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra For scaling see: http://www.advancedreachtool.com	

Contributing exposure scenario	
Use descriptors covered	PROC8a: Transfer of substance or mixture (charging and discharging) at non-dedicated facilities Use domain: industrial

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 27.05.2025

Version: 8.0

Date / Previous version: 19.09.2023

Previous version: 7.0

Product: **BUTYLGLYCOL**

(ID no. 30034845/SDS_GEN_RO/EN)

Date of print 13.10.2025

Operational conditions	
Concentration of the substance	2-butoxyethanol Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	117 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Use suitable chemically resistant gloves.	Effectiveness: 80 %
Use suitable eye protection.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	2,7429 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,021943
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	49,2393 mg/m ³
Risk Characterization Ratio (RCR)	0,502441
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC8b: Transfer of substance or mixture (charging and discharging) at dedicated facilities Use domain: industrial
Operational conditions	
Concentration of the substance	2-butoxyethanol Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	117 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Use suitable chemically resistant gloves.	Effectiveness: 80 %
Use suitable eye protection.	

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 27.05.2025

Version: 8.0

Date / Previous version: 19.09.2023

Previous version: 7.0

Product: **BUTYLGLYCOL**

(ID no. 30034845/SDS_GEN_RO/EN)

Date of print 13.10.2025

Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	2,7429 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,021943
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	24,6196 mg/m ³
Risk Characterization Ratio (RCR)	0,251221
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing). Use domain: industrial
Operational conditions	
Concentration of the substance	2-butoxyethanol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	117 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Use suitable chemically resistant gloves.	Effectiveness: 80 %
Use suitable eye protection.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	1,3714 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,010971
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	24,6196 mg/m ³
Risk Characterization Ratio (RCR)	0,251221
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC10: Roller application or brushing Use domain: industrial

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 27.05.2025

Version: 8.0

Date / Previous version: 19.09.2023

Previous version: 7.0

Product: **BUTYLGLYCOL**

(ID no. 30034845/SDS_GEN_RO/EN)

Date of print 13.10.2025

Operational conditions	
Concentration of the substance	2-butoxyethanol Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	117 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Use suitable chemically resistant gloves.	Effectiveness: 80 %
Use suitable eye protection.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	5,4857 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,043886
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	49,2393 mg/m ³
Risk Characterization Ratio (RCR)	0,502441
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC13: Treatment of articles by dipping and pouring. Use domain: industrial
Operational conditions	
Concentration of the substance	2-butoxyethanol Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	117 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Use suitable chemically resistant gloves.	Effectiveness: 80 %
Use suitable eye protection.	
Exposure estimate and reference to its source	

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 27.05.2025

Version: 8.0

Date / Previous version: 19.09.2023

Previous version: 7.0

Product: **BUTYLGLYCOL**

(ID no. 30034845/SDS_GEN_RO/EN)

Date of print 13.10.2025

Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	2,7429 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,021943
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	49,2393 mg/m ³
Risk Characterization Ratio (RCR)	0,502441
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC15: Use a laboratory reagent. Use domain: industrial
Operational conditions	
Concentration of the substance	2-butoxyethanol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	117 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Use suitable chemically resistant gloves.	Effectiveness: 80 %
Use suitable eye protection.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	0,0686 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,000549
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	24,6196 mg/m ³
Risk Characterization Ratio (RCR)	0,251221
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

7. Short title of exposure scenario

Use in Coatings, (use in professional settings)

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 27.05.2025

Version: 8.0

Date / Previous version: 19.09.2023

Previous version: 7.0

Product: **BUTYLGLYCOL**

(ID no. 30034845/SDS_GEN_RO/EN)

Date of print 13.10.2025

ERC8a, ERC8d; PROC1, PROC2, PROC3, PROC4, PROC5, PROC8a, PROC8b, PROC10, PROC11, PROC13, PROC15, PROC19

Control of exposure and risk management measures

Contributing exposure scenario	
Use descriptors covered	ESVOC SpERC 8.3b.v1: ESVOC SpERC 8.3b.v1
Operational conditions	
Annual amount used in the EU	4.000.000 kg
Minimum emission days per year	365
Emission factor air	98 %
Emission factor water	1 %
Emission factor soil	1 %
Receive Surf. Water (Flow Rate).	18.000 m3/d
Dilution factor river	10
Dilution factor coast	100
Risk Management Measures	
Type of STP	Municipal STP
Assumed sewage treatment plant flow (m3/d)	2.000 m3/d
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Environment
Risk Characterization Ratio (RCR)	0,018688
	Risk from environmental exposure is driven by soil.
Maximum amount of safe use	29,3 kg/d
Risk from environmental exposure is driven by soil.	

Contributing exposure scenario	
Use descriptors covered	ESVOC SpERC 8.3b.v1: ESVOC SpERC 8.3b.v1
Operational conditions	
Annual amount used in the EU	4.000.000 kg
Minimum emission days per year	365
Emission factor air	98 %
Emission factor water	1 %

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 27.05.2025

Version: 8.0

Date / Previous version: 19.09.2023

Previous version: 7.0

Product: **BUTYLGLYCOL**

(ID no. 30034845/SDS_GEN_RO/EN)

Date of print 13.10.2025

Emission factor soil	1 %
Receive Surf. Water (Flow Rate).	18.000 m3/d
Dilution factor river	10
Dilution factor coast	100
Risk Management Measures	
Type of STP	Municipal STP
Assumed sewage treatment plant flow (m3/d)	2.000 m3/d
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Environment
Risk Characterization Ratio (RCR)	0,018688
	Risk from environmental exposure is driven by soil.
Maximum amount of safe use	29,3 kg/d
Risk from environmental exposure is driven by soil.	

Contributing exposure scenario	
Use descriptors covered	PROC1: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions. Use domain: professional
Operational conditions	
Concentration of the substance	2-butoxyethanol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	117 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	0,0343 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,000274
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	0,0492 mg/m ³
Risk Characterization Ratio (RCR)	0,000502
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 27.05.2025

Version: 8.0

Date / Previous version: 19.09.2023

Previous version: 7.0

Product: **BUTYLGLYCOL**

(ID no. 30034845/SDS_GEN_RO/EN)

Date of print 13.10.2025

Contributing exposure scenario	
Use descriptors covered	PROC2: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions Use domain: professional
Operational conditions	
Concentration of the substance	2-butoxyethanol Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	117 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Use suitable chemically resistant gloves.	Effectiveness: 80 %
Use suitable eye protection., Personal measures have to be applied in case of potential exposure only.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	0,2743 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,002194
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	24,6196 mg/m ³
Risk Characterization Ratio (RCR)	0,251221
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition Use domain: professional
Operational conditions	
Concentration of the substance	2-butoxyethanol Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 27.05.2025

Version: 8.0

Date / Previous version: 19.09.2023

Previous version: 7.0

Product: **BUTYLGLYCOL**

(ID no. 30034845/SDS_GEN_RO/EN)

Date of print 13.10.2025

Vapour pressure of the substance during use	117 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Use suitable chemically resistant gloves.	Effectiveness: 80 %
Use suitable eye protection., Personal measures have to be applied in case of potential exposure only.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	0,1371 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,001097
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	14,7718 mg/m ³
Risk Characterization Ratio (RCR)	0,150732
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC4: Chemical production where opportunity for exposure arises Use domain: professional
Operational conditions	
Concentration of the substance	2-butoxyethanol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	117 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Use suitable chemically resistant gloves.	Effectiveness: 80 %
Use suitable eye protection., Personal measures have to be applied in case of potential exposure only.	
Exposure estimate and reference to its source	

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 27.05.2025

Version: 8.0

Date / Previous version: 19.09.2023

Previous version: 7.0

Product: **BUTYLGLYCOL**

(ID no. 30034845/SDS_GEN_RO/EN)

Date of print 13.10.2025

Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	1,3714 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,010971
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	49,2393 mg/m ³
Risk Characterization Ratio (RCR)	0,502441
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC5: Mixing or blending in batch processes Use domain: professional
Operational conditions	
Concentration of the substance	2-butoxyethanol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	117 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Use suitable chemically resistant gloves.	Effectiveness: 80 %
Use suitable eye protection.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	2,7429 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,021943
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	49,2393 mg/m ³
Risk Characterization Ratio (RCR)	0,502441
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC8a: Transfer of substance or mixture (charging and discharging) at non-dedicated facilities Use domain: professional
Operational conditions	

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 27.05.2025

Version: 8.0

Date / Previous version: 19.09.2023

Previous version: 7.0

Product: **BUTYLGLYCOL**

(ID no. 30034845/SDS_GEN_RO/EN)

Date of print 13.10.2025

Concentration of the substance	2-butoxyethanol Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	117 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Provide a good standard of general or controlled ventilation (5 to 10 air changes per hour)	Effectiveness: 70 %
Use suitable chemically resistant gloves.	Effectiveness: 80 %
Use suitable eye protection.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	2,7429 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,021943
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	36,9294 mg/m ³
Risk Characterization Ratio (RCR)	0,376831
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC8b: Transfer of substance or mixture (charging and discharging) at dedicated facilities Use domain: professional
Operational conditions	
Concentration of the substance	2-butoxyethanol Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	117 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Use suitable chemically resistant	Effectiveness: 80 %

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 27.05.2025

Version: 8.0

Date / Previous version: 19.09.2023

Previous version: 7.0

Product: **BUTYLGLYCOL**

(ID no. 30034845/SDS_GEN_RO/EN)

Date of print 13.10.2025

gloves.	
Use suitable eye protection.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	2,7429 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,021943
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	49,2393 mg/m ³
Risk Characterization Ratio (RCR)	0,502441
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC10: Roller application or brushing Use domain: professional
Operational conditions	
Concentration of the substance	2-butoxyethanol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	117 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Provide a good standard of general or controlled ventilation (5 to 10 air changes per hour)	Effectiveness: 70 %
Use suitable chemically resistant gloves.	Effectiveness: 80 %
Use suitable eye protection.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	5,4857 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,043886
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	36,9294 mg/m ³
Risk Characterization Ratio (RCR)	0,376831
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 27.05.2025

Version: 8.0

Date / Previous version: 19.09.2023

Previous version: 7.0

Product: **BUTYLGLYCOL**

(ID no. 30034845/SDS_GEN_RO/EN)

Date of print 13.10.2025

Contributing exposure scenario	
Use descriptors covered	PROC10: Roller application or brushing Use domain: professional
Operational conditions	
Concentration of the substance	2-butoxyethanol Content: >= 0 % - <= 25 %
Physical state	liquid
Vapour pressure of the substance during use	117 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Outdoor
Risk Management Measures	
Use suitable chemically resistant gloves.	Effectiveness: 80 %
Use suitable eye protection.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	3,2914 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,026331
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	51,7012 mg/m ³
Risk Characterization Ratio (RCR)	0,527563
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC11: Non industrial spraying Use domain: professional
Operational conditions	
Concentration of the substance	2-butoxyethanol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	117 Pa
Process temperature	20 °C
Duration and Frequency of activity	240 min 5 days per week
Indoor/Outdoor	Indoor
Application rate	< 3 l/min

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 27.05.2025

Version: 8.0

Date / Previous version: 19.09.2023

Previous version: 7.0

Product: **BUTYLGLYCOL**

(ID no. 30034845/SDS_GEN_RO/EN)

Date of print 13.10.2025

Risk Management Measures	
Wear suitable respiratory protection.	Effectiveness: 95 %
Use suitable chemically resistant gloves.	Effectiveness: 80 %
Ensure that the task is not carried out overhead. Regular inspection and maintenance of equipment and machines. Provide specific employee training to prevent/minimize exposures.	
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	
Use suitable eye protection.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	21,4286 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,171429
Assessment method	EASY TRA v4.2, Advanced REACH Tool v1.5
	Worker - inhalation, long-term - systemic
Exposure estimate	55 mg/m ³
Risk Characterization Ratio (RCR)	0,561224
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra For scaling see: http://www.advancedreachtool.com	

Contributing exposure scenario	
Use descriptors covered	PROC11: Non industrial spraying Use domain: professional
Operational conditions	
Concentration of the substance	2-butoxyethanol Content: >= 0 % - <= 25 %
Physical state	liquid
Vapour pressure of the substance during use	117 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Application rate	< 3 l/min
Risk Management Measures	
Use suitable chemically resistant gloves.	Effectiveness: 80 %
Ensure that the task is not carried out overhead. Regular inspection and maintenance of equipment and	

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 27.05.2025

Version: 8.0

Date / Previous version: 19.09.2023

Previous version: 7.0

Product: **BUTYLGLYCOL**

(ID no. 30034845/SDS_GEN_RO/EN)

Date of print 13.10.2025

machines. Provide specific employee training to prevent/minimize exposures.	
Ensure that a spraying booth is used.	
Use suitable eye protection.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	12,8571 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,102857
Assessment method	EASY TRA v4.2, Advanced REACH Tool v1.5
	Worker - inhalation, long-term - systemic
Exposure estimate	62 mg/m ³
Risk Characterization Ratio (RCR)	0,632653
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra For scaling see: http://www.advancedreachtool.com	

Contributing exposure scenario	
Use descriptors covered	PROC13: Treatment of articles by dipping and pouring. Use domain: professional
Operational conditions	
Concentration of the substance	2-butoxyethanol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	117 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Use suitable chemically resistant gloves.	Effectiveness: 80 %
Use suitable eye protection.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	2,7429 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,021943
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	49,2393 mg/m ³
Risk Characterization Ratio (RCR)	0,502441
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 27.05.2025

Version: 8.0

Date / Previous version: 19.09.2023

Previous version: 7.0

Product: **BUTYLGLYCOL**

(ID no. 30034845/SDS_GEN_RO/EN)

Date of print 13.10.2025

Contributing exposure scenario	
Use descriptors covered	PROC15: Use a laboratory reagent. Use domain: professional
Operational conditions	
Concentration of the substance	2-butoxyethanol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	117 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Use suitable chemically resistant gloves.	Effectiveness: 80 %
Use suitable eye protection.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	0,0686 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,000549
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	24,6196 mg/m ³
Risk Characterization Ratio (RCR)	0,251221
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC19: Manual activities involving hand contact Use domain: professional
Operational conditions	
Concentration of the substance	2-butoxyethanol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	117 Pa
Process temperature	20 °C
Duration and Frequency of activity	240 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 27.05.2025

Version: 8.0

Date / Previous version: 19.09.2023

Previous version: 7.0

Product: **BUTYLGLYCOL**

(ID no. 30034845/SDS_GEN_RO/EN)

Date of print 13.10.2025

Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %
Use suitable chemically resistant gloves.	Effectiveness: 80 %
Use suitable eye protection.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	28,2857 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,226286
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	51,7012 mg/m ³
Risk Characterization Ratio (RCR)	0,527563
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

8. Short title of exposure scenario

Use in Coatings, (consumer use)

ERC8a, ERC8d; PC9a

Control of exposure and risk management measures

Contributing exposure scenario	
Use descriptors covered	ESVOC SpERC 8.3c.v1: ESVOC SpERC 8.3c.v1
Operational conditions	
Annual amount used in the EU	4.000.000 kg
Minimum emission days per year	365
Emission factor air	98,5 %
Emission factor water	1 %
Emission factor soil	0,5 %
Receive Surf. Water (Flow Rate).	18.000 m ³ /d
Dilution factor river	10
Dilution factor coast	100
Risk Management Measures	
Type of STP	Municipal STP

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 27.05.2025

Version: 8.0

Date / Previous version: 19.09.2023

Previous version: 7.0

Product: **BUTYLGLYCOL**

(ID no. 30034845/SDS_GEN_RO/EN)

Date of print 13.10.2025

Assumed sewage treatment plant flow (m3/d)	2.000 m3/d
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Environment
Risk Characterization Ratio (RCR)	0,018696
	Risk from environmental exposure is driven by soil.
Maximum amount of safe use	58,6 kg/d
Risk from environmental exposure is driven by soil.	

Contributing exposure scenario	
Use descriptors covered	ESVOC SpERC 8.3b.v1: ESVOC SpERC 8.3b.v1
Operational conditions	
Annual amount used in the EU	4.000.000 kg
Minimum emission days per year	365
Emission factor air	98 %
Emission factor water	1 %
Emission factor soil	1 %
Receive Surf. Water (Flow Rate).	18.000 m3/d
Dilution factor river	10
Dilution factor coast	100
Risk Management Measures	
Type of STP	Municipal STP
Assumed sewage treatment plant flow (m3/d)	2.000 m3/d
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Environment
Risk Characterization Ratio (RCR)	0,018688
	Risk from environmental exposure is driven by soil.
Maximum amount of safe use	29,3 kg/d
Risk from environmental exposure is driven by soil.	

Contributing exposure scenario	
Use descriptors covered	PC9a: Coatings and paints, thinners, paint removers
Operational conditions	
Concentration of the substance	2-butoxyethanol Content: >= 0 % - <= 3 %

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 27.05.2025

Version: 8.0

Date / Previous version: 19.09.2023

Previous version: 7.0

Product: **BUTYLGLYCOL**

(ID no. 30034845/SDS_GEN_RO/EN)

Date of print 13.10.2025

Vapour pressure of the substance during use	117 Pa
Process temperature	20 °C
Duration and Frequency of activity	Exposure duration: 132 min Relevant for inhalative exposure estimates
Duration and Frequency of activity	Application duration: 120 min Relevant for inhalative exposure estimates
Duration and Frequency of activity	1 uses per day
Room size	20 m ³
Ventilation rate per hour	0,6
Temperature (Application)	20 °C
body weight	65 kg
Uptake fraction dermal	100 %
Release area	150000 cm ²
	Release area increases over time
Release duration	120 min
	Relevant for inhalative exposure estimates
Contact rate	30 mg/min
Release duration	120 min
	Relevant for dermal exposure estimates
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ConsExpo v4.1, Dermal model: constant application rate, Uptake model: Uptake fraction
	Consumer - dermal, long-term - systemic
Exposure estimate	1,6615 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,022154
	The calculation is based on the internal chronic dose.
Assessment method	EASY TRA v4.2, ConsExpo v4.1, Inhalation model: exposure to vapour - evaporation
	Consumer - inhalation, long-term - systemic
Exposure estimate	15,6224 mg/m ³
Risk Characterization Ratio (RCR)	0,264786
	The exposure calculation is based on the mean concentration on the day of exposure.
Guidance to Downstream Users	
For scaling see: http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp	

9. Short title of exposure scenario

Use in Cleaning Agents, (use in professional settings)

ERC8a, ERC8d; PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC10, PROC11, PROC13

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 27.05.2025

Version: 8.0

Date / Previous version: 19.09.2023

Previous version: 7.0

Product: **BUTYLGLYCOL**

(ID no. 30034845/SDS_GEN_RO/EN)

Date of print 13.10.2025

Control of exposure and risk management measures

Contributing exposure scenario	
Use descriptors covered	ESVOC SpERC 8.4b.v1: ESVOC SpERC 8.4b.v1
Operational conditions	
Annual amount used in the EU	3.000.000 kg
Minimum emission days per year	365
Emission factor air	2 %
Emission factor water	1 ppm
Emission factor soil	0 %
Receive Surf. Water (Flow Rate).	18.000 m3/d
Dilution factor river	10
Dilution factor coast	100
Risk Management Measures	
Type of STP	Municipal STP
Assumed sewage treatment plant flow (m3/d)	2.000 m3/d
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Environment
Risk Characterization Ratio (RCR)	0,01868
	Risk from environmental exposure is driven by soil.
Maximum amount of safe use	44 kg/d
Risk from environmental exposure is driven by soil.	

Contributing exposure scenario	
Use descriptors covered	ESVOC SpERC 8.4b.v1: ESVOC SpERC 8.4b.v1
Operational conditions	
Annual amount used in the EU	3.000.000 kg
Minimum emission days per year	365
Emission factor air	2 %
Emission factor water	1 ppm
Emission factor soil	0 %
Receive Surf. Water (Flow Rate).	18.000 m3/d

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 27.05.2025

Version: 8.0

Date / Previous version: 19.09.2023

Previous version: 7.0

Product: **BUTYLGLYCOL**

(ID no. 30034845/SDS_GEN_RO/EN)

Date of print 13.10.2025

Dilution factor river	10
Dilution factor coast	100
Risk Management Measures	
Type of STP	Municipal STP
Assumed sewage treatment plant flow (m3/d)	2.000 m3/d
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Environment
Risk Characterization Ratio (RCR)	0,01868
	Risk from environmental exposure is driven by soil.
Maximum amount of safe use	44 kg/d
Risk from environmental exposure is driven by soil.	

Contributing exposure scenario	
Use descriptors covered	PROC2: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions Use domain: professional
Operational conditions	
Concentration of the substance	2-butoxyethanol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	117 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Use suitable chemically resistant gloves.	Effectiveness: 80 %
Use suitable eye protection., Personal measures have to be applied in case of potential exposure only.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	0,2743 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,002194
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	24,6196 mg/m ³

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 27.05.2025

Version: 8.0

Date / Previous version: 19.09.2023

Previous version: 7.0

Product: **BUTYLGLYCOL**

(ID no. 30034845/SDS_GEN_RO/EN)

Date of print 13.10.2025

Risk Characterization Ratio (RCR)	0,251221
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition Use domain: professional
Operational conditions	
Concentration of the substance	2-butoxyethanol Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	117 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Use suitable chemically resistant gloves.	Effectiveness: 80 %
Use suitable eye protection., Personal measures have to be applied in case of potential exposure only.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	0,1371 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,001097
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	14,7718 mg/m ³
Risk Characterization Ratio (RCR)	0,150732
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC4: Chemical production where opportunity for exposure arises Use domain: professional
Operational conditions	
Concentration of the substance	2-butoxyethanol Content: $\geq 0\%$ - $\leq 100\%$

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 27.05.2025

Version: 8.0

Date / Previous version: 19.09.2023

Previous version: 7.0

Product: **BUTYLGLYCOL**

(ID no. 30034845/SDS_GEN_RO/EN)

Date of print 13.10.2025

Physical state	liquid
Vapour pressure of the substance during use	117 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Use suitable chemically resistant gloves.	Effectiveness: 80 %
Use suitable eye protection., Personal measures have to be applied in case of potential exposure only.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	1,3714 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,010971
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	49,2393 mg/m ³
Risk Characterization Ratio (RCR)	0,502441
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC8a: Transfer of substance or mixture (charging and discharging) at non-dedicated facilities Use domain: professional
Operational conditions	
Concentration of the substance	2-butoxyethanol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	117 Pa
Process temperature	20 °C
Duration and Frequency of activity	240 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %
Use suitable chemically resistant	Effectiveness: 80 %

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 27.05.2025

Version: 8.0

Date / Previous version: 19.09.2023

Previous version: 7.0

Product: **BUTYLGLYCOL**

(ID no. 30034845/SDS_GEN_RO/EN)

Date of print 13.10.2025

gloves.	
Use suitable eye protection.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	2,7429 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,021943
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	51,7012 mg/m ³
Risk Characterization Ratio (RCR)	0,527563
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC8b: Transfer of substance or mixture (charging and discharging) at dedicated facilities Use domain: professional
Operational conditions	
Concentration of the substance	2-butoxyethanol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	117 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Use suitable chemically resistant gloves.	Effectiveness: 80 %
Use suitable eye protection.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	2,7429 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,021943
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	49,2393 mg/m ³
Risk Characterization Ratio (RCR)	0,502441
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC10: Roller application or brushing

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 27.05.2025

Version: 8.0

Date / Previous version: 19.09.2023

Previous version: 7.0

Product: **BUTYLGLYCOL**

(ID no. 30034845/SDS_GEN_RO/EN)

Date of print 13.10.2025

	Use domain: professional
Operational conditions	
Concentration of the substance	2-butoxyethanol Content: $\geq 0\%$ - $\leq 25\%$
Physical state	liquid
Vapour pressure of the substance during use	117 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %
Use suitable chemically resistant gloves.	Effectiveness: 80 %
Use suitable eye protection.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	3,2914 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,026331
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	51,7012 mg/m ³
Risk Characterization Ratio (RCR)	0,527563
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC11: Non industrial spraying Use domain: professional
Operational conditions	
Concentration of the substance	2-butoxyethanol Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	117 Pa
Process temperature	20 °C
Duration and Frequency of activity	240 min 5 days per week
Indoor/Outdoor	Indoor

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 27.05.2025

Version: 8.0

Date / Previous version: 19.09.2023

Previous version: 7.0

Product: **BUTYLGLYCOL**

(ID no. 30034845/SDS_GEN_RO/EN)

Date of print 13.10.2025

Application rate	< 3 l/min
Risk Management Measures	
Wear suitable respiratory protection.	Effectiveness: 95 %
Use suitable chemically resistant gloves.	Effectiveness: 80 %
Ensure that the task is not carried out overhead. Regular inspection and maintenance of equipment and machines. Provide specific employee training to prevent/minimize exposures.	
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	
Use suitable eye protection.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	21,4286 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,171429
Assessment method	EASY TRA v4.2, Advanced REACH Tool v1.5
	Worker - inhalation, long-term - systemic
Exposure estimate	55 mg/m ³
Risk Characterization Ratio (RCR)	0,561224
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra For scaling see: http://www.advancedreachtool.com	

Contributing exposure scenario	
Use descriptors covered	PROC11: Non industrial spraying Use domain: professional
Operational conditions	
Concentration of the substance	2-butoxyethanol Content: >= 0 % - <= 25 %
Physical state	liquid
Vapour pressure of the substance during use	117 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Application rate	< 3 l/min
Risk Management Measures	
Use suitable chemically resistant gloves.	Effectiveness: 80 %
Ensure that the task is not carried out overhead. Regular inspection and	

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 27.05.2025

Version: 8.0

Date / Previous version: 19.09.2023

Previous version: 7.0

Product: **BUTYLGLYCOL**

(ID no. 30034845/SDS_GEN_RO/EN)

Date of print 13.10.2025

maintenance of equipment and machines. Provide specific employee training to prevent/minimize exposures.	
Ensure that a spraying booth is used.	
Use suitable eye protection.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	12,8571 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,102857
Assessment method	EASY TRA v4.2, Advanced REACH Tool v1.5
	Worker - inhalation, long-term - systemic
Exposure estimate	62 mg/m ³
Risk Characterization Ratio (RCR)	0,632653
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra For scaling see: http://www.advancedreachtool.com	

Contributing exposure scenario	
Use descriptors covered	PROC13: Treatment of articles by dipping and pouring. Use domain: professional
Operational conditions	
Concentration of the substance	2-butoxyethanol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	117 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Use suitable chemically resistant gloves.	Effectiveness: 80 %
Use suitable eye protection.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	2,7429 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,021943
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	49,2393 mg/m ³
Risk Characterization Ratio (RCR)	0,502441
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 27.05.2025

Version: 8.0

Date / Previous version: 19.09.2023

Previous version: 7.0

Product: **BUTYLGLYCOL**

(ID no. 30034845/SDS_GEN_RO/EN)

Date of print 13.10.2025

10. Short title of exposure scenario

Use in Cleaning Agents, (consumer use)

ERC8a, ERC8d; PC35

Control of exposure and risk management measures

Contributing exposure scenario	
Use descriptors covered	ESVOC SpERC 8.4c.v1: ESVOC SpERC 8.4c.v1
Operational conditions	
Annual amount used in the EU	2.000.000 kg
Minimum emission days per year	365
Emission factor air	95 %
Emission factor water	2,5 %
Emission factor soil	2,5 %
Receive Surf. Water (Flow Rate).	18.000 m3/d
Dilution factor river	10
Dilution factor coast	100
Risk Management Measures	
Type of STP	Municipal STP
Assumed sewage treatment plant flow (m3/d)	2.000 m3/d
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Environment
Risk Characterization Ratio (RCR)	0,0187
	Risk from environmental exposure is driven by soil.
Maximum amount of safe use	29,3 kg/d
Risk from environmental exposure is driven by soil.	

Contributing exposure scenario	
Use descriptors covered	ESVOC SpERC 8.4c.v1: ESVOC SpERC 8.4c.v1
Operational conditions	
Annual amount used in the EU	2.000.000 kg
Minimum emission days per year	365

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 27.05.2025

Version: 8.0

Date / Previous version: 19.09.2023

Previous version: 7.0

Product: **BUTYLGLYCOL**

(ID no. 30034845/SDS_GEN_RO/EN)

Date of print 13.10.2025

Emission factor air	95 %
Emission factor water	2,5 %
Emission factor soil	2,5 %
Receive Surf. Water (Flow Rate).	18.000 m3/d
Dilution factor river	10
Dilution factor coast	100
Risk Management Measures	
Type of STP	Municipal STP
Assumed sewage treatment plant flow (m3/d)	2.000 m3/d
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Environment
Risk Characterization Ratio (RCR)	0,0187
	Risk from environmental exposure is driven by soil.
Maximum amount of safe use	29,3 kg/d
Risk from environmental exposure is driven by soil.	

Contributing exposure scenario	
Use descriptors covered	PC35: Washing and Cleaning Products (including solvent based products).
Operational conditions	
Concentration of the substance	2-butoxyethanol Content: >= 0 % - <= 7 %
Vapour pressure of the substance during use	117 Pa
Process temperature	20 °C
Duration and Frequency of activity	Exposure duration: 240 min Relevant for inhalative exposure estimates
Duration and Frequency of activity	Application duration: 20 min Relevant for inhalative exposure estimates
Duration and Frequency of activity	1 uses per day
Room size	58 m3
Ventilation rate per hour	0,5
Temperature (Application)	20 °C
body weight	65 kg
Uptake fraction dermal	100 %

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 27.05.2025

Version: 8.0

Date / Previous version: 19.09.2023

Previous version: 7.0

Product: **BUTYLGLYCOL**

(ID no. 30034845/SDS_GEN_RO/EN)

Date of print 13.10.2025

	Amount per use 35 g Relevant for dermal exposure estimates
Release area	100000 cm ²
	Release area increases over time
Release duration	20 min
	Relevant for inhalative exposure estimates
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ConsExpo v4.1, Dermal model: instant application, Uptake model: Uptake fraction
	Consumer - dermal, long-term - systemic
Exposure estimate	37,6923 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,502564
	The calculation is based on the internal chronic dose.
Assessment method	EASY TRA v4.2, ConsExpo v4.1, Inhalation model: exposure to vapour - evaporation
	Consumer - inhalation, long-term - systemic
Exposure estimate	10,6576 mg/m ³
Risk Characterization Ratio (RCR)	0,180637
	The exposure calculation is based on the mean concentration on the day of exposure.
Guidance to Downstream Users	
For scaling see: http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp	

Contributing exposure scenario	
Use descriptors covered	PC35: Washing and Cleaning Products (including solvent based products).
Operational conditions	
Concentration of the substance	2-butoxyethanol Content: >= 0 % - <= 7 %
Vapour pressure of the substance during use	117 Pa
Process temperature	20 °C
Duration and Frequency of activity	Exposure duration: 60 min Relevant for inhalative exposure estimates
Duration and Frequency of activity	1 uses per day
Room size	15 m ³
Ventilation rate per hour	2,5
body weight	65 kg
Uptake fraction dermal	100 %
Spray duration	24,6 sec
Contact rate	46 mg/min
Release duration	0,41 min

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 27.05.2025

Version: 8.0

Date / Previous version: 19.09.2023

Previous version: 7.0

Product: **BUTYLGLYCOL**

(ID no. 30034845/SDS_GEN_RO/EN)

Date of print 13.10.2025

	Relevant for dermal exposure estimates
Risk Management Measures	
Consumer Measures	Ensure spraying away from persons.
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ConsExpo v4.1, Dermal model: constant application rate, Uptake model: Uptake fraction
	Consumer - dermal, long-term - systemic
Exposure estimate	0,0203 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,000271
	The calculation is based on the internal chronic dose.
Assessment method	EASY TRA v4.2, ConsExpo v4.1, Inhalation model: Exposure to spray/dust
	Consumer - inhalation, long-term - systemic
Exposure estimate	0,0072 mg/m ³
Risk Characterization Ratio (RCR)	0,000122
	The exposure calculation is based on the mean concentration on the day of exposure.
Guidance to Downstream Users	
For scaling see: http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp	

11. Short title of exposure scenario

Road and construction applications

ERC8d; PROC8a, PROC8b, PROC10, PROC11, PROC13

Control of exposure and risk management measures

Contributing exposure scenario	
Use descriptors covered	ESVOC SpERC 8.15.v1: ESVOC SpERC 8.15.v1
Operational conditions	
Annual amount used in the EU	250.000 kg
Minimum emission days per year	365
Emission factor air	95 %
Emission factor water	1 %
Emission factor soil	4 %
Receive Surf. Water (Flow Rate).	18.000 m3/d
Dilution factor river	10
Dilution factor coast	100

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 27.05.2025

Version: 8.0

Date / Previous version: 19.09.2023

Previous version: 7.0

Product: **BUTYLGLYCOL**

(ID no. 30034845/SDS_GEN_RO/EN)

Date of print 13.10.2025

Risk Management Measures	
Type of STP	no STP
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Environment
Risk Characterization Ratio (RCR)	0,01868
	Risk from environmental exposure is driven by soil.
Maximum amount of safe use	1,8 kg/d
Risk from environmental exposure is driven by soil.	

Contributing exposure scenario	
Use descriptors covered	PROC8a: Transfer of substance or mixture (charging and discharging) at non-dedicated facilities Use domain: professional
Operational conditions	
Concentration of the substance	2-butoxyethanol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	117 Pa
Process temperature	20 °C
Duration and Frequency of activity	240 min 5 days per week
Indoor/Outdoor	Outdoor
Risk Management Measures	
Use suitable chemically resistant gloves.	Effectiveness: 80 %
Use suitable eye protection.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	2,7429 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,021943
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	51,7012 mg/m ³
Risk Characterization Ratio (RCR)	0,527563
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC8b: Transfer of substance or mixture (charging and discharging) at dedicated facilities Use domain: professional

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 27.05.2025

Version: 8.0

Date / Previous version: 19.09.2023

Previous version: 7.0

Product: **BUTYLGLYCOL**

(ID no. 30034845/SDS_GEN_RO/EN)

Date of print 13.10.2025

Operational conditions	
Concentration of the substance	2-butoxyethanol Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	117 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Outdoor
Risk Management Measures	
Use suitable chemically resistant gloves.	Effectiveness: 80 %
Use suitable eye protection.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	2,7429 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,021943
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	34,4675 mg/m ³
Risk Characterization Ratio (RCR)	0,351709
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC10: Roller application or brushing Use domain: professional
Operational conditions	
Concentration of the substance	2-butoxyethanol Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	117 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Outdoor
Risk Management Measures	
Use suitable chemically resistant gloves.	Effectiveness: 80 %
Use suitable eye protection.	
Exposure estimate and reference to its source	

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 27.05.2025

Version: 8.0

Date / Previous version: 19.09.2023

Previous version: 7.0

Product: **BUTYLGLYCOL**

(ID no. 30034845/SDS_GEN_RO/EN)

Date of print 13.10.2025

Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	5,4857 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,043886
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	86,1687 mg/m ³
Risk Characterization Ratio (RCR)	0,879272
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC11: Non industrial spraying Use domain: professional
Operational conditions	
Concentration of the substance	2-butoxyethanol Content: >= 0 % - <= 25 %
Physical state	liquid
Vapour pressure of the substance during use	117 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Outdoor
Application rate	< 3 l/min
Risk Management Measures	
Use suitable chemically resistant gloves.	Effectiveness: 80 %
Ensure that the task is carried out only downward.	
Wear suitable working clothes.	
Use suitable eye protection.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	12,8571 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,102857
Assessment method	EASY TRA v4.2, Advanced REACH Tool v1.5
	Worker - inhalation, long-term - systemic
Exposure estimate	28 mg/m ³
Risk Characterization Ratio (RCR)	0,285714
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra For scaling see: http://www.advancedreachtool.com	

Contributing exposure scenario	
Use descriptors covered	PROC13: Treatment of articles by dipping and pouring.

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 27.05.2025

Version: 8.0

Date / Previous version: 19.09.2023

Previous version: 7.0

Product: **BUTYLGLYCOL**

(ID no. 30034845/SDS_GEN_RO/EN)

Date of print 13.10.2025

	Use domain: professional
Operational conditions	
Concentration of the substance	2-butoxyethanol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	117 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Outdoor
Risk Management Measures	
Use suitable chemically resistant gloves.	Effectiveness: 80 %
Use suitable eye protection.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	2,7429 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,021943
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	34,4675 mg/m ³
Risk Characterization Ratio (RCR)	0,351709
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

12. Short title of exposure scenario

Use in Oilfield drilling and production operations

ERC8d; PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b

Control of exposure and risk management measures

Contributing exposure scenario	
Use descriptors covered	ESVOC SpERC 8.15.v1: ESVOC SpERC 8.15.v1
Operational conditions	
Annual amount used in the EU	250.000 kg
Minimum emission days per year	365
Emission factor air	95 %

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 27.05.2025

Version: 8.0

Date / Previous version: 19.09.2023

Previous version: 7.0

Product: **BUTYLGLYCOL**

(ID no. 30034845/SDS_GEN_RO/EN)

Date of print 13.10.2025

Emission factor water	1 %
Emission factor soil	4 %
Receive Surf. Water (Flow Rate).	18.000 m3/d
Dilution factor river	10
Dilution factor coast	100
Risk Management Measures	
Type of STP	no STP
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Environment
Risk Characterization Ratio (RCR)	0,01868
	Risk from environmental exposure is driven by soil.
Maximum amount of safe use	18,3 kg/d
Risk from environmental exposure is driven by soil.	

Contributing exposure scenario	
Use descriptors covered	PROC1: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions. Use domain: professional
Operational conditions	
Concentration of the substance	2-butoxyethanol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	117 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	0,0343 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,000274
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	0,0492 mg/m ³
Risk Characterization Ratio (RCR)	0,000502
Guidance to Downstream Users	

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 27.05.2025

Version: 8.0

Date / Previous version: 19.09.2023

Previous version: 7.0

Product: **BUTYLGLYCOL**

(ID no. 30034845/SDS_GEN_RO/EN)

Date of print 13.10.2025

For scaling see: <http://www.ecetoc.org/tra>

Contributing exposure scenario	
Use descriptors covered	PROC2: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions Use domain: professional
Operational conditions	
Concentration of the substance	2-butoxyethanol Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	117 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Use suitable chemically resistant gloves.	Effectiveness: 80 %
Personal measures have to be applied in case of potential exposure only.	
Use suitable eye protection.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	0,2743 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,002194
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	24,6196 mg/m ³
Risk Characterization Ratio (RCR)	0,251221
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition Use domain: professional
Operational conditions	
Concentration of the substance	2-butoxyethanol Content: $\geq 0\%$ - $\leq 100\%$

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 27.05.2025

Version: 8.0

Date / Previous version: 19.09.2023

Previous version: 7.0

Product: **BUTYLGLYCOL**

(ID no. 30034845/SDS_GEN_RO/EN)

Date of print 13.10.2025

Physical state	liquid
Vapour pressure of the substance during use	117 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Use suitable chemically resistant gloves.	Effectiveness: 80 %
Personal measures have to be applied in case of potential exposure only.	
Use suitable eye protection.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	0,1371 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,001097
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	14,7718 mg/m ³
Risk Characterization Ratio (RCR)	0,150732
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC4: Chemical production where opportunity for exposure arises Use domain: professional
Operational conditions	
Concentration of the substance	2-butoxyethanol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	117 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Use suitable chemically resistant gloves.	Effectiveness: 80 %
Personal measures have to be	

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 27.05.2025

Version: 8.0

Date / Previous version: 19.09.2023

Previous version: 7.0

Product: **BUTYLGLYCOL**

(ID no. 30034845/SDS_GEN_RO/EN)

Date of print 13.10.2025

applied in case of potential exposure only.	
Use suitable eye protection.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	1,3714 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,010971
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	49,2393 mg/m ³
Risk Characterization Ratio (RCR)	0,502441
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC8a: Transfer of substance or mixture (charging and discharging) at non-dedicated facilities Use domain: professional
Operational conditions	
Concentration of the substance	2-butoxyethanol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	117 Pa
Process temperature	20 °C
Duration and Frequency of activity	240 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Use suitable chemically resistant gloves.	Effectiveness: 80 %
Use suitable eye protection.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	2,7429 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,021943
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	73,8589 mg/m ³
Risk Characterization Ratio (RCR)	0,753662
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 27.05.2025

Version: 8.0

Date / Previous version: 19.09.2023

Previous version: 7.0

Product: **BUTYLGLYCOL**

(ID no. 30034845/SDS_GEN_RO/EN)

Date of print 13.10.2025

Use descriptors covered	PROC8b: Transfer of substance or mixture (charging and discharging) at dedicated facilities Use domain: professional
Operational conditions	
Concentration of the substance	2-butoxyethanol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	117 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Use suitable chemically resistant gloves.	Effectiveness: 80 %
Use suitable eye protection.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	2,7429 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,021943
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	49,2393 mg/m ³
Risk Characterization Ratio (RCR)	0,502441
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

13. Short title of exposure scenario

Fire foam

ERC8d; PROC1, PROC3, PROC8a, PROC8b, PROC11

Control of exposure and risk management measures

Contributing exposure scenario	
Use descriptors covered	ERC8d: Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor)
Operational conditions	
Annual amount used in the EU	250.000 kg
Minimum emission days per year	20

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 27.05.2025

Version: 8.0

Date / Previous version: 19.09.2023

Previous version: 7.0

Product: **BUTYLGLYCOL**

(ID no. 30034845/SDS_GEN_RO/EN)

Date of print 13.10.2025

Emission factor air	1 ppm
Emission factor water	0,001 %
Emission factor soil	0 %
Receive Surf. Water (Flow Rate).	18.000 m3/d
Dilution factor river	10
Dilution factor coast	100
Risk Management Measures	
Air treatment measures considered suitable are, e.g.	Waste gas treatment by thermal oxidation
Soil treatment measures considered suitable are, e.g.	Isolated drainage to prevent discharge to soil, Sealing of all relevant soil surfaces, Sewage Sludge incineration
Type of STP	no STP
Waste-Related Measures	
Prescribed disposal method	waste combuster
Effectiveness	0 %
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Environment
Risk Characterization Ratio (RCR)	0,01868
	Risk from environmental exposure is driven by soil.
Maximum amount of safe use	66.916,3 kg/d
Risk from environmental exposure is driven by soil.	

Contributing exposure scenario	
Use descriptors covered	PROC1: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions. Use domain: professional
Operational conditions	
Concentration of the substance	2-butoxyethanol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	117 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 27.05.2025

Version: 8.0

Date / Previous version: 19.09.2023

Previous version: 7.0

Product: **BUTYLGLYCOL**

(ID no. 30034845/SDS_GEN_RO/EN)

Date of print 13.10.2025

Indoor/Outdoor	Indoor
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	0,0343 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,000274
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	0,0492 mg/m ³
Risk Characterization Ratio (RCR)	0,000502
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition Use domain: professional
Operational conditions	
Concentration of the substance	2-butoxyethanol Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	117 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Use suitable chemically resistant gloves.	Effectiveness: 80 %
Personal measures have to be applied in case of potential exposure only.	
Use suitable eye protection.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	0,1371 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,001097
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	14,7718 mg/m ³
Risk Characterization Ratio (RCR)	0,150732

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 27.05.2025

Version: 8.0

Date / Previous version: 19.09.2023

Previous version: 7.0

Product: **BUTYLGLYCOL**

(ID no. 30034845/SDS_GEN_RO/EN)

Date of print 13.10.2025

Guidance to Downstream Users

For scaling see: <http://www.ecetoc.org/tra>

Contributing exposure scenario

Use descriptors covered	PROC8a: Transfer of substance or mixture (charging and discharging) at non-dedicated facilities Use domain: professional
--------------------------------	---

Operational conditions

Concentration of the substance	2-butoxyethanol Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	117 Pa
Process temperature	20 °C
Duration and Frequency of activity	240 min 5 days per week
Indoor/Outdoor	Indoor

Risk Management Measures

Use suitable chemically resistant gloves.	Effectiveness: 80 %
Use suitable eye protection.	

Exposure estimate and reference to its source

Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	2,7429 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,021943
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	73,8589 mg/m ³
Risk Characterization Ratio (RCR)	0,753662

Guidance to Downstream Users

For scaling see: <http://www.ecetoc.org/tra>

Contributing exposure scenario

Use descriptors covered	PROC8b: Transfer of substance or mixture (charging and discharging) at dedicated facilities Use domain: professional
--------------------------------	---

Operational conditions

Concentration of the substance	2-butoxyethanol Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	117 Pa
Process temperature	20 °C

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 27.05.2025

Version: 8.0

Date / Previous version: 19.09.2023

Previous version: 7.0

Product: **BUTYLGLYCOL**

(ID no. 30034845/SDS_GEN_RO/EN)

Date of print 13.10.2025

Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Use suitable chemically resistant gloves.	Effectiveness: 80 %
Use suitable eye protection.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	2,7429 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,021943
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	49,2393 mg/m ³
Risk Characterization Ratio (RCR)	0,502441
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC11: Non industrial spraying Use domain: professional
Operational conditions	
Concentration of the substance	2-butoxyethanol Content: >= 0 % - < 1 %
Physical state	liquid
Vapour pressure of the substance during use	117 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Any sized room
Risk Management Measures	
Wear suitable respiratory protection.	Effectiveness: 90 %
Use suitable chemically resistant gloves.	Effectiveness: 80 %
Wear a suitable respiratory protection with adequate effectiveness (90%).	
Use suitable eye protection.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.2, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	2,1429 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,017143

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 27.05.2025

Version: 8.0

Date / Previous version: 19.09.2023

Previous version: 7.0

Product: **BUTYLGLYCOL**

(ID no. 30034845/SDS_GEN_RO/EN)

Date of print 13.10.2025

Assessment method	EASY TRA v4.2, Advanced REACH Tool v1.5
	Worker - inhalation, long-term - systemic
Exposure estimate	37 mg/m ³
Risk Characterization Ratio (RCR)	0,377551
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra For scaling see: http://www.advancedreachttool.com	
