

Safety data sheet

Page: 1/16

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 16.10.2025 Version: 11.0

Date / Previous version: 16.12.2024 Previous version: 10.0

Product: ULTRADUR® B 4406 G4 BLACK 07110 POLYBUTYLENE TEREPHTHALATE

(ID no. 30035777/SDS_GEN_EU/EN)

Date of print 17.10.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

ULTRADUR® B 4406 G4 BLACK 07110 POLYBUTYLENE TEREPHTHALATE

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses: Polymer

Recommended use: Polymer, for industrial processing only

1.3. Details of the supplier of the safety data sheet

Company: BASF SE 67056 Ludwigshafen GERMANY

Telephone: +49 621 60-0

E-mail address: global.info@basf.com

1.4. Emergency telephone number

International emergency number: Telephone: +49 180 2273-112

Date / Revised: 16.10.2025 Version: 11.0

Date / Previous version: 16.12.2024 Previous version: 10.0

Date / Pievious veision. 10.12.2024

Previous Veision

Previous Veision

Previous Veision

Previous Veision

Product: ULTRADUR® B 4406 G4 BLACK 07110 POLYBUTYLENE TEREPHTHALATE

(ID no. 30035777/SDS_GEN_EU/EN)

Date of print 17.10.2025

SECTION 2: Hazards Identification

2.1. Classification of the substance or mixture

For the classification of the mixture the following methods have been applied: extrapolation on the concentration levels of the hazardous substances, on basis of test results and after evaluation of experts. The methodologies used are mentioned at the respective test results.

According to Regulation (EC) No 1272/2008 [CLP]

No need for classification according to GHS criteria for this product.

2.2. Label elements

According to Regulation (EC) No 1272/2008 [CLP]

The product does not require a hazard warning label in accordance with GHS criteria.

2.3. Other hazards

According to Regulation (EC) No 1272/2008 [CLP]

No specific dangers known, if the regulations/notes for storage and handling are considered. Product does not contain a substance above legal limits included in the list established in accordance with Article 59(1) of Regulation (EC) No 1907/2006 for having endocrine disrupting properties or is identified to have endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

SECTION 3: Composition/Information on Ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Chemical nature

Compound based on:polybutylene terephthalate (PBT) additives, fillers, flame retardant, Diantimony trioxide

Regulatory relevant ingredients

Diantimony trioxide

Date / Revised: 16.10.2025 Version: 11.0

Date / Previous version: 16.12.2024 Previous version: 10.0

Product: ULTRADUR® B 4406 G4 BLACK 07110 POLYBUTYLENE TEREPHTHALATE

(ID no. 30035777/SDS_GEN_EU/EN)

Date of print 17.10.2025

Content (W/W): >= 1 % - <= 7 % Carc. 2

CAS Number: 1309-64-4 Carc. 2 (by inhalation) EC-Number: 215-175-0 STOT RE (Lung) 2 REACH registration number: 01- H351, H373

2119475613-35

Substance with EU occupational

exposure limit

For the classifications not written out in full in this section, including the hazard classes and the hazard statements, the full text is listed in section 16.

SECTION 4: First-Aid Measures

4.1. Description of first aid measures

Avoid contact with the skin, eyes and clothing.

If inhaled:

If difficulties occur after dust has been inhaled, remove to fresh air and seek medical attention.

On skin contact:

Burns caused by molten material require hospital treatment.

On contact with eyes:

In case of contact with the eyes, rinse immediately for at least 15 minutes with plenty of water. If irritation develops, seek medical attention.

On ingestion:

Rinse mouth and then drink 200-300 ml of water. If difficulties occur: Seek medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms: (Further) symptoms and / or effects are not known so far

Hazards: No hazard is expected under intended use and appropriate handling.

4.3. Indication of any immediate medical attention and special treatment needed

Treatment: Treat according to symptoms (decontamination, vital functions), no known specific antidote.

Date / Revised: 16.10.2025 Version: 11.0

Date / Previous version: 16.12.2024 Previous version: 10.0

Product: ULTRADUR® B 4406 G4 BLACK 07110 POLYBUTYLENE TEREPHTHALATE

(ID no. 30035777/SDS_GEN_EU/EN)

Date of print 17.10.2025

SECTION 5: Fire-Fighting Measures

5.1. Extinguishing media

Suitable extinguishing media: water spray, foam, dry powder

Unsuitable extinguishing media for safety reasons: water jet

5.2. Special hazards arising from the substance or mixture

Temperature limit: > 290 °C

Endangering substances: Carbon monoxide, tetrahydrofuran, hydrogen halides, brominated

dibenzodioxins

Advice: Under special fire conditions traces of other toxic substances are possible. Formation of further decomposition and oxidation products depends upon the fire conditions.

5.3. Advice for fire-fighters

Special protective equipment:

Wear a self-contained breathing apparatus.

Further information:

Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

SECTION 6: Accidental Release Measures

High risk of slipping due to leakage/spillage of product.

6.1. Personal precautions, protective equipment and emergency procedures

No special precautions necessary.

6.2. Environmental precautions

Prevent releases of this product into the environment. Comprehensive instructions explaining how to prevent releases of plastics pellets, flakes, and powders to the environment during both use and disposal are provided by the industry program 'Operation Clean Sweep' (OCS).

6.3. Methods and material for containment and cleaning up

For small amounts: Pick up with suitable appliance and dispose of. For large amounts: Pick up with suitable appliance and dispose of.

For residues: Sweep/shovel up.

Dispose of absorbed material in accordance with regulations.

Date / Revised: 16.10.2025 Version: 11.0

Date / Previous version: 16.12.2024 Previous version: 10.0

Product: ULTRADUR® B 4406 G4 BLACK 07110 POLYBUTYLENE TEREPHTHALATE

(ID no. 30035777/SDS_GEN_EU/EN)

Date of print 17.10.2025

6.4. Reference to other sections

Information regarding exposure controls/personal protection and disposal considerations can be found in section 8 and 13.

SECTION 7: Handling and Storage

7.1. Precautions for safe handling

Avoid dust formation.

Exhaust ventilation at processing machines is required during thermal processing and/or machining. However, if dust formulation occurs at processing / finishing processing steps like regranulation, mechanical machining (for example drilling, grinding etc.) provide suitable exhaust ventilation.

Cleaning of product-contaminated machine parts with open flames should be avoided. If task are carried out with open flames, ventilation measures are mandatory.

Protection against fire and explosion:

Take precautionary measures against static discharges.

7.2. Conditions for safe storage, including any incompatibilities

Segregate from foods and animal feeds.

Suitable materials for containers: Low density polyethylene (LDPE), High density polyethylene (HDPE), Aluminium, Carbon steel (Iron)

Further information on storage conditions: Keep container tightly closed and dry; store in a cool place. Avoid dust formation, product dust can form an explosive mixture with air.

Storage stability:

Protect against moisture.

7.3. Specific end use(s)

For the relevant identified use(s) listed in Section 1 the advice mentioned in this section 7 is to be observed.

SECTION 8: Exposure Controls/Personal Protection

8.1. Control parameters

Components with occupational exposure limits

Date / Revised: 16.10.2025 Version: 11.0

Date / Previous version: 16.12.2024 Previous version: 10.0

Product: ULTRADUR® B 4406 G4 BLACK 07110 POLYBUTYLENE TEREPHTHALATE

(ID no. 30035777/SDS_GEN_EU/EN)

Date of print 17.10.2025

1309-64-4: Diantimony trioxide

1333-86-4: Carbon black

65997-17-3: Glass, oxide, chemicals

26062-94-2: 1,4-Benzenedicarboxylic acid, polymer with 1,4-butanediol

8.2. Exposure controls

Personal protective equipment

Respiratory protection:

Breathing protection if breathable aerosols/dust are formed. Wear respiratory protection if ventilation is inadequate. (Particle filter EN 143 P3)

Hand protection:

Use additional heat protection gloves when handling hot molten masses (EN 407), e.g. of textile or leather.

Eye protection:

Safety glasses with side-shields (frame goggles) (e.g. EN 166)

Body protection:

Body protection must be chosen depending on activity and possible exposure, e.g. apron, protecting boots, chemical-protection suit (according to EN 14605 in case of splashes or EN ISO 13982 in case of dust).

General safety and hygiene measures

The product contains dangerous ingredients (see paragraph 2, SDS), which are embedded in plastic and are only set free when milled. Avoid inhalation of dusts/mists/vapours. When using, do not eat, drink or smoke. Keep separated from food stuffs and feed stocks. Hands and/or face should be washed before breaks and at the end of the shift. After use of gloves apply skin-cleaning agents and skin cosmetics.

Environmental exposure controls

For information regarding environmental exposure controls, see Section 6.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

State of matter: solid Form: granules

Colour: various, depending on the colourant

Odour: odourless

Odour threshold:

not applicable

melting range: 220 - 230 °C (DIN 53736)

(1,013 hPa)

Date / Revised: 16.10.2025 Version: 11.0

Date / Previous version: 16.12.2024 Previous version: 10.0

Product: ULTRADUR® B 4406 G4 BLACK 07110 POLYBUTYLENE TEREPHTHALATE

(ID no. 30035777/SDS_GEN_EU/EN)

(OECD Guideline 105)

Date of print 17.10.2025

Boiling range:

The substance / product decomposes therefore not

determined.

Sublimation point:

No applicable information available.

Flammability: not self-igniting (derived from flash point)

Flammability of Aerosol Products:

not applicable, the product does not form flammable aerosoles

Lower explosion limit:

For solids not relevant for classification and labelling.

Upper explosion limit:

For solids not relevant for classification and labelling.

Flash point:

not applicable

Auto-ignition temperature: > 350 °C (ASTM D1929)

Thermal decomposition: > 290 °C (TGA)

To avoid thermal decomposition, do not overheat.

pH value:

not applicable

Viscosity, kinematic:

not applicable, the product is a solid

Viscosity, dynamic:

not applicable, the product is a solid

Solubility in water: insoluble

(20 °C, 1,013 hPa)

Partitioning coefficient n-octanol/water (log Kow):

not applicable

Vapour pressure:

not applicable

Relative density:

Study does not need to be

conducted.

Density: 1.60 - 1.70 g/cm3 (EN ISO 1183-1)

(20 °C, 1,013 hPa)

Relative vapour density (air):

not applicable

Particle characteristics

Particle size distribution: spheroidal -

Specific Surface Area: 0.0 m²/g (MSSA, ISO 9227)

9.2. Other information

Information with regard to physical hazard classes

Explosives

Explosion hazard: not explosive

Date / Revised: 16.10.2025 Version: 11.0

Date / Previous version: 16.12.2024 Previous version: 10.0

Product: ULTRADUR® B 4406 G4 BLACK 07110 POLYBUTYLENE TEREPHTHALATE

(ID no. 30035777/SDS_GEN_EU/EN)

Date of print 17.10.2025

Oxidizing properties

Fire promoting properties: not fire-propagating

Pyrophoric properties

Self-ignition temperature: Test type: Spontaneous self-ignition at room-temperature.

not self-igniting

Self-heating substances and mixtures

Self heating ability: It is not a substance capable of (VDI 2263, sheet 1, 1.4.1 (May

spontaneous heating according to 1990))

UN transport regulations class 4.2.

Corrosion to metals

No corrosive effect on metal.

Other safety characteristics

Bulk density: 600 - 900 kg/m3 (OECD Guideline 109)

(20 °C, 1,013 hPa)

Evaporation rate:

The product is a non-volatile solid.

SECTION 10: Stability and Reactivity

10.1. Reactivity

No hazardous reactions if stored and handled as prescribed/indicated.

Corrosion to metals: No corrosive effect on metal.

10.2. Chemical stability

The product is stable if stored and handled as prescribed/indicated.

The product is chemically stable.

10.3. Possibility of hazardous reactions

No hazardous reactions known. The product is chemically stable.

10.4. Conditions to avoid

Temperature: > 290 °C

See SDS section 7 - Handling and storage.

10.5. Incompatible materials

Substances to avoid:

Date / Revised: 16.10.2025 Version: 11.0

Date / Previous version: 16.12.2024 Previous version: 10.0

Product: ULTRADUR® B 4406 G4 BLACK 07110 POLYBUTYLENE TEREPHTHALATE

(ID no. 30035777/SDS_GEN_EU/EN)

Date of print 17.10.2025

No substances known that should be avoided.

10.6. Hazardous decomposition products

Hazardous decomposition products:

Carbon monoxide, tetrahydrofuran, Terephthalic acid, Carbon dioxide, Water Danger by forming of toxic pyrolytic products.

SECTION 11: Toxicological Information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Assessment of acute toxicity:

Contact with molten product may cause thermal burns.

<u>Irritation</u>

Assessment of irritating effects:

Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses.

Experimental/calculated data:

Serious eye damage/irritation

: May cause mechanical irritation.

Respiratory/Skin sensitization

Assessment of sensitization:

Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses.

Germ cell mutagenicity

Assessment of mutagenicity:

Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses.

Carcinogenicity

Assessment of carcinogenicity:

Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses. The ingredient of concern is tightly bound within the product (practically not bioavailable).

There is no formation of respirable dust during intended uses. However, if dust formation occurs at processing/finishing processing steps like regranulation, mechanical machining (for example drilling, grinding etc.), occupational protection regulations have to be considered. Release and inhalative

Date / Revised: 16.10.2025 Version: 11.0

Date / Previous version: 16.12.2024 Previous version: 10.0

Product: ULTRADUR® B 4406 G4 BLACK 07110 POLYBUTYLENE TEREPHTHALATE

(ID no. 30035777/SDS_GEN_EU/EN)

Date of print 17.10.2025

resorption from respirable dust (fine dust), however, cannot be excluded. If dust is formed, the substances can be released, which caused cancer by inhalation in animal studies.

Information on: Diantimony trioxide

Assessment of carcinogenicity:

Indication of possible carcinogenic effect in animal tests. IARC (International Agency for Research on Cancer) has classified this substance as group 2B (The agent is possibly carcinogenic to humans).

,

Reproductive toxicity

Assessment of reproduction toxicity:

Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses.

Developmental toxicity

Assessment of teratogenicity:

Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses.

Specific target organ toxicity (single exposure)

Assessment of STOT single:

not applicable

Repeated dose toxicity and Specific target organ toxicity (repeated exposure)

Assessment of repeated dose toxicity:

Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses.

Aspiration hazard

May be harmful if swallowed and enters airways.

Interactive effects

No data available.

11.2. Information on other hazards

Endocrine disrupting properties

The product does not contain a substance that is considered to have endocrine disrupting properties according to EU REACH Article 57(f).

Date / Revised: 16.10.2025 Version: 11.0

Date / Previous version: 16.12.2024 Previous version: 10.0

Product: ULTRADUR® B 4406 G4 BLACK 07110 POLYBUTYLENE TEREPHTHALATE

(ID no. 30035777/SDS_GEN_EU/EN)

Date of print 17.10.2025

Other information

Other relevant toxicity information

Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses.

SECTION 12: Ecological Information

12.1. Toxicity

Assessment of aquatic toxicity:

The product has not been tested. The statement has been derived from the structure of the product. There is a high probability that the product is not acutely harmful to aquatic organisms.

12.2. Persistence and degradability

Assessment biodegradation and elimination (H2O):

The product is virtually insoluble in water and can thus be separated from water mechanically in suitable effluent treatment plants.

Experience shows this product to be inert and non-degradable.

Elimination information:

Poorly biodegradable.

Assessment of stability in water:

According to structural properties, hydrolysis is not expected/probable.

12.3. Bioaccumulative potential

Assessment bioaccumulation potential:

Does not significantly accumulate in organisms.

Bioaccumulation potential:

The product will not be readily bioavailable due to its consistency and insolubility in water.

12.4. Mobility in soil

Assessment transport between environmental compartments: Adsorption in soil: Adsorption to solid soil phase is not expected.

12.5. Results of PBT and vPvB assessment

Page: 12/16

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 16.10.2025 Version: 11.0

Date / Previous version: 16.12.2024 Previous version: 10.0

Product: ULTRADUR® B 4406 G4 BLACK 07110 POLYBUTYLENE TEREPHTHALATE

(ID no. 30035777/SDS_GEN_EU/EN)

Date of print 17.10.2025

According to Annex XIII of Regulation (EC) No.1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH): The product does not fulfill the criteria for PBT (Persistent/bioaccumulative/toxic) and vPvB (very persistent/very bioaccumulative).

12.6. Endocrine disrupting properties

The product does not contain a substance that is considered to have endocrine disrupting properties according to EU REACH Article 57(f).

(EU REACH Article 57(f), Registration, Evaluation and Authorisation of Chemicals (REACH))

12.7. Other adverse effects

The product does not contain substances that are listed in Regulation (EU) 2024/590 on substances that deplete the ozone layer.

Additional information

Adsorbable organically-bound halogen (AOX):

The product contains according to the formulation, organically bound halogen. It can increase the AOX-value in the water purification plants overflow or if it reaches waters.

Other ecotoxicological advice:

The product is a polymeric compound.

SECTION 13: Disposal Considerations

13.1. Waste treatment methods

Check for possible recycling.

Observe national and local legal requirements.

Dispose of as hazardous waste in compliance with national waste legislation requirements and local regulations.

Contaminated packaging:

Packs must be completely emptied. Completely emptied packagings can be given for recycling.

SECTION 14: Transport Information

Land transport

ADR

Not classified as a dangerous good under transport regulations

UN number or ID number: Not applicable UN proper shipping name: Not applicable Transport hazard class(es): Not applicable Packing group: Not applicable

Date / Revised: 16.10.2025 Version: 11.0

Date / Previous version: 16.12.2024 Previous version: 10.0

Product: ULTRADUR® B 4406 G4 BLACK 07110 POLYBUTYLENE TEREPHTHALATE

(ID no. 30035777/SDS_GEN_EU/EN)

Date of print 17.10.2025

Environmental hazards: I Special precautions for I

user

Not applicable None known

RID

Not classified as a dangerous good under transport regulations

UN number or ID number:
UN proper shipping name:
Transport hazard class(es):
Packing group:
Environmental hazards:
Special precautions for

Not applicable
Not applicable
Not applicable
Not applicable
Not applicable
Not applicable

user

Inland waterway transport

ADN

Not classified as a dangerous good under transport regulations

UN number or ID number:
UN proper shipping name:
Transport hazard class(es):
Packing group:
Environmental hazards:
Special precautions for

Not applicable
Not applicable
Not applicable
Not applicable
Not applicable
Not applicable

user:

Transport in inland waterway vessel

Not evaluated

Sea transport

IMDG

Not classified as a dangerous good under transport regulations

UN number or ID number:
UN proper shipping name:
Transport hazard class(es):
Packing group:
Environmental hazards:
Special precautions for

Not applicable
Not applicable
Not applicable
Not applicable
Not applicable

user

user

Air transport

IATA/ICAO

Date / Revised: 16.10.2025 Version: 11.0

Date / Previous version: 16.12.2024 Previous version: 10.0

Product: ULTRADUR® B 4406 G4 BLACK 07110 POLYBUTYLENE TEREPHTHALATE

(ID no. 30035777/SDS_GEN_EU/EN)

Date of print 17.10.2025

Not classified as a dangerous good under transport regulations

UN number or ID number:
UN proper shipping name:
Transport hazard class(es):
Packing group:
Environmental hazards:
Special precautions for

Not applicable

user

14.1. UN number or ID number

See corresponding entries for "UN number or ID number" for the respective regulations in the tables above.

14.2. UN proper shipping name

See corresponding entries for "UN proper shipping name" for the respective regulations in the tables above.

14.3. Transport hazard class(es)

See corresponding entries for "Transport hazard class(es)" for the respective regulations in the tables above.

14.4. Packing group

See corresponding entries for "Packing group" for the respective regulations in the tables above.

14.5. Environmental hazards

See corresponding entries for "Environmental hazards" for the respective regulations in the tables above.

14.6. Special precautions for user

See corresponding entries for "Special precautions for user" for the respective regulations in the tables above.

14.7. Maritime transport in bulk according to IMO instruments

Maritime transport in bulk is not intended.

SECTION 15: Regulatory Information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Prohibitions, Restrictions and Authorizations

Annex XVII of Regulation (EC) No 1907/2006: Number on List: 78

The synthetic polymer microparticles supplied are subject to conditions laid down by entry 78 of Annex XVII to Regulation (EC) No 1907/2006 of the European Parliament and of the Council. Synthetic Polymer Microparticle content: 50 - 75 %

Date / Revised: 16.10.2025 Version: 11.0

Date / Previous version: 16.12.2024 Previous version: 10.0

Product: ULTRADUR® B 4406 G4 BLACK 07110 POLYBUTYLENE TEREPHTHALATE

(ID no. 30035777/SDS_GEN_EU/EN)

Date of print 17.10.2025

Generic information on the identity of the SPM polymers contained (polymer classes): Polyacetals, other polyethers and epoxide resins; polycarbonates, alkyd resins, polyallyl esters and other polyesters

Directive 2012/18/EU - Control of Major Accident Hazards involving dangerous substances (EU): Listed in above regulation: no

Classification applies for standard conditions of temperature and pressure.

If other regulatory information applies that is not already provided elsewhere in this safety data sheet, then it is described in this subsection.

15.2. Chemical Safety Assessment

Chemical Safety Assessment not required

Product is not classified as hazardous.

A safety data sheet for this product is legally not required and is provided by us just as a courtesy to our customers.

SECTION 16: Other Information

Information on intended use: Do not mill or crush the product. Must not be used in spray form.

<u>Full text of the classifications, including the hazard classes and the hazard statements, if mentioned in section 2 or 3:</u>

Carc. Carcinogenicity

STOT RE Specific target organ toxicity — repeated exposure

H351 Suspected of causing cancer by inhalation.

H373 May cause damage to organs (Lung) through prolonged or repeated

exposure.

Abbreviations

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road. ADN = The European Agreement concerning the International Carriage of Dangerous Goods by Inland waterways. ATE = Acute Toxicity Estimates. CAO = Cargo Aircraft Only. CAS = Chemical Abstract Service. CLP = Classification, Labelling and Packaging of substances and mixtures. DIN = German national organization for standardization. DNEL = Derived No Effect Level. EC50 = Effective concentration median for 50% of the population. EC = European Community. EN = European Standards. IARC = International Agency for Research on Cancer. IATA = International Air Transport Association. IBC-Code = Intermediate Bulk Container code. IMDG = International Maritime Dangerous Goods Code. ISO = International Organization for Standardization. STEL = Short-Term Exposure Limit. LC50 = Lethal concentration median for 50% of the population. LD50 = Lethal dose median for 50% of the population. TLV = Threshold Limit Value. MARPOL = The International Convention for the Prevention of Pollution from Ships. NEN = Dutch Norm. NOEC = No Observed Effect Concentration. OEL = Occupational Exposure Limit. OECD = Organization for Economic Cooperation and Development. PBT = Persistent, Bioaccumulative and Toxic. PNEC = Predicted No Effect Level. PPM = Parts per million. RID = The

Date / Revised: 16.10.2025 Version: 11.0

Date / Previous version: 16.12.2024 Previous version: 10.0

Product: ULTRADUR® B 4406 G4 BLACK 07110 POLYBUTYLENE TEREPHTHALATE

(ID no. 30035777/SDS_GEN_EU/EN)

Date of print 17.10.2025

European Agreement concerning the International Carriage of Dangerous Goods by Rail. TWA = Time Weight Average. UN-number = UN number at transport. vPvB = very Persistent and very Bioaccumulative.

The data contained in this safety data sheet are based on our current knowledge and experience and describe the product only with regard to safety requirements. This safety data sheet is neither a Certificate of Analysis (CoA) nor technical data sheet and shall not be mistaken for a specification agreement. Identified uses in this safety data sheet do neither represent an agreement on the corresponding contractual quality of the substance/mixture nor a contractually designated use. It is the responsibility of the recipient of the product to ensure any proprietary rights and existing laws and legislation are observed.

Vertical lines in the left hand margin indicate an amendment from the previous version.